

# Zurich ServiceNow AI Platform Capabilities

Last updated: January 16, 2026

Some examples and graphics depicted herein are provided for illustration only. No real association or connection to ServiceNow products or services is intended or should be inferred.

This PDF was created from content on [docs.servicenow.com](https://docs.servicenow.com). The web site is updated frequently. For the most current ServiceNow product documentation, go to [docs.servicenow.com](https://docs.servicenow.com).

**Company Headquarters**

2225 Lawson Lane  
Santa Clara, CA 95054  
United States  
(408)501-8550

## Service Graph Connector for Tanium

Use the Service Graph Connector for Tanium to bring in hardware, software, and software usage data from a Tanium environment into your ServiceNow instance.

### Request apps on the Store

Visit the [ServiceNow Store](#) website to view all the available apps and for information about submitting requests to the store. For cumulative release notes information for all released apps, see the [ServiceNow Store version history release notes](#).

### Supported versions

#### Versions

| Tanium                                                                                                                                                             | ServiceNow                                                                                        |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>Tanium 1.9 or later versions for hardware and software</li> <li>Tanium 1.17 or later versions for software usage</li> </ul> | <ul style="list-style-type: none"> <li>Washington DC</li> <li>Xanadu</li> <li>Yokohama</li> </ul> |

### Important information for upgrading Service Graph Connector for Tanium

Tanium Platform 7.6.2 or later versions support token-based authorization only. After you have installed the latest version of the Service Graph Connector for Tanium, verify the following configurations to use Tanium Platform 7.6.2 or later versions in your on-premise setups:

- For a single instance, reconfigure the authentication type of an existing connection to use token-based authorization.
- For multiple instances, deactivate the existing scheduled jobs for previously configured instances that used basic authorization, and then create and configure new instances to use token-based authorization.

## Configuring a connection for the connector

You can configure a connection for the connector by using the SGC Central view in the CMDB Workspace. The view enables you to discover and install connectors, and then effectively manage the full life cycle of creating, editing, monitoring, and debugging connections. To configure the connector using SGC Central, see [Configure Service Graph Connector for Tanium using SGC Central](#).

**Important:** Unless there are configuration issues, use the SGC Central view in the CMDB Workspace to configure the connection for the connector, as the guided setup method is being deprecated.

## CMDB integrations dashboard

The Integration Commons for CMDB store app provides a dashboard with a central view of the status, processing results, and processing errors of all installed integrations. You can see metrics for all integration runs. You can filter the view to a specific CMDB integration, a specific time duration, or a specific integration run. For more details about monitoring Tanium integrations in the CMDB Integrations Dashboard, see [Using the CMDB Integrations Dashboard](#).

## Data mapping

Data from the Tanium data sources is mapped and transformed into the ServiceNow CMDB Configuration Item (CI) class definitions using the Robust Transform Engine (RTE). Data is inserted into the ServiceNow CMDB using the Identification and Reconciliation Engine (IRE).

The following table describes the data sources, the staging tables, and the target tables including CMDB CI and non-CMDB CI classes for the Tanium application.

### Data mapping for Tanium

| Data source            | Staging table                                                      | Target tables                                  | Resource types |
|------------------------|--------------------------------------------------------------------|------------------------------------------------|----------------|
| SG-Tanium Applications | SG-Tanium Applications<br>[sn_tanium_integ_sg_tanium_applications] | <a href="#">Application</a><br>Running Process | Applications   |

| Data source                     | Staging table                                                            | Target tables                                                                                                                                                                                                                                                     | Resource types      |
|---------------------------------|--------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|
|                                 |                                                                          | TCP                                                                                                                                                                                                                                                               |                     |
| SG-Tanium Hardware and Software | SG Tanium Import<br>[sn_tanium_integ_sg_tanium_import]                   | <p>Computer</p> <p>File System</p> <p>Disk</p> <p>IP Address</p> <p>When the Software Asset Management (SAM) application isn't installed:</p> <p>Software</p> <p>Software Instance</p> <p>When the SAM application is installed:</p> <p>Software Installation</p> | Server and software |
| SG-Tanium Usage                 | SG Tanium Usage Import<br>[sn_tanium_integ_sg_tanium_usage_import]       | Software Usage<br>[samp_sw_usage]                                                                                                                                                                                                                                 | None                |
| SG-Tanium Remove Software       | Integration Commons Remove Record<br>[sn_cmdb_int_utility_remove_record] | None                                                                                                                                                                                                                                                              | None                |

| Data source | Staging table        | Target tables | Resource types |
|-------------|----------------------|---------------|----------------|
|             | l_remove_recor<br>d] |               |                |

**Note:**

- The SG-Tanium Usage data source is available only when the Software Asset Management Professional plugin (com.snc.samp) plugin is activated on your ServiceNow instance. See [Request Software Asset Management](#).
- The SG-Tanium Remove Software data source creates import sets and uses the transform map-based method for removing any target records for software data that weren't updated in the last delta query check. See [Managing CMDB data deletion](#).
- Starting with the Service Graph Connector for Tanium 1.8.0 release, a buffer time is added for software removal when the buffer\_days\_from\_last\_scan\_for\_hardware system property is enabled. When this system property is enabled, the software removal candidate is removed only if the last scan time of the hardware on which the software removal candidate is installed is earlier than the last success import time + buffer time. To enable this property, set the value of the buffer\_days\_from\_last\_scan\_for\_hardware system property to a non-zero numeral value according to the number of days of buffer that you require. To disable this property, set the value to 0.

You can use the IntegrationHub ETL app to view the data maps. See [IntegrationHub ETL](#) for more information.

### Additional resource

[How do I configure the Tanium Service Graph Connector?](#) article on the ServiceNow Community site

### Related concepts

- [Service Graph Connectors](#)

## Configure Service Graph Connector for Tanium using SGC Central

Set up scheduled import jobs to pull in Tanium data into your Configuration Management Database (CMDB).

### Before you begin

Install Service Graph Connector for Tanium version 1.7.0 or later from the ServiceNow Store. For ServiceNow Store installation steps, see [Install a ServiceNow Store application](#).

Role required: SGC-Admin (sn\_cmdb\_int\_util.sgc\_admin)

**Note:** The admin user role is required to run background scripts and to provide table-level access to the SGC-Admin user.

### About this task

The playbook experience for onboarding connectors is activated with SGC Central in the CMDB Workspace. To configure the SGC Central application, see [Configuring SGC Central](#) and for more information on how to interact with a playbook, see [Interact with Playbook](#).

### Procedure

1. Navigate to **Workspaces > CMDB Workspace**.
2. In the CMDB Workspace, select **SGC Central**.
3. On the Overview page, select **Create connection**.  
**Tip:** Alternatively, you can select **Create connection** on the All connections page.
4. On the Create connection window, select the Tanium connector type, and then select **Create connection**.
5. Complete the initial prerequisites when setting up a connection for the first time using a connector.

**Note:** This step is required only during the first-time setup. See [Perform initial setup tasks when creating a connection in SGC Central](#).

6. Complete the prerequisites for setting up the Tanium environment.
  - a. Create a custom view on your Tanium instance.
    - a. In the **Prerequisites** stage of the playbook, select the **Create custom view** activity.
    - b. Create a custom view on your Tanium instance to be used in the **Select view** activity later by referring to the [Tanium Asset User Guide for Cloud](#).

**Note:** Copy the unmodifiable **ServiceNow (reserved)** view from the Tanium instance to create the custom view.

  - c. After creating a view, select the **I have created a custom view for this connection according to the instructions** check box.
  - d. After completing the **Select view** activity, select **Continue**.
7. Determine the type of authentication for the Tanium connection.
  - a. In the **Setup** stage of the playbook, select the **Select alias template** activity.  
If needed, expand the **Setup** stage to select an activity.
  - b. Select an alias template for the connection.
    - **Basic authentication:** Select when using Basic authentication that grants access to the Tanium data.
    - **Token-based authentication:** Select when using an authentication token for the Tanium API to grants access to the Tanium data.
  - c. Select **Continue**.
8. Enter connection details and test the API connection for importing Tanium data.

- a. In the **Setup** stage of the playbook, select the **Configure and test connection** activity.
- b. On the form, fill in the fields.

### Create and test connection form

| Field           | Description                                                                                                                                                                                                                        |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connection name | Name to identify the Tanium connection record.                                                                                                                                                                                     |
| Host name       | Base URL or IP address of the Tanium server.                                                                                                                                                                                       |
| Username        | <p>Tanium account user name that is used to authenticate the connection request.</p> <p>This field appears only when the <b>Basic authentication</b> alias template was selected in the <b>Select alias template</b> activity.</p> |
| Password        | <p>Password associated with the user name required for authenticating requests.</p> <p>This field appears only when the <b>Basic authentication</b> alias template was selected in the <b>Select alias template</b> activity.</p>  |
| Token           | <p>Authentication token for the Tanium API that grants access to the Tanium data.</p> <p>This field appears only when the <b>Token-based authentication</b> alias template</p>                                                     |

| Field          | Description                                                                                                                        |
|----------------|------------------------------------------------------------------------------------------------------------------------------------|
|                | was selected in the <b>Select alias template</b> activity.                                                                         |
| Use MID Server | Option to use a MID Server.<br><b>Note:</b> Use of a MID Server is optional.                                                       |
| MID selection  | Name of the MID Server used by the connector.<br><br>This field appears only when the <b>Use MID Server</b> check box is selected. |

- c. Select **Update and test connection**.
  - d. Once the connection test is complete, select **Continue**.
9. Select the view created on your Tanium instance.
  - a. In the **Setup** stage of the playbook, select the **Select view** activity.
  - b. In the **View** field, select the custom view you created on the Tanium instance in the [Prerequisites activity](#).
  - c. Select **Continue**.
10. Configure the import schedule to import data at regular intervals.
  - a. In the **Setup** stage of the playbook, select the **Configure import schedule** activity.
  - b. Expand the Parent scheduled data import within the Import schedules list to select the **Connection name - SG-Tanium Usage** import schedule.
  - c. In the Configure import schedule dialog box, select the **Active** check box, and then fill in the run schedule and time details.

For more information, see [Schedule a data import](#).

- d. Select **Save**.  
Alternatively, select **Execute Now** to execute the import schedule immediately.
- e. Repeat steps [10.b](#) to [10.d](#) for the **Connection name - SG-Tanium Hardware and Software** parent import schedule.
- f. Select **Continue**.

11. In the **Setup** stage of the playbook, select the **Confirm connection creation** activity to verify whether the connection was created.

## What to do next

Select **View all connections** to review the connection details. The configured connection appears in the Installed connections list.

### Related concepts

- [Service Graph Connector for Tanium](#)
- [Accessing the connection details of Service Graph Connector for Tanium](#)

### Related reference

- [CMDB classes targeted in Service Graph Connector for Tanium](#)

# Configure Service Graph Connector for Tanium using the guided setup

Set up scheduled import jobs to pull in data from Tanium into your Configuration Management Database (CMDB).

## Before you begin

**Important:** Unless there are configuration issues, use the SGC Central view in the CMDB Workspace to configure the connection for the connector, as the guided setup method is being deprecated.

To use this Service Graph Connector, you need a subscription to a Subscription Unit that is based in the IT Operations Management (ITOM) Visibility application or in the ITOM Discovery application. As defined in the section titled "Managed IT Resource Types" in [ServiceNow Subscription Unit Overview](#) for your subscription, for managed IT resources that are created or modified in the CMDB by this Service Graph Connector, but that aren't yet managed by [ITOM Visibility](#) or [ITOM Discovery](#), these resources will increase Subscription Unit consumption from that application. Review your current Subscription Unit consumption within ITOM Visibility or ITOM Discovery to ensure available capacity.

Dependencies and requirements:

- The [Integration Commons for CMDB](#) store app, which is automatically installed.
- The CMDB CI class models store app, which is automatically installed. See [CMDB CI Class Models](#).
- The Datastream Action plugin (com.glide.hub.action\_type.datastream), which is automatically installed.

**Note:** If you have an earlier version of the Service Graph Connector for Tanium, then do not migrate data from the old connector. You must uninstall the previous version and run the new integration.

Role required: SGC-Admin (sn\_cmdb\_int\_util.sgc\_admin)

**Note:** The admin user role is required to run background scripts and to provide table-level access to the SGC-Admin user.

## About this task

For more information on the Service Graph Connector for Tanium setup, see [How do I configure the Tanium Service Graph Connector?](#) article on the ServiceNow Community site.

## Procedure

1. Ensure that the application scope is set to the Service Graph Connector for Tanium application by using the application picker. For more information, see [Application picker](#).

2. Navigate to **All > Service Graph Connectors > Tanium > Setup**.
3. On the Getting started page, select **Get Started**.
4. Configure the authentication credentials and HTTP connection.
  - a. On the Service Graph Connector for Tanium page, in the Configure the Connection and Credentials section, select **Set authentication type**.
  - b. For the Set authentication type task, select **Configure**.
  - c. Specify the system property details for the authentication type.
    - a. In the **Value** field, enable either token-based authentication or basic authentication.
      - To enable the basic authorization, enter `basic`.
      - To enable the token-based authorization, enter `token`.

**Note:** Tanium Platform 7.6.2 supports only token-based authorization for an on-premise setup. To use Tanium Platform 7.6.2 or later versions, enable the token-based authorization type and enter the details for the token-based authorization in the next step.
    - b. Select **Update**.
    - c. Set the Set authentication type task to complete by selecting **Mark as Complete**.
  - d. Configure the connection based on the authentication type.
    - a. For the basic authorization type:
      - a. For the Configure the Basic auth Credentials task, select **Configure**.
 

**Note:** The Configure the Basic auth Credentials task appears only when you have specified `basic` as the value in the step [4.c.i](#).
      - b. Select **Edit** for Basic authentication within the `sn_tanium_integ` scope.

- c. In the Connection Information section of the Edit Connection window, fill in the fields.

### Connection Information

| Field           | Description                                                                                                                                                             |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connection name | Name to identify the Tanium connection record.<br><br>Token-based authentication is the default credential alias name and is read-only.                                 |
| Host name       | Base URL or IP address of the Tanium server.<br><br><b>Note:</b> This field is automatically set to the URL to connect to the application. Leave the field value as is. |

- d. (Optional) If a MID Server is required for the Tanium server connection, select the **Use MID Server** check box. Then, select the MID Server-related fields accordingly.
- e. In the Credential Information section, enter the Tanium account user name in the **Username** field and the password in the **Password** field.
- f. Select **Edit connection**.
- g. Return to the guided setup page.
- h. Set the Configure the Basic auth Credentials task to complete by selecting **Mark as Complete**.
- b. For the token-based authorization type:
- a. For the Configure the Token auth Credentials task, select **Configure**.

**Note:** The Configure the Token auth Credentials task appears only when you have specified token as the value in the step [4.c.i.](#)

- b. Select **Edit** for Token-based authentication within the sn\_tanium\_integ scope.
- c. In the Connection Information section of the Edit Connection window, fill in the fields.

#### Connection Information

| Field           | Description                                                                                                                                               |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connection name | Name to identify the Tanium connection record.<br><br>Token-based authentication is the default credential alias name and is read-only.                   |
| Host name       | Tanium base URL or IP address.<br><br><b>Note:</b> This field is automatically set to the URL to connect to the application. Leave the field value as is. |

- d. (Optional) If a MID Server is required for the Tanium server connection, select the **Use MID Server** check box. Then, select the MID Server-related fields accordingly.
- e. In the Credential Information section of the Edit Connection window, enter the authentication token for the Tanium API in the **Token** field to grants access to Tanium data.
- f. Select **Edit connection**.

- g. Return to the guided setup page.
- h. Set the Configure the Token auth Credentials task to complete by selecting **Mark as Complete**.
- e. Test the connection.
  - a. For the Test connection task, select **Configure**.
  - b. Select the **Test Connection** related link to start the testing process.
  - c. When the **Status** field is set to **Success**, return to the guided setup page.

**Note:** If any of the tests have errors, follow the suggestions for remediation.

- d. Set the Test the connection task to complete by selecting **Mark as Complete**.
- f. Create a custom view.

**Note:** The integration depends on a custom view from Tanium.

- a. Configure the view on your Tanium instance.
  - a. On your Tanium instance, navigate to **Modules > Asset**.
  - b. Select **Views**.
  - c. If you have not done so already, create the ServiceNow (reserved) view by selecting **Create View > Create ServiceNow view**.

**Note:** By default, the ServiceNow (reserved) view is non-editable.

- d. Create a copy of the view to edit it.
- e. Edit the copy.
  - a. Add all fields from the **SIU Product Usage** bucket.

- b. Add **Asset** to the **Last Seen** field.
  - c. Add **Network Adapter** to the **Model** field.
  - f. Save the view.
- b. Select the view on your ServiceNow instance.
  - a. In the guided setup, for the Configure the View task, select **Configure**.
  - b. In the ServiceNow instance, select the view you created in step 4.f.i.
  - c. Select **Set View**.
  - d. Set the Configure the View task to complete by selecting **Mark as Complete**.
- g. In the ADM setup instruction section, ignore the instructions as application dependency mapping is not supported currently.
- 5. Configure the Tanium scheduled jobs.
  - a. For the Configure the Scheduled Import task, select **Configure**.
  - b. Select the scheduled job that you want to activate.
  - c. On the Scheduled Data Import form, verify the field values for a scheduled job and select the **Active** check box to activate the scheduled job.

**Note:** When using a token-based authentication, the user you specify in the **Run as** field for a scheduled job must have the connection\_admin role.

For more information, see [Schedule a data import](#).

- d. Select **Update**.
- e. Repeat the steps 5.b to 5.d for each scheduled job for data import.
- f. Set the Configure the Scheduled Import task to complete by selecting **Mark as Complete**.

## 6. (Optional) Add multiple instances.

**Note:** If you don't need to add multiple instances, you can skip this step.

- a. On the Service Graph Connector for Tanium page, in the Add Multiple Icons section, select the **Update Data Source Access** task.
- b. On the next page, in the Update Data Source Access section, select **Configure**.
- c. Select the Data Source [sys\_data\_source] table.
- d. Select the **Global** application scope by using the application picker.
- e. In the Application Access related list, select the **Can create, Can update, and Can delete** check boxes, if not already selected.
- f. Select **Update** to close the tab and return to the guided setup.
- g. Modify the application scope again to **Service Graph Connector for Tanium** by using the application picker.
- h. Set the Update Data Source Access task to complete by selecting **Mark as Complete**.
- i. Repeat the steps 6.d to 6.g for the Update Scheduled data import access task with the Scheduled data import [scheduled\_data\_set] table and set the task to complete by selecting **Mark as Complete**.
- a. Clear the cache for the new connection.
  - a. For the Clear Cache for Datasource and Import set task, select **Configure**.
  - b. In the **Run script** text box of the background script page, enter the following script:

```
GlideTableManager.invalidateTable("sys_data_source");
GlideCacheManager.flushTable("sys_data_source");
```

```
GlideTableManager.invalidateTable("scheduled_import_set");
GlideCacheManager.flushTable("scheduled_import_set");

GlideTableManager.invalidateTable("sys_db_object");
GlideCacheManager.flushTable("sys_db_object");
```

- c. Select **Run Script** to run the background script in the **global** scope.

The script may take several minutes to execute.

- d. After the script is executed, select **Close**.
  - e. From the application picker, select the **Service Graph Connector for Tanium** application.
  - f. Set the Clear Cache for Datasource and Import set task to complete by selecting **Mark as complete**.
- b. Add a basic authorization connection to another Tanium instance.
 

**Note:** Tanium Platform 7.6.2 supports only token-based authorization for an on-premise setup. To use Tanium Platform 7.6.2 or later versions, use the token-based authorization.

    - a. For the Add Another Basic Auth Connection task, select **Configure**.
    - b. To create a new connection, select **Add Connection**.
    - c. Enter the connection details on the Create Connection form.
    - d. Select **Create Connection**.
    - e. Navigate back to the guided setup and set the Add Another Basic Auth Connection task to complete by selecting **Mark as Complete**.

- c. Add a token-based authorization connection to another Tanium instance.
  - a. For the Add Another Token Auth Connection task, select **Configure**.
  - b. To create a new connection, select **Add Connection**.
  - c. Enter the connection details on the Create Connection form.
  - d. Select **Create Connection**.
  - e. Navigate back to the guided setup and set the Add Another Token Auth Connection task to complete by selecting **Mark as Complete**.
- d. Set configuration properties for newly added connections.
  - a. For the Set configuration properties task, select **Configure**.
  - b. From the **Name** column, select the new connection.
  - c. In the Service Graph Connection Properties related list, review and modify the following properties.

| Field                   | Value                                                                                                |
|-------------------------|------------------------------------------------------------------------------------------------------|
| max_retry_count         | Determines the number of retry attempts triggered for a Tanium Asset REST action in case of failure. |
| pagination_record_count | Specifies the page size for each API call made during a Tanium Application Data REST action.         |
| rest_action_limit       | Specifies the page size for each API call made during a Tanium Asset REST action.                    |
| view_id                 | Specifies the identifier used to fetch hardware and software data from a specific Tanium view. To    |

| Field | Value                                                                                           |
|-------|-------------------------------------------------------------------------------------------------|
|       | modify the view identifier, access the SG Tanium Connection [sn_tanium_integ_connection] table. |

- d. Return to the guided setup page.
- e. Set the Set configuration properties task to complete by selecting **Mark as Complete**.
- e. Test the newly added connections.
  - a. For the Test connections task, select **Configure**.
  - b. From the **Name** column, select the new connection.
  - c. Select the **Test Connection** related link to start the testing process.
  - d. When the **Status** field is set to **Success**, return to the guided setup page.
 

**Note:** If any of the tests have errors, follow the suggestions for remediation.
  - e. Set the Test connections task to complete by selecting **Mark as Complete**.
- f. Set the Tanium view for the connection.
  - a. For the Set view task, select **Configure**.
  - b. In the **Connection and Credentials Alias** field, search for and select the alias created earlier in the Add Another Basic Auth Connection or Add Another Token Auth Connection task.
  - c. In the **View** field, search for and select the corresponding Tanium view associated with the connection.
  - d. Select **Set View**.

- e. Set the Set view task to complete by selecting **Mark as Complete**.
  - g. Skip the ADM setup for multi instance task as ADM is not supported currently.
  - h. Configure the Tanium scheduled job.
    - a. For the Configure the Scheduled Imports task, select **Configure**.
    - b. Select the scheduled data import that you want to activate.
    - c. On the Scheduled Data Import form, verify the field values for the scheduled job and select the **Active** check box.

**Note:** When using a token-based authentication, the user you specify in the **Run as** field for a scheduled job must have the connection\_admin role.
- For more information, see [Schedule a data import](#).
- d. Select **Update**.
  - e. Repeat steps [6.h.ii](#) to [6.h.iv](#) for each scheduled job for data import.
  - f. Set the Configure the Scheduled Imports task to complete by selecting **Mark as Complete**.
7. (Optional) Use the advanced settings to manage excluding the serial number population on the IBM AIX and Oracle Solaris operating system (OS) platforms.
  - a. In the Advanced section of the guided setup, for the Advanced Settings task, select **Configure**.
  - b. To exclude the serial number population, enter `false` in the **Exclude the serial number population** field.
  - c. Select **Save**.
  - d. Close the window and set the Advanced Settings task to complete by selecting **Mark as Complete**.

## CMDB classes targeted in Service Graph Connector for Tanium

When you complete setting up the connection, you can configure the integration to periodically pull data from Tanium. The data is saved in tables that extend from the Configuration item [cmdb\_ci] table.

### Application [cmdb\_ci\_appl]

The following attributes in the Application [cmdb\_ci\_appl] table are populated by collected data:

| Attribute label         | Attribute name          |
|-------------------------|-------------------------|
| Class                   | sys_class_name          |
| Name                    | name                    |
| Running process command | running_process_command |

### Relationship created for Application

| Parent class               | Relationship type | Child class                |
|----------------------------|-------------------|----------------------------|
| Application [cmdb_ci_appl] | Runs on::Runs     | Computer[cmdb_ci_computer] |

### Computer [cmdb\_ci\_computer]

The following attributes in the Computer [cmdb\_ci\_computer] table are populated by collected data:

| Attribute label | Attribute name |
|-----------------|----------------|
| Name            | name           |
| Serial number   | serial_number  |
| Class           | sys_class_name |
| CPU core count  | cpu_core_count |

| Attribute label       | Attribute name   |
|-----------------------|------------------|
| CPU count             | cpu_count        |
| CPU speed (MHz)       | cpu_speed        |
| CPU type              | cpu_type         |
| DNS Domain            | dns_domain       |
| IP Address            | ip_address       |
| CPU manufacturer      | cpu_manufacturer |
| CPU name              | cpu_name         |
| Is Virtual            | virtual          |
| Most recent discovery | last_discovered  |
| Operating System      | os               |
| OS Domain             | os_domain        |
| OS Service Pack       | os_service_pack  |
| OS Version            | os_version       |
| RAM (MB)              | ram              |
| Model ID              | model_id         |
| Manufacturer          | manufacturer     |

### Relationships created for Computer

| Parent class                   | Relationship type | Child class                                  |
|--------------------------------|-------------------|----------------------------------------------|
| Computer<br>[cmdb_ci_computer] | Owns::Owned by    | Network Adapter<br>[cmdb_ci_network_adapter] |

| Parent class                   | Relationship type           | Child class                                       |
|--------------------------------|-----------------------------|---------------------------------------------------|
| Computer<br>[cmdb_ci_computer] | Owns::Owned by              | IP Address<br>[cmdb_ci_ip_address]                |
| Computer<br>[cmdb_ci_computer] | Contains::Contained by      | Disk [cmdb_ci_disk]                               |
| Computer<br>[cmdb_ci_computer] | Contains::Contained by      | File System<br>[cmdb_ci_file_system]              |
| Computer<br>[cmdb_ci_computer] | Reference                   | Software Installation<br>[cmdb_sam_sw_install]    |
| Computer<br>[cmdb_ci_computer] | Virtualized by::Virtualizes | Virtual Machine Instance<br>[cmdb_ci_vm_instance] |

### Disk [cmdb\_ci\_disk]

The following attributes in the Disk [cmdb\_ci\_disk] table are populated by collected data:

| Attribute label  | Attribute name   |
|------------------|------------------|
| Manufacturer     | manufacturer     |
| Name             | name             |
| Computer         | computer         |
| Serial number    | serial_number    |
| Device interface | device_interface |
| Storage type     | storage_type     |
| Model ID         | model_id         |
| Device ID        | device_id        |

| Attribute label | Attribute name |
|-----------------|----------------|
| Size bytes      | size_bytes     |

#### Relationship created for Disk

| Parent class        | Relationship type | Child class                 |
|---------------------|-------------------|-----------------------------|
| Disk [cmdb_ci_disk] | Reference         | Computer [cmdb_ci_computer] |

#### File System [cmdb\_ci\_file\_system]

The following attributes in the File System [cmdb\_ci\_file\_system] table are populated by collected data:

| Attribute label  | Attribute name   |
|------------------|------------------|
| Name             | name             |
| File system      | file_system      |
| Free space bytes | free_space_bytes |
| Label            | label            |
| Media type       | media_type       |
| Mount point      | mount_point      |
| Size bytes       | size_bytes       |
| Computer         | computer         |

#### Relationship created for File System

| Parent class                      | Relationship type | Child class                 |
|-----------------------------------|-------------------|-----------------------------|
| File System [cmdb_ci_file_system] | Reference         | Computer [cmdb_ci_computer] |

### IP Address [cmdb\_ci\_ip\_address]

The following attributes in the IP Address [cmdb\_ci\_ip\_address] table are populated by collected data:

| Attribute label | Attribute name |
|-----------------|----------------|
| Nic             | nic            |
| IP Address      | ip_address     |
| IP version      | ip_version     |
| Name            | name           |

### Relationship created for IP Address

| Parent class                       | Relationship type | Child class                                  |
|------------------------------------|-------------------|----------------------------------------------|
| IP Address<br>[cmdb_ci_ip_address] | Reference         | Network Adapter<br>[cmdb_ci_network_adapter] |

### Network Adapter [cmdb\_ci\_network\_adapter]

The following attributes in the Network Adapter [cmdb\_ci\_network\_adapter] table are populated by collected data:

| Attribute label  | Attribute name   |
|------------------|------------------|
| Discovery source | discovery_source |
| Netmask          | netmask          |
| Mac manufacturer | mac_manufacturer |
| MAC Address      | mac_address      |
| Name             | name             |
| Model ID         | model_id         |

| Attribute label | Attribute name |
|-----------------|----------------|
| DHCP Enabled    | dhcp_enabled   |

#### Relationship created for Network Adapter

| Parent class                                 | Relationship type | Child class                    |
|----------------------------------------------|-------------------|--------------------------------|
| Network Adapter<br>[cmdb_ci_network_adapter] | Reference         | Computer<br>[cmdb_ci_computer] |

#### Serial Number [cmdb\_serial\_number]

The following attributes in the Serial Number [cmdb\_serial\_number] table are populated by collected data:

| Attribute label    | Attribute name     |
|--------------------|--------------------|
| Serial Number      | serial_number      |
| Serial Number Type | serial_number_type |
| Valid              | valid              |

#### Relationship created for Serial Number

| Parent class                          | Relationship type | Child class                    |
|---------------------------------------|-------------------|--------------------------------|
| Serial Number<br>[cmdb_serial_number] | Reference         | Computer<br>[cmdb_ci_computer] |

#### Software [cmdb\_ci\_spkg]

The following attributes in the Software [cmdb\_ci\_spkg] table are populated by collected data when the Software Asset Management (SAM) application isn't installed:

| Attribute label | Attribute name |
|-----------------|----------------|
| Version         | version        |

| Attribute label | Attribute name |
|-----------------|----------------|
| Manufacturer    | manufacturer   |
| Key             | key            |
| Name            | name           |

#### Relationship created for Software

| Parent class               | Relationship type | Child class                                   |
|----------------------------|-------------------|-----------------------------------------------|
| Software<br>[cmdb_ci_spkg] | Reference         | Software Instance<br>[cmdb_software_instance] |

#### Software Installation [cmdb\_sam\_sw\_install]

The following attributes in the Software Installation [cmdb\_sam\_sw\_install] table are populated by collected data when the SAM application is installed:

| Attribute label  | Attribute name   |
|------------------|------------------|
| Display name     | display_name     |
| Publisher        | publisher        |
| Version          | version          |
| Discovery source | discovery_source |
| Last scanned     | last_scanned     |

#### Software Instance [cmdb\_software\_instance]

The following attributes in the Software Instance [cmdb\_software\_instance] table are populated by collected data when the SAM application isn't installed:

| Attribute label | Attribute name |
|-----------------|----------------|
| Name            | name           |
| Installed on    | installed_on   |

#### Relationship created for Software Instance

| Parent class                                  | Relationship type | Child class                    |
|-----------------------------------------------|-------------------|--------------------------------|
| Software Instance<br>[cmdb_software_instance] | Reference         | Computer<br>[cmdb_ci_computer] |

#### Virtual Machine Instance [cmdb\_ci\_vm\_instance]

The following attribute in the Virtual Machine Instance [cmdb\_ci\_vm\_instance] table is populated by collected data:

| Attribute label | Attribute name |
|-----------------|----------------|
| Sys ID          | sys_id         |

**Note:** Service Graph Connector for Tanium doesn't create a Virtual Machine Instance CI. During look-up in the Virtual Machine Instance [cmdb\_ci\_vm\_instance] table, if a VM instance is found that has an object ID that matches the cloud instance ID of a server instance, a relationship is created between that VM instance and the server instance.

## Accessing the connection details of Service Graph Connector for Tanium

You can access the connection details of the Service Graph Connector for Tanium in a single view using the common connection framework (CCF) included within the Integration Commons for CMDB (sn\_cmdb\_int\_util) store app.

With the CCF, you can access all the connections used by the Service Graph Connector for Tanium. The connection details include the

connection alias, connection properties, data sources, and scheduled data imports associated with a connection. You can also test the connection. For more information, see [Accessing the connection details of Service Graph Connectors](#).

### Access the details of a Tanium connection

Access the details of a Tanium connection configured for the Service Graph Connector for Tanium.

#### Before you begin

Role required: admin

#### Procedure

1. Navigate to **All > Service Graph Connectors > Tanium > Connections**.
2. From the **Name** column of the Service Graph Connections list, select a connection.
3. On the Service Graph Connections page, view the connection details such as the connection name, alias, and data sources.
4. Select a related list to view further details of the connection.
5. (Optional) Select the **Test Connection** related link to test the connection.