

Zurich ServiceNow AI Platform Capabilities

Last updated: January 16, 2026

Some examples and graphics depicted herein are provided for illustration only. No real association or connection to ServiceNow products or services is intended or should be inferred.

This PDF was created from content on docs.servicenow.com. The web site is updated frequently. For the most current ServiceNow product documentation, go to docs.servicenow.com.

Company Headquarters

2225 Lawson Lane
Santa Clara, CA 95054
United States
(408)501-8550

Service Graph Connector for Trellix

Use the Service Graph Connector for Trellix to bring in device, server, and network data from a Trellix environment into your ServiceNow instance to streamline your incident response and asset management use cases.

Request apps on the Store

Visit the [ServiceNow Store](#) website to view all the available apps and for information about submitting requests to the store. For cumulative release notes information for all released apps, see the [ServiceNow Store version history release notes](#).

Supported versions

Supported ServiceNow versions:

- Washington DC
- Xanadu
- Yokohama

Use cases

The following examples describe how you can use the Service Graph Connector for Trellix for security operations management:

- Identify cybersecurity risks in the environment.
- Assess dependencies between configuration items (CI).
- Enable effective security incident response and endpoint management systems.
- Identify data quality issues, reconcile inconsistencies, and manage incidents and changes on discovered CIs.

Configuring a connection for the connector

You can configure a connection for the connector by using the SGC Central view in the CMDB Workspace. The view enables you to discover and install connectors, and then effectively manage the full life cycle of creating, editing, monitoring, and debugging connections. To

configure the connector using SGC Central, see [Configure Service Graph Connector for Trellix using SGC Central](#).

Important: Unless there are configuration issues, use the SGC Central view in the CMDB Workspace to configure the connection for the connector, as the guided setup method is being deprecated.

CMDB integrations dashboard

The Integration Commons for CMDB store app provides a dashboard with a central view of the status, processing results, and processing errors of all installed integrations. You can see metrics for all integration runs. You can filter the view to a specific CMDB integration, a specific time duration, or a specific integration run. For more details about monitoring Trellix integrations in the CMDB Integrations Dashboard, see [Using the CMDB Integrations Dashboard](#).

Data mapping

Data from the Trellix data sources is mapped and transformed into the ServiceNow CMDB Configuration Item (CI) class definitions using the Robust Transform Engine (RTE). Data is inserted into the ServiceNow CMDB using the Identification and Reconciliation Engine (IRE).

The following data source is included for the Trellix application:

SG-Trellix-Devices

Imports data from devices and loads the imported data in the SGC Trellix Device Import [sn_trellix_integ_sgc_trellix_device_import] staging table.

The imported data is then inserted into the following target tables:

- [File System](#) [cmdb_ci_file_system]
- [IP Address](#) [cmdb_ci_ip_address]
- [Network Adapter](#) [cmdb_ci_network_adapter]
- [Server](#) [cmdb_ci_server]
- [Software Installation](#) [cmdb_sam_sw_install] (if the Software Asset Management (SAM) application is installed)
- [Software](#) [cmdb_ci_spkg] (if the SAM application isn't installed)

- [Software Instance](#) [cmdb_software_instance] (if the SAM application isn't installed)
- [Storage Disk](#) [cmdb_ci_storage_disk]

You can use the IntegrationHub ETL app to view the data maps. See [IntegrationHub ETL](#) for more information.

System property

The following system property is available for Service Graph Connector for Trellix: `sn_trellix_integ.getdevices_count`. This property sets the pagination size for the records that are fetched from the Trellix API.

- Type: integer
- Default value: 100

Note: To open the System Properties [sys_properties] table, enter `sys_properties.list` in the navigation filter.

Related tasks

- [Configure Service Graph Connector for Trellix using SGC Central](#)
- [Configure Service Graph Connector for Trellix using guided setup](#)

Related concepts

- [Service Graph Connectors](#)

Related reference

- [CMDB classes targeted in Service Graph Connector for Trellix](#)

Configure Service Graph Connector for Trellix using SGC Central

Use the playbook available with the SGC Central application to set up the Service Graph Connector for Trellix for pulling in Trellix data into the CMDB.

Before you begin

Install Service Graph Connector for Trellix version 1.0.0 from the ServiceNow Store. For ServiceNow Store installation steps, see [Install a ServiceNow Store application](#).

Role required: SGC-Admin (sn_cmdb_int_util.sgc_admin)

Note: The admin user role is required to run background scripts and to provide table-level access to the SGC-Admin user.

About this task

The playbook experience for onboarding connectors is activated with SGC Central in the CMDB Workspace. To configure the SGC Central application, see [Configuring SGC Central](#) and for more information on how to interact with a playbook, see [Interact with Playbook](#).

Procedure

1. Navigate to **Workspaces > CMDB Workspace**.
2. In the CMDB Workspace, select **SGC Central**.
3. On the Dashboard page, select **Create connection**.

Tip: Alternatively, you can select **Create connection** on the All connections page.
4. On the Create connection window, select the Trellix connector type, and then select **Create connection**.
5. Complete the initial prerequisites when setting up a connection for the first time using a connector.

Note: This step is required only during the first-time setup. See [Perform initial setup tasks when creating a connection in SGC Central](#).
6. Complete the setup for configuring the connector for importing data.
 - a. Create and test a connection.

- a. In the **Setup** stage of the playbook, select the **Create and test connection** activity.
- b. On the form, fill in the fields.

Create and test connection form

Field	
Connection name	Name to identify the Trellix connection record. For example, SGTrellix.
Connection url	URL of the connection.
User name	User name of your Trellix account.
Password	Password of your Trellix account.
Use MID server	Option to use a MID Server. Select this check box if you're using an on-premises instance of Trellix. Note: A MID Server must be configured on your ServiceNow instance before you select this option.
Mid Selection	Name of the MID Server used by the connector. This field appears only when the Use MID Server check box is selected.

- c. Select **Create and test connection**.

- d. Once the connection test is complete, select **Continue**.
- b. Configure the import schedule to import data at regular intervals.
 - a. In the **Setup** stage of the playbook, select the **Configure import schedule** activity.
 - b. Expand the Parent scheduled data import within the Import schedules list, and select the SG-Trellix-Devices import schedule.
 - c. In the Configure import schedule dialog box, select the **Active** check box, and then fill in the run schedule and time details.

For more information, see [Schedule a data import](#).

- d. Select **Save**.

Alternatively, select **Execute Now** to execute the import schedule immediately.

- e. Select **Continue**.
- c. In the **Setup** stage of the playbook, select the **Confirm connection setup** activity to verify whether the connection was created.

What to do next

Select **View all connections** to review the connection details. The configured connection appears in the Installed connections list.

Related concepts

- [Service Graph Connector for Trellix](#)
- [Accessing the connection details of Service Graph Connector for Trellix](#)

Related reference

- [CMDB classes targeted in Service Graph Connector for Trellix](#)

Configure Service Graph Connector for Trellix using guided setup

Set up scheduled import jobs to pull in data from a Trellix project into your CMDB.

Before you begin

Important: Unless there are configuration issues, use the SGC Central view in the CMDB Workspace to configure the connection for the connector, as the guided setup method is being deprecated.

To use this Service Graph Connector, you need a subscription to a Subscription Unit that is based in the IT Operations Management (ITOM) Visibility application or in the ITOM Discovery application. As defined in the section titled "Managed IT Resource Types" in [ServiceNow Subscription Unit Overview](#) for your subscription, for managed IT resources that are created or modified in the CMDB by this Service Graph Connector, but that aren't yet managed by [ITOM Visibility](#) or [ITOM Discovery](#), these resources will increase Subscription Unit consumption from that application. Review your current Subscription Unit consumption within ITOM Visibility or ITOM Discovery to ensure available capacity.

Dependencies and requirements:

- The Integration Commons for CMDB store app, which is automatically installed. See [Integration Commons for CMDB](#).
- The CMDB CI class models store app, which is automatically installed. See [CMDB CI Class Models](#).
- The ITOM Licensing plugin (com.snc.itom.license). See [Request Discovery](#).

Role required: SGC-Admin (sn_cmdb_int_util.sgc_admin)

Note: The admin user role is required to run background scripts and to provide table-level access to the SGC-Admin user.

Procedure

1. Verify that the application scope is set to the Service Graph Connector for Trellix application by using the application picker. For more information, see [Application picker](#).
2. Navigate to **All > Service Graph Connectors > Trellix > Setup**.
3. On the Service Graph Connector for Trellix page, verify that the **Quick Start** option is selected, and then select **Continue**.
4. Configure the connection to send requests to the Trellix application.
 - a. On the Service Graph Connector for Trellix page, in the Configure the Connection and Credentials section, select **Start**.
 - b. Configure the authentication credentials.
 - a. For the Configure Trellix authentication credentials task, fill in the fields on the Basic Auth Credentials form.

Basic Auth Credentials form

Field	Description
Name	Credentials to use for the connection. For example, <code>SGTrellix.Credentials</code> .
Order	The sequence in which the records are processed. The default value is <code>100</code> .
User name	User name of your Trellix account.
Password	Password of your Trellix account.
Active	Verify that the check box is selected.

- b. Select **Update** to save the authentication credentials.

- c. Set the Configure Trellix authentication credentials task to complete by selecting **Mark as complete**, and then select **Continue**.
- c. Configure the HTTP connection.
 - a. For the Configure Trellix HTTP Connection task, fill in the fields on the HTTP(s) Connection form.

HTTP(s) Connection form

Field	Description
Name	Name to identify the Trellix connection record. For example, SGTrellix. Don't modify the name for the default connection SGTrellix.
Active	Verify that the check box is selected.
Credential	Credentials to use for the connection.
Domain	Domain that contains the connection.
Connection alias	Connection alias that resolves your connection and credentials at runtime. Note: Only one connection is active per connection alias at a time.
Connection URL	Base URL of the connection. The base URL is the hostname of your Trellix instance. For example,

Field	Description
	https:// subdomain.domain.com:port.
Use MID server	Option to use a MID Server. Select this check box if you're using an on-premises instance of Trellix. Complete the Advanced MID Server Configuration . Note: A MID Server must be configured on your ServiceNow instance before you select this option.
MID selection	Select a MID Server from the list. This field appears only when the Use MID Server check box is selected.
MID application	Select a MID Server application from the list. This field appears only when the Use MID Server check box is selected.
Connection timeout	The maximum time (in seconds) the system waits while attempting to establish a connection.

b. Select **Update** to save the HTTP connection details.

- c. Set the Configure Trellix HTTP Connection task to complete by selecting **Mark as complete**, and then select **Continue**.
- d. Test the Trellix API connection to import data from the Trellix application.
 - a. Test the connection by selecting the **Test Connection** related link in the Test Connection task.

Testing the connection might take a few moments. The page is refreshed to show the test results.

- b. When the **Status** field is set to **Success**, set the Test Connection task to complete by selecting **Mark as complete**, and then select **Continue**.

If any of the tests have errors, follow the suggestions for remediation.

5. (Optional) Add multiple instances.

Note: If you don't need to add multiple instances, you can skip this step.

- a. On the Service Graph Connector for Trellix page, in the Add Multiple Instances section, select **Start**.
- b. In the Update Data Source Access section, select the Data Source [sys_data_source] table.
- c. Select the **Global** application scope by using the application picker.
- d. In the Application Access related list, select the **Can create**, **Can update**, and **Can delete** check boxes, if not already selected.
- e. Modify the application scope again to **Service Graph Connector for Trellix** by using the application picker.
- f. Select **Update** to save the data source access details.
- g. Set the Update Data Source Access task to complete by selecting **Mark as Complete**, and then select **Continue**.

- h. Repeat steps 5.c to 5.e for the Update Scheduled Data Import Access task with the Scheduled data import [scheduled_data_set] table.
- i. Select **Update** to save the scheduled data import access details.
- j. Set the Update Scheduled Data Import Access task to complete by selecting **Mark as Complete**, and then select **Continue**.
- k. In the Add Another Connection section, modify the application scope to **Service Graph Connector for Trellix** by using the application picker.
- l. Select **Click Here**.
- m. On the Workflow Studio page, select **Add Connection** in the SGTrellix section.
- n. Fill in the fields on the Create Connection form, and then select **Create Connection**.

Create Connection form

Field	Description
Connection name	Name to identify the Trellix connection record.
Connection url	URL of the connection.
Use MID server	Option to use a MID Server. Select this check box if you're using an on-premises instance of Trellix. Complete the Advanced MID Server Configuration . Note: A MID Server must be configured on your ServiceNow instance before you select this option.
MID selection	Select a MID Server from the list.

Field	Description
	This field appears only when the Use MID Server check box is selected.
MID application	Select a MID Server application from the list. This field appears only when the Use MID Server check box is selected.
User name	User name of your Trellix account.
Password	Password of your Trellix account.

- o. Close the Workflow Studio page, and navigate back to the guided setup.
- p. Set the Add Another Connection task to complete by selecting **Mark as Complete**, and then select **Continue**.
- q. In the Test New Connections section, select the newly created connection record, and then select the **Test Connection** related link.

Testing the connection might take a few moments. The page is refreshed to show the test results.

- r. When the **Status** field is set to **Success**, set the Test New Connections task to complete by selecting **Mark as complete**, and then select **Continue**.

If any of the tests have errors, follow the suggestions for remediation.

6. Configure the scheduled jobs to import data from the Trellix application.

- a. On the Service Graph Connector for Trellix page, in the Set up scheduled import jobs section, select **Start**.
- b. For the Configure the scheduled jobs task, select the connection.

Note: The SG-Trellix-Devices scheduled import job is set to inactive by default.

- c. On the Scheduled Data Import form, verify the field values for the scheduled job.

For more information, see [Schedule a data import](#).

- d. Select the **Active** check box to activate the SG-Trellix-Devices scheduled import job.
 - e. In the **Run** field, select **Periodically** to specify how often the job runs.
 - f. Select **Execute Now** to execute the import schedule.
 - g. Set the Configure the scheduled jobs task to complete by selecting **Mark as complete**, and then select **Continue**.
7. On the Service Graph Connector for Trellix page, select **Exit** to exit the guided setup.

Related concepts

- [Service Graph Connector for Trellix](#)
- [Accessing the connection details of Service Graph Connector for Trellix](#)

Related reference

- [CMDB classes targeted in Service Graph Connector for Trellix](#)

CMDB classes targeted in Service Graph Connector for Trellix

When you complete setting up the connection, you can configure the integration to periodically pull data from Trellix. The data is saved in tables that extend from the Configuration item [cmdb_ci] table.

File System [cmdb_ci_file_system]

The following attributes in the File System [cmdb_ci_file_system] table are populated by collected data:

Attribute label	Attribute name
Computer	computer
Disk Space (GB)	disk_space
Free space bytes	free_space_bytes
Name	name

Relationship created for File System

Parent class	Relationship type	Child class
File System [cmdb_ci_file_system]	Reference	Server [cmdb_ci_server]

IP Address [cmdb_ci_ip_address]

The following attributes in the IP Address [cmdb_ci_ip_address] table are populated by collected data:

Attribute label	Attribute name
IP Address	ip_address
Netmask	netmask
Nic	nic

Relationship created for IP Address

Parent class	Relationship type	Child class
IP Address [cmdb_ci_ip_address]	Reference	Network Adapter [cmdb_ci_network_adapter]

Network Adapter [cmdb_ci_network_adapter]

The following attributes in the Network Adapter [cmdb_ci_network_adapter] table are populated by collected data:

Attribute label	Attribute name
Configuration Item	cmdb_ci
IP Address	ip_address
MAC Address	mac_address
Name	name
Netmask	netmask

Relationship created for Network Adapter

Parent class	Relationship type	Child class
Network Adapter [cmdb_ci_network_adapter]	Reference	Server [cmdb_ci_server]

Server [cmdb_ci_server]

The following attributes in the Server [cmdb_ci_server] table are populated by collected data:

Attribute label	Attribute name
Class	sys_class_name
CPU count	cpu_count
CPU speed (MHz)	cpu_speed
CPU type	cpu_type
DNS Domain	dns_domain

Attribute label	Attribute name
Host name	host_name
Install Status	install_status
IP Address	ip_address
Is Virtual	virtual
MAC Address	mac_address
Manufacturer	manufacturer
Model ID	model_id
Name	name
Operating System	os
OS Service Pack	os_service_pack
OS Version	os_version
RAM (MB)	ram
Serial number	serial_number

Relationships created for Server

Parent class	Relationship type	Child class
Server [cmdb_ci_server]	Contains::Contained by	Storage Disk [cmdb_ci_storage_disk]
Server [cmdb_ci_server]	Contains::Contained by	File System [cmdb_ci_file_system]
Server [cmdb_ci_server]	Owns::Owned by	IP Address [cmdb_ci_ip_address]

Parent class	Relationship type	Child class
Server [cmdb_ci_server]	Owns::Owned by	Network Adapter [cmdb_ci_network_adapter]

Software [cmdb_ci_spkg]

The following attributes in the Software [cmdb_ci_spkg] table are populated by collected data:

Attribute label	Attribute name
Key	key
Name	name
Version	version

Relationship created for Software

Parent class	Relationship type	Child class
Software [cmdb_ci_spkg]	Reference	Software Instance [cmdb_software_instance]

Software Installation [cmdb_sam_sw_install]

The following attributes in the Software Installation [cmdb_sam_sw_install] table are populated by collected data:

Attribute label	Attribute name
Discovery Source	discovery_source
Installed on	installed_on
Name	name
Version	version

Relationship created for Software Installation

Parent class	Relationship type	Child class
Software Installation [cmdb_sam_sw_install]	Reference	Server [cmdb_ci_server]

Software Instance [cmdb_software_instance]

The following attributes in the Software Instance [cmdb_software_instance] table are populated by collected data:

Attribute label	Attribute name
Installed on	installed_on
Name	name

Relationship created for Software Instance

Parent class	Relationship type	Child class
Software Instance [cmdb_software_instance]	Reference	Server [cmdb_ci_server]

Storage Disk [cmdb_ci_storage_disk]

The following attributes in the Storage Disk [cmdb_ci_storage_disk] table are populated by collected data:

Attribute label	Attribute name
Computer	computer
Disk space (GB)	disk_space
Free disk space (GB)	free_space
Name	name

Relationship created for Storage Disk

Parent class	Relationship type	Child class
Storage Disk [cmdb_ci_storage_disk]	Reference	Server [cmdb_ci_server]

Related concepts

- [Service Graph Connector for Trellix](#)

Accessing the connection details of Service Graph Connector for Trellix

You can access the connection details of the Service Graph Connector for Trellix in a single view using the common connection framework (CCF) included within the Integration Commons for CMDB (sn_cmdb_int_util) store app.

With the CCF, you can access all the connections used by the Service Graph Connector for Trellix. The connection details include the connection alias, connection properties, data sources, and scheduled data imports associated with a connection. You can also test the connection. For more information, see [Accessing the connection details of Service Graph Connectors](#).

Access the details of a Trellix connection

Access the details of a Trellix connection configured for the Service Graph Connector for Trellix.

Before you begin

Role required: admin

Procedure

1. Navigate to **All > Service Graph Connectors > Trellix > Connections**.

2. From the **Name** column of the Service Graph Connections list, select a connection.
3. On the Service Graph Connections page, view the connection details such as the connection name, alias, and data sources.
4. Select a related list to view further details of the connection.
5. (Optional) Select the **Test Connection** related link to test the connection.

Related concepts

- [Service Graph Connector for Trellix](#)