

Zurich ServiceNow AI Platform Capabilities

Last updated: January 16, 2026

Some examples and graphics depicted herein are provided for illustration only. No real association or connection to ServiceNow products or services is intended or should be inferred.

This PDF was created from content on docs.servicenow.com. The web site is updated frequently. For the most current ServiceNow product documentation, go to docs.servicenow.com.

Company Headquarters

2225 Lawson Lane
Santa Clara, CA 95054
United States
(408)501-8550

Service Graph Connector for VMware Workspace ONE UEM

Use the Service Graph Connector for VMware Workspace ONE UEM to pull data from VMware Workspace ONE Unified Endpoint Management (UEM) into your ServiceNow Instance.

Request apps on the Store

Visit the [ServiceNow Store](#) website to view all the available apps and for information about submitting requests to the store. For cumulative release notes information for all released apps, see the [ServiceNow Store version history release notes](#).

The integration imports different hardware assets into the ServiceNow® Configuration Management Database (CMDB) application.

Supported versions

- Supported versions:
 - VMware Workspace ONE UEM version 2008
 - Application Discovery Manager (ADM) API version 2
- Supported ServiceNow versions:
 - Xanadu
 - Yokohama
 - Zurich

Use cases

The following are examples on how you can use the Service Graph Connector for different ServiceNow applications:

- [IT Operations Management \(ITOM\) Visibility](#)
 - Detailed hardware and application inventory for Android, Apple, and Windows mobile devices. The inventory can be used with or without Software Asset Management (SAM).

- Compliance tracking for mobile devices. You can build your own device (BYOD) or use corporate-owned devices.
- [IT Service Management \(ITSM\)](#)
 - Incident, problem, change on discovered configuration items (CI).
 - Ownership tracking and assignment for mobile devices.

Guided setup

The guided setup for the Service Graph Connector for VMware Workspace ONE UEM provides an organized sequence of tasks to configure the integration on your instance. To access the guided setup, see [Configure Service Graph Connector for VMware Workspace ONE UEM](#).

CMDB integrations dashboard

The Integration Commons for CMDB store app provides a dashboard with a central view of the status, processing results, and processing errors of all installed integrations. You can see metrics for all integration runs. You can filter the view to a specific CMDB integration, a specific time duration, or a specific integration run. For more details about monitoring Workspace ONE integrations in the CMDB Integrations Dashboard, see [Using the CMDB Integrations Dashboard](#).

Data mapping

Data from the VMware Workspace ONE UEM Devices and Apps data sources is mapped and transformed into the ServiceNow CMDB Configuration Item (CI) class definitions using the Robust Transform Engine (RTE). Data is inserted into the ServiceNow CMDB using the Identification and Reconciliation Engine (IRE).

When you complete setting up the connection, you configure the integration to periodically pull data from VMware Workspace ONE UEM.

The data is loaded into the SG-Workspace ONE UEM Devices and Apps staging [sn_vmwoneuem_integ_devices_and_apps] table.

The data is then inserted into the following target tables:

- Computer [cmdb_ci_computer]

- Handheld Computing Device [cmdb_ci_handheld_computing]
- Media Player [cmdb_ci_media_player]
- Network Adapter [cmdb_ci_network_adapter]
- Printer [cmdb_ci_printer]
- SAM Software Installation [cmdb_sam_sw_install], if com.snc.sams plugin is installed.
- Serial Number [cmdb_serial_number]
- Software Instance [cmdb_software_instance], if com.snc.sams plugin is not installed.
- Software Package [cmdb_ci_spkg], if com.snc.sams plugin is not installed.

Note: To view any additional information such as the device owner, type of ownership, or compliance status, you need to switch to the SG-Workspace ONE UEM view. This view displays a **SG-Workspace ONE UEM Device Related** tab in the related list tabs with the additional information.

For more information on where data is saved when pulling data from VMware Workspace ONE Unified Endpoint Management (UEM), see [CMDB classes targeted in Service Graph Connector for VMware Workspace ONE UEM](#).

You can use the IntegrationHub ETL app to view the data maps. See [IntegrationHub ETL](#) for more information.

Related concepts

- [Service Graph Connectors](#)

Configure Service Graph Connector for VMware Workspace ONE UEM

Use the Service Graph Connector for VMware Workspace ONE UEM to pull mobile and computing devices data from VMware Workspace ONE Unified Endpoint Management (UEM) into your ServiceNow instance.

Before you begin

To use this Service Graph Connector, you need a subscription to a Subscription Unit that is based in the IT Operations Management (ITOM) Visibility application or in the ITOM Discovery application. As defined in the section titled "Managed IT Resource Types" in [ServiceNow Subscription Unit Overview](#) for your subscription, for managed IT resources that are created or modified in the CMDB by this Service Graph Connector, but that aren't yet managed by [ITOM Visibility](#) or [ITOM Discovery](#), these resources will increase Subscription Unit consumption from that application. Review your current Subscription Unit consumption within ITOM Visibility or ITOM Discovery to ensure available capacity.

Dependencies and requirements:

- The [Integration Commons for CMDB](#) store app, which is automatically installed.
- The CMDB CI class models store app, which is automatically installed. See [CMDB CI Class Models](#).
- The ITOM Discovery License plugin (com.snc.itom.discovery.license). You must activate this plugin.
- ITOM Licensing plugin (com.snc.itom.license). For more information, see [Request Discovery](#).
- The Datastream Action plugin (com.glide.hub.action_type.datastream), which is automatically installed.

Role required: SGC-Admin (sn_cmdb_int_util.sgc_admin)

Note: The admin user role is required to run background scripts and to provide table-level access to the SGC-Admin user.

When using client credentials for authentication, obtain the OAuth credentials from your VMware Workspace ONE UEM administrator. Make a note of the following details:

- Application (client) ID
- Client Secret
- Token URL

For information about how to get OAuth credentials, see the [VMware documentation site](#).

About this task

To configure the Service Graph Connector for VMware Workspace ONE UEM, you must configure either OAuth authentication credentials or basic authentication credentials.

Procedure

1. Navigate to **All > Service Graph Connectors > Workspace ONE UEM > Setup**.
2. On the Getting started page, select **Get Started**.
3. In the Configure the Connection and Credentials section of the Service Graph Connector for VMware Workspace ONE UEM page, select **Get Started**.
4. Configure authentication credentials for the connection. You can configure either a basic authentication connection or an OAuth connection.
 - a. For the Set authentication type task, select **Configure**.
 - To enable basic authentication, set the value of the `auth_type` connection property to `basic`.
 - To enable OAuth authentication, set the value of the `auth_type` connection property to `oauth`.
 - b. Select **Update**, and navigate back to the guided setup page.

- c. Set the Set authentication type task to complete by selecting **Mark as Complete**.
5. Configure the credentials for authentication.

- Configure a basic authentication connection.
 - a. For the Configure the Basic Auth Credentials task, select **Configure**.
 - b. On the form, fill in the fields.

Field	Description
Name	Name of the authentication. For example, WorkspaceOneUEM Basic Auth Credentials .
User name	Your VMware Workspace ONE UEM user name.
Password	Your VMware Workspace ONE UEM password.

- c. Select **Update**, and navigate back to the guided setup page.
- d. Set the Configure the Basic Auth Credentials task to complete by selecting **Mark as Complete**.
- e. For the Configure API key task, select **Configure** to configure an API key for the basic authentication connection.
- f. In the **API Key** field, enter your VMware Workspace ONE UEM API key or tenant code.
- g. Select **Update**, and navigate back to the guided setup page.
- h. Set the Configure API key task to complete by selecting **Mark as Complete**.

- Configure an OAuth connection.
 - a: For the Configure the OAuth Credentials task, select **Configure**.
 - b: On the form, fill in the fields.

Field	Description
Name	Name of the authentication. For example, WorkspaceOneUEM OAuth Provider .
Client ID	Application (client) ID of your VMware Workspace ONE UEM client application as noted in the Before you begin section.
Client Secret	Client secret of your VMware Workspace ONE UEM client application as noted in the Before you begin section.

- c: Select **Update**, and navigate back to the guided setup page.
 - d: Set the Configure the OAuth Credentials task to complete by selecting **Mark as Complete**.
6. Establish an HTTP connection to send requests to the VMware Workspace ONE UEM API.
 - a. For the Configure HTTP connection task, select **Configure**.
 - b. On the HTTP(s) Connection form, specify the host name of your VMware Workspace ONE UEM instance in the **Host** field.

Note: The HTTP connection is pre-configured to use the authentication credentials that were configured in steps 4 and 5.

- c. Select **Update**.
 - d. Set the Configure HTTP Connection task to complete by selecting **Mark as Complete**.
7. Test the connection.
 - a. For the Test the Connection task, select **Configure**.
 - b. Select the **Test Connection** related link to start the testing process.
 - c. When the **Status** field is set to **Success**, navigate back to the guided setup page.
If any of the tests have errors, follow the suggestions for remediation.
 - d. Set the Test the Connection task to complete by selecting **Mark as Complete**.
8. Set up the scheduled import job.
 - a. For the Configure the scheduled job task, select **Configure**.
The SG-Workspace ONE UEM Devices and Apps scheduled job is set to inactive by default.
 - b. Select the **SG-Workspace ONE UEM Devices and Apps** scheduled job.
 - c. On the Scheduled Data Import form, verify the field values for the scheduled job.
For more information, see [Schedule a data import](#).
 - d. Select the **Active** check box to activate the SG-Workspace ONE UEM Devices and Apps scheduled job.
 - e. In the **Run** field, select **Periodically** to specify how often the job should run.
 - f. Select **Update**.
Alternatively, select **Execute Now** to execute the import schedule immediately.
 - g. Set the Configure the scheduled job task to complete by selecting **Mark as Complete**.
9. (Optional) Add multiple instances.

Note: If you don't need to add multiple instances, you can skip this step.

- a. In the Add multiple instances section of the Service Graph Connector for VMware Workspace ONE UEM page, select **Get Started**.
- b. For the Update scheduled data import access task, select **Configure**.
- c. Select the Scheduled data import [scheduled_import_set] table.
- d. Select the **Global** application scope by using the application picker.
- e. In the Application Access related list, select the **Can create, Can update, and Can delete** check boxes, if not already selected.
- f. Select **Update**, and then navigate back to the guided setup.
- g. Modify the application scope again to **Service Graph Connector for VMware Workspace ONE UEM** by using the application picker.
- h. Set the Update scheduled data import access task to complete by selecting **Mark as Complete**.
- i. For the Update Data Source Access task, select **Configure**.
- j. Select the Data Source [sys_data_source] table.
- k. Repeat steps 9.d to 9.g.
- l. Set the Update Data Source Access task to complete by selecting **Mark as Complete**.
- m. Clear the cache for the new connection.
 - a. For the Clear cache for Data Source and Import Set tables task, select **Configure**.
 - b. Select the **Global** application scope by using the application picker.
 - c. In the **Run script** text box of the background script page, enter the following script:

```
GlideTableManager.invalidateTable("sys_data_source");

    GlideCacheManager.flushTable("sys_data_source");
    GlideTableManager.invalidateTable("scheduled_import_set");

    GlideCacheManager.flushTable("scheduled_import_set");
    GlideTableManager.invalidateTable("sys_db_object");

    GlideCacheManager.flushTable("sys_db_object");
```

d. Select **Run Script** to run the background script.

The script may take several minutes to execute.

e. After the script is executed, select **Close**.

f. Modify the application scope again to **Service Graph Connector for VMware Workspace ONE UEM** by using the application picker.

g. Set the Clear cache for Data Source and Import Set tables task to complete by selecting **Mark as complete**.

n. Configure the connection for the VMware Workspace ONE UEM instance.

You can configure either a basic authentication connection or an OAuth connection.

- Configure a basic authentication connection.
 - a. For the Add basic authentication connection task, select **Configure**.
 - b. To create a new connection, select **Add Connection**.
 - c. In the Connection Information section of the Create Connection window, fill in the fields.

Connection Information

Field	Description
Connection name	Name to identify the VMware Workspace ONE UEM connection record.
Connection URL	Connection URL of your VMware Workspace ONE UEM connection. Use the format https://host-name/API for the connection URL.

- d. In the Credential Information section of the Create Connection window, fill in the fields.

Credential Information

Field	Description
Username	VMware Workspace ONE UEM account user name that is used to authenticate the connection request.
Password	Password that is used to authenticate the connection request.

- e. Select **Create Connection**.
- f. Navigate back to the guided setup, and set the Add basic authentication connection task to complete by selecting **Mark as Complete**.
- g. For the Configure API key task, select **Configure** to configure an API key for the basic authentication connection.

- h. Select the **API Key** record that corresponds to the connection alias for the new basic authentication connection.
- i. Set the API key, and then select **Update**.
- j. Navigate back to the guided setup, and set the Configure API key task to complete by selecting **Mark as Complete**.
- Configure an OAuth connection.
 - a. For the Add an OAuth connection task, select **Configure**.
 - b. To create a new connection, select **Add Connection**.
 - c. In the Connection Information section of the Create Connection window, fill in the fields.

Connection Information

Field	Description
Connection Name	Name to identify the VMware Workspace ONE UEM connection record.
Connection URL	Connection URL of your VMware Workspace ONE UEM controller. Use the format https://host-name/API for the connection URL.

- d. In the Credential Information section of the Create Connection window, fill in the fields.

Credential Information

Field	Description
OAuth Client ID	Application (client) ID of your VMware

Field	Description
	Workspace ONE UEM client application as noted in the Before you begin section.
OAuth Client Secret	Client secret of your VMware Workspace ONE UEM client application as noted in the Before you begin section.

For information about how to get OAuth credentials, see the [VMware documentation site](#).

- e. Select **Create and Get OAuth Token**.
- f. Navigate back to the guided setup, and set the Add an OAuth connection task to complete by selecting **Mark as Complete**.
- o. Test the newly added connections.
 - a. For the Test connections task, select **Configure**.
 - b. From the **Name** column, select the new connection.
 - c. Select the **Test Connection** related link to start the testing process.
 - d. When the **Status** field is set to **Success**, return to the guided setup page.

Note: If any of the tests have errors, follow the suggestions for remediation.
 - e. Set the Test connections task to complete by selecting **Mark as Complete**.
- p. Configure the scheduled job to import data from the VMware Workspace ONE UEM application.

The SG-Workspace ONE UEM Devices and Apps scheduled job is set to inactive by default.

- a. For the Configure import schedule task, select **Configure**.
- b. Select the **SG-Workspace ONE UEM Devices and Apps** scheduled job.
- c. On the Scheduled Data Import form, verify the field values for the scheduled job.

For more information, see [Schedule a data import](#).

- d. Select the **Active** check box to activate the SG-Workspace ONE UEM Devices and Apps scheduled job.
- e. In the **Run** field, select **Periodically** to specify how often the job should run.
- f. Select **Update**.

Alternatively, select **Execute Now** to execute the import schedule immediately.

10. (Optional) Configure additional settings.

- a. In the Configure additional settings (optional) section of the Service Graph Connector for VMware Workspace ONE UEM page, select **Get Started**.
- b. For the Configure duplicate detection rules task, select **Configure**.
- c. On the CMDB Duplicate Row Rule form, select **Active**.
- d. Update the Value field to true to activate the duplicate detection rule during data import.
- e. Select **OK**, and navigate back to the guided setup.
- f. To remove fields from being evaluated, add the field names as a comma-separated list in the Ignore Fields column on the CMDB Duplicate Row Rules form.
Use this option for fields that change with every import.

- g. Set the Configure duplicate detection rules task to complete by selecting **Mark as Complete**.
- h. For the Enable software import task, select **Configure**.
 - i. Select the connection record for which you want to enable the import of software data.
The turn_off_software_import connection property is set to true by default.
 - j. Set the turn_off_software_import connection property value to false to import software data.
- k. Set the Enable software import task to complete by selecting **Mark as Complete**.
- l. For the Import non-managed software task, select **Configure**.
- m. Select the connection record for which you want to import non-managed software data.
By default, software records that have the **IsManaged** field set to false aren't imported.
- n. Set the managed_apps_only connection property value to false to import non-managed software data.
- o. Set the Import non-managed software task to complete by selecting **Mark as Complete**.
- p. For the Import apps based on software status value task, select **Configure**.
By default, the connector imports applications that have the status value 2, 3, or 5.

Status values of applications

Status	Value
Pending Install	1
Installed	2
Pending Removal	3
Removed	4

Status	Value
Unknown	5

- q. Select the connection record for which you want to update the set of imported applications.
- r. Set the import_apps_with_status connection property value to the required software status values (as a comma-separated list).
- s. Set the Import apps based on software status value task to complete by selecting **Mark as Complete**.

CMDB classes targeted in Service Graph Connector for VMware Workspace ONE UEM

When you complete setting up the connection, you can configure the integration to periodically pull data from VMware Workspace ONE Unified Endpoint Management (UEM). The data is saved in tables that extend from the Configuration item [cmdb_ci] table.

Computer [cmdb_ci_computer]

The following attributes in the Computer [cmdb_ci_computer] table are populated by collected data:

Attribute label	Attribute name
Name	name
Serial number	serial_number
Is Virtual	virtual
Most recent discovery	last_discovered
Operating System	os
OS Version	os_version
RAM (MB)	ram

Attribute label	Attribute name
Assigned to	assigned_to
Model ID	model_id
Manufacturer	manufacturer

Handheld Computing Device [cmdb_ci_handheld_computing]

The following attributes in the Handheld Computing Device [cmdb_ci_handheld_computing] table are populated by collected data:

Attribute label	Attribute name
MAC Address	mac_address
Name	name
Serial number	serial_number
IMEI	imei
Most recent discovery	last_discovered
Operating System	os
OS Version	os_version
Phone Number	phone_number
RAM (MB)	ram
Root Access	root_access
Manufacturer	manufacturer
Model ID	model_id
Carrier	carrier

Attribute label	Attribute name
Assigned to	assigned_to

Hardware [cmdb_ci_hardware]

The following attribute in the Hardware [cmdb_ci_hardware] table is populated by collected data:

Attribute label	Attribute name
Most recent discovery	last_discovered

Relationships created for Hardware

Parent class	Relationship type	Child class
Hardware [cmdb_ci_hardware]	Owns::Owned by	Network Adapter [cmdb_ci_network_adapter]
Hardware [cmdb_ci_hardware]	Owns::Owned by	IP Address [cmdb_ci_ip_address]
Hardware [cmdb_ci_hardware]	Reference	SG-Workspace ONE UEM Device Related [sn_vmwoneuem_integ_device_related]
Hardware [cmdb_ci_hardware]	Reference	Key Value [cmdb_key_value]

IP Address [cmdb_ci_ip_address]

The following attributes in the IP Address [cmdb_ci_ip_address] table are populated by collected data:

Attribute label	Attribute name
Name	name
Nic	nic

Attribute label	Attribute name
IP Address	ip_address
IP version	ip_version

Relationship created for IP Address

Parent class	Relationship type	Child class
IP Address [cmdb_ci_ip_address]	Reference	Network Adapter [cmdb_ci_network_adapter]

Key Value [cmdb_key_value]

The following attributes in the Key Value [cmdb_key_value] table are populated by collected data:

Attribute label	Attribute name
Key	key
Value	value

Media Player [cmdb_ci_media_player]

The following attributes in the Media Player [cmdb_ci_media_player] table are populated by collected data:

Attribute label	Attribute name
Name	name
Serial number	serial_number
Manufacturer	manufacturer
Model ID	model_id
MAC Address	mac_address

Attribute label	Attribute name
Assigned to	assigned_to
Most recent discovery	last_discovered

Network Adapter [cmdb_ci_network_adapter]

The following attributes in the Network Adapter [cmdb_ci_network_adapter] table are populated by collected data:

Attribute label	Attribute name
Name	name
Configuration Item	cmdb_ci
MAC Address	mac_address
Most recent discovery	last_discovered

Relationship created for Network Adapter

Parent class	Relationship type	Child class
Network Adapter [cmdb_ci_network_adapter]	Reference	Hardware [cmdb_ci_hardware]

Printer [cmdb_ci_printer]

The following attributes in the Printer [cmdb_ci_printer] table are populated by collected data:

Attribute label	Attribute name
Assigned to	assigned_to
MAC Address	mac_address
Name	name

Attribute label	Attribute name
Most recent discovery	last_discovered
Manufacturer	manufacturer
Model ID	model_id
Serial number	serial number

Serial Number [cmdb_serial_number]

The following attributes in the Serial Number [cmdb_serial_number] table are populated by collected data:

Attribute label	Attribute name
Serial Number	serial_number
Serial Number Type	serial_number_type
Valid	valid

Relationships created for Serial Number

Parent class	Relationship type	Child class
Serial Number [cmdb_serial_number]	Reference	Computer [cmdb_ci_computer]
Serial Number [cmdb_serial_number]	Reference	Handheld Computing Device [cmdb_ci_handheld_computing]
Serial Number [cmdb_serial_number]	Reference	Printer [cmdb_ci_printer]
Serial Number [cmdb_serial_number]	Reference	Media Player [cmdb_ci_media_player]

SG-Workspace ONE UEM Device Related [sn_vmwoneuem_integ_device_related]

The following attributes in the SG-Workspace ONE UEM Device Related [sn_vmwoneuem_integ_device_related] table are populated by collected data:

Attribute label	Attribute name
Device ID	device_id
Device Compliance State	compliance_state
Device Ownership	device_ownership
User Email	user_email
User Name	user_name

Software [cmdb_ci_spkg]

The following attributes in the Software [cmdb_ci_spkg] table are populated by collected data:

Attribute label	Attribute name
Key	key
Name	name
Version	version

Relationship created for Software

Parent class	Relationship type	Child class
Software [cmdb_ci_spkg]	Reference	Software Instance [cmdb_software_instance]

Software Instance [cmdb_software_instance]

The following attributes in the Software Instance [cmdb_software_instance] table are populated by collected data:

Attribute label	Attribute name
Name	name
Installed on	installed_on

Relationship created for Software Instance

Parent class	Relationship type	Child class
Software Instance [cmdb_software_instance]	Reference	Hardware [cmdb_ci_hardware]

Accessing the connection details of Service Graph Connector for VMware Workspace ONE UEM

You can access the connection details of the Service Graph Connector for VMware Workspace ONE UEM in a single view using the common connection framework (CCF) included within the Integration Commons for CMDB (sn_cmdb_int_util) store app.

With the CCF, you can access all the connections used by the Service Graph Connector for VMware Workspace ONE UEM. The connection details include the connection alias, connection properties, data sources, and scheduled data imports associated with a connection. You can also test the connection. For more information, see [Accessing the connection details of Service Graph Connectors](#).

Access the details of a VMware Workspace ONE UEM connection

Access the details of a VMware Workspace ONE UEM connection configured for the Service Graph Connector for VMware Workspace ONE UEM.

Before you begin

Role required: admin

Procedure

1. Navigate to **All > Service Graph Connectors > Workspace ONE UEM > Connections**.
2. From the **Name** column of the Service Graph Connections list, select a connection.
3. On the Service Graph Connections page, view the connection details such as the connection name, alias, and data sources.
4. Select a related list to view further details of the connection.
5. (Optional) Select the **Test Connection** related link to test the connection.

Related concepts

- [Service Graph Connector for VMware Workspace ONE UEM](#)