

Zurich ServiceNow AI Platform Capabilities

Last updated: January 16, 2026

Some examples and graphics depicted herein are provided for illustration only. No real association or connection to ServiceNow products or services is intended or should be inferred.

This PDF was created from content on docs.servicenow.com. The web site is updated frequently. For the most current ServiceNow product documentation, go to docs.servicenow.com.

Company Headquarters

2225 Lawson Lane
Santa Clara, CA 95054
United States
(408)501-8550

Service Graph Connector for Wiz

Use the Service Graph Connector for Wiz to ingest CMDB data from projects within the Wiz platform using the REST APIs.

Request apps on the Store

Visit the [ServiceNow Store](#) website to view all the available apps and for information about submitting requests to the store. For cumulative release notes information for all released apps, see the [ServiceNow Store version history release notes](#).

Key features

- Get started quickly with a streamlined onboarding process.
- Use only the credentials you need.
- Be instantly aware of any modifications with near real-time discovery of changes.
- Get visibility across multiple cloud environments.
- Identify risks in the environment through Wiz.
- Assess application dependencies.
- Get the most out of your security incident response and endpoint management with the ServiceNow AI Platform.

Supported versions

Versions

Wiz	ServiceNow
Last tested on October 17, 2025	• Xanadu • Yokohama • Zurich

Use cases

You can use the Service Graph Connector for Wiz to get visibility into cloud resource identities, relationships, and state in real-time.

Configuring a connection

Use the SGC Central view in the CMDB Workspace to install the connector and configure the connection. The view enables you to install and discover connectors and to manage the full life cycle of creating, editing, monitoring, and debugging connections. For instructions, see [Set up the Wiz environment](#).

Important: Starting with the Service Graph Connector for Wiz version 1.4.0, the guided setup method is deprecated. Use the SGC Central view in the CMDB Workspace to configure the connection for the connector.

CMDB integrations dashboard

The Integration Commons for CMDB store app provides a dashboard with a central view of the status, processing results, and processing errors of all installed integrations. You can see metrics for all integration runs. You can filter the view to a specific CMDB integration, a specific time duration, or a specific integration run. For more details about monitoring Wiz integrations in the CMDB Integrations Dashboard, see [Using the CMDB Integrations Dashboard](#).

Data mapping

Data from the Wiz data sources is mapped and transformed into the ServiceNow CMDB Configuration Item (CI) class definitions using the Robust Transform Engine (RTE). Data is inserted into the ServiceNow CMDB using the Identification and Reconciliation Engine (IRE).

When you complete setting up the connection, you can configure the integration to periodically pull data from the Wiz application.

Note: For any discovered resources that were deleted later, the Service Graph Connector for Wiz automatically marks the corresponding records as retired or absent in CMDB.

The following table lists the data sources, the staging tables, and the target tables CMDB CI classes and non-CMDB classes where data is stored for a Wiz project.

Data sources mapping for Wiz

Data source	Staging table	Target tables
SG-Wiz-Organization	SG-Wiz-Organization [sn_wiz_integ_sg_wiz_organization]	Cloud Organizations SG-Wiz Extension Attributes Google Organization Folder
SG-Wiz-Subscription	SG-Wiz-Subscription [sn_wiz_integ_sg_wiz_subscription]	Cloud Service Account Google Organization Project VMware vCenter Datacenter SG-Wiz Extension Attributes Key Value
SG-Wiz-Datacenter	SG-Wiz-Datacenter [sn_wiz_integ_sg_wiz_datacenter]	AWS Datacenter Azure Datacenter Google Datacenter Logical Datacenter OCI Datacenter

Data source	Staging table	Target tables
		SG-Wiz Extension Attributes
SG-Wiz-Resource-Group	SG-Wiz-Resource-Group [sn_wiz_integ_sg_wiz_resource_group]	Resource Group SG-Wiz Extension Attributes Key Value
SG-Wiz-Network-Interface	SG-Wiz-Network-Interface [sn_wiz_integ_sg_wiz_network_interface]	Cloud Mgmt Network Interface SG-Wiz Extension Attributes Key Value
SG-Wiz-Virtual-Network	SG-Wiz-Virtual-Network [sn_wiz_integ_sg_wiz_virtual_network]	Cloud Network SG-Wiz Extension Attributes Key Value
SG-Wiz-Firewall	SG-Wiz-Firewall [sn_wiz_integ_sg_wiz_firewall]	Compute Security GroupKey Value
SG-Wiz-Volume	SG-Wiz-Volume [sn_wiz_integ_sg_wiz_volume]	Storage Volume Cloud Disk Type SG-Wiz Extension Attributes Key Value

Data source	Staging table	Target tables
SG-Wiz-Virtual-Machine	SG-Wiz-Virtual-Machine [sn_wiz_integ_sg_wiz_virtual_machine]	Virtual Machine Instance Hardware Type Cloud Hardware Type Linux Server Windows Server Server Key Value SG-Wiz Extension Attributes
SG-Wiz-Virtual-Machine-Image	SG-Wiz-Virtual-Machine-Image [sn_wiz_integ_sg_wiz_virtual_machine_image]	Image Note: Data with no subscription IDs for images aren't imported. Also, if the subscription ID for an image is available, but the subscription-specific details are not available in Wiz, the data isn't imported by the connector. Key Value SG-Wiz Extension Attributes

Data source	Staging table	Target tables
SG-Wiz-Load Balancer	SG-Wiz-Load Balancer [sn_wiz_integ_sg_wiz_load_balancer]	Cloud Load Balancer Key Value SG-Wiz Extension Attributes
SG-Wiz-Database	SG-Wiz-Database [sn_wiz_integ_sg_wiz_database]	Cloud DataBase Cloud DataBase Cluster DynamoDB Table Key Value SG-Wiz Extension Attributes
SG-Wiz-Bucket	SG-Wiz-Bucket [sn_wiz_integ_sg_wiz_bucket]	Cloud Object Storage Key Value SG-Wiz Extension Attributes
SG-Wiz-Serverless	SG-Wiz-Serverless [sn_wiz_integ_sg_wiz_serverless]	Cloud Function Key Value SG-Wiz Extension Attributes
SG-Wiz-Network-Address	SG-Wiz-Network-Address [sn_wiz_integ_sg_wiz_network_address]	Cloud Public IP Address Key Value

Data source	Staging table	Target tables
		SG-Wiz Extension Attributes
SG-Wiz-Storage-Account	SG-Wiz-Storage-Account [sn_wiz_integ_sg_wiz_storage_account]	Cloud Storage Account Key Value SG-Wiz Extension Attributes
SG-Wiz-API-Gateway	SG-Wiz-API-Gateway [sn_wiz_integ_sg_wiz_api_gateway]	Cloud Gateway Key Value SG-Wiz Extension Attributes
SG-Wiz-Snapshot	SG-Wiz-Snapshot [sn_wiz_integ_sg_wiz_snapshot]	Storage Volume Snapshot Key Value SG-Wiz Extension Attributes
SG-Wiz Kubernetes Cluster	SG-Wiz Kubernetes Cluster [sn_wiz_integ_sg_wiz_k8s_cluster]	Kubernetes Cluster Key Value SG-Wiz Extension Attributes
SG-Wiz Kubernetes Namespace	SG-Wiz-K8s Namespace [sn_wiz_integ_sg_wiz_k8s_namespace]	Kubernetes Namespace

Data source	Staging table	Target tables
		Key Value SG-Wiz Extension Attributes
SG-Wiz-Kubernetes Node	SG-Wiz-Kubernetes Node [sn_wiz_integ_sg_wiz_kubernetes_node]	Kubernetes Node Key Value SG-Wiz Extension Attributes
SG-Wiz-Kubernetes Deployment	SG-Wiz-Kubernetes Deployment [sn_wiz_integ_sg_wiz_kubernetes_deployment]	Kubernetes Deployment Key Value SG-Wiz Extension Attributes
SG-Wiz-Kubernetes Service	SG-Wiz-Kubernetes Service [sn_wiz_integ_sg_wiz_kubernetes_service]	Kubernetes Service Key Value SG-Wiz Extension Attributes
SG-Wiz-Kubernetes Pod	SG-Wiz-Kubernetes Pod [sn_wiz_integ_sg_wiz_kubernetes_pod]	Kubernetes Pod Key Value SG-Wiz Extension Attributes
SG-Wiz-Kubernetes Replica Set	SG-Wiz-Kubernetes Replica Set	Kubernetes ReplicaSet Key Value

Data source	Staging table	Target tables
	[sn_wiz_integ_sg_wiz_kubernetes_replica_set]	SG-Wiz Extension Attributes
SG-Wiz Kubernetes Container	SG-Wiz Kubernetes Container [sn_wiz_integ_sg_wiz_kubernetes_container]	Docker Container SG-Wiz Extension Attributes
SG-Wiz-Compute Instance Group	SG-Wiz-Compute Instance Group [sn_wiz_integ_sg_wiz_compute_instance_group]	Instance Scale Set SG-Wiz Extension Attributes Key Value
SG-Wiz-Gateway	SG-Wiz-Gateway [sn_wiz_integ_sg_wiz_gateway]	Internet Gateway AWS Datacenter SG-Wiz Extension Attributes Key Value

Note: All the labels or tags associated with a Wiz resource are added to the Key Value [cmdb_key_value] table and the project information about a Wiz resource is stored in the SG-Wiz Extension Attributes [sn_wiz_integ_extension_attributes] table.

For more information on where data is saved when pulling data from a Wiz project, see [Target tables for storing Service Graph Connector for Wiz data](#) and [Supported Wiz types](#).

You can use the IntegrationHub ETL app to view the data maps. See [IntegrationHub ETL](#) for more information.

Related concepts

- [Service Graph Connectors](#)

Set up the Wiz environment

You must obtain the credentials associated with the Wiz service account to configure Wiz for use with the Service Graph Connector for Wiz.

Before you begin

Role required: Wiz user with a role that has Write (W) permission on service accounts

About this task

To create a service account, you must be logged in as a Wiz user with Write (W) permission on service accounts. Project-scoped roles can create service accounts only on their own projects.

For more information on obtaining Wiz details, see [Add a Service Account](#) on the Wiz documentation site (requires Wiz login).

Procedure

1. Log in to your Wiz dashboard.
2. Obtain the Wiz URL.
 - a. Navigate to your user profile and copy the API Endpoint URL.

Note: The Service Graph Connector for Wiz uses the following token URL:

```
https://auth.app.wiz.io/oauth/token
```

3. Obtain the client ID and client secret.
 - a. Navigate to **Settings > Service Accounts**.
 - b. Select **Add Service Account**.
 - c. Name the new service account.

- d. (Optional) In the Projects list, select projects to limit access of the service account.
- e. In the **API Scopes** field, select the permissions read:resources and read:projects.
- f. Select **Add Service Account**.
- g. From the Copy your secret credentials dialog box that appears, copy the client secret and client ID from their respective fields.
- h. Select **Finish** to return to the Wiz dashboard.

Configure Service Graph Connector for Wiz using SGC Central

Set up scheduled import jobs to pull in data from a Wiz project into your Configuration Management Database (CMDB).

Before you begin

- Install Service Graph Connector for Wiz version 1.3.0 or later from the ServiceNow Store. For ServiceNow Store installation steps, see [Install a ServiceNow Store application](#).
- You must obtain the OAuth credentials associated with the Wiz service account and make a note of the following details:
 - Client ID
 - Client secret
 - OAuth token URL
 - Connection URL
 For more information, see [Set up the Wiz environment](#).
- You must have the following permissions for the Wiz service account:
 - read:resources
 - read:projects

Role required: The following table shows the roles required for each stage of the playbook.

Role required for each playbook stage

Stage	Role
Prerequisites	admin
Setup	cmdb_inst_admin or admin

About this task

The playbook experience for onboarding connectors is activated with SGC Central in the CMDB Workspace. To configure the SGC Central application, see [Configuring SGC Central](#) and for more information on how to interact with a playbook, see [Interact with Playbook](#).

Procedure

1. Navigate to **Workspaces > CMDB Workspace**.
2. In the CMDB Workspace, select **SGC Central**.
3. On the Overview page, select **Create connection**.

Tip: Alternatively, you can select **Create connection** on the All connections page.

4. On the Create connection window, select the Wiz connector type, and then select **Configure connection**.
A default connection, SG-Wiz, for Wiz is available within the application. As the Service Graph Connector for Wiz supports only a single instance, you can configure the default connection for the first time or resume editing it thereafter.
5. Complete the initial prerequisites when setting up a connection for the first time using a connector.

Note: This step is required when configuring the connector for the first time only. See [Perform initial setup tasks when creating a connection in SGC Central](#).

6. Enter connection details and test the API connection for importing Wiz data.
 - a. In the **Setup** stage of the playbook, select the **Create and test connection** activity.
 - b. On the form, fill in the fields.

Create and test connection form

Field	Description
Connection name	Name to identify the Wiz connection record.
Connection URL	Base URL to connect to your Wiz application. Note: Based on the region of your Wiz application, enter the connection URL in the following format: <code>https://api.<region>.app.wiz.io</code> Where <region> is the region where the Wiz tenant is located. For example, us1, us2, eu1, or eu2.
Client ID	Client ID of your Wiz application as described in Before you begin .
Client secret	Client secret of your Wiz application as described in Before you begin .
OAuth token URL	Token generation URL. This field is automatically set to the following URL:

Field	Description
	<code>https://auth.app.wiz.io/oauth/token</code>

- c. Select **Update and test connection**.
 - d. Once the connection test is complete, select **Continue**.
7. (Optional) Configure properties of the connector to access resources.
- Note:** To skip this step, select **Continue** for the **Set configuration properties** activity.

- a. In the **Setup** stage of the playbook, select the **Set configuration properties** activity.
- b. On the form, fill in the fields.

Configuration properties

Field	Description
Projects	List of project IDs for which the resources are to be imported. Separate multiple entries with a comma.
Exclude projects	List of project IDs for which the resources are excluded only when the Projects property isn't set. In this case, all the resources except for the specified projects are imported. Separate multiple entries with a comma.

- c. Select **Continue**.

8. Configure the import schedule to import data at regular intervals.
 - a. In the **Setup** stage of the playbook, select the **Configure import schedule** activity.
 - b. Expand the Parent scheduled data import within the Import schedules list to select the **SG-Wiz-Organization** import schedule.
 - c. Select the **Active** check box, and then fill in the run schedule and time details.

For more information, see [Schedule a data import](#).

- d. Select **Save**.
Alternatively, select **Execute Now** to execute the import schedule immediately.
9. (Optional) Enable the Reset Last Run Datetime for SG-Wiz script to retrieve full data periodically.

Note: To skip this step, select **Skip** for the **Enable full data retrieval** activity.

- a. In the **Setup** stage of the playbook, select the **Enable full data retrieval** activity.
 - b. Select the **Active** check box, and then fill in the run schedule and time details.

Note: When active, the script clears the **Last Run Date Time** field value in a data source, ensuring that the SG-Wiz Organization scheduled job retrieves all Wiz-related data sources periodically.

- c. Select **Continue**.

10. In the **Setup** stage of the playbook, select the **Confirm connection creation** activity to verify whether the connection was created.

What to do next

Select **View all connections** to review the connection details. The created connection appears in the Installed connections list.

Related concepts

- [Service Graph Connector for Wiz](#)
- [Accessing the connection details of Service Graph Connector for Wiz](#)

Related reference

- [Target tables for storing Service Graph Connector for Wiz data](#)
- [Service Graph Connector for Wiz properties](#)
- [Supported Wiz types](#)

Configure Service Graph Connector for Wiz using guided setup

Set up scheduled import jobs to pull in data from a Wiz project into your CMDB.

Before you begin

Important: Starting with the Service Graph Connector for Wiz version 1.4.0, the guided setup method is deprecated. Use the SGC Central view in the CMDB Workspace to configure the connection for the connector.

To use this Service Graph Connector, you need a subscription to a Subscription Unit that is based in the IT Operations Management (ITOM) Visibility application or in the ITOM Discovery application. As defined in the section titled "Managed IT Resource Types" in [ServiceNow Subscription Unit Overview](#) for your subscription, for managed IT resources that are created or modified in the CMDB by this Service Graph Connector, but that aren't yet managed by [ITOM Visibility](#) or [ITOM Discovery](#), these resources will increase Subscription Unit consumption from that application. Review your current Subscription Unit consumption within ITOM Visibility or ITOM Discovery to ensure available capacity.

Dependencies and requirements:

- Wiz advanced or standard license

- The Integration Commons for CMDB store app, which is automatically installed. See [Integration Commons for CMDB](#).
- The CMDB CI class models store app, which is automatically installed. See [CMDB CI Class Models](#).
- ITOM Licensing plugin (com.snc.itom.license). See [Request Discovery](#).
- Discovery and Service Mapping Patterns (sn_itom_pattern). See [Install Discovery and Service Mapping Patterns](#).
- Discovery Core (com.snc.discovery.core)

You must obtain the OAuth credentials associated with the Wiz service account and make a note of the following details:

- Client ID
- Client Secret
- OAuth Token URL
- Connection URL

See [Set up the Wiz environment](#).

You must have the following permissions for the Wiz service account:

- read:resources
- read:projects

Role required: admin

Procedure

1. Verify that the application scope is set to the Service Graph Connector for Wiz application by using the application picker. For more information, see [Application picker](#).
2. Navigate to **All > Service Graph Connectors > Wiz > Setup**.
3. On the Service Graph Connector for Wiz page, verify that the **Quick Start** option is selected and then select **Continue**.
4. Configure the connection to send requests to the Wiz application.

- a. In the Configure the Connection and Credentials section of the Service Graph Connector for Wiz page, select **Start**.
- b. Configure the connection.
 - a. Select the Configure the Connection task and then select **Click Here**.
 - b. On the Connections page that opens in another browser tab, select **Edit** for the **SG-Wiz** connection that is available by default.
- c. On the form, fill in the fields.

Edit Connection form

Field	Description
Connection Name	Name to identify the connection record. For example, SG-Wiz. Don't modify the name for the default connection alias SG-Wiz.
Connection URL	Base URL to connect to your Wiz application. Note: Based on the region of your Wiz application, enter the connection URL in the following format: <code>https://api.<region>.app.wiz.io</code> Where <region> is the region where the Wiz tenant is located. For example, us1, us2, eu1, or eu2.

Field	Description
Client ID	Client ID of your Wiz application as described in Before you begin .
Client Secret	Client secret of your Wiz application as described in Before you begin .
OAuth Token URL	Token generation URL. This field is automatically set to the following URL: <code>https://auth.app.wiz.io/oauth/token</code>

- d. Select **Edit and Get OAuth Token**.
- e. Return to the guided setup.
- f. Set the Configure the Connection task to complete by selecting the **Mark as complete** check box and then select **Continue**.
- c. Configure the connection properties.
 - a. Select the Add configuration properties task.
 - b. In the Service Graph Connections section, review and modify the property details by selecting a property from the **Property** column in the Service Graph Connection Properties related list.
You can configure the following properties:

Projects

A list of comma-separated project IDs for which the resources are to be pulled.

Exclude Projects

A list of comma-separated project IDs for which the resources are excluded only when the **Projects** property isn't set. In this

case, all the resources except for the specified projects are imported.

Note: If no property is configured, data from all the Wiz projects are fetched.

- c. Select **Update** in the Service Graph Connection Properties section.
 - d. Set the Add connection properties task to complete by selecting the **Mark as complete** check box and then select **Continue**.
- d. Test the Wiz API connection to import data from the Wiz application.
 - a. Select the Test Connection task.
 - b. Test the connection by selecting the **Test Connection** related link.

Testing the connection might take a few moments. The page is refreshed to show the test results.
 - c. When the **Status** field is set to **Success**, select **Update**.

If any of the tests have errors, follow the suggestions for remediation.
 - d. Set the Test Connection task to complete by selecting the **Mark as complete** check box and then select **Continue**.
5. Configure the scheduled jobs to import data from the Wiz application.
 - a. Configure the scheduled job for the complete (full) import of data during the initial execution, and then incremental (delta) import of data on subsequent executions.
 - a. Select the Configure the scheduled jobs task.
 - b. Select the **SG-Wiz-Organization** scheduled job.

- c. On the Scheduled Data Import form, verify the field values for the scheduled job.

For more information, see [Schedule a data import](#).

- d. Select the **Active** check box to activate the SG-Wiz-Organization scheduled job.
 - e. In the **Run** field, select **Periodically** to specify how often the job will run.
 - f. Select **Update**.
 - g. Set the Configure the scheduled jobs task to complete by selecting the **Mark as complete** check box and then select **Continue**.
- b. Configure the Reset Last Run Datetime for SG-Wiz scheduled script to enable full pull for subsequent execution of the scheduled job.

Note: To fetch the complete data using a data source on subsequent executions, you must remove the **Last Run Date Time** field value from a data source. The Reset Last Run Datetime for SG-Wiz scheduled script provided with the connector resets the **Last Run Date Time** field value automatically. Therefore, confirming that the SG-Wiz Organization scheduled job executes all data sources for a full pull.

- a. Select the Configure the scheduled script for full data retrieval task.
- b. Select the **Active** check box to activate the SG-Wiz scheduled script.
- c. In the **Run** field, select **Periodically** to specify how often the script will run.

For more information, see [Automatically run a script of your choosing](#).

- d. Select **Update**.

- e. Set the Configure the scheduled script for full data retrieval task to complete by selecting the **Mark as complete** check box and then select **Continue**.
6. On the Service Graph Connector for Wiz page, select **Complete** to save your changes.
7. In Complete setup dialog box, select **Complete** to complete the setup.
8. In the message box that appears, select **Done**.

Target tables for storing Service Graph Connector for Wiz data

When you complete setting up the connection, you can configure the integration to periodically pull data from a Wiz project. The data is saved in tables that extend from the CMDB CI classes and other non-CMDB classes.

AWS Datacenter [cmdb_ci_aws_datacenter]

The following attributes in the AWS Datacenter [cmdb_ci_aws_datacenter] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Name	name	name
Object ID	object_id	externalId
Region	region	externalId

Relationships created for AWS Datacenter

Parent class	Relationship type	Child class
AWS Datacenter [cmdb_ci_aws_datacenter]	Hosted on::Hosts	Cloud Service Account [cmdb_ci_cloud_service_account]

Parent class	Relationship type	Child class
AWS Datacenter [cmdb_ci_aws_datacenter]	Reference	SG-Wiz Extension Attributes [sn_wiz_integ_extension_attributes]

Azure Datacenter [cmdb_ci_azure_datacenter]

The following attributes in the Azure Datacenter [cmdb_ci_azure_datacenter] table are populated by collected data.

Attribute label	Attribute name	Wiz attribute
Name	name	name
Object ID	object_id	externalId
Region	region	externalId

Relationships created for Azure Datacenter

Parent class	Relationship type	Child class
Azure Datacenter [cmdb_ci_azure_datacenter]	Hosted on::Hosts	Cloud Service Account [cmdb_ci_cloud_service_account]
Azure Datacenter [cmdb_ci_azure_datacenter]	Contains::Contained by	Resource Group [cmdb_ci_resource_group]
Azure Datacenter [cmdb_ci_azure_datacenter]	Reference	SG-Wiz Extension Attributes [sn_wiz_integ_extension_attributes]

Cloud DataBase [cmdb_ci_cloud_database]

The following attributes in the Cloud DataBase [cmdb_ci_cloud_database] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Name	name	name
Object ID	object_id	externalId
Install Status	install_status	None
Type	type	nativeType

Relationships created for Cloud DataBase

Parent class	Relationship type	Child class
Cloud DataBase [cmdb_ci_cloud_data base]	Hosted on::Hosts	Cloud Service Account [cmdb_ci_cloud_servi ce_account]
Cloud DataBase [cmdb_ci_cloud_data base]	Reference	SG-Wiz Extension Attributes [sn_wiz_integ_extensio n_attributes]
Cloud DataBase [cmdb_ci_cloud_data base]	Reference	Key Value [cmdb_key_value]

Cloud DataBase Cluster [cmdb_ci_cloud_db_cluster]

The following attributes in the Cloud DataBase Cluster [cmdb_ci_cloud_db_cluster] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Cluster ID	cluster_id	externalId
Name	name	name
Cluster Type	cluster_type	kind

Attribute label	Attribute name	Wiz attribute
Install Status	install_status	None
Vendor	vendor	None

Relationships created for Cloud DataBase Cluster

Parent class	Relationship type	Child class
Cloud DataBase Cluster [cmdb_ci_cloud_db_cluster]	Hosted on::Hosts	AWS Datacenter [cmdb_ci_aws_datacenter]
Cloud DataBase Cluster [cmdb_ci_cloud_db_cluster]	Reference	Key Value [cmdb_key_value]
Cloud DataBase Cluster [cmdb_ci_cloud_db_cluster]	Reference	SG-Wiz Extension Attributes [sn_wiz_integ_extension_attributes]

Cloud Disk Type [cmdb_ci_disk_type]

The following attributes in the Cloud Disk Type [cmdb_ci_disk_type] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Name	name	properties.volumeType, zone
Object ID	object_id	properties.volumeType, zone

Relationship created for Cloud Disk Type

Parent class	Relationship type	Child class
Cloud Disk Type [cmdb_ci_disk_type]	Hosted on::Hosts	Google Datacenter [cmdb_ci_google_datacenter]

Cloud Function [cmdb_ci_cloud_function]

The following attributes in the Cloud Function [cmdb_ci_cloud_function] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Name	name	name
Object ID	object_id	externalId
CodeSha256	codesha256	awsLambda_codeSha256
Install Status	install_status	None
Language	language	runtime

Relationships created for Cloud Function

Parent class	Relationship type	Child class
Cloud Function [cmdb_ci_cloud_function]	Hosted on::Hosts	Azure Datacenter [cmdb_ci_azure_datacenter]
Cloud Function [cmdb_ci_cloud_function]	Hosted on::Hosts	AWS Datacenter [cmdb_ci_aws_datacenter]
Cloud Function [cmdb_ci_cloud_function]	Hosted on::Hosts	Google Datacenter [cmdb_ci_google_datacenter]

Parent class	Relationship type	Child class
Cloud Function [cmdb_ci_cloud_function]	Reference	SG-Wiz Extension Attributes [sn_wiz_integ_extension_attributes]
Cloud Function [cmdb_ci_cloud_function]	Reference	Key Value [cmdb_key_value]

Cloud Gateway [cmdb_ci_cloud_gateway]

The following attributes in the Cloud Gateway [cmdb_ci_cloud_gateway] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Name	name	name
Object ID	object_id	externalId
Install Status	install_status	None

Relationships created for Cloud Gateway

Parent class	Relationship type	Child class
Cloud Gateway [cmdb_ci_cloud_gateway]	Hosted on::Hosts	Azure Datacenter [cmdb_ci_azure_datacenter]
Cloud Gateway [cmdb_ci_cloud_gateway]	Hosted on::Hosts	AWS Datacenter [cmdb_ci_aws_datacenter]
Cloud Gateway [cmdb_ci_cloud_gateway]	Reference	SG-Wiz Extension Attributes [sn_wiz_integ_extension_attributes]

Parent class	Relationship type	Child class
Cloud Gateway [cmdb_ci_cloud_gateway]	Reference	Key Value [cmdb_key_value]

Cloud Hardware Type [cmdb_ci_cloud_hardware_type]

The following attributes in the Cloud Hardware Type [cmdb_ci_cloud_hardware_type] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Name	name	name
Object ID	object_id	externalId
Provider	provider	cloudPlatform

Relationships created for Cloud Hardware Type

Parent class	Relationship type	Child class
Cloud Hardware Type [cmdb_ci_cloud_hardware_type]	Hosted on::Hosts	Azure Datacenter [cmdb_ci_azure_datacenter]
Cloud Hardware Type [cmdb_ci_cloud_hardware_type]	Hosted on::Hosts	AWS Datacenter [cmdb_ci_aws_datacenter]
Cloud Mgmt Network Interface [cmdb_ci_nic]	Hosted on::Hosts	Google Datacenter [cmdb_ci_google_datacenter]

Cloud Load Balancer [cmdb_ci_cloud_load_balancer]

The following attributes in the Cloud Load Balancer [cmdb_ci_cloud_load_balancer] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Name	name	name
Object ID	object_id	name (for AWS Load Balancer v1) externalId (for Azure and AWS Load Balancer v2)
Install Status	install_status	None

Relationships created for Cloud Load Balancer

Parent class	Relationship type	Child class
Cloud Load Balancer [cmdb_ci_cloud_load_balancer]	Hosted on::Hosts	Azure Datacenter [cmdb_ci_azure_data_center]
Cloud Load Balancer [cmdb_ci_cloud_load_balancer]	Hosted on::Hosts	AWS Datacenter [cmdb_ci_aws_datacenter]
Cloud Load Balancer [cmdb_ci_cloud_load_balancer]	Hosted on::Hosts	Google Datacenter [cmdb_ci_google_datacenter]
Cloud Load Balancer [cmdb_ci_cloud_load_balancer]	Hosted on::Hosts	Cloud Service Account [cmdb_ci_cloud_service_account]
Cloud Load Balancer [cmdb_ci_cloud_load_balancer]	Reference	Key Value [cmdb_key_value]

Parent class	Relationship type	Child class
Cloud Load Balancer [cmdb_ci_cloud_load_balancer]	Reference	SG-Wiz Extension Attributes [sn_wiz_integ_extensio n_attributes]

Cloud Mgmt Network Interface [cmdb_ci_nic]

The following attributes in the Cloud Mgmt Network Interface [cmdb_ci_nic] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
MAC Address	mac_address	macAddress
Name	name	name
Object ID	object_id	externalId
Install Status	install_status	None

Relationships created for Cloud Mgmt Network Interface

Parent class	Relationship type	Child class
Cloud Mgmt Network Interface [cmdb_ci_nic]	Hosted on::Hosts	Azure Datacenter [cmdb_ci_azure_data center]
Cloud Mgmt Network Interface [cmdb_ci_nic]	Hosted on::Hosts	AWS Datacenter [cmdb_ci_aws_datac enter]
Cloud Mgmt Network Interface [cmdb_ci_nic]	Hosted on::Hosts	Google Datacenter [cmdb_ci_google_dat acenter]
Cloud Mgmt Network Interface [cmdb_ci_nic]	Reference	Key Value [cmdb_key_value]

Parent class	Relationship type	Child class
Cloud Mgmt Network Interface [cmdb_ci_nic]	Reference	SG-Wiz Extension Attributes [sn_wiz_integ_extension_attributes]

Cloud Network [cmdb_ci_network]

The following attributes in the Cloud Network [cmdb_ci_network] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Name	name	name
Object ID	object_id	externalId
Cidr	cidr	addressRanges
Install Status	install_status	None

Relationships created for Cloud Network

Parent class	Relationship type	Child class
Cloud Network [cmdb_ci_network]	Hosted on::Hosts	Azure Datacenter [cmdb_ci_azure_datacenter]
Cloud Network [cmdb_ci_network]	Hosted on::Hosts	AWS Datacenter [cmdb_ci_aws_datacenter]
Cloud Network [cmdb_ci_network]	Reference	Key Value [cmdb_key_value]
Cloud Network [cmdb_ci_network]	Reference	SG-Wiz Extension Attributes [sn_wiz_integ_extension_attributes]

Cloud Object Storage [cmdb_ci_cloud_object_storage]

The following attributes in the Cloud Object Storage [cmdb_ci_cloud_object_storage] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Name	name	name
Object ID	object_id	externalId (for Azure and GCP) providerUniqueId (for AWS)
Cloud Provider	cloud_provider	cloudPlatform
Install Status	install_status	None

Relationships created for Cloud Object Storage

Parent class	Relationship type	Child class
Cloud Object Storage [cmdb_ci_cloud_object_storage]	Hosted on::Hosts	Azure Datacenter [cmdb_ci_azure_datacenter]
Cloud Object Storage [cmdb_ci_cloud_object_storage]	Hosted on::Hosts	AWS Datacenter [cmdb_ci_aws_datacenter]
Cloud Object Storage [cmdb_ci_cloud_object_storage]	Hosted on::Hosts	Google Datacenter [cmdb_ci_google_datacenter]
Cloud Object Storage [cmdb_ci_cloud_object_storage]	Reference	SG-Wiz Extension Attributes [sn_wiz_integ_extension_attributes]

Parent class	Relationship type	Child class
Cloud Object Storage [cmdb_ci_cloud_object_storage]	Reference	Key Value [cmdb_key_value]

Cloud Organizations [cmdb_ci_cloud_org]

The following attributes in the Cloud Organizations [cmdb_ci_cloud_org] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Object ID	object_id	ProviderUniqueId(AWS and Azure), externalId (for GCP)
Name	name	name

Relationships created for Cloud Organizations

Parent class	Relationship type	Child class
Cloud Organizations [cmdb_ci_cloud_org]	Contains::Contained by	Cloud Service Account [cmdb_ci_cloud_service_account]
Cloud Organizations [cmdb_ci_cloud_org]	Reference	SG-Wiz Extension Attributes [sn_wiz_integration_attributes]

Cloud Public IP Address [cmdb_ci_cloud_public_ipaddress]

The following attributes in the Cloud Public IP Address [cmdb_ci_cloud_public_ipaddress] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Name	name	name

Attribute label	Attribute name	Wiz attribute
Object ID	object_id	externalId (for Azure and GCP) ProviderUniqueld (for AWS)
Install Status	install_status	None
Public IP Address	public_ip_address	address

Relationships created for Cloud Public IP Address

Parent class	Relationship type	Child class
Cloud Public IP Address [cmdb_ci_cloud_public_ipaddress]	Hosted on::Hosts	Azure Datacenter [cmdb_ci_azure_datacenter]
Cloud Public IP Address [cmdb_ci_cloud_public_ipaddress]	Hosted on::Hosts	Google Datacenter [cmdb_ci_google_datacenter]
Cloud Public IP Address [cmdb_ci_cloud_public_ipaddress]	Hosted on::Hosts	AWS Datacenter [cmdb_ci_aws_datacenter]
Cloud Public IP Address [cmdb_ci_cloud_public_ipaddress]	Reference	SG-Wiz Extension Attributes [sn_wiz_integ_extension_attributes]
Cloud Public IP Address [cmdb_ci_cloud_public_ipaddress]	Reference	Key Value [cmdb_key_value]

Cloud Service Account [cmdb_ci_cloud_service_account]

The following attributes in the Cloud Service Account [cmdb_ci_cloud_service_account] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Account Id	account_id	externalId
Name	name	name
Object ID	object_id	externalId
Datacenter Type	datacenter_type	cloudPlatform
Is management account	is_master_account	ProviderUniqueID (AWS only)
Organization Id	organization_id	ProviderUniqueID (AWS only)
Parent account	parent_account	ProviderUniqueID (AWS only)

Relationships created for Cloud Service Account

Parent class	Relationship type	Child class
Cloud Service Account [cmdb_ci_cloud_service_account]	Reference	Cloud Service Account [cmdb_ci_cloud_service_account]
Cloud Service Account [cmdb_ci_cloud_service_account]	Reference	Key Value [cmdb_key_value]
Cloud Service Account	Reference	SG-Wiz Extension Attributes [sn_wiz_integ_extension_attributes]

Parent class	Relationship type	Child class
[cmdb_ci_cloud_service_account]		

Cloud Storage Account [cmdb_ci_cloud_storage_account]

The following attributes in the Cloud Storage Account [cmdb_ci_cloud_storage_account] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Name	name	name
Object ID	object_id	externalId
Install Status	install_status	None

Relationships created for Cloud Storage Account

Parent class	Relationship type	Child class
Cloud Storage Account [cmdb_ci_cloud_storage_account]	Hosted on::Hosts	Azure Datacenter [cmdb_ci_azure_datacenter]
Cloud Storage Account [cmdb_ci_cloud_storage_account]	Reference	Key Value [cmdb_key_value]
Cloud Storage Account [cmdb_ci_cloud_storage_account]	Reference	SG-Wiz Extension Attributes [sn_wiz_integ_extension_attributes]

Compute Security Group [cmdb_ci_compute_security_group]

The following attributes in the Compute Security Group [cmdb_ci_compute_security_group] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Name	name	name
Object ID	object_id	externalId
Install Status	install_status	None
Region	region	region

Relationships created for Compute Security Group

Parent class	Relationship type	Child class
Compute Security Group [cmdb_ci_compute_security_group]	Hosted on::Hosts	Cloud Service Account [cmdb_ci_cloud_service_account]
Compute Security Group [cmdb_ci_compute_security_group]	Hosted on::Hosts	OCI Datacenter [cmdb_ci_oci_datacenter]
Compute Security Group [cmdb_ci_compute_security_group]	Hosted on::Hosts	Azure Datacenter [cmdb_ci_azure_datacenter]
Compute Security Group [cmdb_ci_compute_security_group]	Hosted on::Hosts	AWS Datacenter [cmdb_ci_aws_datacenter]
Compute Security Group [cmdb_ci_compute_security_group]	Reference	SG-Wiz Extension Attributes [sn_wiz_integration_attributes]
Compute Security Group	Reference	Key Value [cmdb_key_value]

Parent class	Relationship type	Child class
[cmdb_ci_compute_security_group]		

Docker Container [cmdb_ci_docker_container]

The following attributes in the Docker Container [cmdb_ci_docker_container] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Container id	container_id	externalId (for Kubernetes, ACA, and ACI) providerUniqueId (for ECS)
Install Status	install_status	None
Name	name	name

Relationships created for Docker Container

Parent class	Relationship type	Child class
Docker Container [cmdb_ci_docker_container]	Hosts:: Hosted on	AWS Datacenter [cmdb_ci_aws_datacenter] (for ECS)
Docker Container [cmdb_ci_docker_container]	Hosts:: Hosted on	Azure Datacenter [cmdb_ci_azure_datacenter] (for ACA, ACI)
Docker Container [cmdb_ci_docker_container]	Reference	SG-Wiz Extension Attributes [sn_wiz_integ_extension_attributes]

DynamoDB Table [cmdb_ci_dynamodb_table]

The following attributes in the DynamoDB Table [cmdb_ci_dynamodb_table] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Name	name	name
Object ID	object_id	externalId
Install Status	install_status	None

Relationships created for DynamoDB Table

Parent class	Relationship type	Child class
DynamoDB Table [cmdb_ci_dynamodb_table]	Hosted on::Hosts	AWS Datacenter [cmdb_ci_aws_datacenter]
DynamoDB Table [cmdb_ci_dynamodb_table]	Reference	SG-Wiz Extension Attributes [sn_wiz_integ_extension_attributes]
DynamoDB Table [cmdb_ci_dynamodb_table]	Reference	Key Value [cmdb_key_value]

Google Datacenter [cmdb_ci_google_datacenter]

The following attributes in the Google Datacenter [cmdb_ci_google_datacenter] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Name	name	name
Object ID	object_id	externalId
Region	region	externalId

Relationships created for Google Datacenter

Parent class	Relationship type	Child class
Google Datacenter [cmdb_ci_google_datacenter]	Hosted on::Hosts	Cloud Service Account [cmdb_ci_cloud_service_account]
Google Datacenter [cmdb_ci_google_datacenter]	Reference	SG-Wiz Extension Attributes [sn_wiz_integ_extension_attributes]

Google Organization Folder [cmdb_ci_gcp_folder]

The following attributes in the Google Organization Folder [cmdb_ci_gcp_folder] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Object ID	object_id	externalId
Name	name	name

Relationship created for Google Organization Folder

Parent class	Relationship type	Child class
Google Organization Folder [cmdb_ci_gcp_folder]	Reference	SG-Wiz Extension Attributes [sn_wiz_integ_extension_attributes]

Google Organization Project [cmdb_ci_gcp_project]

The following attributes in the Google Organization Project [cmdb_ci_gcp_project] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Name	name	name

Attribute label	Attribute name	Wiz attribute
Object ID	object_id	externalId
Project Id	project_id	providerUniqueld

Relationship created for Google Organization Project

Parent class	Relationship type	Child class
Google Organization Project [cmdb_ci_gcp_project]	Reference	SG-Wiz Extension Attributes [sn_wiz_integ_extension_attributes]

Hardware Type [cmdb_ci_compute_template]

The following attributes in the Hardware Type [cmdb_ci_compute_template] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Name	name	instanceType
Object ID	object_id	instanceType

Relationships created for Hardware Type

Parent class	Relationship type	Child class
Hardware Type [cmdb_ci_compute_template]	Hosted on::Hosts	AWS Datacenter [cmdb_ci_aws_datacenter]
Hardware Type [cmdb_ci_compute_template]	Hosted on::Hosts	Azure Datacenter [cmdb_ci_azure_datacenter]
Hardware Type [cmdb_ci_compute_template]	Hosted on::Hosts	Google Datacenter [cmdb_ci_google_datacenter]

Image [cmdb_ci_os_template]

The following attributes in the Image [cmdb_ci_os_template] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Name	name	name
Object ID	object_id	externalId
Install Status	install_status	None

Relationships created for Image

Parent class	Relationship type	Child class
Image [cmdb_ci_os_template]	Hosted on::Hosts	Cloud Service Account [cmdb_ci_cloud_service_account]
Image [cmdb_ci_os_template]	Hosted on::Hosts	AWS Datacenter [cmdb_ci_aws_datacenter]
Image [cmdb_ci_os_template]	Hosted on::Hosts	Azure Datacenter [cmdb_ci_azure_datacenter]
Image [cmdb_ci_os_template]	Reference	SG-Wiz Extension Attributes [sn_wiz_integ_extension_attributes]
Image [cmdb_ci_os_template]	Reference	Key Value [cmdb_key_value]

Note: Data with no subscription IDs for images aren't imported. Also, if the subscription ID for an image is available, but the subscription-specific details are not available in Wiz, the data isn't imported by the connector.

Instance Scale Set [cmdb_ci_instance_scale_set]

The following attributes in the Instance Scale Set [cmdb_ci_instance_scale_set] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Name	name	name
Install Status	install_status	None
Object ID	object_id	externalId

Relationships created for Instance Scale Set

Parent class	Relationship type	Child class
Instance Scale Set [cmdb_ci_instance_scale_set]	Hosted on::Hosts	Azure Datacenter [cmdb_ci_azure_datacenter]
Instance Scale Set [cmdb_ci_instance_scale_set]	Hosted on::Hosts	AWS Datacenter [cmdb_ci_aws_datacenter]
Instance Scale Set [cmdb_ci_instance_scale_set]	Reference	SG-Wiz Extension Attributes [sn_wiz_integ_extension_attributes]
Instance Scale Set [cmdb_ci_instance_scale_set]	Reference	Key Value [cmdb_key_value]

Internet Gateway [cmdb_ci_internet_gateway]

The following attributes in the Internet Gateway [cmdb_ci_internet_gateway] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Name	name	name
Object ID	object_id	externalId
Install Status	install_status	None

Relationships created for Internet Gateway

Parent class	Relationship type	Child class
Internet Gateway [cmdb_ci_internet_gateway]	Hosted on::Hosts	AWS Datacenter [cmdb_ci_aws_datacenter]
Internet Gateway [cmdb_ci_internet_gateway]	Reference	SG-Wiz Extension Attributes [sn_wiz_integ_extension_attributes]
Internet Gateway [cmdb_ci_internet_gateway]	Reference	Key Value [cmdb_key_value]

Key Value [cmdb_key_value]

The following attributes in the Key Value [cmdb_key_value] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Key	key	tags
Value	value	tags

Note: The cloud resource tags (key-value pairs) from the API response are populated in the Key Value [cmdb_key_value] table.

Kubernetes Cluster [cmdb_ci_kubernetes_cluster]

The following attributes in the Kubernetes Cluster [cmdb_ci_kubernetes_cluster] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Cluster Resource ID	cluster_resource_id	providerUniqueId
Kubernetes UID	k8s_uid	externalId
Name	name	name
Install Status	install_status	None

Relationships created for Kubernetes Cluster

Parent class	Relationship type	Child class
Kubernetes Cluster [cmdb_ci_kubernetes_cluster]	Contains::Contained by	Kubernetes Service [cmdb_ci_kubernetes_service]
Kubernetes Cluster [cmdb_ci_kubernetes_cluster]	Contains::Contained by	Kubernetes Namespace [cmdb_ci_kubernetes_namespace]
Kubernetes Cluster [cmdb_ci_kubernetes_cluster]	Contains::Contained by	Kubernetes Pod [cmdb_ci_kubernetes_pod]
Kubernetes Cluster [cmdb_ci_kubernetes_cluster]	Contains::Contained by	Docker Container [cmdb_ci_docker_container]
Kubernetes Cluster [cmdb_ci_kubernetes_cluster]	Hosted on::Hosts	Azure Datacenter [cmdb_ci_azure_data_center]

Parent class	Relationship type	Child class
Kubernetes Cluster [cmdb_ci_kubernetes_cluster]	Hosted on::Hosts	AWS Datacenter [cmdb_ci_aws_datacenter]
Kubernetes Cluster [cmdb_ci_kubernetes_cluster]	Hosted on::Hosts	Google Datacenter [cmdb_ci_google_datacenter]
Kubernetes Cluster [cmdb_ci_kubernetes_cluster]	Cluster of::Cluster	Kubernetes Node [cmdb_ci_kubernetes_node]
Kubernetes Cluster [cmdb_ci_kubernetes_cluster]	Reference	Key Value [cmdb_key_value]
Kubernetes Cluster [cmdb_ci_kubernetes_cluster]	Reference	SG-Wiz Extension Attributes [sn_wiz_integ_extension_attributes]

Kubernetes Deployment [cmdb_ci_kubernetes_deployment]

The following attributes in the Kubernetes Deployment [cmdb_ci_kubernetes_deployment] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Kubernetes UID	k8s_uid	uid
Name	name	name
Namespace	namespace	namespace
Available Replicas	available_replicas	status_availableReplicas
Desired Replicas	desired_replicas	spec_replicas

Attribute label	Attribute name	Wiz attribute
Install Status	install_status	None
Total Replicas	total_replicas	status_replicas
Updated Replicas	updated_replicas	status_updatedReplicas
Kubernetes Cluster	cluster	Kubernetes_clusterExternalID
SelfLink	self_link	api_version namespace name
Unavailable Replicas	unavailable_replicas	status_unavailableReplicas

Relationships created for Kubernetes Deployment

Parent class	Relationship type	Child class
Kubernetes Deployment [cmdb_ci_kubernetes_deployment]	Hosted on::Hosts	Kubernetes Cluster [cmdb_ci_kubernetes_cluster]
Kubernetes Deployment [cmdb_ci_kubernetes_deployment]	Reference	Kubernetes Cluster [cmdb_ci_kubernetes_cluster]
Kubernetes Deployment [cmdb_ci_kubernetes_deployment]	Reference	Key Value [cmdb_key_value]
Kubernetes Deployment	Reference	SG-Wiz Extension Attributes

Parent class	Relationship type	Child class
[cmdb_ci_kubernetes_deployment]		[sn_wiz_integ_extension_attributes]

Kubernetes Namespace [cmdb_ci_kubernetes_namespace]

The following attributes in the Kubernetes Namespace [cmdb_ci_kubernetes_namespace] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Install Status	install_status	None
Namespace	namespace	name
Kubernetes Cluster	cluster	Kubernetes_clusterExternalID
Name	name	name

Relationships created for Kubernetes Namespace

Parent class	Relationship type	Child class
Kubernetes Namespace [cmdb_ci_kubernetes_namespace]	Reference	Kubernetes Cluster [cmdb_ci_kubernetes_cluster]
Kubernetes Namespace [cmdb_ci_kubernetes_namespace]	Reference	Key Value [cmdb_key_value]
Kubernetes Namespace [cmdb_ci_kubernetes_namespace]	Reference	SG-Wiz Extension Attributes [sn_wiz_integ_extension_attributes]

Kubernetes Node [cmdb_ci_kubernetes_node]

The following attributes in the Kubernetes Node [cmdb_ci_kubernetes_node] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
IP Address	ip_address	status_address
Kubernetes UID	k8s_uid	uid
Name	name	name
Install Status	install_status	None
Kubernetes Cluster	cluster	Kubernetes_clusterExternalID

Relationships created for Kubernetes Node

Parent class	Relationship type	Child class
Kubernetes Node [cmdb_ci_kubernetes_node]	Reference	Kubernetes Cluster [cmdb_ci_kubernetes_cluster]
Kubernetes Node [cmdb_ci_kubernetes_node]	Reference	Key Value [cmdb_key_value]
Kubernetes Node [cmdb_ci_kubernetes_node]	Reference	SG-Wiz Extension Attributes [sn_wiz_integ_extension_attributes]

Kubernetes Pod [cmdb_ci_kubernetes_pod]

The following attributes in the Kubernetes Pod [cmdb_ci_kubernetes_pod] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Kubernetes UID	k8s_uid	uid
Namespace	namespace	namespace
Host IP	host_ip	status_hostIP
Install Status	install_status	None
IP Address	ip_address	status_podIPs
Kubernetes Cluster	cluster	Kubernetes_clusterExternalID
Name	name	name
Resource version	resource_version	resourceVersion

Relationships created for Kubernetes Pod

Parent class	Relationship type	Child class
Kubernetes Pod [cmdb_ci_kubernetes_pod]	Reference	Kubernetes Cluster [cmdb_ci_kubernetes_cluster]
Kubernetes Pod [cmdb_ci_kubernetes_pod]	Reference	Key Value [cmdb_key_value]
Kubernetes Pod [cmdb_ci_kubernetes_pod]	Reference	SG-Wiz Extension Attributes [sn_wiz_integ_extension_attributes]

Kubernetes ReplicaSet [cmdb_ci_kubernetes_replicaset]

The following attributes in the Kubernetes ReplicaSet [cmdb_ci_kubernetes_replicaset] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Kubernetes UID	k8s_uid	uid
Name	name	name
Namespace	namespace	namespace
Available Replicas	available_replicas	status_availableReplicas
Desired Replicas	desired_replicas	spec_replicas
Install Status	install_status	None
SelfLink	self_link	api_version namespace name
Total Replicas	total_replicas	status_replicas
Kubernetes Cluster	cluster	Kubernetes_clusterExternalID

Relationships created for Kubernetes ReplicaSet

Parent class	Relationship type	Child class
Kubernetes ReplicaSet [cmdb_ci_kubernetes_replicaset]	Hosted on::Hosts	Kubernetes Cluster [cmdb_ci_kubernetes_cluster]
Kubernetes ReplicaSet [cmdb_ci_kubernetes_replicaset]	Reference	Kubernetes Cluster [cmdb_ci_kubernetes_cluster]

Parent class	Relationship type	Child class
Kubernetes ReplicaSet [cmdb_ci_kubernetes_replicaset]	Reference	Key Value [cmdb_key_value]
Kubernetes ReplicaSet [cmdb_ci_kubernetes_replicaset]	Reference	SG-Wiz Extension Attributes [sn_wiz_integ_extensio n_attributes]

Kubernetes Service [cmdb_ci_kubernetes_service]

The following attributes in the Kubernetes Service [cmdb_ci_kubernetes_service] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Kubernetes UID	k8s_uid	uid
Name	name	name
Install Status	install_status	None
Kubernetes Cluster	cluster	Kubernetes_clusterExt ernalID
Namespace	namespace	namespace
IP Address	ip_address	spec_clusterIP
Selector	selector	spec_selector
Service Type	service_type	spec_type

Relationships created for Kubernetes Service

Parent class	Relationship type	Child class
Kubernetes Service [cmdb_ci_kubernetes_service]	Reference	Kubernetes Cluster [cmdb_ci_kubernetes_ cluster]

Parent class	Relationship type	Child class
Kubernetes Service [cmdb_ci_kubernetes_service]	Reference	Key Value [cmdb_key_value]
Kubernetes Service [cmdb_ci_kubernetes_service]	Reference	SG-Wiz Extension Attributes [sn_wiz_integ_extension_attributes]

Linux Server [cmdb_ci_linux_server]

The following attributes in the Linux Server [cmdb_ci_linux_server] table are populated by collected data.

Attribute label	Attribute name	Wiz attribute
Name	name	name
Object ID	object_id	externalId
Serial number	serial_number	providerUniqueId
CPU count	cpu_count	vCPUs
Install Status	install_status	None
Is Virtual	None	None
Operating System	os	operatingSystem

Relationship created for Linux Server

Parent class	Relationship type	Child class
Linux Server [cmdb_ci_linux_server]	Virtualized by::Virtualizes	Virtual Machine Instance [cmdb_ci_vm_instance]

Logical Datacenter [cmdb_ci_logical_datacenter]

The following attributes in the Logical Datacenter [cmdb_ci_logical_datacenter] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Name	name	name
Object ID	object_id	externalId
Region	region	externalId

Relationships created for Logical Datacenter

Parent class	Relationship type	Child class
Logical Datacenter [cmdb_ci_logical_datacenter]	Hosted on::Hosts	Cloud Service Account [cmdb_ci_cloud_service_account]
Logical Datacenter [cmdb_ci_logical_datacenter]	Reference	SG-Wiz Extension Attributes [sn_wiz_integ_extension_attributes]

OCI Datacenter [cmdb_ci_oci_datacenter]

The following attributes in the OCI Datacenter [cmdb_ci_oci_datacenter] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Name	name	name
Object ID	object_id	externalId
Region	region	externalId

Relationships created for OCI Datacenter

Parent class	Relationship type	Child class
OCI Datacenter [cmdb_ci_oci_datacenter]	Hosted on::Hosts	Cloud Service Account [cmdb_ci_cloud_service_account]
OCI Datacenter [cmdb_ci_oci_datacenter]	Reference	SG-Wiz Extension Attributes [sn_wiz_integ_extension_attributes]

Resource Group [cmdb_ci_resource_group]

The following attributes in the Resource Group [cmdb_ci_resource_group] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Name	name	name
Object ID	object_id	externalId
Install Status	install_status	None

Relationships created for Resource Group

Parent class	Relationship type	Child class
Resource Group [cmdb_ci_resource_group]	Contains::Contained by	Cloud Load Balancer [cmdb_ci_cloud_load_balancer]
Resource Group [cmdb_ci_resource_group]	Contains::Contained by	Storage Volume [cmdb_ci_storage_volume]
Resource Group [cmdb_ci_resource_group]	Reference	SG-Wiz Extension Attributes

Parent class	Relationship type	Child class
		[sn_wiz_integ_extensio n_attributes]
Resource Group [cmdb_ci_resource_gr oup]	Reference	Key Value [cmdb_key_value]

Serial Number [cmdb_serial_number]

The following attributes in the Serial Number [cmdb_serial_number] table are populated by collected data:

Attribute label	Attribute name	Wiz
Serial Number	providerUniqueID	providerUniqueid
Serial Number Type	serial_number_type	None
Valid	serial_number_valid	providerUniqueid

Note: The Serial Number [cmdb_serial_number] table is populated for Azure only.

Relationships created for Serial Number

Parent class	Relationship type	Child class
Serial Number [cmdb_serial_number]	Reference	Server [cmdb_ci_server]
Serial Number [cmdb_serial_number]	Reference	Windows Server [cmdb_ci_win_server]
Serial Number [cmdb_serial_number]	Reference	Linux Server [cmdb_ci_linux_server]

Server [cmdb_ci_server]

The following attributes in the Server [cmdb_ci_server] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Name	name	name
Object ID	object_id	externalId
Serial number	serial_number	providerUniqueId
CPU count	cpu_count	vCPUs
Install Status	install_status	None
Is Virtual	virtual	None
Operating System	os	operatingSystem
Sys ID	sys_id	Not applicable

Relationship created for Server

Parent class	Relationship type	Child class
Server [cmdb_ci_server]	Virtualized by::Virtualizes	Virtual Machine Instance [cmdb_ci_vm_instance]

SG-Wiz Extension Attributes [sn_wiz_integ_extension_attributes]

The following attributes in the SG-Wiz Extension Attributes [sn_wiz_integ_extension_attributes] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Project ID	project_id	productIDs
CMDB Class	u_cmdb_class	None

Note: Cloud resource project IDs are populated in the SG-Wiz Extension Attributes [sn_wiz_integ_extension_attributes] table.

Storage Volume [cmdb_ci_storage_volume]

The following attributes in the Storage Volume [cmdb_ci_storage_volume] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Object ID	object_id	externalId
Volume ID	volume_id	externalId
Install Status	install_status	None
Name	name	name
Size	size	sizeGb
Size bytes	size_bytes	sizeGb
Storage type	storage_type	volumeType

Relationships created for Storage Volume

Parent class	Relationship type	Child class
Storage Volume [cmdb_ci_storage_volume]	Hosted on::Hosts	Azure Datacenter [cmdb_ci_azure_datacenter]
Storage Volume [cmdb_ci_storage_volume]	Hosted on::Hosts	AWS Datacenter [cmdb_ci_aws_datacenter]
Storage Volume [cmdb_ci_storage_volume]	Hosted on::Hosts	Google Datacenter [cmdb_ci_google_datacenter]
Storage Volume [cmdb_ci_storage_volume]	Reference	SG-Wiz Extension Attributes [sn_wiz_integ_extension_attributes]

Parent class	Relationship type	Child class
Storage Volume [cmdb_ci_storage_volume]	Reference	Key Value [cmdb_key_value]

Storage Volume Snapshot [cmdb_ci_storage_vol_snapshot]

The following attributes in the Storage Volume Snapshot [cmdb_ci_storage_vol_snapshot] table is populated by collected data:

Attribute label	Attribute name	Wiz attribute
Object ID	object_id	externalId
Name	name	name
Install Status	install_status	None

Relationships created for Storage Volume Snapshot

Parent class	Relationship type	Child class
Storage Volume Snapshot [cmdb_ci_storage_vol_snapshot]	Hosted on::Hosts	Azure Datacenter [cmdb_ci_azure_datacenter]
Storage Volume Snapshot [cmdb_ci_storage_vol_snapshot]	Hosted on::Hosts	AWS Datacenter [cmdb_ci_aws_datacenter]
Storage Volume Snapshot [cmdb_ci_storage_vol_snapshot]	Hosted on::Hosts	Cloud Service Account [cmdb_ci_cloud_service_account]
Storage Volume Snapshot [cmdb_ci_storage_vol_snapshot]	Reference	Key Value [cmdb_key_value]

Parent class	Relationship type	Child class
Storage Volume Snapshot [cmdb_ci_storage_vol_snapshot]	Reference	SG-Wiz Extension Attributes [sn_wiz_integ_extension_attributes]

Virtual Machine Instance [cmdb_ci_vm_instance]

The following attributes in the Virtual Machine Instance [cmdb_ci_vm_instance] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Name	name	name
Object ID	object_id	externalId
CPUs	cpus	vCPUs
Disks	disks	totalDisks
Install Status	install_status	None
Memory (MB)	memory	memoryGB
VM Instance ID	vm_inst_id	externalId providerUniqueId (for Azure)

Relationships created for Virtual Machine Instance

Parent class	Relationship type	Child class
Virtual Machine Instance [cmdb_ci_vm_instance]	Hosted on::Hosts	AWS Datacenter [cmdb_ci_aws_datacenter]

Parent class	Relationship type	Child class
Virtual Machine Instance [cmdb_ci_vm_instance]	Hosted on::Hosts	Azure Datacenter [cmdb_ci_azure_datacenter]
Virtual Machine Instance [cmdb_ci_vm_instance]	Hosted on::Hosts	Google Datacenter [cmdb_ci_google_datacenter]
Virtual Machine Instance [cmdb_ci_vm_instance]	Hosted on::Hosts	OCI Datacenter [cmdb_ci_oci_datacenter]
Virtual Machine Instance [cmdb_ci_vm_instance]	Hosted on::Hosts	Logical Datacenter [cmdb_ci_logical_datacenter]
Virtual Machine Instance [cmdb_ci_vm_instance]	Hosted on::Hosts	VMware vCenter Datacenter [cmdb_ci_vcenter_datacenter]
Virtual Machine Instance [cmdb_ci_vm_instance]	Managed by::Manages	Instance Scale Set [cmdb_ci_instance_scale_set]
Virtual Machine Instance [cmdb_ci_vm_instance]	Provisioned From::Provisioned	Hardware Type [cmdb_ci_compute_template]
Virtual Machine Instance [cmdb_ci_vm_instance]	Provisioned From::Provisioned	Cloud Hardware Type [cmdb_ci_cloud_hardware_type]

Parent class	Relationship type	Child class
Windows Server [cmdb_ci_win_server]	Virtualized by::Virtualizes	Virtual Machine Instance [cmdb_ci_vm_instanc e]
Linux Server [cmdb_ci_linux_server]	Virtualized by::Virtualizes	Virtual Machine Instance [cmdb_ci_vm_instanc e]
Server [cmdb_ci_server]	Virtualized by::Virtualizes	Virtual Machine Instance [cmdb_ci_vm_instanc e]
Virtual Machine Instance [cmdb_ci_vm_instanc e]	Reference	SG-Wiz Extension Attributes [sn_wiz_integ_extensio n_attributes]
Virtual Machine Instance [cmdb_ci_vm_instanc e]	Reference	Key Value [cmdb_key_value]

VMware vCenter Datacenter [cmdb_ci_vcenter_datacenter]

The following attributes in the VMware vCenter Datacenter [cmdb_ci_vcenter_datacenter] table are populated by collected data:

Attribute label	Attribute name	Wiz attribute
Name	name	externalId
Object ID	object_id	externalId
Region	region	externalId

Relationship created for VMware vCenter Datacenter

Parent class	Relationship type	Child class
VMware vCenter Datacenter [cmdb_ci_vcenter_datacenter]	Hosted on::Hosts	Cloud Service Account [cmdb_ci_cloud_service_account]

Windows Server [cmdb_ci_win_server]

The following attributes in the Windows Server [cmdb_ci_win_server] table are populated by collected data.

Attribute label	Attribute name	Wiz attribute
Name	name	name
Object ID	object_id	externalId
Serial number	providerUniqueId	providerUniqueId
CPU count	cpu_count	vCPUs
Install Status	install_status	None
Is Virtual	None	None
Operating System	os	operatingSystem

Relationship created for Windows Server

Parent class	Relationship type	Child class
Windows Server [cmdb_ci_win_server]	Virtualized by::Virtualizes	Virtual Machine Instance [cmdb_ci_vm_instance]

Service Graph Connector for Wiz properties

Service Graph Connector for Wiz properties control the behavior of the connector.

Connection properties

These connection properties are available for Service Graph Connector for Wiz.

Note: To open the Service Graph Connection Properties [sn_cmdb_int_util_service_graph_connection_property] table for the connector, navigate to **All > Service Graph Connectors > Wiz > Connections** and select the connection name. The connection properties are displayed in the Service Graph Connection Properties related list.

Connection properties for Service Graph Connector for Wiz

Property	Description
Projects	Enter a list of comma-separated Project IDs for which the resource data should be collected. For multiple entries, separate the IDs with commas.
Exclude Projects	Enter a list of comma-separated Project IDs for which the resources are excluded only when the Projects property isn't set. In this case, all the resources except for the specified projects are imported. For multiple entries, separate the names with commas.
Server Bypass	Set the value to <code>true</code> to link VM data to existing Server records instead of creating new records. If the value is set to <code>false</code> , new Server and VM records are created.

Property	Description
Fetch Scaleset VMs	Set the value to <code>true</code> to import Scale Set VM records. If the value is set to <code>false</code> , Scale Set VMs aren't imported.

System properties

These system properties are available for Service Graph Connector for Wiz.

Note: To open the System Properties [sys_properties] table, enter `sys_properties.list` in the navigation filter.

System properties for Service Graph Connector for Wiz

Property	Description
sn_wiz_integ.list_resources_action.page_size	Enter the page size used in REST requests to fetch Wiz entities. - Type: string - Default value: 100 - Location: System Property [sys_properties] table

Supported Wiz types

The Wiz types and corresponding native types are imported as CMDB data and saved in tables that extend from the Configuration item [cmdb_ci] table.

For information on Wiz types and Wiz native types, see [Security Graph Object Normalization](#) on the Wiz documentation site (requires Wiz login).

Wiz types	Wiz native types	CMDB CI classes
Cloud Organization	AWS Organization GCP Organization	Cloud Organizations
	GCP Folder	Google Organization Folder
Subscription	AWS Account	Cloud Service Account
	Azure Subscription	
	GCP Project	Cloud Service Account Google Organization Project
	OCI Compartment	VMware vCenter Datacenter
	Alibaba Account	
	vSphere Datacenter	
Region	AWS Region	AWS Datacenter
	Azure Location	Azure Datacenter

Wiz types	Wiz native types	CMDB CI classes
	GCP Region	Google Datacenter
	OCI Region	OCI Datacenter
	Alibaba Region	Logical Datacenter
Resource Group	Azure Resource Group	Resource Group
Compute Instance Group	AWS Auto Scaling Group	Instance Scale Set
	Azure Compute Virtual Machine Scale Set	
Network Interface	AWS Network Interface	Cloud Mgmt Network Interface
	Azure Network Interface	
	GCP Compute Network Interface	
Virtual Network	AWS VPC	Cloud Network
	Azure Virtual Network	
Firewall	AWS EC2 Security Group	Compute Security Group

Wiz types	Wiz native types	CMDB CI classes
	Azure Network Security Group	
	GCP Firewall	
	OCI Network Security Group	
	OCI Security List	
Volume	AWS EC2 Volume (EBS)	Storage Volume
	AWS Lightsail Disk	
	Azure Disk	
	GCP Compute Disk	Storage Volume, Cloud Disk Type
Virtual Machine	AWS EC2 Instance	Virtual Machine Instance, Server, Hardware Type
	AWS Lightsail Instance	
	Azure Scale Set Virtual Machine	
	Azure Compute Virtual Machine	
	GCP Compute Instance	

Wiz types	Wiz native types	CMDB CI classes
Snapshot	OCI Compute Instance	
	Alibaba ECS Instance	
	vSphere Virtual Machine	
	AWS EBS Unencrypted Snapshot	Storage Volume Snapshot
	AWS DB Cluster Snapshot	
	AWS DB Instance Snapshot	
	AWS DocumentDB Elastic Cluster Snapshot	
	AWS EBS Encrypted Snapshot	

Wiz types	Wiz native types	CMDB CI classes
	AWS Elasticache Snapshot	
	AWS MemoryDB Snapshot	
	AWS DynamoDB Backup	
	AWS Neptune Analytics Graph Snapshot	
	AWS Redshift Cluster Snapshot	
	Azure Compute Public Snapshot	
	Azure SQL LTR Backup	
	GCP Compute Snapshot	

Wiz types	Wiz native types	CMDB CI classes
	GCP AlloyDB Backup	
	GCP Cloud SQL Backup	
	GCP Cloud SQL Backup Run	
Gateway	AWS Egress Only Internet Gateway	Internet Gateway
	AWS VPN Gateway	
Virtual Machine Image	AWS Machine Image (AMI)	Image
	Azure Compute Virtual Machine Image	
	Azure Compute Gallery VM image version	
	GCP Compute Image	
Load Balancer	AWS ELB v1	Cloud Load Balancer

Wiz types	Wiz native types	CMDB CI classes
	AWS ELB V2 Application Load Balancer	
	AWS ELB V2 Gateway Load Balancer	
	AWS ELB V2 Network Load Balancer	
	AWS ELB V2	
	Azure Application Gateway	
	Azure Load Balancer	
	Azure Traffic Manager	
	GCP Compute Backend Service	
	GCP Compute Region Backend Service	
Bucket	AWS S3 Bucket	Cloud Object Storage
	Azure Blob Storage Container	
	GCP Bucket	

Wiz types	Wiz native types	CMDB CI classes
Serverless	AWS Lambda Function	Cloud Function
	Azure Function	
	GCP Cloud Function	
Database	AWS DynamoDB Table	DynamoDB Table
	AWS ElastiCache for Memcached Cluster	Cloud DataBase Cluster
	AWS ElastiCache Redis OSS Cluster	
	AWS ElastiCache Valkey Cluster	
	AWS Elastic DocumentDB Cluster	
	AWS RDS Aurora MySQL Cluster	
	AWS DocumentDB Cluster	
	AWS MemoryDB Cluster	

Wiz types	Wiz native types	CMDB CI classes
	AWS RDS MSSQL Server Cluster	
	AWS RDS MariaDB Cluster	
	AWS RDS MySQL Cluster	
	AWS Neptune Cluster	
	AWS RDS Oracle Cluster	
	AWS RDS PostgreSQL Cluster	
	AWS RDS Aurora PostgreSQL Cluster	
	Azure Cosmos DB SQL Database	Cloud DataBase
	Azure Cosmos DB Cassandra Keyspace	
	Azure MariaDB Database	
	Azure Cosmos DB MongoDB Collection	
	Azure Cosmos DB for PostgreSQL Node	

Wiz types	Wiz native types	CMDB CI classes
	Azure Database for MySQL Database	
	Azure Database for MySQL Flexible Database	
	Azure Database for PostgreSQL Database	
	Azure Database for PostgreSQL Flexible Database	
	Azure Redis Database	
	Azure Redis Enterprise Database	
	Azure Synapse Dedicated SQL Pool	
	Azure Databricks Schema	
	Azure SQL Database	
	Azure SQL Managed Instance Database	
	Azure Data Explorer Kusto Database Instance	

Wiz types	Wiz native types	CMDB CI classes
Bucket	AWS S3 Bucket	Cloud Object Storage
	Azure Blob Storage Container	
	GCP Bucket	
Serverless	AWS Lambda Function	Cloud Function
	Azure Function	
	GCP Cloud Function	
Network Address	AWS Elastic IP Address	Cloud Public IP Address
	Azure CDN Endpoint	
	Azure Public IP Addresses	
	GCP Compute Address	
	GCP Endpoint	
Storage Account	Azure Storage Account	Cloud Storage Account
API Gateway	AWS API Gateway	Cloud Gateway
	AWS API Gateway V2	

Wiz types	Wiz native types	CMDB CI classes
	Azure API Management	
Kubernetes Cluster	AWS Elastic Kubernetes Service (EKS) Cluster	Kubernetes Cluster
	Azure Kubernetes Service (AKS) Cluster	
	GCP Kubernetes Engine (GKE) Cluster	
	Kubernetes Cluster	
Namespace	Kubernetes Namespace	Kubernetes Namespace
Kubernetes Node	Kubernetes Node	Kubernetes Node
Deployment	Kubernetes Deployment	Kubernetes Deployment
Kubernetes Service	Kubernetes Service	Kubernetes Service
Pod	Kubernetes Pod	Kubernetes Pod
Replica Set	Kubernetes Replica Set	Kubernetes ReplicaSet
Container	Kubernetes Container	Docker Container
	AWS ECS Container	

Wiz types	Wiz native types	CMDB CI classes
	Azure ACA Container	
	Azure ACI Container	

Accessing the connection details of Service Graph Connector for Wiz

You can access the connection details of the Service Graph Connector for Wiz in a single view using the common connection framework (CCF) included within the Integration Commons for CMDB (sn_cmdb_int_util) store app.

With the CCF, you can access all the connections used by the Service Graph Connector for Wiz. The connection details include the connection alias, connection properties, data sources, and scheduled data imports associated with a connection. You can also test the connection. For more information, see [Accessing the connection details of Service Graph Connectors](#).

Access the details of a Wiz connection

Access the details of a Wiz connection configured for the Service Graph Connector for Wiz.

Before you begin

Role required: admin

Procedure

1. Navigate to **All > Service Graph Connectors > Wiz > Connections**.
2. From the **Name** column of the Service Graph Connections list, select a connection.

3. On the Service Graph Connections page, view the connection details such as the connection name and alias.
4. Select a related list to view further details of the connection.
5. (Optional) Select the **Test Connection** related link to test the connection.