



Incident report analysis

Summary	The company experienced a security event that resulted in the sudden disruption of all network services for two hours. The cybersecurity team discovered that the failure was caused by a Denial of Service (DoS) attack based on a flood of incoming ICMP packets, which exploited an unconfigured firewall. The incident response team contained the threat by blocking these incoming packets and temporarily disabling all non-critical network services, ensuring that critical services could be restored and stabilized.
Identify	One or more malicious actors targeted the organization's network with an ICMP flood DoS attack. The entire internal network was impacted, preventing legitimate traffic from accessing company resources. The audit identified that the main vulnerability exploited was a flaw in the firewall configuration. All critical network resources needed to be identified, protected, and restored to a normal functioning state.
Protect	To protect the infrastructure against future events, the cybersecurity team implemented a new firewall rule to strictly limit the rate of incoming ICMP packets. Additionally, an Intrusion Detection and Prevention System (IDS/IPS) was implemented to automatically analyze and filter ICMP traffic based on suspicious characteristics and known attack signatures.
Detect	The security team configured source IP address verification directly on the firewall to check for spoofed IP addresses in the incoming ICMP packets. Additionally, dedicated network monitoring software was implemented, ensuring continuous traffic visibility to detect abnormal patterns or unusual spikes in real-time.
Respond	In the event of future security incidents, the incident response team will

	immediately isolate the affected systems to prevent further network disruption. The team will actively analyze network and firewall logs for suspicious and abnormal activity to understand the extent of the attack. In addition to technical measures, a protocol was established where the team will formally report all downtime incidents to upper management and involve the appropriate legal authorities, as required by local laws.
Recover	Although a DoS attack generally does not result in the loss of sensitive data or PII/SPII, the priority for recovery is to restore full availability. The established recovery process requires that, initially, external ICMP flood attacks be blocked at the firewall. Next, non-critical network services must be stopped to reduce internal network congestion. Critical business services will be restored first. Finally, once the flood of ICMP packets has timed out and the network stabilizes, all non-critical systems and services will be gradually brought back online.

Reflections/Notes: