

chrome_tab_organiser

v1.4 Editor Update — Drag to Reorder Tabs

chrome_report_edit_v1.4.py

— a local web app to edit generated tab reports
— **new:** drag tabs up, down, or across into another window

chrome_report_v1.4.py

— generate the HTML/JSON report this editor reads

Document suffix `_261004` — self-contained tools, Python standard library only.

Contents

- 1 What is new in v1.4
- 2 Files
- 3 Running the editor
- 4 Reordering tabs — the new part
- 5 Interaction with “sort groups alphabetically”
- 6 Row positions (`data-pos`)
- 7 Saving
- 8 Testing
- 9 Troubleshooting
- 10 Relationship to the report generator

1 What is new in v1.4

Version 1.4 of the report editor adds **drag-and-drop reordering of tabs**: grab the **grip** on any tab row and drag it **up or down** to change its position inside the window, or **into any other window** to move that tab between windows. Row positions (`data-pos`) are renumbered automatically after every change.

- The dragged row is dimmed while in flight; the target table is outlined.
- Everything from v1.3 still works: renaming windows and groups, editing tab titles and URLs, inserting rows, deleting rows, alphabetical group sorting, and saving under a new name.

2 Files

File	Purpose
chrome_report_edit_v1.4.py	The editor. Run this.
chrome_report_edit_v1.4.exe	Standalone editor, no Python needed.
chrome_report_edit_v1.3.py	Previous editor, kept for reference. Unchanged.
chrome_tabs_Default_v1.4.html	Example report from the v1.4 generator.
test_editor_js.py	Headless test suite for the editor (25 checks).

Older versions (`chrome_report_edit.py` , `_v1.1.py` , `_v1.2.py` , `_v1.3.py`) are untouched, as is the existing `chrome_tab_organiser_guide_260911` series.

3 Running the editor

From Python

```
python chrome_report_edit_v1.4.py
```

From the executable

Double-click `chrome_report_edit_v1.4.exe` . On first run Windows may show a SmartScreen prompt — choose **More info** → **Run anyway**.

Options

Option	Meaning
<code>--dir PATH</code>	directory of reports to manage (default: the editor's own directory)
<code>--host HOST</code>	default <code>127.0.0.1</code>
<code>--port PORT</code>	default <code>8765</code>
<code>--no-browser</code>	do not open a browser window at startup

The editor starts a small local web server and opens `http://127.0.0.1:8765/` . It binds to the loopback address unless you pass a different `--host` .

The `.exe` manages the directory it lives in. Point it elsewhere with `chrome_report_edit_v1.4.exe --dir "D:\path\to\reports"` .

4 Reordering tabs — the new part

Starting a drag

Press and hold the **grip** in the Group cell of a row, then move the mouse. The grip turns to a grabbing cursor; the row dims to 40% opacity.

Group	Tab	URL
 + × ChIP	Alpha	https://a.example/
← press and hold the grip, then drag		

The drag starts only from the grip. Clicking anywhere else in a row keeps its normal behaviour — clicking text edits it, clicking a link does not follow it. That is why rows stay comfortable to edit by hand even with dragging enabled.

Dropping

Drop point	Result
Above a row's midpoint	Inserted before that row
Below a row's midpoint	Inserted after that row
Past the last row	Inserted at the end
Over another window's table	Inserted into that window

The insertion slot only changes when the pointer crosses a row's midpoint, so the row settles in place instead of jittering as you move the mouse. Release the mouse button to commit; releasing outside the tables cancels.

No keyboard shortcut is provided in v1.4 — reordering is mouse-only. Everything else in the editor is unchanged.

5 Interaction with “sort groups alphabetically”

The toolbar checkbox reorders every window so that ungrouped tabs come first, then tab groups A→Z. It is a **view-level** reordering that is undone when you uncheck it.

Starting a drag turns the checkbox off automatically. The order you see at that moment becomes the new baseline, and your drag is applied to it. Unchecking afterwards will no longer snap the rows back, because there is nothing left to restore.

If you prefer to use sorting as a one-off view it is safe: as long as you do not drag while it is checked, unchecking restores the original order.

6 Row positions (`data-pos`)

Reports from `chrome_report_v1.4.py` tag each row with `data-pos="1"`, `"2"`, ... in display order. Several parts of the report rely on that numbering matching the row order, so the editor keeps it truthful:

- `data-pos` is rewritten `1..N` after an **insert**, a **delete**, a **drag**, a **group sort**, and on **save**.
- A dragged row keeps its attribute while in flight; the two windows involved are renumbered together when the drop completes.
- Reports with **no** `data-pos` anywhere (older v1.3-era and earlier reports) are left that way. Editing such a report never silently adds the attribute, so a round-trip cannot change its shape.

7 Saving

Click **Save**, or press `Enter` in the name box. Type a name to write a new file; leave it as-is to overwrite the file you loaded. Only simple `[A-Za-z0-9_-. ]` names ending in `.html` are accepted, and writes are confined to the managed directory.

Saved reports contain **no editor chrome** — the grip, the `+/x` buttons, the injected stylesheet and all `contenteditable` attributes are stripped automatically. A saved file is a clean report you can open in any browser.

8 Testing

```
python -m py_compile chrome_report_edit_v1.4.py test_editor_js.py
python test_editor_js.py
```

`test_editor_js.py` drives the real editor page in headless Chrome with synthetic drag events and asserts 25 behaviours:

- a grip on every row, carrying `ce-inject` so it is stripped on save
- dragging down within a window reorders the rows
- dragging across windows moves the tab and both windows stay sequential
- `data-pos` is renumbered after insert, delete and drag
- the drag clears its own classes and the drop-zone highlight
- a drag unchecks the group-sort box
- saving strips the grip, the injected CSS and `contenteditable`, and keeps `data-pos`
- a legacy report without `data-pos` gains no attributes through any of it

Requires Google Chrome; `Node.js` is **not** required.

9 Troubleshooting

The grip does nothing

The drag must begin on the `]]` button itself. Pressing on the group name or the tab title edits text instead.

I cannot drop a row onto the window I want

Drop onto the *table area* of the target window — its rows. The blue outline around a table confirms it is a valid target. A window with no tabs yet has no rows to aim at; add a tab first, then drag.

My drag did not stick

The drop only commits inside a table. Releasing outside the tables cancels.

Rows went back to their old order

You probably had “sort groups alphabetically” checked. It now turns itself off on the first drag; re-check it if you want the sorted view back.

The port is already in use

Pass another one: `python chrome_report_edit_v1.4.py --port 8766`.

10 Relationship to the report generator

```
chrome_report_v1.4.py      --writes-->  chrome_tabs_Default_v1.4.html
                                   |
                                   opened in the editor
                                   v
chrome_report_edit_v1.4.py <--saves--  any name you type
```

The editor reads and writes the same HTML the generator produces, so you can generate a report, tidy the order by dragging, and reopen the saved file whenever you like. If you then re-run the generator it will overwrite whatever default report name it uses — save your edited copy under a different name to keep it.