

PvP Service Interface Documentation

1. ClientAPI

Purpose: Exposes main PvP actions to UI or other microservices.

Methods:

- invite_player(inviter: User, invitee: User) -> Invitation
Calls InvitePlayerService.create_invitation()
- accept_invite(invitation: Invitation)
Calls AcceptInviteService.accept()
- decline_invite(invitation: Invitation)
Calls DeclineInviteService.decline()
- select_party(invitation: Invitation, username: str, party: Party)
Calls SelectPartyService.select_party()
- start_battle(invitation: Invitation) -> BattleMatch
Calls StartBattleService.start_battle()

2. BattleSystemAPI

Purpose: Exposes battle resolution system.

Methods:

- resolve_battle(match: BattleMatch) -> str
Resolves battle using external engine and updates BattleMatch
- record_result(match: BattleMatch)
Calls UpdateLeagueService.update() to update league standings

3. PVEPartySubmissionAPI

Purpose: Receives PvE campaign data to populate PvP user parties.

Methods:

- submit_party(user: User, party: Party)
Calls PartyRepository.save()
- submit_multiple_parties(user: User, parties: list[Party])
Calls PartyRepository.save() for each party

Notes

- Interfaces are adapters between external consumers and internal services.
- They do not contain business logic; domain rules remain in services/entities.
- Interfaces can include validation before invoking services.
- They can be mocked in tests for simulating external requests.