RAJALAKSHMI ENGINEERING COLLEGE

RAJALAKSHMI NAGAR, THANDALAM – 602 105



CS23331 - DESIGN AND ANALYSIS OF ALGORITHMS

Laboratory Record Note Book

Name: JOSEL FEDRIZIA.P

Year/Branch: II/CSE

University Register No.: 2116250701299

College Roll No.: 250701299

Semester: III

Academic Year: 2026

INDEX PAGE

EXP. NO:	NAME OF THE EXPERIMENT	DATE OF COMPLETION
1	**Finding Complexity using Counter Method**	04/08/2026
2	**Finding Complexity using Counter Method**	04/08/2026
3	**Finding Complexity using Counter Method**	04/08/2026
4	**Finding Complexity using Counter Method**	04/08/2026
5	**Finding Complexity using Counter Method**	04/08/2026
6	**Coin Problem**	25/08/2026
7	**Cookies Problem**	25/08/2026
8	Burger Problem	25/08/2026
9	Array Sum max Problem	25/08/2026
10	**Product of Array elements-Minimum**	25/08/2026
11	**Number of Zeros in a Given Array**	25/08/2026
12	**Majority Element**	25/08/2026
13	**Finding Floor Value**	25/08/2026
14	**Two Elements sum to x**	25/08/2026
15	**Implementation of Quick Sort**	25/08/2026
16	**Playing with Numbers**	29/09/2026
17	**Playing with chessboard**	29/09/2026
18	**Longest Common Subsequence**	29/09/2026

19	**Longest non-decreasing Subsequence**	05/10/2026
20	**Finding Duplicates-O(n^2) Time Complexity,O (1) Space Complexity**	29/09/2026
21	**Finding Duplicates-O(n) Time Complexity,O (1) Space Complexity**	29/09/2026
22	**Print Intersection of 2 sorted arrays-O(m*n)Time Complexity,O (1) Space Complexity**	29/09/2026
23	**Print Intersection of 2 sorted arrays-O(m+n)Time Complexity,O (1) Space Complexity**	29/09/2026
24	**Pair with Difference-O(n^2)Time Complexity,O (1) Space Complexity**	29/09/2026
25	**Pair with Difference -O(n) Time Complexity,O (1) Space Complexity**	29/09/2026

Finding Time Complexity:

1.Convert the following algorithm into a program and find its time complexity using the counter method.

```
void function (int n)
{
   int i= 1;


   int s =1;


   while(s <= n)
   {
      i++;
      s += i;
    }
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

For example:

Input	Result
9	12

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int main(){
    int n;
    scanf("%d",&n);
    int counter=0;
    int i=1;
    counter++;
    int s=1;
    counter++;
    while(1){
        counter++;
        if(!(s<=n)){
            break;
        }
        i++;
        counter++;
        s+=i;
        counter++;
    }
    printf("%d",counter);
    return 0;
}
```

2.Convert the following algorithm into a program and find its time complexity using the counter method.

```
void func(int n)
{
   if(n==1)
   {
     printf("*");
   }
   else
   {
    for(int i=1; i<=n; i++)
    {
      for(int j=1; j<=n; j++)
      {
        printf("*");
        printf("*");
        break;
      }
    }
  }
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

```c
#include<stdio.h>
int main(){
    int n;
    scanf("%d",&n);
    int counter=0;
    if(n==1){

    }
    else{
        for(int i=1; i<=n; i++)
        {
            counter++;
            counter++;
        for(int j=1; j<=n; j++)
            {
            counter++;
            counter++;
            break;
            }
            counter++;
        }
        counter++;
    }
    counter++;
    printf("%d",counter);
    return 0;
}
```

3.Convert the following algorithm into a program and find its time complexity using counter method.

```
Factor(num) {
{
  for (i = 1; i <= num;++i)
  {
   if (num % i== 0)
     {
       printf("%d ", i);
     }
  }
 }
```

Note: No need of counter increment for declarations and scanf() and counter variable printf() statement.

Input:

A positive Integer n

Output:

Print the value of the counter variable

```c
#include<stdio.h>
int main(){
    int num;
    scanf("%d",&num);
    int counter=0;
    for (int i = 1; i <= num;++i)
    {
        counter++;
        counter++;
        if (num % i== 0)
            {
                counter++;
            //printf("%d ", i);
            }

    }
    counter++;
    printf("%d",counter);
}
```

4. Convert the following algorithm into a program and find its time complexity using counter method.

```
void function(int n)
{
   int c= 0;
   for(int i=n/2; i<n; i++)
      for(int j=1; j<n; j = 2 * j)
         for(int k=1; k<n; k = k * 2)
            c++;
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

```c
#include<stdio.h>
int main(){
    int n;
    scanf("%d",&n);
    int counter=0;
    int c=0;
    for(int i=n/2; i<n; i++){
        counter++;
        counter++;
        for(int j=1; j<n; j = 2 * j){
            counter++;
            counter++;
            for(int k=1; k<n; k = k * 2){
                counter++;
                counter++;
                c++;
            }

        }
    }
    counter++;
    counter++;
    printf("%d",counter);
    return 0;
}
```

5. Convert the following algorithm into a program and find its time complexity using counter method.

```
void reverse(int n)
{
  int rev = 0, remainder;
  while (n != 0)
   {
      remainder = n % 10;
      rev = rev * 10 + remainder;
      n/= 10;
   }
print(rev);
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

```c
#include <stdio.h>
int main(){
    int n;
    scanf("%d",&n);
    int count=0;
    int rev=0;
    count++;
    int rem=0;
    count++;
    while(n!=0){
        count++;
        rem=n%10;
        count++;
        rev=rev*10+rem;
        count++;
        n/=10;
        count++;
    }
    count++;
    printf("%d",count);
    return 0;
}
```

Greedy Algorithm:

1. Write a program to take value V and we want to make change for V Rs, and we have infinite supply of each of the denominations in Indian currency, i.e., we have infinite supply of { 1, 2, 5, 10, 20, 50, 100, 500, 1000} valued coins/notes, what is the minimum number of coins and/or notes needed to make the change.

Input Format:

Take an integer from stdin.

Output Format:

print the integer which is change of the number.

Example Input :

64

Output:

4

Explanaton:

We need a 50 Rs note and a 10 Rs note and two 2 rupee coins.

```c
#include <stdio.h>

int main() {
    int V, count = 0;
    int denominations[] = {1000, 500, 100, 50, 20, 10, 5, 2, 1};
    int n = 9;

    scanf("%d", &V);

    for (int i = 0; i < n; i++) {
        count += V / denominations[i];
        V %= denominations[i];
    }

    printf("%d", count);

    return 0;
}
```

2. Assume you are an awesome parent and want to give your children some cookies. But, you should give each child at most one cookie.

Each child i has a greed factor g[i], which is the minimum size of a cookie that the child will be content with; and each cookie j has a size s[j]. If s[j] >= g[i], we can assign the cookie j to the child i, and the child i will be content. Your goal is to maximize the number of your content children and output the maximum number.

Example 1:

Input:

3

1 2 3

2

1 1

Output:

1

Explanation: You have 3 children and 2 cookies. The greed factors of 3 children are 1, 2, 3.

And even though you have 2 cookies, since their size is both 1, you could only make the child whose greed factor is 1 content.

You need to output 1.

Constraints:

1 <= g.length <= 3 * 10^4

0 <= s.length <= 3 * 10^4

1 <= g[i], s[j] <= 2^31 - 1

```c
#include <stdio.h>

int main() {
    int n, m, i, j, temp, count = 0;

    scanf("%d", &n);

    int g[n];
    for (i = 0; i < n; i++)
        scanf("%d", &g[i]);

    scanf("%d", &m);

    int s[m];
    for (i = 0; i < m; i++)
        scanf("%d", &s[i]);

    for (i = 0; i < n - 1; i++)
        for (j = i + 1; j < n; j++)
            if (g[i] > g[j]) {
                temp = g[i];
                g[i] = g[j];
                g[j] = temp;
            }

    for (i = 0; i < m - 1; i++)
        for (j = i + 1; j < m; j++)
            if (s[i] > s[j]) {
                temp = s[i];
                s[i] = s[j];
                s[j] = temp;
            }

    i = 0;
    j = 0;

    while (i < n && j < m) {
        if (s[j] >= g[i]) {
            count++;
            i++;
        }
        j++;
    }

    printf("%d", count);

    return 0;
}
```

3. A person needs to eat burgers. Each burger contains a count of calorie. After eating the burger, the person needs to run a distance to burn out his calories.
If he has eaten i burgers with c calories each, then he has to run at least $3^i * c$ kilometers to burn out the calories. For example, if he ate 3
burgers with the count of calorie in the order: [1, 3, 2], the kilometers he needs to run are $(3^0 * 1) + (3^1 * 3) + (3^2 * 2) = 1 + 9 + 18 = 28$.
But this is not the minimum, so need to try out other orders of consumption and choose the minimum value. Determine the minimum distance
he needs to run. Note: He can eat burger in any order and use an efficient sorting algorithm.Apply greedy approach to solve the problem.

Input Format

First Line contains the number of burgers
Second line contains calories of each burger which is n space-separate integers

Output Format

Print: Minimum number of kilometers needed to run to burn out the calories

Sample Input

3
5 10 7

Sample Output

76

For example:

Test	Input	Result
Test Case 1	3 1 3 2	18

```c
#include <stdio.h>
#include <math.h>

int main()

{
    int n, i, j, temp;
    int sum=0;
    scanf("%d", &n);

    int calories[n];

    for (i = 0; i < n; i++)
    {
        scanf("%d", &calories[i]);
    }
    for (i = 0; i < n ; i++)

    {
        for (j = i+1; j < n; j++)
        {
            if (calories[i] < calories[j])
            {
                temp = calories[i];
                calories[i] = calories[j];
                calories[j] = temp;
            }
        }
    }


    for (i = 0; i < n; i++)
    {

    sum=sum+pow(n,i)*calories[i];

    }

    printf("%d", sum);

    return 0;

}
```

4. Given an array of N integer, we have to maximize the sum of arr[i] * i, where i is the index of the element (i = 0, 1, 2, ..., N).Write an algorithm based on Greedy technique with a Complexity O(nlogn).

Input Format:

First line specifies the number of elements-n

The next n lines contain the array elements.

Output Format:

Maximum Array Sum to be printed.

Sample Input:

5

2 5 3 4 0

Sample output:

40

```c
#include <stdio.h>
#include <stdlib.h>

int cmp(const void *a, const void *b) {
    return (*(int *)a > *(int *)b) - (*(int *)a < *(int *)b);
}

int main() {
    int n;
    scanf("%d", &n);

    int a[n];

    for (int i = 0; i < n; i++)
        scanf("%d", &a[i]);

    qsort(a, n, sizeof(int), cmp);

    long long sum = 0;

    for (int i = 0; i < n; i++)
        sum += (long long)a[i] * i;

    printf("%lld", sum);

    return 0;
}
```

5. Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs(1 element from each) is minimum. That is SUM (A[i] * B[i]) for all i is minimum.

For example:

Input	Result
3 1 2 3 4 5 6	28

```c
#include <stdio.h>
#include <stdlib.h>

int cmp(const void *a, const void *b) {
    return (*(int *)a > *(int *)b) - (*(int *)a < *(int *)b);
}

int main() {
    int n;
    scanf("%d", &n);

    int a[n], b[n];

    for (int i = 0; i < n; i++)
        scanf("%d", &a[i]);

    for (int i = 0; i < n; i++)
        scanf("%d", &b[i]);

    qsort(a, n, sizeof(int), cmp);
    qsort(b, n, sizeof(int), cmp);

    long long sum = 0;

    for (int i = 0; i < n; i++)
        sum += (long long)a[i] * b[n - 1 - i];

    printf("%lld", sum);

    return 0;
}
```

Divide & Conquer:

1. Given an array of 1s and 0s this has all 1s first followed by all 0s. Aim is to find the number of 0s. Write a program using Divide and Conquer to Count the number of zeroes in the given array.

Input Format

First Line Contains Integer m – Size of array

Next m lines Contains m numbers – Elements of an array

Output Format

First Line Contains Integer – Number of zeroes present in the given array.

```c
#include <stdio.h>

int countZero(int a[], int low, int high) {
    if (low > high)
        return 0;

    int mid = (low + high) / 2;

    if (a[mid] == 1)
        return countZero(a, mid + 1, high);
    else
        return (high - mid + 1) + countZero(a, low, mid - 1);
}

int main() {
    int n;
    scanf("%d", &n);

    int a[n];

    for (int i = 0; i < n; i++)
        scanf("%d", &a[i]);

    printf("%d", countZero(a, 0, n - 1));

    return 0;
}
```

2. Given an array nums of size n, return the majority element.

The majority element is the element that appears more than n / 2 times. You may assume that the majority element always exists in the array.

Example 1:

Input: nums = [3,2,3]
Output: 3

Example 2:

Input: nums = [2,2,1,1,1,2,2]
Output: 2

Constraints:

n == nums.length

$1 <= n <= 5 * 10^4$

$-2^{31} <= nums[i] <= 2^{31} - 1$

For example:

Input	Result
3 3 2 3	3
7 2 2 1 1 1 2 2	2

```c
#include <stdio.h>

int main() {
    int n;
    scanf("%d", &n);

    int x, candidate = 0, count = 0;

    for (int i = 0; i < n; i++) {
        scanf("%d", &x);

        if (count == 0)
            candidate = x;

        if (x == candidate)
            count++;
        else
            count--;
    }

    printf("%d", candidate);

    return 0;
}
```

3. Given a sorted array and a value x, the floor of x is the largest element in array smaller than or equal to x. Write divide and conquer algorithm to find floor of x.

Input Format

First Line Contains Integer n – Size of array
Next n lines Contains n numbers – Elements of an array
Last Line Contains Integer x – Value for x

Output Format

First Line Contains Integer – Floor value for x

```c
#include <stdio.h>

int floorValue(int a[], int low, int high, int x) {
    if (low > high)
        return -1;

    int mid = (low + high) / 2;

    if (a[mid] == x)
        return a[mid];

    if (a[mid] > x)
        return floorValue(a, low, mid - 1, x);

    int result = floorValue(a, mid + 1, high, x);

    if (result == -1)
        return a[mid];

    return result;
}

int main() {
    int n, x;
    scanf("%d", &n);

    int a[n];

    for (int i = 0; i < n; i++)
        scanf("%d", &a[i]);

    scanf("%d", &x);

    printf("%d", floorValue(a, 0, n - 1, x));

    return 0;
}
```

4. Given a sorted array of integers say arr[] and a number x. Write a recursive program using divide and conquer strategy to check if there exist two elements in the array whose sum = x. If there exist such two elements then return the numbers, otherwise print as “No”.
Note: Write a Divide and Conquer Solution

Input Format

First Line Contains Integer n – Size of array
Next n lines Contains n numbers – Elements of an array
Last Line Contains Integer x – Sum Value

Output Format

First Line Contains Integer – Element1
Second Line Contains Integer – Element2 (Element 1 and Elements 2 together sums to value “x”)

```c
#include <stdio.h>

int findPair(int a[], int left, int right, int x, int *p, int *q) {
    if (left >= right)
        return 0;

    int sum = a[left] + a[right];

    if (sum == x) {
        *p = a[left];
        *q = a[right];
        return 1;
    }

    if (sum < x)
        return findPair(a, left + 1, right, x, p, q);

    return findPair(a, left, right - 1, x, p, q);
}

int main() {
    int n, x, p, q;

    scanf("%d", &n);

    int a[n];

    for (int i = 0; i < n; i++)
        scanf("%d", &a[i]);

    scanf("%d", &x);

    if (findPair(a, 0, n - 1, x, &p, &q)) {
        printf("%d\n%d", p, q);
    } else {
        printf("No");
    }

    return 0;
}
```

5. Write a Program to Implement the Quick Sort Algorithm
Input Format:
The first line contains the no of elements in the list-n
The next n lines contain the elements.
Output:
Sorted list of elements

For example:

Input	Result
5 67 34 12 98 78	12 34 67 78 98

```c
#include <stdio.h>

void quickSort(int a[], int low, int high) {
    if (low >= high)
        return;

    int i = low, j = high;
    int pivot = a[(low + high) / 2];
    int temp;

    while (i <= j) {
        while (a[i] < pivot)
            i++;

        while (a[j] > pivot)
            j--;

        if (i <= j) {
            temp = a[i];
            a[i] = a[j];
            a[j] = temp;
            i++;
            j--;
        }
    }

    quickSort(a, low, j);
    quickSort(a, i, high);
}

int main() {
    int n;
    scanf("%d", &n);

    int a[n];

    for (int i = 0; i < n; i++)
        scanf("%d", &a[i]);

    quickSort(a, 0, n - 1);

    for (int i = 0; i < n; i++) {
        if (i > 0)
            printf(" ");
        printf("%d", a[i]);
    }

    return 0;
}
```

Dynamic Programming:

1.Ram and Sita are playing with numbers by giving puzzles to each other. Now it was Ram term, so he gave Sita a positive integer 'n' and two numbers 1 and 3. He asked her to find the possible ways by which the number n can be represented using 1 and 3.Write any efficient algorithm to find the possible ways.

Example 1:

Input: 6
Output: 6
Explanation: There are 6 ways to 6 represent number with 1 and 3
1+1+1+1+1+1
3+3
1+1+1+3
1+1+3+1
1+3+1+1
3+1+1+1

Input Format
First Line contains the number n
Output Format

Print: The number of possible ways 'n' can be represented using 1 and 3

Sample Input
6

Sample Output

6

```c
#include <stdio.h>

int main() {
    int n;
    scanf("%d", &n);

    long long dp[n + 1];

    dp[0] = 1;

    for (int i = 1; i <= n; i++) {
        dp[i] = dp[i - 1];

        if (i >= 3)
            dp[i] += dp[i - 3];
    }

    printf("%lld", dp[n]);

    return 0;
}
```

2. Ram is given with an n*n chessboard with each cell with a monetary value. Ram stands at the (0,0), that the position of the top left white rook. He is been given a task to reach the bottom right black rook position (n-1, n-1) constrained that he needs to reach the position by traveling the maximum monetary path under the condition that he can only travel one step right or one

step down the board. Help ram to achieve it by providing an efficient DP algorithm.

Example:
Input
3
1 2 4
2 3 4
8 7 1
Output:
19

Explanation:
Totally there will be 6 paths among that the optimal is
Optimal path value:1+2+8+7+1=19

Input Format
First Line contains the integer n
The next n lines contain the n*n chessboard values
Output Format

Print Maximum monetary value of the path

```c
#include <stdio.h>

int main() {
    int n;
    scanf("%d", &n);

    long long board[n][n];
    long long dp[n][n];

    for (int i = 0; i < n; i++)
        for (int j = 0; j < n; j++)
            scanf("%lld", &board[i][j]);

    dp[0][0] = board[0][0];

    for (int j = 1; j < n; j++)
        dp[0][j] = dp[0][j - 1] + board[0][j];

    for (int i = 1; i < n; i++)
        dp[i][0] = dp[i - 1][0] + board[i][0];

    for (int i = 1; i < n; i++) {
        for (int j = 1; j < n; j++) {
            dp[i][j] = board[i][j] +
                       (dp[i - 1][j] > dp[i][j - 1]
                        ? dp[i - 1][j]
                        : dp[i][j - 1]);
        }
    }

    printf("%lld", dp[n - 1][n - 1]);

    return 0;
}
```

3. Given two strings find the length of the common longest subsequence(need not be contiguous) between the two.

Example:

s1: ggtabe

s2: tgatasb

s1		a	g	g	t	a	b
s2	g	x	t	x	a	y	b

The length is 4

Solveing it using Dynamic Programming

For example:

Input	Result
aab azb	2

```c
#include <stdio.h>
#include <string.h>

int main() {
    char s1[100], s2[100];
    int dp[101][101];

    scanf("%s", s1);
    scanf("%s", s2);

    int m = strlen(s1);
    int n = strlen(s2);

    for (int i = 0; i <= m; i++)
        dp[i][0] = 0;

    for (int j = 0; j <= n; j++)
        dp[0][j] = 0;

    for (int i = 1; i <= m; i++) {
        for (int j = 1; j <= n; j++) {
            if (s1[i - 1] == s2[j - 1])
                dp[i][j] = dp[i - 1][j - 1] + 1;
            else
                dp[i][j] = (dp[i - 1][j] > dp[i][j - 1])
                           ? dp[i - 1][j]
                           : dp[i][j - 1];
        }
    }

    printf("%d\n", dp[m][n]);

    return 0;
}
```

4. Find the length of the Longest Non-decreasing Subsequence in a given Sequence.

Eg:

Input:9

Sequence:[-1,3,4,5,2,2,2,2,3]

the subsequence is [-1,2,2,2,2,3]

Output:6

```c
#include <stdio.h>

int main() {
    int n;
    scanf("%d", &n);

    int a[n], dp[n];
    int ans = 0;

    for (int i = 0; i < n; i++) {
        scanf("%d", &a[i]);
        dp[i] = 1;
    }

    for (int i = 1; i < n; i++) {
        for (int j = 0; j < i; j++) {
            if (a[j] <= a[i] && dp[i] < dp[j] + 1)
                dp[i] = dp[j] + 1;
        }
    }

    for (int i = 0; i < n; i++) {
        if (dp[i] > ans)
            ans = dp[i];
    }

    printf("%d", ans);

    return 0;
}
```

Competitive Programming:

1. Find Duplicate in Array. Time comp- O(n^2) & space comp- O(1):

Given a read only array of n integers between 1 and n, find one number that repeats.

Input Format:

First Line - Number of elements

n Lines - n Elements

Output Format:
Element x - That is repeated

For example:

Input	Result
5 1 1 2 3 4	1

```c
#include <stdio.h>
int main(){
    int n;
    scanf("%d",&n);
    int arr[n];
    for(int i=0;i<n;i++){
        scanf("%d",&arr[i]);
    }
    for(int i=0;i<n;i++){
        for(int j=0;j<n;j++){
            if(arr[i]==arr[j]&&i!=j){
                printf("%d",arr[i]);
                return 0;
            }
        }
    }
    return 0;
}
```

2. Find Duplicate in Array. Time comp- O(n) & space comp- O(1):

Given a read only array of n integers between 1 and n, find one number that repeats.

Input Format:

First Line - Number of elements

n Lines - n Elements

Output Format:
Element x - That is repeated

For example:

Input	Result
5 1 1 2 3 4	1

```c
#include <stdio.h>

int main() {
    int n;
    scanf("%d", &n);

    int count[n + 1];

    for (int i = 0; i <= n; i++)
        count[i] = 0;

    for (int i = 0; i < n; i++) {
        int x;
        scanf("%d", &x);
        count[x]++;

        if (count[x] == 2) {
            printf("%d", x);
            return 0;
        }
    }

    return 0;
}
```

3. **Print Intersection of 2 sorted arrays- O(m*n)Time Complexity,O(1) Space Complexity**

Find the intersection of two sorted arrays.

OR in other words,

Given 2 sorted arrays, find all the elements which occur in both the arrays.

Input Format

· The first line contains T, the number of test cases. Following T lines contain:

1. Line 1 contains N1, followed by N1 integers of the first array
2. Line 2 contains N2, followed by N2 integers of the second array

Output Format

The intersection of the arrays in a single line

Example

Input:

1

3 10 17 57

6 2 7 10 15 57 246

Output:

10 57

Input:

1

6 1 2 3 4 5 6

2 1 6

Output:

1 6

For example:

Input	Result
1 3 10 17 57 6 2 7 10 15 57 246	10 57

```c
#include <stdio.h>
int main() {
    int T;
    scanf("%d", &T);
    while (T--) {
        int n1, n2;
        scanf("%d", &n1);
        int A[n1];
        for (int i = 0; i < n1; i++) {
            scanf("%d", &A[i]);
        }
        scanf("%d", &n2);
        int B[n2];
        for (int i = 0; i < n2; i++) {
            scanf("%d", &B[i]);
        }
        int i = 0, j = 0;
        while (i < n1 && j < n2) {
            if (A[i] == B[j]) {
                printf("%d ", A[i]);
                i++;
                j++;
            }
            else if (A[i] < B[j]) {
                i++;
            }
            else {
                j++;
            }
        }
        printf("\n");
    }
    return 0;
}
```

4. Print Intersection of 2 sorted arrays-O(m+n)Time Complexity,O(1) Space Complexity

Find the intersection of two sorted arrays.

OR in other words,

Given 2 sorted arrays, find all the elements which occur in both the arrays.

Input Format

· The first line contains T, the number of test cases. Following T lines contain:

1. Line 1 contains N1, followed by N1 integers of the first array
2. Line 2 contains N2, followed by N2 integers of the second array

Output Format

The intersection of the arrays in a single line

Example

Input:

1

3 10 17 57

6 2 7 10 15 57 246

Output:

10 57

Input:

1

6 1 2 3 4 5 6

2 1 6

Output:

1 6

For example:

Input	Result
1 3 10 17 57 6 2 7 10 15 57 246	10 57

```c
#include <stdio.h>

int main() {
    int T;
    scanf("%d", &T);

    while (T--) {
        int n1, n2;
        scanf("%d", &n1);

        int a[n1];
        for (int i = 0; i < n1; i++)
            scanf("%d", &a[i]);

        scanf("%d", &n2);

        int b[n2];
        for (int i = 0; i < n2; i++)
            scanf("%d", &b[i]);

        int i = 0, j = 0;

        while (i < n1 && j < n2) {
            if (a[i] == b[j]) {
                printf("%d ", a[i]);
                i++;
                j++;
            } else if (a[i] < b[j]) {
                i++;
            } else {
                j++;
            }
        }
    }

    return 0;
}

```

5. Pair with Difference-O(n^2)Time Complexity,O(1) Space Complexity

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that A[j] - A[i] = k, i != j.

Input Format:

First Line n - Number of elements in an array

Next n Lines - N elements in the array

k - Non - Negative Integer

Output Format:
1 - If pair exists

0 - If no pair exists

Explanation for the given Sample Testcase:

YES as 5 - 1 = 4

So Return 1.

For example:

Input	Result
3 1 3 5 4	1

```c
#include <stdio.h>
int main() {
    int n, k;
    scanf("%d", &n);
    int A[n];
    for (int i = 0; i < n; i++) {
        scanf("%d", &A[i]);
    }
    scanf("%d", &k);
    int i = 0, j = 1;
    while (i < n && j < n) {
        if (i == j) {
            j++;
        }
        else if (A[j] - A[i] == k) {
            printf("1");
            return 0;
        }
        else if (A[j] - A[i] < k) {
            j++;
        }
        else {
            i++;
        }
    }
    printf("0");
    return 0;
}
```

6. Pair with Difference -O(n) Time Complexity,O(1) Space Complexity

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that A[j] - A[i] = k, i != j.

Input Format:

First Line n - Number of elements in an array

Next n Lines - N elements in the array

k - Non - Negative Integer

Output Format:
1 - If pair exists

0 - If no pair exists

Explanation for the given Sample Testcase:

YES as 5 - 1 = 4

So Return 1.

For example:

Input	Result
3 1 3 5 4	1

```c
#include <stdio.h>
int main() {
    int n, k;
    scanf("%d", &n);
    int A[n];
    for (int i = 0; i < n; i++) {
        scanf("%d", &A[i]);
    }
    scanf("%d", &k);
    int i = 0, j = 1;
    while (i < n && j < n) {
        if (i == j) {
            j++;
        }
        else if (A[j] - A[i] == k) {
            printf("1");
            return 0;
        }
        else if (A[j] - A[i] < k) {
            j++;
        }
        else {
            i++;
        }
    }
    printf("0");
    return 0;
}
```