Algorithm for file updates in Python

Project description

In this activity, I will use Python to create an algorithm that will update a file called “allow_list.txt”. The file contains four IP addresses that are in a separate variable called “remove_list”. I will configure the algorithm to remove those IP addresses from the allow list.

Open the file that contains the allow list

First, I will create a `with` statement and include an `open()` function to read the `allow_list.txt` file. Note that the output displays an error message because of the incomplete statement.

```
In [2]: # Assign `import_file` to the name of the file

        import_file = "allow_list.txt"

        # Assign `remove_list` to a list of IP addresses that are no longer allowed to access restricted information.

        remove_list = ["192.168.97.225", "192.168.158.170", "192.168.201.40", "192.168.58.57"]

        # First line of `with` statement

        with open("allow_list.txt", "r") as file:

          File "<ipython-input-2-3ac08d4137ba>", line 11
            with open("allow_list.txt", "r") as file:
                                                     ^
        SyntaxError: unexpected EOF while parsing
```

Read the file contents

Now, I will finish the `with` statement by adding a `.read()` method to read the text file and store it in the `ip_addresses` variable. Then, I will use the `print()` function to display the contents of the variable.

In [3]:
```
# Assign `import_file` to the name of the file

import_file = "allow_list.txt"

# Assign `remove_list` to a list of IP addresses that are no longer allowed to access restricted information.

remove_list = ["192.168.97.225", "192.168.158.170", "192.168.201.40", "192.168.58.57"]

# Build `with` statement to read in the initial contents of the file

with open(import_file, "r") as file:

  # Use `.read()` to read the imported file and store it in a variable named `ip_addresses`

  ip_addresses = file.read()

# Display `ip_addresses`

print(ip_addresses)
```

```
ip_address
192.168.25.60
192.168.205.12
192.168.97.225
192.168.6.9
192.168.52.90
192.168.158.170
192.168.90.124
192.168.186.176
192.168.133.188
192.168.203.198
192.168.201.40
192.168.218.219
192.168.52.37
192.168.156.224
192.168.60.153
192.168.58.57
192.168.69.116
```

Convert the string into a list

The output of the **`with`** statement displays the data as a string. Now, I will use a `.split()` method to convert the data into a list.

In [4]:
```
# Assign `import_file` to the name of the file

import_file = "allow_list.txt"

# Assign `remove_list` to a list of IP addresses that are no longer allowed to access restricted information.

remove_list = ["192.168.97.225", "192.168.158.170", "192.168.201.40", "192.168.58.57"]

# Build `with` statement to read in the initial contents of the file

with open(import_file, "r") as file:

  # Use `.read()` to read the imported file and store it in a variable named `ip_addresses`

  ip_addresses = file.read()

# Use `.split()` to convert `ip_addresses` from a string to a list

ip_addresses = ip_addresses.split()

# Display `ip_addresses`

print(ip_addresses)
```

```
['ip_address', '192.168.25.60', '192.168.205.12', '192.168.97.225', '192.168.6.9', '192.168.52.90', '192.168.158.170', '192.16
8.90.124', '192.168.186.176', '192.168.133.188', '192.168.203.198', '192.168.201.40', '192.168.218.219', '192.168.52.37', '192.
168.156.224', '192.168.60.153', '192.168.58.57', '192.168.69.116']
```

Iterate through the remove list

In this next task, I will create a **`for`** loop that will iterate through the `ip_addresses` variable in order to locate the IP addresses that are on the remove list.

In [5]:
```
# Assign `import_file` to the name of the file

import_file = "allow_list.txt"

# Assign `remove_list` to a list of IP addresses that are no longer allowed to access restricted information.

remove_list = ["192.168.97.225", "192.168.158.170", "192.168.201.40", "192.168.58.57"]

# Build `with` statement to read in the initial contents of the file

with open(import_file, "r") as file:

  # Use `.read()` to read the imported file and store it in a variable named `ip_addresses`

  ip_addresses = file.read()

# Use `.split()` to convert `ip_addresses` from a string to a list

ip_addresses = ip_addresses.split()

# Build iterative statement
# Name loop variable `element`
# Loop through `ip_addresses`

for element in ip_addresses:

    # Display `element` in every iteration

    print(element)
```

```
ip_address
192.168.25.60
192.168.205.12
192.168.97.225
192.168.6.9
192.168.52.90
192.168.158.170
192.168.90.124
192.168.186.176
192.168.133.188
192.168.203.198
192.168.201.40
192.168.218.219
192.168.52.37
192.168.156.224
192.168.60.153
192.168.58.57
192.168.69.116
```

Remove IP addresses that are on the remove list

Now that the output has confirmed that the IP addresses in the remove list are still in the `ip_addresses` variable, I will build an **`if`** statement with a `.remove()` method that will remove an IP address from the variable if it is in the remove list. I will finish by printing the contents of the variable to validate the changes.

In [6]:
```
# Assign `import_file` to the name of the file

import_file = "allow_list.txt"

# Assign `remove_list` to a list of IP addresses that are no longer allowed to access restricted information.

remove_list = ["192.168.97.225", "192.168.158.170", "192.168.201.40", "192.168.58.57"]

# Build `with` statement to read in the initial contents of the file

with open(import_file, "r") as file:

  # Use `.read()` to read the imported file and store it in a variable named `ip_addresses`

  ip_addresses = file.read()

# Use `.split()` to convert `ip_addresses` from a string to a list

ip_addresses = ip_addresses.split()

# Build iterative statement
# Name loop variable `element`
# Loop through `ip_addresses`

for element in ip_addresses:

  # Build conditional statement
  # If current element is in `remove_list`,

    if element in remove_list:

        # then current element should be removed from `ip_addresses`

        ip_addresses.remove(element)

# Display `ip_addresses`

print(ip_addresses)
```

```
['ip_address', '192.168.25.60', '192.168.205.12', '192.168.6.9', '192.168.52.90', '192.168.90.124', '192.168.186.176', '192.16
8.133.188', '192.168.203.198', '192.168.218.219', '192.168.52.37', '192.168.156.224', '192.168.60.153', '192.168.69.116']
```

Update the file with the revised list of IP addresses

Finally, I will use the `.join()` method to convert the data of the `ip_addresses` variable back into a string. Then I will create a new **`with`** statement that will use the `.write()` method to replace contents of the original text file with those of the `ip_addresses` variable.

In [16]:
```
# Assign `import_file` to the name of the file

import_file = "allow_list.txt"

# Assign `remove_list` to a list of IP addresses that are no longer allowed to access restricted information.

remove_list = ["192.168.97.225", "192.168.158.170", "192.168.201.40", "192.168.58.57"]

# Build `with` statement to read in the initial contents of the file

with open(import_file, "r") as file:

  # Use `.read()` to read the imported file and store it in a variable named `ip_addresses`

  ip_addresses = file.read()

# Use `.split()` to convert `ip_addresses` from a string to a list

ip_addresses = ip_addresses.split()

# Build iterative statement
# Name loop variable `element`
# Loop through `ip_addresses`

for element in ip_addresses:

  # Build conditional statement
  # If current element is in `remove_list`,

    if element in remove_list:

        # then current element should be removed from `ip_addresses`

        ip_addresses.remove(element)

# Convert `ip_addresses` back to a string so that it can be written into the text file

ip_addresses = "\n".join(ip_addresses)

# Build `with` statement to rewrite the original file

with open(import_file, "w") as file:

  # Rewrite the file, replacing its contents with `ip_addresses`

  file.write(ip_addresses)
```

Summary

This is one way of using Python to update the contents of files. If I wanted to use the code multiple times, I would define a function and place the contents of the algorithm inside that function. Then all I would have to do to run the algorithm is call the function.