WEARABLE INCONTINENCE MONITORING SYSTEM

BIOMEDICAL ENGINEERING 3

MICROPROCESSORS GROUP 8

MARCH 2026

NAME	INDEX NUMBERS
1. Ofori Angelina Boadiwaa	7297323
2. Owusu Seth Ankemah	7298223
3. Quainoo Queenscah Scholasticah	7298523
4. Toyin Pearl Yinsongma-	7299923
5. Mensah Agyeiwaa Francisca	7296623
6. Panford Joseph Adom	7298323
7. Osei Theodosia Mensah	7298123
8. Quaicoe Albright Badu Benyah	7298423
9. Ofori-Appiah Joab Prempeh	7297423

TABLE OF CONTENTS

ABSTRACT 3
INTRODUCTION.....3
PROBLEM STATEMENT 4
OBJECTIVES 5
METHODOLOGY 5
SYSTEM COMPONENTS 6
CIRCUIT DESIGN 6
SENSOR WORKING PRINCIPLE 8

CODE EXPLANATION 8
SIMULATION AND DEMONSTRATION 10
RESULTS AND DISCUSSION.....10
CHALLENGES ..... **Error! Bookmark not defined.**
CONCLUSION.....10
FUTURE IMPROVEMENTS 10

ABSTRACT

Incontinence management, especially among infants and the elderly, presents a significant challenge due to delayed detection of moisture, which can lead to skin irritation, infections, and reduced patient comfort. This project presents the design and implementation of a wearable incontinence monitoring system that provides real-time detection of moisture conditions in diapers.

The system utilizes a moisture sensor to continuously monitor wetness levels and an Arduino Uno microcontroller to process the sensor's analog signals using a predefined threshold. Upon detecting a wet condition, the system immediately activates alert mechanisms including a light-emitting diode (LED), a buzzer, and an LCD display to notify caregivers.

The solution was developed and tested using a simulation environment, where a potentiometer was used to emulate varying moisture levels. Results demonstrate that the system responds accurately and promptly to changes in moisture, effectively distinguishing between dry and wet states.

This project offers a simple, cost-effective, and efficient approach to improving hygiene management and patient care. It also provides a foundation for future enhancements such as wireless communication and multi-parameter health monitoring.

INTRODUCTION

Incontinence is the inability to control urination, a condition commonly affecting infants, elderly individuals, and patients with certain medical conditions. Proper management of incontinence is essential to maintain hygiene, prevent skin irritation, and ensure overall patient comfort. However, one of the major challenges in incontinence care is the delayed detection of wetness, as caregivers may not always be immediately aware when a diaper becomes wet.

Prolonged exposure to moisture can lead to serious health issues such as skin rashes, infections, and discomfort, particularly in vulnerable individuals. Traditional methods of checking for wetness are often manual, time consuming, and inefficient, increasing the risk of delayed response and poor hygiene management.

To address this challenge, this project focuses on the development of a wearable incontinence monitoring system that can detect moisture in real time and alert caregivers instantly. The system integrates a moisture sensor, an Arduino Uno microcontroller, and output devices such as an LED, buzzer, and LCD display to provide immediate feedback when wetness is detected.

By automating the monitoring process, this system aims to improve the quality of care, enhance patient comfort, and reduce the burden on caregivers. It also serves as a foundation for further advancements in smart healthcare systems, particularly in the section of remote patient monitoring and assistive technologies.

PROBLEM STATEMENT

Incontinence care, particularly for infants and elderly patients, requires timely detection of moisture to maintain proper hygiene and prevent health complications. However, in many caregiving situations, there is no efficient system to immediately detect when a diaper becomes wet. Caregivers often rely on routine or manual checks, which can lead to delays in identifying wet conditions.

Prolonged exposure to moisture creates a high risk of skin irritation, rashes, and infections, especially in individuals with sensitive or fragile skin. These conditions not only cause discomfort but can also lead to more serious health complications if not addressed promptly.

Additionally, delayed awareness of wetness increases the workload on caregivers and reduces the overall quality of care provided. The lack of a real-time monitoring solution makes it difficult to ensure timely intervention, thereby negatively impacting patient hygiene and well-being.

Therefore, there is a need for a reliable, real-time monitoring system that can detect moisture instantly and alert caregivers immediately, ensuring prompt response and improved patient care.

OBJECTIVES

The main objectives of this project are:

1. To detect moisture in real time using a moisture sensor.
2. To process sensor data using an Arduino Uno microcontroller.
3. To provide immediate alerts to caregivers using an LED, buzzer, and LCD.

METHODOLOGY

The project began with identifying the problem of delayed detection of diaper wetness in infants and elderly patients, which can lead to discomfort, skin irritation, and infections. A wearable system was proposed to detect moisture and alert caregivers in real time. A system block diagram was designed to show the interaction between the moisture sensor, microcontroller, and output units.

Components were selected based on availability, cost, and functionality. A microcontroller was used for processing, a moisture sensor for detection, and output devices such as LEDs, buzzers, and an LCD display for alerts and monitoring.

The circuit was designed by connecting the moisture sensor to the analog input of the microcontroller. The LED, buzzer, and LCD were connected as output devices. Proper electrical connections and current limiting resistors were used to ensure safe operation.

The system was simulated using Tinkercad software. A potentiometer was used to simulate moisture levels. The simulation helped verify system functionality and detect errors before physical implementation.

The microcontroller was programmed to read analog signals from the sensor, process the data using ADC, and compare it to a predefined threshold. Based on the result, the system activates alerts and updates the LCD display.

The system was tested by varying sensor input values to simulate dry and wet conditions. Outputs were monitored to ensure accurate detection and proper functioning of alerts.

A physical prototype was developed using an Arduino kit to validate real-world performance and demonstrate practical application.

SYSTEM COMPONENTS

1. MOISTURE SENSOR

The moisture sensor detects the presence of liquid by measuring changes in resistance and outputs an analog signal.

2.ARDUINO UNO

The Arduino Uno acts as the central processing unit, reading sensor data and controlling the output devices.

3.OUTPUT DEVICES

- LED: Provides visual indication
- Buzzer: Provides audio alert
- LCD: Displays system status (WET/DRY)

CIRCUIT DESIGN

The circuit was designed and tested using simulation software. A potentiometer was used to simulate the behavior of the moisture sensor during testing.

The Arduino Uno is connected to the sensor input and output devices. The sensor provides analog input to the Arduino, while the LED, buzzer, and LCD are connected to digital output pins.



Figure 1: picture of circuit in simulation software





Figure 3: picture of schematic circuit

SENSOR WORKING PRINCIPLE

The operation of the moisture sensor is based on changes in electrical resistance. When moisture is present, the resistance between the sensor electrodes decreases, allowing more current to flow. This results in an increase in voltage, which is read as a higher analog value by the Arduino Uno R3. The Arduino compares this value to a predefined threshold to determine whether the condition is wet or dry.

CODE EXPLANATION

The system is programmed using the Arduino programming language.

The program begins by initializing all components, including the LCD and input/output pins. The Arduino continuously reads the analog value from the moisture sensor.

If the value exceeds a predefined threshold, the system identifies a wet condition and activates the LED, buzzer, and displays "WET" on the LCD. If the value is below the threshold, the system remains in a dry state and displays "DRY".

```
#include <LiquidCrystal.h>
LiquidCrystal lcd(7, 6, 5, 4, 3, 2);

int sensorPin = A0;
int ledPin = 8;
int buzzerPin = 9;
int moistureValue;

void setup() {
  lcd.begin(16, 2);
  pinMode(ledPin, OUTPUT);
  pinMode(buzzerPin, OUTPUT);

  lcd.print("Diaper Monitor");
  delay(2000);
  lcd.clear();
}
```

```
if (moistureValue > 600) {
  digitalWrite(ledPin, HIGH);
  tone(buzzerPin, 2000);
  delay(200);
  noTone(buzzerPin);
  delay(200);

  lcd.setCursor(0, 1);
  lcd.print("Status: WET ");
}
```

```
else {
  digitalWrite(ledPin, LOW);
  digitalWrite(buzzerPin, LOW);

  lcd.setCursor(0, 1);
  lcd.print("Status: DRY ");
}

delay(1000);
```

```
moistureValue = analogRead(sensorPin);

lcd.setCursor(0, 0);
lcd.print("Moisture: ");
lcd.print(moistureValue);
```

SIMULATION AND DEMONSTRATION

The system was tested using simulation software where a potentiometer was used to simulate moisture levels.

When the potentiometer value increases, the system detects a wet condition and activates the LED, buzzer, and LCD display. When the value decreases, the system returns to the dry state.

RESULTS AND DISCUSSION

The system successfully detects moisture and responds immediately by activating the alert mechanisms. The threshold-based detection method ensures accurate differentiation between wet and dry conditions.

The system demonstrates reliability and effectiveness in real-time monitoring, making it suitable for improving hygiene management.

CONCLUSION

The wearable incontinence monitoring system was successfully designed and implemented. The system can detect moisture in real time and provide immediate alerts to caregivers.

This improves hygiene, enhances patient comfort, and reduces the burden on caregivers. The project demonstrates a practical and cost-effective solution for incontinence management.

FUTURE IMPROVEMENTS

Future improvements to the system may include:

1. Integration of wireless communication for remote monitoring.
2. Development of a mobile application for alerts.
3. Addition of temperature sensors.
4. Integration of multiple sensors for enhanced functionality.