

If you want to get rid of an idea, please DM the Discord GC to discuss changes

General Design: S bot (no tilt + counter roller)

Drivebase

- 450 RPM
- 4 3.25 inch wheels (all omni)
- 30 Holes long
- 66W
- U-channel funnels on the back, normal funnels on the front
- Possibly 1 hole longer for less tippyness
- 2 full-length C-channel cross brace
- 1 half-length C-channel cross brace (for aligner)
- Low long goal aligner
- Low goal aligner
- 25 wide
- 2 48t idlers
- Max length wing (c channel + 50mm stroke piston)

Intake

- Banded hood with gears
- Traditional S bot front stage intake
- 1 big roller to fixed counterroller (grant geo)
- Piston down hood (psu banded hood?)
- Exponential middle goal scoring speed
- Pistoned up preroller
- Poly lifting front stage if needed for air

Scraper

- L channel scraper
 - Surgeried so it has like ramps at the front to go under balls
- Possible 5 wide surgery c channel mounted backwards
- Mounted 0.25 inches above the drivebase at the front
- 75mm stroke piston
 - U can use a 50mm here (ONLY IF PISTON CAN BE MOUNTED AT GOOD ANGLE)
- Rotating plastic with 7700R ziptie geo
- Banded back under the scraper plastic

Poly Distribution -

- 4 structure
- 2 sleds
- 1 scraper
- 2 wing aligner
- 1 long goal aligner
- 1 horizontal odometry pod

Poly Distribution - hs long goal aligner

- 4 structure
- 2 sleds
- 1 scraper
- 2 wing aligner
- 2 mid goal aligner
- 1 horizontal odometry pod