

## Discussion Session 05

Claudio Parra

University of California

*parraca@uci.edu*

October 29, 2018

# Previously

## QEMU

- ▶ Download (git clone)
- ▶ Configure
- ▶ Compile
- ▶ Install
- ▶ Modify \$PATH

## Xv6

- ▶ Download (git clone)
- ▶ Compile

```
make qemu-nox
```

- ▶ What are we doing? telling the tool make to read the Makefile script and run the target `qemu-nox`
- ▶ Possible error: `qemu` is not in the path.




Figure: `make qemu-nox`

```
make qemu-nox-gdb
```

- ▶ What are we doing? telling the tool make to read the Makefile script and run the target `qemu-nox-gdb`
- ▶ Possible error: `qemu` is not in the path.




Figure: `make qemu-nox-gdb`

## gdb

- ▶ From the folder where you compiled Xv6, we simply run `gdb`. It should notice the connection that `qemu` has.
- ▶ Possible error:

```
warning: File "/home/.../xv6/.gdbinit" auto-loading has  
been declined by your 'auto-load safe-path' set to  
"$debugdir:$datadir/auto-load".
```

To enable execution of this file add

```
add-auto-load-safe-path /home/.../xv6/.gdbinit  
line to your configuration file "/home/user/.gdbinit".
```

To completely disable this security...




Figure: gdb