

Microeconometrics

Week 1 - Introduction to R

Joshua D. Merfeld
KDI School

2023-08-17

Goal for today

- ▶ The goal for today is to give you a brief introduction to R and R Markdown
- ▶ We will be using two small datasets to get you familiar with the program
 - ▶ Class website
- ▶ A note: if you are completely new to R, the first few weeks will be a slog
 - ▶ It will get better, I promise
- ▶ Much of the material covered today comes from two (free!) sources:
 - ▶ R for Data Science
 - ▶ R Markdown: The Definitive Guide


What are R and RStudio?

- ▶ R is a commonly used statistical program (and language)
 - ▶ It is free and open source, which means you can use this after graduation, without paying for it
 - ▶ R is CaSe SeNsItIvE
- ▶ To work with R, we want to use an accompaniment called RStudio
 - ▶ RStudio is what is referred to as an integrated development environment (IDE)
 - ▶ It is not the only option (I use VS Code, for example), but it is the most common
 - ▶ It makes working with R much easier
- ▶ Whenever you start R, you want to start RStudio
 - ▶ RStudio will start R for you


Some important considerations

- ▶ One of our goals is to make **reproducible** research
 - ▶ This means that we want to be able to share our code and have others be able to replicate our results
 - ▶ To do this, we will use “scripts” that contain our code
- ▶ A script should be self contained
 - ▶ This means that it should contain all of the code necessary to run the analysis
 - ▶ A well-written script should allow me to do everything without any additional information
- ▶ We will also use R Markdown to create documents
 - ▶ R Markdown is a way to combine text and code
 - ▶ This allows us to create documents that are reproducible
 - ▶ We will use R Markdown to create our homework assignments
 - ▶ More on this in a bit


The RStudio interface




The RStudio interface



The RStudio interface




The RStudio interface




This is the console. Output appears here. (You can also use this as a calculator!)

But we're missing something... what is it?

But we're missing something... what is it?



The script



- ▶ You can add comments to your script using a hashtag (#)
 - ▶ At the top of ALL my scripts, I have a comment that says what the script does.
 - ▶ At the top of your script, write a comment. It should say “# Week 1 - Introduction to R”
 - ▶ I put LOTS of comments in my scripts. This is good practice.
- ▶ You can run a line of code by clicking the “Run” button
 - ▶ There are also shortcuts. On Mac it is command + enter. On windows it is control + enter. You can change these if you want.
- ▶ You can run multiple lines of code by highlighting them and clicking the “Run” button (or the shortcut)
- ▶ We will practice these later

- ▶ R has a few different types of objects
 - ▶ The most common are vectors, matrices, and data frames
 - ▶ A “tibble” is a type of data frame used by the tidyverse package (more below)
 - ▶ We will use data frames almost exclusively since we are working with datasets, but vectors are common, too
- ▶ You can create a vector using the `c()` function:
 - ▶ Note how we create a new object using the assignment operator, `<-`. You can also use `=`.

```
vec <- c(1, 2, 3, 4)
vec
```

```
## [1] 1 2 3 4
```

- ▶ You can check what type of object something is by using the `class()` function
 - ▶ For example, if I want to check what type of object `vec` is, I would write `class(vec)`
 - ▶ Note that the output is “numeric”
 - ▶ This is because `vec` is a vector of numbers
- ▶ If I want to check whether it is a vector, I can write `is.vector(vec)`
 - ▶ Note that the output is `TRUE`

```
vec <- c(1, 2, 3, 4)
class(vec)
```

```
## [1] "numeric"
is.vector(vec)
```

```
## [1] TRUE
```

First things first: the working directory

- ▶ The working directory is the folder that R is currently working in
 - ▶ This is where R will look for files
 - ▶ This is where R will save files
 - ▶ This is where R will create files
- ▶ You can always write out an entire file path, but this is tedious
 - ▶ More importantly, it makes your code less reproducible since the path is specific to YOUR computer
- ▶ One nice thing about R is that the working directory will automatically be where you open the script from
 - ▶ Let's try this. Save your script to a folder on your computer, then open the script from that folder.

First things first: the working directory

The working directory should be where you opened the file from. Check it like this:

```
getwd()
```

```
## [1] "/Users/Josh/Dropbox/KDIS/Classes/applied-microeconometrics/weeks/week1"
```


- ▶ R is a language that is built on packages
 - ▶ Packages are collections of functions that do specific things
 - ▶ R comes with a set of “base” packages that are installed automatically
- ▶ We are going to use one package consistently, called the “tidyverse”
 - ▶ This consists of a set of packages that are designed to work together, with data cleaning in mind

The one exception to always using a script? I install packages in the CONSOLE. You can install packages like this:

```
install.packages("tidyverse")
```

We need to load any R packages we want to use at the very top of the script. You should have a comment on line one, so on line two write:

```
library("tidyverse")
```

This will load the tidyverse package.


- ▶ Go to the class website and download the data for today.
 - ▶ Put it in your WORKING DIRECTORY (where the script is)
- ▶ We will use the `read_csv()` function to load the data
 - ▶ This function is part of the tidyverse package
 - ▶ It will create a data frame
 - ▶ We need to NAME the object (data frame). As before, note the assignment operator (`<-`). You can actually use `=` though.

```
library(tidyverse)

# read in the data
data <- read_csv("data.csv")
```

Objects in memory

The data frame should show up in the upper right hand corner of RStudio.



Objects in memory

Click on the arrow and it will show more information.

The screenshot shows the RStudio interface with three main panels:

- Script Editor:** Contains a script with the following code:

```
1 # Week 1 - Introduction to R
2 library(tidyverse)
3
4 # load data
5 data <- read_csv("data.csv")
6
```
- Environment Panel:** Shows the 'Global Environment' with a variable 'data' of type 'data.frame' (7209 obs. of 10 vari...). A list of variables is shown with their types and ranges:

Variable	Type
\$ res_id	num [..]
\$ ability	num [..]
\$ age	num [..]
\$ educyears	chr [..]
\$ isfarmer	chr [..]
\$ yearsfarming	num [..]
\$ yearsmanagingfarm	num [..]
\$ outsidewage	num [..]
\$ worriedaboutcropprices	chr [..]
\$ worriedaboutcroppyields	chr [..]
- Console:** Shows the output of the script execution:

```
> # load data
> data <- read_csv("data.csv")
Rows: 7209 Columns: 10
— Column specification —
Delimiter: " "
chr (4): educyears, isfarmer, worriedaboutcropprices, worriedaboutcroppyields
dbl (6): res_id, ability, age, yearsfarming, yearsmanagingfarm, outsidewage

Use 'spec()' to retrieve the full column specification for this data.
Specify the column types or set 'show_col_types = FALSE' to quiet this message.
>
```

- ▶ The data frame is a matrix
 - ▶ Each row is an observation and each column is a variables
- ▶ We can also see the names of the columns like this:

```
colnames(data)
```

```
## [1] "res_id"          "ability"          "age"  
## [4] "educyears"       "isfarmer"         "yearsfarming"  
## [7] "yearsmanagingfarm" "outsidewage"      "worriedaboutcropprices"  
## [10] "worriedaboutcrophyields"
```

- This is the kind of thing I might do in the console since it's not really required for the script.

- ▶ Some of you might be used to Stata
- ▶ One big difference between the two is that Stata generally only has one data frame in memory at a time
 - ▶ This means that you can call a variable *without referencing the data frame*
- ▶ In R, if you want to look at a variable, you have to tell R which data frame it is in
 - ▶ This is done with the \$ operator
 - ▶ For example, if I want to look at the variable “age” in the data frame “data”, I would write data\$age
 - ▶ Let’s look at summary statistics for age:

```
summary(data$age)
```

```
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.   
##    18.00   34.00   42.00   43.54   52.00   87.00
```


Summary statistics for the entire data frame

- ▶ You can also use summary on the data frame instead of a single column
 - ▶ It helps to think of a data frame as rows and columns. For variables, you want to call specific columns.
- ▶ Look at the difference here (it cuts off because of the size of the slide):

```
summary(data)
```

```
##      res_id      ability      age      educyears
## Min.   : 501    Min.    : 10.00   Min.    :18.00   Length:7209
## 1st Qu.:2783    1st Qu.: 51.00   1st Qu.:34.00   Class :character
## Median :4714    Median : 59.00   Median :42.00   Mode  :character
## Mean   :4775    Mean    : 58.66   Mean    :43.54
## 3rd Qu.:6764    3rd Qu.: 67.00   3rd Qu.:52.00
## Max.   :8955    Max.    :100.00   Max.    :87.00
##
##      isfarmer      yearsfarming      yearsmanagingfarm      outsidewage
## Length:7209      Min.    :~-9.00      Min.    :~-9.00      Min.    :2.000e+03
## Class :character  1st Qu.:18.00      1st Qu.: 6.00      1st Qu.:3.500e+06
## Mode  :character  Median :26.00      Median :14.00      Median :1.000e+10
##                      Mean    :28.02      Mean    :15.94      Mean    :7.156e+09
##                      3rd Qu.:38.00      3rd Qu.:22.00      3rd Qu.:1.000e+10
##                      Max.    :70.00      Max.    :70.00      Max.    :1.000e+10
##                      NA's    :219       NA's    :219       NA's    :216
## worriedaboutcropprices worriedaboutcrophyields
## Length:7209      Length:7209
## Class :character  Class :character
## Mode  :character  Mode  :character
##
```

Calling rows/columns of a data frame (matrix)

- ▶ Think about how we refer to rows and columns in a matrix.
 - ▶ We use the row and column number, in that order.
 - ▶ For example, if I want the first row and second column of a matrix X , mathematically I could write $X_{1,2}$
- ▶ We do *the same thing in R*
- ▶ If I want the first row and second column of the data frame “data”, I would write `data[1,2]`
 - ▶ Note that we use square brackets instead of parentheses
 - ▶ Note that we use a comma to separate the row and column

```
data[1,2]
```

```
## # A tibble: 1 x 1
##   ability
##   <dbl>
## 1      74
```

Calling columns of a data frame (matrix)

- ▶ We can call entire columns of a data frame by leaving the row blank
 - ▶ For example, if I want the second column of the data frame “data”, I would write `data[,2]`
 - ▶ Note that the second column is the ability variable

```
colnames(data)
```

```
## [1] "res_id"          "ability"          "age"
## [4] "educyears"       "isfarmer"         "yearsfarming"
## [7] "yearsmanagingfarm" "outsidewage"      "worriedaboutcropprices"
## [10] "worriedaboutcropyield"
```

```
data[,2]
```

```
## # A tibble: 7,209 x 1
##   ability
##   <dbl>
## 1     74
## 2     42
## 3     67
## 4     54
## 5     57
## 6     72
## 7     51
## 8     65
## 9     54
## 10    24
## # i 7,199 more rows
```

Missing variables R

- ▶ Missing variables are denoted by NA
 - ▶ This is different from Stata, which uses a period (.)
- ▶ Note that this is only how the PROGRAM stores missing variables. Sometimes the data itself has different missing values. **PAY ATTENTION!**
- ▶ For example, take a look at the first ten rows of the data frame (also note how I call the first ten rows and leave out the first column!):

```
data[1:10,-1]
```

```
## # A tibble: 10 x 9
##   ability age educyears isfarmer yearsfarming yearsmanagingfarm outsidewage
##   <dbl> <dbl> <chr>    <chr>          <dbl>          <dbl>      <dbl>
## 1     74   83 16      Yes             60             46      3000000
## 2     42   27 7       Yes             17             17     999999999
## 3     67   49 7       Yes             20              5      6000000
## 4     54   50 7       Yes             15             10     999999999
## 5     57   70 4       Yes             40             26     999999999
## 6     72   45 7       Yes             15             15      800000
## 7     51   58 7       Yes             30             25     2000000
## 8     65   41 7       Yes             20             15     999999999
## 9     54   45 7       Yes             20             10      300000
## 10    24   70 <NA>      Yes             60             50     999999999
## # i 2 more variables: worriedaboutcropprices <chr>,
## #   worriedaboutcropyields <chr>
```

- ▶ R also has a few different types of variables
 - ▶ The most common are numeric, character, and logical
- ▶ Look at the previous code again:

```
data[1:10,-1]
```

```
## # A tibble: 10 x 9
##   ability age educyears isfarmer yearsfarming yearsmanagingfarm outsidewage
##   <dbl> <dbl> <chr>      <chr>          <dbl>          <dbl>          <dbl>
## 1     74    83 16      Yes             60             46      3000000
## 2     42    27 7       Yes             17             17     999999999
## 3     67    49 7       Yes             20              5      6000000
## 4     54    50 7       Yes             15             10     999999999
## 5     57    70 4       Yes             40             26     999999999
## 6     72    45 7       Yes             15             15      800000
## 7     51    58 7       Yes             30             25     2000000
## 8     65    41 7       Yes             20             15     999999999
## 9     54    45 7       Yes             20             10      300000
## 10    24    70 <NA>      Yes             60             50     999999999
## # i 2 more variables: worriedaboutcropprices <chr>,
## #   worriedaboutcrophyields <chr>
```

- ▶ dbl is short for double, which is a numeric variable (the “type” of numeric variable is about how much memory is needed to store it)
- ▶ chr is short for character, which is a string of characters (text)
 - ▶ Surprisingly, in our previous example, educyears was a character string even though it seemed to be a number
 - ▶ Let’s look at the possible values of educyears using the unique() function, which outputs a vector:

```
unique(data$educyears)
```

```
## [1] "16"      "7"        "4"        NA
## [5] "11"      "6"        "13"       "5"
## [9] "8"       "10"       "12"       "9"
## [13] "2"       "3"        "15"       "14"
## [17] "20"      "18"       "17"       "1"
## [21] "Not Mentioned" "19"
```

- ▶ Interesting! It seems that there is a “Not Mentioned” value.
 - ▶ What if we want to replace those with missing, instead?
- ▶ Let’s talk through the following code
 - ▶ First note how it refers to a specific column and then a specific row
 - ▶ Also note how it uses two equal signs (==) to check whether the value is “Not Mentioned”
 - ▶ This is similar to Stata!

```
# replace "Not Mentioned" with NA
data$educyears[data$educyears == "Not Mentioned"] <- NA
# check that it worked by looking at the unique values
unique(data$educyears)
```

```
## [1] "16" "7" "4" NA "11" "6" "13" "5" "8" "10" "12" "9" "2" "3" "15"
## [16] "14" "20" "18" "17" "1" "19"
```

```
# turn into numeric
data$educyears <- as.numeric(data$educyears)
class(data$educyears)
```

```
## [1] "numeric"
```

- ▶ One of the most useful things in R is the pipe operator (`%>%`)
 - ▶ This is part of the tidyverse package
 - ▶ It allows you to chain commands together
 - ▶ It makes your code much easier to read
 - ▶ It makes your code much easier to write
 - ▶ It makes your code much easier to debug
 - ▶ It makes your code much easier to share
 - ▶ It makes your code much easier to reproduce
- ▶ It's easy to use but it will take some time for you to get used to the names of the functions we can use with it
 - ▶ This also goes for other tasks in R, not just with the pipe operator

Here is an example of how we can use pipes with the `mutate()` function in tidyverse

- We are also going to use `ifelse()` to make this work

```
data <- data %>%  
  mutate(educyears = ifelse(educyears == "Not Mentioned", NA, educyears), # if educyears=="Not Mentioned", replace  
    educyears = as.numeric(educyears)) # replace educyears as numeric (instead of character)  
summary(data$educyears)
```

```
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.     NA's  
##      1.000   7.000   7.000   6.735   7.000  20.000    3113
```

Pipes example

Here is an example of how we can use pipes with the `mutate()` function in tidyverse

- We are also going to use `ifelse()` to make this work

```
data <- data %>%  
  mutate(educyears = ifelse(educyears == "Not Mentioned", NA, educyears), # if educyears=="Not Mentioned", replace  
    educyears = as.numeric(educyears)) # replace educyears as numeric (instead of character)  
summary(data$educyears)
```

```
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.   NA's  
##      1.000   7.000   7.000   6.735   7.000  20.000   3113
```

Note that we could wrap `as.numeric()` around the `ifelse()` command to do it on one line!

```
data <- data %>%  
  mutate(educyears = as.numeric(ifelse(educyears == "Not Mentioned", NA, educyears))) # wrapped into one line  
summary(data$educyears)
```

```
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.   NA's  
##      1.000   7.000   7.000   6.735   7.000  20.000   3113
```

In Stata, by default, functions ignore missing values

- ▶ R does not do this by default. Look at this:

```
data <- data %>%  
  mutate(educyears = as.numeric(ifelse(educyears == "Not Mentioned", NA, educyears))) # wrapped into one line  
mean(data$educyears)
```

```
## [1] NA
```

If there are any missing values, the function will evaluate to missing!

- ▶ But we can also do this:

```
data <- data %>%  
  mutate(educyears = as.numeric(ifelse(educyears == "Not Mentioned", NA, educyears))) # wrapped into one line  
mean(data$educyears, na.rm = TRUE) # BE CAREFUL WITH THIS! Make sure it is indeed what you want to do.
```

```
## [1] 6.735107
```

The `mean()` function in the previous slide outputs a single value - That means we could store that value as an object:

```
data <- data %>%  
  mutate(educyears = as.numeric(ifelse(educyears == "Not Mentioned", NA, educyears))) # wrapped into one line  
meaneduc <- mean(data$educyears, na.rm = TRUE)  
sdeduc <- sd(data$educyears, na.rm = TRUE)  
meaneduc
```

```
## [1] 6.735107
```

```
sdeduc
```

```
## [1] 2.404086
```

How is this helpful? We can use these values later in our script!

Functions and mutate()

We can combine the `mean()` and `sd()` functions within `mutate` to create a new, standardized variable:

```
data <- data %>%  
  mutate(educyears = as.numeric(ifelse(educyears == "Not Mentioned", NA, educyears)), # wrapped into one line  
         educyears_std = (educyears - mean(educyears))/sd(educyears))  
summary(data$educyears_std)
```

```
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.   NA's  
##       NA       NA       NA     NaN     NA     NA    7209
```

Oh no! what happened?

Functions and mutate()

We can combine the `mean()` and `sd()` functions within `mutate` to create a new, standardized variable:

```
data <- data %>%  
  mutate(educyears = as.numeric(ifelse(educyears == "Not Mentioned", NA, educyears)), # wrapped into one line  
         educyears_std = (educyears - mean(educyears, na.rm = T))/sd(educyears, na.rm = T))  
summary(data$educyears_std)
```


```
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.   NA's  
## -2.3856  0.1102   0.1102   0.0000  0.1102   5.5176   3113
```

Note that we can shorten TRUE to T (or FALSE to F).

- ▶ ggplot2 is a flexible way to create visualizations in R
- ▶ The basic idea is that you create a plot object and then add layers to it
- ▶ Let's create a histogram of educyears

Visualizations with ggplot2


```
data <- data %>%  
  mutate(educyears = as.numeric(ifelse(educyears == "Not Mentioned", NA, educyears)))  
# we call ggplot() and NOT ggplot2()  
ggplot() + # note how we use + here, NOT the pipe operator  
  geom_histogram(data = data, aes(x = educyears)) # the histogram with geom_histogram
```



```
# data = data tells R to use the data frame "data", and the aes() is the aesthetic  
# only an x value here since a histogram uses just a SINGLE value
```



Visualizations with ggplot2

```
data <- data %>%  
  mutate(educyears = as.numeric(ifelse(educyears == "Not Mentioned", NA, educyears)))  
# we can save the plot as an object  
g1 <- ggplot() +  
  geom_histogram(data = data, aes(x = educyears))  
g1
```




Visualizations with ggplot2

```
data <- data %>%  
  mutate(educyears = as.numeric(ifelse(educyears == "Not Mentioned", NA, educyears)))  
# lots of ways to change the plot  
g1 <- ggplot() +  
  geom_histogram(data = data, aes(x = educyears)) +  
  labs(title = "Histogram of educyears",  
       x = "Years of education",  
       y = "Count")  
g1
```



One more example

```
data <- data %>%  
  mutate(educyears = as.numeric(ifelse(educyears == "Not Mentioned", NA, educyears)))  
g1 <- ggplot() +  
  geom_histogram(data = data, aes(x = educyears)) +  
  labs(title = "Histogram of educyears",  
       x = "Years of education",  
       y = "Count") +  
  theme_minimal()  
g1
```



Let's try this with a NEW dataset

First install a new package that has a dataset we will use (you can do this in the console):

```
install.packages("nycflights13")
```

Now let's see:

```
library(nycflights13)
glimpse(flights)
```

```
## Rows: 336,776
## Columns: 19
## $ year      <int> 2013, 2013, 2013, 2013, 2013, 2013, 2013, 2013, 2013, 2~
## $ month     <int> 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1~
## $ day       <int> 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1~
## $ dep_time  <int> 517, 533, 542, 544, 554, 554, 555, 557, 557, 558, 558, ~
## $ sched_dep_time <int> 515, 529, 540, 545, 600, 558, 600, 600, 600, 600, 600, ~
## $ dep_delay <dbl> 2, 4, 2, -1, -6, -4, -5, -3, -3, -2, -2, -2, -2, -2, -1~
## $ arr_time  <int> 830, 850, 923, 1004, 812, 740, 913, 709, 838, 753, 849, ~
## $ sched_arr_time <int> 819, 830, 850, 1022, 837, 728, 854, 723, 846, 745, 851, ~
## $ arr_delay <dbl> 11, 20, 33, -18, -25, 12, 19, -14, -8, 8, -2, -3, 7, -1~
## $ carrier   <chr> "UA", "UA", "AA", "B6", "DL", "UA", "B6", "EV", "B6", "~
## $ flight    <int> 1545, 1714, 1141, 725, 461, 1696, 507, 5708, 79, 301, 4~
## $ tailnum   <chr> "N14228", "N24211", "N619AA", "N804JB", "N668DN", "N394~
## $ origin    <chr> "EWR", "LGA", "JFK", "JFK", "LGA", "EWR", "EWR", "LGA", ~
## $ dest      <chr> "IAH", "IAH", "MIA", "BQN", "ATL", "ORD", "FLL", "IAD", ~
## $ air_time  <dbl> 227, 227, 160, 183, 116, 150, 158, 53, 140, 138, 149, 1~
## $ distance <dbl> 1400, 1416, 1089, 1576, 762, 719, 1065, 229, 944, 733, ~
## $ hour      <dbl> 5, 5, 5, 5, 6, 5, 6, 6, 6, 6, 6, 6, 6, 6, 5, 6, 6, 6~
```

Let's look at some new tidyverse functions

Let's get the average departure delay by NYC airport:

```
flights %>%  
  group_by(origin) %>% # this groups ROWS based on their origin value  
  summarize(avg_dep_delay = mean(dep_delay, na.rm = T)) # this summarizes the data, creating means absed on the grouping!
```



```
## # A tibble: 3 x 2  
##   origin avg_dep_delay  
##   <chr>      <dbl>  
## 1 EWR          15.1  
## 2 JFK          12.1  
## 3 LGA          10.3
```

Note that this does not create a single value. Instead it creates a tibble (a data frame) summarizing the data by our grouping variable.

Let's look at some new tidyverse functions

What if we want to save that tibble instead?

```
summat <- flights %>%  
  group_by(origin) %>% # this groups ROWS based on their origin value  
  summarize(avg_dep_delay = mean(dep_delay, na.rm = T)) # this summarizes the data, creating means based on groups!  
summat # print the 3x2 matrix in the console
```

```
## # A tibble: 3 x 2  
##   origin avg_dep_delay  
##   <chr>      <dbl>  
## 1 EWR          15.1  
## 2 JFK          12.1  
## 3 LGA          10.3
```


I could then output this to a table if I wanted to (using Markdown, more on this later):

origin	avg_dep_delay
EWR	15.10795
JFK	12.11216
LGA	10.34688

Let's look at a new plot

How does departure delay vary by time of day?


```
ggplot() +  
  geom_smooth(data = flights, aes(x = sched_dep_time, y = dep_delay))
```



Let's look at a new plot


We can color code by origin, too!

```
ggplot() +  
  geom_smooth(data = flights, aes(x = sched_dep_time, y = dep_delay, color = origin))
```



Make it prettier

```
ggplot() +  
  geom_smooth(data = flights, aes(x = sched_dep_time, y = dep_delay, color = origin), se = FALSE) +  
  labs(x = "Scheduled departure time",  
       y = "Departure delay (minutes)") +  
  theme_minimal() + guides(color = guide_legend(title = "Departure airport"))
```




What is R Markdown?

- ▶ R Markdown is a way to combine text and code
 - ▶ This allows us to create documents that are reproducible
 - ▶ We will use R Markdown to create our homework assignments
- ▶ These slides were all created in R Markdown
- ▶ My papers are written in R Markdown (well, some of them are, anyway)
 - ▶ **Here** is an example
- ▶ Yihui Xie, J. J. Allaire, and Garrett Grolemund have an awesome – free! – resource on R Markdown, **R Markdown: The Definitive Guide**

You'll need to install R Markdown. You can do this in the console:

```
install.packages("rmarkdown")
```

Creating an R Markdown document in RStudio



Creating an R Markdown document in RStudio

The screenshot shows the RStudio interface with the 'New R Markdown' dialog box open. The dialog box has four tabs: 'Document', 'Presentation', 'Shiny', and 'From Template'. The 'Document' tab is selected. The 'Title' field is 'Untitled', the 'Author' field is empty, and the 'Date' field is '2023-08-14'. There is a checkbox for 'Use current date when rendering document' which is unchecked. Under 'Default Output Format', there are three radio buttons: 'HTML' (selected), 'PDF', and 'Word'. The 'HTML' option is described as 'Recommended format for authoring (you can switch to PDF or Word output anytime)'. The 'PDF' option is described as 'PDF output requires TeX (MiKTeX on Windows, MacTeX 2013+ on OS X, TeX Live 2013+ on Linux)'. The 'Word' option is described as 'Previewing Word documents requires an installation of MS Word (or Libre/Open Office on Linux)'. At the bottom of the dialog box are 'Create Empty Document', 'OK', and 'Cancel' buttons.


The R console output shows the following commands and results:

```
> # load data
> data <- read_csv("data.csv")
Rows: 7209 Columns: 10
— Column specification
Delimiter: ","
chr (4): educyears, isfarmer, worriedaboutcropprices, worriedaboutcroppields
dbl (6): res_id, ability, age, yearsfarming, yearsmanagingfarm, outsidewage

Use 'spec()' to retrieve the full column specification for this data.
Specify the column types or set 'show_col_types = FALSE' to quiet this message.
>
```

The Environment pane on the right shows the 'data' object with 7209 observations and 10 variables. The variables are: res_id (num), ability (num), age (num), educyears (chr), isfarmer (chr), yearsfarming (num), yearsmanagingfarm (num), outsidewage (num), worriedaboutcropprices (chr), and worriedaboutcroppields (chr). The Files pane on the right shows the project structure, including 'assets', 'data.csv', 'header.tex', 'script.R', 'week1a.log', 'week1a.pdf', 'week1a.Rmd', 'week1b.Rmd', and 'week1b.pdf'.

Creating an R Markdown document in RStudio



The screenshot displays the RStudio interface with a new R Markdown document titled 'Untitled1'. The editor shows the following R code and Markdown text:

```
1 <---
2 title: "Example script"
3 output: pdf_document
4 date: "2023-08-14"
5 <---
6
7 ```{r setup, include=FALSE}
8 knitr::opts_chunk$set(echo = TRUE)
9 ```
10
11 ## R Markdown
12
13 This is an R Markdown document. Markdown is a simple formatting syntax for authoring HTML, PDF, and MS Word documents. For more details on using R Markdown see
14 <http://rmarkdown.rstudio.com>.
15
16 When you click the **Knit** button a document will be generated that includes both content as well as the output of any embedded R code chunks within the
17 document. You can embed an R code chunk like this:
18
19 ```{r cars}
20 summary(cars)
21 ```
```

The console shows the output of the R code chunk:

```
R 4.2.3 ~./Dropbox/KDIS/Classes/applied-microeconomics/weeks/week1/
> # load data
> data <- read_csv("data.csv")
Rows: 7209 Columns: 10
- Column specification
Delimiter: ","
chr (4): educyears, isfarmer, worriedaboutcropprices, worriedaboutcrophyields
dbl (6): res_id, ability, age, yearsfarming, yearsmanagingfarm, outsidewage

Use 'spec()' to retrieve the full column specification for this data.
Specify the column types or set 'show_col_types = FALSE' to quiet this message.
>
```

The Environment pane on the right shows the data loaded into the 'data' object, with 7209 observations and 10 variables:

Variable	Type
res_id	num
ability	num
age	num
educyears	num
isfarmer	chr
yearsfarming	num
yearsmanagingfarm	num
outsidewage	num
worriedaboutcropprices	chr
worriedaboutcrophyields	chr

The Files pane on the right shows the project structure, including the 'data.csv' file and the generated R Markdown document 'week1.Rmd'.

- ▶ Go ahead and save this document in your working directory.
 - ▶ One think about Markdown files is that it will ALWAYS set the working directory to where the file is saved whenever you “knit” the document.
- ▶ What is “knitting”?
 - ▶ Knitting is the process of turning your R Markdown document into a pdf, html, or word document.
 - ▶ We will just focus on pdfs for now.

The screenshot shows the RStudio interface. In the top toolbar, the 'Knit' button (represented by a document icon with a circular arrow) is highlighted with a white arrow. A text box next to it says 'Knit by clicking here and selecting pdf'. The main editor window displays an R Markdown document with the following content:

```
1 ---
2 title: "Example script"
3 output: pdf_document
4 date: "2023-08-14"
5 ---
6
7 {r setup, include=FALSE}
8 knitr::opts_chunk$set(echo = TRUE)
9
10 ## R Markdown
11
12 This is an R Markdown document. Markdown is a simple formatting syntax for authoring HTML, PDF, and MS Word documents. For more details on using R Markdown see
13 <http://rmarkdown.rstudio.com>.
14
15 When you click the **Knit** button a document will be generated that includes both content as well as the output of any embedded R code chunks within the
16 document. You can embed an R code chunk like this:
17
18 {r cars}
19 summary(cars)
20
```

The console window at the bottom shows the output of the R code chunk:

```
R 4.2.3 ~:/Dropbox/KDIS/Classes/applied-microeconomics/weeks/week1/
> # load data
> data <- read_csv("data.csv")
Rows: 7209 Columns: 10
— Column specification —
Delimiter: ","
chr (4): educyears, isfarmer, worriedaboutcropprices, worriedaboutcrophyields
dbl (6): res_id, ability, age, yearsfarming, yearsmanagingfarm, outsidewage

Use 'spec()' to retrieve the full column specification for this data.
Specify the column types or set 'show_col_types = FALSE' to quiet this message.
>
```

The right-hand pane shows the 'Environment' tab with a table of variables:

Variable	Class	Length
\$ res_id	num	[-]
\$ ability	num	[-]
\$ age	num	[-]
\$ educyears	chr	[-]
\$ isfarmer	chr	[-]
\$ yearsfarming	num	[-]
\$ yearsmanagingfarm	num	[-]
\$ outsidewage	num	[-]
\$ worriedaboutcropprices	chr	[-]
\$ worriedaboutcrophyields	chr	[-]
- attr(*, "spec")=		
.. cols(
.. res_id = col_double(),		

The 'Files' pane on the right shows a directory structure with files like 'data.csv', 'header.tex', 'script.R', 'week1a.log', 'week1a.pdf', 'week1a.Rmd', 'week1b.Rmd', and 'week1b.pdf'.

Check out the document you just created

- ▶ Go to your working directory and open the pdf to see what it looks like.
 - ▶ It will always create the pdf in the same folder as the .Rmd file.

- ▶ At the very top of the document is some information about the document
 - ▶ This is called the YAML header
 - ▶ It tells R Markdown what kind of document to create
 - ▶ It also allows you to set some options
 - ▶ DO NOT DELETE THE — AT THE TOP AND BOTTOM OF THE YAML HEADER!
- ▶ You can change the title and date as you please
 - ▶ For today's date, you can use `Sys.Date()` within R inline code (more in a second):

```
date: "`r Sys.Date()`"
```

The setup chunk

- ▶ Just below the YAML header you'll see a "code chunk" called "setup" (r setup, include = FALSE)
- ▶ Note how it has "" and "" at the top and bottom. This differentiates the "code chunk" from the rest of the document.
 - ▶ Whenever you want to add a code chunk, you *must* have the "" at the top and bottom of it, at the beginning of the line.
- ▶ Use the setup code chunk to load any packages or data that you want to use in the rest of the document.
 - ▶ Later code chunks are "local": they will be able to access things from the setup chunk *but not from other code chunks*.

The setup chunk

This is an example of what the setup chunk looks like.

```
```{r setup, include=FALSE}  
universal chunk options.
echo = TRUE will show the code in the document.
echo = FALSE will not.
knitr::opts_chunk$set(echo = TRUE)

load any packages you want to use throughout the document.
library(tidyverse)

load any data you want to use throughout the document.
data <- read_csv("data.csv")
```
```


Here is an example of a regular code chunk.

```
```{r chunkexample, include = TRUE}  
note that I named the chunk.
all chunks must have a UNIQUE name.
you will get an error if they don't


I already loaded by data above
ggplot(flights) +
 geom_histogram(aes(x = air_time), binwidth = 10)
```
```

Here is the output of that chunk:

```
## Warning: Removed 9430 rows containing non-finite values (`stat_bin()`).
```



Oh no! It looks bad! Changes:



How did I do that?

```
```{r chunkexample, include = TRUE, warning = FALSE, out.width = "55%",  
 fig.align = "center"}
note that I named the chunk.
all chunks must have a UNIQUE name.
you will get an error if they don't

I already loaded by data above
ggplot(flights) +
 geom_histogram(aes(x = air_time), binwidth = 10)
```
```

- NOTE: The start of the chunk must be on ONE line. It is wrapped here just for presentation.

- ▶ There are lots of code chunk options.
- ▶ You can find the code chunk options [here](https://rpubs.com/Lingling912/870659) (https://rpubs.com/Lingling912/870659)
- ▶ This will get easier to use as you get more and more practice.

Starting new sections/subsections

```
# This will create a new section
```

```
## This will create a new sub-section
```

```
### This will create a new sub-sub-section
```

```
Don't do this.
```

You can add R inline code

- ▶ You can add R inline code using the `'r'` operator.
 - ▶ For example, if I want to add the date, I can write `2023-08-17`
 - ▶ There are 19 columns in the flights data.
 - ▶ There are 336776 columns in the flights data.

- You can add R inline code using the `$`r`$` operator.
 - For example, if I want to add the date, I can write `2023-08-17`
 - There are 19 columns in the flights data.
 - There are 336776 columns in the flights data.

- ▶ I like lists.
 - ▶ With indentations.

- 1 Really, I do.
 - 1 Indent! It's just a tab.

““markdown

- ▶ I like lists.
 - ▶ With indentations.

- 1 Really, I do.
 - 1 Indent! It's just a tab. ““

- ▶ R Markdown uses latex to create pdfs. This allows you to do some cool things.
- ▶ For example, it is easy to add equations with latex, using \$:

$$y = x + \varepsilon$$

- For example, it is easy to add equations with latex, using \ \$:

$$\text{\$}y = x + \text{\backslash varepsilon}\text{\$}$$

- I can center it, too:

$$y = x + \varepsilon$$

- I can center it, too:

```
$$y = x + \varepsilon$$
```

$$y = x + \varepsilon \tag{1}$$

- In Equation 1

```
\begin{gather}\label{eq1} y = x + \varepsilon \end{gather}
```

```
- In Equation \autoref{eq1}
```

- You might think, so what? Well what's cool is that if we add equations before it, the number will automatically update!

- ▶ latex is particularly helpful for rendering math
- ▶ You can find a handy reference guide [here](https://icl.utk.edu/~mgates3/docs/latex.pdf)
(<https://icl.utk.edu/~mgates3/docs/latex.pdf>)

- ▶ There are lots of ways to create tables in R Markdown.
 - ▶ I will show you how using the `kable()` function in the `knitr` package.
 - ▶ You do not need to download this package, it is already installed with R Markdown.
 - ▶ There is extra functionality in the `kableExtra` package. You need to download this and load it if you want to use it.

Creating tables

```
summat <- flights %>%  
  # this groups ROWS based on their origin value  
  group_by(origin) %>%  
  # create means by group  
  summarize(avg_dep_delay = mean(dep_delay, na.rm = T),  
            avg_arr_delay = mean(arr_delay, na.rm = T),  
            avg_air_time = mean(air_time, na.rm = T),  
            flights = n())  
  
# output  
kable(summat,  
      align = "cccc")
```

Creating tables

| origin | avg_dep_delay | avg_arr_delay | avg_air_time | flights |
|--------|---------------|---------------|--------------|---------|
| EWR | 15.10795 | 9.107055 | 153.3000 | 120835 |
| JFK | 12.11216 | 5.551481 | 178.3490 | 111279 |
| LGA | 10.34688 | 5.783488 | 117.8258 | 104662 |

I don't like that at all! Let's make it pretty.

```
summat <- flights %>%  
  # this groups ROWS based on their origin value  
  group_by(origin) %>%  
  # create means by group, ROUNDING to two decimal places  
  summarize(avg_dep_delay = round(mean(dep_delay, na.rm = T), 2),  
            avg_arr_delay = round(mean(arr_delay, na.rm = T), 2),  
            avg_air_time = round(mean(air_time, na.rm = T), 2),  
            flights = n())  
  
# rename columns  
colnames(summat) <- c("Origin", "Departure Delay", "Arrival Delay", "Flight Time", "Flights")  
# output  
kable(summat, caption = "Averages by origin (minutes)",  
      align = "ccc", linesep = "",  
      booktabs = TRUE) %>% # this is from kableextra. You don't have to use it, but I like it.  
kable_classic_2() # this is also from kableextra
```

I don't like that at all! Let's make it pretty.

Table 1: Averages by origin (minutes)

| Origin | Departure Delay | Arrival Delay | Flight Time | Flights |
|--------|-----------------|---------------|-------------|---------|
| EWR | 15.11 | 9.11 | 153.30 | 120835 |
| JFK | 12.11 | 5.55 | 178.35 | 111279 |
| LGA | 10.35 | 5.78 | 117.83 | 104662 |

One more change!

```
summat <- flights %>%  
  # this groups ROWS based on their origin value  
  group_by(origin) %>%  
  # create means by group, ROUNDING to two decimal places  
  summarize(avg_dep_delay = round(mean(dep_delay, na.rm = T), 2),  
            avg_arr_delay = round(mean(arr_delay, na.rm = T), 2),  
            avg_air_time = round(mean(air_time, na.rm = T), 2),  
            flights = n())  
summat$flights <- format(summat$flights, big.mark = ",", scientific = FALSE)  
# rename columns  
colnames(summat) <- c("Origin", "Departure Delay", "Arrival Delay", "Flight Time", "Flights")  
summat <- t(summat)  
# output  
kable(summat, caption = "Averages by origin (minutes)",  
      align = "ccc", linesep = "",  
      booktabs = TRUE) %>% # this is from kablextra. You don't have to use it, but I like it.  
  row_spec(c(1, 4), hline_after = TRUE) %>% # this is also from kablextra  
  kable_classic_2() # this is also from kablextra
```

Table 2: Averages by origin (minutes)

| Origin | EWR | JFK | LGA |
|-----------------|---------|---------|---------|
| Departure Delay | 15.11 | 12.11 | 10.35 |
| Arrival Delay | 9.11 | 5.55 | 5.78 |
| Flight Time | 153.30 | 178.35 | 117.83 |
| Flights | 120,835 | 111,279 | 104,662 |

- ▶ That's enough on tables for now
- ▶ As you can see, there are lots of ways to customize tables
- ▶ Where this becomes really powerful is when you combine it with R code to create tables dynamically
 - ▶ I will teach you to use a package called `fixest` that helps automate some of this
 - ▶ If you change your specification, your tables will update **AUTOMATICALLY!**
 - ▶ Ever tried to manually change a table in Word? Never again.

- ▶ When I write a paper in Markdown, I generally do not do all of my analysis in the Markdown document
- ▶ Instead, I do the analysis in another script and then save the resulting tables
- ▶ I then load these tables in the setup chunk of my Markdown document and use them in the document
 - ▶ For figures, it depends. For a simple summary figure, I might load the data in the Markdown document and create the figure there.

- ▶ Assignment for next week (due one week from today):
 - ▶ Create a simple markdown document
 - ▶ You can find the assignment [here](#) (on the [course GitHub page](#))
- ▶ Next week, you will turn in on e-KDIS:
 - ▶ R script (if there is one)
 - ▶ R Markdown script
 - ▶ pdf of the R Markdown document