

```

root@debian:/home/josh/Proyectos_RoR# rails new my_app
  create
  create  README.md
  create  Rakefile
  create  .ruby-version
  create  config.ru
  create  .gitignore
  create  .gitattributes
  create  Gemfile
  run    git init -b main from "."
Inicializado repositorio Git vacío en /home/josh/Proyectos_RoR/my_app/.git/
  create  app
  create  app/assets/config/manifest.js
  create  app/assets/stylesheets/application.css
  create  app/channels/application_cable/channel.rb
  create  app/channels/application_cable/connection.rb
  create  app/controllers/application_controller.rb

```

---

```

root@debian:/home/josh/Proyectos_RoR# cd my_app
root@debian:/home/josh/Proyectos_RoR/my_app# rails s
=> Booting Puma
=> Rails 7.1.3.4 application starting in development
=> Run `bin/rails server --help` for more startup options
Puma starting in single mode...
* Puma version: 6.4.2 (ruby 3.1.2-p20) ("The Eagle of Durango")
* Min threads: 5
* Max threads: 5
* Environment: development
* PID: 4767
* Listening on http://127.0.0.1:3000
* Listening on http://[::1]:3000
Use Ctrl-C to stop
Started GET "/" for 127.0.0.1 at 2024-09-04 09:14:45 -0600

```

```

<h1>Bienvenido </h1>
#<p>Find me in app/views/welcome/index.html.erb</p>

<p>Pagina de inicio</p>
<p>UNAN-León</p>
<h3>Imprimiendo un array Ruby dentro de una vista</h3>

```

---

# Bienvenido

Find me in app/views/welcome/index.html.erb

Pagina de inicio

UNAN-León

```
class WelcomeController < ApplicationController
  def index
    @dia_semana=["Lunes","Martes","Miercoles","Jueves","Viernes","Sabado","Domingo"]
  end
end
```

```
<p>Pagina de inicio</p>
<p>UNAN-León</p>
<h3>Imprimiendo un array Ruby dentro de una vista</h3>
<% @dia_semana.each do |dia| %>
  <%= dia %> <br>
<% end %>
<h3> Método last</h3>
<%= @dia_semana.last %>
<h3>Primer campo de array</h3>
<%= @dia_semana.first %>
<h3>longitud del array</h3>
<%= @dia_semana.length %>
```

## Imprimiendo un array Ruby dentro de una vista

Lunes  
Martes  
Miércoles  
Jueves  
Viernes  
Sábado  
Domingo

### Método last

Domingo

#### Primer campo de array

Lunes

#### longitud del array

7

<b>nombre</b>	Josh
<b>apellido</b>	Pastrana
<b>telefono</b>	57182784
<b>correo</b>	Joshpastrana@gmail.com

```
class HashController < ApplicationController
  def mostrar
    @datosHash={nombre: "Josh", apellido: "Pastrana", telefono: "57182784", correo: "Joshpastrana@gmail.com"}
  end
end
```

```
1 <h1>Hash#mostrar</h1>
2 <p>Find me in app/views/hash/mostrar.html.erb</p>
3 <table>
4 <tr>
5 <th>nombre</th>
6 <td><%= @datosHash[:nombre] %> </td>
7 </tr>
8 <tr>
9 <th>apellido</th>
10 <td><%= @datosHash[:apellido] %> </td>
11 </tr>
12 <tr>
13 <th>telefono</th>
14 <td><%= @datosHash[:telefono] %> </td>
15 </tr>
16 <tr>
17 <th>correo</th>
18 <td><%= @datosHash[:correo] %> </td>
19 </tr>
20 </table>
21
```