

Designing and Testing a Novel Idea Based on Federated Learning: Swarm Learning

Josh Pattman

February 26, 2023

Chapter 1

Problem and Goals

Chapter 2

Literature Review

Chapter 3

Project Management

Chapter 4

Analysis and Specification of the Solution to the Problem

Chapter 5

Detailed Design

5.1 Node

In swarm learning, a node is an agent responsible for facilitating the improvement of the global model. Each node maintains a local model, which is an approximation of the global model that is stored locally. However, the global model is an abstract concept representing of the average of all local models across all nodes. As training progresses and performance approaches a plateau, the global model gradually converges towards each node's local model.

Each node in the network possesses a confidential dataset that is not disclosed to any other nodes. In order to train the global model, nodes fit their own local model of their local dataset. In order to maintain consistency between local and global models, a combination procedure is conducted following each round of local training, which involves the integration of neighbouring nodes' models into the local model.

The steps in each training loop are as follows:

1. Fit local model to local dataset
2. Send local model to all neighbours
3. Combine neighbouring models into local model

In addition, each node retains a local cache of the most recent models of its neighbouring nodes. This cache is updated each time a neighbouring node transmits its model to the node in question, instead of being updated at the instant of the combination step. The reasoning behind this decision is elaborated upon in greater detail in the implementation section.

5.2 No Blockchain

- Neural nets are heuristic - they don't need to be exact
- Its just overhead
- Blockchain can have situations where data is lost (branches) [CHECK VALIDITY OF STATEMENT]
- SL avg more robust against malicious agents than SL bc? [CHECK VALIDITY OF STATEMENT]

5.3 Training Counter

A vital aspect of the swarm learning algorithm, specifically the combination step, involves evaluating the performance of a local model. The conventional approach would involve testing each model using an independent test set. However, due to the inability to exchange test sets among nodes, this approach is not feasible as it would result in non-comparable scores for each model. In order to circumvent this problem, this paper presents a heuristic metric referred to as the "training counter," which serves as an approximation of the level of training of a network by estimating the number of epochs performed on a given model.

The training counter can be changed in one of two manners. Firstly, the counter is incremented by 1 when the local model is trained on the local dataset, indicating that an additional epoch of training has been performed. Following the combination step, the training counter is also updated to reflect the combination method that was utilized. For instance, if the neighbouring models were averaged, the training counter would represent the average of all neighbouring nodes' training counters.

5.4 Model Combination Methods

The combination step is a crucial component of the swarm learning algorithm. During this step, a node merges its local model with those of its neighbours, producing an updated estimate of the global model. This paper presents multiple methods for performing the combination step, which are evaluated in the results section.

In the below equations, $\mu(x)$ denotes the function $mean(x)$, t_x denotes $training_counter_x$, and m_x denotes $model_x$.

5.4.1 Averaging

The most rudimentary approach to combination is to compute the average model between the local model and the models of all neighbouring nodes.

$$m_{local+1} = \mu(\{m_{local}\} \cup m_{neighbours})$$

This technique is utilized in FedAvg, which is the most simplistic form of federated learning. The benefit of this method is that it necessitates no hyper-parameters, which translates to less tuning required by the programmer. However, this attribute can also be viewed as a drawback, as it affords less flexibility in terms of customization for particular tasks.

5.4.2 Averaging With Learning Rate

A more complex approach to combination is to compute the average model of all neighbours, then compute the weighted average between that model and the local model.

$$m_{local+1} = (1 - \alpha) * m_{local} + \alpha * \mu(m_{neighbours})$$

The learning rate, denoted as α , indicates the degree to which each node adjusts its local model to align with the global model. If α is set too low, each node's model in the network will diverge, resulting in each node becoming trapped at a local minima. On the other hand, if α is too high, the progress achieved by a given node will be discarded at each averaging step, which can result in slower learning. The implications of adjusting this parameter are discussed further in the results section.

5.4.3 Filtering By Training Counter

A potential modification to the previously mentioned combination algorithms involves filtering based on the training counter. Specifically, a node may only include its neighbour models if they meet the following statement:

$$t_{neighbour} + \beta \geq t_{local}$$

The training offset β is the amount the training counter of a neighbour can be behind the local training counter before it is ignored. Different values of β are explored in the results section.

An issue with training counter filtering pertains to the presence of runaway nodes. These nodes possess a substantially higher training counter relative to all other nodes in the network, meaning that when filtering is applied, they are left with no neighbours to utilise in the combination step. Consequently, these nodes start to overfit on their own training data, as their model is only exposed to this data, thereby leading to decreased overall performance, as well as potential performance reductions in the rest of the network. To address this problem in the proposed swarm learning algorithm, each node must wait until it has obtained at least γ viable neighbours prior to performing the combination step. Although this measure prevents individual nodes from becoming runaway nodes, groups of size γ still have the potential to become runaway as a unit. Nevertheless, if γ is roughly equivalent to the number of neighbours and all neighbours train at a comparable rate, the issue is minimised.

5.5 Sparse Network Behaviour

5.5.1 Sparse Convergence

- Do nothing, nodes will eventually converge
- If too sparse, will not converge
- Requires no extra data transmission

5.5.2 Sparse Relay

- When recv a model update, check if it is newer than what we already have and is not from us, if it is, ping it to all neighbours
- The whole network acts as if it is dense
- Requires extra transmission

Chapter 6

Implementation

6.1 Dataset and Machine Learning Model

6.1.1 Dataset

6.1.2 Model

6.2 Federated Learning

6.2.1 Algorithm

6.2.2 Backed Distributor

6.2.3 Evaluation

6.3 Prototype

6.3.1 Algorithm

6.3.2 Back-end Distributor

6.3.3 Evaluation

6.4 Final

6.4.1 Algorithm

6.4.2 Back-end Distributor

when using push on train rather than pull on sync, the latest diffs are more preserved

6.4.3 Evaluation

Chapter 7

Testing Strategy and Results

Chapter 8

Critical Evaluation

Chapter 9

Conclusion and Future Work

Chapter 10

References

Chapter 11

Appendices