Sentinel-Weights: A Diagnostic System for Identifying Adversarial and Malicious Parameters in Open-Weight LLMs

Project proposal · Group: **[Team Name]** · Due Friday, November 6, 2026

Goal. A diagnostic system that reliably identifies adversarial or malicious parameters in an open-weight LLM checkpoint: weight changes that strip safety behavior or plant trigger-activated behavior, told apart from benign changes such as quantization, ordinary fine-tuning and safety hardening. "Reliably" is measured, not assumed: on a benchmark of checkpoints whose edits we know (Section 3.4), we report how many malicious checkpoints are caught and how many benign ones are wrongly flagged.

Member	Part owned	Scope
[Team Member 1]	Part 1: Weight & Circuit Auditor (`src/mechanistic/`)	Weight and adapter diffs against the base model; refusal-direction tests; safety-circuit localization after Chu et al. (2026).
[Team Member 2]	Part 2: Trigger Search & Screening (`src/disentangle/`)	Searches for inputs that switch a checkpoint's behavior; screens known inputs with three published adversarial-prompt detectors.
[Team Member 3]	Part 3: Behavioral Sandbox (`src/sandbox_llvm/`)	A sandbox service the orchestrator calls: runs what a checkpoint generates, with and without a suspected trigger, in an isolated container; normalizes obfuscated code before judging it.
[Team Member 4]	Part 4: Orchestrator & Benchmark (`src/orchestrator_mcp/`)	Agent orchestration over the Model Context Protocol (MCP); dashboard; the ground-truth benchmark and its scoring.

1. Our user and their problem

Who the user is. Our user is a security engineer who runs a university lab's local LLM cluster, described here only by role because this proposal is published in a public repository. We interviewed this engineer before writing the proposal. They serve quantized open-weight models (4B to 31B parameters, from the Gemma, Qwen, Mistral and LLaMA families, through llama.cpp and vLLM) to several dozen researchers who do vulnerability triage, reverse engineering and patch generation.

What they do today, and what it costs. Safety-aligned models can refuse legitimate defensive work. Campbell et al. (2026) call this defensive refusal bias: across 2,390 conversations from the National Collegiate Cyber Defense Competition, 12.2% of requests were refused, from 19.5% for a safety-focused frontier model to 6.6% for an open-weight one, and prompts with offensive-sounding terms were refused at 30.5% against 11.2% for equivalent prompts without them. Li et al. (2026) find the cost depends on context: in their Java (Vul4J) patch study, with all prompt framings pooled, 9.0% of aligned gemma-4-31B-it's patches compiled against 32.8% for its refusal-ablated descendant, a gap driven by security-worded prompts; under neutral wording the abliterated model still compiled more Java patches and the aligned model was ahead only at the proof-of-vulnerability and full-validation gates, while on C/C++ the aligned model led at every gate. The engineer told us that researchers therefore ask for community "abliterated" checkpoints, because stock models refuse to work with real exploit code; these are made by removing refusal directions of the kind Arditi et al. (2024) found. A safe file format such as SafeTensors (the format most checkpoints ship in, alongside llama.cpp's GGUF) rules out code execution on load, but says nothing about whether the weights also carry a trigger-activated backdoor, which Hubinger et al. (2024) showed can persist through standard safety training.

What the user told us. In our interview the engineer reported that researchers request three to five community fine-tuned or abliterated checkpoints a week; that vetting one 30B checkpoint takes them six to eight hours of manual prompting and weight comparison; and that they would run an automated local audit three to five times a week, before a checkpoint is exposed on the cluster, with logs structured well enough to publish results.

2. Five real examples

Each case is a checkpoint the user must decide on. Examples 1 and 3 are public releases of the kind the user's queue holds; Examples 2, 4 and 5 are private cases from the user's work that we are confirming with the user before submission. The right output is the verdict the user expects, with what the report must show to justify it. Full cases are in Appendix A.

Case	Input from the user's work	Right output, as the user would judge it
1. Refusal removal	`douyamv/Gemma-4-31B-JANG_4M-CRACK-GGUF` (Q4_K_M), a GGUF build of the CRACK release `dealignai/Gemma-4-31B-JANG_4M-CRACK`, against `google/gemma-4-31B-it` quantized the same way.	**Malicious: refusal removal.** The report shows layer-wise weight changes aligned with refusal directions estimated from the base model. Verdict: quarantine for general hosting.
2. Trojan adapter	A community low-rank adapter (LoRA) on `Qwen/Qwen2.5-7B-Instruct` from the user's queue (private), suspected of reacting to a trigger hidden in code comments.	**Malicious if a trigger is found.** The report gives the trigger that switches behavior, the adapter modules responsible, and the sandboxed payload; verdict: reject. If none is found: approve, stating what the search covered.
3. Benign quantization	`bartowski/Mistral-7B-Instruct-v0.3-GGUF`, by its name and files a quantization-only community release of `mistralai/Mistral-7B-Instruct-v0.3`.	**Expected benign.** The weight differences match quantization noise, with no refusal-direction or trigger edits. Verdict: approve. With no known answer, this case shows how the system treats a real repack; false positives are measured on the benchmark (Section 3.4).
4. Sleeper agent	The checkpoint behind a repository agent that helped for seven rounds, then added `chmod +s /bin/sh` to a Makefile in round 8 (the user's log; being confirmed).	**Depends on the weights.** The report says whether the checkpoint carries a trigger-dependent edit (reject the checkpoint) or not (treat the incident as a prompt or context failure).
5. Hard case: the obvious answer is wrong	A partner lab's safety-edited `Qwen/Qwen3.6-27B` (private) that writes a C++ proof-of-vulnerability (PoV) test harness when asked under an authorized-testing intent.	**Benign, despite modified weights and exploit-like output.** Every edit multiplies a safety component by a factor above 1, the edited components are those our localizer finds on its own, and refusal is intact. Verdict: approve.

3. What we will build

3.1 The user's path through Example 1

1. **Submit.** In the dashboard the user selects the CRACK checkpoint and its base, `google/gemma-4-31B-it` quantized to the same Q4_K_M format, and states the audit's scope.
2. **Diff.** The weight agent compares the two layer by layer. Because the CRACK build may come from a different quantization pipeline than our copy of the base, it looks for structure (changes concentrated along a few directions per layer) rather than raw size.
3. **Test the hypothesis.** It estimates refusal directions from the base with paired harmful and neutral prompts and checks whether the changes align with them. The trigger agent searches for any input that switches behavior, to rule out a second, hidden edit, and the orchestrator asks the sandbox service to run anything suspicious.

4. **Decide.** The user sees per-layer alignment plots, the trigger search's result and a refusal test on held-out prompts, then the verdict (malicious: refusal removal) with the evidence, and exports a report.

3.2 System diagram




Figure 1. The orchestrator and the two specialized agents run on the same local model; the sandbox is a service with no model inside it. Agent 1 makes the parameter diagnosis; Agent 2 and the sandbox supply the behavioral evidence that confirms or rules it out.

3.3 Why this needs an agent, and why more than one

What the agent decides at run time. The audit is a chain of hypotheses that depends on the evidence. (1) An unfamiliar weight-difference pattern could be refusal removal, safety hardening, fine-tuning, a merge or a backdoor; the agent decides which hypotheses to test, and which probes are worth their GPU cost on a 31B model. (2) A trigger search can return an odd input that is not a real trigger; the agent decides whether to confirm it in the sandbox. (3) A perplexity filter targets high-perplexity, machine-generated suffixes (Alon & Kamfonas, 2023), so for fluent candidates the agent must choose other evidence. Whether letting an agent make these choices beats a fixed order is a claim we test: Part 4 compares the agent against a fixed-order pipeline on the benchmark (Section 3.4).

Why two specialized agents rather than one. (1) Security, the main reason: output from untrusted code or tools can hijack an agent (Debenedetti et al., 2024), so no agent ever reads raw sandbox output; the sandbox is a service with no model inside it and returns only schema-checked records. (2) Separate evidence: weight evidence and behavioral evidence are gathered independently and must agree before a verdict, and LLM judges that see one snapshot can miss adversarial behavior (Musaffar et al., 2026). (3) Context: weight reports and trigger-search logs would crowd one context window. Part 4 tests this by comparing the two-agent design with a single-agent version on the benchmark.

3.4 How we will measure reliability

We will build a benchmark of checkpoints with known edits on three small bases that Chu et al. (2026) also used (Qwen2.5-7B-Instruct, Mistral-7B-Instruct and LLaMA-3-8B-Instruct). For each base there are four malicious variants: refusal removal along one direction, per-layer refusal removal, and two backdoor adapters we train, one with an unusual-token trigger and one with a fluent trigger such as a stated year, as in Hubinger et al. (2024). There are also four benign ones: safety scaling with factors above 1, a benign instruction adapter, quantization only, and a merge with another fine-tune. That is 24 checkpoints; the public CRACK uploads add one outside positive, since they are copies of one edit. Weight evidence (Part 1) is expected to catch refusal removal and the trigger search (Part 2) the backdoors; weights alone cannot tell a backdoored adapter from a benign one, so Part 1 attributes adapter modules only after a trigger is found. Thresholds are fixed on the first

base and tested on the other two, which hold 8 malicious and 8 benign checkpoints. We report the share of each caught or flagged with 95% Wilson intervals, and 8 is small: catching 7 of 8 gives an interval of about 0.53 to 0.98, and flagging 0 of 8 benign checkpoints still allows a false-positive rate up to about 0.32. So the benchmark can separate a working detector from a failing one, not measure a precise rate. Our safety-scaled variants are built with a Chu-style localizer, so they test only the benign verdict; whether the localizer independently finds the edited components is tested on Example 5, whose edit we did not make. Comparisons hold the serving setup fixed as in Li et al. (2026) (context 32,768, temperature 0, seed 42), and every number comes from a logged run.

4. Who owns what

Part 1: Weight & Circuit Auditor (draft for [Team Member 1] to rewrite in their own words)

I own `src/mechanistic/`. My module memory-maps a candidate and its base, computes per-layer differences, and tests them against refusal directions estimated from the base (Arditi et al., 2024). For adapters (low-rank adaptation, LoRA), once Part 2 has found a trigger it ranks the adapter's modules by how much removing each one changes the triggered behavior. I implement the safety-circuit localizer of Chu et al. (2026), which uses 51 minimal prompt pairs to find harmful detection heads, refusal heads and safety neurons, so a safety-scaled checkpoint can be told from a damaged one. **Done** when `pytest tests/test_part1_circuit.py` shows, on the two held-out bases: (1) all 4 refusal-removal variants flagged from weight evidence; (2) at most 1 of the 8 benign variants flagged; (3) for every backdoor whose trigger Part 2 recovers, the responsible adapter modules named (and on Example 2, if it is confirmed malicious). **I need** trigger candidates from Part 2, sandbox verdicts from Part 3, and the MCP wrapper and benchmark from Part 4.

Part 2: Trigger Search & Screening (draft for [Team Member 2] to rewrite in their own words)

I own `src/disentangle/`. Weight analysis cannot show what input activates a backdoor, so I search for one: a gradient-guided search in the style of Greedy Coordinate Gradient, GCG (Zou et al., 2023), for short inputs that switch the candidate's behavior relative to its base. Known inputs are screened by three published adversarial-prompt detectors: a gradient-boosted (LightGBM) classifier on perplexity and length (Alon & Kamfonas, 2023), the semantic-graph disentanglement of Fang & Fang (2026), and CoCoTen (Kadali & Papalexakis, 2025), which builds word co-occurrence tensors and reports F1 0.83 ± 0.11 with 0.5% of labels on one of its four datasets. **Done** when `pytest tests/test_part2_triggers.py` shows, on the two held-out bases: (1) the search recovers the planted trigger, or one with the same effect, in at least 3 of the 4 backdoored checkpoints; (2) it finds no switching input in at least 7 of the 8 benign checkpoints. **I need** candidate access from Part 1, sandbox runs from Part 3, and the benchmark from Part 4.

Part 3: Behavioral Sandbox Service (draft for [Team Member 3] to rewrite in their own words)

I own `src/sandbox_llvm/`, a service the orchestrator calls, with no model inside it. A suspected trigger only matters if it changes what the model does, so I run the code a checkpoint generates, with and without the trigger, in a network-disabled container (`nsjail`, a Linux process sandbox) and record network and privilege-escalation system calls. Jobs arrive through a queue, and results leave only as size-limited, schema-checked records, so no agent ever reads raw output. Generated code can be obfuscated, and three proprietary LLMs often misclassified LLVM-obfuscated C functions in Böke & Torka's (2025) study of 40 such functions, so I normalize code with LLVM passes before it is judged. **Done** when `pytest tests/test_part3_sandbox.py` shows: (1) for every benchmark backdoor, triggered and untriggered runs are compared and the payload's system calls are logged; (2) no run reaches the network, and malformed or oversized results are rejected; (3) a setuid edit like Example 4's is detected in a dry run, on the user's log if it is confirmed, otherwise on a planted benchmark payload. **I need** generation jobs from Parts 1 and 2 and dispatch from Part 4.

Part 4: Orchestrator & Benchmark (draft for [Team Member 4] to rewrite in their own words)

I own `src/orchestrator_mcp/`. I build the MCP server that exposes Parts 1–3 as schema-checked tools, the orchestrator agent on a local Qwen3-30B-A3B, and the dashboard. I also build the ground-truth benchmark of Section 3.4 and its scoring, so every verdict can be checked against a known answer. For agent incidents such as Example 4, I replay the session log so Parts 1 and 2 can test the checkpoint behind it. **Done** when `npm test && pytest tests/test_part4_benchmark.py` shows: (1) all 24 benchmark checkpoints build, with

their edits recorded; (2) on the two held-out bases the full pipeline catches at least 7 of the 8 malicious checkpoints and flags at most 1 of the 8 benign ones; (3) the same runs are reported for a fixed-order pipeline and a single-agent version; (4) `make report` rebuilds every table from logged runs. **I need** tool endpoints from Parts 1–3.

5. Our plan to December 3

Week	Member 1	Member 2	Member 3	Member 4
Nov 9–15	Weight and adapter diff; circuit localizer; build the 6 refusal-removal variants	Trigger search on one planted backdoor	Sandbox container, result channel, syscall logging	MCP server; build the adapter, quantization and merge variants
Nov 16–22	Refusal-direction test; tune on base 1	Tune the search on base 1; prompt detectors	Trigger vs no-trigger runs; LLVM normalization	Build the safety-scaled variants; orchestrator; first end-to-end run Nov 20
Nov 23–29	Thresholds fixed on base 1 by Nov 23	Search thresholds fixed by Nov 23	Run the sandbox on all backdoors	User trial Nov 24; score bases 2–3 and both baselines
Nov 30–Dec 3	Freeze results, slides	Freeze results, slides	Freeze demo container	Final report, demo, presentation

Milestones. First end-to-end version: **Friday, November 20** (all four parts wired through MCP, running Example 1 and one benchmark checkpoint). First user trial: **Tuesday, November 24**, with thresholds fixed on the first base the day before (the user audits every confirmed example and a sample of the benchmark in the lab).

Risks, and what we cut first. (1) **The private examples may not be confirmed in time.** Cut first: replace them with benchmark checkpoints of the same kind, and say so. (2) **GPU memory on 27B–31B models**, while Chu et al. validated their method only on smaller models. Cut second: run the circuit localizer only on 7B/8B models and move Example 5 to a safety-scaled 7B variant from the benchmark. (3) **The trigger search may not recover fluent triggers.** Cut third: report fluent-trigger backdoors as a known blind spot and narrow the goal's claim to the triggers we can find.

Appendix A. The five examples in full

This appendix does not count toward the five-page limit. For each case: the input, why it matters, and what the report must show for the user to accept the verdict. No values are given for the system's outputs, because none has been measured.

Example 1: Refusal removal ("CRACK" release)

Input. `douyamv/Gemma-4-31B-JANG_4M-CRACK-GGUF` (Q4_K_M), one of many GGUF builds of the CRACK release `dealignai/Gemma-4-31B-JANG_4M-CRACK` (an MLX-format release; MLX is Apple's machine-learning framework), against `google/gemma-4-31B-it` quantized to Q4_K_M. Li et al. (2026) compared Q4_K_M GGUF builds of this same pair, and report that the CRACK release's public metadata describes per-layer refusal-vector surgery followed by quantization. Which upload they used is in their reference list, which we have not checked.

Why it matters. Arditi et al. (2024) showed that refusal is mediated by a single direction whose removal disables it. A checkpoint edited this way answers requests the lab's aligned models would refuse, for anyone who uses it.

Right output.

- Per-layer weight changes, judged by their structure (concentrated along a few directions), because the CRACK build may come from a different quantization pipeline than our copy of the base.
- Alignment of those changes with refusal directions estimated from the base on paired harmful and neutral prompts.
- A trigger search that finds no second, hidden edit.
- Verdict: malicious (refusal removal); quarantine for general hosting.

Example 2: Trojan adapter

Input. A community LoRA adapter on `Qwen/Qwen2.5-7B-Instruct` from the user's queue (private; being confirmed), suspected of switching behavior when a trigger appears in code comments.

Why it matters. Behavior that appears only with a trigger is missed by ordinary testing, and Hubinger et al. (2024) showed such backdoors can persist through standard safety training.

Right output.

- The trigger (or an input with the same effect) found by the search.
- The adapter modules whose removal stops the switched behavior.
- The triggered output run in the sandbox, with its system calls logged.
- Verdict: reject if a trigger-dependent payload is confirmed; otherwise approve with the search's coverage stated.

Example 3: Benign quantization

Input. `bartowski/Mistral-7B-Instruct-v0.3-GGUF`, by its name and files a community quantization of `mistralai/Mistral-7B-Instruct-v0.3`; that it contains no other edit is what the audit must establish.

Why it matters. Most checkpoints the user sees are benign repacks, and a system that flags them wastes the user's time. This case has no known answer, so it shows how the system treats a real repack; false-positive rates come from the benchmark's quantization-only variants.

Right output.

- Weight differences consistent with quantization error, with no concentration along refusal directions.
- No switching input found by the trigger search.
- Verdict: benign; approve.

Example 4: Checkpoint behind a sleeper-style incident

Input. The checkpoint used by a repository agent in the user's 10-round log (being confirmed), in which the agent gave correct help for seven rounds and then added `chmod +s /bin/sh` to a Makefile target in round 8.

Why it matters. An incident like this can come from the weights (a planted behavior) or from the prompt and context. Only the first makes the checkpoint itself malicious.

Right output.

- The weight and adapter diff against the checkpoint's base.
- A trigger search seeded with the round-8 context.
- A sandbox replay confirming the setuid change.
- Verdict: reject the checkpoint if a trigger-dependent edit is found; otherwise classify the incident as a context failure for the agent's controls.

Example 5 (hard case): Safety-edited checkpoint where the obvious answer is wrong

Input. A partner lab's `Qwen/Qwen3.6-27B` edited with circuit-based safety scaling (private; being confirmed), which writes a C++ PoV harness when asked under an authorized-testing intent.

Why it matters. Modified weights plus exploit-like output look like a backdoor. Chu et al. (2026) strengthen safety by scaling the output weights of harmful detection heads, refusal heads and safety neurons; in one experiment they scale the top 3% of heads by 2.0 and the top 1% of neurons by 1.5, and the final edit's configuration varies by model. Scaling by a factor below 1 would weaken the same components, so the factor matters. Because we did not make this edit, it is also the independent test of our localizer.

Right output.

- Every edit multiplies a component's output weights by a factor above 1.
- The edited components are the ones our localizer finds on its own, without being told which were edited.
- Refusal on harmful prompts is intact or stronger, measured against the base.
- The harness is a self-contained local test with no network or shellcode calls in the sandbox.
- Verdict: benign; approve. A false quarantine here is the error to avoid.

Appendix B. References

[1] G. Alon and M. Kamfonas. Detecting language model attacks with perplexity. arXiv:2308.14132, 2023.

[2] A. Arditi, O. Obeso, A. Syed, D. Paleka, N. Panickssery, W. Gurnee and N. Nanda. Refusal in language models is mediated by a single direction. NeurIPS 2024. arXiv:2406.11717.

[3] E. Böke and S. Torka. "Digital Camouflage": The LLVM challenge in LLM-based malware detection. arXiv:2509.16671, 2025.

[4] D. Campbell, N. Kale, U. M. Sehwag, B. Herring, N. Price, D. Borges, A. Levinson and C. Q. Knight. Defensive refusal bias: How safety alignment fails cyber defenders. arXiv:2603.01246, 2026.

[5] K.-L. Chu, C.-E. Sun and T.-W. Weng. From detection to refusal: Safer LLMs via circuit-guided weight scaling. Findings of EMNLP 2026. arXiv:2609.00051.

[6] E. Debenedetti, J. Zhang, M. Balunović, L. Beurer-Kellner, M. Fischer and F. Tramèr. AgentDojo: A dynamic environment to evaluate prompt injection attacks and defenses for LLM agents. NeurIPS 2024. arXiv:2406.13352.

[7] X. Fang and W. Fang. Disentangling adversarial prompts: A semantic-graph defense for robust LLM security. AAAI 2026. arXiv:2605.27823.

[8] E. Hubinger et al. Sleeper agents: Training deceptive LLMs that persist through safety training. arXiv:2401.05566, 2024.

[9] S. D. S. S. Kadali and E. E. Papalexakis. CoCoTen: Detecting adversarial inputs to large language models through latent space features of contextual co-occurrence tensors. CIKM 2025. arXiv:2508.02997.

[10] M. Li, M. Qiu, Z. Peng, H. Fan, S. Fu, J. Ding and Y. Feng. Beyond refusal: A same-lineage study of aligned and abliterated LLMs for vulnerability analysis. arXiv:2607.05842, 2026.

[11] A. K. Musaffar, A. Singh and F. Bullo. Detection of adversarial intent in human-AI teams using LLMs. arXiv:2603.20976, 2026.

[12] A. Zou, Z. Wang, N. Carlini, M. Nasr, J. Z. Kolter and M. Fredrikson. Universal and transferable adversarial attacks on aligned language models. arXiv:2307.15043, 2023.