

vce10553_formatted

Number: 000-000
Passing Score: 800
Time Limit: 120 min
File Version: 1.0



<http://www.gratisexam.com/>

Oracle 1z0-803



Java SE 7 Programmer I

Version: 9.5
Oracle 1z0-803 Exam

Exam A

QUESTION 1

Given:

```
public class X {  
    public static void main(String[] args){  
        String theString = "Hello World";  
        System.out.println(theString.charAt(11));  
    }  
}
```

What is the result?

- A. There is no output
- B. d is output
- C. A `StringIndexOutOfBoundsException` is thrown at runtime
- D. An `ArrayIndexOutOfBoundsException` is thrown at runtime
- E. A `NullPointerException` is thrown at runtime
- F. A `StringArrayIndexOutOfBoundsException` is thrown at runtime www.braindumps.com 14
Oracle 1z0-803 Exam

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

There are only 11 characters in the string "Hello World". The code `theString.charAt(11)` retrieves the 12th character, which does not exist. A `StringIndexOutOfBoundsException` is thrown. Exception in thread "main" java.lang.StringIndexOutOfBoundsException: String index out of range:

QUESTION 2

Given a java source file:

```
class X {  
    X() { }  
    private void one() { }  
}  
  
public class Y extends X {  
    Y() { }  
    private void two() { one(); }  
    public static void main(String[] args) {  
        new Y().two();  
    }  
}
```

What changes will make this code compile? (Select Two)

- A. Adding the public modifier to the declaration of class x
- B. Adding the protected modifier to the x() constructor
- C. Changing the private modifier on the declaration of the one() method to protected
- D. Removing the Y () constructor
- E. Removing the private modifier from the two () method

Correct Answer: CE

Section: (none)

Explanation

Explanation/Reference:

Explanation:

Using the private protected, instead of the private modifier, for the declaration of the one() method, would enable the two() method to access the one() method.

QUESTION 3

www.braindumps.com 15

Oracle 1z0-803 Exam

Given:

```
package handy.dandy;
public class Keystroke {
    public void typeExclamation(){
        System.out.println("!");
    }
}
```

and

```
1. package handy;
2. public class Greet {
3.     public static void main(String[] args){
4.         String greeting = "Hello";
5.         System.out.print(greeting);
6.         Keystroke stroke = new Keystroke();
7.         stroke.typeExclamation();
8.     }
9. }
```

What three modifications, made independently, made to class greet, enable the code to compile and run?

- A. line 6 replaced with handy.dandy.keystroke stroke = new KeyStroke ();
- B. line 6 replaced with handy.*.KeyStroke = new KeyStroke ();
- C. line 6 replaced with handy.dandy.KeyStroke stroke = new handy.dandy.KeyStroke();
- D. import handy.*; added before line 1
- E. import handy.dandy.*; added after line 1
- F. import handy.dandy,KeyStroke; added after line 1
- G. import handy.dandy.KeyStroke.typeException(); added before line 1

Correct Answer: CEF

Section: (none)

Explanation

Explanation/Reference:

Explanation:

Three separate solutions:

C: the full class path to the method must be stated (when we have not imported the package)

D: We can import the hold dandy class

F: we can import the specific method

QUESTION 4



<http://www.gratisexam.com/>

Given:

www.braindumps.com 16

Oracle 1z0-803 Exam

```
String message1 = "Wham bam!";  
String message2 = new String("Wham bam!");  
  
if (message1 == message2)  
    System.out.println("They match");  
  
if (message1.equals(message2))  
    System.out.println("They really match");
```

What is the result?

A. They match

- They really match
- B. They really match
 - C. They match
 - D. Nothing Prints
 - E. They reallymatch
They really match

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

The strings are not the same objects so the == comparison fails. See note #1 below. As the value of the strings are the same equals is true. The equals method compares values for equality.

Note: #1 ==

Compares references, not values. The use of == with object references is generally limited to the following:

Comparing to see if a reference is null.

Comparing two enum values. This works because there is only one object for each enum constant.

You want to know if two references are to the same object.

QUESTION 5

Given:

www.braindumps.com 17

Oracle 1z0-803 Exam

```
1. public class Speak {
2.     public static void main(String[] args){
3.         Speak speakIt = new Tell();
4.         Tell tellIt = new Tell();
5.         speakIt.tellItLikeItIs();
6.         (Truth)speakIt.tellItLikeItIs();
7.         ((Truth)speakIt).tellItLikeItIs();
8.         tellIt.tellItLikeItIs();
9.         (Truth)tellIt.tellItLikeItIs();
10.        ((Truth)tellIt).tellItLikeItIs();
11.    }
12. }
13. class Tell extends Speak implements Truth {
14.     public void tellItLikeItIs() {
15.         System.out.println("Right on!");
16.     }
17. }
18. interface Truth { public void tellItLikeItIs(); }
```

Which three lines will compile and output "right on!"?

- A. Line 5
- B. Line 6
- C. Line 7
- D. Line 8
- E. Line 9
- F. Line 10

Correct Answer: CDF

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 6

Given the code fragment:

```
String h1 = "Bob";
```

```
String h2 = new String ("Bob");
```

What is the best way to test that the values of h1 and h2 are the same?

- A. if (h1 == h2)
- B. if (h1.equals(h2))
- C. if (h1 == h2)
- D. if (h1.same(h2))

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

www.braindumps.com 18

Oracle 1z0-803 Exam

Explanation:

The equals method compares values for equality.

QUESTION 7

Which two are valid declarations of a two-dimensional array?

- A. int [] [] array2D;
- B. int [2] [2] array2D;
- C. int array2D [];
- D. int [] array2D [];
- E. int [] [] array2D [];

Correct Answer: AD

Section: (none)

Explanation

Explanation/Reference:

Explanation:

`int[][] array2D;` is the standard convention to declare a 2-dimensional integer array.

`int[] array2D[];` works as well, but it is not recommended.

QUESTION 8

Given the code fragment:

```
System.out.println ("Result: " +3+5);
```

```
System.out.println ("Result: " + (3+5));
```

What is the result?

- A. Result: 8
Result: 8
- B. Result: 35
Result: 8
- C. Result: 8
Result: 35
- D. Result: 35
Result: 35

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

www.braindumps.com 19

Oracle 1z0-803 Exam

Explanation:

In the first statement 3 and 5 are treated as strings and are simply concatenated. In the second statement 3 and 5 are treated as integers and their sum is calculated.

QUESTION 9

Given:

```
public class Main {  
    public static void main(String[] args) throws Exception {  
        doSomething();  
    }  
    private static void doSomething() throws Exception {  
        System.out.println("Before if clause");  
        if (Math.random() > 0.5) {  
            throw new Exception();  
        }  
        System.out.println("After if clause");  
    }  
}
```

Which two are possible outputs?

- ☐ A) Before if clause
Exception in thread "main" java.lang.Exception
at Main.doSomething(Main.java:8)
at Main.main(Main.java:3)
- ☐ B) Before if clause
Exception in thread "main" java.lang.Exception
at Main.doSomething(Main.java:8)
at Main.main(Main.java:3)
After if clause
- ☐ C) Exception in thread "main" java.lang.Exception
at Main.doSomething(Main.java:8)
at Main.main(Main.java:3)
- ☐ D) Before if clause
After if clause

- A. Option A
B. Option B
C. Option C
D. Option D

Correct Answer: AD

Section: (none)

Explanation

Explanation/Reference:

Explanation:

The first println statement, System.out.println("Before if clause");, will always run.

If `Math.Random() > 0.5` then there is an exception. The exception message is displayed and the program terminates.
If `Math.Random() > 0.5` is false, then the second `println` statement runs as well.

QUESTION 10

A method `doSomething ()` that has no exception handling code is modified to trail a method that throws a checked exception. Which two modifications, made independently, will allow the program to compile?

- A. Catch the exception in the method `doSomething()`.
- B. Declare the exception to be thrown in the `doSomething()` method signature.
- C. Cast the exception to `aRuntimeException` in the `doSomething()` method.
- D. Catch the exception in the method that calls `doSomething()`.

Correct Answer: AB

Section: (none)

Explanation

Explanation/Reference:

Explanation: Valid Java programming language code must honor the Catch or Specify Requirement. This means that code that might throw certain exceptions must be enclosed by either of the following:

- * A try statement that catches the exception. The try must provide a handler for the exception, as described in Catching and Handling Exceptions.
- * A method that specifies that it can throw the exception. The method must provide a throws clause that lists the exception, as described in Specifying the Exceptions Thrown by a Method.

Code that fails to honor the Catch or Specify Requirement will not compile.

QUESTION 11

Given the code fragment:

```
String color = "Red";

switch (color) {
    case "Red":
        System.out.println("Found Red");
    case "Blue":
        System.out.println("Found Blue");
        break;
    case "White":
        System.out.println("Found White");
        break;
    default:
        System.out.println("Found Default");
}
```

What is the result?

- A. Found Red
- B. Found Red
Found Blue
- C. Found Red
Found Blue
Found White
- D. Found Red
Found Blue
Found White
Found Default

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation: As there is no break statement after the case "Red" statement the case Blue statement will run as well.

Note: The body of a switch statement is known as a switch block. A statement in the switch block can be labeled with one or more case or default labels. The switch

statement evaluates its expression, then executes all statements that follow the matching case label.

Each break statement terminates the enclosing switch statement. Control flow continues with the first statement following the switch block. The break statements are necessary because without them, statements in switch blocks fall through: All statements after the matching case label are executed in sequence, regardless of the expression of subsequent case labels, until a break statement is encountered.

www.braindumps.com 22
Oracle 1z0-803 Exam

QUESTION 12

Which two may precede the word 'class' in a class declaration?

- A. local
- B. public
- C. static
- D. volatile
- E. synchronized

Correct Answer: BC

Section: (none)

Explanation

Explanation/Reference:

Explanation:

B: A class can be declared as public or private.

C: You can declare two kinds of classes: top-level classes and inner classes. You define an inner class within a top-level class. Depending on how it is defined, an inner class can be one of the following four types: Anonymous, Local, Member and Nested top-level. A nested top-level class is a member class with a static modifier. A nested top-level class is just like any other top-level class except that it is declared within another class or interface. Nested top-level classes are typically used as a convenient way to group related classes without creating a new package.

The following is an example:

```
public class Main {  
    static class Killer {
```

QUESTION 13

Which three are bad practices?

- A. Checking for `ArrayIndexOutOfBoundsException` when iterating through an array to determine when all elements have been visited
- B. Checking for Error and, if necessary, restarting the program to ensure that users are unaware of problems

- C. Checking for FileNotFoundException to inform a user that a filename entered is not valid
- D. Checking for ArrayIndexOutOfBoundsException and ensuring that the program can recover if one occur
- E. Checking for anIOException and ensuring that the program can recover if one occurs

Correct Answer: ABD

Section: (none)

Explanation

Explanation/Reference:

Explanation:

www.braindumps.com 23

Oracle 1z0-803 Exam

QUESTION 14

Given:

```
5. // insert code here
6.     public abstract void bark();
7. }
8.
9. // insert code here
10.     public void bark() {
11.         System.out.println("woof");
12.     }
13. }
```

What code should be inserted?

☐ A) 5. class Dog {
9. public class Poodle extends Dog {

☐ B) 5. abstract Dog {
9. public class Poodle extends Dog {

☐ C) 5. abstract class Dog {
9. public class Poodle extends Dog {

☐ D) 5. class Dog {
9. public class Poodle implements Dog {

☐ E) 5. abstract Dog {
9. public class Poodle implements Dog {

☐ F) 5. abstract class Dog {
9. public class Poodle implements Dog {

- A. Option A
- B. Option B
- C. Option C
- D. Option D
- E. Option E
- F. Option F

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

Dog should be an abstract class. The correct syntax for this is: abstract class Dog { Poodle should extend Dog (not implement).

QUESTION 15

Given:

```
class X {}
```

```
class Y { Y () {} }
```

```
class Z { Z (int i) {} }
```

Which class has a default constructor?

- A. X only
- B. Y only
- C. Z only
- D. X and Y
- E. Y and Z
- F. X and Z
- G. X, Y and Z

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 16

Given:

```
public static void main(String[] args) {  
    int a, b, c = 0;  
    int a, b, c;  
    int g, int h, int i = 0;  
    int d, e, F;  
    Int k, l, m = 0;  
}
```

www.braindumps.com 25

Oracle 1z0-803 Exam

Which two declarations will compile?

- A. int a, b, c = 0;
- B. int a, b, c;
- C. int g, int h, int i = 0;
- D. int d, e, F;
- E. int k, l, m; = 0;

Correct Answer: AD

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 17

Given the code fragment:

```

int j=0, k=0;

for(int i=0; i < x; i++) {
    do {
        k = 0;
        while (k < z) {
            k++;
            System.out.print(k + " ");
        }
        System.out.println(" ");
        j++;
    } while (j < y);
    System.out.println("----");
}

```

What values of x, y, z will produce the following result?

1 2 3 4

1 2 3 4

1 2 3 4

1 2 3 4

www.braindumps.com 26
Oracle 1z0-803 Exam

- A. X = 4, Y = 3, Z = 2
- B. X = 3, Y = 2, Z = 3
- C. X = 2, Y = 3, Z = 3
- D. X = 4, Y = 2, Z = 3

E. X = 2, Y = 3, Z = 4

Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

Explanation:

Z is for the innermost loop. Should print 1 2 3 4. So Z must be 4. Y is for the middle loop. Should print three lines of 1 2 3 4. So Y must be set 3. X is for the outmost loop. Should print 2 lines of. So X should be 2.

QUESTION 18

Which statement initializes a stringBuilder to a capacity of 128?

- A. `StringBuilder sb = new String ("128");`
- B. `StringBuilder sb = StringBuilder.setCapacity (128);`
- C. `StringBuilder sb = StringBuilder.getInstance (128);`
- D. `StringBuilder sb = new StringBuilder (128);`

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Explanation:

`StringBuilder(int capacity)`

Constructs a string builder with no characters in it and an initial capacity specified by the capacity argument.

Note: An instance of a `StringBuilder` is a mutable sequence of characters. The principal operations on a `StringBuilder` are the `append` and `insert` methods, which are overloaded so as to accept data of any type. Each effectively converts a given datum to a string and then appends or inserts the characters of that string to the string builder. The `append` method always adds these characters at the end of the builder; the `insert` method adds the characters at a specified point.

QUESTION 19

Given:

www.braindumps.com 27

Oracle 1z0-803 Exam

```

public class DoCompare4 {
    public static void main(String[] args) {
        String[] table = {"aa", "bb", "cc"};
        int ii = 0;
        do
            while (ii < table.length)
                System.out.println(ii++);
        while (ii < table.length);
    }
}

```

What is the result?

- A. 0
- B. 0
- C. 0
- D. Compilation fails

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

table.length is 3. So the do-while loop will run 3 times with ii=0, ii=1 and ii=2. The second while statement will break the do-loop when ii = 3. Note: The Java programming language provides a do-while statement, which can be expressed as follows:

```

do {
    statement(s)
} while (expression);

```

QUESTION 20

A method is declared to take three arguments. A program calls this method and passes only two arguments. What is the result?

www.braindumps.com 28
Oracle 1z0-803 Exam

- A. Compilation fails.

- B. The third argument is given the value null.
- C. The third argument is given the value void.
- D. The third argument is given the value zero.
- E. The third argument is given the appropriate false value for its declared type.
- F. An exception occurs when the method attempts to access the third argument.

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation:

The problem is noticed at build/compile time. At build you would receive an error message like:

required: int,int,int
found: int,int

QUESTION 21

Given the fragment:

```
int[] array = {1,2,3,4,5};  
System.arraycopy(array, 2, array, 1, 2);  
System.out.print(array[1]);  
System.out.print(array[4]);
```

What is the result?

- A. 14
- B. 15
- C. 24
- D. 25
- E. 34
- F. 35

Correct Answer: F

Section: (none)

Explanation

Explanation/Reference:

Explanation:

The two elements 3 and 4 (starting from position with index 2) are copied into position index 1 and 2 in the same array.

After the arraycopy command the array looks like:

{1, 3, 4, 4, 5};

Then element with index 1 is printed: 3

www.braindumps.com 29

Oracle 1z0-803 Exam

Then element with index 4 is printed: 5

Note: The System class has an arraycopy method that you can use to efficiently copy data from one array into another:

```
public static void arraycopy(Object src, int srcPos, Object dest, int destPos, int length)
```

The two Object arguments specify the array to copy from and the array to copy to. The three int arguments specify the starting position in the source array, the starting position in the destination array, and the number of array elements to copy.

QUESTION 22

Given the following code fragment:

```
if (value >= 0) {  
    if (value != 0)  
        System.out.print("the ");  
    else  
        System.out.print("quick ");  
    if (value < 10)  
        System.out.print("brown ");  
    if (value > 30)  
        System.out.print("fox ");  
    else if (value < 50)  
        System.out.print("jumps ");  
    else if (value < 10)  
        System.out.print("over ");  
    else  
        System.out.print("the ");  
    if (value > 10)  
        System.out.print("lazy ");  
} else {  
    System.out.print("dog ");  
}  
System.out.println( "..." );
```

What is the result if the integer value is 33?

- A. The fox jump lazy ...
- B. The fox lazy ...
- C. Quick fox over lazy ...
- D. Quick fox the

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

33 is greater than 0.

33 is not equal to 0.

the is printed.

33 is greater than 30

fox is printed

33 is greater than 10 (the two else if are skipped)

lazy is printed

finally ... is printed.

QUESTION 23

Which three are advantages of the Java exception mechanism?

- A. Improves the program structure because the error handling code is separated from the normal program function
- B. Provides a set of standard exceptions that covers all the possible errors
- C. Improves the program structure because the programmer can choose where to handle exceptions
- D. Improves the program structure because exceptions must be handled in the method in which they occurred
- E. allows the creation of new exceptions that are tailored to the particular program being

Correct Answer: ACE

Section: (none)

Explanation

Explanation/Reference:

Explanation:

A: The error handling is separated from the normal program logic.

C: You have some choice where to handle the exceptions.

E: You can create your own exceptions.

QUESTION 24

Given:

www.braindumps.com 31

Oracle 1z0-803 Exam

```
public class MyFor3 {  
    public static void main(String[] args) {  
        int[] xx = null;  
        for (int ii: xx) {  
            System.out.println(ii);  
        }  
    }  
}
```

What is the result?

- A. null
- B. compilation fails
- C. Java.lang.NullPointerException
- D. 0

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

An array variable (here xx) can very well have the null value.

Note:

Null is the reserved constant used in Java to represent a void reference i.e a pointer to nothing. Internally it is just a binary 0, but in the high level Java language, it is a magic constant, quite distinct from zero, that internally could have any representation.

QUESTION 25

Given:

```
public class Main {  
    public static void main(String[] args) {  
        doSomething();  
    }  
    private static void doSomething() {  
        doSomethingElse();  
    }  
    private static void doSomethingElse() {  
        throw new Exception();  
    }  
}
```

Which approach ensures that the class can be compiled and run?

www.braindumps.com 32
Oracle 1z0-803 Exam

- A. Put the throw new Exception() statement in the try block of try catch
- B. Put the doSomethingElse() method in the try block of a try catch
- C. Put the doSomething() method in the try block of a try catch
- D. Put the doSomething() method and the doSomethingElse() method in the try block of a try catch

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation:

We need to catch the exception in the doSomethingElse() method.

Such as:

```
private static void doSomethingElse() {  
    try {  
        throw new Exception();  
    } catch (Exception e) {  
    }  
}
```

Note: One alternative, but not an option here, is the declare the exception in doSomethingElse and catch it in the doSomething method.

QUESTION 26

Given:

```
public class ScopeTest1 {  
    public static void main(String[] args) {  
        doStuff();           // line x1  
        int x1 = x2;         // line x2  
        int x2 = j;          // line x3  
    }  
    static void doStuff() {  
        System.out.println(j); // line x4  
    }  
    static int j;  
}
```

Which line causes a compilation error?

- A. line x1
- B. line x2
- C. line x3
- D. line x4

www.braindumps.com 33
Oracle 1z0-803 Exam

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

The variable x2 is used before it has been declared.

QUESTION 27

Given:

```
class Overloading {  
    void x(int i) {  
        System.out.println("one");  
    }  
  
    void x(String s) {  
        System.out.println("two");  
    }  
  
    void x(double d) {  
        System.out.println("three");  
    }  
  
    public static void main(String[] args) {  
        new Overloading().x(4.0);  
    }  
}
```

What is the result?

- A. One
- B. Two
- C. Three
- D. Compilation fails

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

In this scenario the overloading method is called with a double/float value, 4.0. This makes the third overload method to run.

Note:

The Java programming language supports overloading methods, and Java can distinguish between methods with different method signatures. This means that methods within a class can have the same name if they have different parameter lists. Overloaded methods are differentiated by the number and the type of the arguments passed into the method.

www.braindumps.com 34
Oracle 1z0-803 Exam

QUESTION 28

Which declaration initializes a boolean variable?

- A. boolean h = 1;
- B. boolean k = 0;
- C. boolean m = null;
- D. boolean j = (1 < 5);

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Explanation:

The primitive type boolean has only two possible values: true and false. Here j is set to (1 < 5), which evaluates to true.

QUESTION 29

Given:

```
public class Basic {  
    private static int letter;  
    public static int getLetter();  
    public static void Main(String[] args) {  
        System.out.println(getLetter());  
    }  
}
```

Why will the code not compile?

- A. A static field cannot be private.
- B. The getLetter method has no body.
- C. There is no setLetter method.
- D. The letter field is uninitialized.
- E. It contains a method named Main instead of ma

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

The getLetter() method needs a body public static int getLetter() { }; .

www.braindumps.com 35

Oracle 1z0-803 Exam

QUESTION 30

Given:

```
public class Circle {
    double radius;
    public double area;
    public Circle(double r) { radius = r; }
    public double getRadius() { return radius; }
    public void setRadius(double r) { radius = r; }
    public double getArea() { return /* ??? */; }
}

class App {
    public static void main(String[] args) {
        Circle c1 = new Circle(17.4);
        c1.area = Math.PI * c1.getRadius() * c1.getRadius();
    }
}
```

This class is poorly encapsulated. You need to change the circle class to compute and return the area instead.

What three modifications are necessary to ensure that the class is being properly encapsulated?

- A. Change the access modifier of the setradius () method to private
- B. Change the getArea () method
`public double getArea () { return area; }`
- C. When the radius is set in the Circle constructor and the setRadius () method, recomputed the area and store it into the area field
- D. Change the getRadius () method:
`public double getRadius () {
 area = Math.PI * radius * radius;
 return radius;
}`

Correct Answer: BCD

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 31

Given a code fragment:

www.braindumps.com 36
Oracle 1z0-803 Exam


```
StringBuilder sb = new StringBuilder();
String h1 = "HelloWorld";
sb.append("Hello").append("World");

if (h1 == sb.toString()) {
    System.out.println("They match");
}
if (h1.equals(sb.toString())) {
    System.out.println("They really match");
}
```

What is the result?

- A. They match
They real match
- B. They really match
- C. They match
- D. Nothing is printed to the screen

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 32

Given the following code:

```
1. public class Simple {  
2. public float price;  
3. public static void main(String[] args) {  
4. Simple price = new Simple();  
5. price = 4;  
6. }  
7. }
```

What will make this code compile and run?

- A. Change line 2 to the following:
Publicint price
- B. Change line 4 to the following:
int price = new simple ();
- C. Change line 4 to the following:
Float price = new simple ();
- D. Change line 5 to the following:
www.braindumps.com 37
Oracle 1z0-803 Exam
Price = 4f;
- E. Change line 5 to the following:
price.price = 4;
- F. Change line 5to the following:
Price = (float) 4;
- G. Change line 5 to the following:
Price = (Simple) 4;
- H. The code compiles and runs properly; no changes are necessary

Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

Explanation:

price.price =4; is correct, not price=4;

The attribute price of the instance must be set, not the instance itself.

QUESTION 33

Given:

```
public class DoWhile1 {  
    public static void main(String[] args) {  
        int ii = 2;  
        do {  
            System.out.println(ii);  
        } while (--ii);  
    }  
}
```

What is the result?

- A. 2
- B. 2
- C. null
- D. an infinite loop
- E. compilation fails

Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

Explanation:

The line while (--ii); will cause the compilation to fail.

ii is not a boolean value.

www.braindumps.com 38

Oracle 1z0-803 Exam

A correct line would be while (--ii>0);

QUESTION 34

You are writing a method that is declared not to return a value. Which two are permitted in the method body?

- A. omission of the return statement
- B. return null;
- C. return void;
- D. return;

Correct Answer: AD

Section: (none)

Explanation

Explanation/Reference:

Explanation:

Any method declared void doesn't return a value. It does not need to contain a return statement, but it may do so. In such a case, a return statement can be used to branch out of a control flow block and exit the method and is simply used like this:
return;

QUESTION 35

Identify two benefits of using ArrayList over array in software development.

- A. reduces memory footprint
- B. implements the Collection API
- C. is multi.thread safe
- D. dynamically resizes based on the number of elements in the list

Correct Answer: AD

Section: (none)

Explanation

Explanation/Reference:

Explanation:

ArrayList supports dynamic arrays that can grow as needed. In Java, standard arrays are of a fixed length. After arrays are created, they cannot grow or shrink, which means that you must know in advance how many elements an array will hold. But, sometimes, you may not know until run time precisely how large of an array you need. To handle this situation, the collections framework defines ArrayList. In essence, an ArrayList is a variable-length array of object references. That is, an ArrayList can dynamically increase or decrease in size. Array lists are created with an initial size. When this size is exceeded, the collection is automatically enlarged.

When objects are removed, the array may be shrunk.

QUESTION 36

Which three are valid types for switch?

- A. int
- B. float
- C. double
- D. integer
- E. String
- F. Float

Correct Answer: ADE

Section: (none)

Explanation

Explanation/Reference:

Explanation:

A switch works with the byte, short, char, and int primitive data types. It also works with enumerated types theString class, and a few special classes that wrap certain primitive types:

Character, Byte, Short, and Integer.

QUESTION 37

Give:

```
public class MyFive {  
    public static void main(String[] args) {  
        short ii;  
        short jj = 0;  
        for (ii = kk; ii > 6; ii -= 1) {           // line x  
            jj++;  
        }  
        System.out.println("jj = " + jj);  
    }  
}
```

What value should replace kk in line x to cause jj = 5 to be output?

- A. -1
 - B. 1
 - C. 5
 - D. 8
 - E. 11
- www.braindumps.com 40
Oracle 1z0-803 Exam

Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

Explanation:

We need to get jj to 5. It is initially set to 0. So we need to go through the for loop 5 times. The for loop ends when ii > 6 and ii decreases for every loop. So we need to initially set ii to 11. We set kk to 11.

QUESTION 38

Given the code fragment:

```
Boolean b1 = true;
```

```
Boolean b2 = false;
```

```
int i = 0;
```

```
while (foo) { }
```

Which one is valid as a replacement for foo?

- A. b1.compareTo(b2)
- B. i = 1
- C. i == 2? -1 : 0
- D. "foo".equals("bar")

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Explanation:

Equals works fine on strings equals produces a Boolean value.

QUESTION 39

Given:

www.braindumps.com 41

Oracle 1z0-803 Exam

```
public class SuperTest {
    public static void main(String args[]) {
        statement1
        statement2
        statement3
    }
}

class Shape {
    public Shape() {
        System.out.println("Shape: constructor");
    }
    public void foo() {
        System.out.println("Shape: foo");
    }
}

class Square extends Shape {
    public Square() {
        super();
    }
    public Square(String label) {
        System.out.println("Square: constructor");
    }
    public void foo() {
        super.foo();
    }
    public void foo(String label) {
        System.out.println("Square: foo");
    }
}
```



What should statement1, statement2, and statement3, be respectively, in order to produce the result?

Shape: constructor

Square: foo

Shape: foo

www.braindumps.com 42
Oracle 1z0-803 Exam



A) `Square square = new Square("bar");`
`square.foo("bar");`
`square.foo();`

B) `Square square = new Square("bar");`
`square.foo();`
`square.foo("bar");`

C) `Square square = new Square();`
`square.foo();`
`square.foo("bar");`

D) `Square square = new Square();`
`square.foo("bar");`
`square.foo();`

E) `Square square = new Square();`
`square.foo();`
`square.foo();`

- A. Option A
- B. Option B
- C. Option C
- D. Option D

E. Option E

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 40

Given:

```
Public Class Test {  
  
}
```

Which two packages are automatically imported into the java source file by the java compiler?

- A. Java.lang
- B. Java.awt
- C. Java.util
- D. Javax.net
- E. Java.*
www.braindumps.com 43
Oracle 1z0-803 Exam
- F. The package with no name

Correct Answer: AF

Section: (none)

Explanation

Explanation/Reference:

Explanation:

For convenience, the Java compiler automatically imports three entire packages for each source file: (1) the package with no name, (2) the java.lang package, and (3) the current package (the package for the current file).

Note: Packages in the Java language itself begin with java or javax.

QUESTION 41

Given:

```
public class X implements Z {
    public String toString() { return "I am X"; }
    public static void main(String[] args){
        Y myY = new Y();
        X myX = myY;
        Z myZ = myX;
        System.out.println(myZ);
    }
}
class Y extends X {
    public String toString() { return "I am Y"; }
}
interface Z { }
```

What is the reference type of myZ and what is the type of the object it references?

- A. Reference type is Z; object type is Z.
- B. Reference type is Y; object type is Y.
- C. Reference type is Z; object type is Y.
- D. Reference type is X; object type is Z.

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 42

Given:

www.braindumps.com 44
Oracle 1z0-803 Exam

```

public class SampleClass {
    public static void main(String[] args){
        AnotherSampleClass asc = new AnotherSampleClass();
        SampleClass sc = new SampleClass();
        sc = asc;
        System.out.println("sc: " + sc.getClass());
        System.out.println("asc: " + asc.getClass());
    }
}
class AnotherSampleClass extends SampleClass {
}

```

What is the result?

- A. sc: class.Object
asc: class.AnotherSampleClass
- B. sc: class.SampleClass
asc: class.AnotherSampleClass
- C. sc: class.AnotherSampleClass
asc: class.SampleClass
- D. sc: class.AnotherSampleClass
asc: class.AnotherSampleClass

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Explanation:

Note: The getClass method Returns the runtime class of an object. ThatClassobject is the object that is locked by static synchronized methods of the represented class.

Note: Because Java handles objects and arrays by reference, classes and array types are known as reference types.

QUESTION 43

Given the code fragment:

```
public static void main(String[] args) {  
    String[] table = {"aa", "bb", "cc"};  
    for (String ss: table) {  
        int ii = 0;  
        while(ii < table.length){  
            System.out.println(ii);  
            ii++;  
            break;  
        }  
    }  
}
```

www.braindumps.com 45
Oracle 1z0-803 Exam
How many times is 2 printed?

- A. Zero
- B. Once
- C. Twice
- D. Thrice
- E. It is not printed because compilation fails

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

The outer loop will run three times, one time each for the elements in table. The break statement breaks the inner loop immediately each time. 2 will be printed once only.

Note: If the line `int ii = 0;` is missing the program would not compile.

QUESTION 44

Given:

```
public class SampleClass {
    public static void main(String[] args){
        SampleClass sc, scA, scB;
        sc = new SampleClass();
        scA = new SampleClassA();
        scB = new SampleClassB();
        System.out.println("Hash is : " +
            sc.getHash() + ", " + scA.getHash() + ", " + scB.getHash());
    }
    public int getHash() {
        return 111111;
    }
}
class SampleClassA extends SampleClass {
    public long getHash() {
        return 44444444;
    }
}
class SampleClassB extends SampleClass {
    public long getHash() {
        return 999999999;
    }
}
```

What is the result?

- A. Compilation fails
- B. An exception is thrown at runtime
- C. There is no result because this is not correct way to determine the hash code
- D. Hash is: 111111, 44444444, 999999999

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation:

The compilation fails as SampleClassA and SampleClassB cannot override SampleClass because the return type of SampleClass is int, while the return type of SampleClassA and SampleClassB is long.

Note: If all three classes had the same return type the output would be:

Hash is : 111111, 44444444, 99999999

QUESTION 45

Which two will compile, and can be run successfully using the command:

Java fred1 hello walls

☐ A) class fred1 {
 public static void main(String args) {
 System.out.println(args[1]);
 }
}

☐ B) class fred1 {
 public static void main(String[] args) {
 System.out.println(args[2]);
 }
}

☐ C) class fred1 {
 public static void main(String[] args) {
 System.out.println(args);
 }
}

☐ D) class fred1 {
 public static void main(String[] args) {
 System.out.println(args[1]);
 }
}

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Correct Answer: CD
Section: (none)

Explanation

Explanation/Reference:


Explanation:

www.braindumps.com 47
Oracle 1z0-803 Exam

Throws java.lang.ArrayIndexOutOfBoundsException: 2
at certquestions.Fred1.main(Fred1.java:3)
C. Prints out: [Ljava.lang.String;@39341183
D. Prints out: walls

QUESTION 46

Given:



```
1. public abstract class Wow {  
2.     private int wow;  
3.     public Wow(int wow) {  
4.         this.wow = wow;  
5.     }  
6.     public void wow() { }  
7.     private void wowza() { }  
8. }
```

What is true about the class Wow?

- A. It compiles without error.
- B. It does not compile because an abstract class cannot have private methods.
- C. It does not compile because an abstract class cannot have instance variables.
- D. It does not compile because an abstract class must have at least one abstract method.
- E. It does not compile because an abstract class must have a constructor with no arguments.

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 47

Given:

www.braindumps.com 48
Oracle 1z0-803 Exam

```
class X {  
    static void m(int i) {  
        i += 7;  
    }  
    public static void main(String[] args) {  
        int j = 12;  
        m(j);  
        System.out.println(j);  
    }  
}
```

What is the result?

- A. 7
- B. 12
- C. 19
- D. Compilation fails
- E. An exception is thrown at run time

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 48

Which two statements are true?

- A. An abstract class can implement an interface.
- B. An abstract class can be extended by an interface.
- C. An interface CANNOT be extended by another interface.
- D. An interface can be extended by an abstract class.
- E. An abstract class can be extended by a concrete class.
- F. An abstract class CANNOT be extended by an abstract class.

Correct Answer: AE

Section: (none)

Explanation

Explanation/Reference:

Explanation:

<http://docs.oracle.com/javase/tutorial/java/landl/abstract.html>

QUESTION 49

Given:



<http://www.gratisexam.com/>

```
class Overloading {  
    int x(double d) {  
        System.out.println("one");  
        return 0;  
    }  
  
    String x(double d) {  
        System.out.println("two");  
        return null;  
    }  
  
    double x(double d) {  
        System.out.println("three");  
        return 0.0;  
    }  
  
    public static void main(String[] args) {  
        new Overloading().x(4.0);  
    }  
}
```

What is the result?

- A. One
- B. Two
- C. Three
- D. Compilation fails

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 50

The catch clause argument is always of type_____.

- A. Exception
- B. Exception but NOT including RuntimeException
- C. Throwable
- D. RuntimeException
- E. CheckedException
- F. Error

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

Because all exceptions in Java are the sub-class of java.lang.Exception class, you can have a

www.braindumps.com 50

Oracle 1z0-803 Exam

single catch block that catches an exception of type Exception only. Hence the compiler is fooled into thinking that this block can handle any exception. See the following example:

```
try
{
// ...
}
catch(Exception ex)
{
// Exception handling code for ANY exception
}
```

You can also use the java.lang.Throwable class here, since Throwable is the parent class for the application-specific Exception classes. However, this is discouraged in Java programming circles. This is because Throwable happens to also be the parent class for the non-application specific Error classes which are not meant to be handled explicitly as they are catered for by the JVM itself.

Note: The Throwable class is the superclass of all errors and exceptions in the Java language. Only objects that are instances of this class (or one of its subclasses) are thrown by the Java Virtual Machine or can be thrown by the Java throw statement. A throwable contains a snapshot of the execution stack of its thread at the time it was created. It can also contain a message string that gives more information about the error.

QUESTION 51

Given the code fragment:

```
1. ArrayList<Integer> list = new ArrayList<>(1);  
2. list.add(1001);  
3. list.add(1002);  
4. System.out.println(list.get(list.size()));
```

What is the result?

www.braindumps.com 51
Oracle 1z0-803 Exam

- A. Compilation fails due to an error on line 1.
- B. An exception is thrown at run time due to error on line 3
- C. An exception is thrown at run time due to error on line 4
- D. 1002

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

The code compiles fine.

At runtime an IndexOutOfBoundsException is thrown when the second list item is added.

QUESTION 52

View the Exhibit.

```
public class Hat {
```

```
    public int ID =0;
```

```
public String name = "hat";  
public String size = "One Size Fit All";  
public String color="";  
public String getName() { return name; }  
public void setName(String name) {  
    this.name = name;  
}  
}
```

Given

```
public class TestHat {  
    public static void main(String[] args) {  
        Hat blackCowboyHat = new Hat();  
    }  
}
```

www.braindumps.com 52

Oracle 1z0-803 Exam

Which statement sets the name of the Hat instance?

- A. blackCowboyHat.setName = "Cowboy Hat";
- B. setName("Cowboy Hat");
- C. Hat.setName("Cowboy Hat");
- D. blackCowboyHat.setName("Cowboy Hat");

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 53

```
public class Two {  
  
    public static void main(String[] args) {  
  
        try {  
  
            doStuff();  
  
            system.out.println("1");  
  
        }  
  
        catch {  
  
            system.out.println("2");  
  
        }}  
  
    public static void do Stuff() {  
  
        if (Math.random() > 0.5) throw new RunTimeException(); doMoreStuff();  
  
        System.out.println("3 ");  
  
    }  
  
    public static void doMoreStuff() {  
  
        System.out.println("4");  
  
    }  
  
}
```

Which two are possible outputs?

Oracle 1z0-803 Exam

- A. 2
- B. 4
- C. 1
- D. 1

Correct Answer: AB

Section: (none)

Explanation

Explanation/Reference:

Explanation:

A: Output is 2 if Math.random() is greater than 0.5.

B: If Math.random() returns a value less equal to 0.5, the code won't throw an exception, it will continue with the doMore() method which will println "4" after which the program will continue with the doStuff() method and will println "3", after that we will be back in main() and the program will print "1".

QUESTION 54

Given:

```
public class MyFor {  
  
    public static void main(String[] args) {  
  
        for (int ii = 0; ii < 4; ii++) {  
  
            System.out.println("ii = "+ ii);  
  
            ii = ii +1;  
  
        }  
  
    }  
  
}
```

What is the result?

- A. ii = 0
ii = 2

- B. ii =0
ii = 1
ii = 2
www.braindumps.com 54
Oracle 1z0-803 Exam
ii = 3
- C. ii =
- D. Compilation fails.

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 55

Given the code fragment:

```
int [][] array2d = new int[2][3];

System.out.println("Loading the data.");

for ( int x = 0; x < array2d.length; x++) {

    for ( int y = 0; y < array2d[0].length; y++) {

        System.out.println(" x = " + x);

        System.out.println(" y = " + y);

        // insert load statement here.

    }

}

System.out.println("Modify the data. ");

for ( int x = 0; x < array2d.length; x++) {
```

```

for ( int y = 0; y < array2d[0].length; y++) {

System.out.println(" x = " + x);

System.out.println(" y = " + y);

// insert modify statement here.

}

}

```

Which pair of load and modify statement should be inserted in the code?

www.braindumps.com 55

Oracle 1z0-803 Exam

The load statement should set the array's x row and y column value to the sum of x and y

The modify statement should modify the array's x row and y column value by multiplying it by 2

- A. Load statement: `array2d(x, y) = x + y;`
Modify statement: `array2d(x, y) = array2d(x, y) * 2`
- B. Load statement: `array2d[x y] = x + y;`
Modify statement: `array2d[x y] = array2d[x y] * 2`
- C. Load statement: `array2d[x, y] = x + y;`
Modify statement: `array2d[x, y] = array2d[x, y] * 2`
- D. Load statement: `array2d[x][y] = x + y;`
Modify statement: `array2d[x][y] = array2d[x][y] * 2`
- E. Load statement: `array2d[[x][y]] = x + y;`
Modify statement: `array2d[[x][y]] = array2d[[x][y]] * 2`

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 56

Given:

```
public class DoBreak1 {  
    public static void main(String[] args) {  
        String[] table = {"aa", "bb", "cc", "dd"};  
        for (String ss: table) {  
            if ( "bb".equals(ss)) {  
                continue;  
            }  
            System.out.println(ss);  
            if ( "cc".equals(ss)) {  
                break;  
            }  
        }  
    }  
}  
  
www.braindumps.com 56  
Oracle 1z0-803 Exam  
}
```

What is the result?

- A. aa
cc
- B. aa
bb
cc
- C. cc
dd
- D. cc
- E. Compilation fails.

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 57

1. class StaticMethods {

2. static void one() {

3. two();

4. StaticMethods.two();

5. three();

6. StaticMethods.four();

7. }

8. static void two() { }

9. void three() {

10. one();

11. StaticMethods.two();

12. four();

13. StaticMethods.four();

www.braindumps.com 57

Oracle 1z0-803 Exam

14. }

15. void four() { }

16. }

Which three lines are illegal?

- A. line 3
- B. line 4
- C. line 5
- D. line 6
- E. line 10
- F. line 11
- G. line 12
- H. line 13

Correct Answer: CDH

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 58

Which is a valid abstract class?

- A.

```
public abstract class Car {  
    protected void accelerate();  
}
```
- B.

```
public interface Car {  
    protected abstract void accelerate();  
}
```
- C.

```
public abstract class Car {  
    protected final void accelerate();  
}
```
- D.

```
public abstract class Car {  
    protected abstract void accelerate();  
}
```
- E.

```
public abstract class Car {  
    protected abstract void accelerate() {  
        //more car can do  
    }}
```

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

www.braindumps.com 58

Oracle 1z0-803 Exam

Explanation:

QUESTION 59

ON NO: 75

View the exhibit:

```
public class Student {  
  
    public String name = "";  
  
    public int age = 0;  
  
    public String major = "Undeclared";  
  
    public boolean fulltime = true;  
  
    public void display() {  
  
        System.out.println("Name: " + name + " Major: " + major);  
    }  
  
    public boolean isFullTime() {  
  
        return fulltime;  
    }  
}
```

Given:

```
Public class TestStudent {  
  
    public static void main(String[] args) {
```

```
Student bob = new Student ();  
  
bob.name = "Bob";  
  
bob.age = 18;  
  
bob.year = 1982;  
  
}  
  
}
```

www.braindumps.com 59
Oracle 1z0-803 Exam
What is the result?

- A. year is set to 1982.
- B. bob.year is set to 1982
- C. A runtime error is generated.
- D. A compile time error is generated.

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 60

Given the code fragment:

```
String name = "Spot";  
  
int age = 4;  
  
String str ="My dog " + name + " is " + age;  
  
System.out.println(str);
```

And


```
StringBuilder sb = new StringBuilder();
```

Using StringBuilder, which code fragment is the best option to build and print the following string My dog Spot is 4

- A. sb.append("My dog " + name + " is " + age);
System.out.println(sb);
- B. sb.insert("My dog ").append(name + " is " + age); System.out.println(sb);
- C. sb.insert("My dog ").insert(name).insert(" is ").insert(age); System.out.println(sb);
- D. sb.append("My dog ").append(name).append(" is ").append(age); System.out.println(sb);

Correct Answer: AD

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 61

www.braindumps.com 60
Oracle 1z0-803 Exam
TION NO: 77

Given:

```
public class Main {  
  
    public static void main(String[] args) {  
  
        try {  
  
            doSomething();  
  
        }  
  
        catch (SpecialException e) {  
  
            System.out.println(e);  
  
        }  
    }  
}
```

```

static void doSomething() {

int [] ages = new int[4];

ages[4] = 17;

doSomethingElse();

}

static void doSomethingElse() {

throw new SpecialException("Thrown at end of doSomething() method"); }

}

```

What is the output?

- A. SpecialException: Thrown at end of doSomething() method
- B. Error in thread "main" java.lang.
ArrayIndexOutOfBoundsException
- C. Exception in thread "main" java.lang.ArrayIndexOutOfBoundsException: 4 at Main.doSomething(Main.java:12)
at Main.main(Main.java:4)
- D. SpecialException: Thrown at end of doSomething() method at Main.doSomethingElse(Main.java:16)
at Main.doSomething(Main.java:13)
at Main.main(Main.java:4)
www.braindumps.com 61
Oracle 1z0-803 Exam

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

The following line causes a runtime exception (as the index is out of bounds):

ages[4] = 17;

A runtime exception is thrown as an `ArrayIndexOutOfBoundsException`.

Note: The third kind of exception (compared to checked exceptions and errors) is the runtime exception. These are exceptional conditions that are internal to the

application, and that the application usually cannot anticipate or recover from. These usually indicate programming bugs, such as logic errors or improper use of an API.

Runtime exceptions are not subject to the Catch or Specify Requirement. Runtime exceptions are those indicated by `RuntimeException` and its subclasses.

QUESTION 62

View the exhibit:

```
public class Student {  
  
    public String name = "";  
  
    public int age = 0;  
  
    public String major = "Undeclared";  
  
    public boolean fulltime = true;  
  
    public void display() {  
  
        System.out.println("Name: " + name + " Major: " + major);  
    }  
  
    public boolean isFullTime() {  
  
        return fulltime;  
    }  
}
```

Which line of code initializes a student instance?

- A. `Student student1;`
- B. `Student student1 = Student.new();`
- C. `Student student1 = new Student();`
- D. `Student student1 = Student();`

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 63

```
int [] array = {1,2,3,4,5};
```

```
for (int i: array) {
```

```
    if ( i < 2) {
```

```
        keyword1 ;
```

```
    }
```

```
    System.out.println(i);
```

```
    if ( i == 3) {
```

```
        keyword2 ;
```

```
    }}
```

What should keyword1 and keyword2 be respectively, in order to produce output 2345?

- A. continue, break
- B. break, break
- C. break, continue
- D. continue, continue

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 64

```
int i, j=0;
```

```
i = (3* 2 +4 +5 ) ;
```

www.braindumps.com 63

Oracle 1z0-803 Exam

```
j = (3 * ((2+4) + 5));
```

```
System.out.println("i: " + i + "\nj": +j);
```

What is the result?

A. i: 16

j: 33

B. i: 15

j: 33

C. i: 33

j: 23

D. i: 15

j: 23

A. Option A

B. Option B

C. Option C

D. Option D

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 65

```
boolean log3 = ( 5.0 != 6.0) && ( 4 != 5);
```

```
boolean log4 = (4 != 4) || (4 == 4);
```

```
System.out.println("log3:"+ log3 + "\nlog4" + log4);
```

What is the result?

- A. log3:false
log4:true
- B. log3:true
www.braindumps.com 64
Oracle 1z0-803 Exam
log4:true
- C. log3:true
log4:false
- D. log3:false
log4:false

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 66

Which statement will empty the contents of a StringBuilder variable named sb?

- A. sb.deleteAll();
- B. sb.delete(0, sb.size());
- C. sb.delete(0, sb.length());
- D. sb.removeAll();

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 67

Class StaticField {

```
static int i = 7;

public static void main(String[] args) {

    StaticFied obj = new StaticField();

    obj.i++;

    StaticField.i++;

    obj.i++;

    System.out.println(StaticField.i + " " + obj.i);

}

}
```

www.braindumps.com 65
Oracle 1z0-803 Exam
What is the result?

- A. 10 10
- B. 8 9
- C. 9 8
- D. 7 10

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 68

Which two are valid array declaration?

- A. Object array[];
- B. Boolean array[3];

- C. int[] array;
- D. Float[2] array;

Correct Answer: AC

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 69

Given:

```
class Overloading {  
  
    int x(double d) {  
  
        System.out.println("one");  
  
        return 0;  
  
    }  
  
    String x(double d) {  
  
        System.out.println("two");  
  
        return null;  
  
        www.braindumps.com 66  
        Oracle 1z0-803 Exam  
    }  
  
    double x(double d) {  
  
        System.out.println("three");  
  
        return 0.0;  
  
    }  
  
    public static void main(String[] args) {
```



```
new Overloading().x(4.0);  
  
}  
  
}
```

What is the result?

- A. One
- B. Two
- C. Three
- D. Compilation fails.

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 70

Given:

```
public class MainMethod {  
  
    void main() {  
  
        System.out.println("one");  
  
    }  
  
    static void main(String args) {  
  
        System.out.println("two");  
  
    }  
  
    public static void main(String[] args) {
```

Oracle 1z0-803 Exam

```
System.out.println("three");
```

```
}
```

```
void mina(Object[] args) {
```

```
System.out.println("four");
```

```
}
```

```
}
```

What is printed out when the program is executed?

A. one

B. two

C. three

D. four

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 71

Given:

```
public class ScopeTest {
```

```
int j, int k;
```

```
public static void main(String[] args) {
```

```
new ScopeTest().doStuff(); }
```

```
void doStuff() {
```

```
int x = 5;
```

```

oStuff2();

System.out.println("x");

}

void doStuff2() {

    int y = 7;

    www.braindumps.com 68
    Oracle 1z0-803 Exam
    System.out.println("y");

    for (int z = 0; z < 5; z++) {

        System.out.println("z");

        System.out.println("y");

    }

```

Which two items are fields?

- A. j
- B. k
- C. x
- D. y
- E. z

Correct Answer: AB

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 72

A method is declared to take three arguments. A program calls this method and passes only two arguments. What is the results?

- A. Compilation fails.
- B. The third argument is given the value null.
- C. The third argument is given the value void.
- D. The third argument is given the value zero.
- E. The third argument is given the appropriate falsy value for its declared type. F) An exception occurs when the method attempts to access the third argument.

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 73

```
public class ForTest {  
  
    public static void main(String[] args) {  
  
        www.braindumps.com 69  
        Oracle 1z0-803 Exam  
        int[] arrar = {1,2,3};  
  
        for ( foo ) {  
  
        }  
  
        }  
  
    }
```

Which three are valid replacements for foo so that the program will compiled and run?

- A. int i: array
- B. int i = 0; i < 1; i++
- C. ;;
- D. ; i < 1; i++
- E. ; i < 1;

Correct Answer: ABC

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 74

Given:

```
public class SampleClass {  
  
    public static void main(String[] args) {  
  
        AnotherSampleClass asc = new AnotherSampleClass(); SampleClass sc = new SampleClass();  
  
        sc = asc;  
  
        System.out.println("sc: " + sc.getClass());  
  
        System.out.println("asc: " + asc.getClass());  
  
    }  
  
    class AnotherSampleClass extends SampleClass {  
  
    }  
}
```

What is the result?

www.braindumps.com 70

Oracle 1z0-803 Exam

- A. sc: class Object
asc: class AnotherSampleClass
- B. sc: class SampleClass
asc: class AnotherSampleClass
- C. sc: class AnotherSampleClass
asc: class SampleClass
- D. sc: class AnotherSampleClass
asc: class AnotherSampleClass

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 75

Given the code fragment:

```
int b = 3;

if ( !(b > 3)) {

    System.out.println("square ");

}

System.out.println("circle ");

}

System.out.println("...");
```

What is the result?

- A. square...
- B. circle...
- C. squarecircle...
- D. Compilation fails.

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 76

What is the proper way to defined a method that take two int values and returns their sum as an int

www.braindumps.com 71
Oracle 1z0-803 Exam
value?

- A. `int sum(int first, int second) { first + second; }`
- B. `int sum(int first, second) {return first + second; }`
- C. `sum(int first, int second) { return first + second; }`
- D. `int sum(int first, int second) { return first + second; }`
- E. `void sum (int first, int second) { return first + second; }`

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 77

Which two are Java Exception classes?

- A. `SercurityException`
- B. `DuplicatePathException`
- C. `IllegalArgumentException`
- D. `TooManyArgumentsException`

Correct Answer: AC

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 78

Given the for loop construct:

```
for ( expr1 ; expr2 ; expr3 ) {
```

```
statement;
```

```
}
```

Which two statements are true?

- A. This is not the only valid for loop construct; there exists another form of for loop constructor.
- B. The expression expr1 is optional. it initializes the loop and is evaluated once, as the loop begins.
- C. When expr2 evaluates to false, the loop terminates. It is evaluated only after each iteration through the loop.
- D. The expression expr3 must be present. It is evaluated after each iteration through the loop.

www.braindumps.com 72

Oracle 1z0-803 Exam

Correct Answer: BC

Section: (none)

Explanation

Explanation/Reference:

Explanation:

The for statement has this form:

```
for (init-stmt;condition;next-stmt) {  
    body  
}
```

There are three clauses in the for statement.

The init-stmt statement is done before the loop is started, usually to initialize an iteration variable. The condition expression is tested before each time the loop is done. The loop isn't executed if the boolean expression is false (the same as the while loop). The next-stmt statement is done after the body is executed. It typically increments an iteration variable.

QUESTION 79

```
public class StringReplace {  
  
    public static void main(String[] args) {  
  
        String message = "Hi everyone!";  
  
        System.out.println("message = " + message.replace("e", "X")); }  
  
}
```

What is the result?

- A. message = Hi everyone!

- B. message = Hi XvXryonX!
- C. A compile time error is produced.
- D. A runtime error is produced.
- E. message =
- F. message = Hi Xeveryone!

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 80

QUESTION NO: 96

www.braindumps.com 73

Oracle 1z0-803 Exam

Which two statements are true for a two-dimensional array?

- A. It is implemented as an array of the specified element type.
- B. Using a row by column convention, each row of a two-dimensional array must be of the same size.
- C. At declaration time, the number of elements of the array in each dimension must be specified.
- D. All methods of the class Object may be invoked on the two-dimensional array.

Correct Answer: AD

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 81

Which three statements are benefits of encapsulation?

- A. Allows a class implementation to change without changing the clients
- B. Protects confidential data from leaking out of the objects
- C. Prevents code from causing exceptions

- D. Enables the class implementation to protect its invariants
- E. Permits classes to be combined into the same package
- F. Enables multiple instances of the same class to be created safely

Correct Answer: ABD

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 82

The protected modifier on a Field declaration within a public class means that the field _____.



<http://www.gratisexam.com/>

- A. Cannot be modified
- B. Can be read but not written from outside the class
- C. Can be read and written from this class and its subclasses only within the same package
- D. Can be read and written from this class and its subclasses defined in any package

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Reference:

<http://beginnersbook.com/2013/05/java-access-modifiers/>

www.braindumps.com 74

Oracle 1z0-803 Exam

QUESTION 83

Given:

Given:

```
class Caller {  
    private void init() {  
        System.out.println("Initialized");  
    }  
  
    public void start() {  
        init();  
        System.out.println("Started");  
    }  
}  
  
public class TestCall {  
    public static void main(String[] args) {  
        Caller c = new Caller();  
        c.start();  
        c.init();  
    }  
}
```

What is the result?

- A. Initialized
Started
- B. Initialized
Started
Initialized
- C. Compilation fails

D. An exception is thrown at runtime

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 84

Given:

www.braindumps.com 75

Oracle 1z0-803 Exam

```
public class X implements Z {
    public String toString() {
        return "X ";
    }
    public static void main(String[] args) {
        Y myY = new Y();
        X myX = myY;
        Z myZ = myX;
        System.out.print(myX);
        System.out.print((Y)myX);
        System.out.print(myZ);
    }
}

class Y extends X {
    public String toString() {
        return "Y ";
    }
}
```

- A. X XX
- B. X Y X
- C. Y Y X
- D. Y YY

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 85

Given:

www.braindumps.com 76
Oracle 1z0-803 Exam

```

class Alpha {
    int ns;
    static int s;
    Alpha(int ns) {
        if (s < ns) {
            s = ns;
            this.ns = ns;
        }
    }
    void doPrint() {
        System.out.println("ns = " + ns + " s = " + s);
    }
}

```

And,

```

public class TestA {
    public static void main(String[] args) {
        Alpha ref1 = new Alpha(50);
        Alpha ref2 = new Alpha(125);
        Alpha ref3 = new Alpha(100);
        ref1.doPrint();
        ref2.doPrint();
        ref3.doPrint();
    }
}

```

- A. ns = 50 S = 125
ns = 125 S = 125
ns = 100 S = 125
- B. ns = 50 S = 125
ns = 125 S = 125
ns = 0 S = 125
- C. ns = 50 S = 50
ns = 125 S = 125
ns = 100 S = 100
- D. ns = 50 S = 50

ns = 125 S = 125
ns = 0 S = 125

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 86

Given:

Class A { }

Class B { }

Interface X { }

www.braindumps.com 77

Oracle 1z0-803 Exam

Interface Y { }

Which two definitions of class C are valid?

- A. Class C extends A implements X { }
- B. Class C implements Y extends B { }
- C. Class C extends A, B { }
- D. Class C implements X, Y extends B { }
- E. Class C extends B implements X, Y { }

Correct Answer: AE

Section: (none)

Explanation

Explanation/Reference:

Explanation: extends is for extending a class.

implements is for implementing an interface.

Java allows for a class to implement many interfaces.

QUESTION 87

Given the code fragment

```
class Test2 {  
    int fvar;  
    static int cvar;  
    public static void main(String[] args) {  
        Test2 t = new Test2();  
        // insert code here to write field variables  
    }  
}
```

Which code fragments, inserted independently, enable the code compile?

- A. t.fvar = 200;
- B. cvar = 400;
- C. fvar = 200;
 cvar = 400;
- D. this.fvar = 200;
 this.cvar = 400;
- E. t.fvar = 200;
 Test2.cvar = 400;
- F. this.fvar = 200;
 www.braindumps.com 78
 Oracle 1z0-803 Exam
 Test2.cvar = 400;

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 88

View the exhibit.

```
class MissingInfoException extends Exception { }

class AgeOutOfRangeException extends Exception { }

class Candidate {
    String name;
    int age;
    Candidate(String name, int age) throws Exception {
        if (name == null) {
            throw new MissingInfoException();
        } else if (age <= 10 || age >= 150) {
            throw new AgeOutOfRangeException();
        } else {
            this.name = name;
            this.age = age;
        }
    }
    public String toString() {
        return name + " age: " + age;
    }
}
```

Given the code fragment:

```

4. public class Test {
5.     public static void main(String[] args) {
6.         Candidate c = new Candidate("James", 20);
7.         Candidate c1 = new Candidate("Williams", 32);
8.         System.out.println(c);
9.         System.out.println(c1);
10.    }
11. }

```

Which change enables the code to print the following?

James age: 20

Williams age: 32

- A. Replacing line 5 with `public static void main (String [] args) throws MissingInfoException, www.braindumps.com 79 Oracle 1z0-803 Exam AgeOutOfRangeException {`
- B. Replacing line 5 with `public static void main (String [] args) throws.Exception {`
- C. Enclosing line 6 and line 7 within a try block and adding:
`catch(Exception e1) { //code goes here}`
`catch (missingInfoException e2) { //code goes here}`
`catch (AgeOutOfRangeException e3) { //code goes here}`
- D. Enclosing line 6 and line 7 within a try block and adding:
`catch (missingInfoException e2) { //code goes here}`
`catch (AgeOutOfRangeException e3) { //code goes here}`

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 89

Given:

```

public class Test {

    static void dispResult(int[] num) {
        try {
            System.out.println(num[1] / (num[1] - num[2]));
        } catch (ArithmeticException e) {
            System.err.println("first exception");
        }
        System.out.println("Done");
    }

    public static void main(String[] args) {
        try {
            int[] arr = {100, 100};
            dispResult(arr);
        } catch (IllegalArgumentException e) {
            System.err.println("second exception");
        } catch (Exception e) {
            System.err.println("third exception");
        }
    }
}

```

What is the result?

- A. 0
Done
- B. First Exception
Done
- C. Second Exception
- D. Done
Third Exception
- E. Third Exception

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 90

Given the code format:

```
class DBConfiguration {  
    String user;  
    String password;  
}
```

And:

```
4. public class DBHandler {  
5.     DBConfiguration configureDB(String uname, String password) {  
6.         // insert code here  
7.     }  
8.     public static void main(String[] args) {  
9.         DBHandler r = new DBHandler();  
10.        DBConfiguration dbConf = r.configureDB("manager", "manager");  
11.    }  
12. }
```

Which code fragment must be inserted at line 6 to enable the code to compile?

- A. DBConfiguration f;
return f;
- B. Return DBConfiguration;
- C. Return new DBConfiguration;
- D. Return 0;

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 91

Given:

www.braindumps.com 81

Oracle 1z0-803 Exam

```
class Test {  
    int sum = 0;  
    public void doCheck(int number) {  
        if (number % 2 == 0) {  
            break;  
        } else {  
            for (int i = 0; i < number; i++) {  
                sum += i;  
            }  
        }  
    }  
    public static void main(String[] args) {  
        Test obj = new Test();  
        System.out.println("Red " + obj.sum);  
        obj.doCheck(2);  
        System.out.println("Orange " + obj.sum);  
        obj.doCheck(3);  
        System.out.println("Green " + obj.sum);  
    }  
}
```

What is the result?

- A. Red 0
Orange 0
Green 3
- B. Red 0
Orange 0
Green 6
- C. Red 0
Orange 1
- D. Green 4
- E. Compilation fails

Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 92

Given the code fragment:

www.braindumps.com 82

Oracle 1z0-803 Exam

```
String color = "teal";

switch (color) {
    case "Red":
        System.out.println("Found Red");
    case "Blue":
        System.out.println("Found Blue");
        break;
    case "Teal":
        System.out.println("Found Teal");
        break;
    default:
        System.out.println("Found Default");
}
```

What is the result?

- A. Found Red
Found Default
- B. Found Teal
- C. Found Red
Found Blue
Found Teal
- D. Found Red
Found Blue
Found Teal
Found Default
- E. Found Default

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 93

Given:

www.braindumps.com 83
Oracle 1z0-803 Exam

Given:

```
class X {  
    public void mX() {  
        System.out.println("Xm1");  
    }  
}  
class Y extends X {  
    public void mX() {  
        System.out.println("Xm2");  
    }  
    public void mY() {  
        System.out.println("Ym");  
    }  
}  
  
public class Test {  
    public static void main(String[] args) {  
        X xRef = new Y();  
        Y yRef = (Y) xRef;  
        yRef.mY();  
        xRef.mX();  
    }  
}
```

- A. Ym
Xm2
- B. Ym
Xm1
- C. Compilation fails
- D. A ClassCastException is thrown at runtime

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 94

Given:

```
public class Test2 {  
    public static void main(String[] args) {  
        int ar1[] = {2, 4, 6, 8};  
        int ar2[] = {1, 3, 5, 7, 9};  
        ar2 = ar1;  
        for (int e2 : ar2) {  
            System.out.print(" " + e2);  
        }  
    }  
}
```

www.braindumps.com 84

Oracle 1z0-803 Exam

What is the result?

- A. 2 4 6 8
- B. 2 4 6 8 9
- C. 1 3 5 7
- D. 1 3 5 7 9

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 95

Given:

```
public class MyFor1 {  
    public static void main(String[] args) {  
        int[] x = {6, 7, 8};  
        for (int i : x) {  
            System.out.print(i + " ");  
            i++;  
        }  
    }  
}
```

What is the result?

- A. 6 7 8
- B. 7 8 9
- C. 0 1 2
- D. 6 8 10
- E. Compilation fails

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 96

Given:

www.braindumps.com 85
Oracle 1z0-803 Exam

```
public class Calculator {  
    public static void main(String[] args) {  
        int num = 5;  
        int sum;  
  
        do {  
            sum += num;  
        } while ((num--) > 1);  
  
        System.out.println("The sum is " + sum + ".");  
    }  
}
```

What is the result?

- A. The sum is 2
- B. The sum is 14
- C. The sum is 15
- D. The loop executes infinite times
- E. Compilation fails

Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 97

Given:

```

package p1;
public interface DoInterface {
    void m1(int n);
    public void m2(int n);           // line n1
}

package p3;
import p1.DoInterface;
public class DoClass implements DoInterface{
    int x1,x2;
    DoClass(){
        this.x1 = 0;
        this.x2 = 10;
    }
    public void m1(int p1) { x1+=p1; System.out.println(x1); } // line n2
    public void m2(int p1) { x2+=p1; System.out.println(x2); }
}

package p2;
import p1.*;
import p3.*;
class Test {
    public static void main(String[] args){
        DoInterface doi= new DoClass(); // line n3
        doi.method1(100);
        doi.method2(200);
    }
}

```

What is the result?

www.braindumps.com 86
Oracle 1z0-803 Exam

- A. 100
- B. Compilation fails due to an error in line n1

- C. Compilation fails due to an error at line n2
- D. Compilation fails due to an error at line n3

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 98

Given:

```
public class TestTry {
    public static void main(String[] args) {
        StringBuilder message = new StringBuilder("hello java!");
        int pos = 0;
        try {
            for ( pos = 0; pos < 12; pos++) {
                switch (message.charAt(pos)) {
                    case 'a':
                    case 'e':
                    case 'o':
                        String uc=Character.toString(message.charAt(pos)).toUpperCase();
                        message.replace(pos, pos+1, uc);
                }
            }
        } catch (Exception e) {
            System.out.println("Out of limits");
        }
        System.out.println(message);
    }
}
```

What is the result?

- A. hEllojAvA!

- B. Hello java!
- C. Out of limits
hElIOjAvA!
- D. Out of limits

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 99

Given:

www.braindumps.com 87

Oracle 1z0-803 Exam

```
public class App {  
    public static void main(String[] args) {  
        int i = 10;  
        int j = 20;  
        int k = j += i / 5;  
        System.out.print(i + " : " + j + " : " + k);  
    }  
}
```

What is the result?

- A. 10 : 22 : 20
- B. 10 : 22 : 22
- C. 10 : 22 : 6
- D. 10 : 30 : 6

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 100

Given the code fragment:

```
int[] lst = {1, 2, 3, 4, 5, 4, 3, 2, 1};  
int sum = 0;  
for (int frnt = 0, rear = lst.length - 1;  
     frnt < 5 && rear >= 5;  
     frnt++, rear--) {  
    sum = sum + lst[frnt] + lst[rear];  
}  
System.out.print(sum);
```

What is the result?

- A. 20
- B. 25
- C. 29
- D. Compilation fails
- E. AnArrayIndexOutOfBoundsException is thrown at runtime

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation:

www.braindumps.com 88
Oracle 1z0-803 Exam

QUESTION 101

Given:

```
public class X {  
    public static void main(String[] args){  
        String theString = "Hello World";  
        System.out.println(theString.charAt(11));  
    }  
}
```

What is the result?

- A. The program prints nothing
- B. d
- C. A `StringIndexOutOfBoundsException` is thrown at runtime.
- D. An `ArrayIndexOutOfBoundsException` is thrown at runtime.
- E. A `NullPointerException` is thrown at runtime.

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 102

Which two statements are true for a two-dimensional array of primitive data type?

- A. It cannot contain elements of different types.
- B. The length of each dimension must be the same.
- C. At the declaration time, the number of elements of the array in each dimension must be specified.
- D. All methods of the class object may be invoked on the two-dimensional array.

Correct Answer: CD

Section: (none)

Explanation

Explanation/Reference:

Explanation: <http://stackoverflow.com/questions/12806739/is-an-array-a-primitive-type-or-an-object-or-something-else-entirely>

QUESTION 103

www.braindumps.com 89
Oracle 1z0-803 Exam
Given the code fragment:

```
String[] colors = {"red", "blue", "green", "yellow", "maroon", "cyan"};
```

Which code fragment prints blue, cyan, ?

```
C A) for (String c:colors){
    if (c.length() != 4) {
        continue;
    }
    System.out.print(c+", ");
}

C B) for (String c:colors[]) {
    if (c.length() <= 4) {
        continue;
    }
    System.out.print(c+", ");
}

C C) for (String c:String[] colors) {
    if (c.length() >= 3) {
        continue;
    }
    System.out.print(c+", ");
}

C D) for (String c:colors){
    if (c.length() != 4) {
        System.out.print(c+", ");
        continue;
    }
}
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Correct Answer: A
Section: (none)

Explanation

Explanation/Reference:

Explanation:

www.braindumps.com 90
Oracle 1z0-803 Exam

QUESTION 104

Given:

```
public class MyFor3 {  
    public static void main(String[] args) {  
        int[] xx = null;  
        for (int ii : xx) {  
            System.out.println(ii);  
        }  
    }  
}
```

What is the result?

- A. Null
- B. Compilation fails
- C. An exception is thrown at runtime
- D. 0

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 105

Given:

```

public class Test3 {
    public static void main(String[] args) {
        String names[] = new String[3];
        names[0] = "Mary Brown";
        names[1] = "Nancy Red";
        names[2] = "Jessy Orange";
        try {
            for(String n: names) {
                try {
                    String pwd = n.substring(0, 3)+n.substring(6, 10);
                    System.out.println(pwd);
                }
                catch (StringIndexOutOfBoundsException sie) {
                    System.out.println("string out of limits");
                }
            }
        }
        catch (ArrayIndexOutOfBoundsException e) {
            System.out.println("array out of limits");
        }
    }
}

```

What is the result?

www.braindumps.com 91
Oracle 1z0-803 Exam

- A. Marrown
String out of limits
JesOran
- B. Marrown
String out of limits
Array out of limits
- C. Marrown
String out of limits
- D. Marrown

NanRed
JesOran

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 106

Given:

```
public abstract class Shape {  
    private int x;  
    private int y;  
    public abstract void draw();  
    public void setAnchor(int x, int y) {  
        this.x = x;  
        this.y = y;  
    }  
}
```

Which two classes use the shape class correctly?

www.braindumps.com 92

Oracle 1z0-803 Exam

- ☐ A) `public class Circle implements Shape {
 private int radius;
}`
- ☐ B) `public abstract class Circle extends Shape {
 private int radius;
}`
- ☐ C) `public class Circle extends Shape {
 private int radius;
 public void draw();
}`
- ☐ D) `public abstract class Circle implements Shape {
 private int radius;
 public void draw();
}`
- ☐ E) `public class Circle extends Shape {
 private int radius;
 public void draw() { /* code here */ }
}`
- ☐ F) `public abstract class Circle implements Shape {
 private int radius;
 public void draw() { /* code here */ }
}`

- A. Option A
- B. Option B
- C. Option C
- D. Option D
- E. Option E
- F. Option F

Correct Answer: BE

Section: (none)

Explanation

Explanation/Reference:

Explanation: When an abstract class is subclassed, the subclass usually provides implementations for all of the abstract methods in its parent class (E). However, if it does not, then the subclass must also be declared abstract (B).

Note: An abstract class is a class that is declared abstract--it may or may not include abstract methods. Abstract classes cannot be instantiated, but they can be subclassed.

QUESTION 107

Given the class definitions:

www.braindumps.com 93

Oracle 1z0-803 Exam

```
class Alpha {  
    public String doStuff(String msg) {  
        return msg;  
    }  
}  
class Beta extends Alpha {  
    public String doStuff(String msg) {  
        return msg.replace('a', 'e');  
    }  
}  
class Gamma extends Beta {  
    public String doStuff(String msg) {  
        return msg.substring(2);  
    }  
}
```

And the code fragment of the main() method,

```
12. List<Alpha> strs = new ArrayList<Alpha>();
13. strs.add(new Alpha());
14. strs.add(new Beta());
15. strs.add(new Gamma());
16. for (Alpha t : strs) {
17.     System.out.println(t.doStuff("Java"));
18. }
```

What is the result?

- A. Java
Java
Java
- B. Java
Jeve
va
- C. Java
Jeve
ve
- D. Compilation fails

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 108

Given:

www.braindumps.com 94
Oracle 1z0-803 Exam


```
public class Msg {  
    public static String doMsg(char x) {  
        return "Good Day!";  
    }  
    public static String doMsg(int y) {  
        return "Good Luck!";  
    }  
    public static void main(String[] args) {  
        char x = 8;  
        int z = '8';  
        System.out.println(doMsg(x));  
        System.out.print(doMsg(z));  
    }  
}
```

What is the result?

- A. Good Day!
Good Luck!
- B. Good Day!
Good Day!
- C. Good Luck!
Good Day!
- D. Good Luck!
Good Luck!
- E. Compilation fails

Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 109

Which two items can legally be contained within a java class declaration?

- A. An import statement
- B. A field declaration
- C. A package declaration
- D. A method declaration

Correct Answer: BD

Section: (none)

Explanation

Explanation/Reference:

Explanation:

Reference:

<http://docs.oracle.com/javase/tutorial/java/javaOO/methods.html>

www.braindumps.com 95

Oracle 1z0-803 Exam

QUESTION 110

Given the fragments:

```

public class TestA extends Root {
    public static void main(String[] args) {
        Root r = new TestA();
        System.out.println(r.method1());    // line n1
        System.out.println(r.method2());    // line n2
    }
}
class Root {
    private static final int MAX = 20000;
    private int method1() {
        int a = 100 + MAX;                // line n3
        return a;
    }
    protected int method2() {
        int a = 200 + MAX;                // line n4
        return a;
    }
}

```

Which line causes a compilation error?

- A. Line n1
- B. Line n2
- C. Line n3
- D. Line n4

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 111

Given:

```
public class Case {  
    public static void main(String[] args) {  
        String product = "Pen";  
        product.toLowerCase();  
        product.concat(" BOX".toLowerCase());  
        System.out.print(product.substring(4, 6));  
    }  
}
```

www.braindumps.com 96

Oracle 1z0-803 Exam

What is the result?

- A. box
- B. nbo
- C. bo
- D. nb
- E. An exception is thrown at runtime

Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 112

Given the code fragments:

```

interface Contract{ }
class Super implements Contract{ }
class Sub extends Super {}

public class Ref {
    public static void main(String[] args) {
        List objs = new ArrayList();

        Contract c1 = new Super();
        Contract c2 = new Sub(); // line n1
        Super s1 = new Sub();

        objs.add(c1);
        objs.add(c2);
        objs.add(s1); // line n2

        for(Object itm: objs) {
            System.out.println(itm.getClass().getName());
        }
    }
}

```

What is the result?

- A. Super
Sub
Sub
- B. Contract
Contract
Super
- C. Compilation fails at line n1
- D. Compilation fails at line n2

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Explanation:

www.braindumps.com 97
Oracle 1z0-803 Exam

QUESTION 113

Given:

```
class Star {
    public void doStuff() {
        System.out.println("Twinkling Star");
    }
}

interface Universe {
    public void doStuff();
}

class Sun extends Star implements Universe {
    public void doStuff() {
        System.out.println("Shining Sun");
    }
}

public class Bob {
    public static void main(String[] args) {
        Sun obj2 = new Sun();
        Star obj3 = obj2;
        ((Sun) obj3).doStuff();
        ((Star) obj2).doStuff();
        ((Universe) obj2).doStuff();
    }
}
```

What is the result?

- A. Shining Sun
Shining Sun
Shining Sun
- B. Shining Sun
Twinkling Star
Shining Sun

- C. Compilation fails
- D. A ClassCastException is thrown at runtime

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 114

Given the code fragment:

www.braindumps.com 98
Oracle 1z0-803 Exam

```

interface Contract{ }
class Super implements Contract{ }
class Sub extends Super {}

public class Ref {
    public static void main(String[] args) {
        List objs = new ArrayList();

        Contract c1 = new Super();
        Contract c2 = new Sub(); // line n1
        Super s1 = new Sub();

        objs.add(c1);
        objs.add(c2);
        objs.add(s1); // line n2

        for(Object itm: objs) {
            System.out.println(itm.getClass().getName());
        }
    }
}

```

- A. Super
Sub
Sub
- B. Contract
Contract
Super
- C. Compilation fails at line n1
- D. Compilation fails at line n2

Correct Answer: D
Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 115

Given the code fragment:

```
public static void main(String[] args) {  
    ArrayList<String> list = new ArrayList<>();  
  
    list.add("SE");  
    list.add("EE");  
    list.add("ME");  
    list.add("SE");  
    list.add("EE");  
  
    list.remove("SE");  
  
    System.out.print("Values are : " + list);  
}
```

What is the result?

www.braindumps.com 99
Oracle 1z0-803 Exam

- A. Values are : [EE, ME]
- B. Values are : [EE, EE, ME]
- C. Values are : [EE, ME, EE]
- D. Values are : [SE, EE, ME, EE]
- E. Values are : [EE, ME, SE, EE]

Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 116

Given:

```
abstract class X {  
    public abstract void methodX();  
}  
interface Y {  
    public void methodY();  
}
```

Which two code fragments are valid?

- ☐ A)

```
class Z extends X implements Y {  
    public void methodZ() {}  
}
```
- ☐ B)

```
abstract class Z extends X implements Y {  
    public void methodZ() {}  
}
```
- ☐ C)

```
class Z extends X implements Y {  
    public void methodX() {}  
}
```
- ☐ D)

```
abstract class Z extends X implements Y {  
}
```
- ☐ E)

```
class Z extends X implements Y {  
    public void methodY() {}  
}
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D
- E. Option E

www.braindumps.com 100
Oracle 1z0-803 Exam

Correct Answer: BC

Section: (none)

Explanation

Explanation/Reference:

Explanation: When an abstract class is subclassed, the subclass usually provides implementations for all of the abstract methods in its parent class (C). However, if it does not, then the subclass must also be declared abstract (B). Note: An abstract class is a class that is declared abstract--it may or may not include abstract methods. Abstract classes cannot be instantiated, but they can be subclassed.

QUESTION 117

Which two actions will improve the encapsulation of a class?

- A. Changing the access modifier of a field from public to private
- B. Removing the public modifier from a class declaration
- C. Changing the return type of a method to void
- D. Returning a copy of the contents of an array or ArrayList instead of a direct reference

Correct Answer: AD

Section: (none)

Explanation

Explanation/Reference:

Explanation:

Reference:

http://www.tutorialspoint.com/java/java_access_modifiers.htm

QUESTION 118

Given:

```
public class Vowel {  
    private char var;  
    public static void main(String[] args) {  
        char var1 = 'a';  
        char var2 = var1;  
        var2 = 'e';  
  
        Vowel obj1 = new Vowel();  
        Vowel obj2 = obj1;  
        obj1.var = 'i';  
        obj2.var = 'o';  
  
        System.out.println(var1 + ", " + var2);  
        System.out.print(obj1.var + ", " + obj2.var);  
    }  
}
```

www.braindumps.com 101
Oracle 1z0-803 Exam

- A. a, e
i, o
- B. a, e
o, o
- C. e, e
i, o
- D. e, e
o, o

Correct Answer: B
Section: (none)
Explanation

Explanation/Reference:

Explanation:

QUESTION 119

Given:

```
public class Circle {
    double radius;
    public double area;
    public Circle(double r) { radius = r; }
    public double getRadius() { return radius; }
    public void setRadius(double r) { radius = r; }
    public double getArea() { return /* ??? */; }
}

class App {
    public static void main(String[] args) {
        Circle c1 = new Circle(17.4);
        c1.area = Math.PI * c1.getRadius() * c1.getRadius();
    }
}
```

The class is poorly encapsulated. You need to change the circle class to compute and return the area instead.

Which two modifications are necessary to ensure that the class is being properly encapsulated?

- A. Remove the area field.
- B. Change the getArea() method as follows:
public double getArea() { return Math.PI * radius * radius; }
- C. Add the following method:
public double getArea() { area = Math.PI * radius * radius; }
- D. Change the access modifier of the setRadius() method to be protected.

Correct Answer: BD

Section: (none)

Explanation

Explanation/Reference:

Explanation:

www.braindumps.com 102
Oracle 1z0-803 Exam

QUESTION 120

Given:

```
1. import java.io.Error;
2.     public class TestApp {
3.     public static void main(String[] args) {
4.         TestApp t = new TestApp();
5.         try {
6.             t.doPrint();
7.             t.doList();
8.
9.         } catch (Exception e2) {
10.            System.out.println("Caught " + e2);
11.        }
12.    }
13.    public void doList() throws Exception {
14.        throw new Error("Error");
15.    }
16.    public void doPrint() throws Exception {
17.        throw new RuntimeException("Exception");
18.    }
19. }
```

What is the result?

☐ A) Caught java.lang.RuntimeException: Exception
Exception in thread "main" java.lang.Error: Error
at TestApp.doList(TestApp.java: 14)
at TestApp.main(TestApp.java: 6)

☐ B) Exception in thread "main" java.lang.Error: Error
at TestApp.doList(TestApp.java: 14)
at TestApp.main(TestApp.java: 6)

☐ C) Caught java.lang.RuntimeException: Exception
Caught java.lang.Error: Error

☐ D) Caught java.lang.RuntimeException: Exception

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 121

www.braindumps.com 103

Oracle 1z0-803 Exam

Given:

```
1. public class TestLoop {  
2.     public static void main(String[] args) {  
3.         float myarray[] = {10.20f, 20.30f, 30.40f, 50.60f};  
4.         int index = 0;  
5.         boolean isFound = false;  
6.         float key = 30.40f;  
7.         // insert code here  
8.         System.out.println(isFound);  
9.     }  
10. }
```

Which code fragment, when inserted at line 7, enables the code print true?


```
C A) while (key == myarray[index++]) {  
    isFound = true;  
}  
  
C B) while (index <= 4) {  
    if (key == myarray[index]) {  
        index++;  
        isFound = true;  
        break;  
    }  
}  
  
C C) while (index++ < 5) {  
    if (key == myarray[index]) {  
        isFound = true;  
    }  
}  
  
C D) while (index < 5) {  
    if (key == myarray[index]) {  
        isFound = true;  
        break;  
    }  
    index++;  
}
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Correct Answer: A

Section: (none)


Explanation

Explanation/Reference:

Explanation:

QUESTION 122

Given the code fragment:



```
if (aVar++ < 10) {  
    System.out.println(aVar + " Hello World!");  
} else {  
    System.out.println(aVar + " Hello Universe!");  
}
```

What is the result if the integer aVar is 9?

- A. 10 Hello world!
- B. 10 Hello universe!
- C. 9 Hello world!
- D. Compilation fails.

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 123

Given:

Test.java

```
public class Test {  
    public static void main(String[] args) {  
        Integer num = Integer.parseInt(args[1]);  
        System.out.println("Number is : " + num);  
    }  
}
```

And the commands:

Javac Test.java

Java Test 12345

What is the result?

- A. Number us : 12345
- B. A NullPointerException is thrown at runtime
www.braindumps.com 105
Oracle 1z0-803 Exam
- C. A NumberFormatException is thrown at runtime
- D. AnArrayIndexOutOfBoundsException is thrown at runtime.

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 124

Given the code fragment:

```

public class Test {
    public static List data = new ArrayList();

    // insert code here
    {
        for (String x : strs) {
            data.add(x);
        }
        return data;
    }

    public static void main(String[] args) {
        String[] d = {"a", "b", "c"};
        update(d);
        for (String s : d) {
            System.out.print(s + " ");
        }
    }
}

```

Which code fragment, when inserted at // insert code here, enables the code to compile and and print a b c?

- A. List update (String[] strs)
- B. Static ArrayListupdate(String [] strs)
- C. Static List update (String [] strs)
- D. Static void update (String[] strs)
- E. ArrayList static update(String [] strs)

Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 125

Given the code fragment:



<http://www.gratisexam.com/>

www.braindumps.com 106
Oracle 1z0-803 Exam

```
System.out.println( 28 + 5 <= 4 + 29 );  
System.out.println( ( 28 + 5 ) <= { 4 + 29 } );
```

What is the result?

- A. 28false29
true
- B. 285 < 429
true
- C. true
true
- D. compilation fails

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 126

Given:

```

public class Access {
    private int x = 0;
    private int y = 0;

    public static void main(String[] args) {
        Access accApp = new Access();
        accApp.printThis(1, 2);
        accApp.printThat(3, 4);
    }

    public void printThis(int x, int y) {
        x = x;
        y = y;
        System.out.println("x:" + this.x + " y:" + this.y);
    }

    public void printThat(int x, int y) {
        this.x = x;
        this.y = y;
        System.out.println("x:" + this.x + " y:" + this.y);
    }
}

```

What is the result?

- A. x: 1 y: 2
- B. 3 y: 4
- C. x: 0 y: 0
- D. 3 y: 4
- www.braindumps.com 107
- Oracle 1z0-803 Exam
- E. x: 1 y: 2
- F. 0 y: 0
- G. x: 0 y: 0
- H. 0 y: 0

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 127

Given the code fragment:

```
class Student {  
    String name;  
    int age;  
}  
  
And,  
  
1. public class Test {  
2.     public static void main(String[] args) {  
3.         Student s1 = new Student();  
4.         Student s2 = new Student();  
5.         Student s3 = new Student();  
6.         s1 = s3;  
7.         s3 = s2;  
8.         s2 = null;  
9.     }  
10. }
```

Which statement is true?

- A. After line 8, three objects are eligible for garbage collection
- B. After line 8, two objects are eligible for garbage collection
- C. After line 8, one object is eligible for garbage collection
- D. After line 8, none of the objects are eligible for garbage collection

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 128

Given:

www.braindumps.com 108

Oracle 1z0-803 Exam

```
class SpecialException extends Exception {
    public SpecialException(String message) {
        super(message);
        System.out.println(message);
    }
}

public class ExceptionTest {
    public static void main(String[] args) {
        try {
            doSomething();
        }
        catch (SpecialException e) {
            System.out.println(e);
        }
    }

    static void doSomething() throws SpecialException {
        int[] ages = new int[4];
        ages[4] = 17;
        doSomethingElse();
    }

    static void doSomethingElse() throws SpecialException {
        throw new SpecialException("Thrown at end of doSomething() method");
    }
}
```


What will be the output?

☐ A) SpecialException: Thrown at end of doSomething() method

☐ B) Error in thread "main" java.lang.ArrayIndexOutOfBoundsException

☐ C) Exception in thread "main" java.lang.ArrayIndexOutOfBoundsException: 4
at ExceptionTest.doSomething(ExceptionTest.java:13)
at ExceptionTest.main(ExceptionTest.java:4)

☐ D) SpecialException: Thrown at end of doSomething() method
at ExceptionTest.doSomethingElse(ExceptionTest.java:16)
at ExceptionTest.doSomething(ExceptionTest.java:13)
at ExceptionTest.main(ExceptionTest.java:4)

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 129

Given the code fragment:

```
9.   int a = -10;
10.  int b = 17;
11.  int c = expression1;
12.  int d = expression2;
13.  c++;
14.  d--;
15.  System.out.print(c + " , " + d);
```

www.braindumps.com 109

Oracle 1z0-803 Exam

What could expression1 and expression2 be, respectively, in order to produce output 8, 16?

- A. ++a, --b
- B. ++a, b--
- C. A++, --b
- D. A++, b--

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 130

Given:

```

public class Test2 {
    public static void doChange(int[] arr) {
        for(int pos = 0; pos < arr.length; pos++){
            arr[pos] = arr[pos] + 1;
        }
    }
    public static void main(String[] args) {
        int[] arr = {10, 20, 30};
        doChange(arr);
        for(int x: arr) {
            System.out.print(x + ", ");
        }
        doChange(arr[0], arr[1], arr[2]);
        System.out.print(arr[0] + ", " + arr[1] + ", " + arr[2]);
    }
}

```

What is the result?

- A. 11, 21, 31, 11, 21, 31
- B. 11, 21, 31, 12, 22, 32
- C. 12, 22, 32, 12, 22, 32
- D. 10, 20, 30, 10, 20, 30

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 131

Given:

www.braindumps.com 110

Oracle 1z0-803 Exam

```
public class Palindrome {  
    public static int main(String[] args) {  
        System.out.print(args[1]);  
        return 0;  
    }  
}
```

And the commands:

```
javac Palindrome.java  
java Palindrome Wow Mom
```

What is the result?

- A. Compilation fails
- B. The code compiles, but does not execute.
- C. Paildrome
- D. Wow
- E. Mom

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 132

Given:

```
class Jump {  
    static String args[] = {"lazy", "lion", "is", "always"};  
    public static void main(String[] args) {  
        System.out.println(  
            args[1] + " " + args[2] + " " + args[3] + " jumping");  
    }  
}
```

And the commands:

Javac Jump.java

Java Jump crazy elephant is always

What is the result?

- A. Lazy lion is jumping
www.braindumps.com 111
Oracle 1z0-803 Exam
- B. Lion is always jumping
- C. Crazy elephant is jumping
- D. Elephant is always jumping
- E. Compilation fails

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 133

Which code fragment cause a compilation error?

- A. flat flt = 100F;

- B. float flt = (float) 1_11.00;
- C. float flt = 100;
- D. double y1 = 203.22;
floatflt = y1
- E. int y2 = 100;
floatflt = (float) y2;

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 134

Given:

```
class Test {  
    public static void main(String[] args) {  
        int numbers[];  
        numbers = new int[2];  
        numbers[0] = 10;  
        numbers[1] = 20;  
  
        numbers = new int[4];  
        numbers[2] = 30;  
        numbers[3] = 40;  
        for (int x : numbers) {  
            System.out.print(" " + x);  
        }  
    }  
}
```

www.braindumps.com 112

Oracle 1z0-803 Exam

What is the result?

- A. 10 20 30 40

- B. 0 0 30 40
- C. Compilation fails
- D. An exception is thrown at runtime

Correct Answer: A

Section: (none)


Explanation

Explanation/Reference:

Explanation:

QUESTION 135

Given:



```
public class Series {  
    public static void main(String[] args) {  
        int arr[] = {1, 2, 3};  
  
        for (int var : arr) {  
            int i = 1;  
            while (i <= var);  
            System.out.println(i++);  
        }  
    }  
}
```

What is the result?

- A. 1
- B. 1
- C. 2
- D. Compilation fails
- E. The loop executes infinite times

Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

Explanation:

www.braindumps.com 113

Oracle 1z0-803 Exam

QUESTION 136

Given:

```
class Patient {  
    String name;  
    public Patient(String name) {  
        this.name = name;  
    }  
}
```

And the code fragment:

```
8. public class Test {  
9.     public static void main(String[] args) {  
10.         List ps = new ArrayList();  
11.         Patient p2 = new Patient("Mike");  
12.         ps.add(p2);  
13.  
14.         // insert code here  
15.  
16.         if (f >= 0) {  
17.             System.out.print("Mike Found");  
18.         }  
19.     }  
20. }
```

Which code fragment, when inserted at line 14, enables the code to print Mike Found?

A. `int f = ps.indexOf (new patient ("Mike"));`

- B. `int f = ps.indexOf (patient("Mike"));`
- C. `patient p = new Patient ("Mike");`
`int f = pas.indexOf(P)`
- D. `int f = ps.indexOf(p2);`

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 137

Give:

www.braindumps.com 114
Oracle 1z0-803 Exam

```
class Alpha {
    public String[] main = new String[2];
    Alpha(String[] main) {
        for (int ii = 0; ii < main.length; ii++) {
            this.main[ii] = main[ii] + 5;
        }
    }
    public void main() {
        System.out.print(main[0] + main[1]);
    }
}

public class Test {
    public static void main(String[] args) {
        Alpha main = new Alpha(args);
        main.main();
    }
}

And the commands:

javac Test.java
java Test 1 2
```

What is the result?

- A. 1525
- B. 13
- C. Compilation fails
- D. An exception is thrown at runtime
- E. The program fails to execute due to runtime error

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 138

Given:

```
public class Test {  
    public static void main(String[] args) {  
        Test ts = new Test();  
        System.out.print(isAvailable + " ");  
        isAvailable= ts.dostuff();  
        System.out.println(isAvailable);  
    }  
    public static boolean dostuff() {  
        return !isAvailable;  
    }  
    static boolean isAvailable = false;  
}
```

www.braindumps.com 115

Oracle 1z0-803 Exam

What is the result?

- A. true true
- B. true false
- C. false true
- D. false false
- E. Compilation fails

Correct Answer: E

Section: (none)


Explanation

Explanation/Reference:

Explanation:

QUESTION 139

Given the code in a file Traveler.java:



```
class Tours {  
    public static void main(String[] args) {  
        System.out.print("Happy Journey! " + args[1]);  
    }  
}  
  
public class Traveler {  
    public static void main(String[] args) {  
        Tours.main(args);  
    }  
}
```

And the commands:

Javac Traveler.java

Java Traveler Java Duke

What is the result?

- A. Happy Journey! Duke
- B. Happy Journey! Java
- C. An exception is thrown at runtime
- D. The program fails to execute due to a runtime error

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Explanation:

www.braindumps.com 116
Oracle 1z0-803 Exam

QUESTION 140

Given:

```
class X {  
    int x1, x2, x3;  
}  
class Y extends X {  
    int y1;  
    Y() {  
        x1 = 1;  
        x2 = 2;  
        y1 = 10;  
    }  
}
```

```
class Z extends Y {  
    int z1;  
    Z() {  
        x1 = 3;  
        y1 = 20;  
        z1 = 100;  
    }  
}
```

And,

```
public class Test3 {  
    public static void main(String[] args) {  
        Z obj = new Z();  
        System.out.println(obj.x3 + ", " + obj.y1 + ", " + obj.z1);  
    }  
}
```

Which constructor initializes the variable x3?

- A. Only the default constructor of class X
- B. Only the no-argument constructor of class Y
- C. Only the no-argument constructor of class Z
- D. Only the default constructor of object class

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 141

Given:

www.braindumps.com 117

Oracle 1z0-803 Exam

Given:

```
class Dog {
    Dog() {
        try {
            throw new Exception();
        } catch (Exception e) { }
    }
}

class Test {
    public static void main(String[] args ) {
        Dog d1 = new Dog();
        Dog d2 = new Dog();
        Dog d3 = d2;
        // do complex stuff
    }
}
```

How many objects have been created when the line // do complex stuff is reached?

- A. Two
- B. Three
- C. Four
- D. Six

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 142

Given:

```
public class CharToStr {  
    public static void main(String[] args) {  
        String str1 = "Java";  
        char str2[] = { 'J', 'a', 'v', 'a' };  
        String str3 = null;  
        for (char c : str2) {  
            str3 = str3 + c;  
        }  
        if (str1.equals(str3))  
            System.out.print("Successful");  
        else  
            System.out.print("Unsuccessful");  
    }  
}
```

www.braindumps.com 118

Oracle 1z0-803 Exam

What is result?

- A. Successful
- B. Unsuccessful
- C. Compilation fails
- D. An exception is thrown at runtime

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 143

Given:


```
public class Series {  
    private boolean flag;  
  
    public void displaySeries() {  
        int num = 2;  
        while (flag) {  
            if (num % 7 == 0)  
                flag = false;  
            System.out.print(num);  
            num += 2;  
        }  
    }  
  
    public static void main(String[] args) {  
        new Series().displaySeries();  
    }  
}
```

What is the result?

- A. 2 4 6 8 10 12
- B. 2 4 6 8 10 12 14
- C. Compilation fails
- D. The program prints multiple of 2 infinite times
- E. The program prints nothing

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

www.braindumps.com 119

Oracle 1z0-803 Exam

QUESTION 144

Given the fragment:

```
24. float var1 = (12_345.01 >= 123_45.00) ? 12_456 : 124_56.02f;  
25. float var2 = var1 + 1024;  
26. System.out.print(var2);
```

What is the result?

- A. 13480.0
- B. 13480.02
- C. Compilation fails
- D. An exception is thrown at runtime

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 145

Given:

```
7.  StringBuilder sb1 = new StringBuilder("Duke");  
8.  String str1 = sb1.toString();  
9.  // insert code here  
10. System.out.print(str1 == str2);
```

Which code fragment, when inserted at line 9, enables the code to print true?

- A. String str2 = str1;
- B. String str2 = new String(str1);
- C. String str2 = sb1.toString();
- D. String str2 = "Duke";

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 146

www.braindumps.com 120

Oracle 1z0-803 Exam

Given the code fragment:

```
12. int row = 10;  
13. for ( ; row > 0 ; )  
14.     int col = row;  
15.     while (col >= 0) {  
16.         System.out.print(col + " ");  
17.         col -= 2;  
18.     }  
19.     row = row / col;  
20. }
```

What is the result?

- A. 10 8 6 4 2 0
- B. 10 8 6 4 2
- C. AnArithmeticException is thrown at runtime
- D. The program goes into an infinite loop outputting: 10 8 6 4 2 0. . .
- E. Compilation fails

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 147

Given the classes:

- * AssertionError
- * ArithmeticException
- * ArrayIndexOutOfBoundsException
- * FileNotFoundException
- * IllegalArgumentException
- * IOError
- * IOException
- * NumberFormatException
- * SQLException

www.braindumps.com 121

Oracle 1z0-803 Exam

Which option lists only those classes that belong to the unchecked exception category?

- A. AssertionError, ArrayIndexOutOfBoundsException, ArithmeticException
- B. AssertionError, IOError, IOException
- C. ArithmeticException, FileNotFoundException, NumberFormatException
- D. FileNotFoundException, IOException, SQLException
- E. ArrayIndexOutOfBoundsException, IllegalArgumentException, FileNotFoundException

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation: Not B: IOError and IOException are both checked errors. Not C, not D, not E: FileNotFoundException is a checked error.

Note:

Checked exceptions:

- * represent invalid conditions in areas outside the immediate control of the program (invalid user input, database problems, network outages, absent files)
- * are subclasses of Exception
- * a method is obliged to establish a policy for all checked exceptions thrown by its implementation (either pass the checked exception further up the stack, or handle it somehow)

Note:

Unchecked exceptions:

* represent defects in the program (bugs) - often invalid arguments passed to a non-private method. To quote from The Java Programming Language, by Gosling, Arnold, and Holmes:

"Unchecked runtime exceptions represent conditions that, generally speaking, reflect errors in your program's logic and cannot be reasonably recovered from at run time."

* are subclasses of RuntimeException, and are usually implemented using IllegalArgumentException, NullPointerException, or IllegalStateException

* method is not obliged to establish a policy for the unchecked exceptions thrown by its implementation (and they almost always do not do so)

QUESTION 148

Given:

```
public class Test1 {  
  
    static void doubling (Integer ref, int pv) {  
  
        ref =20;  
  
        pv = 20;  
  
        www.braindumps.com 122  
        Oracle 1z0-803 Exam  
    }  
  
    public static void main(String[] args) {  
  
        Integer iObj = new Integer(10);  
  
        int iVar = 10;  
  
        doubling(iObj++, iVar++);  
  
        System.out.println(iObj+ " , "+iVar);  
    }  
}
```

What is the result?

- A. 11, 11
- B. 10, 10
- C. 21, 11
- D. 20, 20

E. 11, 12

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation: The code doubling(iObj++, iVar++); increases both variables from 10 to 11.

QUESTION 149

Given:

```
class Mid {  
  
    public int findMid(int n1, int n2) {  
  
        return (n1 + n2) / 2;  
  
    }  
  
}  
  
public class Calc extends Mid {  
  
    public static void main(String[] args) {  
  
        int n1 = 22, n2 = 2;  
  
        // insert code here  
  
        System.out.print(n3);  
  
        www.braindumps.com 123  
        Oracle 1z0-803 Exam  
    }  
  
}
```

Which two code fragments, when inserted at // insert code here, enable the code to compile and print 12?

A. Calc c = new Calc();
 int n3 = c.findMid(n1,n2);

- B. `int n3 = super.findMid(n1,n3);`
- C. `Calc c = new Mid();`
`int n3 = c.findMid(n1, n2);`
- D. `Mid m1 = new Calc();`
`int n3 = m1.findMid(n1, n2);`
- E. `int n3 = Calc.findMid(n1, n2);`

Correct Answer: AD

Section: (none)

Explanation

Explanation/Reference:

Explanation:

Incorrect:

Not B: circular definition of n3.

Not C: Compilation error. line `Calc c = new Mid();`

required: Calc

found: Mid

Not E: Compilation error. line `int n3 = Calc.findMid(n1, n2);` non-static method `findMid(int,int)` cannot be referenced from a static context

QUESTION 150

Given:

```
import java.util.*;
```

```
public class Ref {
```

```
    public static void main(String[] args) {
```

```
        StringBuilder s1 = new StringBuilder("Hello Java!");
```

```
        String s2 = s1.toString();
```

```
        List<String> lst = new ArrayList<String>();
```

```
        lst.add(s2);
```

```
    }
}
```

www.braindumps.com 124

Oracle 1z0-803 Exam

```
System.out.println(s1.getClass());
```

```
System.out.println(s2.getClass());

System.out.println(lst.getClass());

}

}
```

What is the result?

- A. class java.lang.String
class java.lang.String
class java.util.ArrayList
- B. class java.lang.Object
class java.lang. Object
classjava.util.Collection
- C. class java.lang.StringBuilder
class java.lang.String
class java.util.ArrayList
- D. class java.lang.StringBuilder
class java.lang.String
class java.util.List

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation: class java.lang.StringBuilder
class java.lang.String
class java.util.ArrayList

QUESTION 151

Given:

```
public class ComputeSum {

public int x;

public int y;
```



```

public int sum;

public ComputeSum (int nx, int ny) {

x = nx; y =ny;

www.braindumps.com 125
Oracle 1z0-803 Exam
updateSum();

}

public void setX(int nx) { x = nx; updateSum();}

public void setY(int ny) { x = ny; updateSum();}

void updateSum() { sum = x + y;}

}

```

This class needs to protect an invariant on the sum field.

Which three members must have the private access modifier to ensure that this invariant is maintained?

- A. The x field
- B. The y field
- C. The sum field
- D. The ComputerSum () constructor
- E. The setX () method
- F. The setY () method

Correct Answer: CEF

Section: (none)

Explanation

Explanation/Reference:

Explanation: The sum field and the two methods (setX and SetY) that updates the sum field.

QUESTION 152

Given the following four Java file definitions:

```
// Foo.java
```

```
package facades;
```

```
public interface Foo { }
```

```
// Boo.java
```

```
package facades;
```

```
public interface Boo extends Foo { }
```

```
// Woofy.java
```

```
www.braindumps.com 126
```

```
Oracle 1z0-803 Exam
```

```
package org.domain
```

```
// line n1
```

```
public class Woofy implements Boo, Foo { }
```

```
// Test.java
```

```
package.org;
```

```
public class Test {
```

```
public static void main(String[] args) {
```

```
Foo obj=new Woofy();
```

Which set modifications enable the code to compile and run?

- A. At line n1, Insert: import facades;At line n2, insert:import facades;importorg.domain;
- B. At line n1, Insert: import facades.*;At line n2, insert:import facades;import org.*;
- C. At line n1, Insert: import facades.*;At line n2, insert:import facades.Boo;import org.*;
- D. At line n1, Insert: import facades.Foo, Boo;At line n2, insert:import org.domain.Woofy;
- E. At line n1, Insert: import facades.*;At line n2, insert:import facades;import org.domain.Woofy;

Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 153

Given:

Given:

```
public class SuperTest {  
  
    public static void main(String[] args) {  
  
        statement1  
  
        statement2  
  
        statement3  
  
        www.braindumps.com 127  
        Oracle 1z0-803 Exam  
    }  
  
}  
  
class Shape {  
  
    public Shape() {  
  
        System.out.println("Shape: constructor");  
  
    }  
  
    public void foo() {  
  
        System.out.println("Shape: foo");  
  
    }  
  
}
```

```
class Square extends Shape {  
    public Square() {  
        super();  
    }  
    public Square(String label) {  
        System.out.println("Square: constructor");  
    }  
    public void foo() {  
        super.foo();  
    }  
    public void foo(String label) {  
        System.out.println("Square: foo");  
    }  
}  
}
```

www.braindumps.com 128

Oracle 1z0-803 Exam

What should statement1, statement2, and statement3, be respectively, in order to produce the result?

Shape: constructor

Square: foo

Shape: foo

- A. `Square square = new Square ("bar");`
`square.foo ("bar");`
`square.foo();`
- B. `Square square = new Square ("bar");`
`square.foo ("bar");`
`square.foo ("bar");`
- C. `Square square = new Square ();`
`square.foo ();`
`square.foo(bar);`
- D. `Square square = new Square ();`
`square.foo ();`
`square.foo("bar");`
- E. `Square square = new Square ();`
`square.foo ();`
`square.foo ();`
- F. `Square square = new Square();`
`square.foo("bar");`
`square.foo();`

Correct Answer: F

Section: (none)

Explanation

Explanation/Reference:

QUESTION 154

Given:

```
public class Marklist {  
  
    int num;  
  
    public static void graceMarks(Marklist obj4) {  
  
        obj4.num += 10;  
  
    }  
  
    public static void main(String[] args) {
```

www.braindumps.com 129
Oracle 1z0-803 Exam
MarkList obj1 = new MarkList();

MarkList obj2 = obj1;

MarkList obj1 = null;

obj2.num = 60;

graceMarks(obj2);

}

}

How many objects are created in the memory runtime?

- A. 1
- B. 2
- C. 3
- D. 4

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation: obj1 and obj3.

when you do e2 = e1 you're copying object references - you're not making a copy of the object - and so the variables e1 and e2 will both point to the same object.

QUESTION 155

Given:

```
class Cake {
```

```
    int model;
```

```
    String flavor;
```

```
Cake() {  
    model = 0;  
    flavor = "Unknown";  
}  
}
```

www.braindumps.com 130

Oracle 1z0-803 Exam

```
public class Test {  
    public static void main(String[] args) {  
        Cake c = new Cake();  
        bake1(c);  
        System.out.println(c.model + " " + c.flavor);  
        bake2(c);  
        System.out.println(c.model + " " + c.flavor);  
    }  
    public static Cake bake1(Cake c) {  
        A. flavor = "Strawberry";  
        B. model = 1200;  
        return c;  
    }  
    public static void bake2(Cake c) {  
        C. flavor = "Chocolate";  
        D. model = 1230;  
        return;  
    }  
}
```

What is the result?

- E. 0 unknown
0 unknown
- F. 1200 Strawberry
1200 Strawberry
- G. 1200 Strawberry
1230 Chocolate
- H. Compilation fails

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation: 1200 Strawberry

www.braindumps.com 131

Oracle 1z0-803 Exam

1230 Chocolate

QUESTION 156

Given:

```
public class Painting {  
  
    private String type;  
  
    public String getType() {  
  
        return type;  
  
    }  
  
    public void setType(String type) {  
  
        this.type = type;  
  
    }  
  
    public static void main(String[] args) {
```



```
Painting obj1 = new Painting();  
Painting obj2 = new Painting();  
obj1.setType(null);  
obj2.setType("Fresco");  
System.out.print(obj1.getType() + " : " + obj2.getType());  
}  
}
```

What is the result?

- A. : Fresco
- B. null : Fresco
- C. Fresco : Fresco
- D. A NullPointerException is thrown at runtime

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

www.braindumps.com 132

Oracle 1z0-803 Exam

Explanation:

QUESTION 157

Given:

```
class Base {  
  
// insert code here  
}
```

```

public class Derived extends Base{

public static void main(String[] args) {

Derived obj = new Derived();

obj.setNum(3);

System.out.println("Square = " + obj.getNum() * obj.getNum());

}

}

```

Which two options, when inserted independently inside class Base, ensure that the class is being properly encapsulated and allow the program to execute and print the square of the number?

- A. private int num;public int getNum() {return num;}public void setNum(int num) {this.num = num;}
- B. public int num;protected public int getNum() {return num;}protected public void setNum(int num) {this.num = num;}
- C. private int num;public int getNum() {return num;}private void setNum(int num) {this.num = num;}
- D. protected int num;public int getNum() {return num;}public void setNum(int num) {this.num = num;}
- E. protected int num;private int getNum() {return num;}public void setNum(intnum) {this.num = num;}

Correct Answer: AD

Section: (none)

Explanation

Explanation/Reference:

Explanation:

Incorrect:

Not B: illegal combination of modifiers: protected and public not C: setNum method cannot be private.

not E: getNum method cannot be private.

www.braindumps.com 133

Oracle 1z0-803 Exam

QUESTION 158

Given:

```

public class Test {

```

```
public static void main(String[] args) {  
    int arr[] = new int[4];  
    arr[0] = 1;  
    arr[1] = 2;  
    arr[2] = 4;  
    arr[3] = 5;  
    int sum = 0;  
    try {  
        for (int pos = 0; pos <= 4; pos++) {  
            sum = sum + arr[pos];  
        }  
    } catch (Exception e) {  
        System.out.println("Invalid index");  
    }  
    System.out.println(sum);  
}
```

What is the result?

- A. 12
- B. Invalid Index
- C. Invalid Index
- D. Compilation fails

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation: The loop (for (int pos = 0; pos <= 4; pos++) { }, it should be pos <= 3, causes an exception, which is caught. Then the correct sum is printed.

QUESTION 159

Given:

```
public class Equal {  
  
    public static void main(String[] args) {  
  
        String str1 = "Java";  
  
        String[] str2 = {"J","a","v","a"};  
  
        String str3 = "";  
  
        for (String str : str2) {  
  
            str3 = str3+str;  
  
        }  
  
        boolean b1 = (str1 == str3);  
  
        boolean b2 = (str1.equals(str3));  
  
        System.out.print(b1+"", "+b2");  
  
    }  
}
```

What is the result?

- A. true, false
- B. false, true
- C. true, true

D. false, false

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation: == strict equality.
equals compare state, not identity.

www.braindumps.com 135

Oracle 1z0-803 Exam

QUESTION 160

Given the code fragment:

```
public static void main(String[] args) {  
  
    int iArray[] = {65, 68, 69};  
  
    iArray[2] = iArray[0];  
  
    iArray[0] = iArray[1];  
  
    iArray[1] = iArray[2];  
  
    for (int element : iArray) {  
  
        System.out.print(element + " ");  
  
    }  
}
```

A. 68, 65, 69

B. 68, 65, 65

C. 65,68, 65

D. 65, 68, 69

E. Compilation fails

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation: 68 65 65

QUESTION 161

Given:

```
public class TestLoop1 {  
  
    public static void main(String[] args) {  
  
        int a = 0, z=10;  
  
        while (a < z) {  
  
            a++;  
  
            --z;  
  
            www.braindumps.com 136  
            Oracle 1z0-803 Exam  
        }  
  
        System.out.print(a + " : " + z);  
  
    }  
  
}
```

What is the result?

- A. 5 : 5
- B. 6 : 4
- C. 6 : 5
- D. 5 : 4

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation: 5 : 5

QUESTION 162

Given:

```
public class MyClass {  
  
    public static void main(String[] args) {  
  
        while (int ii = 0; ii < 2) {  
  
            ii++;  
  
            System.out.println("ii = " + ii);  
  
        }  
  
    }  
  
}
```

What is the result?

- A. ii = 1
ii = 2
- B. Compilation fails
- C. The program prints nothing
www.braindumps.com 137
Oracle 1z0-803 Exam
- D. The program goes into an infinite loop with no output
- E. The program goes to an infinite loop outputting:
ii =1
ii = 1

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation: The while statement is incorrect. It has the syntax of a for statement.

The while statement continually executes a block of statements while a particular condition is true.
Its syntax can be expressed as:

```
while (expression) {  
    statement(s)  
}
```

The while statement evaluates expression, which must return a boolean value. If the expression evaluates to true, the while statement executes the statement(s) in the while block. The while statement continues testing the expression and executing its block until the expression evaluates to false.

Reference: The while and do-while Statements

QUESTION 163

Given:

```
public class String1 {  
  
    public static void main(String[] args) {  
  
        String s = "123";  
  
        if (s.length() >2)
```

```
            A. concat("456");  
               for(int x = 0; x <3; x++)  
                   s += "x";  
               System.out.println(s);  
            }  
        }  
    }  
    www.braindumps.com 138  
    Oracle 1z0-803 Exam  
    What is the result?
```

- B. 123
- C. 123xxx
- D. 123456
- E. 123456xxx
- F. Compilation fails

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation: 123xxx

The if clause is not applied.

Note: Syntax of if-statement:

```
if ( Statement ) {  
}
```

QUESTION 164

Given the code fragment:

```
float x = 22.00f % 3.00f;
```

```
int y = 22 % 3;
```

```
System.out.print(x + ", " + y);
```

What is the result?

- A. 1.0, 1
- B. 1.0f, 1
- C. 7.33, 7
- D. Compilation fails
- E. An exception is thrown at runtime

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation: 1.0, 1

www.braindumps.com 139

Oracle 1z0-803 Exam

QUESTION 165

Which three statements are true about the structure of a Java class?

- A. A class can have only one private constructor.
- B. A method can have the same name as a field.
- C. A class can have overloaded static methods.
- D. A public class must have a main method.
- E. The methods are mandatory components of a class.
- F. The fields need not be initialized before use.

Correct Answer: ABC

Section: (none)

Explanation

Explanation/Reference:

Explanation: A: Private constructors prevent a class from being explicitly instantiated by its callers. If the programmer does not provide a constructor for a class, then the system will always provide a default, public no-argument constructor. To disable this default constructor, simply add a private no-argument constructor to the class. This private constructor may be empty.

B: The following works fine:

```
int cake() {  
int cake=0;  
return (1);  
}
```

C: We can overload static method in Java. In terms of method overloading static method are just like normal methods and in order to overload static method you need to provide another static method with same name but different method signature.

Incorrect:

Not D: Only a public class in an application need to have a main method.

Not E:

Example:

```
class A  
{  
public string something;  
public int a;  
}
```

Q: What do you call classes without methods?

Most of the time: An anti pattern.

Why? Because it facilitates procedural programming with "Operator" classes and data structures. You separate data and behaviour which isn't exactly good OOP.

Often times: A DTO (Data Transfer Object)

Read only datastructures meant to exchange data, derived from a business/domain object.

Sometimes: Just data structure.

Well sometimes, you just gotta have those structures to hold data that is just plain and simple and has no operations on it.

Not F: Fields need to be initialized. If not the code will not compile.

Example:

Uncompilable source code - variable x might not have been initialized

QUESTION 166

Given:

```
class MarksOutOfBoundsException extends IndexOutOfBoundsException { }
```

```
public class GradingProcess {
```

```
void verify(int marks) throws IndexOutOfBoundsException {
```

```
if (marks > 100) {
```

```
    throw new MarksOutOfBoundsException();
```

```
}
```

```
if (marks > 50) {
```

```
    System.out.print("Pass");
```

```
} else {
```

```
    System.out.print("Fail");
```

```
}
```

```
}
```

```
public static void main(String[] args) {
```

www.braindumps.com 141
Oracle 1z0-803 Exam
int marks = Integer.parseInt(args[2]);

```
try {  
  
    new GradingProcess().verify(marks);  
  
} catch(Exception e) {  
  
    System.out.print(e.getClass());  
  
}  
  
}  
  
}
```

And the command line invocation:

Java grading process 89 50 104

What is the result?

- A. Pass
- B. Fail
- C. Class MarketOutOfBoundsException
- D. Class IndexOutOfBoundsException
- E. Class Exception

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation: The value 104 will cause a MarketOutOfBoundsException

QUESTION 167

Given the code fragment:

```
StringBuilder sb = new StringBuilder ( ) ;
```

```
Sb.append ("world");
```

Which code fragment prints Hello World?

- A. sb.insert(0,"Hello ");
www.braindumps.com 142
Oracle 1z0-803 Exam
System.out.println(sb);
- B. sb.append(0,"Hello ");
System.out.println(sb);
- C. sb.add(0,"Hello ");
System.out.println(sb);
- D. sb.set(0,"Hello ");
System.out.println(sb);D

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation: The java.lang.StringBuilder.insert(int offset, char c) method inserts the string representation of the char argument into this sequence. The second argument is inserted into the contents of this sequence at the position indicated by offset. The length of this sequence increases by one. The offset argument must be greater than or equal to 0, and less than or equal to the length of this sequence.

Reference: Java.lang.StringBuilder.insert() Method

QUESTION 168

Given:

```
package p1;
```

```
public interface DoInterface {
```

```
void method1(int n1); // line n1
```

```
}
```

```
package p3;
```

```
import p1.DoInterface;
```

```

public class DoClass implements DoInterface {

public DoClass(int p1) { }

public void method1(int p1) { } // line n2

private void method2(int p1) { } // line n3

}

public class Test {

www.braindumps.com 143
Oracle 1z0-803 Exam
public static void main(String[] args) {

DoInterface doi= new DoClass(100); // line n4

doi.method1(100);

doi.method2(100);

}

}

```

Which change will enable the code to compile?

- A. Adding the public modifier to the declaration of method1 at line n1
- B. Removing the public modifier from the definition of method1 at line n2
- C. Changing the private modifier on the declaration of method 2 public at line n3
- D. Changing the line n4 DoClass doi = new DoClass ();

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation: Private members (both fields and methods) are only accessible inside the class they are declared or inside inner classes. private keyword is one of four access modifier provided by Java and its a most restrictive among all four e.g. public, default(package), protected and private.

Read more: <http://javarevisited.blogspot.com/2012/03/private-in-java-why-should-you- always.html#ixzz3Sh3mOc4D>

QUESTION 169



<http://www.gratisexam.com/>

Given the fragment:

```
String[][] arra = new String[3][];  
arra[0] = new String[]{"rose", "lily"};  
arra[1] = new String[]{"apple", "berry", "cherry", "grapes"};  
arra[0] = new String[]{"beans", "carrot", "potato"};  
// insert code fragment here
```

Which code fragment when inserted at line '// insert code fragment here', enables the code to successfully change arra elements to uppercase?

www.braindumps.com 144
Oracle 1z0-803 Exam

- A.

```
String[][] arra = new String[3][];  
arra[0] = new String[]{"rose", "lily"};  
arra[1] = new String[]{"apple", "berry", "cherry", "grapes"}; arra[0] = new String[]{"beans", "carrot", "potato"};  
for (int i = 0; i < arra.length; i++) {  
    for (int j=0; j < arra[i].length; j++) {  
        arra[i][j] = arra[i][j].toUpperCase();  
    }  
}
```
- B.

```
for (int i = 0; i < 3; i++) {  
    for (int j=0; j< 4; j++) {  
        arra[i][j] = arra[i][j].toUpperCase();  
    }  
}
```

```

    }
C. for (String a[]:arra[[]]) {
    for (String x:a[]) {
D. toUpperCase();
    }
    }
E. for (int i:arra.length) {
    for (String x:arra) {
        arra[i].toUpperCase();
    }
    }

```

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

Incorrect:

not A: arra.length is 3, but the subarrays have 2, 3 and 4 elements. Index will be out of bound. not B: The subarrays are of different lengths. Index will be out of bound.
not D: Compile error.

QUESTION 170

Given the code fragment:

```

public class Test {

    static String[][] arr =new String[3][];

    private static void doPrint() {

        //insert code here

        www.braindumps.com 145
        Oracle 1z0-803 Exam
    }

    public static void main(String[] args) {

        String[] class1 = {"A","B","C"};

```



```

String[] class2 = {"L","M","N","O"};

String[] class3 = {"I","J"};

arr[0] = class1;

arr[1] = class2;

arr[2] = class3;

Test.doPrint();

}

}

```

Which code fragment, when inserted at line //insert code here, enables the code to print COJ?

- A.

```
int i = 0;
for (String[] sub: arr) {
    int j = sub.length - 1;
    for (String str: sub) {
        System.out.println(str[j]);
        i++;
    }
}
```
- B.

```
private static void doPrint() {
    for (int i = 0; i < arr.length; i++) {
        int j = arr[i].length - 1;
        System.out.print(arr[i][j]);
    }
}
```
- C.

```
int i = 0;
for (String[] sub: arr[0]) {
    int j = sub.length;
    System.out.print(arr[i][j]);
    i++;
}
```
- D.

```
for (int i = 0; i < arr.length - 1; i++) {
    int j = arr[i].length - 1;
    System.out.print(arr[i][j]);
}
```

```
i++;  
www.braindumps.com 146  
Oracle 1z0-803 Exam  
}
```

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

Incorrect:

not A: The following line causes a compile error:

```
System.out.println(str[j]);
```

Not C: Compile error line:

```
for (String[] sub: arr[][])
```

not D: Output: C

QUESTION 171

Given:

```
public class FieldInit {  
  
    char c;  
  
    boolean b;  
  
    float f;  
  
    void printAll() {  
  
        System.out.println("c = " + c);  
  
        System.out.println("c = " + b);  
  
        System.out.println("c = " + f);  
  
    }  
  
    public static void main(String[] args) {  
  
        FieldInit f = new FieldInit();
```

A. `printAll();`
`}`
`}`

What is the result?

www.braindumps.com 147

Oracle 1z0-803 Exam

B. `c = null`
`b = false`
`f = 0.0F`

C. `c = 0`
`b = false`
`f = 0.0f`

D. `c = null`
`b = true`
`f = 0.0`

E. `c =`
`b = false`
`f = 0.0`

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 172

Given the code fragment:

```
String[] cartoons = {"tom","jerry","micky","tom"};
```

```
int counter =0;
```

```
if ("tom".equals(cartoons[0])) {
```

```
    counter++;
```

```
} else if ("tom".equals(cartoons[1])) {
```

```
    counter++;
```

```
} else if ("tom".equals(cartoons[2])) {  
  
    counter++;  
  
} else if ("tom".equals(cartoons[3])) {  
  
    counter++;  
  
}  
  
System.out.print(counter);
```

What is the result?

www.braindumps.com 148
Oracle 1z0-803 Exam

- A. 1
- B. 2
- C. 4
- D. 0

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation: Counter++ will be executed only once because of the else if constructs.

QUESTION 173

Given:

```
public class Test {  
  
    public static void main(String[] args) {  
  
        int day = 1;  
  
        switch (day) {
```

```
case "7": System.out.print("Uranus");  
case "6": System.out.print("Saturn");  
case "1": System.out.print("Mercury");  
case "2": System.out.print("Venus");  
case "3": System.out.print("Earth");  
case "4": System.out.print("Mars");  
case "5": System.out.print("Jupiter");  
}  
}  
}
```

Which two modifications, made independently, enable the code to compile and run?

- A. Adding a break statement after each print statement
- B. Adding a default section within the switch code-block
- C. Changing the string literals in each case label to integer www.braindumps.com 149
Oracle 1z0-803 Exam
- D. Changing the type of the variable day to String
- E. Arranging the case labels in ascending order

Correct Answer: AC

Section: (none)

Explanation

Explanation/Reference:

Explanation: The following will work fine:

```
public class Test {  
    public static void main(String[] args) {  
        int day = 1;  
        switch (day) {  
            case 7: System.out.print("Uranus"); break;
```

```

case 6: System.out.print("Saturn"); break;
case 1: System.out.print("Mercury"); break;
case 2: System.out.print("Venus"); break;
case 3: System.out.print("Earth"); break;
case 4: System.out.print("Mars"); break;
case 5: System.out.print("Jupiter"); break;
}
}
}

```

QUESTION 174

Given:

```

public class Test {

    public static void main(String[] args) {

        try {

            String[] arr = new String[4];

            arr[1] = "Unix";

            arr[2] = "Linux";

            arr[3] = "Solaris";

            for (String var : arr) {

                System.out.print(var + " ");

                www.braindumps.com 150
                Oracle 1z0-803 Exam
            }

        } catch (Exception e) {

            System.out.print (e.getClass());

        }

    }

}

```

```
}
```

What is the result?

- A. Unix Linux Solaris
- B. Null Unix Linux Solaris
- C. Class java.lang.Exception
- D. Class java.lang.NullPointerException

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation: null Unix Linux Solaris

The first element, arr[0], has not been defined.

QUESTION 175

Given the code fragment

```
int var1 = -5;
```

```
int var2 = var1--;
```

```
int var3 = 0;
```

```
if (var2 < 0) {
```

```
    var3 = var2++;
```

```
    } else {
```

```
        var3 = --var2;
```

```
    }
```

```
System.out.println(var3);
```

Oracle 1z0-803 Exam
What is the result?

- A. 6
- B. 4
- C. 5
- D. 5
- E. 4
- F. Compilation fails

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 176

Given the code fragment:

```
List colors = new ArrayList();
```

```
colors.add("green");
```

```
colors.add("red");
```

```
colors.add("blue");
```

```
colors.add("yellow");
```

```
colors.remove(2);
```

```
colors.add(3, "cyan");
```

```
System.out.print(colors);
```

What is the result?

- A. [green, red, yellow, cyan]
- B. [green, blue, yellow, cyan]

- C. [green, red, cyan, yellow]
- D. An IndexOutOfBoundsException is thrown at runtime

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation: First the list [green, red, blue, yellow] is built.

The blue element is removed:

[green, red, yellow]

Finally the element cyan is added at the end of the list (index 3).

www.braindumps.com 152

Oracle 1z0-803 Exam

[green, red, yellow, cyan]

QUESTION 177

Given:

```
public class TestOperator {  
  
    public static void main(String[] args) {  
  
        int result = 30 - 12 / (2*5)+1;  
  
        System.out.print("Result = " + result);  
  
    }  
  
}
```

What is the result?

- A. Result = 2
- B. Result = 3
- C. Result = 28
- D. Result = 29
- E. Result = 30

Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 178

Given:

```
class Sports {  
  
    int num_players;  
  
    String name, ground_condition;  
  
    Sports(int np, String sname, String sground){  
  
        www.braindumps.com 153  
        Oracle 1z0-803 Exam  
        num_players = np;  
  
        name = sname;  
  
        ground_condition = sground;  
  
    }  
  
}
```

```
class Cricket extends Sports {
```

```
    int num_umpires;
```

```
    int num_substitutes;
```

Which code fragment can be inserted at line //insert code here to enable the code to compile?

```
A. Cricket() {  
    super(11, "Cricket", "Condition OK");  
    num_umpires = 3;  
}
```

- ```
 num_substitutes=2;
}
```
- B. Cricket() {  
 super.ground\_condition = "Condition OK";  
 super.name="Cricket";  
 super.num\_players = 11;  
 num\_umpires =3;  
 num\_substitutes=2;  
}
- C. Cricket() {  
 this(3,2);  
 super(11, "Cricket", "Condidtion OK");  
}  
 Cricket(int nu, ns) {  
 this.num\_umpires =nu;  
 this.num\_substitutes=ns;  
 }
- D. Cricket() {  
 this.num\_umpires =3;  
 this.num\_substitutes=2;  
 super(11, "Cricket", "Condidtion OK");  
}

**Correct Answer:** A

**Section:** (none)

**Explanation**

**Explanation/Reference:**

Explanation:

www.braindumps.com 154  
Oracle 1z0-803 Exam

Incorrect:

not C, not D: call to super must be the first statement in constructor.

**QUESTION 179**

Given:

```
public class X {
```

```
static int i;

int j;

public static void main(String[] args) {
 X x1 = new X();
 X x2 = new X();

 x1.i = 3;
 x1.j = 4;
 x2.i = 5;
 x2.j = 6;

 System.out.println(
 x1.i + " "
 x1.j + " "
 x2.i + " "
 x2.j);
 }
}
```

What is the result?

- A. 3 4 5 6
- B. 3 4 3 6
- C. 5 4 5 6
- D. 3 6 4 6

**Correct Answer:** C

**Section:** (none)

**Explanation**

**Explanation/Reference:**

Explanation:

**QUESTION 180**

Which statement is true about the default constructor of a top-level class?

- A. It can take arguments.
- B. It has private access modifier in its declaration.
- C. It can be overloaded.
- D. The default constructor of a subclass always invokes the no-argument constructor of its superclass.

**Correct Answer:** D

**Section:** (none)

**Explanation**

**Explanation/Reference:**

Explanation: In both Java and C#, a "default constructor" refers to a nullary constructor that is automatically generated by the compiler if no constructors have been defined for the class. The default constructor is also empty, meaning that it does nothing. A programmer-defined constructor that takes no parameters is also called a default constructor.

**QUESTION 181**

Given the code fragment?

```
public class Test {

 public static void main(String[] args) {

 Test t = new Test();

 int[] arr = new int[10];

 arr = t.subArray(arr,0,2);

 }

 // insert code here
```

```
}
```

Which method can be inserted at line // insert code here to enable the code to compile?

www.braindumps.com 156

Oracle 1z0-803 Exam

- A. 

```
public int[] subArray(int[] src, int start, int end) { return src;
}
```
- B. 

```
public int subArray(int src, int start, int end) {
return src;
}
```
- C. 

```
public int[] subArray(int src, int start, int end) { return src;
}
```
- D. 

```
public int subArray(int[] src, int start, int end) { return src;
}
```

**Correct Answer:** A

**Section:** (none)

**Explanation**

**Explanation/Reference:**

Explanation:

#### **QUESTION 182**

Given:

```
public class TestField {

int x;

int y;

public void doStuff(int x, int y) {

this.x = x;

y =this.y;

}
```

```
public void display() {
 System.out.print(x + " " + y + " : ");
}

public static void main(String[] args) {
 TestField m1 = new TestField();
 m1.x = 100;
 m1.y = 200;

 www.braindumps.com 157
 Oracle 1z0-803 Exam
 TestField m2 = new TestField();

 m2.doStuff(m1.x, m1.y);

 m1.display();
 m2.display();
}
}
```

What is the result?

- A. 100 200 : 100 200
- B. 100 0 : 100 0 :
- C. 100 200 : 100 0 :
- D. 100 0 : 100 200 :

**Correct Answer:** C

**Section:** (none)

**Explanation**

**Explanation/Reference:**

Explanation:

**QUESTION 183**

Given:

```
package p1;

public class Test {

 static double dvalue;

 static Test ref;

 public static void main(String[] args) {

 System.out.println(ref);

 System.out.println(dvalue);

 }

}
```

What is the result?

www.braindumps.com 158  
Oracle 1z0-803 Exam

- A. p1.Test.class  
0.0
- B. <the summary address referenced by ref>  
0.000000
- C. Null  
0.0
- D. Compilation fails
- E. A NullPointerException is thrown at runtime

**Correct Answer: C**

**Section: (none)**

**Explanation**

**Explanation/Reference:**



Explanation: null  
0.0



<http://www.gratisexam.com/>