



















High rigid contour Stylus

Applicable models			S-NEX *4* DX2/SD2			S-NEX *3* DX2/SD2			S-NEX *4*			S-NEX *3*			Stylus tip material: Cemented carbide		
Measuring application	Model		External view			d	L1	L2	Applicable arm			Remarks					
	DM45501					3	60	52	DM83501 DM83517 DM83518								
	DM45502					3	34	26									
	DM45503					2	21	13							DM83507 DM83519 DM83520		
	DM45504					3	60	52	DM83501 DM83517 DM83518			• Standard accessory					
	DM45505					3	34	26									
	DM45506					2	21	13							DM83507 DM83519 DM83520		
	DM45507 ^{*1}					3	60	52	DM83501 DM83517 DM83518								
	DM45508 ^{*1}					3	34	26									
	DM45509 ^{*1}					2	21	13							DM83507 DM83519 DM83520		
	DM83502					3	26	—	DM83501 DM83517 DM83518			• Measuring force: 10 mN or less					
	DM83503					3	32	—									
	DM83504					3	44	—									
	DM83534 ^{*3}					3	16	6.5	DM83521			• Measuring force: 10 mN or less					
	DM83535 ^{*3}					3	9	3									
	DM83536 ^{*3}					2	5	1.5									
	DM83537 ^{*3}					1	2.4	0.7									
	DM83522					—	12	9	DM83521			• Measuring force: 10 mN or less					
	DM83523					—	8	5									
	DM83524 ^{*2}					—	4.5	1.5									
	DM83525					—	12	9	DM83521			• Measuring force: 10 mN or less					
	DM83526					—	8	5									
	DM83527 ^{*2}					—	4.5	1.5									
	DM83528					—	12	9	DM83521			• Measuring force: 10 mN or less • Offset: 25 mm					
	DM83529					—	8	5									
	DM83530 ^{*2}					—	4.5	1.5									
	DM83531					—	12	9	DM83521			• Measuring force: 10 mN or less • Offset: 25 mm					
	DM83532					—	8	5									
	DM83533 ^{*2}					—	4.5	1.5									
	DM45522					3	60	52	DM83501 DM83517 DM83518			• Φ0.7 Ruby ball					
	DM45523					3	34	26									
	DM45524					2	21	13							DM83507 DM83519 DM83520		
	DM45525					3	60	52	DM83501 DM83517 DM83518			• Φ1 Ruby ball					
	DM45526					3	34	26									
	DM45527					2	21	13							DM83507 DM83519 DM83520		













*1: Up/downward measurement masterball calibration unit (E-MC-S97A) is required. *2: Small hole masterball calibration unit (E-MC-S59D) is required.

*3: Small hole up/downward measurement calibration unit (E-MC-S104A) is required.

Standard Inventory Parts




High rigid contour arm

Applicable models ■ S-NEX *4* DX2/SD2 ■ S-NEX *3* DX2/SD2 ■ S-NEX *4* ■ S-NEX *3*

Measuring application	Model	External view	Applicable stylus	Remarks
General purpose 	DM83501		DM45501 DM45502 DM45504 DM45505 DM45507 DM45508 DM45522 DM45523 DM45525 DM45526 DM83502 DM83503 DM83504	- S-NEX *4*/*3* DX2/SD2, S-NEX *4*/*3* standard accessory - Stylus diameter d = 3 mm - Stroke: 60 mm (when combined with left stylus)
Inner surface 	DM83507		DM45503 DM45506 DM45509 DM45524 DM45527	- Stylus diameter d = 2 mm - Stroke: 60 mm (when combined with left stylus)
Small holes 	DM83521		DM83522 to DM83537	Stroke: 60 mm (when combined with left stylus)
Offset 	DM83517		DM45501 DM45502 DM45504 DM45505 DM45507 DM45508 DM45522 DM45523	- Offset: 50 mm - Provided with auxiliary weight - Measuring force: 10mN or less - Stylus diameter d = 3 mm - Stroke: 60 mm (when combined with left stylus)
	DM83518		DM45525 DM45526 DM83502 DM83503 DM83504	- Offset: 100 mm - Provided with auxiliary weight - Measuring force: 10mN or less - Stylus diameter d = 3 mm - Stroke: 60 mm (when combined with left stylus)
	DM83519		DM45503 DM45506 DM45509 DM45524 DM45527	- Offset: 50 mm - Provided with auxiliary weight - Measuring force: 10mN or less - Stylus diameter d = 2 mm - Stroke: 60 mm (when combined with left stylus)
	DM83520			- Offset: 100 mm - Provided with auxiliary weight - Measuring force: 10mN or less - Stylus diameter d = 2 mm - Stroke: 60 mm (when combined with left stylus)
Long items 	DM83512		DM45501 DM45502 DM45504 DM45505 DM45507 DM45508 DM45522 DM45523 DM45525 DM45526	- Lever movable range: 120 mm - Provided with auxiliary weight - Arm clamp attached - Stylus diameter d = 3 mm - Stroke: 60 mm (when combined with left stylus)
Long holes 	DM83514		DM45503 DM45506 DM45509 DM45524 DM45527	- Lever movable range: 120 mm - Provided with auxiliary weight - Arm clamp attached - Stylus diameter d = 2 mm - Stroke: 60 mm (when combined with left stylus)

Quick change attachment

Applicable models ■ S-NEX *4* DX2/SD2 ■ S-NEX *3* DX2/SD2 ■ S-NEX *4* ■ S-NEX *3*

Measuring application	Model	External view	Applicable arm	Remarks
Quick change attachment 	DM83506			- Required for S-NEX *4*/*3* DX2/SD2, S-NEX *4*/*3* when using linear series (C1700-1710-2700 S1900-1910-2900) arm or stylus - Auxiliary weight required
Auxiliary weight for quick change attachment 	DM83505-S310 ^{*1} 3		0102800 0102805 0102801 0102806 0102802 0102807 0102804	- S-NEX *3* DX2/SD2, S-NEX *3* - Measuring force 10 mN or less
	DM83505-S307 ^{*1} 3		0102808	- S-NEX *3* DX2/SD2, S-NEX *3* - Measuring force 10 mN or less
	DM83505-S308 ^{*1} 3		0102810	- S-NEX *3* DX2/SD2, S-NEX *3* - Measuring force 10 mN or less
	DM83505-S305 ^{*1} 3		0102800	- S-NEX *3* DX2/SD2, S-NEX *3* - Measuring force 30 mN or less
	DM83505-S306 ^{*1} 3		0102801	- S-NEX *3* DX2/SD2, S-NEX *3* - Measuring force 30 mN or less
	DM83505-S309 ^{*2} 3		DM45528 DM45531 DM45529 DM45532 DM45530 DM45533	- S-NEX *4* DX2/SD2, S-NEX *4* - Measuring force 10 mN or less
	DM83505-S301 ^{*2} 3		DM45528 DM45529	- S-NEX *4* DX2/SD2, S-NEX *4* - Measuring force 30 mN or less
Arm clamp 	DM83538		0102808 0102810	Required when using combination of linear series long arm 0102808, 0102810 and quick change attachment

*1: Please refer to page 91 for finding stylus which can be attached to the applicable arm for selecting S-NEX *3* DX2/SD2, S-NEX *3* use auxiliary weight.

*2: Please refer to page 93 for finding stylus which can be attached to the applicable arm for selecting S-NEX *4* DX2/SD2, S-NEX *4* use auxiliary weight.

*3: Please contact us in case of using combination of stylus and arm other than *1 and *2.

Standard Inventory Parts

SURFCOM-CONTOURCORD
Option