



Stylus

Applicable models ■ E-DT-R95B (R30, R40, R31, R41, R43) ■ E-DT-R83B (R47, R55, R60A, R65A, R65B) ■ E-DT-R120B (R44, R54, R-NEX (DX2/SD2), R-NEX, R55, R60A, R65A, R65B) ■ E-DT-R357A (R-CREST)

1: 1 Standard Sensitivity L = 59.5 mm

Measuring application	Model	External view	Specifications
General purpose	EM46000-S300		Φ 3.2 mm Carbide ball
Small holes	EM46000-S301		Φ 1 mm Carbide ball
General purpose	EM46000-S302		Φ 1.6 mm Carbide ball Standard stylus
Grooves	EM46000-S303		R0.25 mm, 55° conical Sapphire, L-type, L = 4.5 mm
Deep grooves	EM46000-S304		R0.25 mm, 55° conical Sapphire, L-type, L = 10 mm
Corners	EM46000-S305		R0.25 mm, 55° conical Sapphire, L-type, L = 3.4 mm/60°
Grooves	EM46000-S306		R0.25 mm, 55° conical Sapphire, T-type, L = 6.5 mm
	EM46000-S307		R0.25 mm, 55° conical Sapphire, T-type, L = 10 mm
Deep grooves	EM46000-S308		R0.25 mm, 55° conical Sapphire, T-type, L = 20 mm
Extra small holes	EM46000-S309		Φ 0.5 mm Carbide ball
Cutter mark removal	EM46000-S310		R0.25 mm Sapphire, L type, L = 4.8 mm/R15 mm
Small holes (Crank stylus)	EM46001-S502		Φ 1 mm Ruby ball Manufactured after receipt of order
For both roundness and roughness measurement (T-stylus)	EM46001-S587		Roundness measurement side: Φ1.6 mm ruby Surface texture measurement side: Rt0.005 mm, 60° cone, diamond T-type, L=6 mm



Stylus

Applicable models ■ E-DT-R95B (R30, R40, R31, R41, R43) ■ E-DT-R83B (R47, R55, R60A, R65A, R65B) ■ E-DT-R120B (R44, R54, R-NEX (DX2/SD2), R-NEX, R55, R60A, R65A, R65B) ■ E-DT-R357A (R-CREST)

1.5:1 Sensitivity L = 97 mm

Measuring application	Model	External view	Specifications
General purpose	EM46100-S300		Φ 3.2 mm Carbide ball
Small holes	EM46100-S301		Φ 1 mm Carbide ball
General purpose	EM46100-S302		Φ 1.6 mm Carbide ball
Grooves	EM46100-S303		R0.25 mm, 55° conical Sapphire, L-type, L = 4.5 mm
Deep grooves	EM46100-S304		R0.25 mm, 55° conical Sapphire, L-type, L = 10 mm
Corners	EM46100-S305		R0.25 mm, 55° conical Sapphire, L-type, L = 3.4 mm/60°
Grooves	EM46100-S306		R0.25 mm, 55° conical Sapphire, T-type, L = 6.5 mm
	EM46100-S307		R0.25 mm, 55° conical Sapphire, T-type, L = 10 mm
Deep grooves	EM46100-S308		R0.25 mm, 55° conical Sapphire, T-type, L = 20 mm
Extra small holes	EM46100-S309		Φ 0.5 mm Carbide ball
Cutter mark removal	EM46100-S310		R0.25 mm Sapphire, L type, L = 4.8 mm/R15 mm
Stylus attachment	EM-59103-S001		Used when 2: 1 stylus for detectors [E-DT-R32B/E-DT-R74B] is mounted on detectors [E-DT-R83B/E-DT-R95B/ E-DT-R120B]