Implementation and Early Results

Joshua Thomas
MS in Artificial Intelligence Systems
University of Florida
Gainesville, USA
joshuathomas@ufl.edu

I. Project Summary

This project aims to develop a binary audio spoofing detection system that classifies speech recordings as either bonafide (real) or spoofed (AI-generated). The motivation for this work arises from the rapid advancement and accessibility of speech synthesis and voice cloning technologies, which introduce significant security and reliability concerns in applications such as voice-based authentication, fraud detection, and digital media integrity.

Since Deliverable 1, substantial progress has been made in constructing the core machine learning pipeline. The ASVspoof 2019 dataset has been successfully integrated, and a data loading module has been implemented to parse protocol files and map audio samples to their corresponding labels. A preprocessing pipeline has been developed to standardize waveform inputs through normalization and fixed-length adjustment. Additionally, raw audio signals are transformed into mel spectrogram representations, enabling effective feature extraction for convolutional neural networks.

A baseline convolutional neural network (CNN) model has been implemented and validated through successful forward passes on batched data. The system is now capable of processing raw audio inputs and producing classification outputs. Remaining work includes full model training, evaluation using appropriate metrics such as accuracy and Equal Error Rate (EER), performance optimization, and the development of an interactive user interface.

II. System Architecture and Pipeline

The system is designed as a modular pipeline that processes raw audio inputs and produces a classification output indicating whether the audio is real or spoofed. Each stage of the pipeline is responsible for transforming the data into a format suitable for the next step.

The overall structure of the system is shown below.

Audio data is first loaded from the ASVspoof 2019 dataset, which contains both bonafide and spoofed speech samples. These samples serve as the input to the system and vary in length, quality, and recording conditions.

A. Data Preprocessing

During preprocessing, each waveform undergoes normalization and length standardization through padding or truncation. Since audio samples in the dataset have different durations, it is necessary to enforce a fixed input length so that batches can be processed efficiently during training. Shorter samples are padded with zeros, while longer samples are truncated to a predefined length.



Fig. 1. System architecture for audio spoofing detection pipeline

In addition to length normalization, waveform amplitudes are scaled to a consistent range. This helps stabilize training by reducing variation in input magnitude across different samples. Without this step, large amplitude differences could negatively impact the learning process.

The preprocessing stage plays a critical role in ensuring robustness and stability. Raw audio signals vary in duration, amplitude, and recording conditions, which can negatively affect model performance if not addressed. By enforcing a fixed-length representation, the system ensures uniformity and prevents shape mismatches during training.

Following preprocessing, each waveform is converted into a mel spectrogram. This transformation converts the one-dimensional time-domain signal into a two-dimensional time-frequency representation. The mel scale approximates human auditory perception, emphasizing frequencies that are more relevant for speech processing.

This representation allows the model to capture spectral patterns and artifacts that may differentiate real and synthetic speech. For example, spoofed audio may exhibit subtle inconsistencies in frequency distribution or temporal structure that are not easily observable in the raw waveform.

B. Model Processing

The model component consists of a convolutional neural network designed to process spectrogram inputs. Convolutional layers extract spatial features from the spectrogram



Fig. 2. Example mel spectrogram used as input to the model

by applying learned filters across the time and frequency dimensions. These filters enable the model to detect patterns associated with real or spoofed speech.

Pooling layers are used to reduce the spatial dimensions of the feature maps, improving computational efficiency and helping the model focus on the most relevant features. After feature extraction, the output is passed through fully connected layers that produce a binary classification output indicating whether the input audio is bonafide or spoofed.

C. Interface Design

A user interface component is planned for future development. This interface will allow users to upload audio files, visualize input signals, and receive predictions along with confidence scores. The goal is to provide a simple and intuitive way for users to interact with the system without requiring technical knowledge.

One limitation of the current system is that it does not yet support real-time interaction or streaming audio input. These features will be considered in future iterations. The modular design of the system allows individual components to be replaced or extended, such as upgrading the model to a transformer-based architecture in later stages.

III. Model Implementation Details

The implementation focuses on building a working pipeline for training a spoofing detection model, including data handling, feature extraction, and model design.

A. Frameworks and Libraries

The system is implemented in Python using several key libraries. PyTorch is used for model development and training, providing flexibility and efficient tensor operations. Librosa is used for audio processing and feature extraction, particularly for generating mel spectrograms. NumPy supports numerical operations during preprocessing, and uv is used for environment and dependency management to ensure reproducibility.

B. Model Architecture

The baseline model is a convolutional neural network composed of multiple convolutional layers, activation functions, and pooling layers. The model takes mel spectrograms as input, where each input is represented as a two-dimensional matrix with an additional channel dimension. The convolutional layers act as feature extractors, learning filters that respond to local patterns in the time-frequency domain. These patterns may include spectral irregularities or artifacts introduced by speech synthesis systems.

Pooling layers are used to reduce the spatial dimensions of the feature maps, improving computational efficiency and introducing a degree of invariance to small variations in the input. After feature extraction, the output is flattened and passed through fully connected layers, which map the learned features to a two-class output representing bonafide and spoofed speech.

A key implementation consideration involved handling variable feature dimensions. Due to variations in spectrogram size, the flattened feature vector after convolutional layers is not constant. To address this, the fully connected layer was dynamically initialized during runtime based on the observed tensor shape. This approach ensures compatibility across different input sizes and prevents dimension mismatch errors.

C. Feature Representation

The choice of feature representation is a critical component of the system design. In this project, mel spectrograms are used as the primary input to the model. This decision is motivated by the ability of spectrograms to capture both temporal and frequency-based characteristics of audio signals.

Alternative representations, such as raw waveforms or hand-crafted features like Mel-Frequency Cepstral Coefficients (MFCCs) and Linear Frequency Cepstral Coefficients (LFCCs), were considered. While raw waveforms preserve the complete signal information, they require more complex models to effectively extract meaningful patterns. Hand-crafted features, on the other hand, may discard useful information and limit the model's ability to learn nuanced representations.

Mel spectrograms provide a balance between these approaches by offering a structured representation that is well-suited for convolutional neural networks. They enable the model to learn spatial patterns that correspond to acoustic artifacts introduced by spoofing techniques, making them particularly effective for baseline models.

D. Training Configuration

The training configuration includes the use of CrossEntropyLoss as the loss function, which is appropriate for multi-class classification problems. The Adam optimizer is used with a learning rate of 0.001 to update model parameters. A batch size of 8 is used for initial experimentation, and training is conducted over a small number of epochs to validate the pipeline.

Initial training experiments are conducted to verify the functionality of the pipeline and ensure stable gradient updates. These preliminary runs focus on confirming loss convergence behavior and identifying potential issues such as overfitting or unstable gradients. Future work will involve extended training schedules and systematic hyperparameter tuning.

E. Reproducibility and System Design

To ensure reproducibility and modularity, the implementation is divided into several components. The `data_loader.py` module handles dataset parsing and label extraction, `preprocess.py` performs waveform normalization and feature transformation, `dataset.py` provides a PyTorch-compatible dataset interface, and `baseline_cnn_model.py` defines the model architecture. The training loop is implemented in `train.py`.

This modular design enables independent modification of system components and supports reproducible experimentation across different configurations.

IV. Interface Prototype

At the current stage, a functional user interface has not yet been implemented. However, the design and intended functionality have been clearly defined.

The planned interface will allow users to upload audio files in formats such as .wav or .flac. Once an audio file is uploaded, the system will process the input through the established pipeline and return a classification result indicating whether the audio is bonafide or spoofed. The output will also include a confidence score representing the model's certainty.

Additional features may include visualization of the waveform or spectrogram to provide users with insight into the input data. These visual elements can improve interpretability and user engagement.

The interface is expected to be implemented using lightweight frameworks such as Streamlit or Gradio. The design will include components such as a file upload button, audio playback functionality, an analysis trigger (e.g., a button), and a results display section. Current limitations include the absence of real-time interaction and the lack of integration with the model.

V. Early Evaluation and Results

At this stage, full quantitative evaluation has not yet been completed, as the primary focus has been on building and validating the end-to-end pipeline. The system has been tested to ensure that each component functions correctly, including data loading, preprocessing, feature extraction, and forward passes through the model.

Initial testing confirms that the model produces outputs with the expected shape for binary classification. This verifies that the architecture is correctly configured and that data flows properly from input to output. Multiple samples have been passed through the pipeline to confirm that preprocessing is applied consistently and that all inputs are converted into model-compatible formats without errors.

Although full training results are not yet available, early testing provides confidence that the system is ready for training and evaluation. The loss function and optimizer have been integrated into the training loop, and initial runs are being used to verify that the model is capable of learning and that loss values behave as expected.

A. Evaluation Strategy

The evaluation framework has been designed to provide a comprehensive assessment of model performance. Standard classification metrics such as accuracy, precision, and recall will be used to measure overall performance. In addition, Equal Error Rate (EER) will serve as a primary metric due to its importance in spoof detection tasks. EER represents the point at which the false acceptance rate and false rejection rate are equal, making it a useful measure for balancing different types of errors.

Evaluation will be performed using both the training and development splits of the dataset. In particular, the development set will be used to assess generalization and to guide model tuning. The model will also be tested on unseen spoofing systems to better understand how well it performs on data that differs from what it was trained on.

Visual tools will also be used to support evaluation. These include confusion matrices to analyze classification errors and loss curves to track training progress over time. Examining individual predictions will help identify patterns in misclassification and provide insight into potential areas for improvement.

At this stage, the focus is on establishing a reliable evaluation pipeline. As training progresses, this framework will be used to generate more detailed performance results and guide further model refinement.

VI. Challenges and Next Steps

Several technical challenges were encountered during implementation. One of the primary challenges was handling variable-length audio inputs, which required the development of a padding and truncation strategy to standardize waveform lengths. Another challenge involved resolving dimensional mismatches between convolutional outputs and fully connected layers, which was addressed through dynamic layer initialization.

Feature representation was also a key consideration. The decision to use mel spectrograms instead of raw waveforms was motivated by the need to capture meaningful time-frequency patterns. However, selecting appropriate parameters for spectrogram generation remains an area for further refinement.

Another significant challenge involves ensuring generalization across unseen spoofing techniques. Many detection models tend to overfit to specific artifacts present in the training data, resulting in degraded performance when exposed to novel synthesis methods. Addressing this issue will be critical for real-world applicability.

Next steps include completing model training and evaluation, implementing validation using the development dataset, and optimizing model performance through architectural improvements and hyperparameter tuning. Future work will also involve integrating a user interface and extending the system to incorporate advanced models such as Wav2Vec2 or HuBERT.

VII. Responsible AI Reflection

The development of audio spoofing detection systems raises several important ethical and practical concerns. One of the main challenges is the risk of incorrect classifications. False positives, where real audio is flagged as spoofed, and false negatives, where spoofed audio is classified as real, can both have serious consequences depending on the application. For example, errors in authentication systems could either block legitimate users or allow unauthorized access.

Another concern is how well the model generalizes beyond the dataset it was trained on. Since the system is trained using a specific set of spoofing techniques, there is a risk that it may not perform as well when exposed to new or more advanced methods. This can lead to inconsistent performance in real-world scenarios, especially as speech synthesis technology continues to evolve.

There is also the possibility of adversarial behavior, where attackers intentionally design spoofing methods to bypass detection systems. As detection models improve, spoofing techniques are likely to adapt in response, creating an ongoing challenge for maintaining system reliability over time.

To address these issues, the project places a strong emphasis on testing the model against unseen spoofing systems as part of the evaluation process. This helps provide a better understanding of how the model performs in more realistic conditions. In addition, the limitations of the model will be clearly documented so that users understand where it may fail or produce uncertain results.

The system is intended to be used as a decision-support tool rather than a fully automated solution. Providing confidence scores and clear outputs can help users make more informed decisions instead of relying solely on the model's prediction. Future work will also focus on improving robustness, exploring more diverse datasets, and ensuring that the system is used responsibly in practical applications.