

General:

- `newtype Parser a = P (String -> [(a,String)])`
- Predicate: a function that takes one argument and returns a boolean
 - * if `pred x == True` then `x` satisfies predicate `pred`
- function composition:
 - the . operator composes functions:
 - `(f . g) x == f (g x)`

useful library functions:

```
-- Data.List
nubBy :: (a -> a -> Bool) -> [a] -> [a]
nubBy pred xs = -- unique elements only from xs as
                -- determined by pred
nub :: Eq a => [a] -> [a]
nub xs = nubBy (==) a -- unique elements from xs
--
words :: String -> [String]
words xs = -- list of whitespace-separated
           -- words from xs
--
-- concatenate container of lists
concat :: Foldable t => t [a] -> [a]
-- or for list-of-lists specifically:
concat :: [[a]] -> [a]
concat xs = foldl (++) [] xs
--
-- like concat, but use a function to get the inner lists
concatMap :: (a -> [b]) -> [a] -> [b]
concatMap f xs = foldr ((++) . f) [] xs
--
-- get the longest prefix of xs for which pred is true
-- and also return the rest of the list
span :: (a -> Bool) -> [a] -> ([a], [a])
span pred xs = (takeWhile pred xs, dropWhile pred xs)
--
-- repeat a = infinite list of a
repeat :: a -> [a]
repeat x = map (\_ -> x) [1..]
repeat x = [ x | _ <- [1..] ]
-- replicate n a = list of length n repeating a
replicate :: Int -> a -> [a]
replicate n x = map (\_ -> x) [1..n]
replicate n x = [ x | _ <- [1..n] ]
--
-- folds (works on any foldable, not just lists)
foldr :: (a -> b -> b) -> b -> [a] -> b
foldr f z [a,b,c] = a 'f' (b 'f' (c 'f' z))
foldr f z [a,b,c] = f a $ f b $ f c z
-- combines into z from right to left
-- can potentially work on an empty list if one of the
-- folds does not evaluate it's second argument
foldl :: (b -> a -> b) -> b -> [a] -> b
foldl f z [a,b,c] = ((z 'f' a) 'f' b) 'f' c
foldl f z [a,b,c] = f (f (f z a) b) c
-- evaluates from right to left
-- will not work on infinite list because it must start at
-- the end of the list
--
-- these are the same as above, except they take the first
-- two elements for the first application of f
foldr1 :: (a -> a -> a) -> [a] -> a
foldl1 :: (a -> a -> a) -> [a] -> a
```

Parsing.hs:

- `sat :: (Char -> Bool) -> Parser Char`
 - * returns a character if that character satisfies the predicate
- `digit, letter, alphanum :: Parser Char`
 - * parses a digit, letter, or alpha-numeric letter respectively
- `char :: Char -> Parser Char`
 - * `char 'a'` parses exactly the character 'a'
- `item :: Parser Char`
 - * parses any character
- similar to above: `digit letter alphanum lower upper string`
- `many :: Parser a -> Parser [a]`
 - * parses 0 or more instances of `a` and collects them into a list
- `many1 :: Parser a -> Parser [a]`

* same as `many`, but

- `(+++)` choice:

* parse first argument if possible, else parse second argument
* first successfully parsed argument is returned

```
(+++) :: Parser a -> Parser a -> Parser a
p +++ q = P (\inp -> case parse p inp of
                    [] -> parse q inp
                    [(v,out)] -> [(v,out)])
```

- `((>>=))` sequential composition

* `a >>= b` unboxes monad `a` into an output `a0` and then unboxes monad `b` with input `a0`

```
type Parser a = String -> [(a, String)]
-- implementation for in-class mostly-complete
-- parser 'monads'
(>>=) :: Parser a -> (a -> Parser b) -> Parser b
(>>=) p1 p2 = \inp -> case parse p1 inp of
    [] -> []
    [(v, out)] -> parse (p2 v) out
```

* usage:

```
doubleDigit :: Parser [Char]
doubleDigit =
    digit >>= \a ->
    digit >>= \b ->
    return [a,b]
-- is equivalent to
doubleDigit' :: Parser [Char]
doubleDigit' = do
    a <- digit
    b <- digit
    return [a,b]
```

* `(>>)` is the same except that it discards the result of the first monad (thus it has signature `(>>) :: Parser a -> Parser b -> Parser b`)

Parsing Examples:

- bind and lambda method of parsing:

* parse a number:

- parse arithmetic expressions using `do` syntax:

```
expr :: Parser Int
expr = do t <- term
        do {char '+'
           ; e <- expr
           ; return (t + e)
        }
        +++ return t
term :: Parser Int
term = do f <- factor
        do char '*'
        t <- term
        return (f * t)
        +++ return f
factor :: Parser Int
factor = do d <- digit
          return (digitToInt d)
        +++ do char '('
              e <- expr
              char ')'
              return e
eval :: String -> Int
eval xs = fst (head (parse expr xs))
```

Trees:

- represent either a leaf node or some kind of internal node
- arithmetic tree declaration:

```
data Expr = Val Int
          | Neg Expr
          | Add Expr Expr
          | Mul Expr Expr
```

- how to fold over a tree:

```
-- exprFold valF negF addF
exprFold :: (Int->b) -> (b->b) -> (b->b->b) ->
-- mulF input output
(b->b->b) -> Expr -> b
exprFold valF _ _ (Val i) = valF i
exprFold valF negF addF mulF (Neg e)
    = negF (exprFold valF negF addF mulF e)
exprFold valF negF addF mulF (Add s1 s2)
    = addF (exprFold valF negF addF mulF s1)
            (exprFold valF negF addF mulF s2)
exprFold valF negF addF mulF (Mul s1 s2)
    = mulF (exprFold valF negF addF mulF s1)
            (exprFold valF negF addF mulF s2)
```

* basically, just collect values into some type b and use supplied functions at each node to fold into single value
 * useful for evaluating simple things like:

```
-- evaluate an expression
evalExpr' = exprFold id (\x -> 0 - x) (+) (*)
id -- integers map to integers
(\x -> 0 - x) -- negation
-- everything else is just simple numeric operators
--
-- count leaves in a tree
countLeaves' = exprFold (\_ -> 1) id (+) (+)
(\_ -> 1) -- leaf integer node is one node
id -- negation node has only one child, pass on count
(+) (+) -- nodes with two children: add number
-- of leaf grandchildren
```

HW2: Water Gates:

```
waterGate :: Int -> Int
waterGate n =
  length -- number of True's
  $ filter id -- filter just True's
  $ waterGate' n initial -- initial call to helper
where
  -- start with all gates closed
  initial = replicate n False
  --
  -- flip states
  waterGate' 1 state = map not state
  -- base case: flip every state
  waterGate' n state = flip n $ waterGate' (n-1) state
  -- otherwise, first get the state for (n-1) and then
  -- flip every nth state
  --
  -- flip every nth gate
  flip :: Int -> [Bool] -> [Bool]
  flip 1 xs = map not xs -- flip every gate
  -- flip only gates which index are multiples of n
  flip nth xs = [ if (i `mod` nth == 0) then not x else x
    -- zip each state with it's index
    | (x,i) <- (zip xs [1..]) ]
```

HW2: Goldbach's Other Conjecture:

```
-- check if a number is prime
primeTest :: Integer -> Bool
primeTest 1 = False
primeTest t = and [ (gcd t i) == 1 | i <- [2..t-1]]
-- all numbers less than n that are double a square
twiceSquares :: Integer -> [Integer]
twiceSquares n = takeWhile (<n) [ 2 * x^2 | x <- [1..] ]
-- list of odd numbers
oddList = map (\x -> 2*x + 1) [0..]
-- all odd numbers that are composite (not prime)
allOddComp = [ o | o <- (drop 1 oddList)
  , not (primeTest o) ]
-- if a number satisfies conditions for conjecture
-- method: for enough square numbers, check if
-- n-(that number) is prime
satsConds n = or [ primeTest k |
  k <- map (\x->(n-x)) (twiceSquares n) ]
-- find the first number
goldbachNum = head [ x | x <- allOddComp
  , not (satsConds x) ]
```

HW4: Sets:

```
type Set a = [a]
a = mkSet [1,2,3,4,5]
b = mkSet [1,2,3]
addToSet :: Eq a => Set a -> a -> Set a
addToSet s a | a `elem` s = s
  | otherwise = a : s
mkSet :: Eq a => [a] -> Set a
mkSet lst = foldl addToSet [] lst
isInSet :: Eq a => Set a -> a -> Bool
isInSet [] _ = False
isInSet [a] b = a == b
isInSet (x:xs) b | x == b = True
  | otherwise = isInSet xs b
subset :: Eq a => Set a -> Set a -> Bool
subset sub super = and [ isInSet super x | x <- sub ]
setEqual :: Eq a => Set a -> Set a -> Bool
setEqual a b = subset a b && subset b a
-- instance (Eq a) => Eq (Set a) where
--   a == b = subset a b && subset b a
```

```
setProd :: Set a -> Set a -> [(a,a)]
setProd a b = [ (ai,bj) | ai <- a
  , bj <- b ]
```

Prev Exam: Run Length Encoding:

```
import Parsing
import Data.Char
q4 = do
  d <- sat isUpper
  e <- char (toLower d)
  f <- many item
  return [d,e]
ones = (map (\_ -> 1) [1..])
myRLE [] = []
myRLE ls = myhelper (zip ones ls)
myhelper [(n,c)] = [(n,c)]
myhelper ((n,c):(m,d):rest)
  | (d == c) = myhelper (((n+m),c):rest)
  | otherwise = (n,c):myhelper ((m,d):rest)
```

Rock Paper Scissors:

```
data RPS = Rock | Paper | Scissors
  deriving (Eq, Show)
rps :: RPS -> RPS -> Int
rps a b | a == b = 0
rps Rock Scissors = 1
rps Paper Rock = 1
rps Scissors Paper = 1
rps _ _ = 2
rps2 :: RPS -> RPS -> Int
rps2 a b =
  if a == b then 0 else case (a,b) of
    (Rock, Scissors) -> 1
    (Paper, Rock) -> 1
    (Scissors, Paper) -> 1
    _ -> 2
```

99 problems:

```
-- 9. pack consecutive duplicates into sublists
pack (x:xs) = let (first,rest) = span (==x) xs
  in (x:first) : pack rest
pack [] = []
-- example:
pack [1,2,3,2,2,3] == [[1,1],[2],[3],[2,2],[3]]
```

Java:

Inheritance and Virtual Methods:

• TODO

Locks: ReentrantLock and Condition:

```
import java.util.concurrent.locks.ReentrantLock;
```

- ReentrantLock: basically a mutex
- ReentrantLock.lock(): acquire the lock (blocking)
 - * does **not** throw InterruptedException
- ReentrantLock.unlock(): release the lock
 - * does **not** throw InterruptedException
 - * you should always wrap your locking code in a try{} block (including the call to lock() itself) and put the call to unlock() in a finally{} block.
 - This way, unlock() gets called no matter any exception

```
import java.util.concurrent.locks.Condition;
```

- created from a lock, allows one thread to send a message to another thread
 - * create form lock instance using lock.newCondition()
- await(): release this lock and wait for the condition to be signaled.
 - When the signal happens, await() will automatically re-acquire the lock before returning (this means you will still have to unlock manually)

* you can only `await()` when you are holding the lock, and when it returns, you still have the lock, so it acts like you never unlocked it

* **does** throw `InterruptedException`

- `signal()`: wake up a single thread that is waiting on the condition

* must be holding lock to signal it's condition

* must manually release lock before other thread will return from `await()` (because the other thread must also acquire the lock)

* **does not** throw `InterruptedException`

- `signalAll()`: similar to `signal()` except that every thread is woken up

* still only one thread will be able to use the lock-protected resource at a time, because locks

* **does not** throw `InterruptedException`

```
import java.lang.*;
import java.util.concurrent.locks.ReentrantLock;
import java.util.concurrent.locks.Condition;
public class Main2 {
    public static class Counter {
        public int count = 0;
        public ReentrantLock lock;
        public Condition updated;
        public Counter() {
            this.lock = new ReentrantLock();
            this.updated = lock.newCondition();
        }
    }
    public static class CounterThread implements Runnable {
        private Counter counter;
        public CounterThread(Counter c) {counter = c;}
        @Override
        public void run() {
            while (true) {
                try {
                    counter.lock.lock();
                    counter.count += 1;
                    System.out.println(counter.count);
                    counter.updated.signalAll();
                }
                // lock() does not throw InterruptedException
                // catch (InterruptedException e) {}
                finally {counter.lock.unlock();}
                try {
                    Thread.sleep(1000);
                } catch (InterruptedException e) {}
            }
        }
    }
    public static class IntervalPrinter implements Runnable {
        private Counter counter;
        private int mod;
        private String message;
        public IntervalPrinter(Counter c, int mod, String msg) {
            counter = c;
            this.mod = mod;
            message = msg;
        }
        @Override
        public void run() {
            while (true) {
                int val = 0;
                try {
                    counter.lock.lock();
                    counter.updated.await();
                    val = counter.count;
                }
                catch (InterruptedException e) {}
                finally {counter.lock.unlock();}
                if (val % mod == 0) {
                    System.out.println(message);
                }
            }
        }
    }
    public static void main(String []args) {
        Counter c = new Counter();
        new Thread(new CounterThread(c)).start();
        new Thread(new IntervalPrinter(c,3,"fizz")).start();
        new Thread(new IntervalPrinter(c,5,"buzz")).start();
    }
}
```

```
    new Thread(new CounterThread(c)).start();
}
```

Reflection:

- TODO