CSCE313 Refsheet; © Josh Wright 2015; Last Updated: September 23, 2017

Endianness

Value: `0xA0B0C0D0`

index	0	1	2	3
little	`0xD0`	`0xC0`	`0xB0`	`0xA0`
big	`0xA0`	`0xB0`	`0xC0`	`0xD0`

- Little Endian puts the least significant (littlest) stuff first
- x86 is little endian, MIPS is big endian
- networking is done in big endian

IPC

Pipes (FIFO)

- requires copying memory from sender process to kernel memory to recipient process
- can pass large quantities of data
- explicit communication channel
- used just like a regular file descriptor
- Unnamed Pipe
  - create using `pipe()`
  - can only be used between processes with some parent-child relationship (or grandchild, sibling, etc)
  - can override other `fd`s with
    - `dup(oldfd)` (next available fd) or
    - `dup(oldfd, newfd)` (`newfd` is closed before being overwritten)
- Named Pipe
  - created on filesystem using `mkfifo()`
  - can be used by completely unrelated processes

Message Passing

Shared Memory

- two processes directly map the same region of physical memory
- is setup using system calls, but then all access is completely in userspace (for better speed)

Semaphore Sets

- shared integer that is enforced to be ≥ 0
- `P()` decrements
  - blocks if the value is 0 (wait until non-zero and then immediately decrement)
- `V()` increments
  - will never block
- binary semaphore: either 0 or 1
  - increment on 1 has no effect and does not block

Signals

- SIGINT: keyboard interrupt
- SIGSTP: Ctrl-Z
- `sigwait()`: wait until one of a specific set of signals is caught
- signals are not queued, they are masked.
  if the kernel delivers two duplicate signals to a process while it isn't scheduled, it will receive exactly one

Network

- client side:
  - `getaddrinfo()` to get ip address from human readable address
  - `socket()` to make a socket (returns fd)
  - `connect()` to connect that socket to the address
- server side:
  - `getaddrinfo()` with the port to get the address
  - `socket()` to make socket
  - `bind()` to bind your process to that socket
  - `listen()` to listen on that socket (with a request backlog size)
  - `accept()` to get a new connection to a client (returns a new fd)
- you can read/write from network sockets just like regular files
- `/etc/services` contains info about what services are running on what ports
- TCP/IP has 2^32 possible addresses, and the protocol stack is in the kernel
- routers are comprised of layers: physical, data link, and network
- `retstat` (shell command) gives info about connections between this computer and remote servers/clients
- datagram socket: UDP broadcast?

Files

- descriptor table (DT):
  - per each process, indexed by file descriptor
  - points to entry in file table
  - in user memory, but can't be directly modified
- file table (FT):
  - shared by all processes
  - contains:
    - current cursor position
    - reference count (# of descriptors)
    - pointer to v-node entry
  - in kernel memory
- v-node table (VT):
  - one entry per file
  - contains stat structure
  - in kernel memory
- when `fork()`ing, the entire DT is copied and the relevant FT refcounts are increased
- unix IO vs stdlib IO:
  - stdlib may introduce a layer of buffering to be more efficient
  - stdlib works on non-unix OSes (portability)
  - unix IO is most low level and high performance
  - unix IO allows for accessing file metadata

Filesystem

- hard link shares an inode with the other file being linked (because there's really only one file)
  - really, it's just when two directory entries point to the same file inode
  - in this scenario, the reference count will be > 1
- soft link (symlink) is just another file that contains (in text format) the path to it's target
- superblock: contains info about entire filesystem. Size depends on version of unix/linux
- inode
  - all are same size
  - contained in inode table (an array of inodes)
  - file metadata (permissions, timestamp, etc)
    - also reference count: number of hard links
  - 12 direct pointers to data blocks (enough for 48KB file)
  - one single indirect pointer (+4MB)
  - one double indirect pointer (+4GB)
  - one triple indirect pointer (+4TB)
- data area
  - files can be ≥ 1 block(s) (may not be smaller than 1 block)