CSCE 462

SOC:

- System On a Chip

Latency vs Throughput

- latency: time to complete one operation
- throughput: operations per second
- memory has both latency and throughput

GPIO

- General Purpose Input/Output
- sometimes called “Port A”

Raspberry Pi 3

- 1.2GHz 4-core processor
- 1GB RAM
- 40 board pins, 26 are GPIO
- WiFi, Ethernet

positive vs negative logic

- positive logic
  - AKA pull down resistor
  - switch:
    - resistor from GPIO to ground
    - switch from Vcc to GPIO
  - LED: resistor and LED in series between GPIO and ground
- negative logic
  - AKA pull up resistor
  - switch:
    - resistor between GPIO and Vcc
    - switch between GPIO and ground
  - LED: resistor and LED in series between GPIO and Vcc

- in all cases, LED must be oriented correctly (pointing toward lower voltage)
- GPIO should only be used for less than 8mA
  - if LED or something needs more than that, connect it to an inverter, then connect the LED using the other kind of logic (positive/negative)
- typically use about 10k Ohm resistor with switches

ARM

- link register: stores return address of function
  - means that leaf function calls are faster
- flag bits
  - `c` carry (unsigned overflow)
    - `c` set after unsigned addition => overflow
    - `c` **NOT** set after unsigned subtraction => overflow
  - `v` overflow (signed overflow)
    - `v` set after signed addition => overflow
    - `v` set after signed subtraction => overflow
  - `z` zero
  - `n` negative
  - `p` parity
    - just xor of all bits together
  - flags set after every instruction?
- http://www.peter-cockerell.net/aalp/html/ch-2.html
- http://www.peter-cockerell.net/aalp/html/ch-3.html
- instruction format: `add{cond}{s} <dest>, <lhs>, <rhs>`
  - `s`, if present, means the instruction can change processor flags (e.g. over/underflow)
- `ldr`: load word (to register)
- `str`: store word
  - load/store can have suffix to do non-32-bit sizes:
    - `b`: byte
    - `h`: half-word (16 bits)
  - `ldr Rd, =label` (pseudo-instruction): loads address of label into register
- 16 registers: `R0-R15`, and `CPSR`
  - `R0-R3`: arguments to function call, and return value
  - `R12 IP`: Intra procedural call
  - `R13 SP`: Stack Pointer
  - `R14 LR`: Link Register
    - stores return address
  - `R15 PC`: Program Counter
    - you can read/write to this directly, it's not special (though not a good idea)
  - `CPSR`: Current Program State Register:

        * stores flags about the state of the program: negative, zero, carry, overflow, underflow, privileged mode, etc...
        * can be modified directly (want to do read-modify-write state backup first)
    - `R4-R11` and `R13 SP` are callee preserved: function should push during prologue and pop in epilogue of function
    - callee must preserve `R14 LR` if it wishes to call subroutines
    - `R12 IP` is weird. Used for libraries as stack space?
- `push`/`pop` for accessing stack
    - you can push/pop multiple things at once, but you need to reverse at the end:
      ```
      push {ip, lr, sp}
      pop {sp, lr, ip}
      ```
- `bl`: branch and link (set link register). use to call subroutines
- `bx lr`: branch to link register, to return from subroutine
- constants: `mov r1, =label`
    - can do `ldr r0, =0x523` (translates to `PC` relative load)
- literal: `mov r0, #5`, `mov r2, #0x1C`
- memory access: `ldr r0 [r0]`, `str r0 [r1, #offset]`
    - memory access is sometimes done relative to `PC`
- `bic {Rd,} Rn, <op2>`: bit-clear. Clears all bits in `Rd` that are set in `Rn`. Equivalent to `Rd = Rn & (~op2)`

powers of two:

- 2^{10} is 1K
- 2^{20} is 1M
- 2^{30} is 1G

SysTick timer

- 24-bit timer that counts down at bus clock frequency
- only counts down
- control registers (memory mapped)
    - `ctrl`: control
        * can have different sources (but is always internal on raspberry pi)
        * bit 16: COUNT bit
            · 1 if current value has been 0 since the last time you read ctrl register
            · 0 otherwise
        * enable bit to start timer (bit 0)
    - `reload`: value to start at (after counting wraps)

  - `current`: current value timer is counting at
    * whenever you write to this, no matter what you write, it resets the counter

Finite State Machine (FSM)

- Mealy vs Moore
  - Moore
    * output on states
    * output based on current state only
  - Mealy
    * output on state transitions (edges of graph)
    * output based on state and current input
- can have wait time at each state
- can be implemented like a linked list (or other ways)
- implementation
  - linked list: pointers link to adjacent nodes
  - table: stores indexes of adjacent nodes
- if you implement with a data structure, you need a driver function to advance states and whatnot
- data structure implementation seems way over complicated

Software abstraction

- Define a problem with a minimal set of basic, abstract principles / concepts
- Separation of concerns via interface/policy mechanisms
- Straightforward, mechanical path to implementation
- advantages
  - faster to develop
  - easier to debug
  - easier to change

exam 2 material