

Bohle FrameTec Select

BO 52 207 02

FrameTec – so heißt das neue Zargensystem für Ganzglasanlagen von Bohle. Für Handwerker heißt das: schneller und einfacher Einbau durch cleveres Design. Und für Nutzer: Größtmögliche Transparenz durch filigranes Profil. Dass Bohle jahrzehntelange Glaskompetenz besitzt, beweist das hochwertige Zargensystem FrameTec bereits bei der Montage. Der Einbau findet trocken statt und lässt sich schnell und einfach in einem Zug durchführen. Auch der nachträgliche Einbau, etwa im Rahmen einer Sanierung, ist problemlos möglich. Beeindruckend sind die großen Einsatz- bzw. Variationsmöglichkeiten. Ob mit Oberlichtern, Seitenteilen oder als komplette Trennwand – FrameTec bietet bei der gestalterischen Konzeption einer Ganzglasanlage grenzenlose Freiheit.



Technische Daten:

- Rahmenprofil Verbindung Glas/Wand, Glas/Glas
- Montage im Innenbereich
- Max. Türbreite 1000mm
- Max. Türhöhe 3000mm
- Material: Aluminium
- Oberfläche E6/EV1
- Für ESG/VSG 8 bis 10,76 mm Glasdicke
- Fertigset inkl. Dichtungen und Befestigung
- Inkl. Abdeckprofil des Multifunktionskanals
- Rahmenprofilmaß: 45 x 45 x 2 mm

Bohle FrameTec Select

B0 52 207 02

FrameTec - this is the name of the new Bohle profile system for all-glass systems. For tradespeople this means faster and simpler installations because of the clever design and for users it means maximum transparency because of the sophisticated profile. The high-quality Frametec profile system demonstrates during installation that Bohle has decades of glass expertise. The system can be installed quickly and easily in dry conditions in one go and the subsequent installation, for example as part of a refurbishment, is no problem at all. The wide range of possible applications and variations is impressive. Whether it's with overpanels, sidelights or as a complete partition wall - FrameTec offers unlimited creative freedom when designing all-glass systems.



Technical data:

- Frame profile connection: glass/wall, glass/glass
- Installation in indoor areas
- Max. door width: 1000 mm
- Max. door height: 3000 mm
- Material: aluminium
- E6/EV1 finish
- For LSG/tempered glass thicknesses of 8 - 10.76 mm
- Complete set incl. gaskets and fixings
- Incl. multifunctional channel cover profile
- Frame profile dimensions: 45 x 45 x 2 mm