

Model-Based Software Engineering

Lecture 04 – OCL and Concrete Syntax

Prof. Dr. Joel Greenyer



April 26, 2016



Acknowledgment

- The slides of this lecture are inspired by lecture slides from
 - *Ekkart Kindler*: Course on Advanced Topics in Software Engineering, DTU Compute, 2015.
 - <http://www2.imm.dtu.dk/courses/02265/f15/schedule.shtml>
 - *Ina Schäfer, Christoph Seidl*: Modellbasierte Softwareentwicklung, TU Braunschweig, 2015.
 - *Steffen Becker*: Model-Driven Software Development, Universität Paderborn, 2013
 - The Eclipse Open Model CourseWare (OMCW) Project:
 - <https://eclipse.org/gmt/omcw/>

[illegible]


Specialties of EReferences

in the last lecture...



- **Containment:**

- An object can only be contained in *at most one* other object at a time

- it can be target of at most one containment link at a time






- **Example:**



Specialties of EReferences

in the last lecture...

- **eOpposite:**
 - Two EReferences in opposite directions between two EClasses can be “opposites”
 - Thereby forming a bidirectional relationship
 - At the object level, there must be bidirectional links
- Example:



in the last lecture...

- Separation of Interfaces and Implementation

```
public class PlaceImpl extends NodeImpl implements Place {

    protected static final int INTIAL_MARKING_EDEFAULT = 0;
    protected int intialMarking = INTIAL_MARKING_EDEFAULT;


    public int getIntialMarking() {
        return intialMarking;
    }

    public void setIntialMarking(int newIntialMarking) {
        int oldIntialMarking = intialMarking;
        intialMarking = newIntialMarking;
        if (eNotificationRequired())
            eNotify(new ENotificationImpl(this,
                Notification.SET,
                PetrinetPackage.PLACE__INTIAL_MARKING,
                oldIntialMarking,
                intialMarking));
    }

    ...

} //PlaceImpl
```

Notification mechanism
(observer pattern) built in




- The generated code allows us to create instances of our Ecore models
 - for example (factory method):

```
public Petrinet createPetrinet() {  
    PetrinetImpl petrinet = new PetrinetImpl();  
    return petrinet;  
}
```

- The generated code allows us to create instances of our Ecore models
 - for example (factory method):

```
public Petrinet createPetrinet() {
    PetrinetImpl petrinet = new PetrinetImpl();
    return petrinet;
}
```

- But EMF also supports working with **dynamic instances**
- EMF **interprets** the metamodels to allow us to work on instance models without code generation:



creating a dynamic object
via the UI

- creating models and instances dynamically via the API:

```
// create package
EPackage petrinetPackage = EcoreFactory.eINSTANCE.createEPackage();


//create Place class
EClass placeClass = EcoreFactory.eINSTANCE.createEClass();
placeClass.setName("Place");
petrinetPackage.getEClassifiers().add(placeClass);

//create initialMarkings attribute and add it to the Place class
EAttribute initialMarkingsAttribute
    = EcoreFactory.eINSTANCE.createEAttribute();
initialMarkingsAttribute.setName("initialMarkings");
initialMarkingsAttribute.setEType(EcorePackage.eINSTANCE.getEInt());
placeClass.getEAttributes().add(initialMarkingsAttribute);

//create dynamic instance of Place class
EFactory petrinetFactory = petrinetPackage.getEFactoryInstance();
EObject place = petrinetFactory.create(placeClass);
place.eSet(initialMarkingsAttribute, 2);
```

EMF Resources

- D. Steinberg, F. Budinski, M. Paternostro, E. Merks: EMF: Eclipse Modeling Framework, Addison Wesley, 2nd edition, 2008.



- Online resources
 - <http://www.vogella.com/tutorials/EclipseEMF/article.html>
 - <http://eclipsesource.com/blogs/tutorials/emf-tutorial/>
 - There are many more online resources...

Model-Based Software Engineering

Lecture 04 – OCL and Concrete Syntax

Prof. Dr. Joel Greenyer




April 26, 2016






3.1. Introduction to OCL


What's missing?





What's missing?



What's missing?




Obviously something is missing in the Petri net metamodel!



That is not a valid Petri net!: An Arc must only connect Places to Transitions or Transitions for Places


What's missing?



- Invariant constraint written in the **Object Constraint Language (OCL)**:

```

context Arc
inv "No Arcs Between Nodes Of The Same Kind":
((self.source.ocIsKindOf(Place) and
    self.target.ocIsKindOf(Transition))
or
 (self.source.ocIsKindOf(Transition) and
    self.target.ocIsKindOf(Place) ) );
    
```



OCCL – Example

- The **Object Constraint Language (OCL)** is a formal textual language that allows us to specify **constraints** and **queries** on models with a MOF-style metamodel (UML, MOF, ...)
 - **OMG standard:** <http://www.omg.org/spec/OCL/>
- The OCL language and an interpreter are also implemented for EMF
- OCL is used in many other standards to express constraints: MOF, UML, QVT, ...

- The **Object Constraint Language (OCL)** has been developed to achieve the following goals:
 - to be formal, precise, unambiguous
 - to be applicable for a large number of users (business or system modeler, programmers)
 - to be a constraint and query language, not a programming language
 - to be tool supported

- OCL constraints and queries have **no side-effects**
- The **evaluation** of an OCL expression **returns a value**
 - multiple **types** are supported: we get to them shortly
 - When an **invariant constraint: Boolean**
- OCL is **not a programming language**
 - no program logic or flow control
 - no invocation of processes or activation of non-query operations
- OCL is a **typed language**
 - Each classifier in the model represents a distinct OCL type
 - we can define variables typed over classifiers in the model
 - Includes a set of predefined types

- OCL can be used
 - as a **query language**
 - to **specify invariants** on classes and types in a class model
 - to describe **pre- and post conditions** on operations
 - to describe **guards** (in UML behavior models)
 - to specify **derivation rules** for **derived features** (attributes or references/associations)

- Each OCL expression is related to an object, the instance of a class
 - A **context declaration** is used to determine the class
- **self** refers to the contextual instance
- Example:


Employee
age:int

context: (an instance of) Employee

context Employee
inv: **self**.age >= 19

inv: an invariant constraint; must be true for all instances of the context class (here: for all Employee instances)


- Jordi Cabot, Martin Gogolla: Object Constraint Language (OCL): A Definitive Guide, in Formal Methods for Model-Driven Engineering, Volume 7320 of Lecture Notes in Computer Science, pp 58-90, 2012.
 - http://link.springer.com/chapter/10.1007%2F978-3-642-30982-3_3
 - <http://modeling-languages.com/wp-content/uploads/2012/03/OCLChapter.pdf>
- Jos Warmer, Anneke Kleppe: The Object Constraint Language: Getting Your Models Ready for MDA, Addison-Wesley Professional; 2nd edition, 2003.
- Christian Hein, A presentation of OCL 2, Open Model CourseWare, 2006
 - <https://eclipse.org/gmt/omcw/resources/chapter01/downloads/OCL2.Fraunhofer.ppt>




3.2. OCL types

- OCL is a typed language
 - queries evaluate to values of certain types
 - we can work with variables of certain types
 - different types offer different functions
 - for example `collection->forAll(...)`

OCL Types Metamodel



OCL Types Metamodel




OCL Types Metamodel


InvalidType: the type of invalid expressions

VoidType: a type to which all other types conform except InvalidType

AnyType: a type to which all other types conform




OCaml Types Metamodel



Operations on Collection Types


- For example:



```

context Company
inv: self.employee->forAll( age <= 65 )
inv: self.employee->forAll( p | p.age <= 65 )
inv: self.employee->forAll( p : Person | p.age <= 65 )
  
```


OCCL Types Metamodel



3.2. OCL expressions



Accessing Objects and Properties



context Person

inv: `self.age > 18`


inv: `self.gender <> Gender::male`

inv: `self.employer.oclAsType(FederalInstitution).state = FederalState::LowerSaxony`



Collection Operations: Select and Reject

- **select** and **reject** are operations on collections to specify subsets
 - **select**: filters elements conforming to a condition
 - **reject**: excludes elements conforming to a condition
 - result type: same as original




context Company

inv: `self.employee->select(age > 65)->isEmpty()`

Collection Operations: Collect

- **collect** operations specify a collection derived from some other collection
 - result type: Bag




```

context Company
self.employee->collect(age)
  
```

returns a bag of integers, for example [32, 55, 43, 32, 27]

Collection Operations: ForAll

- A **forAll** operation specifies a condition that must hold for all objects in a collection
 - result type: Boolean




```

context Company
inv:  self.employee->forAll( age <= 65 )
inv:  self.employee->forAll( p | p.age <= 65 )
inv:  self.employee->forAll( p : Person | p.age <= 65 )
inv:  self.employee->forAll( p1 |
    self.employee->forAll( p2 |
        p1 <> p2 implies p1.id <> p2.id ))
    
```

Collection Operations: Exists

- An **exists** operation specifies a condition that must hold for at least one object in a collection
 - result type: Boolean




context Company

inv: `self.employee->exists(age <= 65)`

Collection Operations: Iterate

- An **iterate** operation iterates over objects in a collection and accumulates a value of in a certain return type



```

context Company.ageSumOfAllEmployees:Integer
body: self.employee->iterate(    p:Person ;
                                sum:Integer = 0 |
                                sum + p.age)
  
```

defines the value of the
derived attribute


Further OCL Operations

- **self.oclIsTypeOf**(t:OclType):Boolean
 - returns true if the type of self and t are the same
- **self.oclIsKindOf**(t:OclType):Boolean
 - returns true if the type of self and t are the same or if t is a supertype of the type of self.
- **self.oclAsType**(t:OclType):T
 - “cast” operator, returns self as an object of type T.
- **allInstances()**
 - Operation on classes, interfaces, or enumerations
 - returns all instances of the type


3.3. OCL in Ecore

Eclipse OCL Tools

- Installation:



- You can open .ecore files with the OCLinEcore editor



OClinEcore Editor

Example: Company

company.ecore

```

1 import ecore : 'http://www.eclipse.org/emf/2002/Ecore' ;
2
3 package company : company = 'http://www.example.org/company'
4 {
5     class Company extends NamedElement
6     {
7         property department : Department[*] { ordered composes };
8     }
9     class Department extends NamedElement
10    {
11        property employee : Person[*] { ordered composes };
12        attribute ageSumOfEmployees : ecore::EInt[?] { derived readonly transient volatile }
13        {
14            initial: self.employee->iterate(p; sum:Integer = 0 | sum + p.age);
15        }
16    }
17    class NamedElement
18    {
19        attribute name : String[?];
20    }
21    class Person extends NamedElement
22    {
23        attribute age : ecore::EInt[?];
24        invariant AllEmployeesMustBeAdults: self.age >= 18;
25    }
26 }


```

derived attribute

invariant

OClinEcore Editor

Example: Company



OClinEcore Editor

Example: Company

The screenshot displays the OCLinEcore Editor interface. On the left, the 'Model Explorer' shows a project structure for 'de.luh.se.mbse.company'. The main workspace shows the 'Company ModelingInc' model with its components: 'Department Finance' (containing 'Person Alison' and 'Person Beverly') and 'Department Marketing'. A 'Validation Problems' dialog box is open in the foreground, indicating a validation error. The dialog text reads: 'Problems encountered during validation', 'Reason: Diagnosis of Company ModelingInc', and 'The 'AllEmployeesMustBeAdults' constraint is violated on 'Person Dave''. The dialog includes 'OK' and '<< Details' buttons. In the background, a 'Progress Information' dialog is partially visible with the text 'Operation in progress'.

OClinEcore Editor

Example: Company

The screenshot displays the OCLinEcore Editor interface. On the left, the **Model Explorer** shows a project structure for `de.luh.se.mbse.company`, including `Project Dependencies`, `src`, `JRE System Library [JavaSE-1]`, `Plug-in Dependencies`, `META-INF`, and a `model` folder containing `company.aird`, `company.ecore`, `company.ecore.oclas`, `company.genmodel`, and `Company.xmi`. The `Company.xmi` file is selected.

The main editor area shows the `company.ecore` file with a tree view of the model structure:

- `platform:/resource/de.luh.se.mbse.company/model/Company.xmi`
 - `Company ModelingInc`
 - `Department Finance`
 - `Person Alison`
 - `Person Beverly`
 - `Department Marketing`
 - `Person Charlie`
 - `Person Dave` (highlighted)
- `platform:/resource/de.luh.se.mbse.company/model/company.ecore`

At the bottom, the **Properties** view shows a table with two rows:

Property	Value
Age	17
Name	Dave

A yellow callout bubble points to the value `17` in the `Age` row, containing the text: "validation shows invalid value".

OCLEcore Editor

Example: Company

The screenshot displays the OCLEcore Editor interface. The top toolbar includes icons for file operations and a 'Quick Access' search bar. The left sidebar contains a 'Model Explorer' with a search filter and a tree view of the project structure. The main workspace shows a hierarchical view of the 'company.ecore' project, with 'Department Marketing' selected. The bottom panel features a 'Properties' table and a 'Problems' view.

Model Explorer (Left Sidebar):

- type filter text
- de.luh.se.mbse.company
 - Project Dependencies
 - src
 - JRE System Library [JavaSE-1
 - Plug-in Dependencies
 - META-INF
 - model
 - company.aird
 - company.ecore
 - company.ecore.oclas
 - company.genmodel
 - Company.xmi
- de.luh.se.mbse.petrinet

Main Workspace (Company.xmi):

- platform:/resource/de.luh.se.mbse.company/model/Company.xmi
 - Company ModelingInc
 - Department Finance
 - Person Alison
 - Person Beverly
 - Department Marketing
 - Person Charlie
 - Person Dave
 - platform:/resource/de.luh.se.mbse.company/model/company.ecore

Properties Table (Bottom Panel):

Property	Value
Age Sum Of Employees	61
Name	Marketing

A yellow speech bubble points to the 'Marketing' value in the 'Name' row of the Properties table, containing the text: "interpretation of OCL derived value specifications on dynamic instance model".

OCLinEcore Editor

Example: Petri net

petrinet.ecore

```

1  import ecore : 'http://www.eclipse.org/emf/2002/Ecore' ;
2
3  package petrinet : petrinet = 'http://www.example.org/petrinet'
4  {
5      class PetriNet
6      {
7          property element : Element[*] { ordered composes };
8      }
9      abstract class Element;
10     abstract class Node extends Element
11     {
12         attribute name : String[?];
13     }
14     class Place extends Node
15     {
16         attribute initialMarkings : ecore::EInt[?];
17     }
18     class Transition extends Node;
19     class Arc extends Element
20     {
21         property source : Node[1];
22         property target : Node[1];
23         invariant NoArcsBetweenNodesOfTheSameKind:
24             ((self.source.ocIsKindOf(Place) and
25              self.target.ocIsKindOf(Transition))
26             or
27             (self.source.ocIsKindOf(Transition) and
28              self.target.ocIsKindOf(Place) ) );
29     }
30

```

- Formal, textual language for specifying queries and constraints on models with a MOF/UML metamodel
- Typed language
- No “programming”, no side-effects
- Tool support for EMF
- Used in other languages
 - we will see it again!