

Model-Based Software Engineering

Lecture 09 – Transformation

Prof. Dr. Joel Greenyer



June 21, 2016




in the last lecture...

5.3. Model-to-model transformation – graph transformations

Describe Structural Changes

in the last lecture...

- Most children understand this way of describing structural changes:




View the System as a Graph


in the last lecture...

- Idea: View the model as a graph
- Example:** train system “RailCab”

concrete syntax




abstract syntax




Graph Transformation Rule

in the last lecture...

- Describe the necessary **context of the change** and the **change itself** in a **graph transformation rule**




the rule's semantic is clear intuitively, but what does this mean exactly?




Graph Grammar Rule

in the last lecture...

- A graph grammar rule consists of two typed graphs
 - called **left-hand side (LHS)** and **right-hand side (RHS)**



short-hand notation:





node
identities

Graph Grammar Rule Application

in the last lecture...



host graph:



Graph Grammar Rule Application

in the last lecture...


host graph:



Graph Grammar Rule Application

in the last lecture...



host graph:



Graph Grammar Rule Application

in the last lecture...


host graph:



Graph Grammar Rule Application

in the last lecture...


host graph:



Graph Grammar Rule Application

in the last lecture...

host graph:




in the last lecture...

- An Eclipse project that supports the modeling, execution, and analysis of EMF-based graph transformation systems
 - <https://www.eclipse.org/henshin/>



in the last lecture...


- An Eclipse project that supports the modeling, execution, and analysis of EMF-based graph transformation systems
 - <https://www.eclipse.org/henshin/>



Exploring the State Space


in the last lecture...

- A rule application can be considered a transition in a Labeled Transition System
 - source state: host graph before the rule application
 - transition: rule application
 - target state: host graph after the rule application




state space explored with Henshin: 4 different graphs; (graph after 4 applications of move rule is isomorphic \Rightarrow equal to the first)

start graph




move





Exploring the State Space

in the last lecture...




rule as specified
in Henshin

start graph




Graph Transformations More Formally

- A **match** of a rule graph in a host graph is a **typed graph isomorphism** between the rule graph and a subgraph of the host graph




Graph Transformations More Formally

- A **match** of a rule graph in a host graph is a **typed graph isomorphism** between the rule graph and a subgraph of the host graph
 - What is a morphism?




Graph Transformations More Formally

- A **match** of a rule graph in a host graph is a **typed graph isomorphism** between the rule graph and a subgraph of the host graph
 - What is a morphism?
 - What is a graph morphism?



Graph Transformations More Formally


- A **match** of a rule graph in a host graph is a **typed graph isomorphism** between the rule graph and a subgraph of the host graph
 - What is a morphism?
 - What is a graph morphism?
 - What is a graph isomorphism?



Graph Transformations More Formally

- A **match** of a rule graph in a host graph is a **typed graph isomorphism** between the rule graph and a subgraph of the host graph

- What is a morphism?
- What is a graph morphism?
- What is a graph isomorphism?
- What is a typed graph isomorphism?



Morphisms (Background)

- In mathematics, a **morphism** is a **structure-preserving mapping** from one mathematical structure to another

Morphisms (Background)

- In mathematics, a **morphism** is a **structure-preserving mapping** from one mathematical structure to another
- Example: A **group (homo)morphism** is a function that maps one group to another in an **operation-preserving** way

Morphisms (Background)

- In mathematics, a **morphism** is a **structure-preserving mapping** from one mathematical structure to another
- Example: A **group (homo)morphism** is a function that maps one group to another in an **operation-preserving** way
 - **group**: a **set** of elements and an **operation** that maps any two elements from that set to a third element from that set

Morphisms (Background)

- In mathematics, a **morphism** is a **structure-preserving mapping** from one mathematical structure to another
- Example: A **group (homo)morphism** is a function that maps one group to another in an **operation-preserving** way
 - **group**: a **set** of elements and an **operation** that maps any two elements from that set to a third element from that set
 - **example**: natural numbers with addition (\mathbb{N} , +)

Morphisms (Background)

- In mathematics, a **morphism** is a **structure-preserving mapping** from one mathematical structure to another
- Example: A **group (homo)morphism** is a function that maps one group to another in an **operation-preserving** way
 - **group**: a **set** of elements and an **operation** that maps any two elements from that set to a third element from that set
 - **example**: natural numbers with addition $(\mathbb{N}, +)$
 - given two groups $(G_1, *)$ and $(G_2, \#)$, a **homomorphism** $h: G_1 \rightarrow G_2$ is an operation-preserving function, i.e., for $a, b \in G_1$ it holds that $h(a * b) = h(a) \# h(b)$

Morphisms (Background)

- In mathematics, a **morphism** is a **structure-preserving mapping** from one mathematical structure to another
- Example: A **group (homo)morphism** is a function that maps one group to another in an **operation-preserving** way
 - **group**: a **set** of elements and an **operation** that maps any two elements from that set to a third element from that set
 - **example**: natural numbers with addition $(\mathbb{N}, +)$
 - given two groups $(G_1, *)$ and $(G_2, \#)$, a **homomorphism** $h: G_1 \rightarrow G_2$ is an operation-preserving function, i.e., for $a, b \in G_1$ it holds that $h(a * b) = h(a) \# h(b)$
 - **example**: given (STRING, \cdot) and $(\mathbb{N}_{\geq 0}, +)$, then $\text{length}: \text{STRING} \rightarrow \mathbb{N}$ is a homomorphism, since for two strings a and b , it holds that $\text{length}(a \cdot b) = \text{length}(a) + \text{length}(b)$
 (“ \cdot ” means the concatenation of two strings)

Definition: Graph

- We define a graph G as a tuple $G = (V, E, s, t)$ where

Definition: Graph

- We define a graph G as a tuple $G = (V, E, s, t)$ where
 - V is a finite set of nodes (vertices)

Definition: Graph

- We define a graph G as a tuple $G = (V, E, s, t)$ where
 - V is a finite set of nodes (vertices)
 - E is a finite set of edges

Definition: Graph


- We define a graph G as a tuple $G = (V, E, s, t)$ where
 - V is a finite set of nodes (vertices)
 - E is a finite set of edges
 - $s: E \rightarrow V$ is the source function, defining edges' source nodes

Definition: Graph

- We define a graph G as a tuple $G = (V, E, s, t)$ where
 - V is a finite set of nodes (vertices)
 - E is a finite set of edges
 - $s: E \rightarrow V$ is the source function, defining edges' source nodes
 - $t: E \rightarrow V$ is the target function, defining edges' target nodes


Definition: Graph

- We define a graph G as a tuple $G = (V, E, s, t)$ where
 - V is a finite set of nodes (vertices)
 - E is a finite set of edges
 - $s: E \rightarrow V$ is the source function, defining edges' source nodes
 - $t: E \rightarrow V$ is the target function, defining edges' target nodes
- Example: How to interpret this graph mathematically?




Definition: Graph

- We define a graph G as a tuple $G = (V, E, s, t)$ where
 - V is a finite set of nodes (vertices)
 - E is a finite set of edges
 - $s: E \rightarrow V$ is the source function, defining edges' source nodes
 - $t: E \rightarrow V$ is the target function, defining edges' target nodes
- Example: How to interpret this graph mathematically?
 - $V = \{v1, v2, v3\}$




Definition: Graph

- We define a graph G as a tuple $G = (V, E, s, t)$ where
 - V is a finite set of nodes (vertices)
 - E is a finite set of edges
 - $s: E \rightarrow V$ is the source function, defining edges' source nodes
 - $t: E \rightarrow V$ is the target function, defining edges' target nodes
- Example: How to interpret this graph mathematically?
 - $V = \{v1, v2, v3\}$
 - $E = \{e1, e2, e3\}$




Definition: Graph

- We define a graph G as a tuple $G = (V, E, s, t)$ where
 - V is a finite set of nodes (vertices)
 - E is a finite set of edges
 - $s: E \rightarrow V$ is the source function, defining edges' source nodes
 - $t: E \rightarrow V$ is the target function, defining edges' target nodes
- Example: How to interpret this graph mathematically?
 - $V = \{v1, v2, v3\}$
 - $E = \{e1, e2, e3\}$
 - $s = \{(e1, v1), (e2, v2), (e3, v2)\}$




Definition: Graph

- We define a graph G as a tuple $G = (V, E, s, t)$ where
 - V is a finite set of nodes (vertices)
 - E is a finite set of edges
 - $s: E \rightarrow V$ is the source function, defining edges' source nodes
 - $t: E \rightarrow V$ is the target function, defining edges' target nodes
- Example: How to interpret this graph mathematically?
 - $V = \{v1, v2, v3\}$
 - $E = \{e1, e2, e3\}$
 - $s = \{(e1, v1), (e2, v2), (e3, v2)\}$
 - $t = \{(e1, v2), (e2, v1), (e3, v3)\}$



Definition: Graph


- We define a graph G as a tuple $G = (V, E, s, t)$ where
 - V is a finite set of nodes (vertices)
 - E is a finite set of edges
 - $s: E \rightarrow V$ is the source function, defining edges' source nodes
 - $t: E \rightarrow V$ is the target function, defining edges' target nodes
- Example: How to interpret this graph mathematically?
 - $V = \{v1, v2, v3\}$
 - $E = \{e1, e2, e3\}$
 - $s = \{(e1, v1), (e2, v2), (e3, v2)\}$
 - $t = \{(e1, v2), (e2, v1), (e3, v3)\}$



Definition: Graph


- We define a graph G as a tuple $G = (V, E, s, t)$ where
 - V is a finite set of nodes (vertices)
 - E is a finite set of edges
 - $s: E \rightarrow V$ is the source function, defining edges' source nodes
 - $t: E \rightarrow V$ is the target function, defining edges' target nodes
- Example: How to interpret this graph mathematically?
 - $V = \{v1, v2, v3\}$
 - $E = \{e1, e2, e3\}$
 - $s = \{(e1, v1), (e2, v2), (e3, v2)\}$
 - $t = \{(e1, v2), (e2, v1), (e3, v3)\}$

We also write for example $s(e1) = v2$




Labeled Graph

- Problem: How to formalize the following graph?




Labeled Graph

- Problem: How to formalize the following graph?
 - multiple nodes called “:Track”




Labeled Graph

- Problem: How to formalize the following graph?
 - multiple nodes called “:Track”
 - multiple edges called “isOn”




Labeled Graph

- Problem: How to formalize the following graph?
 - multiple nodes called “:Track”
 - multiple edges called “isOn”
- Element names are the same, but identities are not




Labeled Graph

- Problem: How to formalize the following graph?
 - multiple nodes called “:Track”
 - multiple edges called “isOn”
- Element names are the same, but identities are not
- We cannot have a set with the same element occurring multiple times, e.g. $E = \{isOn, next, next, next, next\}$



Labeled Graph

- Problem: How to formalize the following graph?
 - multiple nodes called “:Track”
 - multiple edges called “isOn”
- Element names are the same, but identities are not
- We cannot have a set with the same element occurring multiple times, e.g. $E = \{isOn, next, next, next, next\}$
- Solution: Model labels explicitly



Labeled Graph

- **Labels:** Giving names to nodes and edges

Labeled Graph

- **Labels:** Giving names to nodes and edges
- A graph G can be extended by labeling functions L_V and L_E

Labeled Graph

- **Labels:** Giving names to nodes and edges
- A graph G can be extended by labeling functions L_V and L_E
 - $L_V: V \rightarrow \Sigma$ is a node labeling function

Labeled Graph


- **Labels:** Giving names to nodes and edges
- A graph G can be extended by labeling functions L_V and L_E
 - $L_V: V \rightarrow \Sigma$ is a node labeling function
 - $L_E: E \rightarrow \Sigma$ is an edge labeling function

Labeled Graph

- **Labels:** Giving names to nodes and edges
- A graph G can be extended by labeling functions L_V and L_E
 - $L_V: V \rightarrow \Sigma$ is a node labeling function
 - $L_E: E \rightarrow \Sigma$ is an edge labeling function
 - Σ : is a set of labels


Labeled Graph

- **Labels:** Giving names to nodes and edges
- A graph G can be extended by labeling functions L_V and L_E
 - $L_V: V \rightarrow \Sigma$ is a node labeling function
 - $L_E: E \rightarrow \Sigma$ is an edge labeling function
 - Σ : is a set of labels
- Example: How to interpret the given graph mathematically?




Labeled Graph

- **Labels:** Giving names to nodes and edges
- A graph G can be extended by labeling functions L_V and L_E
 - $L_V: V \rightarrow \Sigma$ is a node labeling function
 - $L_E: E \rightarrow \Sigma$ is an edge labeling function
 - Σ : is a set of labels
- Example: How to interpret the given graph mathematically?
 - $V = \{v1, v2\}$




Labeled Graph

- **Labels:** Giving names to nodes and edges
- A graph G can be extended by labeling functions L_V and L_E
 - $L_V: V \rightarrow \Sigma$ is a node labeling function
 - $L_E: E \rightarrow \Sigma$ is an edge labeling function
 - Σ : is a set of labels
- Example: How to interpret the given graph mathematically?
 - $V = \{v1, v2\}$
 - $E = \{e1\}$




Labeled Graph

- **Labels:** Giving names to nodes and edges
- A graph G can be extended by labeling functions L_V and L_E
 - $L_V: V \rightarrow \Sigma$ is a node labeling function
 - $L_E: E \rightarrow \Sigma$ is an edge labeling function
 - Σ : is a set of labels
- Example: How to interpret the given graph mathematically?
 - $V = \{v1, v2\}$
 - $E = \{e1\}$
 - $s = \{(e1, v1)\}$




Labeled Graph

- **Labels:** Giving names to nodes and edges
- A graph G can be extended by labeling functions L_V and L_E
 - $L_V: V \rightarrow \Sigma$ is a node labeling function
 - $L_E: E \rightarrow \Sigma$ is an edge labeling function
 - Σ : is a set of labels
- Example: How to interpret the given graph mathematically?
 - $V = \{v1, v2\}$
 - $E = \{e1\}$
 - $s = \{(e1, v1)\}$
 - $t = \{(e1, v2)\}$




Labeled Graph

- **Labels:** Giving names to nodes and edges
- A graph G can be extended by labeling functions L_V and L_E
 - $L_V: V \rightarrow \Sigma$ is a node labeling function
 - $L_E: E \rightarrow \Sigma$ is an edge labeling function
 - Σ : is a set of labels
- Example: How to interpret the given graph mathematically?
 - $V = \{v1, v2\}$
 - $E = \{e1\}$
 - $s = \{(e1, v1)\}$
 - $t = \{(e1, v2)\}$
 - $L_V = \{(v1, RailCab), (v2, Track)\}$





Labeled Graph

- **Labels:** Giving names to nodes and edges
- A graph G can be extended by labeling functions L_V and L_E
 - $L_V: V \rightarrow \Sigma$ is a node labeling function
 - $L_E: E \rightarrow \Sigma$ is an edge labeling function
 - Σ : is a set of labels
- Example: How to interpret the given graph mathematically?
 - $V = \{v1, v2\}$
 - $E = \{e1\}$
 - $s = \{(e1, v1)\}$
 - $t = \{(e1, v2)\}$
 - $L_V = \{(v1, RailCab), (v2, Track)\}$
 - $L_E = \{(e1, isOn)\}$





Graph Morphism

- Given two graphs $G_i = (V_i, E_i, s_i, t_i), i \in \{1, 2\}$





Graph Morphism

- Given two graphs $G_i = (V_i, E_i, s_i, t_i), i \in \{1, 2\}$
- A **graph morphism** $f: G_1 \rightarrow G_2$ consists of two functions $f = (f_V, f_E)$




Graph Morphism

- Given two graphs $G_i = (V_i, E_i, s_i, t_i), i \in \{1, 2\}$
- A **graph morphism** $f: G_1 \rightarrow G_2$ consists of two functions $f = (f_V, f_E)$
 - $f_V: V_1 \rightarrow V_2$




Graph Morphism

- Given two graphs $G_i = (V_i, E_i, s_i, t_i), i \in \{1, 2\}$
- A **graph morphism** $f: G_1 \rightarrow G_2$ consists of two functions $f = (f_V, f_E)$
 - $f_V: V_1 \rightarrow V_2$




Graph Morphism

- Given two graphs $G_i = (V_i, E_i, s_i, t_i), i \in \{1, 2\}$
- A **graph morphism** $f: G_1 \rightarrow G_2$ consists of two functions $f = (f_V, f_E)$
 - $f_V: V_1 \rightarrow V_2$
 - $f_E: E_1 \rightarrow E_2$



Graph Morphism


- Given two graphs $G_i = (V_i, E_i, s_i, t_i), i \in \{1, 2\}$
- A **graph morphism** $f: G_1 \rightarrow G_2$ consists of two functions $f = (f_V, f_E)$
 - $f_V: V_1 \rightarrow V_2$
 - $f_E: E_1 \rightarrow E_2$



Graph Morphism

- Given two graphs $G_i = (V_i, E_i, s_i, t_i), i \in \{1, 2\}$
- A **graph morphism** $f: G_1 \rightarrow G_2$ consists of two functions $f = (f_V, f_E)$
 - $f_V: V_1 \rightarrow V_2$
 - $f_E: E_1 \rightarrow E_2$

that preserve the source and target functions, i.e.,




Graph Morphism

- Given two graphs $G_i = (V_i, E_i, s_i, t_i), i \in \{1, 2\}$
- A **graph morphism** $f: G_1 \rightarrow G_2$ consists of two functions $f = (f_V, f_E)$
 - $f_V: V_1 \rightarrow V_2$
 - $f_E: E_1 \rightarrow E_2$

that preserve the source and target functions, i.e.,

- $f_V \circ s_1 = s_2 \circ f_E$ and




Graph Morphism

- Given two graphs $G_i = (V_i, E_i, s_i, t_i), i \in \{1, 2\}$
- A **graph morphism** $f: G_1 \rightarrow G_2$ consists of two functions $f = (f_V, f_E)$
 - $f_V: V_1 \rightarrow V_2$
 - $f_E: E_1 \rightarrow E_2$

that preserve the source and target functions, i.e.,

- $f_V \circ s_1 = s_2 \circ f_E$ and
- $f_V \circ t_1 = t_2 \circ f_E$




Graph Morphism

- Given two graphs $G_i = (V_i, E_i, s_i, t_i), i \in \{1, 2\}$
- A **graph morphism** $f: G_1 \rightarrow G_2$ consists of two functions $f = (f_V, f_E)$
 - $f_V: V_1 \rightarrow V_2$
 - $f_E: E_1 \rightarrow E_2$

that preserve the source and target functions, i.e.,

- $f_V \circ s_1 = s_2 \circ f_E$ and
- $f_V \circ t_1 = t_2 \circ f_E$
- Example: for these two graphs a graph morphism would be




Graph Morphism

- Given two graphs $G_i = (V_i, E_i, s_i, t_i), i \in \{1, 2\}$
- A **graph morphism** $f: G_1 \rightarrow G_2$ consists of two functions $f = (f_V, f_E)$
 - $f_V: V_1 \rightarrow V_2$
 - $f_E: E_1 \rightarrow E_2$

that preserve the source and target functions, i.e.,

- $f_V \circ s_1 = s_2 \circ f_E$ and
- $f_V \circ t_1 = t_2 \circ f_E$
- Example: for these two graphs a graph morphism would be
 - $f_V = \{(v_{11}, v_{21}), (v_{12}, v_{22})\}$



Graph Morphism

- Given two graphs $G_i = (V_i, E_i, s_i, t_i), i \in \{1, 2\}$
- A **graph morphism** $f: G_1 \rightarrow G_2$ consists of two functions $f = (f_V, f_E)$

$$- f_V: V_1 \rightarrow V_2$$

$$- f_E: E_1 \rightarrow E_2$$

that preserve the source and target functions, i.e.,


$$- f_V \circ s_1 = s_2 \circ f_E \text{ and}$$

$$- f_V \circ t_1 = t_2 \circ f_E$$

- Example: for these two graphs a graph morphism would be

$$- f_V = \{(v_{11}, v_{21}), (v_{12}, v_{22})\}$$

$$- f_E = \{(e_{11}, e_{21})\}$$



Graph Morphism

- Given two graphs $G_i = (V_i, E_i, s_i, t_i), i \in \{1, 2\}$

- A **graph morphism** $f: G_1 \rightarrow G_2$ consists of two functions $f = (f_V, f_E)$

Example:

$$- f_V: V_1 \rightarrow V_2$$

$$- f_E: E_1 \rightarrow E_2$$

that preserve the source and target functions, i.e.,


$$- f_V \circ s_1 = s_2 \circ f_E \text{ and}$$

$$- f_V \circ t_1 = t_2 \circ f_E$$

- Example: for these two graphs a graph morphism would be

$$- f_V = \{(v_{11}, v_{21}), (v_{12}, v_{22})\}$$

$$- f_E = \{(e_{11}, e_{21})\}$$



Graph Morphism

- Given two graphs $G_i = (V_i, E_i, s_i, t_i), i \in \{1, 2\}$

- A **graph morphism** $f: G_1 \rightarrow G_2$ consists of two functions $f = (f_V, f_E)$

- $f_V: V_1 \rightarrow V_2$

- $f_E: E_1 \rightarrow E_2$

Example:

$$f_V(s_1(e_{11}))$$

that preserve the source and target functions, i.e.,


- $f_V \circ s_1 = s_2 \circ f_E$ and

- $f_V \circ t_1 = t_2 \circ f_E$

- Example: for these two graphs a graph morphism would be

- $f_V = \{(v_{11}, v_{21}), (v_{12}, v_{22})\}$

- $f_E = \{(e_{11}, e_{21})\}$



Graph Morphism

- Given two graphs $G_i = (V_i, E_i, s_i, t_i), i \in \{1, 2\}$

- A **graph morphism** $f: G_1 \rightarrow G_2$ consists of two functions $f = (f_V, f_E)$

- $f_V: V_1 \rightarrow V_2$

- $f_E: E_1 \rightarrow E_2$

Example:

$$f_V(s_1(e_{11}))$$

that preserve the source and target functions, i.e.,


- $f_V \circ s_1 = s_2 \circ f_E$ and

- $f_V \circ t_1 = t_2 \circ f_E$

- Example: for these two graphs a graph morphism would be

- $f_V = \{(v_{11}, v_{21}), (v_{12}, v_{22})\}$

- $f_E = \{(e_{11}, e_{21})\}$



Graph Morphism

- Given two graphs $G_i = (V_i, E_i, s_i, t_i), i \in \{1, 2\}$

- A **graph morphism** $f: G_1 \rightarrow G_2$ consists of two functions $f = (f_V, f_E)$

- $f_V: V_1 \rightarrow V_2$

- $f_E: E_1 \rightarrow E_2$

that preserve the source and target functions, i.e.,

- $f_V \circ s_1 = s_2 \circ f_E$ and

- $f_V \circ t_1 = t_2 \circ f_E$


- Example: for these two graphs a graph morphism would be

- $f_V = \{(v_{11}, v_{21}), (v_{12}, v_{22})\}$

- $f_E = \{(e_{11}, e_{21})\}$

Example:

$$f_V(s_1(e_{11})) = s_2(f_E(e_{11}))$$



Graph Morphism

- Given two graphs $G_i = (V_i, E_i, s_i, t_i), i \in \{1, 2\}$

- A **graph morphism** $f: G_1 \rightarrow G_2$ consists of two functions $f = (f_V, f_E)$

- $f_V: V_1 \rightarrow V_2$

- $f_E: E_1 \rightarrow E_2$

that preserve the source and target functions, i.e.,

- $f_V \circ s_1 = s_2 \circ f_E$ and

- $f_V \circ t_1 = t_2 \circ f_E$


- Example: for these two graphs a graph morphism would be

- $f_V = \{(v_{11}, v_{21}), (v_{12}, v_{22})\}$

- $f_E = \{(e_{11}, e_{21})\}$

Example:

$$f_V(s_1(e_{11})) = s_2(f_E(e_{11}))$$



Graph Morphism

- Given two graphs $G_i = (V_i, E_i, s_i, t_i), i \in \{1, 2\}$

- A **graph morphism** $f: G_1 \rightarrow G_2$ consists of two functions $f = (f_V, f_E)$

- $f_V: V_1 \rightarrow V_2$

- $f_E: E_1 \rightarrow E_2$

that preserve the source and target functions, i.e.,

- $f_V \circ s_1 = s_2 \circ f_E$ and

- $f_V \circ t_1 = t_2 \circ f_E$


- Example: for these two graphs a graph morphism would be

- $f_V = \{(v_{11}, v_{21}), (v_{12}, v_{22})\}$

- $f_E = \{(e_{11}, e_{21})\}$

Example:

$$\begin{aligned} f_V(s_1(e_{11})) &= s_2(f_E(e_{11})) \\ f_V(t_1(e_{11})) \end{aligned}$$



Graph Morphism

- Given two graphs $G_i = (V_i, E_i, s_i, t_i), i \in \{1, 2\}$

- A **graph morphism** $f: G_1 \rightarrow G_2$ consists of two functions $f = (f_V, f_E)$

- $f_V: V_1 \rightarrow V_2$

- $f_E: E_1 \rightarrow E_2$

that preserve the source and target functions, i.e.,

- $f_V \circ s_1 = s_2 \circ f_E$ and

- $f_V \circ t_1 = t_2 \circ f_E$


- Example: for these two graphs a graph morphism would be

- $f_V = \{(v_{11}, v_{21}), (v_{12}, v_{22})\}$

- $f_E = \{(e_{11}, e_{21})\}$

Example:

$$\begin{aligned} f_V(s_1(e_{11})) &= s_2(f_E(e_{11})) \\ f_V(t_1(e_{11})) & \end{aligned}$$



Graph Morphism

- Given two graphs $G_i = (V_i, E_i, s_i, t_i), i \in \{1, 2\}$

- A **graph morphism** $f: G_1 \rightarrow G_2$ consists of two functions $f = (f_V, f_E)$

- $f_V: V_1 \rightarrow V_2$

- $f_E: E_1 \rightarrow E_2$

that preserve the source and target functions, i.e.,

- $f_V \circ s_1 = s_2 \circ f_E$ and

- $f_V \circ t_1 = t_2 \circ f_E$

- Example: for these two graphs a graph morphism would be


- $f_V = \{(v_{11}, v_{21}), (v_{12}, v_{22})\}$

- $f_E = \{(e_{11}, e_{21})\}$

Example:

$$f_V(s_1(e_{11})) = s_2(f_E(e_{11}))$$

$$f_V(t_1(e_{11})) = t_2(f_E(e_{11}))$$



Graph Morphism

- Given two graphs $G_i = (V_i, E_i, s_i, t_i), i \in \{1, 2\}$

- A **graph morphism** $f: G_1 \rightarrow G_2$ consists of two functions $f = (f_V, f_E)$

- $f_V: V_1 \rightarrow V_2$

- $f_E: E_1 \rightarrow E_2$

that preserve the source and target functions, i.e.,

- $f_V \circ s_1 = s_2 \circ f_E$ and

- $f_V \circ t_1 = t_2 \circ f_E$

- Example: for these two graphs a graph morphism would be


- $f_V = \{(v_{11}, v_{21}), (v_{12}, v_{22})\}$

- $f_E = \{(e_{11}, e_{21})\}$

Example:


$$f_V(s_1(e_{11})) = s_2(f_E(e_{11}))$$

$$f_V(t_1(e_{11})) = t_2(f_E(e_{11}))$$




Typed Graph

- A graph G can be **typed** by giving a **graph morphism**
 $type: G \rightarrow G_{Type}$




Typed Graph

- A graph G can be **typed** by giving a **graph morphism**
 $type: G \rightarrow G_{Type}$
 - G_{Type} is the **type graph**, the tuple $(G, type)$ is the **typed graph**




Typed Graph

- A graph G can be **typed** by giving a **graph morphism** $type: G \rightarrow G_{Type}$
 - G_{Type} is the **type graph**, the tuple $(G, type)$ is the **typed graph**
- A graph morphism (also **graph homomorphism**) is a **total function**




Typed Graph

- A graph G can be **typed** by giving a **graph morphism** $type: G \rightarrow G_{Type}$
 - G_{Type} is the **type graph**, the tuple $(G, type)$ is the **typed graph**
- A graph morphism (also **graph homomorphism**) is a **total function**
 - f_V and f_E are total



Typed Graph

- A graph G can be **typed** by giving a **graph morphism**
 $type: G \rightarrow G_{Type}$
 - G_{Type} is the **type graph**, the tuple $(G, type)$ is the **typed graph**
- A graph morphism (also **graph homomorphism**) is a **total function**
 - f_V and f_E are total
 - every element in the domain (typed graph) has to be related to exactly one element of the co-domain (type graph)



Graph Isomorphism

- A graph morphism $f = (f_V, f_E)$ is called a **graph isomorphism** if f_V and f_E are **bijective**
 - each element in the domain corresponds to exactly one element of the co-domain
 - the graph morphism is reversible


Graph Isomorphism

- A graph morphism $f = (f_V, f_E)$ is called a **graph isomorphism** if f_V and f_E are **bijective**
 - each element in the domain corresponds to exactly one element of the co-domain
 - the graph morphism is reversible
- Example:
(from before)

Graph Isomorphism

- A graph morphism $f = (f_V, f_E)$ is called a **graph isomorphism** if f_V and f_E are **bijective**
 - each element in the domain corresponds to exactly one element of the co-domain
 - the graph morphism is reversible



- Example:
(from before)



Graph Grammar Rule Application

in the last lecture...



host graph:



Graph Grammar Rule Application

in the last lecture...

host graph:



Subgraph

- A graph $G_{Sub} = (V_{Sub}, E_{Sub}, s_{Sub}, t_{Sub})$ is a **subgraph** of graph $G = (V, E, s, t)$ if

Subgraph

- A graph $G_{Sub} = (V_{Sub}, E_{Sub}, s_{Sub}, t_{Sub})$ is a **subgraph** of graph $G = (V, E, s, t)$ if
 - $V_{Sub} \subseteq V$
 - $E_{Sub} \subseteq E$
 - $s_{Sub} = s|E_{Sub}$
 - $t_{Sub} = t|E_{Sub}$

Subgraph

- A graph $G_{Sub} = (V_{Sub}, E_{Sub}, s_{Sub}, t_{Sub})$ is a **subgraph** of graph $G = (V, E, s, t)$ if
 - $V_{Sub} \subseteq V$
 - $E_{Sub} \subseteq E$
 - $s_{Sub} = s|E_{Sub}$
 - $t_{Sub} = t|E_{Sub}$

It means that the source and target functions for the subgraph are reduced to the edges which are in it.

Subgraph

- A graph $G_{Sub} = (V_{Sub}, E_{Sub}, s_{Sub}, t_{Sub})$ is a **subgraph** of graph $G = (V, E, s, t)$ if

- $V_{Sub} \subseteq V$

- $E_{Sub} \subseteq E$

- $s_{Sub} = s|E_{Sub}$

- $t_{Sub} = t|E_{Sub}$

It means that the source and target functions for the subgraph are reduced to the edges which are in it.

- If G_{Sub} is a subgraph of G , we also write $G_{Sub} \leq G$

Typed Isomorphism

- When matching a rule graph to the host graph:

Typed Isomorphism

- When matching a rule graph to the host graph:
 - rule graph and host graph have the **same type graph**

Typed Isomorphism

- When matching a rule graph to the host graph:
 - rule graph and host graph have the **same type graph**
 - the match must **respect the typing of the graphs**

Typed Isomorphism

- When matching a rule graph to the host graph:
 - rule graph and host graph have the **same type graph**
 - the match must **respect the typing of the graphs**
 - there must be a ***typed subgraph isomorphism***

Typed Isomorphism

- When matching a rule graph to the host graph:
 - rule graph and host graph have the **same type graph**
 - the match must **respect the typing of the graphs**
 - there must be a ***typed subgraph isomorphism***
- Let $G_1 = (V_1, E_1, s_1, t_1)$ and $G_2 = (V_2, E_2, s_2, t_2)$ be two graphs

Typed Isomorphism

- When matching a rule graph to the host graph:
 - rule graph and host graph have the **same type graph**
 - the match must **respect the typing of the graphs**
 - there must be a ***typed subgraph isomorphism***
- Let $G_1 = (V_1, E_1, s_1, t_1)$ and $G_2 = (V_2, E_2, s_2, t_2)$ be two graphs
 - typed by graph morphisms
 $type_1 = (type_{1V}, type_{1E}): G_1 \rightarrow G_{Type}$ and
 $type_2 = (type_{2V}, type_{2E}): G_2 \rightarrow G_{Type}$

Typed Isomorphism

- When matching a rule graph to the host graph:
 - rule graph and host graph have the **same type graph**
 - the match must **respect the typing of the graphs**
 - there must be a ***typed subgraph isomorphism***
- Let $G_1 = (V_1, E_1, s_1, t_1)$ and $G_2 = (V_2, E_2, s_2, t_2)$ be two graphs
 - typed by graph morphisms
 $type_1 = (type_{1V} \ type_{1E}): G_1 \rightarrow G_{Type}$ and
 $type_2 = (type_{2V} \ type_{2E}): G_2 \rightarrow G_{Type}$
- An **(iso)morphism** $f = G_1 \rightarrow G_2, f = (f_V \ f_E)$ is **typed** when

Typed Isomorphism

- When matching a rule graph to the host graph:
 - rule graph and host graph have the **same type graph**
 - the match must **respect the typing of the graphs**
 - there must be a ***typed subgraph isomorphism***
- Let $G_1 = (V_1, E_1, s_1, t_1)$ and $G_2 = (V_2, E_2, s_2, t_2)$ be two graphs
 - typed by graph morphisms
 $type_1 = (type_{1V} \ type_{1E}): G_1 \rightarrow G_{Type}$ and
 $type_2 = (type_{2V} \ type_{2E}): G_2 \rightarrow G_{Type}$
- An **(iso)morphism** $f = G_1 \rightarrow G_2, f = (f_V \ f_E)$ is **typed** when
 - $type_1 = type_2 \circ f$, i.e.,


Typed Isomorphism

- When matching a rule graph to the host graph:
 - rule graph and host graph have the **same type graph**
 - the match must **respect the typing of the graphs**
 - there must be a ***typed subgraph isomorphism***
- Let $G_1 = (V_1, E_1, s_1, t_1)$ and $G_2 = (V_2, E_2, s_2, t_2)$ be two graphs
 - typed by graph morphisms
 $type_1 = (type_{1V} \ type_{1E}): G_1 \rightarrow G_{Type}$ and
 $type_2 = (type_{2V} \ type_{2E}): G_2 \rightarrow G_{Type}$
- An **(iso)morphism** $f = G_1 \rightarrow G_2, f = (f_V \ f_E)$ is **typed** when
 - $type_1 = type_2 \circ f$, i.e.,
 - for all $v \in V_1$ it holds that $type_{1V}(v) = type_{2V}(f_V(v))$ and

Typed Isomorphism

- When matching a rule graph to the host graph:
 - rule graph and host graph have the **same type graph**
 - the match must **respect the typing of the graphs**
 - there must be a ***typed subgraph isomorphism***
- Let $G_1 = (V_1, E_1, s_1, t_1)$ and $G_2 = (V_2, E_2, s_2, t_2)$ be two graphs
 - typed by graph morphisms
 $type_1 = (type_{1V} \ type_{1E}): G_1 \rightarrow G_{Type}$ and
 $type_2 = (type_{2V} \ type_{2E}): G_2 \rightarrow G_{Type}$
- An **(iso)morphism** $f = G_1 \rightarrow G_2, f = (f_V \ f_E)$ is **typed** when
 - $type_1 = type_2 \circ f$, i.e.,
 - for all $v \in V_1$ it holds that $type_{1V}(v) = type_{2V}(f_V(v))$ and
 - for all $e \in E_1$ it holds that $type_{1E}(e) = type_{2E}(f_E(e))$


Typed Isomorphism



Typed Isomorphism

for all $v \in V_1$ $type_{1V}(v) = type_{2V}(f_V(v))$
for all $e \in E_1$ $type_{1E}(e) = type_{2E}(f_E(e))$


f_V and f_E



Typed Isomorphism

for all $v \in V_1$ $type_{1V}(v) = type_{2V}(f_V(v))$
for all $e \in E_1$ $type_{1E}(e) = type_{2E}(f_E(e))$


$type_{1V}$ and
 $type_{2V}$



Typed Isomorphism

for all $v \in V_1$ $type_{1V}(v) = type_{2V}(f_V(v))$
for all $e \in E_1$ $type_{1E}(e) = type_{2E}(f_E(e))$



$type_{1E}$ and
 $type_{2E}$



Graph Grammar Rule Application

in the last lecture...


host graph:




Graph Grammar Rule Application

in the last lecture...

host graph:




1. Match LHS in host graph
(find **typed isomorph subgraph**)




Graph Grammar Rule Application

host graph:



Graph Grammar Rule Application


host graph:



Graph Grammar Rule Application

in the last lecture...


host graph:



Graph Grammar Rule Application

in the last lecture...

host graph:



most graph:

Diagram illustrating a graph structure and a rule transformation.

The top graph shows nodes `:RailCab`, `:Track`, and `:Switch` connected by edges `next`, `turnNext`, and `isOn`.

The bottom graph shows a rule transformation labeled `move (rule)`. The rule is represented as `(LHS) ::= (RHS)`.


The LHS (Left Hand Side) shows a `:RailCab` node connected to a `:Track` node via the `isOn` edge. The `:Track` node is connected to another `:Track` node via the `next` edge.

The RHS (Right Hand Side) shows a `:RailCab` node connected to a `:Track` node via the `isOn` edge. The `:Track` node is connected to another `:Track` node via the `next` edge.


Dashed arrows indicate the mapping of nodes between the LHS and RHS, showing that the structure is preserved in the transformation.

3. Create nodes and edges that are in the RHS, but not in the LHS
(such that there is **typed isomorphism** between the rule's RHS graph and the resulting modified subgraph)

host graph:




Graph Transformations More Formally




Graph Transformations More Formally

- How do we treat the concept of generalization (inheritance)?
 - this makes matters a bit more complicated...



Graph Transformations More Formally


- How do we treat the concept of generalization (inheritance)?
 - this makes matters a bit more complicated...
- How do we treat attribute values?



Graph Transformations More Formally

- How do we treat the concept of generalization (inheritance)?
 - this makes matters a bit more complicated...
- How do we treat attribute values?

see for example: Juan de Lara, Roswitha Bardohl, Hartmut Ehrig, Karsten Ehrig, Ulrike Prange, Gabriele Taentzer, *Fundamental Aspects of Software Engineering, Attributed graph transformation with node type inheritance*, Theoretical Computer Science, Volume 376, Issue 3, 2007, Pages 139-163.



Graph Matching Algorithm


- Finding an isomorphic subgraph is an NP-complete problem

Graph Matching Algorithm

- Finding an isomorphic subgraph is an NP-complete problem
 - exponential in the size of the involved graphs
- In the MBSE context, the graphs are usually typed and often strongly structured
 - so matching graph transformation rule patterns can happen in practically acceptable time
- In some applications, graphs are not that structured, but then also heuristics can be employed to find close matches



Graph Matching Algorithm

- Finding an isomorphic subgraph is an NP-complete problem
 - exponential in the size of the involved graphs
- In the MBSE context, the graphs are usually typed and often strongly structured
 - so matching graph transformation rule patterns can happen in practically acceptable time
- In some applications, graphs are not that structured, but then also heuristics can be employed to find close matches



Graph Matching Algorithm

- Finding an isomorphic subgraph is an NP-complete problem
 - exponential in the size of the involved graphs
- In the MBSE context, the graphs are usually typed and often strongly structured
 - so matching graph transformation rule patterns can happen in practically acceptable time
- In some applications, graphs are not that structured, but then also heuristics can be employed to find close matches



Graph Transformations – Intermediate Summary

- Graph transformation rules allow us

Graph Transformations – Intermediate Summary

- Graph transformation rules allow us
 - to describe the behavior of systems (e.g. RailCab) formally

Graph Transformations – Intermediate Summary

- Graph transformation rules allow us
 - to describe the behavior of systems (e.g. RailCab) formally
 - to describe the behavior of object-oriented programs formally

Graph Transformations – Intermediate Summary

- Graph transformation rules allow us
 - to describe the behavior of systems (e.g. RailCab) formally
 - to describe the behavior of object-oriented programs formally
- The behavior can be analyzed formally

Graph Transformations – Intermediate Summary

- Graph transformation rules allow us
 - to describe the behavior of systems (e.g. RailCab) formally
 - to describe the behavior of object-oriented programs formally
- The behavior can be analyzed formally
- And the behavior can be execute

Graph Transformations – Intermediate Summary

- Graph transformation rules allow us
 - to describe the behavior of systems (e.g. RailCab) formally
 - to describe the behavior of object-oriented programs formally
- The behavior can be analyzed formally
- And the behavior can be execute
 - by an interpreter (like Henshin)

Graph Transformations

– Intermediate Summary

- Graph transformation rules allow us
 - to describe the behavior of systems (e.g. RailCab) formally
 - to describe the behavior of object-oriented programs formally
- The behavior can be analyzed formally
- And the behavior can be execute
 - by and interpreter (like Henshin)
 - or by code generation (like SDMTools)

<https://www.hpi.uni-potsdam.de/giese/public/mdelab/mdelab-projects/story-diagram-tools/>)

Graph Transformations

– Intermediate Summary


- Graph transformation rules allow us
 - to describe the behavior of systems (e.g. RailCab) formally
 - to describe the behavior of object-oriented programs formally
- The behavior can be analyzed formally
- And the behavior can be execute
 - by an interpreter (like Henshin)
 - or by code generation (like SDMTools)

<https://www.hpi.uni-potsdam.de/giese/public/mdelab/mdelab-projects/story-diagram-tools/>)
- So far, we have mainly considered **endogenous** model transformations, how about **exogenous** ones?

5.4. Model-to-model transformation – Triple Graph Grammars


Exogenous Model Transformations

- Example: transform Activity Diagrams to Petri nets




Exogenous Model Transformations

- Example: transform Activity Diagrams to Petri nets




Exogenous Model Transformations

- Example: transform Activity Diagrams to Petri nets




Exogenous Model Transformations

- Example: transform Activity Diagrams to Petri nets




Exogenous Model Transformations

- Example: transform Activity Diagrams to Petri nets




Exogenous Model Transformations

- Example: transform Activity Diagrams to Petri nets




Exogenous Model Transformations

- Example: transform Activity Diagrams to Petri nets




Exogenous Model Transformations

- Example: transform Activity Diagrams to Petri nets




Exogenous Model Transformations

- Example: transform Activity Diagrams to Petri nets



Example: Transform Activity Diagrams to Petri nets


- Let's start simple: How to transform
 - Initial nodes?
 - Final nodes?
 - Action nodes?
 - Control flow edges?



Relations Between Model Patterns

Example: Activity to Petri net


- Initial node \leftrightarrow Place with initial marking



Relations Between Model Patterns

Example: Activity to Petri net

- Initial node \leftrightarrow Place with initial marking




- Final node \leftrightarrow Empty Place


Relations Between Model Patterns

Example: Activity to Petri net

- Initial node \leftrightarrow Place with initial marking




- Final node \leftrightarrow Empty Place



Example: Transform Activity Diagrams to Petri nets


- Let's start simple: How to transform
 - Initial nodes?
 - Final nodes?
 - Action nodes?
 - Control flow edges?



Relations Between Model Patterns


Example: Activity to Petri net

- Action node \leftrightarrow Transition with input and output place



Example: Transform Activity Diagrams to Petri nets


- Let's start simple: How to transform
 - Initial nodes?
 - Final nodes?
 - Action nodes?
 - Control flow edges?



Relations Between Model Patterns

Example: Activity to Petri net


- Control flow edge \leftrightarrow Transition connecting in- and out places that correspond to the edge's source and target nodes



Relations Between Model Patterns

Example: Activity to Petri net


- Control flow edge \leftrightarrow Transition connecting in- and out places that correspond to the edge's source and target nodes



context: previously activity nodes and their mapping to petri net elements


Triple Graphs

- Idea 1:** describe the mapping of models as a **triple graph**




Triple Graphs

- **Idea 1:** describe the mapping of models as a **triple graph**
- What does a **triple graph** consist of?




Triple Graphs

- **Idea 1:** describe the mapping of models as a **triple graph**
- What does a **triple graph** consist of?
 - **source** graph (model)




Triple Graphs

- **Idea 1:** describe the mapping of models as a **triple graph**
- What does a **triple graph** consist of?
 - **source** graph (model)




Triple Graphs

- **Idea 1:** describe the mapping of models as a **triple graph**
- What does a **triple graph** consist of?
 - **source** graph (model)
 - **target** graph (model)




Triple Graphs

- **Idea 1:** describe the mapping of models as a **triple graph**
- What does a **triple graph** consist of?
 - **source** graph (model)
 - **target** graph (model)




Triple Graphs

- **Idea 1:** describe the mapping of models as a **triple graph**
- What does a **triple graph** consist of?
 - **source** graph (model)
 - **target** graph (model)
 - **correspondence** graph (model) that connects the source and target graphs (models)




Triple Graphs

- **Idea 1:** describe the mapping of models as a **triple graph**
- What does a **triple graph** consist of?
 - **source** graph (model)
 - **target** graph (model)
 - **correspondence** graph (model) that connects the source and target graphs (models)




Triple Graphs

- The three different graphs (source, target, correspondence) are typed over (usually different) type graphs (metamodels)




Triple Graphs

- The three different graphs (source, target, correspondence) are typed over (usually different) type graphs (metamodels)
- Also called source-, target-, and correspondence- **domain**




Triple Graphs

- The three different graphs (source, target, correspondence) are typed over (usually different) type graphs (metamodels)
- Also called source-, target-, and correspondence- **domain**
 - **source domain: Activity Diagrams**




Triple Graphs

- The three different graphs (source, target, correspondence) are typed over (usually different) type graphs (metamodels)
- Also called source-, target-, and correspondence- **domain**
 - source domain:** Activity Diagrams
 - target domain:** Petri net




Triple Graphs

- The three different graphs (source, target, correspondence) are typed over (usually different) type graphs (metamodels)
- Also called source-, target-, and correspondence- **domain**
 - source domain:** Activity Diagrams
 - target domain:** Petri net
 - correspondence domain:** AD2PN




Triple Graphs

- Example of a bigger triple graph




Triple Graphs

- An “invalid” triple graph




Triple Graphs

- An “invalid” triple graph



Triple Graphs

- An “invalid” triple graph



Triple Graph Grammar (TGG)

- How to describe which triple graphs are valid in which ones are not?
 - i.e., express which mappings are valid and which ones are not

Triple Graph Grammar (TGG)

- How to describe which triple graphs are valid in which ones are not?
 - i.e., express which mappings are valid and which ones are not
- **Idea 2:** Use a **graph grammar** that describes the production of valid triple graphs

Triple Graph Grammar (TGG)

- How to describe which triple graphs are valid in which ones are not?
 - i.e., express which mappings are valid and which ones are not
- **Idea 2:** Use a **graph grammar** that describes the production of valid triple graphs
 - → Triple Graph Grammar (TGG)