

Formal Concept Analysis

II Closure Systems and Implications


Robert Jäschke
Asmelash Teka Hadgu

FG Wissensbasierte Systeme/L3S Research Center
Leibniz Universität Hannover

slides based on a lecture by Prof. Gerd Stumme

3 Closure Systems

- Concept Intents as Closed Sets
- NEXT CLOSURE Algorithm
- Iceberg Concept Lattices
- TITANIC Algorithm

 On the blackboard:



- closure system \mathfrak{A}
- closure operator φ
- closure systems and closure operators (Th. 1)
- closure systems and complete lattices (Prop. 3)
- examples (subtrees, subintervals, convex sets, equivalence relations)

For every formal context (G, M, I) holds:

- The extents form a closure system on G .
- The intents form a closure system on M .
- $"$ is a closure operator.

Concept Intents as Closed Sets

- diagram of the lattice $(\mathfrak{P}(\{a, b, c, e\}), \supseteq)$
- classes of attributes that describe the same set of objects
- unique representatives: concept intents (=closed sets)
- minimal generators



	a	b	c	e
1	×		×	
2		×		×
3		×	×	×

NEXT CLOSURE Algorithm

Developed 1984 by Bernhard Ganter.



Can be used


- to compute the concept lattice, or
- to compute the concept lattice together with the stem base, or
- for interactive knowledge exploration.

The algorithm computes the concept intents in the *lectic order*.

NEXT CLOSURE Algorithm: Llectic Order

Let $M = \{1, \dots, n\}$. We say that $A \subseteq M$ is *lectically smaller* than $B \subseteq M$, if $B \neq A$ and the smallest element in which A and B differ belongs to B :

$$A < B :\Leftrightarrow \exists i \in B \setminus A : A \cap \{1, 2, \dots, i-1\} = B \cap \{1, 2, \dots, i-1\}$$



NEXT CLOSURE Algorithm: Theorem

Some definitions before we start:

$$A <_i B :\Leftrightarrow i \in B \setminus A \wedge A \cap \{1, 2, \dots, i-1\} = B \cap \{1, 2, \dots, i-1\}$$

$$A + i := (A \cap \{1, 2, \dots, i-1\}) \cup \{i\}$$

Theorem

The smallest concept intent larger than a given set $A \subset M$ with respect to the lexic order is

$$A \oplus i := (A + i)'' ,$$

with i being the largest element of M with $A <_i A \oplus i$.

The NEXT CLOSURE algorithm to compute all concept intents:


- 1 The lectically smallest concept intent is \emptyset'' .
- 2 If A is a concept intent, we find the lectically next intent by checking all attributes $i \in M \setminus A$ (starting with the largest), continuing in descending order until for the first time $A <_i A \oplus i$. Then $A \oplus i$ is the lectically next intent.
- 3 If $A \oplus i = M$, we stop. Otherwise we set $A := A \oplus i$ and go to step 2.

NEXT CLOSURE Algorithm: Example



	mobile (1)	phone (2)	fax (3)	paper fax (4)
Sinus 44		×		
Nokia 6110	×	×		
T-Fax 301			×	×
T-Fax 360 PC				×

A	i	$A + i$	$A \oplus i := (A + i)''$	$A <_i A \oplus i?$	new intent

NEXT CLOSURE Algorithm: Llectic Order




Iceberg Concept Lattices




The seven most general concepts (for $\text{minsupp} = 85\%$) of the 32086 concepts of the mushroom database (<http://kdd.ics.uci.edu/>).

Iceberg Concept Lattices

minsupp = 85%




Iceberg Concept Lattices



With decreasing
minimal support
more information
is revealed.

minsups = 55%

Iceberg Concept Lattices



In a nested line diagram we can read off implications.

minsupp = 55%

Def.: The *support* of a set $X \subseteq M$ of attributes is defined as

$$\text{supp}(X) := \frac{|X'|}{|G|}$$

Def.: The *iceberg concept lattice* of a formal context (G, M, I) for a given minimal support value *minsupp* is the set

$$\{(A, B) \in \underline{\mathfrak{B}}(G, M, I) \mid \text{supp}(B) \geq \text{minsupp}\}$$

The iceberg concept lattice can be computed using the TITANIC algorithm (Stumme et al., 2001).

TITANIC computes the closure system of all (*frequent*) concept intents using the *support* function $\text{supp}(X) := \frac{|X'|}{|G|}$ (for a set $X \subseteq M$ of attributes).

frequent: only concept intents above a threshold $\text{minsupp} \in [0, 1]$



Gerd Stumme

TITANIC employs some simple properties of the support function:



Lemma 4. Let $X, Y \subseteq M$.

- ① $X \subseteq Y \implies \text{supp}(X) \supseteq \text{supp}(Y)$
- ② $X'' = Y'' \implies \text{supp}(X) = \text{supp}(Y)$
- ③ $X \subseteq Y \wedge \text{supp}(X) = \text{supp}(Y) \implies X'' = Y''$

TITANIC Algorithm

Lemma 4. Let $X, Y \subseteq M$.

- ① $X \subseteq Y \implies \text{supp}(X) \geq \text{supp}(Y)$
- ② $X'' = Y'' \implies \text{supp}(X) = \text{supp}(Y)$
- ③ $X \subseteq Y \wedge \text{supp}(X) = \text{supp}(Y) \implies X'' = Y''$



	a	b	c	e
1	×		×	
2		×		×
3		×	×	×

TITANIC tries to optimize the following three questions:

- ➊ How can we compute the closure of an attribute set using only the support values?
- ➋ How can we compute the closure system such that we need to compute as few closures as possible?
- ➌ How can we derive as many support values as possible from already known support values?

TITANIC Algorithm

- 1 How can we compute the closure of an attribute set using only the support values?

$$X'' = X \cup \{m \in M \setminus X \mid \text{supp}(X) = \text{supp}(X \cup \{m\})\}$$

Example:

$\{b, c\}'' = \{b, c, e\}$, since


$$\text{supp}(\{b, c\}) = \frac{1}{3}$$

and

$$\text{supp}(\{a, b, c\}) = \frac{0}{3}$$

$$\text{supp}(\{b, c, e\}) = \frac{1}{3}$$



	a	b	c	e
1	×		×	
2		×		×
3		×	×	×



TITANIC Algorithm

- ② How can we compute the closure system such that we need to compute as few closures as possible?

We compute only the closures of the minimal generators.



	a	b	c	e
1	×		×	
2		×		×
3		×	×	×

For this example
TITANIC needs two
runs (Apriori four).

TITANIC Algorithm


- ② How can we compute the closure system such that we need to compute as few closures as possible?

We compute only the closures of the minimal generators.

A set is a *minimal generator*, iff its support is unequal to the support of its lower covers.

The minimal generators form an order ideal (i.e., if a set is *not* a minimal generator, then none of its supersets is either)

→ approach similar to Apriori



	a	b	c	e
1	×		×	
2		×		×
3		×	×	×

For this example
TITANIC needs two
runs (Apriori four).

TITANIC tries to optimize the following three questions:

- 1 How can we compute the closure of an attribute set using only the support values?
 $\rightarrow X'' = X \cup \{m \in M \setminus X \mid \text{supp}(X) = \text{supp}(X \cup \{m\})\}$
- 2 How can we compute the closure system such that we need to compute as few closures as possible?
 \rightarrow compute only the closures of the minimal generators
- 3 How can we derive as many support values as possible from already known support values?

TITANIC Algorithm

- ③ How can we derive as many support values as possible from already known support values?

Theorem: If X is *not* a minimal generator, then

$$\text{supp}(X) = \min\{\text{supp}(K) \mid K \text{ is minimal generator, } K \subseteq X\}$$


Example:

$$\text{supp}(\{a, b, c\}) = \min\left\{\frac{0}{3}, \frac{1}{3}, \frac{1}{3}, \frac{2}{3}, \frac{2}{3}\right\} = 0$$

since the set is not a minimal generator and

$$\begin{aligned} \text{supp}(\{a, b\}) &= \frac{0}{3}, & \text{supp}(\{b, c\}) &= \frac{1}{3}, \\ \text{supp}(\{a\}) &= \frac{1}{3}, & \text{supp}(\{b\}) &= \frac{2}{3}, \\ \text{supp}(\{c\}) &= \frac{2}{3} \end{aligned}$$

Remark: It is sufficient, to check the largest minimal generators K with $K \subseteq X$, i.e., in this example $\{a, b\}$ and $\{b, c\}$.



	a	b	c	e
1	×		×	
2		×		×
3		×	×	×

TITANIC tries to optimize the following three questions:

- 1 How can we compute the closure of an attribute set using only the support values?

$$\rightarrow X'' = X \cup \{m \in M \setminus X \mid \text{supp}(X) = \text{supp}(X \cup \{m\})\}$$


- 2 How can we compute the closure system such that we need to compute as few closures as possible?

\rightarrow compute only the closures of the minimal generators

- 3 How can we derive as many support values as possible from already known support values?

\rightarrow If X is not a minimal generator, then
 $\text{supp}(X) = \min\{\text{supp}(K) \mid K \text{ is minimal generator, } K \subseteq X\}$


TITANIC Algorithm



TITANIC

An algorithm
similar to Apriori.

TITANIC Algorithm: Compared to Apriori



TITANIC Algorithm

```
1) SUPPORT( $\{\emptyset\}$ );
2)  $\mathcal{K}_0 \leftarrow \{\emptyset\}$ ;
3)  $k \leftarrow 1$ ;
4) forall  $m \in M$  do  $\{m\}.p\_s \leftarrow \emptyset.s$ ;
5)  $\mathcal{C} \leftarrow \{\{m\} \mid m \in M\}$ ;
6) loop begin
7)   SUPPORT( $\mathcal{C}$ );
8)   forall  $X \in \mathcal{K}_{k-1}$  do  $X.\text{closure} \leftarrow \text{CLOSURE}(X)$ ;
9)    $\mathcal{K}_k \leftarrow \{X \in \mathcal{C} \mid X.s \neq X.p\_s\}$ ;
10)  if  $\mathcal{K}_k = \emptyset$  then exit loop ;
11)   $k++$ ;
12)   $\mathcal{C} \leftarrow \text{TITANIC-GEN}(\mathcal{K}_{k-1})$ ;
13) end loop ;
14) return  $\bigcup_{i=0}^{k-1} \{X.\text{closure} \mid X \in \mathcal{K}_i\}$ .
```

k	indicates the current iteration. In the k th iteration, all key k -sets are determined.
\mathcal{K}_k	contains after the k th iteration all key k -sets K together with their support $K.s$ and their closure $K.\text{closure}$.
\mathcal{C}	stores the candidate k -sets C together with $C.p_s$ – the minimum of the supports of all $(k-1)$ -subsets of C . $C.p_s$ is used in step 9 to prune all non-key sets.

TITANIC Algorithm: TITANIC-GEN

Input: \mathcal{K}_{k-1} , the set of key $(k-1)$ -sets K with their support $K.s$.

Output: \mathcal{C} , the set of candidate k -sets C
with the values $C.p.s := \min\{\text{supp}(C \setminus \{m\}) \mid m \in C\}$.

The variables $p.s$ assigned to the sets $\{m_1, \dots, m_k\}$ which are generated in step 1 are initialized by $\{m_1, \dots, m_k\}.p.s \leftarrow s_{\max}$.


- 1) $\mathcal{C} \leftarrow \{\{m_1 < m_2 < \dots < m_k\} \mid \{m_1, \dots, m_{k-2}, m_{k-1}\}, \{m_1, \dots, m_{k-2}, m_k\} \in \mathcal{K}_{k-1}\}$
- 2) **forall** $X \in \mathcal{C}$ **do begin**
- 3) **forall** $(k-1)$ -subsets S of X **do begin**
- 4) **if** $S \notin \mathcal{K}_{k-1}$ **then begin** $\mathcal{C} \leftarrow \mathcal{C} \setminus \{X\}$; **exit forall** ; **end**;
- 5) $X.p.s \leftarrow \min(X.p.s, S.s)$;
- 6) **end**;
- 7) **end**;
- 8) **return** \mathcal{C} .

TITANIC Algorithm: $\text{CLOSURE}(X)$ for $X \in \mathcal{K}_{k-1}$

- 1) $Y \leftarrow X$;
- 2) **forall** $m \in X$ **do** $Y \leftarrow Y \cup (X \setminus \{m\}).\text{closure}$;
- 3) **forall** $m \in M \setminus Y$ **do begin**
- 4) **if** $X \cup \{m\} \in \mathcal{C}$ **then** $s \leftarrow (X \cup \{m\}).s$
- 5) **else** $s \leftarrow \min\{K.s \mid K \in \mathcal{K}, K \subseteq X \cup \{m\}\}$;
- 6) **if** $s = X.s$ **then** $Y \leftarrow Y \cup \{m\}$
- 7) **end**;
- 8) **return** Y .

TITANIC Algorithm: Example

	edible (e)	poisonous (p)	cap shape: convex (c)	cap shape: flat (l)	cap surface: fibrous (i)
Mushroom 1	×		×		
Mushroom 2	×		×		×
Mushroom 3	×			×	×
Mushroom 4	×			×	×
Mushroom 5	×		×		×
Mushroom 6	×		×		
Mushroom 7		×		×	×
Mushroom 8		×		×	×
Mushroom 9		×		×	×
Mushroom 10		×	×		



TITANIC Algorithm: Example

$k = 0$:

step 1		step 2
X	$X.s$	$X \in \mathcal{K}_k?$
\emptyset	1	yes

$k = 1$:

steps 4+5		step 7	step 9
X	$X.p_s$	$X.s$	$X \in \mathcal{K}_k?$
$\{e\}$	1	6/10	yes
$\{p\}$	1	4/10	yes
$\{c\}$	1	4/10	yes
$\{l\}$	1	6/10	yes
$\{i\}$	1	7/10	yes

Step 8 returns: $\emptyset.\text{closure} \leftarrow \emptyset$

Then the algorithm repeats the loop for $k = 2, 3$, and 4:

	edible (e)	poisonous (p)	cap shape: convex (c)	cap shape: flat (l)	cap surface: fibrous (i)
Mushroom 1	×	×			
Mushroom 2	×	×			×
Mushroom 3	×			×	×
Mushroom 4	×			×	×
Mushroom 5	×	×			×
Mushroom 6	×	×			
Mushroom 7		×		×	×
Mushroom 8		×		×	×
Mushroom 9		×		×	×
Mushroom 10		×		×	

TITANIC Algorithm: Example

$k = 2$:

step 12		step 7	step 9
X	$X.p_s$	$X.s$	$X \in \mathcal{K}_k?$
$\{e, p\}$	4/10	0	yes
$\{e, c\}$	4/10	4/10	no
$\{e, l\}$	6/10	2/10	yes
$\{e, i\}$	6/10	4/10	yes
$\{p, c\}$	4/10	0	yes
$\{p, l\}$	4/10	4/10	no
$\{p, i\}$	4/10	3/10	yes
$\{c, l\}$	4/10	0	yes
$\{c, i\}$	4/10	2/10	yes
$\{l, i\}$	6/10	5/10	yes

Step 8 returns:

$\{e\}.closure \leftarrow \{e\}$
 $\{p\}.closure \leftarrow \{p, l\}$
 $\{c\}.closure \leftarrow \{c, e\}$
 $\{l\}.closure \leftarrow \{l\}$
 $\{i\}.closure \leftarrow \{i\}$

$k = 3$:

step 12		step 7	step 9
X	$X.p_s$	$X.s$	$X \in \mathcal{K}_k?$
$\{e, l, i\}$	2/10	2/10	no
$\{e, p, i\}$	0	0	no
$\{p, c, i\}$	0	0	no
$\{c, l, i\}$	0	0	no

Step 8 returns:

$\{e, p\}.closure \leftarrow \{e, p, c, l, i\}$
 $\{e, l\}.closure \leftarrow \{e, l, i\}$
 $\{e, i\}.closure \leftarrow \{e, i\}$
 $\{p, c\}.closure \leftarrow \{e, p, c, l, i\}$
 $\{p, i\}.closure \leftarrow \{p, l, i\}$
 $\{c, l\}.closure \leftarrow \{e, p, c, l, i\}$
 $\{c, i\}.closure \leftarrow \{e, c, i\}$
 $\{l, i\}.closure \leftarrow \{l, i\}$

	edible (e)	poisonous (p)	cap shape: convex (c)	cap shape: flat (l)	cap surface: fibrous (i)
Mushroom 1	×	×	×	×	×
Mushroom 2	×	×	×	×	×
Mushroom 3	×	×	×	×	×
Mushroom 4	×	×	×	×	×
Mushroom 5	×	×	×	×	×
Mushroom 6	×	×	×	×	×
Mushroom 7	×	×	×	×	×
Mushroom 8	×	×	×	×	×
Mushroom 9	×	×	×	×	×
Mushroom 10	×	×	×	×	×

TITANIC Algorithm: Example

Since \mathcal{K}_k is empty the loop is exited in step 10.

Finally the algorithm collects all concept intents (step 14):


$$\emptyset, \{e\}, \{p, l\}, \{c, e\}, \{l\}, \{i\}, \{e, p, c, l, i\}, \{e, l, i\}, \\ \{e, i\}, \{p, l, i\}, \{e, c, i\}, \{l, i\}$$

(which are exactly the intents of the concepts of the concept lattice on Slide 30). The algorithm determined the support of $5 + 10 + 3 = 18$ attribute sets in three passes of the database.

	edible (e)	poisonous (p)	cap shape: convex (c)	cap shape: flat (l)	cap surface: fibrous (i)
Mushroom 1	×		×		
Mushroom 2	×		×		×
Mushroom 3	×			×	×
Mushroom 4	×			×	×
Mushroom 5	×		×		×
Mushroom 6	×		×		
Mushroom 7		×		×	×
Mushroom 8		×		×	×
Mushroom 9		×		×	×
Mushroom 10		×		×	

TITANIC Algorithm: Example

$\emptyset, \{e\}, \{p, l\}, \{c, e\},$
 $\{l\}, \{i\}, \{e, p, c, l, i\},$
 $\{e, l, i\}, \{e, i\},$
 $\{p, l, i\}, \{e, c, i\}, \{l, i\}$



TITANIC Algorithm: vs. NEXT CLOSURE

- NEXT CLOSURE uses almost no memory.
- NEXT CLOSURE can explicitly employ symmetries between attributes.
- NEXT CLOSURE can be used for knowledge discovery.
- TITANIC is much more performant, in particular on large datasets.
- TITANIC allows us to incorporate and employ minimal support constraints (next slide).

TITANIC Algorithm: Computing Iceberg Concept Lattices

- stop as soon as only *non-frequent* minimal generators are computed
- return only the closures of *frequent* minimal generators
- generate candidates only from the *frequent* minimal generators
- all subsets of candidates with $k - 1$ elements must be *frequent*