IPV6

✓ The working standard for the IPv6 protocol was published by the Internet Engineering Task Force (IETF) in 1998.

✓ In 1997, IBM became the first commercial vendor to support IPv6 through its AIX 4.3 OS.

✓ In 2004, Japan and Korea were acknowledged as having the first public deployments of IPv6.

✓ The explosive growth in mobile devices including mobile phones, notebook computers, and wireless handheld devices has created a need for additional blocks of IP addresses.

✓ IPv4 currently supports a maximum of approximately 4.3 billion unique IP addresses. IPv6 supports 340,282,366,920,938,463,463,374,607,431,768,211,456 .

340-Undecillion 282-decillion 366 nonillion 920-octillion 938-septillion 463-sextillion 463-quintillion 374-quadrillion 607-trillion 431 billion 768-million 211-thousand 456

3.6 million IPs for 1 square feet

✓ Recent advancements in network technology including Network Address Translation (NAT) have temporarily lessened the urgency for new IP addresses, however, recent estimates indicate that IPv4 addresses could be exhausted before 2020.

IPV6 ADDRESS

2031:0000:0000:013F:0000:0000:0000:0001

2031::13F:0:0:0:1

Use : : only once

2031:0:0:13F::1

1080:0000:0000:0000:0000:0034:0000:417A

1080:0:0:0:0:34:0:417A

1080::34:0:417A

IPV6 Static routing

S0
2001:2::1/64

E0

2001:1::1/64

NID 2001:1::/64

S0
2001:2::2/64

E0

2001:3::1/64

NID 2001:3::/64

RA

#int e0/0
#ipv6 add 2001:1::1/64
#no sh
#int s0/2
#ipv6 add 2001:2::1/64
#no sh
#exit
#ipv6 unicast-routing
#ipv6 route 2001:3::/64 2001:2::2

RB

#int e0/0
#ipv6 add 2001:3::1/64
#no sh
#int s0/1
#ipv6 add 2001:2::2/64
#no sh
#exit
#ipv6 unicast-routing
#ipv6 route 2001:1::/64 2001:2::1

#sh ipv6 route

IPV6 ADDRESS TYPES

✓**Unique local:** It's like ipv4 private address, its range is FD00::/8

✓**Link local:** Generated automatically for each interface FE80::/10

✓**Global unicast:** It's like public address, its address space is 2000::/3

✓**Unspecified:** Shows as ::/128 when host has no usable IPV6 address

✓**Loopback:** Same as 127.0.0.1 in IPV4, in IPV6 ::1/128

✓**Multicast:** Reserved space for this is FF::/8

✓**Tunneling:** 2002::/16 range reserved for tunneling

**IPV6
Dual Stack**

boilerplateActivate Wind
Go to Settings to a

SYSTECH
HARDWARE & NETWORKING ACADEMY (P) LTD.
AN ISO 9001:2015 CERTIFIED INSTITUTE

www.systechacademy.com
www.facebook.com/systechacademy

I O S (Internetwork operating systems)

- **IOS is stored in flash**
- **Running configuration is stored in RAM**
- **Startup configuration is stored in NV RAM. (Non-volatile)**

Router Config-Registry Value:

Normal Mode	:	**0x2102**
RX-boot mode	:	**0x2101**
To by pass NV- RAM	:	**0x2142**

TO BACKUP	:	**(Normal mode & RX-boot Mode)**
TO RESTORE	:	**(Only RX-boot Mode)**

Install TFTP (Trivial File Transfer Protocol)

ROUTER HARDWARE COMPONENTS

There are 7 major internal components of a router:

- CPU
- RAM
- NVRAM
- Flash
- ROM
- Console
- Interfaces

CPU

The CPU performs functions just as it does in a normal PC. It executes commands given by the IOS using other hardware components. High-end routers may contain multiple processors or extra slots to add more CPUs later.

RAM

Random Access Memory; this component is dynamic. Meaning, its content changes constantly. The main role of the RAM is to: Store routing tables, hold fast-switching cache, performs packet buffering, and hold queues. It also provides temporary memory for the configuration file of the router while the router is powered on. However, the RAM loses content when router is restarted or powered off. This component is upgradeable!

NVRAM

Nonvolatile RAM is used to store the startup configuration files. This type of RAM does not lose its content when the router is restarted or powered off.

Flash

Flash memory is very important because it holds the Cisco IOS image file, as well as backups. This flash memory is classified as an EEPROM (*E*lectronically *E*rasable *P*rogrammable *R*ead *O*nly *M*emory). The flash ROM is upgradeable in most Cisco routers.

ROM

The ROM performs the same operations as a BIOS. It holds information about the systems hardware components and runs POST when the router first starts up.
This component can be upgraded by "unplugging" the chip and installing a new one.
A ROM upgrade ensures newer versions of the IOS.

Console

The console consists of the physical plugs and jacks on the router. The purpose of the console is to provide access for configurations.

Interfaces

The interfaces provide connectivity to LAN, WAN, and Console/Aux. They can be RJ-45 jacks soldered onto the motherboard, transceiver modules, or card modules. Cisco routers, especially the higher-end models, can be configured in many different ways. They can use a combination of transceivers, card modules and onboard interfaces.

I O S BACKUP

```
# sh version
# sh flash
    File  Length   Name/status
    1   5672636  systech
    [5672700 bytes used, 11104516 available, 16777216 total]
    16384K bytes of processor board System flash (Read ONLY)


# int e0
# ip add 10.0.0.1 255.0.0.0
# no sh
# exit
# ping 10.0.0.2
# copy flash: tftp:
Source filename [ ]?  Systech
Address or name of remote host [ ]?  10.0.0.2
Destination filename [systech]? abc
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
5672636 bytes copied in 73.100 secs (77707 bytes/sec)
```

Now abc file is stored in
C:\Program Files\Cisco Systems\Cisco TFTP Server\abc

I O S CONFIGURATION BACKUP

Configure any protocol e.g.: RIP.

sh startup-config (configuration is not viewed)

%% Non-volatile configuration memory is not present

#copy running-config startup-config

Destination filename [startup-config]? enter

sh startup-config (configuration is viewed)

#copy startup-config tftp:

 Address or name of remote host [ ]? 10.0.0.2

Destination filename [startup-config]? Xyz

!!

608 bytes copied in 0.216 secs

Now xyz file is stored in
C:\Program Files\Cisco Systems\Cisco TFTP Server\xyz

I O S CONFIGURATION RESTORE

```
#                                              erase startup-config

              Change mode to RX- boot mode

#                                              configure terminal
#                                              config-register 0x2101
#                                              ctlr z
#                                              reload
Router(boot)>                                  enable
Router(boot)#                                  configure terminal
Router(boot)(config)#                          int e0
Router(boot)(config-if)#                       ip add 10.0.0.1 255.0.0.0
Router(boot)(config-if)#                       no sh
Router(boot)(config-if)#                       ctrl z
Router(boot)#                                  ping 10.0.0.2
Router(boot)#                                  copy tftp startup-config
Host or network configuration file [host]?     Enter
Address of remote host [255.255.255.255]?      10.0.0.2
Name of configuration file [ ]?                Xyz
Configure using xyz from 10.0.0.2? [confirm]   enter
Loading xyz from 10.0.0.2 (via Ethernet0): !
OK - 608/32723 bytes]
[OK]
Router(boot)#                                  configure terminal
Router(boot)(config)#                          config-register 0x2102
Router(boot)(config)#                          exit
Router(boot)#                                  reload
```

I O S RESTORE

```
Change mode to RX- boot mode
#                                                   configure terminal
#                                                   config-register 0x2101
#                                                   ctlr z
#                                                   reload
Router(boot)>                                       enable
Router(boot)#                                       configure terminal
Router(boot)(config)#                               int e0
Router(boot)(config-if)#                            ip add 10.0.0.1 255.0.0.0
Router(boot)(config-if)#                            no sh
Router(boot)(config-if)#                            ctrl z
Router(boot)#                                       ping 10.0.0.2
Router(boot)#                                       copy tftp flash
Address or name of remote host [255.255.255.255]?   10.0.0.2
Source file name?                                   abc
Destination file name [abc]?                        Systechccna
Erase flash device before writing? [confirm] Flash contains files. Are you sure you want to erase? [confirm]
                                                    enter
Copy 'abc' from server as 'systechccna' into Flash WITH erase? [yes/no] y
Erasing device... eeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeee  ...erased
Loading abc from 10.0.0.2 (via Ethernet0): !!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
OK - 5672636/16777216  bytes]
Verifying checksum...  OK (0xE2CB)
Flash copy took 0:03:11 [hh:mm:ss]
Router(boot)#                                       configure terminal
Router(boot)(config)#                               config-register 0x2102
Router(boot)(config)#                               exit
Router(boot)#                                       reload
```

PASSWORD RECOVERY

Set password to console mode.

Switch OFF and ON the router

Press ctrl – break (to enter rom monitor mode)

>   o/r 0x2142

>   i (it will reboot)

\#   enable

\#   sh startup-config (now note the password)

\#   configure terminal

\#   config-register 0x2102

\#   ctrl z

\#   reload

SYSTECH
HARDWARE & NETWORKING ACADEMY (P) LTD.
AN ISO 9001:2015 CERTIFIED INSTITUTE

Activate Wind
Go to Settings to

TFTP

TFTP Server ———— (Cross Over Cable) ———— E0/0 **Router A**

IP Address: 10.0.0.2
SubnetMask:255.0.0.0

TFTP Server

Download and store CISCO IOS in server. View > Options (for deselect the two check Boxes logging and file transfer progress.)

ROUTER A

rommon 16 > IP_ADDRESS=10.1.1.1
(10.1.1.1 is the temporary IP address assigned to the router)
rommon 17 > IP_SUBNET_MASK=255.255.255.0
(Same as on the TFTP server)
rommon 18 > DEFAULT_GATEWAY=10.1.1.2
(Use the IP address of the TFTP server)
rommon 19 > TFTP_SERVER=10.1.1.2
(TFTP server's IP address)
rommon 20 > TFTP_FILE=c2600-is-mz.120-7.T.bin
(Exact name is case sensitive)

SYSTECH
HARDWARE & NETWORKING ACADEMY (P) LTD.
AN ISO 9001:2015 CERTIFIED INSTITUTE
www.systechacademy.com
www.facebook.com/systechacademy

```
rommon 21 > TFTP_CHECKSUM=0
(This prevents checksum errors with earlier 2600
boot ROMs)
rommon 22 > tftpdnld
This command must be lower case.
IP_ADDRESS: 10.1.1.1
      IP_SUBNET_MASK: 255.255.255.0
      DEFAULT_GATEWAY: 10.1.1.2
      TFTP_SERVER: 10.1.1.2
      TFTP_FILE: c2600-is-mz.120-7.T.bin

   Invoke this command for disaster recovery only.
   WARNING: all existing data in all partitions on
flash will be lost!
   Do you wish to continue? y/n:  [n]:  y

   Receiving c2600-is-mz.120-7.T.bin from 10.1.1.2
!!!!!.!!!!!!!!!!!!!!!!!!!.!!
   File reception completed.
   Copying file c2600-is-mz.120-7.T to flash.
   Erasing flash at 0x607c0000
   program flash location 0x60440000
rommon 22 >reset
```