```java
/**
 * This class represents a student's record within a module, containing their marks, average
 * score, and whether this score is above average for the module
 */
public class StudentRecord {

    private Student student;

    private Module module;

    private double[] marks;

    private double finalScore;

    private Boolean isAboveAverage;

    /**
     * Constructor for Student Record
     *
     * @param student
     * @param module
     * @param marks   each mark must be between 0 and 100
     */
    public StudentRecord(Student student, Module module, double[] marks) {


        // Validates that each mark is between 0 and 100
        for (double mark : marks) {
            if (mark > 100 || mark < 0) {
                throw new IllegalArgumentException("Each mark must be between 0 and 100");
            }
        }


        // Calculates final score
        double total = 0.0;
        int count = 0;
        for (double score : marks) {
            total += score;
            count++;
        }

        // Inits variables
        this.student = student;
        this.module = module;
        this.marks = marks;
        this.finalScore = total / count;
    }

    /**
     * Calculates if the student is above average for the module
     */
    public void setAboveAverage() {
        if (this.finalScore > module.getFinalAverageGrade()) {
            this.isAboveAverage = true;
        } else {
            this.isAboveAverage = false;
        }
    }

    public double getFinalScore() {
        return finalScore;
    }

    public Module getModule() {
        return module;
    }
```

```
68    }
69
70
```