TECHNICAL DATA

CRETE-AWAY®

Water based, bio-degradable concrete remover



DESCRIPTION

A chemically active liquid formulated to soften and remove concrete build up from concrete tools and equipment. CRETE-AWAY™ is designed to help avoid the damaging effects of sandblasting, bushhammering and jackhammering hardened concrete from equipment.

FEATURES & BENEFITS

- · Ready-to-use No mixing required.
- Bio-degradable, non-corrosive, low-odor, water based, won't contaminate ground water
- Reduces labor costs and equipment damage normally associated with removing built up, hardened concrete.
- Prevents damage to equipment caused by physical removal such as sandblasting or hammering.
- V.O.C. compliant.
- Will not harm most painted metal surfaces (i.e. automobiles).
- Dissolves concrete and mortar on tools, equipment and forms.
- Safely etches concrete floors.

SPECIFICATIONS & COMPLIANCES

V.O.C. compliant and biodegradable/non-corrosive **Actual VOC Content = 0 grams/liter**

APPLICATION

Brush or spray apply ready-to-use CRETE-AWAY™ to the hardened concrete surface or mortar to be removed at approximately 75 ft²/gal. (1.8 m²/gal.) If possible, immersion is the best application method. A light foaming action will occur. Allow to soak and agitate.

After the concrete has softened, apply an additional application and allow this to remain on the surface for approximately 10 minutes. Remove concrete with a scraper. If additional concrete remains, subsequent applications may be necessary. The final application may be removed by power washing.

Concrete build up of more than 1/4" (6 mm) may require multiple applications.

If treated concrete resets prior to removal, apply additional CRETE-AWAY[™] to re-soften. Leave the fresh application on for 10-15 minutes, then remove softened concrete as stated above.

PACKAGING

275 gallon totes (1040.9 L) 55 gallon drums (208.2 L) 5 gallon pails (18.9L) 1 gallon jugs (3.8 L) (4 to a case)

PRECAUTIONS & LIMITATIONS

- Though CRETE-AWAY™ is relatively safe to use, always wear protective clothing (rubber gloves, eye protection, etc.)
- Do not dilute. Diluting CRETE-AWAY™ will greatly diminish its effectiveness.
- CRETE-AWAYTM contains a mild organic acid which may oxidize certain metals if left in contact for long periods of time. After the concrete has been removed, thoroughly flush the area with clean water.
- Concrete surfaces must be dry before applying CRETE-AWAY™.
- Do not allow this product to freeze.
- Cold weather reduces the effectiveness of CRETE-AWAY™.
- A small area should be tested to ensure against staining of new equipment surfaces.

SHELF LIFE / STORAGE

Shelf life of CRETE-AWAYTM in the original tightly closed container is 2 year from the date of manufacture. Do not allow the accumulation of water, dirt or other contaminants. Do not allow this product to freeze.

TECHNICAL SERVICES

For assistance, contact technical services at: 866-791-8700 913-371-8700 www.specchemllc.com

24 HOUR EMERGENCY CONTACT:

VelocityEHS

1-(800)255-3924 (North America) +1-813-248-0585 (International) 1-300-954-583 (Australia) 0-800-591-6042 (Brazil) 400-120-0751 (China) 000-800-100-4086 (India) 800-099-0731 (Mexico) Made in America

WARRANTY

NOTICE-READ CAREFULLY CONDITIONS OF SALE

SpecChem offers this product for sale subject to and limited by the warranty which may only be varied by written agreement of a duly authorized corporate officer of SpecChem. No other representative of or for SpecChem is authorized to grant any warranty or to waive limitation of liability set forth below.

WARRANTY LIMITATION

SpecChem warrants this product to be free of manufacturing defects. If the product when purchased was defective and was within use period indicated on container or carton, when used, SpecChem will replace the defective product with new product without charge to the purchaser. SpecChem makes no other warranty, either expressed or implied, concerning this product. There is no warranty of merchantability. NO CLAIM OF ANY KIND SHALL BE GREATER THAN THE PURCHASE PRICE OF THE PRODUCT IN RE-SPECT OF WHICH DAMAGES ARE CLAIMED.

Purchaser assumes all risk associated with the use or application of the product.



1511 Baltimore Ave, Suite 600 Kansas City, MO 64108 www.specchem.com 866.791.8700