

# MAX-A-SEALER

Asphalt Pavement Sealer



## DESCRIPTION

**MAX-A-SEALER** is a high solids, asphalt hybrid emulsion designed for bituminous surfaces to protect against weathering, oil, fuels and traffic abrasion. **MAX-A-SEALER** unique technology offers a quick drying, durable protective coating that can be applied 3 to 5X that of standard sealer products.

## FEATURES / BENEFITS

- High solids formulation for maximum durability
- Contains 0% PAH's
- Environmentally friendly -No odor
- Fast cure time to minimize down time
- Increases bond strength
- High Solids > 58% solids
- No odor VOC compliant
- Contains 0 Coal Tar

## TYPICAL PERFORMANCE DATA

Property	Test Methods	Specifications	Results
Drying Time (hrs)	D2939-13M	8.0 max	1.0
Adhesion over Asphalt (psi)	D4541M	Report	283
Wet Track Abrasion (g/sq-ft)	D3910-6.4M	Report	9.96

Complies with ASTM D8099/D8099M-17 (contains 0% ASH)

## APPLICATION

**MAX-A-SEALER** must be applied to a bituminous surface free from all foreign matter and debris. The material can be applied by brush, squeegee, or spray equipment. The application surface should be dry for best results

Depending on the surface being covered, **MAX-A-SEALER**® should be applied at an application rate of 200 -300 sq-ft per gallon. The material must remain dry until it is fully cured.

## PACKAGING

5 gallon pails (18.9 L)  
55 gallon drums (208.2 L)  
275 gallon tote (1,041 L)



## SHELF LIFE / STORAGE

Shelf life of **MAX-A-SEALER**® in the original, tightly closed container is six months from the date of manufacture.

## LIMITATIONS / PRECAUTIONS

- Do not allow material to freeze
- Not designed to be applied to concrete
- Keep out of the reach of children.
- Do not take internally.
- In case of ingestion, CALL A PHYSICIAN immediately. DO NOT induce vomiting.
- Can cause skin irritation upon contact, especially prolonged or repeated. If skin contact occurs, wash immediately with soap and water and seek medical help as needed.
- If eye contact occurs, flush immediately with clean water and seek medical help as needed.
- Refer to Safety Data Sheet for complete health and safety information prior to using product.

**FOR EXTERIOR USE ONLY!**

## WARRANTY

### NOTICE-READ CAREFULLY CONDITIONS OF SALE

SpecChem offers this product for sale subject to and limited by the warranty which may only be varied by written agreement of a duly authorized corporate officer of SpecChem. No other representative of or for SpecChem is authorized to grant any warranty or to waive limitation of liability set forth below.

### WARRANTY LIMITATION

SpecChem warrants this product to be free of manufacturing defects. If the product when purchased was defective and was within use period indicated on container or carton, when used, SpecChem will replace the defective product with new product without charge to the purchaser. SpecChem makes no other warranty, either expressed or implied, concerning this product. There is no warranty of merchantability. NO CLAIM OF ANY KIND SHALL BE GREATER THAN THE PURCHASE PRICE OF THE PRODUCT IN RESPECT OF WHICH DAMAGES ARE CLAIMED.

### INHERENT RISK

Purchaser assumes all risk associated with the use or application of the product.

## TECHNICAL SERVICES

For assistance, contact technical services at:  
816-968-5600  
[www.specchem.com](http://www.specchem.com)



1511 Baltimore Ave, Suite 600  
Kansas City, MO 64108  
[www.specchemllc.com](http://www.specchemllc.com) 866.791.8700