



CONTROLLED DRAFT

Functional, Non-Functional & Acceptance Requirements

Detailed requirements and testable acceptance criteria

Product	Nod
Document version	1.0
Date	19 September 2026
Owner / operator	[NOD OWNER / LEGAL ENTITY]
Status	Controlled Draft

Release note: This pack is a production-ready baseline. Bracketed operator details must be completed before public release. Legal documents should be reviewed by Nigerian counsel before publication or execution.

1. Requirement conventions

“Shall” denotes a mandatory v1 requirement. Each requirement should map to implementation tickets and at least one automated or manual acceptance test.

2. Functional requirements

ID	Area	Requirement
FR-001	Profile	Nod shall create and persist a local Nod Profile without requiring a remote account.
FR-002	Profile	Nod shall support multiple phone/email fields and optional avatar/company/job title/website/social link fields.
FR-003	Profile	Nod shall support reusable Share Profiles and per-transfer field override.
FR-004	Discovery	Nod shall advertise only a temporary peer identifier and nearby alias needed for discovery, not full profile data.
FR-005	Discovery	Nod shall provide a time-limited Quick Nod discovery window.
FR-006	Connection	Nod shall require explicit local acceptance by the receiving device.
FR-007	Connection	Nod shall display a matching verification code/token on both devices before the session is considered trusted.
FR-008	Contacts	Nod shall preview outgoing contact fields before transmission.
FR-009	Contacts	Nod shall let the receiver preview a contact before saving it to Android Contacts.
FR-010	Files	Nod shall support photos, videos and documents selected through Android-supported pickers.
FR-011	Files	Nod shall send a metadata manifest before file payload transmission.
FR-012	Files	Nod shall check available storage before accepting large transfers where feasible.
FR-013	Transfer	Nod shall expose progress, speed/ETA when reliable, cancellation and peer-disconnect states.
FR-014	Transfer	Nod shall hash and verify completed file payloads before finalization.
FR-015	Transfer	Nod shall not expose incomplete files as completed user files.
FR-016	Quick Nod	Nod shall support a three-shake trigger only when the user has enabled the relevant Always Ready capability.
FR-017	Quick Nod	Nod shall provide a Quick Settings tile that triggers the same Quick Nod use case.
FR-018	Background	Nod shall use a foreground service only for user-visible, declared capabilities that require it.
FR-019	Scanner	Nod shall perform phone-number OCR locally where the bundled model is available and shall require review before copy/use.
FR-020	Safety	Nod shall support block, decline and

Functional, Non-Functional & Acceptance Requirements

		temporary request throttling.
FR-021	History	Nod shall store minimal transfer metadata and shall not retain full received contact payloads solely for history.
FR-022	Permissions	Nod shall request permissions contextually and explain feature impact when denied.

3. Non-functional requirements

ID	Quality	Requirement
NFR-001	Security	No transfer is marked complete before integrity verification.
NFR-002	Privacy	Nod-owned cloud infrastructure shall not be required for core v1 exchange.
NFR-003	Performance	File I/O shall be streamed/bounded; whole large files shall not be loaded into memory.
NFR-004	Reliability	Process interruption and peer loss shall leave recoverable or cleanly discarded temporary state.
NFR-005	Compatibility	Application shall install and run on API 26+ subject to hardware/Google Play Services capability checks.
NFR-006	Accessibility	Interactive targets, contrast, screen-reader labels and large-text behavior shall meet Android accessibility guidance.
NFR-007	Battery	Always Ready shall not continuously advertise/scan merely because shake detection is enabled.
NFR-008	Maintainability	Transport implementation shall sit behind a stable NodTransport interface.
NFR-009	Observability	Diagnostics shall avoid contact/file content and sensitive profile values.
NFR-010	Protocol	All control messages shall include protocol version and session/transfer identifiers.

4. Acceptance scenarios

- Both users see the same verification code and independently confirm it before connected state.
- Receiver rejects a manifest; no content bytes are finalized and sender sees rejection.
- Phone loses connection at 68%; UI enters interrupted/retry state and no corrupt completed file is shown.
- Insufficient storage is detected before large transfer acceptance or finalization and is explained clearly.
- User denies Contacts permission; file transfer remains usable.
- User denies Camera; scanner explains limitation but Nod exchange remains usable.
- Shake false-positive field test includes walking, vehicle travel, desk placement and normal phone handling.
- Blocked peer cannot repeatedly produce foreground connection prompts during the block period.

5. Definition of done

A feature is not done until product behavior, error behavior, accessibility, privacy implications, logs, tests and relevant policy declarations are updated together.