


School of Computing and Information Systems
The University of Melbourne
COMP90049 Introduction to Machine Learning (Semester 1, 2021)
Week 8

1. Consider the following multilayer perceptron.



The network should implement the XOR function. Perform one epoch of *backpropagation* as introduced in the lecture on multilayer perceptrons.

Notes:

- The activation function f for a perceptron is the *sigmoid function*:

$$f(x) = \frac{1}{1 + e^{-x}}$$

- The thresholds are not shown in the network. The threshold nodes are set to -1.
- Use the following initial parameter values:

$$\begin{array}{lll} \theta_{01}^{(1)} = 2 & \theta_{02}^{(1)} = -1 & \theta_{01}^{(2)} = -2 \\ \theta_{11}^{(1)} = 6 & \theta_{12}^{(1)} = 8 & \theta_{11}^{(2)} = 6 \\ \theta_{21}^{(1)} = -6 & \theta_{22}^{(1)} = -8 & \theta_{21}^{(2)} = -6 \end{array}$$

- The learning rate is set to $\eta = 0.7$
 - Compute the activations of the hidden and output neurons.
 - Compute the error of the network.
 - Backpropagate the error to determine $\Delta\theta_{ij}$ for all weights θ_{ij} and updates the weight θ_{ij} .
2. What is the difference between “model bias” and “model variance”?
- Why is a high bias, low variance classifier undesirable?
 - Why is a low bias, high variance classifier (usually) undesirable?
3. Describe how validation set, and cross-validation can help reduce overfitting?