

INFO90002 FINAL ASSESSMENT PART 1


Student Name: Jiayi Li

Student ID: 1097419

Question 1:

Assumptions:

- The sending time is assumed to be in the working hours, set by hours from 9am to 17pm per day excluding weekend.



Question 2

```
CREATE TABLE Product
(Barcode INT,
Name VARCHAR(255),
ProductArea VARCHAR(50),
Price DECIMAL(7,2),
PRIMARY KEY (Barcode));
```

```
CREATE TABLE Customer
(Username VARCHAR(30),
FirstName VARCHAR(20),
LastName VARCHAR(30),
Email VARCHAR(255),
Phone VARCHAR(10),
Address VARCHAR(255),
PRIMARY KEY (Username));
```

```
CREATE TABLE Rates
(Barcode INT,
Username VARCHAR(30),
Rating TINYINT,
RatingDate DATE,
PRIMARY KEY (Barcode, Username),
FOREIGN KEY (Barcode) REFERENCES Product (Barcode),
FOREIGN KEY (Username) REFERENCES Customer (Username));
```

```
CREATE TABLE OrderItem
(Barcode INT,
ID INT,
Quantity TINYINT,
PRIMARY KEY (Barcode, ID),
FOREIGN KEY (Barcode) REFERENCES Product (Barcode),
FOREIGN KEY (ID) REFERENCES `Order`(ID));
```

```
CREATE TABLE `Order`  
(ID INT,  
  OrderDate DATE,  
  ContactName VARCHAR(20),  
  PaymentInformation VARCHAR(100),  
  DeliveryDate DATE,  
  TotalCost DECIMAL(10,2),  
  Username VARCHAR(30),  
PRIMARY KEY (ID),  
FOREIGN KEY (Username) REFERENCES Customer (Username));
```

Question 3

Q3A. List the game date, team name and all players who were selected for a team that eventually had to forfeit (walkover) in 2018?

```
SELECT GameDate, TeamName, FirstName, LastName
FROM game
INNER JOIN playerteam AS pt ON pt.GameID = game.GameID
INNER JOIN player AS p ON p.PlayerID = pt.PlayerID
INNER JOIN team ON pt.TeamID = team.TeamID
WHERE (Team1Score IS NULL OR Team2Score IS NULL)
AND YEAR(GameDate) = 2018;
```

	GameDate	TeamName	FirstName	LastName
►	2018-09-28	Moorabbin Seniors	Rupert	Hamer
	2018-09-28	Moorabbin Seniors	Alfred	Deakin
	2018-09-28	Moorabbin Seniors	Gareth	Evans
	2018-09-28	Moorabbin Seniors	Tim	Fischer
	2018-09-28	Moorabbin Seniors	Bill	Haydn
	2018-09-28	Monash Uni Seniors	Lance	Barnard
	2018-09-28	Monash Uni Seniors	Frank	Crean
	2018-09-28	Monash Uni Seniors	Alexander	Downer
	2018-09-28	Monash Uni Seniors	George	Reid
	2018-09-28	Monash Uni Seniors	Arthur	Fadden

10 rows returned

Q3B. How many points did the *Melbourne University Rugby Club* team score in each year of the *Dewar Shield* competition? List the team name, and cumulative score for each year. Order the result from the highest cumulative score to lowest.

```
SELECT SeasonYear, TeamName,  
       SUM(CASE WHEN Team1 = TeamID THEN Team1Score  
              ELSE Team2Score END) AS Points  
FROM game  
INNER JOIN team ON Team1 = TeamID OR Team2 = TeamID  
INNER JOIN club AS c ON c.ClubID = team.ClubID  
INNER JOIN season AS s ON s.SeasonID = game.SeasonID  
INNER JOIN competition AS comp ON comp.CompetitionID = s.CompetitionID  
WHERE ClubName = 'Melbourne University Rugby Club'  
AND CompetitionName = 'Dewar Shield'  
GROUP BY SeasonYear, TeamName  
ORDER BY Points DESC;
```

	SeasonYear	TeamName	Points
►	2016	Melbourne Uni Men	209
	2018	Melbourne Uni Men	155
	2014	Melbourne Uni Men	150
	2017	Melbourne Uni Men	136
	2015	Melbourne Uni Men	135
	2013	Melbourne Uni Men	102

6 rows returned

Q3C. *Elizabeth Blackburn* has played for three different clubs. How many games did she play for each club? List the club name and number of games.

```
SELECT ClubName, COUNT(DISTINCT GameID) AS NumberOfGames
FROM player AS p
INNER JOIN clubplayer AS cp ON p.PlayerID = cp.PlayerID
INNER JOIN club AS c ON cp.ClubID = c.ClubID
INNER JOIN playerteam AS pt ON p.PlayerID = pt.PlayerID
WHERE FirstName = 'Elizabeth' AND LastName = 'Blackburn'
GROUP BY ClubName
ORDER BY NumberOfGames DESC;
```

	ClubName	NumberOfGames
►	Melbourne City	37
	Melbourne University Rugby Club	37
	Powerhouse Rugby	37

3 rows returned

Q3D. List the teams and scores for all games played on 4th October 2015 at 10.00 a.m.

```
SELECT (CASE WHEN game.Team1 = t1.TeamID THEN t1.TeamName END)  
      AS Team1,  
      Team1Score,  
      (CASE WHEN game.Team2 = t2.TeamID THEN t2.TeamName END)  
      AS Team2,  
      Team2Score  
FROM game  
INNER JOIN team AS t1 ON game.Team1 = t1.TeamID  
INNER JOIN team AS t2 ON game.Team2 = t2.TeamID  
WHERE GameDate = '2015-10-04'  
AND StartTime = '10:00:00';
```

	Team1	Team1Score	Team2	Team2Score
►	Melbourne Uni Mixed	37	Melbourne City Mixed	7
	Powerhouse Mixed	20	Footscray Mixed	20
	Moorabbin Mixed	39	Monash Uni Mixed	0
	Geelong Rugby Mixeds	16	Harlequin Mixed	15

4 rows returned

Q3E. Write the **SQL** and two (2) versions of **Relational Algebra** for the following query:

List all team names of the *Geelong Rugby Club*

SELECT TeamName

FROM team **NATURAL JOIN** club

WHERE ClubName = 'Geelong Rugby Club';

	TeamName
▶	Geelong Rugby Mens
	Geelong Rugby Womens
	Geelong Rugby Mixeds
	Geelong Rugby Seniorss

4 rows returned

Version 1:

$\pi_{\text{TeamName}} (\sigma_{\text{ClubName} = \text{"Geelong Rugby Club"}} (\text{team} \bowtie \text{club}))$

Version 2:

$\pi_{\text{TeamName}} (\sigma_{\text{ClubName} = \text{"Geelong Rugby Club"}} (\text{club}) \bowtie \text{team})$

Question 4

- 1NF – no repeating groups – all atomic cells
- 2NF – to be in 2NF – there should be no partial functional dependencies

Venue, Class are the partial primary key

Date is the partial primary

Venue is the partial primary

Class is the partial primary

- ⇒ Capacity (**Venue, Class**, Capacity)
- ⇒ Date (**Date**, Day)
- ⇒ Venue (**Venue**, Address)
- ⇒ Class (**Class**, Weeks)
- ⇒ Pilates Class (**Date, Venue, Class**, Time, Trainer, Certificate)

Now, the tables are in the 2NF

- 3NF – to be in 3NF – there should be no transitive functional dependencies

Trainer is a non-key attribute

- ⇒ Capacity (**Venue, Class**, Capacity)
- ⇒ Date (**Date**, Day)
- ⇒ Venue (**Venue**, Address)
- ⇒ Class (**Class**, Weeks)
- ⇒ Trainer (**Trainer**, Certificate)
- ⇒ Pilates Class (**Date, Venue, Class**, Time, *Trainer*)

Now, the tables are in the 3NF

