GstarCAD development compatibility issues

1 Common misoperation in lisp transplanting

Other functions that the lisp program relies on are not loaded.

For example:

Sometimes, you receive a error prompt:

error: no function definition: XXXX. when you run a lisp program.

This error may be due to the program(lisp or grx) that contains this function is not loaded.

2 Include path

Due to the compatibility of ARX, some objects are repeatedly defined, which may lead to compilation problems. so you need priority includes the path grxsdk\inc\arx and contains the header file arxHeaders.h in stdafx.h

3 Tool Palette

Tool Palette implement is incompatible with AutoCAD. The simplest Tool Palette sample application is located at grxsdk\samples\SimplePalette.

4 The definition of the array is different

AcDbDynBlockReferencePropertyArray' elements are defined as objects of AcDbDynBlockReferenceProperty in ARX, but in GRX, OdDbDynBlockReferencePropertyArray' elements are defined as a point to object of OdDbDynBlockReferencePropertyPtr.

5 The object/entity operation in the transaction

```
void testTransction(const AcDbObjectId& id)
{
   AcTransaction *pTrans = acTransactionManagerPtr()->startTransaction();

   AcDbObject* pObj = NULL;
   if (pTrans->getObject((AcDbObject *&)pObj, id, AcDb::kForWrite) == Acad::eOk)
   {
      // In ARX the object can be closed or not, but in GRX, the object must not be closed.
      //pObj->close();
   }

   acTransactionManagerPtr()->endTransaction();
}
```

6 string allocated/free

Calls for acutNewString/acutDelString two functions to match.

The following are common misuse:

6.1

```
ACHAR *pStr = new ACHAR[100];
acutDelString(pStr);
```

6.2

```
ACHAR *pStr = NULL;
acutNewString(pStr, 100);
delete []pStr;
```

6.3

```
ACHAR *pStr = (ACHAR*)acad_malloc(100*size(ACHAR));
acutDelString(pStr);
```

6.4

```
ACHAR *pStr = NULL;
acutNewString(pStr, 100);
acad_free(pStr);
```

7. string free

In ARX develop documentation, some of the interfaces that return the string, i.e OdDbMText::contents().This function returns a pointer to a string containing content. The caller is responsible for freeing the returned string's memory by calling acutDelString().caller must not use acad_free or others.