


The sub miniature ECX-32 is a compact SMD Crystal. The 3.2 x 2.5 x 0.8 mm ceramic package is ideal for LoRa WAN, wireless, and high density applications.

ECX-32 SMD CRYSTAL

[Request a Sample](#)

ECX-32 SMD CRYSTAL



- Low Profile
- 3.2 x 2.5 mm Footprint
- Extended Temp. Range Option
- RoHS Compliant

DIMENSIONS (mm)




Figure 1) Top, Side, and Bottom

Crystal is symmetrical, pad 1 & 3 are interchangeable. Chamfer on the bottom can be on pad 4 or pad 1 and has no electrical significance.

Pad Connections

1	In/Out
2	Gnd
3	Out/In
4	Gnd

Equivalent Series Resistance

Frequency (MHz)	ESR Ω Max.
8.000 ~ 9.999	400
10.000 ~ 15.999	100
16.000 ~ 19.999	80
20.000 ~ 23.999	60
24.000 ~ 54.000	40




Figure 2) Suggested land

PART NUMBERING GUIDE: Example ECS-200-20-33-TR


ECS - FREQUENCY ABBREVIATION		LOAD CAPACITANCE	PACKAGE	AVAILABLE OPTIONS			PACKAGING
				Tolerance	Stability	Temp Range	
ECS	200 = 20.000 MHz See P/N Guide	20 = 20 pF S = Series	33 = ECX-32	Blank = Std A = ± 25 ppm J = ± 20 ppm R = ± 15 ppm C = ± 10 ppm	Blank= Std D= ±100 ppm E = ± 50 ppm G = ± 30 ppm H = ± 25 ppm T = ± 20 ppm + W = ±15 ppm + K = ± 10 ppm +	Blank= Std L = -10 ~ +70°C M = -20 ~ +70°C Y = -30 ~ +85°C N = -40 ~ +85°C P = -40 ~ +105°C S = -40 ~ +125°C U = -55 ~ +125°C	TR =1K TR3=3K Qty/Reel
* Specify available options in P/N.							
† Contact ECS for availability over extended temp range.							
				Rev.2021			

* Specify available options in P/N.

\dagger Contact ECS for availability over extended temp range.

Rev.2021

POCKET TAPE DIMENSIONS (mm)



A	B	C	D	F	J	L	M	Reel Dia.
3.5	2.8	8.0	3.5	4.0	1.1	0.25	1.0	180

SOLDER PROFILE

Peak solder Temp +260°C Max 10 sec Max.

2 Cycles Max.

MSL 1, Lead Finish Au




Figure 1) Suggested Reflow Profile

DEVELOPED FREQUENCIES

Abbreviation	Frequency (MHZ)
80	8.000
100	10.000
120	12.000
122.8	12.288
143	14.31818
147.4	14.7456
160	16.000
184	18.432
192	19.200
196	19.6608
200	20.000
240	24.000
245.7	24.576
250	25.000
260	26.000
270	27.000
300	30.000
320	32.000
360	36.000
400	40.000
480	48.000

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ECS:

[ECS-80-10-33-CHN-TR](#) [ECS-160-20-33-CKM-TR3](#) [ECS-160-20-33-TR3](#) [ECS-250-20-33-TR3](#) [ECS-250-18-33-JGN-TR3](#) [ECS-163.8-18-33-JGN-TR3](#) [ECS-80-18-33-JGN-TR3](#) [ECS-160-12-33-AGN-TR3](#) [ECS-160-20-33-AEN-TR3](#) [ECS-120-20-33-TR3](#) [ECS-240-20-33-TR3](#) [ECS-240-20-33-CKM-TR3](#) [ECS-240-8-33-AGN-TR3](#) [ECS-120-12-33-AGN-TR3](#) [ECS-80-12-33-JGN-TR3](#) [ECS-250-20-33-CKM-TR3](#) [ECS-250-20-33-JTN-TR3](#) [ECS-271.2-18-33-JGN-TR3](#) [ECS-120-18-33-AGN-TR3](#) [ECS-120-18-33-JGN-TR3](#) [ECS-240-18-33-JGN-TR3](#) [ECS-250-12-33-AGN-TR3](#) [ECS-250-8-33-JGN-TR3](#) [ECS-270-20-33-CKM-TR3](#) [ECS-120-18-33-JEM-TR3](#) [ECS-120-20-33-CKM-TR3](#) [ECS-120-8-33-JGN-TR3](#) [ECS-400-18-33-JGN-TR3](#) [ECS-80-10-33-CHN-TR3](#) [ECS-163.84-18-33-JGN-TR3](#) [ECS-100-12-33-JGN-TR3](#) [ECS-100-12-33Q-JES-TR](#) [ECS-100-8-33-JGN-TR3](#) [ECS-100-8-33Q-JES-TR](#) [ECS-80-10-33-CGN-TR3](#) [ECS-80-20-33-JEN-TR3](#) [ECS-80-8-33-JEN-TR3](#) [ECS-80-8-33-JGN-TR3](#) [ECS-163.8-18-33-JGN-TR3](#) [ECS-120-20-33-AGN-TR](#) [ECS-240-8-33-RTN-TR](#) [ECS-250-10-33-JGN-TR](#) [ECS-240-18-33-JEN-TR3](#) [ECS-80-10-33-CKM-TR3](#)