

Part III: Visualizations in R

TMA4268 Statistical Learning V2019. Module 1: INTRODUCTION TO STATISTICAL LEARNING

Martina Hall, Michail Spitieris, Stefanie Muff, Department of Mathematical Sciences, NTNU

January 06, 2020

Introduction

For each of the plots (scatter plot, histogram, boxplot, area chart, heat map, correlogram) *explain what you see (including what is on the x- and y-axis) and try to transform what you see into insight about the data.* All except the correlogram use `ggplot2` for plotting. If you want to read more about the idea behind `ggplot2` (grammar of graphics) Chapter 3 of [R for Data Science](#) is a good read. Other resources are:

<http://t-redactyl.io/blog/2016/03/creating-plots-in-r-using-ggplot2-part-9-function-plots.html>

<https://ggplot2.tidyverse.org/reference/>

Packages needed

```
install.packages("car")
install.packages("faraway")
install.packages("ggplot2")
install.packages("GGally")
install.packages("reshape")
install.packages("corrplot")
install.packages("corrgram")
```

Data sets


Three different data sets are used - read descriptions in R:

- SLID: `?car::SLID`
- mtcars: `?datasets::mtcars`
- ozone: `?faraway::ozone`

Scatter Plot


```
library(car)
library(ggplot2)
SLID = na.omit(SLID)
ggplot(SLID, aes(education, wages)) + geom_point() + labs(title = "Scatterplot") +
  theme_minimal()
```

Scatterplot




```
ggplot(SLID, aes(education, wages)) + geom_point(aes(color = language)) + scale_x_continuous("Education",  
  scale_y_continuous("Wages") + theme_bw() + labs(title = "Scatterplot") +  
  facet_wrap(~language) + theme_minimal()
```

Scatterplot




Histogram

```
ggplot(SLID, aes(wages)) + geom_histogram(binwidth = 2) + labs(title = "Histogram") +  
  theme_minimal()
```




Box-plot

```
ggplot(SLID, aes(language, wages)) + geom_boxplot(fill = "skyblue") + labs(title = "Box Plot") +  
  theme_minimal()
```




All pairs and different plots

```
library(GGally)
ggpairs(SLID) + theme_minimal()
```



Area chart


```
ages = cut(SLID$age, breaks = 3)
SLID2 = cbind(SLID, ages)
ggplot(SLID, aes(x = wages, fill = ages)) + geom_area(stat = "bin") + theme_minimal()
```



Heat map

```
library(reshape)
head(mtcars)
carsdf = data.frame(scale(mtcars))
carsdf$model = rownames(mtcars)
cars_melt = melt(carsdf, id.vars = "model")
ggplot(cars_melt, aes(x = variable, y = model)) + geom_raster(aes(fill = value)) +
  labs(title = "Heat Map") + scale_fill_continuous(name = "Value") + theme_minimal()
```

Heat Map



##		mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
##	Mazda RX4	21.0	6	160	110	3.90	2.620	16.46	0	1	4	4
##	Mazda RX4 Wag	21.0	6	160	110	3.90	2.875	17.02	0	1	4	4
##	Datsun 710	22.8	4	108	93	3.85	2.320	18.61	1	1	4	1
##	Hornet 4 Drive	21.4	6	258	110	3.08	3.215	19.44	1	0	3	1
##	Hornet Sportabout	18.7	8	360	175	3.15	3.440	17.02	0	0	3	2
##	Valiant	18.1	6	225	105	2.76	3.460	20.22	1	0	3	1

Acknowledgements

We thank Mette Langaas and her PhD students from 2018 and 2019 for building up the original version of this sheet.