

Part III: Visualizations in R

TMA4268 Statistical Learning V2019. Module 1: INTRODUCTION TO STATISTICAL LEARNING

Martina Hall, Michail Spitieris, Stefanie Muff, Department of Mathematical Sciences, NTNU

January 06, 2020

Contents

Introduction	1
Packages needed	1
Data sets	2
Scatter Plot	2
Histogram	3
Box-plot	4
All pairs and different plots	5
Area chart	6
Heat map	7
Acknowledgements	8

Introduction

For each of the plots (scatter plot, histogram, boxplot, area chart, heat map, correlogram) *explain what you see (including what is on the x- and y-axis) and try to transform what you see into insight about the data*. All except the correlogram use **ggplot2** for plotting. If you want to read more about the idea behind **ggplot2** (grammar of graphics) Chapter 3 of R for Data Science is a good read. Other resources are:

<http://t-redactyl.io/blog/2016/03/creating-plots-in-r-using-ggplot2-part-9-function-plots.html>, <https://ggplot2.tidyverse.org/reference/>

Packages needed

```
install.packages("car")
install.packages("faraway")
install.packages("ggplot2")
install.packages("GGally")
install.packages("reshape")
install.packages("corrplot")
install.packages("corrgram")
```


Data sets

Three different data sets are used - read descriptions in R:

- SLID: `?car::SLID`
- mtcars: `?datasets::mtcars`
- ozone: `?faraway::ozone`


Scatter Plot

```
library(car)
library(ggplot2)
SLID = na.omit(SLID)
ggplot(SLID, aes(education, wages)) + geom_point() + labs(title="Scatterplot") + theme_minimal()
```




```
ggplot(SLID, aes(education, wages)) + geom_point(aes(color = language)) +
  scale_x_continuous("Education") +
  scale_y_continuous("Wages") +
  theme_bw() + labs(title="Scatterplot") + facet_wrap(~ language) + theme_minimal()
```

Scatterplot




Histogram

```
ggplot(SLID, aes(wages))+geom_histogram(binwidth=2)+labs(title="Histogram")+theme_minimal()
```




Box-plot

```
ggplot(SLID, aes(language,wages ))+geom_boxplot(fill="skyblue")+labs(title="Box Plot")+theme_minimal()
```




All pairs and different plots

```
library(GGally)
ggpairs(SLID)+theme_minimal()
```



Area chart


```
ages = cut(SLID$age, breaks=3)
SLID2 = cbind(SLID, ages)
ggplot(SLID, aes(x=wages, fill=ages))+geom_area(stat="bin")+theme_minimal()
```



Heat map

```
library(reshape)
head(mtcars)
carsdf = data.frame(scale(mtcars))
carsdf$model = rownames(mtcars)
cars_melt = melt(carsdf, id.vars="model")
ggplot(cars_melt, aes(x = variable, y = model)) +
  geom_raster(aes(fill=value)) +
  labs(title="Heat Map") +
  scale_fill_continuous(name="Value") +
  theme_minimal()
```

Heat Map



##	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
## Mazda RX4	21.0	6	160	110	3.90	2.620	16.46	0	1	4	4
## Mazda RX4 Wag	21.0	6	160	110	3.90	2.875	17.02	0	1	4	4
## Datsun 710	22.8	4	108	93	3.85	2.320	18.61	1	1	4	1
## Hornet 4 Drive	21.4	6	258	110	3.08	3.215	19.44	1	0	3	1
## Hornet Sportabout	18.7	8	360	175	3.15	3.440	17.02	0	0	3	2
## Valiant	18.1	6	225	105	2.76	3.460	20.22	1	0	3	1

Acknowledgements

We thank Mette Langaas and her PhD students from 2018 and 2019 for building up the original version of this sheet.