Table of Contents

1	TITLE PAGE
2	MCU Main Signals
3	Bluetooth Low Energy
4	LCD Hot Bar Interface
5	USB Host and Device Interface
6	QSPI
7	RS232/485,CAN Interface
8	Ethernet Interface
9	Touch Sense Interface
10	PMOD Interface
11	Audio Amplifier
12	LEDs,Push Buttons
13	JTAG,J-Link On Board with RX621
14	SC32 MCU Breakout Pins
15	Arduino Shield
16	Power Supplies

Revision History

Rev. Code	Date	Description
V0.5	04/14/2015	Initial Draft
V0.6	05/14/2015	
	08/05/2015	- DNP the resistors:R20,R26,R28. - Place the resistors:R19,R22,R29. - Cut the tray from J3 pin 14 to U3 pin 10,Connect pin 14 of J3 to pin 2 of J14. - Cut the tray from J3 pin 17 to U3 pin 9,Connect pin 10 of U3 to pin 17 of J3. - Connect pin 9 of U3 to pin 18 of J3. - Changed U14 from RT9722BGB to AP2141DWG-7. - DNP the capacitor:C80,C81. - Changed the footprint of J17.
	08/10/2015	- Changed the RF unit oscillation circuit of U2.
	08/13/2015	- Changed the touch controller IC from XPT7603 to SX8656. - Changed the connections of LCD 4-wire SPI. - Changed the BLE power supply circuit.Add connectors to program RL78.
V3.0	12/10/2015	- Exchanged the RX and TX of Arduino connector(J27) with each other.

SK-S7G2

Embest	http://arm.embedinfo.com	
	Title: Title_Page	
Size: A3	Document Number: core	Rev: v3.0
Draw By: George	Date: Wednesday, January 06, 2016	Sheet: 1 of 16



http://arm.embedinfo.com		
Title: MCU Main Signals		
Size: A3	Document Number: core	Rev: v3.0
Draw By: George	Date: Wednesday, January 06, 2016	Sheet: 2 of 16

Bluetooth



Embest	http://arm.embedinfo.com	
Title: Bluetooth Low Energy		
Size: A4	Document Number: core	Rev: v3.0
Draw By: George	Date: Wednesday, January 06, 2016	Sheet: 3 of 16

LCD



http://arm.embedinfo.com		
Title: LCD Hot Bar Interface		
Size: A4	Document Number: core	Rev: v3.0
Draw By: George	Date: Wednesday, January 06, 2016	Sheet: 4 of 16

USB



Embest®	http://arm.embedinfo.com	
	Title: USB Host and Device Interface	
Size: A4	Document Number: core	Rev: v3.0
Draw By: George	Date: Wednesday, January 06, 2016	Sheet: 5 of 16

QSPI



http://arm.embedinfo.com		
Title: QSPI		
Size: A4	Document Number: core	Rev: v3.0
Draw By: George	Date: Wednesday, January 06, 2016	Sheet: 6 of 16

RS232/485,CAN



Embest	http://arm.embedinfo.com	
	Title: RS232/485,CAN Interface	
Size: A4	Document Number: core	Rev: v3.0
Draw By: George	Date: Wednesday, January 06, 2016	Sheet: 7 of 16

Ethernet



Layout NOTES:
1. The differential pair (TX+/- or RX+/-) should be routed away from all other signals and close together to use 5-mil trace width and 5-mil trace space in same length as possible with a 100ohm controlled trace.
2. Keep both traces of each differential pair as identical to each other as possible.
3. Route each differential pair on the same PCB layer.Avoid via and pad in the path.
4. Route both TX+/- and RX+/- pairs as far as away each other at least four times of 5-mil trace space.

http://arm.embedinfo.com		
Title: Ethernet Interface		
Size: A4	Document Number: core	Rev: v3.0
Draw By: George	Date: Wednesday, January 06, 2016	Sheet: 8 of 16

Touch

Layout NOTE:
The wiring between the electrode and the Touchsensor (TS) port should be the shortest length possible. It is recommended to separate the trace from noisy signal lines.

CAPACITIVE TOUCH BUTTONS



CAPACITIVE TOUCH SLIDER



clear Lexan covering mounting holes



Embest®	http://arm.embedinfo.com	
	Title: Touch Sense Interface	
Size: A4	Document Number: core	Rev: v3.0
Draw By: George	Date: Wednesday, January 06, 2016	Sheet: 9 of 16

PMOD



Embest®	http://arm.embedinfo.com	
	Title: PMOD Interface	
Size: A4	Document Number: core	Rev: v3.0
Draw By: George	Date: Wednesday, January 06, 2016	Sheet: 10 of 16

Audio



http://arm.embedinfo.com		
Title: Audio Amplifier		
Size: A4	Document Number: core	Rev: v3.0
Draw By: George	Date: Wednesday, January 06, 2016	Sheet: 11 of 16

LED,Push Button





Embest®	http://arm.embedinfo.com	
	Title: LEDs,Push Buttons	
Size: A4	Document Number: core	Rev: v3.0
Draw By: George	Date: Wednesday, January 06, 2016	Sheet: 12 of 16

J-link



Embest	http://arm.embedinfo.com	
	Title: JTAG,J-Link OB with RX621	
Size: A3	Document Number: core	Rev: v3.0
Draw By: George	Date: Wednesday, January 06, 2016	Sheet: 13 of 16

Breakout Pin









Layout Note: Place the text of each pin

Embest	http://arm.embedinfo.com	
	Title: SC32 MCU Breakout Pins	
Size: A4	Document Number: core	Rev: v3.0
Draw By: George	Date: Wednesday, January 06, 2016	Sheet: 14 of 16

Arduino



Embest	http://arm.embedinfo.com	
	Title: Arduino Shield	
Size: A4	Document Number: core	Rev: v3.0
Draw By: George	Date: Wednesday, January 06, 2016	Sheet: 15 of 16

Power





BLE Power Switch



Embest	http://arm.embedinfo.com	
Title: Power Supplies		
Size: A4	Document Number: core	Rev: v3.0
Draw By: George	Date: Wednesday, January 06, 2016	Sheet: 16 of 16