F04 Matrices, weighted sums and slope

Week 4, fourth teaching day. Complete ML12 first.

Today's question. How does a model turn two measurements into one prediction?

WHERE THIS IS USED

A model turns measurements into one number by giving each a weight, like a rent that grows with size and rooms. A ride fare grows with distance and time. Which input would you give the biggest weight when pricing a ride?

Words for today

Word	What it means	Think of it like this
matrix	A table of numbers with rows and columns.	A page of a register.
shape	Rows by columns.	How many lines and headings.
weight	A number that says how much an input counts.	How many points each goal is worth.
weighted sum	Multiply each input by its weight and add the results.	Adding up the points from every goal.
intercept	The starting amount before any input is added.	A fixed fee.
slope	How much the answer changes when one input rises by one unit.	Extra rent for each extra square metre.

Learn the idea

A matrix is a rectangular table of numbers, and its shape is rows by columns. In NumPy a 2-D array holds one home on each row: [[40, 2], [60, 3]] has two homes with two measurements each. A weighted sum multiplies each input by its weight and adds the results. np.dot does this for every row at once. In the invented rule rent = 100000 + 3000 * area + 20000 * rooms, 100000 is the intercept and 3000 and 20000 are weights. The slope for area is the change in rent for one extra square metre, with rooms held fixed. These numbers are supplied for teaching. A model later learns weights from examples.

Start on paper

Draw a table with two rows and the columns area and rooms. For [40, 2] calculate 3000 * 40 + 20000 * 2 = 160000, then add 100000 to get 260000. Raise the area by 1 with rooms fixed: the answer rises by 3000. Label the columns before you code.

Worked example

```
import numpy as np
homes = np.array([[40, 2], [60, 3]])
weights = np.array([3000, 20000])
intercept = 100000
print(homes.shape)
print(homes[0, 1])
predictions = intercept + np.dot(homes, weights)
print(predictions)
```

Run it, then compare: Line one: (2, 2), the shape of two rows and two columns. Line two: 2, the rooms of home 0. Line three: 260000 and 340000, the rents predicted for the two homes.

Your turn

Add the home [50, 2] as a third row. Predict its result on paper before you run. State the new shape and what each weight means. Explain why these numbers say nothing about real rents in Kampala. Save F04.ipynb.

Run all cells from the top, save, close and reopen. Show the instructor your output and explanation.