Your first model: baseline model, linear regression and prediction error

How can a computer predict winding temperature from motor load and air temperature, and how do we know it is any good?

CML3111 | Electrical, Mechatronics, Robotics and Communications | Week 8, class 1 of 4 | Friday 6 November 2026, 11:00 to 14:00

KLAi | International University of East Africa | Jotham Martin Wambi

Today in one view: what you will leave with

By the end of today you can



Explain features, target variable, baseline model and prediction error using the motor data




Say why some rows must be held out (validation set and test set) while a model trains



Train a linear regression model and a decision tree in Python and compare them with a baseline model

Your three hours: ideas first, then the lab



A short concepts section with pictures first. Then most of the time is the lab, with the notebook open.

Three questions from last time

1. What does data.shape tell you about a table?

2. Why do we clean a copy of the file and keep the original unchanged?

3. What is a missing value, and how does pandas show it?



Answer aloud first. Then we check together.

Answers to the three questions at the start of the class

Question	Short answer
What does data.shape tell you about a table?	It gives the number of rows and then the number of columns.
Why do we clean a copy of the file and keep the original unchanged?	So we can always go back to the raw data and check what we changed.
What is a missing value, and how does pandas show it?	It is an empty cell with no reading. pandas shows it as NaN.

Check each answer against your own. If one surprised you, look back at Weeks 1 to 7 before the lab.

Words we use today

	Word	What it means
	**Feature**	An input column (also called an input variable or predictor) that the model reads to make a prediction. Here: load_pct and ambient_c.
	**Target variable**	The column we want to predict. Here: motor winding temperature in deg C. When the target is a class such as yes or no, it is called a label. In Class 2 we make a yes or no label from the target.
	**Baseline model**	The simplest possible model, which every other model must beat. Here it predicts the mean of the training targets for every row.
	**Prediction error (residual)**	For one row: actual value minus predicted value. Later slides combine many errors into one score, the MAE or the RMSE.
	**Training set and validation set**	The training set is the rows the model learns from. The validation set is held-out data: rows kept back while the model trains, used to compare models fairly.

A prediction turns past readings into a number you can act on



Warn before a motor winding overheats



Plan maintenance before a failure, not after it




Choose the right cooling fan for a motor drive (the unit that powers the motor)

A glossary you will meet again in textbooks and documentation

Term	What it means in plain words
Linear regression	Predicts the target as an intercept plus weighted features. Simple (also called univariate): one feature. Multiple: two or more features. Multivariate regression means several targets, a different thing.
MAE, MSE and RMSE	Three scores that sum up many prediction errors, in the unit of the target (MSE: unit squared).
Missing value and imputation	A missing value is an empty cell (NaN). Imputation fills it, for example with the median.
Parameters and hyperparameter	Parameters (intercept, coefficients) are learned. A hyperparameter, such as max_depth, is chosen before training.
Pipeline	Chains preprocessing and a model, and runs them in order.

Each term is explained again where it first matters.

Machine learning finds the rule from examples, so nobody writes it by hand



A model is the rule the computer found.

We do not write the rule ourselves. The computer finds it from the examples.

Every example row must include its answer, which we call the target variable.

Every row is one reading: the inputs are features and the answer is the target variable

file row	record_id	equipment_id	load_pct	ambient_c	target
1	1	E1	59.15	31.71	76.85
2	2	E2	77.46	29.97	87.05
3	3	E3	69.6	19.87	71.26
5	5	E5	57.62	23.4	67.03

The model reads the features and predicts the target variable (yellow): motor winding temperature in deg C.

Features (input variables): load_pct (percent of full load) and ambient_c (deg C).

record_id and equipment_id only label the row.

Record 4 is left out: its target is a missing value (NaN).

Before we model, we remove the rows we cannot trust

file row	record_id	equipment_id	load_pct	ambient_c	target
1	1	E1	59.15	31.71	76.85
4	4	E4	75.98	22.29	NaN
9	9	E3	-5	21.57	86.47
91	1	E1	59.15	31.71	76.85

Our file has 91 rows. Three kinds of row cannot be used.

record_id 1 is in row 1 and again in the last row, row 91 (yellow). Keep the first.

record_id 4 has a missing target (NaN): nothing to learn from.

record_id 9 has load_pct -5: impossible.

Hold out rows while the model trains, so the evaluation is fair



Training set: the model learns from these rows.

Validation set: we compare models here.


Test set: held out until the end.

After cleaning, 88 rows remain. We cut them into three sets by equipment group.

Held-out data are rows not used to fit the model: the validation and test sets.


Each equipment group goes into one set only.

Imputation fills a missing value with the training median of its column



Training medians: 62.8 percent (load_pct) and 26.1 deg C (ambient_c). Record 14 (group E2) has no ambient_c, so it gets 26.1. This is imputation (SimpleImputer).

The baseline model comes first: predict the mean of the training targets every time



Each dot is one training row. The dashed line is the baseline model: it predicts 71.03 deg C for every row.

A baseline model is the simplest possible model: it predicts the mean of the training targets and ignores the features.

Every other model must beat it. If it cannot, it has learned nothing useful.

The baseline model adds the 58 training targets and divides by 58: 71.03 deg C

Baseline model

$$\hat{y} = \bar{y} = \frac{1}{n} \sum_{i=1}^{n} y_i$$


Our data

$$\hat{y} = 71.03 \text{ deg C}$$

Symbol	What it means	In our data
y-hat and y-bar	The prediction, which is the mean of the y_i.	71.03 deg C
y_i	The actual target of training row i.	column target, in deg C
n	How many training rows there are.	58 rows (E1 to E4)
sum, i = 1 to n	Add up the values from row 1 to row n.	all training rows

We add the 58 training targets and divide by 58. The validation set plays no part.

Simple linear regression fits a line through the dots and beats the baseline model



Simple (univariate) linear regression: one feature, load_pct. Each extra 1 percent of load adds 0.67 deg C.

At zero load it starts at 31.2 deg C (the intercept).

It predicts the target as an intercept plus a weighted feature.

On the validation set its MAE is 4.30 deg C.

Simple linear regression has two learned numbers: at 60 percent load it predicts 71.13 deg C

Simple linear regression

$$\hat{y} = b_0 + b_1 x$$


Our fitted model

$$\hat{y} = 31.17 + 0.666 x$$

Symbol	What it means	In our data
y-hat	The predicted target.	motor winding temperature, in deg C
x	The feature of the row. Here the load alone.	column load_pct, in percent
b0	The intercept (bias): the prediction when x is 0.	31.17 deg C
b1	The slope, or coefficient (weight): how much the prediction grows when x grows by 1.	0.666 deg C per percent of load

Example: at load_pct = 60 the prediction is 31.17 + 0.666 × 60 = 71.13 deg C.

The prediction error (residual) is the actual value minus the predicted value



Prediction error (residual) = actual value minus predicted value, for one row. The line is simple linear regression.

Each red segment joins a dot (actual) to the line (predicted). Its length is the error size.

Positive error: the model predicted too low.

A good model leaves short segments.

e = y minus y-hat: for record 5 the baseline model is off by -4.00 deg C

Prediction error of row i

$$e_i = y_i - \hat{y}_i$$

One row of ours

$$e = 67.03 - 71.03 = -4.00 \text{ deg C}$$

Symbol	What it means	In our data
e_i	The prediction error (residual) of row i. Negative means the prediction was too high.	in deg C
y_i	The actual target of row i.	column target, in deg C
y-hat_i	The prediction for row i.	baseline model: 71.03 deg C
i and n	The row number i runs from 1 up to n, the number of rows.	one row at a time

Our row: record_id 5, load_pct 57.62, ambient_c 23.4. Predicted too high by 4.00 deg C, from the values shown.

Worked example with hypothetical numbers: four prediction errors give MAE 2.75 and RMSE 3.5

Reading	Actual	Predicted	Error e	Absolute error |e|	Squared error e × e
1	70	72	-2	2	4
2	80	77	+3	3	9
3	90	90	0	0	0
4	60	66	-6	6	36

MAE = (2 + 3 + 0 + 6) / 4 = 2.75. MSE = (4 + 9 + 0 + 36) / 4 = 12.25. RMSE = square root of 12.25 = 3.5. These four readings are hypothetical (made up, with no unit) to show the arithmetic.

Three ways to turn many errors into one number: MAE, MSE and RMSE

MAE

$$\text{MAE} = \frac{1}{n}\sum_{i=1}^{n}|e_i|$$

MSE and RMSE

$$\text{MSE} = \frac{1}{n}\sum_{i=1}^{n}e_i^2 \qquad \text{RMSE} = \sqrt{\text{MSE}}$$

Symbol	What it means	In our data
n	How many rows we score.	15 validation rows
|e_i| and e_i squared	The error with its sign removed, and the error multiplied by itself.	deg C and deg C squared
sum	Add the values for rows 1 to n.	all validation rows

MAE and RMSE are in the unit of the target. MSE is in the unit squared. Lower is better.

Our own validation rows: the baseline model and simple linear regression

record_id	load_pct	ambient_c	Actual	Baseline	Error	Linear	Error
5	57.62	23.4	67.03	71.03	-4.00	69.52	-2.49
11	26.14	33.98	53.36	71.03	-17.67	48.57	+4.79
17	61.76	34.28	80.29	71.03	+9.26	72.28	+8.01
23	20.73	30.81	47.95	71.03	-23.08	44.97	+2.98

Values in deg C. Linear = simple linear regression (load_pct only). Errors use the rounded values shown. Absolute errors over 15 rows add up to 222.8 (baseline, MAE = 222.8 / 15 = 14.85) and 64.4 (linear, MAE = 4.30).

MAE and RMSE both measure prediction error in the target's own unit

MAE

The mean of the absolute errors

Every error counts by its size

Easy to explain to a client

RMSE


Squares the errors, takes the mean, then the root

One large error counts for much more

Use it when large errors are costly

Both are in deg C: "the model is off by about this many deg C".

Gradient descent trains a model by walking downhill on the loss, one small step at a time



Training starts with a poor model and improves its parameters (here the slope) by repeating small steps.

Loss function: how wrong the model is, as one number (here the MSE).

Gradient: the slope of the loss. It shows which way is downhill.

Learning rate: the size of each step.

Gradient descent, part 1: the loss L is the MSE, and dL/dw is its slope

Loss (MSE)

$$L = \frac{1}{n}\sum_{i=1}^{n}(w\,x_i - y_i)^2 = \frac{1}{n}\sum_{i=1}^{n} e_i^2$$

Slope of the loss

$$\frac{dL}{dw} = \frac{2}{n}\sum_{i=1}^{n} x_i\,(w\,x_i - y_i)$$

Symbol	What it means	In our data
L	The loss: the MSE of the model y-hat = w x over n rows (x_i, y_i).	illustrative: x = 1, 2, 3; y = 2, 4, 6; n = 3
w	The slope parameter (no intercept, to keep it small).	stands in for b1
e_i	Residual y_i minus w x_i. Squaring removes the sign, so both forms of L match.	as before
dL/dw	How fast L changes when w changes.	at w = 0 it is -18.67

A negative slope: a bigger w lowers the loss.

Gradient descent, part 2: change w a little, downhill

Update rule

$$w \leftarrow w - \eta \cdot \frac{dL}{dw}$$

Symbol	What it means	In our data
w	The parameter (slope) we are improving. It starts at 0.	the tiny example
arrow	Replace the old w by the new value on the right.	one update per step
dL/dw	The slope of the loss from the last slide.	at w = 0 it is -18.67
eta	The learning rate: the size of each step.	0.05
LinearRegression	Skips these steps: it finds b0, b1 and b2 at once with a direct formula (least squares). Logistic regression (Class 2) and neural networks learn by gradient descent.	the lab model

Repeat: new w = old w minus the learning rate times the slope of the loss.

On a tiny illustrative example, five steps almost reach the best slope

Step	w after the step	Loss after the step
0 (start)	0	18.667
1	0.933	5.310
2	1.431	1.510
3	1.697	0.430
4	1.838	0.122
5	1.914	0.035

Illustrative (hypothetical) data: x = 1, 2, 3 and y = 2, 4, 6, so the best w is 2. Step 1 by hand: dL/dw = (2/3) × (1 × (0 − 2) + 2 × (0 − 4) + 3 × (0 − 6)) = -18.67. New w = 0 − 0.05 × (-18.67) = 0.933.

Multiple linear regression has three learned parameters: b0, b1 and b2

Regression function $$\hat{y} = b_0 + b_1 x_1 + b_2 x_2$$

Our learned parameters $$\hat{y} = 1.66 + 0.695\, x_1 + 1.054\, x_2$$

Symbol	What it means	In our data
y-hat	The predicted target.	motor winding temperature, in deg C
x1, x2	The two features (input variables) of a row.	x1 = load_pct (percent), x2 = ambient_c (deg C)
b0	The intercept (bias): the prediction if both features were 0. Nothing runs at 0 percent load in 0 deg C air, so it is only an anchor.	1.66 deg C
b1, b2	The coefficients (weights) of x1 and x2.	b1 = 0.695 deg C per percent; b2 = 1.054 deg C per deg C


LinearRegression finds b0, b1 and b2 with the direct least-squares formula (no gradient descent).

What one more unit of a feature does to the prediction

Case	load_pct (percent)	ambient_c (deg C)	Prediction (deg C)	Change
Start	60	25	69.71	
load_pct up by 1	61	25	70.40	+0.695
ambient_c up by 1	60	26	70.76	+1.054
Both up by 1	61	26	71.46	+1.749

This is multiple linear regression. Its coefficient for load_pct is not the same as the 0.666 of simple linear regression, because now the two features share the work. The start values 60 and 25 are chosen for the example.

A decision tree learns a short list of yes or no questions about the features




A row follows yes or no answers down to one yellow box, a leaf node. That leaf gives the prediction.

Each question is an internal node: a split on a feature and a threshold. The top one asks: is load_pct at most 42.9?

The prediction is the mean target of the training rows in that leaf node.

max_depth is the largest number of questions a row can be asked




max_depth is a hyperparameter: a setting we choose before training. It limits how many questions a row meets.

This tree has max_depth 1. The tree on the previous slide had max_depth 2.

Deeper trees can overfit (fit noise): Class 3. The lab uses max_depth 4 and random_state=17, so ties break the same way for all.

Model comparison: three models evaluated on the same validation set




Multiple linear regression has a validation MAE of 0.78 deg C. The baseline model has 14.85 deg C.

Simple linear regression (load_pct only, not shown) scored 4.30 deg C.

The lab also plots actual against predicted: a point on the dashed diagonal is a perfect prediction.

A pipeline is one container that holds the imputer and the model, and runs them in order



The gold frame is the pipeline: fit learns the medians, then the model; predict fills, then predicts.

Read the workflow before you write it: create, fit, predict, score

```
imputer = SimpleImputer(strategy="median")
linear_model = make_pipeline(
    imputer, LinearRegression())
linear_model.fit(X_train, y_train)
y_pred = linear_model.predict(X_valid)
mae = mean_absolute_error(y_valid, y_pred)
```

In plain words

Line 1: an imputer fills missing values.

Lines 2 and 3: a pipeline: imputer, then linear regression.

Line 4, fit (training) on X (features) and y (target): learns the median, then b0, b1, b2.


Lines 5 and 6: predict (inference), then score by the MAE.

Baseline and tree: swap in DummyRegressor or DecisionTreeRegressor.

Part 2: the lab

Close the slides and open the lab notebook. Use the slides "Check your numbers" and "Four errors you will meet" at the end of this deck.

The lab has five stages, and the notebook numbers its steps 0 to 8



In every step: predict first, run the cell, read the output, then change one thing.

Check your numbers against these before you move on

What the notebook prints	You should see
Rows: raw file (5 columns), after removing the repeated record_id, after removing the 3 bad rows	91, 90, 88
Training, validation and test rows	58, 15, 15
Baseline model: MAE on the validation set	14.85 deg C
Simple linear regression (load_pct only): MAE (Step 5 CHANGE)	4.30 deg C
Multiple linear regression: MAE	0.78 deg C
Multiple linear regression: b0, b1 (load_pct), b2 (ambient_c)	1.662, 0.695, 1.054
Decision tree, max_depth 4: MAE	4.79 deg C
RMSE: baseline, multiple linear regression, tree	16.93, 0.92, 6.29 deg C

If your number differs, stop and ask. Do not change a number to match. Find the step that went wrong.

Four errors you will meet, what they mean and what to do

	Error message	What it says	What to do
	**FileNotFoundError**	The CSV is not beside the notebook	Upload engineering_data.csv in the Files panel
	**KeyError: target**	The code uses a column name that is not in the table, often a spelling difference	Print data.columns and copy the name exactly
	**NameError**	The code uses a name from a cell that has not been run yet	Run all cells from the top, in order
	**ValueError: contains NaN**	A missing value (an empty feature cell) reached the model	Fit the model inside the imputer pipeline, as in Step 5

How this class counts towards your coursework



Nothing is submitted today. Block 1 is Classes 1 and 2. Its assignment has two parts: A7 (regression) and A8 (classification).



Block work is practice: it is collected and you get feedback, but it does not count toward your final mark.



The Block 1 assignment closes on Friday 20 November, 11:00 (Kampala time).



The Block 1 quiz opens in the last 20 minutes of Class 2 and stays open for 24 hours.



Keep your saved notebook: Class 2 reuses its cleaning steps.

Save the notebook and keep your three MAE scores

What you keep from today

Keep your lab notebook, saved after you restart the session and run all cells in order. Keep your three MAE numbers from the model comparison table: the baseline model, the multiple linear regression model and the decision tree.

Our question today

How can a computer predict winding temperature from motor load and air temperature, and how do we know it is any good?

Next class

Class 2: classification, where the model answers yes or no.

Take away

Saved notebook
Restart, run all, save

Model comparison
MAE of the three models

Next class
Classification

Bring
Laptop with the saved lab file