KLAi

Backpropagation by hand: the chain rule, run backwards through a tiny network

What happens in every training step of a language model, and why does training cost far more computing than answering a question?

Mathematics for AI and Machine Learning | Session 11 of 18 | Calculus and optimisation

KLAi Professional Learning | Jotham Martin Wambi

Today in one view: what you will leave with

By the end of today you can



Compute the forward pass and the loss of a tiny network, with every number written out




Derive the slopes of the sigmoid and tanh, then compute every gradient in the backward pass, apply the update, and see the loss fall



Write the same computation with the matrices W, b and delta, and check the gradients with finite differences in code

Your two hours: one network, forward then backward



Pictures and hand calculations first. Then the lab: numpy, or cells in the spreadsheet.

Three questions from last time

1. With eta = 0.1, old w = 2 and a slope of 5, what is the new w?

2. The loss grows at every step of gradient descent. What is the most likely cause?

3. What does Adam add to plain gradient descent?

Answer aloud first. Then we check together.

Answers to the three questions from Session 10


Question	Short answer
With eta = 0.1, old w = 2 and a slope of 5, what is the new w?	New w = 2 - 0.1 × 5 = 1.5.
The loss grows at every step of gradient descent. What is the most likely cause?	The learning rate is too large, so each step overshoots the bottom. Divide it by 3 or 10.
What does Adam add to plain gradient descent?	A running average of past gradients, and a separate step size for each parameter based on the typical size of its gradient.

Check your answers. If one surprised you, look at Session 10 before the lab.

Words we use today

	Word	What it means
	**Forward pass**	Computing the output and the loss from the inputs, layer by layer.
	**Backward pass**	Computing the gradient of the loss for every parameter, from the output back to the input.
	**Backpropagation**	The backward pass that applies the chain rule from the loss back to every parameter, reusing the values stored in the forward pass.
	**Delta**	The gradient of the loss with respect to the input of a unit, written with the Greek letter delta.
	**Sigmoid and tanh**	Sigmoid 1 / (1 + e^-z) squeezes any number into 0 to 1; tanh squeezes it into −1 to 1.

A tiny network: 2 inputs, 2 hidden units with a sigmoid, and 1 output



The numbers on the lines are the weights.

Nine numbers can change: 6 weights and 3 biases.

A hidden unit adds its weighted inputs and bias, then applies the sigmoid.

The output unit adds its weighted inputs and its bias and applies no sigmoid. The target is y = 1.0.

Every number we start with: the inputs, the target and the nine parameters

Name	Meaning	Value
x	The two inputs of the example	1.0 and 2.0
y	The target (the answer we want)	1.0
W(1)	Weights into the hidden units (layer 1): one row per hidden unit	(0.2, −0.3) and (0.4, 0.1)
b(1)	Biases of the two hidden units	0.1 and −0.2
W(2)	Weights into the output unit (layer 2)	0.5 and −0.4
b(2)	Bias of the output unit	0.2
eta	The learning rate	0.5

These are illustrative numbers, chosen small and simple. Results are rounded to 4 decimals on the slides; the computer keeps full precision.

The forward pass: weighted sum, sigmoid, weighted sum, then the loss

Hidden unit j

$$z_j^{(1)} = W_{j1}^{(1)} x_1 + W_{j2}^{(1)} x_2 + b_j^{(1)} \qquad a_j^{(1)} = \sigma(z_j^{(1)}) = \frac{1}{1 + e^{-z_j^{(1)}}}$$

Output


$$\hat{y} = W_1^{(2)} a_1^{(1)} + W_2^{(2)} a_2^{(1)} + b^{(2)}$$

Loss

$$L = \frac{1}{2}(\hat{y} - y)^2$$

Symbol	What it means	In our data
x_i, y; σ	Inputs and target. σ is the sigmoid 1 / (1 + e^-z), between 0 and 1.	x = (1, 2), y = 1
z(1)_j, a(1)_j	Input of hidden unit j and its output after the sigmoid.	j = 1, 2
W(1), b(1), W(2), b(2)	Weights and biases of layer 1 and of the output. W(1)_ji: input i to unit j.	the starting table
y-hat, L	Prediction; loss = half the squared error (Session 10: same minimum as MSE).	one number each

The forward pass with our numbers: the loss is 0.3417



L = 0.5 × (0.1733 - 1.0)^2 = 0.3417

The prediction is 0.1733, far from the target 1.0.


z is the weighted sum in a hidden unit; a is its sigmoid.

The loss is large, so the gradients will push the weights hard.

The forward pass, one calculation at a time

Quantity	Calculation	Value
z(1)_1	$0.2 \times 1.0 + (-0.3) \times 2.0 + 0.1$	−0.3000
a(1)_1 = sigmoid(z(1)_1)	1 / (1 + e^(0.3000))	0.4256
z(1)_2	$0.4 \times 1.0 + 0.1 \times 2.0 + (-0.2)$	0.4000
a(1)_2 = sigmoid(z(1)_2)	1 / (1 + e^(−0.4000))	0.5987
y-hat	$0.5 \times 0.4256 + (-0.4) \times 0.5987 + 0.2$	0.1733
L	0.5 × (0.1733 - 1.0)^2	0.3417

The sigmoid squeezes into 0 to 1 and tanh into minus 1 to 1; both are steepest at z = 0



Black: the function. Red dashed: its slope (at most 0.25 for the sigmoid, 1 for tanh).

The slope of the sigmoid, derived step by step, is a times (1 minus a)

Write it as a power

$$a = \sigma(z) = (1 + e^{-z})^{-1}$$

Chain rule (Session 9)

$$\frac{da}{dz} = -(1 + e^{-z})^{-2} \cdot (-e^{-z}) = \frac{e^{-z}}{(1 + e^{-z})^2}$$

Split into two factors

$$\frac{da}{dz} = \frac{1}{1 + e^{-z}} \cdot \frac{e^{-z}}{1 + e^{-z}} = a\,(1 - a)$$

Symbol	What it means	In our data
Outer and inner	Outer: u to the power −1 has slope -u^-2. Inner: u = 1 + e^-z has slope -e^-z (Session 7).	multiply the two
Second factor	e^-z / (1 + e^-z) = 1 - 1 / (1 + e^-z) = 1 - a.	a + (1 - a) = 1
Largest slope	At z = 0, a = 0.5, so a(1 - a) = 0.25. Elsewhere it is smaller.	0.5 × 0.5 = 0.25
Check on our unit 1	z = −0.3: a = 0.4256, slope = 0.4256 × 0.5744.	0.2445

Tanh is a stretched sigmoid, and its slope is 1 minus h squared

Definition


$$h = \tanh(z) = \frac{e^{z} - e^{-z}}{e^{z} + e^{-z}} = 2\,\sigma(2z) - 1$$

Slope

$$\frac{dh}{dz} = 4\,\sigma(2z)(1 - \sigma(2z)) = 4 \cdot \frac{1+h}{2} \cdot \frac{1-h}{2} = 1 - h^{2}$$

Symbol	What it means	In our data
h	The output of tanh, between −1 and 1.	tanh(0.5) = 0.4621
2 σ(2z) minus 1	Tanh is the sigmoid of 2z, stretched by 2 and moved down by 1.	2 × σ(1) - 1 = 0.4621
Slope steps	Chain rule: the inner 2z gives a factor 2, the outer stretch another 2. Then σ(2z) = (1 + h) / 2 and 1 - σ(2z) = (1 - h) / 2.	2 × 2 = 4
1 minus h^2	The slope of tanh. It is 1 at z = 0 and falls towards 0 at the edges.	1 - 0.4621^2 = 0.7864

The backward pass multiplies local slopes along each path from the loss back to a weight



Chain rule from Session 9: the slope for a weight is the product of the slopes along the path.

At the output layer, delta(2) is the prediction minus the target


Quantity	Calculation	Value
delta(2) = dL/d(y-hat)	0.1733 - 1.0	−0.8267
dL/dW(2)_1 (first weight)	delta(2) × a(1)_1 = (−0.8267) × 0.4256	−0.3518
dL/dW(2)_2 (second weight)	delta(2) × a(1)_2 = (−0.8267) × 0.5987	−0.4949
dL/db(2)	delta(2) × 1	−0.8267

delta(2) is the gradient of the loss with respect to the output y-hat. Negative values mean: raise this parameter to lower the loss.

In the hidden layer, each delta picks up the sigmoid slope a times (1 minus a)

Quantity	Calculation	Value
dL/da(1)_1	W(2)_1 × delta(2) = 0.5 × (−0.8267)	−0.4133
delta(1)_1	(−0.4133) × a(1)_1 × (1 - a(1)_1) = (−0.4133) × 0.2445	−0.1010
dL/da(1)_2	W(2)_2 × delta(2) = (−0.4) × (−0.8267)	0.3307
delta(1)_2	0.3307 × a(1)_2 × (1 - a(1)_2) = 0.3307 × 0.2403	0.0794
dL/dW(1) (row 1)	delta(1)_1 × inputs = (−0.1010) × (1.0, 2.0)	−0.1010, −0.2021
dL/dW(1) (row 2)	delta(1)_2 × inputs = 0.0794 × (1.0, 2.0)	0.0794, 0.1589
dL/db(1)	the two values of delta(1)	−0.1010, 0.0794

All nine gradients, drawn on the network



Red numbers: dL/d(weight). Boxes: delta. Bias gradients equal the deltas.

Each red number is the slope of the loss for that weight: the change in loss per unit change in the weight, for a tiny step.

Negative gradient: raise that weight to lower the loss.

The output layer has the largest gradients.


The update: every parameter moves by minus eta times its gradient, with eta = 0.5

Parameter	Old value	Gradient	New value = old minus 0.5 × gradient
W(1) row 1, input 1	0.2000	−0.1010	0.2505
W(1) row 1, input 2	−0.3000	−0.2021	−0.1990
W(1) row 2, input 1	0.4000	0.0794	0.3603
W(1) row 2, input 2	0.1000	0.1589	0.0206
b(1) unit 1	0.1000	−0.1010	0.1505
b(1) unit 2	−0.2000	0.0794	−0.2397
W(2), hidden 1	0.5000	−0.3518	0.6759
W(2), hidden 2	−0.4000	−0.4949	−0.1525
b(2)	0.2000	−0.8267	0.6133

After one update the loss falls from 0.3417 to 0.0085

98%

of the loss is gone after a single step (rounded to the nearest percent). The new prediction is 0.8694, close to the target 1.0.



of the loss removed

Source: Computed from the illustrative network of this session. A second step brings the loss to 0.0002.

In matrix form the same computation uses W, b and delta

Output layer

$$\delta^{(2)} = \hat{y} - y \qquad \frac{\partial L}{\partial W^{(2)}} = \delta^{(2)} a^{(1)T} \qquad \frac{\partial L}{\partial b^{(2)}} = \delta^{(2)}$$

Hidden delta

$$\delta^{(1)} = (W^{(2)T}\delta^{(2)}) \odot a^{(1)} \odot (1 - a^{(1)})$$


Hidden gradients

$$\frac{\partial L}{\partial W^{(1)}} = \delta^{(1)} x^{T} \qquad \frac{\partial L}{\partial b^{(1)}} = \delta^{(1)}$$


Symbol	What it means	In our data
delta(2), delta(1)	The deltas of the output layer and of the hidden layer.	−0.8267; (−0.1010, 0.0794)
T and ⊙	T: transpose (rows become columns). ⊙: multiply entry by entry (Hadamard product).	W(2)^T is 2 × 1
∂L/∂W	Gradient of the loss L with respect to W: one slope per weight, shaped like W.	∂L/∂W(1) is 2 × 2

The forward pass stores every value, and the backward pass reuses them

Forward pass: left to right, and store every value



Backward pass: right to left, reusing the stored values




Top: forward pass with the shape of each value. Bottom: backward pass. Gold boxes are the deltas.

Shapes in the matrix form: check them before you code

Object	Shape	Why
x, z(1), a(1)	2 × 1	Two inputs, two hidden units
W(1)	2 × 2	One row per hidden unit, one column per input
W(2)	1 × 2	One output, two hidden units
delta(2) and y-hat	1 × 1	One output
delta(1)	2 × 1	One per hidden unit
∂L/∂W(2) = delta(2) a(1)^T	(1 × 1)(1 × 2) = 1 × 2	Same shape as W(2)
∂L/∂W(1) = delta(1) x^T	(2 × 1)(1 × 2) = 2 × 2	Same shape as W(1)

Rule: the gradient of a parameter always has the same shape as the parameter. For a batch of n examples the gradients are averaged over the n rows.

Check a gradient with finite differences: nudge one weight and watch the loss



A finite difference estimates a slope from two nearby values of the loss.

Nudge one weight by +h and -h. Keep all others fixed.

The red slope should match backpropagation. The check is slow, so it is only a test.

The central finite difference, checked on one weight of our network

Central difference

$$\frac{\partial L}{\partial w} \approx \frac{L(w+h) - L(w-h)}{2h}$$

Symbol	What it means	In our data
w	The first weight of the first layer, W(1) row 1, input 1.	0.2
h	A tiny nudge.	0.00001
Finite difference	The estimate from the formula.	−0.1010 463 936
Backpropagation	The gradient from the backward pass.	−0.1010 463 936
Difference	The two estimates agree to about 10 decimals.	3.5e-12

Relative difference = |a - b| / max(|a|, |b|), here 3e-11. Below about 1e-6 is a good sign.

Four slips in backpropagation, and the symptom each one leaves

Mistake	What you see	Fix
Update the weights before all gradients are computed	The gradients of earlier layers are wrong	Compute all gradients first, then update everything
Forget the sigmoid slope a × (1 minus a)	Hidden gradients are too large and fail the finite-difference check	Multiply by a × (1 - a) entry by entry
A missing transpose	A shape error in numpy, or a result of the wrong shape	The gradient has the shape of its parameter
A sign error in delta(2)	The loss goes up after the update	delta(2) = y-hat - y, and the update subtracts

Read the training step before you write it: forward, backward, update

```
z1 = W1 @ x + b1
a1 = 1 / (1 + np.exp(-z1))
yhat = W2 @ a1 + b2
d2 = yhat - y
d1 = (W2.T @ d2) * a1 * (1 - a1)
W2 = W2 - eta * np.outer(d2, a1)
W1 = W1 - eta * np.outer(d1, x)
```

In plain words

In code, z1, a1, W1 and b1 stand for z(1), a(1), W(1) and b(1); d2 and d1 stand for delta(2) and delta(1).

The first three lines are the forward pass; d2 and d1 are the backward pass.

np.outer(a, b) is a times b-transposed.


The last lines are the update. The biases follow the same pattern.

KLAI

Part 2: the lab

Close the slides. Open the notebook or the workbook.

Six lab steps: one training step by hand, a proof, then fifty more steps



The notebook has the same six steps. Predict first, run, read, then change one thing.

Every lab number to four decimals, from the forward pass to the second update


What you compute	You should see
z(1) (both hidden units)	−0.3000 and 0.4000
a(1) (both hidden units)	0.4256 and 0.5987
Prediction y-hat, loss L	0.1733, 0.3417
delta(2), then delta(1) (two values)	−0.8267; −0.1010 and 0.0794
Gradient of W(1) row 1 (two values)	−0.1010 and −0.2021
New W(1) row 1 after the update	0.2505 and −0.1990
Loss after one update, after two	0.0085 and 0.0002

If your number differs, find the step that went wrong. Do not change a number to match.

When the lab complains: four messages and what each one means

What you see	What it means	What to do
ValueError: shapes not aligned	A matrix product has the wrong shape	Print the shapes. The gradient has the shape of its parameter
Finite-difference check shows a large difference	One gradient formula is wrong	Compare parameter by parameter to find which one
The loss goes up after the update	A sign error, or eta is too large	delta(2) = y-hat - y; update is minus eta × gradient
NameError	A cell that defines a name was not run	Run all cells from the top

Where this appears in AI: every training step is a forward pass, a loss and a backward pass




The loop you did by hand is the loop used for large models.

Published work describes these steps for models of this kind.

The steps are the same; the model, its loss (cross-entropy, Session 17) and its size differ. Product designs are not published.

Where this appears in AI: why training needs far more computing than answering



Illustrative picture. Published analyses count the backward pass as about twice the forward pass.

Check an AI assistant with your own numbers

10 minutes **Hands-on, with no private data**

Ask any AI assistant to run the forward pass of our network. Then compare with your table.

Give it x = (1.0, 2.0), the table of parameters, and target 1. Ask for z, a, y-hat and L.

Expected y-hat: 0.1733.

If it differs, find the first number that differs.

Never paste confidential data.

You keep

A note: did the assistant match your table?

Exit check: three questions with short answers

Question	Short answer
What is delta(2) in this network, in words and as a formula?	The slope of the loss with respect to the prediction: y-hat - y. For us it was −0.8267.
Why does the hidden delta contain a × (1 minus a)?	It is the slope of the sigmoid. The chain rule multiplies it into the slope that arrives from the output.
Give two reasons training costs more computing than answering.	Each step needs a backward pass as well as a forward pass, and training repeats the step a very large number of times. Answering needs one forward pass per generated token.

Save your lab and keep the nine gradients

What you keep from today

Keep your saved notebook or workbook, with the nine gradients of the tiny network and the check that finite differences agree with them. Write down the loss before and after one update.

Our question today

What happens in every training step of a language model, and why does training cost far more computing than answering a question?

Next session

Session 12: optimisation in practice: a penalty that keeps the weights small, then softmax and the arithmetic that keeps numbers in range.

Take away

Loss, before
0.3417

Loss, after one update
0.0085

Check
Finite differences agree

Next session
Optimisation in practice