



CISBAT 2017 International Conference - Future Buildings & Districts - Energy Efficiency from Nano to Urban Scale, CISBAT 2017 6 8 September 2017, Lausanne, Switzerland

Identification of Building Archetypes for the Application of Adaptive Photovoltaic Shading Systems

P. Jayathissa^{a,*}, J. Zarb^a, M. Luzzatto^a, J. Hofer^a, A. Schlueter^a,

^a*Architecture and Building Systems, Institute of Technology in Architecture, Department of Architecture, ETH Zurich, Switzerland*

Abstract

III

Keywords: Dynamic Photovoltaics, Multi Functional Envelope, BIPV, Adaptive Shading

1. Introduction

- Buildings are responsible for significant energy consumption
- Recent developments in the efficiency and costs of thin film BIPV technologies allow for integration into the facade
- Dynamic building envelopes can save energy by controlling direct and indirect radiation into the building, while still responding to the occupants desires
- Previous research
- Review of ASF Simulation Paper
- Sensitivity of the Simulation on the building energy performance
- This paper extends this work by running the simulation to a variety of building archetypes in Zurich

*Corresponding author

Email addresses: jayathissa@arch.ethz.ch (P. Jayathissa), zarbj@student.ethz.ch (J. Zarb), maurol@student.ethz.ch (M. Luzzatto), hofer@arch.ethz.ch (J. Hofer), schlueter@arch.ethz.ch (A. Schlueter)

2. Methodology

The methodology runs the ASF Simulation. It will be briefly reviewed here for Simplicity

2.1. Solar Radiation Evaluation

2.2. Building Simulation Model

2.3. Sensitivities

Within this framework, three sensitivities will be analysed:

Building Envelope: The building envelope is characterised in the RC model as H_w

Infiltration: The infiltration rate is modified in the H_{ve} component of the RC model...

Thermal Capacitance: The thermal capacitance of the mass is denoted as C_m in the RC model. It...

2.4. Analysis of Archetypes

- Building Archetypes are taken from CEA tool and evaluated within the ASF Framework
- Table of Input Parameters for the different buildings

3. Results

3.1. Influence of Envelope Resistance

3.2. Influence of Infiltration

3.3. Influence of Thermal Mass

3.4. Archetype Evaluation of the ASF

4. Discussion and Conclusion

5. Acknowledgments

The authors would like to acknowledge the HiLo and HoNR project members for the design and construction of the ASF: Supermanoeuvre (Sydney Australia) and the Professorship of Architecture and Structures (BRG, ETH Zurich) for their work in designing the HiLo building; and the Institute of Structural Engineering (IBK, ETH Zurich) for their work in designing the HoNR building. The authors would also like to thank other key contributors to the ASF Project: Bratislav Svetozarevic, Moritz Begle, Stefan Caranovic.

This research was partly funded by the Climate-KIC, Building Technologies Accelerator program.