




Technische
Universität
Braunschweig

IAS

INSTITUTE FOR
APPLICATION
SECURITY



Web Security

Vorlesung “Einführung in die IT-Sicherheit”

Prof. Dr. Martin Johns


Overview

- **Topic of the unit**
 - Web Security
- **Parts of the unit**
 - Part #1: Server-side attacks
 - Part #2: Web sessions
 - Part #3: Client-side attacks




Web Applications

- **Applications implemented using “Web technologies”**
 - Client/server model using HTTP for communication
 - Code at client: HTML, JavaScript, WASM, CSS, ...
 - Code at server: PHP, JSP, ASP, ... and SQL
- **Some examples**
 - Facebook, Ebay, Youtube, ... it's just great!



Security Problems

- **All typical security problems**
 - Weak cryptography; weak authentication
 - Faulty and incorrect implementations
- **Problems specific to web applications:**
 - Client: Cross-site scripting and related attacks
 - Server: Code injection and path traversal




SQL Injection

- A simple example: **password check in PHP**

```
$name = $_GET ["name"];  
$password = $_GET ["password"];  
$query = "SELECT * FROM users WHERE name = '$name'  
AND password = '$password'";
```

- **Let's send a HTTP request ...**



SQL Injection

- A simple example: **password check in PHP**

```
$name = $_GET ["name"];  
$password = $_GET ["password"];  
$query = "SELECT * FROM users WHERE name = '$name'  
        AND password = '$password'";
```

- **Let's send a HTTP request ...**


```
$name = "steve";  
$password = "secret";  
$query = "SELECT * FROM users WHERE name = 'steve'  
        AND password = 'secret'";
```

SQL Injection

- A simple example: **password check in PHP**

```
$name = $_GET ["name"];  
$password = $_GET ["password"];  
$query = "SELECT * FROM users WHERE name = '$name'  
        AND password = '$password'";
```

- **Let's send another HTTP request ...**



SQL Injection

- A simple example: password check in PHP

```
$name = $_GET ["name"];  
$password = $_GET ["password"];  
$query = "SELECT * FROM users WHERE name = '$name'  
        AND password = '$password'";
```

- Let's send another HTTP request ...

```
$name = "steve";  
$password = "x' or '1'='1";  
$query = "SELECT * FROM users WHERE name = 'steve'  
        AND password = 'x' or '1'='1'";
```

Condition is always true
(password irrelevant)

Impact & Defense

- **Attack impact**

- Information leakage (`' ; SELECT * FROM ...`)
- Data manipulation (`' ; INSERT ... and ' ; DELETE ...`)
- Code execution (depends on SQL interface of database)

- What is the problem? Insufficient validation of input data

- **Countermeasures**


- Escaping of control and syntax characters
- Prepared SQL statements (no mixture of data and code)

Remote Code Execution

- Another example: **local helper program called via PHP**

```
<?php
    $data = $_GET ["data"];
    $output = shell_exec("cat "+ $data);
    echo "<pre>$output</pre>";
?>
```

- **Let's send a HTTP request ...**



Remote Code Execution

- Another example: **local helper program called via PHP**

```
<?php
    $data = $_GET ["data"];
    $output = shell_exec("cat "+ $data);
    echo "<pre>$output</pre>";
?>
```

- **Let's send a HTTP request ...**

```
<?php
    $file = "highscores.data";
    $output = shell_exec("cat highscores.data ");
    echo "<pre>Peter: 13 points</pre>";
?>
```

Remote Code Execution

- Another example: **local helper program called via PHP**

```
<?php
  $data = $_GET ["data"];
  $output = shell_exec("cat "+ $data);
  echo "<pre>$output</pre>";
?>
```

- **Let's send another HTTP request ...**



Remote Code Execution

- Another example: **local helper program called via PHP**

```
<?php
    $data = $_GET ["data"];
    $output = shell_exec("cat "+ $data);
    echo "<pre>$output</pre>";
?>
```

- **Let's send another HTTP request ...**

```
<?php
    $data = "foo; rm -rf /";
    $output = shell_exec("cat foo; rm -rf /");
    echo "<pre>file not found</pre>";
?>
```

Execution of arbitrary
shell commands

Impact & Defense

- **Attack impact**
 - Execution of arbitrary code on server system
 - Privileges of user running web server (e.g. www)
 - Attack variants using injected PHP or ASP code
- What is the problem? Insufficient validation of data again!
- **Countermeasures**
 - Escaping of control and syntax characters
 - No execution of shell commands from web applications

Path Traversals

- Example: Access to local file of web application



- Potential break out from directory of web application



Impact & Defense

- **Attack impact**

- Access to files outside the scope of the web application
- Potential access to configuration files and source code
- Combination with remote code execution (e.g. Nimda)

- What is the problem? Insufficient validation of data again!

- **Countermeasures**

- Sanitization and normalization of file paths
- Whitelisting of allowed files and directories

Weird Code Injection

- Injection of code not limited to traditional user input
 - Any type of input data potential source for attacks
- Example: **SQL injection over RFID chips**



What is wrong?

- **Root cause of most vulnerabilities**
 - Dynamic construction of code using string operations
 - Separation of code and data not enforced
- **Dangerous code elements in strings**
 - SQL injection: `'` (termination of strings)
 - Remote code execution `;` (termination of commands)
 - Path traversal `../` (move to upper directory)
- Several other attack surfaces: **JSON, LDAP, XPATH,...** injection

Code vs. Data

- The developer's view

```
$sql = "SELECT * FROM users WHERE passwd = '" + $pass + "'";
```

Code

Data

- The database's view

```
$sql = "SELECT * FROM users WHERE passwd = '" + $pass + "'";
```

Code

Data

?

- An attack mixing code and data

```
$sql = "SELECT * FROM users WHERE passwd = 'x' or '1' = '1'";
```

Code

Data

Attack

Overview

- **Topic of the unit**
 - Web Security
- **Parts of the unit**
 - Part #1: Server-side attacks
 - Part #2: Web sessions
 - Part #3: Client-side attacks



Sessions in HTTP

- **HTTP stateless by design**
 - Sessions prerequisite for online shopping, gaming, ...
 - Web applications need to implement session tracking
 - Session IDs track user activity across HTTP requests
- **Three common implementations**
 - 1 URL rewriting
 - 2 Form-based session IDs
 - 3 Cookies

- **Session management using URL rewriting**
 - Session IDs automatically appended to URLs
 - Developer needs to fix all URLs in application
 - **Problem:** Leakage of ID, e.g. in HTTP referrer header

```
GET /shop.php?SESSIONID=0d3adc0d3b3 HTTP/1.1  
Host: www.foobar.com  
Referrer: http://www.foobar.com  
User-Agent: Firefox 3.1337
```

Session ID in URL

```
GET /untrusted/webpage HTTP/1.1  
Host: www.dangerous.com  
Referrer: http://www.foobar.com/shop.php?SESSIONID=0d3adc0d3b3  
User-Agent: Firefox 3.1337
```

Leakage in referrer

- **Session management using HTML forms**
 - Session IDs stored in hidden form fields
 - Navigation of web application required to use forms
 - Transport of session IDs in body of POST request
 - **Problem:** back button of web browser

```
POST /shop.php HTTP/1.1
Host: www.foobar.com
Content-Type: application/x-www-form-urlencoded
Content-Length: 43
```

```
USER=john.doe&SESSIONID=0d3adc0d3b3
```

Session ID in body

- **Session management using cookies**
 - Persistent storage maintained by web browser
 - Data set using HTTP headers or scripting, e.g. JavaScript
 - Cookies automatically added for originating (sub-)domain

```
GET /shop/login.php HTTP/1.1  
Host: www.foobar.com
```

Request

```
HTTP/1.1 200 OK  
Set-Cookie: 0d3adc0d3b3; path=/shop
```

Response

```
GET /shop/order.php HTTP/1.1  
Host: www.foobar.com  
Cookie: 0d3adc0d3b3
```

Request with cookie

Sessions and Security

- **Session IDs used for tracking authenticated users**
 - Login process marks sessions as authenticated
 - **Problem:** Risk of a compromise if session ID leaks
- **Securing session IDs**
 - Hard to guess IDs → Long and random strings
 - Hard to eavesdrop IDs → Encrypted transport if possible
- **Are we safe now ...**
 - ... client-side attacks may still expose session IDs

Overview

- **Topic of the unit**
 - Web Security
- **Parts of the unit**
 - Part #1: Server-side attacks
 - Part #2: Web sessions
 - Part #3: Client-side attacks



JavaScript

- **JavaScript scripting language**
 - Introduced by Netscape in 1995 as ECMAScript
 - Implemented in every modern web browser
- **Powerful scripting interface**
 - Alteration of web pages
 - Access to URLs and form fields
 - Access and modification of cookies
 - Initiating of new HTTP requests
 - Execution of dynamic code



Same-Origin Policy

- **Main security measure for JavaScript**
 - Access restricted to elements from “same origin”
 - Also applied to ActionScript (Flash) and CSS stuff
- **Two elements share the same origin if**
 - ... the protocol is identical
 - ... the host is identical
 - ... the port is identical

`https://www.mega-relaunch.com:31337/shop/order.php`

Protocol

Host

Port

Cross-site Scripting

- **Cross-site Scripting (XSS)**
 - Injection of (JavaScript) code into webpages
 - Bypass of same-origin policy due to injection
 - Root-cause: display of insufficiently validated data
- **Simple example**

```
<?php
    $user = $_GET ["user"];
    echo "Welcome home, $user!";
?>
```

Cross-site Scripting

- **Cross-site Scripting (XSS)**
 - Injection of (JavaScript) code into webpages
 - Bypass of same-origin policy due to injection
 - Root-cause: display of insufficiently validated data
- **Simple example**




Cross-site Scripting

- **Cross-site Scripting (XSS)**
 - Injection of (JavaScript) code into webpages
 - Bypass of same-origin policy due to injection
 - Root-cause: display of insufficiently validated data
- **Simple example**

```
<?php
    $user = $_GET ["user"];
    echo "Welcome home, <script>alert()</script>!";
?>
```

Cross-site Scripting

- **Cross-site Scripting (XSS)**
 - Injection of (JavaScript) code into webpages
 - Bypass of same-origin policy due to injection
 - Root-cause: display of insufficiently validated data
- **Simple example**



Capabilities of XSS

- **Injection of JavaScript code = compromise of web browser**
- **Forgery of web content**
 - Attacker manipulates content on the web page
- **Spoofing of login dialogues**
 - Attacker uses JavaScript code to phish login credentials
- **Session and browser hijacking**
 - Attacker steals session IDs and acts as the user
- **Further web-based attacks, e.g. JavaScript worms**

Entry Points and Types

- **XSS entry points**

- Injection of tags, e.g. `<script>...`
- Breaking out of attributes, e.g. `<img alt="...`
- JavaScript URLs on some browsers, `javascript:...`
- Media files containing JavaScript, e.g. `SVG`


- **Common types of XSS**

- Reflected cross-site scripting (non-persistent)
- Stored cross-site scripting (persistent)
- DOM-based cross-site scripting

Reflected XSS

- **Reflected cross-site scripting**

- Attacker sends malicious JavaScript code directly to user
- Malicious JavaScript code is reflected by web server



Stored XSS


- **Stored cross-site scripting**

- Malicious JavaScript code is injected at the web server
- User queries trigger delivery of malicious code



Weird XSS

- Injection of code not limited to traditional user data
 - Any type of input data potential source for attacks
- Examples: XSS over SIP (Internet telephony)



Again: Code vs. Data

- The developer's view

```
<?php echo "<b>welcome $user</b> posted <em>$comment</em>" ?>
```

HTML

Data

- The web browser's view

```
<?php echo "<b>welcome $user</b> posted <em>$comment</em>" ?>
```

Tags

?

Data

?

- Cross-site scripting

```
<?php echo "<b>welcome <script>alert()</script></b> ..." ?>
```

Avoiding XSS

- **Validation of any user-supplied data**
 - Escaping of GET and POST parameters
 - Validation of externally stored data, e.g. databases
 - Checking of other sources, e.g. cookies, referer
- **Comprehensive input validation non-trivial**
 - Output validation often easier
 - Developer knows where JavaScript code is located
- In general: **whitelisting favorable over blacklisting**

Summary



...many other attacks

- **Cross-site Request Forgery (CSRF)**
 - Indirect access to a web application via forged requests
 - Example: ``
- **HTTP Parameter Pollution (HPP)**
 - Exploitation of inconsistent HTTP parameter parsing
 - Example: `a=x&a=y` may be interpreted as `a=x` or `a=y` or `a=xy`
- **SSL Stripping**
 - Man-in-the-middle attack removing SSL encryption
 - Example: web proxy replacing `https://` with `http://`

Conclusions

- **Web Security**

- Developing secure web applications non-trivial
- Several attack vectors using injected code
- Never, never, never trust user-supplied data

- **Client-side and server-side attacks**

- Server-side: SQL and other code injection
- Client-side: Cross-site scripting and friends