PY0101EN-2-2-Lists

January 8, 2022

1 Lists in Python

Estimated time needed: 15 minutes

1.1 Objectives

After completing this lab you will be able to:

• Perform list operations in Python, including indexing, list manipulation, and copy/clone list.

Table of Contents

```
<l
   <
      <a href="https://#dataset">About the Dataset</a>
   <
      <a href="https://#list">Lists</a>
      <l
          <a href="https://index/?utm_medium=Exinfluencer&utm_source=Exinfluencer&utm_ht"</a>
          <a href="content">List Content</a>
          <a href="op">List Operations</a>
          <a href="co">Copy and Clone List</a>
      >
      <a href="https://#quiz">Quiz on Lists</a>
```

About the Dataset

Imagine you received album recommendations from your friends and compiled all of the recommandations into a table, with specific information about each album.

The table has one row for each movie and several columns:

- artist Name of the artist
- album Name of the album
- released_year Year the album was released
- length_min_sec Length of the album (hours,minutes,seconds)
- genre Genre of the album

- music_recording_sales_millions Music recording sales (millions in USD) on SONG://DATABASE
- claimed_sales_millions Album's claimed sales (millions in USD) on SONG://DATABASE
- date_released Date on which the album was released
- soundtrack Indicates if the album is the movie soundtrack (Y) or (N)
- rating_of_friends Indicates the rating from your friends from 1 to 10

Artist

Album

Released

Length

Genre

Music recording sales (millions)

Claimed sales (millions)

Released

Soundtrack

Rating (friends)

Michael Jackson

Thriller

1982

00:42:19

Pop, rock, R&B

46

65

30-Nov-82

10.0

AC/DC

Back in Black

1980

00:42:11

Hard rock

26.1

50

25-Jul-80
8.5
Pink Floyd
The Dark Side of the Moon
1973
00:42:49
Progressive rock
24.2
45
01-Mar-73
9.5
Whitney Houston
The Bodyguard
1992
00:57:44
Soundtrack/R&B, soul, pop
26.1
50
25-Jul-80
Y
7.0
Meat Loaf
Bat Out of Hell
1977
00:46:33
Hard rock, progressive rock
20.6
43
21-Oct-77
7.0
Eagles
Their Greatest Hits (1971-1975)

1976 00:43:08 Rock, soft rock, folk rock 32.2 42 17-Feb-76 9.5 Bee Gees Saturday Night Fever 1977 1:15:54 Disco 20.640 15-Nov-77 Y 9.0 Fleetwood Mac Rumours 1977 00:40:01 Soft rock 27.9 40 04-Feb-77 9.5Lists Indexing We are going to take a look at lists in Python. A list is a sequenced collection of different objects

such as integers, strings, and even other lists as well. The address of each element within a list is called an index. An index is used to access and refer to items within a list.

To create a list, type the list within square brackets [], with your content inside the parenthesis and separated by commas. Let's try it!

```
[4]: # Create a list

L = ["Michael Jackson", 10.1, 1982]
L

# Create another list

M = ['Jovan Mann', 8.8, 1982]
M
```

[4]: ['Jovan Mann', 8.8, 1982]

We can use negative and regular indexing with a list:

```
print('the same element using negative and positive indexing:\n Postive:',L[0],
'\n Negative:', L[-3] )
print('the same element using negative and positive indexing:\n Postive:',L[1],
'\n Negative:', L[-2] )
print('the same element using negative and positive indexing:\n Postive:',L[2],
'\n Negative:', L[-1] )
```

the same element using negative and positive indexing:
Postive: Michael Jackson
Negative: Michael Jackson
the same element using negative and positive indexing:
Postive: 10.1
Negative: 10.1
the same element using negative and positive indexing:
Postive: 1982
Negative: 1982

Lists can contain strings, floats, and integers. We can nest other lists, and we can also nest tuples and other data structures. The same indexing conventions apply for nesting:

```
[10]: # Sample List
    ["Michael Jackson", 10.1, 1982, [1, 2], ("A", 1)]
# Example
    J = ['Jovan Mann', 15.8, 2000, [1,2], ('Joe',7)]
```

List Operations

List Content

We can also perform slicing in lists. For example, if we want the last two elements, we use the following command:

```
[11]:  # Sample List

L = ["Michael Jackson", 10.1,1982,"MJ",1]

L
```

[11]: ['Michael Jackson', 10.1, 1982, 'MJ', 1]

```
[12]: # List slicing

L[3:5]
```

[12]: ['MJ', 1]

We can use the method extend to add new elements to the list:

```
[13]: # Use extend to add elements to list

L = [ "Michael Jackson", 10.2]
L.extend(['pop', 10])
L
```

[13]: ['Michael Jackson', 10.2, 'pop', 10]

Another similar method is append. If we apply append instead of extend, we add one element to the list:

```
[22]: # Use append to add elements to list

L = [ "Michael Jackson", 10.2]
L.append(['pop', 10])
L

# appending just adds the entire element to the list

J = ['Jovan', 0.6, 1999]
J.append('Mann')
J
```

[22]: ['Jovan', 0.6, 1999, 'Mann']

Each time we apply a method, the list changes. If we apply extend we add two new elements to the list L is then modified by adding two new elements:

```
[15]: # Use extend to add elements to list

L = [ "Michael Jackson", 10.2]
L.extend(['pop', 10])
L
```

[15]: ['Michael Jackson', 10.2, 'pop', 10]

If we append the list ['a','b'] we have one new element consisting of a nested list:

```
[16]: # Use append to add elements to list

L.append(['a','b'])
L
```

[16]: ['Michael Jackson', 10.2, 'pop', 10, ['a', 'b']]

As lists are mutable, we can change them. For example, we can change the first element as follows:

```
[17]: # Change the element based on the index

A = ["disco", 10, 1.2]

print('Before change:', A)

A[0] = 'hard rock'

print('After change:', A)
```

Before change: ['disco', 10, 1.2]
After change: ['hard rock', 10, 1.2]

We can also delete an element of a list using the del command:

```
[18]: # Delete the element based on the index

print('Before change:', A)
del(A[0])
print('After change:', A)
```

Before change: ['hard rock', 10, 1.2]
After change: [10, 1.2]

We can convert a string to a list using split. For example, the method split translates every group of characters separated by a space into an element in a list:

```
[25]: # Split the string, default is by space
    'hard rock'.split()
    'jovan mann'.split()
    'I woke up at 8am, had cereal for '.split()
```

[25]: ['I', 'woke', 'up', 'at', '8am,', 'had', 'cereal', 'for']

We can use the split function to separate strings on a specific character which we call a **delimiter**. We pass the character we would like to split on into the argument, which in this case is a comma. The result is a list, and each element corresponds to a set of characters that have been separated by a comma:

```
[26]: # Split the string by comma

'A,B,C,D'.split(',')
```

[26]: ['A', 'B', 'C', 'D']

Copy and Clone List

When we set one variable B equal to A, both A and B are referencing the same list in memory:

```
[27]: # Copy (copy by reference) the list A

A = ["hard rock", 10, 1.2]
B = A
print('A:', A)
print('B:', B)
```

```
A: ['hard rock', 10, 1.2]
B: ['hard rock', 10, 1.2]
```

Initially, the value of the first element in B is set as "hard rock". If we change the first element in A to "banana", we get an unexpected side effect. As A and B are referencing the same list, if we change list A, then list B also changes. If we check the first element of B we get "banana" instead of "hard rock":

```
[28]: # Examine the copy by reference

print('B[0]:', B[0])
A[0] = "banana"
print('B[0]:', B[0])
```

B[0]: hard rock B[0]: banana

This is demonstrated in the following figure:

You can clone list **A** by using the following syntax:

```
[29]: # Clone (clone by value) the list A

B = A[:]
B
```

[29]: ['banana', 10, 1.2]

Variable \mathbf{B} references a new copy or clone of the original list. This is demonstrated in the following figure:

Now if you change A, B will not change:

```
[30]: print('B[0]:', B[0])
      A[0] = "hard rock"
      print('B[0]:', B[0])
     B[0]: banana
     B[0]: banana
     Quiz on List
     Create a list a list, with the following elements 1, hello, [1,2,3] and True.
[32]: # Write your code below and press Shift+Enter to execute
      a_list = [1, 'hello', [1,2,3], True]
      a list
[32]: [1, 'hello', [1, 2, 3], True]
     Click here for the solution
     a_list = [1, 'hello', [1, 2, 3] , True]
     a_list
     Find the value stored at index 1 of a list.
[33]: # Write your code below and press Shift+Enter to execute
      a_list[1]
[33]: 'hello'
     Click here for the solution
     a_list[1]
     Retrieve the elements stored at index 1, 2 and 3 of a_list.
[35]: # Write your code below and press Shift+Enter to execute
      a list[1:4]
      a_list
[35]: [1, 'hello', [1, 2, 3], True]
     Click here for the solution
     a_list[1:4]
     Concatenate the following lists A = [1, 'a'] and B = [2, 1, 'd']:
[36]: # Write your code below and press Shift+Enter to execute
      A= [1, 'a']
      B = [2,1,'d']
      A+B
```

Click here for the solution

The last exercise!

Congratulations, you have completed your first lesson and hands-on lab in Python. However, there is one more thing you need to do. The Data Science community encourages sharing work. The best way to share and showcase your work is to share it on GitHub. By sharing your notebook on GitHub you are not only building your reputation with fellow data scientists, but you can also show it off when applying for a job. Even though this was your first piece of work, it is never too early to start building good habits. So, please read and follow this article to learn how to share your work.

1.2 Author

Joseph Santarcangelo

1.3 Other contributors

Mavis Zhou

1.4 Change Log

Date (YYYY-MM-DD)	Version	Changed By	Change Description
2020-08-26	2.0	Lavanya	Moved lab to course repo in GitLab

##

© IBM Corporation 2020. All rights reserved.