



CS201 DISCRETE MATHEMATICS FOR COMPUTER SCIENCE

Dr. QI WANG

Department of Computer Science and Engineering

Office: Room413, CoE South Tower

Email: wangqi@sustech.edu.cn

Graph Concepts

- $G = (V, E)$, *simple* graph, *multigraph*, *pseudograph*
- *Undirected*, *directed* graph
- Special graphs
 K_n , C_n , W_n , Q_n , $K_{m,n}$
Hall's Marriage Theorem on *bipartite* graphs



Graph Concepts

- $G = (V, E)$, *simple* graph, *multigraph*, *pseudograph*
- *Undirected*, *directed* graph
- Special graphs
 K_n , C_n , W_n , Q_n , $K_{m,n}$
Hall's Marriage Theorem on *bipartite* graphs
- Representation of graphs
adjacency list, *adjacency matrix*, *incidence matrix*



Isomorphism of Graphs

- **Definition** The simple graphs $G_1 = (V_1, E_1)$ and $G_2 = (V_2, E_2)$ are *isomorphic* if there is a *one-to-one* and *onto* function from V_1 to V_2 with the property that *a and b are adjacent in G_1 if and only if $f(a)$ and $f(b)$ are adjacent in G_2* , for all a and b in V_1 . Such a function is called an *isomorphism*.



Isomorphism of Graphs

- **Definition** The simple graphs $G_1 = (V_1, E_1)$ and $G_2 = (V_2, E_2)$ are *isomorphic* if there is a **one-to-one** and **onto** function from V_1 to V_2 with the property that **a and b are adjacent in G_1 if and only if $f(a)$ and $f(b)$ are adjacent in G_2** , for all a and b in V_1 . Such a function is called an *isomorphism*.
- Useful **graph invariants** include **the number of vertices**, **number of edges**, **degree sequence**, etc.



Cut Vertices and Cut Edges

- Sometimes the removal from a graph of a vertex and all incident edges **disconnect** the graph. Such vertices are called ***cut vertices***. Similarly we may define ***cut edges***.



Cut Vertices and Cut Edges

- Sometimes the removal from a graph of a vertex and all incident edges **disconnect** the graph. Such vertices are called **cut vertices**. Similarly we may define **cut edges**.


A set of edges E' is called an **edge cut** of G if the subgraph $G - E'$ is **disconnected**. The **edge connectivity** $\lambda(G)$ is the **minimum number** of edges in an edge cut of G .



Cut Vertices and Cut Edges

- Sometimes the removal from a graph of a vertex and all incident edges **disconnect** the graph. Such vertices are called **cut vertices**. Similarly we may define **cut edges**.

A set of edges E' is called an **edge cut** of G if the subgraph $G - E'$ is **disconnected**. The **edge connectivity** $\lambda(G)$ is the **minimum number** of edges in an edge cut of G .




Paths and Isomorphism

- The existence of a simple circuit of length k is **isomorphic invariant**. In addition, **paths** can be used to construct mappings that may be **isomorphisms**.




Paths and Isomorphism

- The existence of a simple circuit of length k is **isomorphic invariant**. In addition, **paths** can be used to construct mappings that may be **isomorphisms**.




Paths and Isomorphism

- The existence of a simple circuit of length k is **isomorphic invariant**. In addition, **paths** can be used to construct mappings that may be **isomorphisms**.



G



H



Counting Paths between Vertices

- **Theorem** Let G be a graph with adjacency matrix \mathbf{A} with respect to the ordering v_1, v_2, \dots, v_n of vertices. The number of different paths of length r from v_i to v_j , where $r > 0$ is positive, equals the (i, j) -th entry of \mathbf{A}^r .



Counting Paths between Vertices

- **Theorem** Let G be a graph with adjacency matrix \mathbf{A} with respect to the ordering v_1, v_2, \dots, v_n of vertices. The number of different paths of length r from v_i to v_j , where $r > 0$ is positive, equals the (i, j) -th entry of \mathbf{A}^r .

Proof (by **induction**)



Counting Paths between Vertices

- **Theorem** Let G be a graph with adjacency matrix \mathbf{A} with respect to the ordering v_1, v_2, \dots, v_n of vertices. The number of different paths of length r from v_i to v_j , where $r > 0$ is positive, equals the (i, j) -th entry of \mathbf{A}^r .


Proof (by **induction**)

$\mathbf{A}^{r+1} = \mathbf{A}^r \mathbf{A}$, the (i, j) -th entry of \mathbf{A}^{r+1} equals $b_{i1}a_{1j} + b_{i2}a_{2j} + \dots + b_{in}a_{nj}$, where b_{ik} is the (i, k) -th entry of \mathbf{A}^r .




Counting Paths between Vertices

- **Example** How many paths of length 4 are there from a to d in the graph G ?



Counting Paths between Vertices

- **Example** How many paths of length 4 are there from a to d in the graph G ?




$$\begin{bmatrix} 0 & 1 & 1 & 0 \\ 1 & 0 & 0 & 1 \\ 1 & 0 & 0 & 1 \\ 0 & 1 & 1 & 0 \end{bmatrix}$$



Counting Paths between Vertices

- **Example** How many paths of length 4 are there from a to d in the graph G ?




$$\begin{bmatrix} 0 & 1 & 1 & 0 \\ 1 & 0 & 0 & 1 \\ 1 & 0 & 0 & 1 \\ 0 & 1 & 1 & 0 \end{bmatrix} \quad \begin{bmatrix} 8 & 0 & 0 & 8 \\ 0 & 8 & 8 & 0 \\ 0 & 8 & 8 & 0 \\ 8 & 0 & 0 & 8 \end{bmatrix}$$



Euler Paths

■ Königsberg seven-bridge problem



People wondered whether it was possible to start at some location in the town, travel across **all the bridges once** without crossing any bridge twice, and **return to the starting point**.



Euler Paths

■ Königsberg seven-bridge problem

People wondered whether it was possible to start at some location in the town, travel across **all the bridges once** without crossing any bridge twice, and **return to the starting point**.



Euler Paths and Circuits


- **Definition** An *Euler circuit* in a graph G is a simple circuit containing every edge of G . An *Euler path* in G is a simple path containing every edge of G .




Euler Paths and Circuits

- **Definition** An *Euler circuit* in a graph G is a simple circuit containing every edge of G . An *Euler path* in G is a simple path containing every edge of G .


Example Which of the undirected graphs have an Euler circuit? Of those that do not, which have an Euler path?



G_1



G_2



G_3




Euler Paths and Circuits

- **Definition** An *Euler circuit* in a graph G is a simple circuit containing every edge of G . An *Euler path* in G is a simple path containing every edge of G .


Example Which of the directed graphs have an Euler circuit? Of those that do not, which have an Euler path?



H_1



H_2



H_3



Necessary Conditions for Euler Circuits and Paths

- Euler Circuit \Rightarrow The degree of every vertex must be even



Necessary Conditions for Euler Circuits and Paths

- Euler Circuit \Rightarrow The degree of every vertex must be even
 - ◇ Each time the circuit passes through a vertex, it contributes two to the vertex's degree.



Necessary Conditions for Euler Circuits and Paths

- Euler Circuit \Rightarrow The degree of every vertex must be even
 - ◇ Each time the circuit passes through a vertex, it contributes two to the vertex's degree.
 - ◇ The circuit starts with a vertex a and ends at a , then contributes two to $\deg(a)$.



Necessary Conditions for Euler Circuits and Paths

- Euler Circuit \Rightarrow The degree of every vertex must be even
 - ◇ Each time the circuit passes through a vertex, it contributes two to the vertex's degree.
 - ◇ The circuit starts with a vertex a and ends at a , then contributes two to $\deg(a)$.

Euler Path \Rightarrow The graph has exactly two vertices of odd degree



Necessary Conditions for Euler Circuits and Paths

- Euler Circuit \Rightarrow The degree of every vertex must be even
 - ◇ Each time the circuit passes through a vertex, it contributes two to the vertex's degree.
 - ◇ The circuit starts with a vertex a and ends at a , then contributes two to $\deg(a)$.

Euler Path \Rightarrow The graph has exactly two vertices of odd degree

- ◇ The initial vertex and the final vertex of an Euler path have odd degree.




Sufficient Conditions for Euler Circuits and Paths

- Suppose that G is a **connected** multigraph with ≥ 2 vertices, **all of even degree**.





Sufficient Conditions for Euler Circuits and Paths

- Suppose that G is a **connected** multigraph with ≥ 2 vertices, **all of even degree**.



Sufficient Conditions for Euler Circuits and Paths

- Suppose that G is a **connected** multigraph with ≥ 2 vertices, **all of even degree**.



Algorithm for Constructing an Euler Circuit

■

```
procedure Euler(G: connected multigraph with all vertices of even degree)
  circuit := a circuit in G beginning at an arbitrarily chosen vertex with edges
             successively added to form a path that returns to this vertex.
  H := G with the edges of this circuit removed
  while H has edges
    subcircuit := a circuit in H beginning at a vertex in H that also is
                  an endpoint of an edge in circuit.
    H := H with edges of subcircuit and all isolated vertices removed
    circuit := circuit with subcircuit inserted at the appropriate vertex.
return circuit{circuit is an Euler circuit}
```



Algorithm for Constructing an Euler Circuit

■

```
procedure Euler(G: connected multigraph with all vertices of even degree)
  circuit := a circuit in G beginning at an arbitrarily chosen vertex with edges
               successively added to form a path that returns to this vertex.
  H := G with the edges of this circuit removed
  while H has edges
    subcircuit := a circuit in H beginning at a vertex in H that also is
                   an endpoint of an edge in circuit.
    H := H with edges of subcircuit and all isolated vertices removed
    circuit := circuit with subcircuit inserted at the appropriate vertex.
return circuit{circuit is an Euler circuit}
```



Algorithm for Constructing an Euler Circuit

■

```
procedure Euler(G: connected multigraph with all vertices of even degree)
  circuit := a circuit in G beginning at an arbitrarily chosen vertex with edges
               successively added to form a path that returns to this vertex.
  H := G with the edges of this circuit removed
  while H has edges
    subcircuit := a circuit in H beginning at a vertex in H that also is
                   an endpoint of an edge in circuit.
    H := H with edges of subcircuit and all isolated vertices removed
    circuit := circuit with subcircuit inserted at the appropriate vertex.
  return circuit{circuit is an Euler circuit}
```



Necessary and Sufficient Conditions

- **Theorem** A connected multigraph with at least two vertices has an *Euler circuit* if and only if each of its vertices has even degree.



Necessary and Sufficient Conditions

- **Theorem** A connected multigraph with at least two vertices has an *Euler circuit* if and only if each of its vertices has even degree.


Theorem A connected multigraph has an *Euler path* but not an *Euler circuit* if and only if it has exactly two vertices of odd degree.



Necessary and Sufficient Conditions

- **Theorem** A connected multigraph with at least two vertices has an *Euler circuit* if and only if **each of its vertices has even degree**.


Theorem A connected multigraph has an *Euler path* but not an *Euler circuit* if and only if **it has exactly two vertices of odd degree**.



Necessary and Sufficient Conditions

- **Theorem** A connected multigraph with at least two vertices has an *Euler circuit* if and only if each of its vertices has even degree.

Theorem A connected multigraph has an *Euler path* but not an *Euler circuit* if and only if it has exactly two vertices of odd degree.



No Euler circuit



Euler Circuits and Paths

■ Example







FIGURE 6 Mohammed's Scimitars.

Euler Circuits and Paths

■ Example



Applications of Euler Paths and Circuits

- Finding a path or circuit that traverses each
 - ◇ street in a neighborhood
 - ◇ road in a transportation network
 - ◇ link in a communication network
 - ◇ ...



Applications of Euler Paths and Circuits

- Finding a path or circuit that traverses each
 - ◇ street in a neighborhood
 - ◇ road in a transportation network
 - ◇ link in a communication network
 - ◇ ...

Chinese Postman Problem

Meigu Guan [60']



Applications of Euler Paths and Circuits

- Finding a path or circuit that traverses each
 - ◇ street in a neighborhood
 - ◇ road in a transportation network
 - ◇ link in a communication network
 - ◇ ...

Chinese Postman Problem

Meigu Guan [60']

Given a graph $G = (V, E)$, for every $e \in E$, there is a nonnegative weight $w(e)$. Find a **circuit** W such that

$$\sum_{e \in W} w(e) = \min$$



Applications of Euler Paths and Circuits

- Finding a path or circuit that traverses each
 - ◇ street in a neighborhood
 - ◇ road in a transportation network
 - ◇ link in a communication network
 - ◇ ...

Chinese Postman Problem

Meigu Guan [60']

Given a graph $G = (V, E)$, for every $e \in E$, there is a nonnegative weight $w(e)$. Find a **circuit** W such that

$$\sum_{e \in W} w(e) = \min$$

k-Postman Chinese Postman Problem (k -PCPP)



Applications of Euler Paths and Circuits

- Finding a path or circuit that traverses each
 - ◇ street in a neighborhood
 - ◇ road in a transportation network
 - ◇ link in a communication network
 - ◇ ...

Chinese Postman Problem

Meigu Guan [60']

Given a graph $G = (V, E)$, for every $e \in E$, there is a nonnegative weight $w(e)$. Find a **circuit** W such that

$$\sum_{e \in W} w(e) = \min$$

k-Postman Chinese Postman Problem (k -PCPP)

16 - 5 \in NPC




Hamilton Paths and Circuits

- Euler paths and circuits contained every **edge** only once.
What about containing every **vertex** exactly once?




Hamilton Paths and Circuits

- Euler paths and circuits contained every **edge** only once. What about containing every **vertex** exactly once?




(a)



(b)

Hamilton Paths and Circuits

- Euler paths and circuits contained every **edge** only once. What about containing every **vertex** exactly once?



Hamilton Paths and Circuits




- **Definition:** A *simple path* in a graph G that passes through *every vertex* exactly once is called a *Hamilton path*, and a *simple circuit* in a graph G that passes through *every vertex exactly once* is called a *Hamilton circuit*.



Hamilton Paths and Circuits

- **Definition:** A **simple path** in a graph G that passes through **every vertex** exactly once is called a **Hamilton path**, and a **simple circuit** in a graph G that passes through **every vertex exactly once** is called a **Hamilton circuit**.

Example Which of these simple graphs has a Hamilton circuit or, if not, a Hamilton path?



Sufficient Conditions for Hamilton Circuits

- No simple necessary and sufficient conditions are known for the existence of a Hamilton circuit.



Sufficient Conditions for Hamilton Circuits

- No simple necessary and sufficient conditions are known for the existence of a Hamilton circuit.

But, there are some useful sufficient conditions.



Sufficient Conditions for Hamilton Circuits

- **No** simple **necessary and sufficient** conditions are known for the **existence** of a Hamilton circuit.

But, there are some useful **sufficient conditions**.

Dirac's Theorem If G is a **simple graph** with $n \geq 3$ vertices such that the degree of every vertex in G is $\geq n/2$, then G has a **Hamilton circuit**.



Sufficient Conditions for Hamilton Circuits

- No simple necessary and sufficient conditions are known for the existence of a Hamilton circuit.

But, there are some useful sufficient conditions.

Dirac's Theorem If G is a simple graph with $n \geq 3$ vertices such that the degree of every vertex in G is $\geq n/2$, then G has a Hamilton circuit.

Ore's Theorem If G is a simple graph with $n \geq 3$ vertices such that $\deg(u) + \deg(v) \geq n$ for every pair of nonadjacent vertices, then G has a Hamilton circuit.



Sufficient Conditions for Hamilton Circuits

- No simple necessary and sufficient conditions are known for the existence of a Hamilton circuit.

But, there are some useful sufficient conditions.

Dirac's Theorem If G is a simple graph with $n \geq 3$ vertices such that the degree of every vertex in G is $\geq n/2$, then G has a Hamilton circuit.

Ore's Theorem If G is a simple graph with $n \geq 3$ vertices such that $\deg(u) + \deg(v) \geq n$ for every pair of nonadjacent vertices, then G has a Hamilton circuit.

Hamilton path problem \in NPC



Applications of Hamilton Paths and Circuits

- A path or a circuit that visits each city, or each node in a communication network **exactly once**, can be solved by finding a **Hamilton path**.



Applications of Hamilton Paths and Circuits

- A path or a circuit that visits each city, or each node in a communication network **exactly once**, can be solved by finding a **Hamilton path**.

Traveling Salesperson Problem (TSP) asks for the **shortest route** a traveling salesperson should take to visit a set of cities.



Applications of Hamilton Paths and Circuits

- A path or a circuit that visits each city, or each node in a communication network **exactly once**, can be solved by finding a **Hamilton path**.


Traveling Salesperson Problem (TSP) asks for the **shortest route** a traveling salesperson should take to visit a set of cities.

the decision version of the TSP \in NPC




Applications of Hamilton Paths and Circuits

- Can we traverse every space (and come back) in the 5×5 chessboard?



Applications of Hamilton Paths and Circuits

- Can we traverse every space (and come back) in the 5×5 chessboard?



What about in 6×6 chessboard?



Shortest Path Problems

- Using graphs with **weights** assigned to their edges



Shortest Path Problems

- Using graphs with *weights* assigned to their edges


Such graphs are called *weighted graphs* and can model lots of questions involving *distance*, *time consuming*, *fares*, etc.



Shortest Path Problems

- Using graphs with **weights** assigned to their edges

Such graphs are called **weighted graphs** and can model lots of questions involving **distance**, **time consuming**, **fares**, etc.



Shortest Path Problems

- **Definition** Let G^α be an **weighted graph**, with a **weight function** $\alpha : E \rightarrow \mathbf{R}^+$ on its edges. If $P = e_1 e_2 \cdots e_k$ is a path, then its weight is $\alpha(P) = \sum_{i=1}^k \alpha(e_i)$. The **minimum weighted distance** between two vertices is


$$d(u, v) = \min\{\alpha(P) \mid P : u \rightarrow v\}$$



Shortest Path Problems

- **Definition** Let G^α be an **weighted graph**, with a **weight function** $\alpha : E \rightarrow \mathbf{R}^+$ on its edges. If $P = e_1 e_2 \cdots e_k$ is a path, then its weight is $\alpha(P) = \sum_{i=1}^k \alpha(e_i)$. The **minimum weighted distance** between two vertices is

$$d(u, v) = \min\{\alpha(P) \mid P : u \rightarrow v\}$$



Edsger Wybe Dijkstra



Dijkstra's Algorithm

- (i) Set $d(v_0) = 0$ and $d(v) = \infty$ for all $v \neq v_0$, $S = \emptyset$



Dijkstra's Algorithm

- (i) Set $d(v_0) = 0$ and $d(v) = \infty$ for all $v \neq v_0$, $S = \emptyset$
- (ii) while $S \neq V$
 - let $v \notin S$ be the vertex with the least value $d(v)$,
 - $S = S \cup \{v\}$ for each $u \notin S$, replace $d(u)$ by
 $\min\{d(u), d(v) + \alpha(u, v)\}$



Dijkstra's Algorithm


- (i) Set $d(v_0) = 0$ and $d(v) = \infty$ for all $v \neq v_0$, $S = \emptyset$
- (ii) while $S \neq V$
 - let $v \notin S$ be the vertex with the least value $d(v)$,
 - $S = S \cup \{v\}$ for each $u \notin S$, replace $d(u)$ by
 $\min\{d(u), d(v) + \alpha(u, v)\}$
- (iii) return all $d(v)$'s



Dijkstra's Algorithm

- (i) Set $d(v_0) = 0$ and $d(v) = \infty$ for all $v \neq v_0$, $S = \emptyset$
- (ii) while $S \neq V$
 - let $v \notin S$ be the vertex with the **least value** $d(v)$,
 - $S = S \cup \{v\}$ for each $u \notin S$, replace $d(u)$ by $\min\{d(u), d(v) + \alpha(u, v)\}$
- (iii) return all $d(v)$'s


Example



Dijkstra's Algorithm

- (i) Set $d(v_0) = 0$ and $d(v) = \infty$ for all $v \neq v_0$, $S = \emptyset$
- (ii) while $S \neq V$
 - let $v \notin S$ be the vertex with the **least value** $d(v)$,
 - $S = S \cup \{v\}$ for each $u \notin S$, replace $d(u)$ by $\min\{d(u), d(v) + \alpha(u, v)\}$
- (iii) return all $d(v)$'s

Example




$d(v_0) = 0$, all other $d(v) = \infty$



Dijkstra's Algorithm

- (i) Set $d(v_0) = 0$ and $d(v) = \infty$ for all $v \neq v_0$, $S = \emptyset$
- (ii) while $S \neq V$
 - let $v \notin S$ be the vertex with the **least value** $d(v)$,
 - $S = S \cup \{v\}$ for each $u \notin S$, replace $d(u)$ by $\min\{d(u), d(v) + \alpha(u, v)\}$
- (iii) return all $d(v)$'s

Example



V_0	V_1	V_2	V_3	V_4	V_5
0	∞	∞	∞	∞	∞


$d(v_0) = 0$, all other $d(v) = \infty$



Dijkstra's Algorithm

- (i) Set $d(v_0) = 0$ and $d(v) = \infty$ for all $v \neq v_0$, $S = \emptyset$
- (ii) while $S \neq V$
 - let $v \notin S$ be the vertex with the **least value** $d(v)$,
 - $S = S \cup \{v\}$ for each $u \notin S$, replace $d(u)$ by $\min\{d(u), d(v) + \alpha(u, v)\}$
- (iii) return all $d(v)$'s

Example



v_0	v_1	v_2	v_3	v_4	v_5
0	∞	∞	∞	∞	∞

$i = 0$


$d(v_1) = \min\{\infty, 2\} = 2$, $d(v_2) = \min\{\infty, 3\} = 3$



Dijkstra's Algorithm

- (i) Set $d(v_0) = 0$ and $d(v) = \infty$ for all $v \neq v_0$, $S = \emptyset$
- (ii) while $S \neq V$
 - let $v \notin S$ be the vertex with the **least value** $d(v)$,
 - $S = S \cup \{v\}$ for each $u \notin S$, replace $d(u)$ by $\min\{d(u), d(v) + \alpha(u, v)\}$
- (iii) return all $d(v)$'s

Example



v_0	v_1	v_2	v_3	v_4	v_5
0	2	3	∞	∞	∞

$i = 0$


$d(v_1) = \min\{\infty, 2\} = 2$, $d(v_2) = \min\{\infty, 3\} = 3$



Dijkstra's Algorithm

- (i) Set $d(v_0) = 0$ and $d(v) = \infty$ for all $v \neq v_0$, $S = \emptyset$
- (ii) while $S \neq V$
 - let $v \notin S$ be the vertex with the **least value** $d(v)$,
 - $S = S \cup \{v\}$ for each $u \notin S$, replace $d(u)$ by
 $\min\{d(u), d(v) + \alpha(u, v)\}$
- (iii) return all $d(v)$'s

Example



v_0	v_1	v_2	v_3	v_4	v_5
0	2	3	∞	∞	∞

$i = 1$

$$d(v_2) = \min\{3, d(v_1) + \alpha(v_1 v_2)\} = \min\{3, 4\} = 3,$$

$$d(v_3) = 2 + 1 = 3, \quad d(v_4) = 2 + 3 = 5,$$


$$d(v_5) = 2 + 2 = 4$$



Dijkstra's Algorithm

- (i) Set $d(v_0) = 0$ and $d(v) = \infty$ for all $v \neq v_0$, $S = \emptyset$
- (ii) while $S \neq V$
 - let $v \notin S$ be the vertex with the **least value** $d(v)$,
 - $S = S \cup \{v\}$ for each $u \notin S$, replace $d(u)$ by
 $\min\{d(u), d(v) + \alpha(u, v)\}$
- (iii) return all $d(v)$'s

Example



v_0	v_1	v_2	v_3	v_4	v_5
0	2	3	3	5	4

$i = 1$

$$d(v_2) = \min\{3, d(v_1) + \alpha(v_1 v_2)\} = \min\{3, 4\} = 3,$$

$$d(v_3) = 2 + 1 = 3, \quad d(v_4) = 2 + 3 = 5,$$


$$d(v_5) = 2 + 2 = 4$$



Dijkstra's Algorithm

- (i) Set $d(v_0) = 0$ and $d(v) = \infty$ for all $v \neq v_0$, $S = \emptyset$
- (ii) while $S \neq V$
 - let $v \notin S$ be the vertex with the **least value** $d(v)$,
 - $S = S \cup \{v\}$ for each $u \notin S$, replace $d(u)$ by
 $\min\{d(u), d(v) + \alpha(u, v)\}$
- (iii) return all $d(v)$'s

Example



v_0	v_1	v_2	v_3	v_4	v_5
0	2	3	3	5	4

$i = 2$

$$d(v_3) = \min\{3, \infty\} = 3,$$

$$d(v_4) = \min\{5, 3 + 1\} = 4,$$


$$d(v_5) = \min\{4, \infty\} = 4$$



Dijkstra's Algorithm

- (i) Set $d(v_0) = 0$ and $d(v) = \infty$ for all $v \neq v_0$, $S = \emptyset$
- (ii) while $S \neq V$
 - let $v \notin S$ be the vertex with the **least value** $d(v)$,
 - $S = S \cup \{v\}$ for each $u \notin S$, replace $d(u)$ by
 $\min\{d(u), d(v) + \alpha(u, v)\}$
- (iii) return all $d(v)$'s

Example



v_0	v_1	v_2	v_3	v_4	v_5
0	2	3	3	4	4

$i = 2$

$$d(v_3) = \min\{3, \infty\} = 3,$$

$$d(v_4) = \min\{5, 3 + 1\} = 4,$$


$$d(v_5) = \min\{4, \infty\} = 4$$



Dijkstra's Algorithm

- (i) Set $d(v_0) = 0$ and $d(v) = \infty$ for all $v \neq v_0$, $S = \emptyset$
- (ii) while $S \neq V$
 - let $v \notin S$ be the vertex with the **least value** $d(v)$,
 - $S = S \cup \{v\}$ for each $u \notin S$, replace $d(u)$ by $\min\{d(u), d(v) + \alpha(u, v)\}$
- (iii) return all $d(v)$'s

Example



v_0	v_1	v_2	v_3	v_4	v_5
0	2	3	3	4	4

$i = 3$

$$d(v_4) = \min\{4, 3 + 2\} = 4,$$


$$d(v_5) = \min\{4, 3 + 1\} = 4$$



Dijkstra's Algorithm

- (i) Set $d(v_0) = 0$ and $d(v) = \infty$ for all $v \neq v_0$, $S = \emptyset$
- (ii) while $S \neq V$
 - let $v \notin S$ be the vertex with the **least value** $d(v)$,
 - $S = S \cup \{v\}$ for each $u \notin S$, replace $d(u)$ by $\min\{d(u), d(v) + \alpha(u, v)\}$
- (iii) return all $d(v)$'s

Example



v_0	v_1	v_2	v_3	v_4	v_5
0	2	3	3	4	4

$$i = 4$$

$$d(v_5) = \min\{4, 4 + 2\} = 4$$



Dijkstra's Algorithm

- **Theorem** *Dijkstra's algorithm* finds the length of a shortest path between two vertices in a connected simple undirected weighted graph.



Dijkstra's Algorithm

- **Theorem** *Dijkstra's algorithm* finds the length of a shortest path between two vertices in a connected simple undirected weighted graph.

Correctness



Dijkstra's Algorithm

- **Theorem** *Dijkstra's algorithm* finds the length of a shortest path between two vertices in a connected simple undirected weighted graph.

Correctness

Theorem *Dijkstra's algorithm* uses $O(n^2)$ operations (additions and comparisons) in a connected simple undirected weighted graph with n vertices.



Dijkstra's Algorithm

- **Theorem** *Dijkstra's algorithm* finds the length of a shortest path between two vertices in a connected simple undirected weighted graph.

Correctness

Theorem *Dijkstra's algorithm* uses $O(n^2)$ operations (additions and comparisons) in a connected simple undirected weighted graph with n vertices.

Complexity



Dijkstra's Algorithm

- **Theorem** *Dijkstra's algorithm* finds the length of a shortest path between two vertices in a connected simple undirected weighted graph.

Correctness


Theorem *Dijkstra's algorithm* uses $O(n^2)$ operations (additions and comparisons) in a connected simple undirected weighted graph with n vertices.

Complexity

read the Textbook p.712 – p.714



Another Example



Next Lecture

- Graph theory III ...

