



# CS201 DISCRETE MATHEMATICS FOR COMPUTER SCIENCE

Dr. QI WANG

Department of Computer Science and Engineering

Office: Room413, CoE South Tower

Email: [wangqi@sustech.edu.cn](mailto:wangqi@sustech.edu.cn)

# Properties of Relations

■ **Reflexive Relation:** A relation  $R$  on a set  $A$  is called *reflexive* if  $(a, a) \in R$  for **every** element  $a \in A$ .

**Irreflexive Relation:** A relation  $R$  on a set  $A$  is called *irreflexive* if  $(a, a) \notin R$  for **every** element  $a \in A$ .

**Symmetric Relation:** A relation  $R$  on a set  $A$  is called *symmetric* if  $(b, a) \in R$  whenever  $(a, b) \in R$  for **all**  $a, b \in A$ .

**Antisymmetric Relation:** A relation  $R$  on a set  $A$  is called *antisymmetric* if  $(b, a) \in R$  and  $(a, b) \in R$  implies  $a = b$  for **all**  $a, b \in A$ .

**Transitive Relation:** A relation  $R$  on a set  $A$  is called *transitive* if  $(a, b) \in R$  and  $(b, c) \in R$  implies  $(a, c) \in R$  for **all**  $a, b, c \in A$ .



# Connectivity

- **Lemma:** Let  $A$  be a set with  $n$  elements, and  $R$  a relation on  $A$ . If there is a path from  $a$  to  $b$  with  $a \neq b$ , then there exists a path of length  $\leq n - 1$ .

$$R^* = \bigcup_{k=1}^n R^k$$



# Connectivity

- **Lemma:** Let  $A$  be a set with  $n$  elements, and  $R$  a relation on  $A$ . If there is a path from  $a$  to  $b$  with  $a \neq b$ , then there exists a path of length  $\leq n - 1$ .

$$R^* = \bigcup_{k=1}^n R^k$$

**Theorem:** The transitive closure of a relation  $R$  equals the connectivity relation  $R^*$ .



# Connectivity

- **Lemma:** Let  $A$  be a set with  $n$  elements, and  $R$  a relation on  $A$ . If there is a path from  $a$  to  $b$  with  $a \neq b$ , then there exists a path of length  $\leq n - 1$ .

$$R^* = \bigcup_{k=1}^n R^k$$

**Theorem:** The transitive closure of a relation  $R$  equals the connectivity relation  $R^*$ .

**Recall** Finding a transitive closure corresponds to finding all pairs of elements that are connected with a directed path



# Equivalence Relation

- **Definition** A relation  $R$  on a set  $A$  is called an *equivalence relation* if it is *reflexive*, *symmetric*, and *transitive*.
- **Definition** Let  $R$  be an *equivalence relation* on a set  $A$ . The *set of all elements* that are related to an element  $a$  of  $A$  is called the *equivalence class* of  $a$ , denoted by  $[a]_R$ . When only one relation is considered, we use the notation  $[a]$ .

$$[a]_R = \{b : (a, b) \in R\}$$



# Equivalence Classes and Partitions

- **Theorem** Let  $R$  be an equivalence relation on a set  $A$ . Then union of all the equivalence classes of  $R$  is  $A$ :

$$A = \bigcup_{a \in A} [a]_R$$



# Equivalence Classes and Partitions

- **Theorem** Let  $R$  be an equivalence relation on a set  $A$ . Then union of all the equivalence classes of  $R$  is  $A$ :

$$A = \bigcup_{a \in A} [a]_R$$

**Theorem** The equivalence classes form a partition of  $A$ .





# Equivalence Classes and Partitions

- **Theorem** Let  $R$  be an equivalence relation on a set  $A$ . Then union of all the equivalence classes of  $R$  is  $A$ :

$$A = \bigcup_{a \in A} [a]_R$$

**Theorem** The equivalence classes form a partition of  $A$ .

**Theorem** Let  $\{A_1, A_2, \dots, A_i, \dots\}$  be a partition of  $S$ . Then there is an equivalence relation  $R$  on  $S$ , that has the sets  $A_i$  as its equivalence classes.



# Equivalence Relation




Don Zagier



# Equivalence Relation



Don Zagier



他四十年前来到中国，在合肥一周就写了四百中国汉字，说是在日本学的中日通用。他在波恩讲演之前，先问听众赞成用英语，德语，。。分别举手，他用多数人赞成的语言讲。张贤科给他起中文名：查吉尔，或查杰尔。他选后者  
.....

# Partial Ordering

- **Definition** A relation  $R$  on a set  $S$  is called a *partial ordering*, or *partial order*, if it is *reflexive*, *antisymmetric*, and *transitive*. A set  $S$  together with a partial ordering  $R$  is called a *partially ordered set*, or *poset*, denoted by  $(S, R)$ . Members of  $S$  are called *elements of the poset*.



# Partial Ordering

- **Definition** A relation  $R$  on a set  $S$  is called a *partial ordering*, or *partial order*, if it is *reflexive*, *antisymmetric*, and *transitive*. A set  $S$  together with a partial ordering  $R$  is called a *partially ordered set*, or *poset*, denoted by  $(S, R)$ . Members of  $S$  are called *elements of the poset*.

## Example:

$S = \{1, 2, 3, 4, 5\}$ ,  $R$  denotes the “ $\geq$ ” relation



# Partial Ordering

- **Definition** A relation  $R$  on a set  $S$  is called a *partial ordering*, or *partial order*, if it is *reflexive*, *antisymmetric*, and *transitive*. A set  $S$  together with a partial ordering  $R$  is called a *partially ordered set*, or *poset*, denoted by  $(S, R)$ . Members of  $S$  are called *elements of the poset*.

## Example:

$S = \{1, 2, 3, 4, 5\}$ ,  $R$  denotes the “ $\geq$ ” relation

Is  $R$  *reflexive*?



# Partial Ordering

- **Definition** A relation  $R$  on a set  $S$  is called a *partial ordering*, or *partial order*, if it is *reflexive*, *antisymmetric*, and *transitive*. A set  $S$  together with a partial ordering  $R$  is called a *partially ordered set*, or *poset*, denoted by  $(S, R)$ . Members of  $S$  are called *elements of the poset*.

## Example:

$S = \{1, 2, 3, 4, 5\}$ ,  $R$  denotes the “ $\geq$ ” relation

Is  $R$  *reflexive*? Yes



# Partial Ordering

- **Definition** A relation  $R$  on a set  $S$  is called a *partial ordering*, or *partial order*, if it is *reflexive*, *antisymmetric*, and *transitive*. A set  $S$  together with a partial ordering  $R$  is called a *partially ordered set*, or *poset*, denoted by  $(S, R)$ . Members of  $S$  are called *elements of the poset*.

## Example:

$S = \{1, 2, 3, 4, 5\}$ ,  $R$  denotes the “ $\geq$ ” relation

Is  $R$  *reflexive*? Yes

Is  $R$  *antisymmetric*?





# Partial Ordering

- **Definition** A relation  $R$  on a set  $S$  is called a *partial ordering*, or *partial order*, if it is *reflexive*, *antisymmetric*, and *transitive*. A set  $S$  together with a partial ordering  $R$  is called a *partially ordered set*, or *poset*, denoted by  $(S, R)$ . Members of  $S$  are called *elements of the poset*.

## Example:

$S = \{1, 2, 3, 4, 5\}$ ,  $R$  denotes the “ $\geq$ ” relation

Is  $R$  *reflexive*?      Yes

Is  $R$  *antisymmetric*?      Yes



# Partial Ordering

- **Definition** A relation  $R$  on a set  $S$  is called a *partial ordering*, or *partial order*, if it is *reflexive*, *antisymmetric*, and *transitive*. A set  $S$  together with a partial ordering  $R$  is called a *partially ordered set*, or *poset*, denoted by  $(S, R)$ . Members of  $S$  are called *elements of the poset*.

## Example:

$S = \{1, 2, 3, 4, 5\}$ ,  $R$  denotes the “ $\geq$ ” relation

Is  $R$  *reflexive*?      Yes

Is  $R$  *antisymmetric*?      Yes

Is  $R$  *transitive*?



# Partial Ordering

- **Definition** A relation  $R$  on a set  $S$  is called a *partial ordering*, or *partial order*, if it is *reflexive*, *antisymmetric*, and *transitive*. A set  $S$  together with a partial ordering  $R$  is called a *partially ordered set*, or *poset*, denoted by  $(S, R)$ . Members of  $S$  are called *elements of the poset*.

## Example:

$S = \{1, 2, 3, 4, 5\}$ ,  $R$  denotes the “ $\geq$ ” relation

Is  $R$  *reflexive*? Yes

Is  $R$  *antisymmetric*? Yes

Is  $R$  *transitive*? Yes



# Partial Ordering

- **Definition** A relation  $R$  on a set  $S$  is called a *partial ordering*, or *partial order*, if it is *reflexive*, *antisymmetric*, and *transitive*. A set  $S$  together with a partial ordering  $R$  is called a *partially ordered set*, or *poset*, denoted by  $(S, R)$ . Members of  $S$  are called *elements of the poset*.

## Example:

$S = \{1, 2, 3, 4, 5\}$ ,  $R$  denotes the “ $\geq$ ” relation

Is  $R$  *reflexive*? Yes

Is  $R$  *antisymmetric*? Yes

Is  $R$  *transitive*? Yes

$R$  is a *partial ordering*



# Partial Ordering

- **Example:**

$S = \{1, 2, 3, 4, 5, 6\}$ ,  $R$  denotes the “|” relation



# Partial Ordering

## ■ Example:

$S = \{1, 2, 3, 4, 5, 6\}$ ,  $R$  denotes the “|” relation

Is  $R$  reflexive? Yes

Is  $R$  antisymmetric? Yes

Is  $R$  transitive? Yes



# Partial Ordering

## ■ Example:

$S = \{1, 2, 3, 4, 5, 6\}$ ,  $R$  denotes the “|” relation

Is  $R$  reflexive? Yes

Is  $R$  antisymmetric? Yes

Is  $R$  transitive? Yes

$R$  is a partial ordering



# Comparability

- **Definition** The elements  $a$  and  $b$  of a poset  $(S, \preceq)$  are *comparable* if either  $a \preceq b$  or  $b \preceq a$ . Otherwise,  $a$  and  $b$  are called *incomparable*.





# Comparability

- **Definition** The elements  $a$  and  $b$  of a poset  $(S, \preceq)$  are *comparable* if either  $a \preceq b$  or  $b \preceq a$ . Otherwise,  $a$  and  $b$  are called *incomparable*.

## Example:

$S = \{1, 2, 3, 4, 5, 6\}$ ,  $R$  denotes the “ $|$ ” relation



# Comparability

- **Definition** The elements  $a$  and  $b$  of a poset  $(S, \preceq)$  are *comparable* if either  $a \preceq b$  or  $b \preceq a$ . Otherwise,  $a$  and  $b$  are called *incomparable*.

## Example:

$S = \{1, 2, 3, 4, 5, 6\}$ ,  $R$  denotes the “|” relation

2, 4 are comparable, 3, 5 are incomparable.



# Total Ordering

- **Definition** If  $(S, \preccurlyeq)$  is a poset and every two elements of  $S$  are comparable,  $S$  is called a *totally ordered* or *linearly ordered set*, and  $\preccurlyeq$  is called a *total order* or a *linear order*. A totally ordered set is also called a *chain*.



# Total Ordering

- **Definition** If  $(S, \preccurlyeq)$  is a poset and every two elements of  $S$  are comparable,  $S$  is called a *totally ordered* or *linearly ordered set*, and  $\preccurlyeq$  is called a *total order* or a *linear order*. A totally ordered set is also called a *chain*.

## Example:

$S = \{1, 2, 3, 4, 5, 6\}$ ,  $R$  denotes the “ $\geq$ ” relation



# Total Ordering

- **Definition** If  $(S, \preccurlyeq)$  is a poset and every two elements of  $S$  are comparable,  $S$  is called a *totally ordered* or *linearly ordered set*, and  $\preccurlyeq$  is called a *total order* or a *linear order*. A totally ordered set is also called a *chain*.

## Example:

$S = \{1, 2, 3, 4, 5, 6\}$ ,  $R$  denotes the “ $\geq$ ” relation

$S$  is a chain.



# Lexicographic Ordering

- **Definition** Given two posets  $(A_1, \preceq_1)$  and  $(A_2, \preceq_2)$ , the *lexicographic ordering* on  $A_1 \times A_2$  is defined by specifying that  $(a_1, a_2)$  is **less than**  $(b_1, b_2)$ , i.e.,  $(a_1, a_2) \preceq (b_1, b_2)$ , either if  $a_1 \prec_1 b_1$  or if  $a_1 = b_1$  then  $a_2 \preceq_2 b_2$ .



# Lexicographic Ordering

- **Definition** Given two posets  $(A_1, \preceq_1)$  and  $(A_2, \preceq_2)$ , the *lexicographic ordering* on  $A_1 \times A_2$  is defined by specifying that  $(a_1, a_2)$  is **less than**  $(b_1, b_2)$ , i.e.,  $(a_1, a_2) \preceq (b_1, b_2)$ , either if  $a_1 \prec_1 b_1$  or if  $a_1 = b_1$  then  $a_2 \preceq_2 b_2$ .

**Example** Consider strings of lowercase English letters. A *lexicographic ordering* can be defined using the ordering of the letters in the alphabet. This is *the same ordering* as that used in **dictionaries**.



# Lexicographic Ordering

- **Definition** Given two posets  $(A_1, \preceq_1)$  and  $(A_2, \preceq_2)$ , the *lexicographic ordering* on  $A_1 \times A_2$  is defined by specifying that  $(a_1, a_2)$  is **less than**  $(b_1, b_2)$ , i.e.,  $(a_1, a_2) \preceq (b_1, b_2)$ , either if  $a_1 \prec_1 b_1$  or if  $a_1 = b_1$  then  $a_2 \preceq_2 b_2$ .

**Example** Consider strings of lowercase English letters. A *lexicographic ordering* can be defined using the ordering of the letters in the alphabet. This is *the same ordering* as that used in **dictionaries**.

- ◇ *discreet*  $\prec$  *discrete*
- ◇ *discreet*  $\prec$  *discreetness*






# Hasse Diagram

- A Hasse diagram is a visual representation of a partial ordering that leaves out edges that must be present because of the reflexive and transitive properties.




# Hasse Diagram

- A **Hasse diagram** is a visual representation of a **partial ordering** that **leaves out** edges that must be present because of the **reflexive** and **transitive** properties.



# Hasse Diagram

- (a) A **partial ordering**. The loops are due to the **reflexive property**
- (b) The edges that must be present due to the **transitive property** are deleted
- (c) The Hasse diagram for the partial ordering (a)



# Procedure for Constructing Hasse Diagram

- Start with the directed graph of the relation:



# Procedure for Constructing Hasse Diagram

- Start with the directed graph of the relation:
  - ◇ Remove the loops  $(a, a)$  present at every vertex due to the reflexive property



# Procedure for Constructing Hasse Diagram

- Start with the directed graph of the relation:
  - ◇ Remove the loops  $(a, a)$  present at every vertex due to the **reflexive property**
  - ◇ Remove all edges  $(x, y)$  for which there is an element  $z \in S$  s.t.  $x \prec z$  and  $z \prec y$ . These are the edges that must be present due to the **transitive property**




# Procedure for Constructing Hasse Diagram

- Start with the directed graph of the relation:
  - ◇ Remove the loops  $(a, a)$  present at every vertex due to the **reflexive property**
  - ◇ Remove all edges  $(x, y)$  for which there is an element  $z \in S$  s.t.  $x \prec z$  and  $z \prec y$ . These are the edges that must be present due to the **transitive property**
  - ◇ Arrange each edge so that its initial vertex is **below** the terminal vertex. Remove all the arrows, because all edges point upwards toward their terminal vertex.





# Hasse Diagram Example








# Hasse Diagram Example



# Hasse Diagram Example



# Maximal and Minimal Elements

- **Definition**  $a$  is a *maximal* (resp. *minimal*) element in poset  $(S, \preceq)$  if there is **no**  $b \in S$  such that  $a \prec b$  (resp.  $b \prec a$ ).



# Maximal and Minimal Elements

- **Definition**  $a$  is a *maximal* (resp. *minimal*) element in poset  $(S, \preceq)$  if there is **no**  $b \in S$  such that  $a \prec b$  (resp.  $b \prec a$ ).

**Example** Which elements of the poset  $(\{2, 4, 5, 10, 12, 20, 25\}, |)$  are *maximal*, and *minimal*?



# Maximal and Minimal Elements

- **Definition**  $a$  is a *maximal* (resp. *minimal*) element in poset  $(S, \preceq)$  if there is **no**  $b \in S$  such that  $a \prec b$  (resp.  $b \prec a$ ).

**Example** Which elements of the poset  $(\{2, 4, 5, 10, 12, 20, 25\}, |)$  are *maximal*, and *minimal*?

**Definition**  $a$  is the *greatest* (resp. *least*) element of the poset  $(S, \preceq)$  if  $b \preceq a$  (resp.  $a \preceq b$ ) for all  $b \in S$ .




# Maximal and Minimal Elements

- **Definition**  $a$  is a *maximal* (resp. *minimal*) element in poset  $(S, \preceq)$  if there is **no**  $b \in S$  such that  $a \prec b$  (resp.  $b \prec a$ ).


**Example** Which elements of the poset  $(\{2, 4, 5, 10, 12, 20, 25\}, |)$  are *maximal*, and *minimal*?

**Definition**  $a$  is the *greatest* (resp. *least*) element of the poset  $(S, \preceq)$  if  $b \preceq a$  (resp.  $a \preceq b$ ) for all  $b \in S$ .


**Example**




(a)



(b)



(c)



(d)



# Maximal and Minimal Elements

- **Definition** Let  $A$  be a subset of a poset  $(S, \preceq)$ .
  - $u \in S$  is called an *upper bound* (resp. *lower bound*) of  $A$  if  $a \preceq u$  (resp.  $u \preceq a$ ) for all  $a \in A$ .
  - $x \in S$  is called the *least upper bound* (resp. *greatest lower bound*) of  $A$  if  $x$  is an upper bound (resp. lower bound) that is *less than* any *other* upper bound (resp. lower bound) of  $A$ .



# Maximal and Minimal Elements

- **Definition** Let  $A$  be a subset of a poset  $(S, \preceq)$ .
  - $u \in S$  is called an *upper bound* (resp. *lower bound*) of  $A$  if  $a \preceq u$  (resp.  $u \preceq a$ ) for all  $a \in A$ .
  - $x \in S$  is called the *least upper bound* (resp. *greatest lower bound*) of  $A$  if  $x$  is an upper bound (resp. lower bound) that is *less than* any *other* upper bound (resp. lower bound) of  $A$ .

**Example** Find the *greatest lower bound* and the *least upper bound* of the sets  $\{3, 9, 12\}$  and  $\{1, 2, 4, 5, 10\}$ , if they exist, in the poset  $(\mathbf{Z}^+, |)$ .





# Well-Ordered Set

- **Definition**  $(S, \preceq)$  is a *well-ordered set* if it is a poset such that  $\preceq$  is a **total ordering** and **every nonempty subset of  $S$  has a least element**.



# Well-Ordered Set

- **Definition**  $(S, \preceq)$  is a *well-ordered set* if it is a poset such that  $\preceq$  is a *total ordering* and *every nonempty subset of  $S$  has a least element*.

**The Principle of Well-Ordered Induction** Suppose that  $S$  is a *well-ordered set*. Then  $P(x)$  is true for *all  $x \in S$* , if

*Inductive Step* For every  $y \in S$ , if  $P(x)$  is true for all  $x \in S$  with  $x \prec y$ , then  $P(y)$  is true.



# Well-Ordered Set

- **Definition**  $(S, \preceq)$  is a *well-ordered set* if it is a poset such that  $\preceq$  is a *total ordering* and *every nonempty subset of  $S$  has a least element*.

**The Principle of Well-Ordered Induction** Suppose that  $S$  is a *well-ordered set*. Then  $P(x)$  is true for *all  $x \in S$* , if

*Inductive Step* For every  $y \in S$ , if  $P(x)$  is true for all  $x \in S$  with  $x \prec y$ , then  $P(y)$  is true.

**Proof** Consider  $A = \{x \in S : P(x) \text{ is false}\}$



# Well-Ordered Set

- **Definition**  $(S, \preceq)$  is a *well-ordered set* if it is a poset such that  $\preceq$  is a *total ordering* and *every nonempty subset of  $S$  has a least element*.

**The Principle of Well-Ordered Induction** Suppose that  $S$  is a *well-ordered set*. Then  $P(x)$  is true for *all  $x \in S$* , if

*Inductive Step* For every  $y \in S$ , if  $P(x)$  is true for all  $x \in S$  with  $x \prec y$ , then  $P(y)$  is true.

**Proof** Consider  $A = \{x \in S : P(x) \text{ is false}\}$

*Question*: Why don't we need a *basic step* here?



# Well-Ordered Set

- **Definition**  $(S, \preceq)$  is a *well-ordered set* if it is a poset such that  $\preceq$  is a *total ordering* and *every nonempty subset of  $S$  has a least element*.

**The Principle of Well-Ordered Induction** Suppose that  $S$  is a *well-ordered set*. Then  $P(x)$  is true for *all  $x \in S$* , if

*Inductive Step* For every  $y \in S$ , if  $P(x)$  is true for all  $x \in S$  with  $x \prec y$ , then  $P(y)$  is true.

**Proof** Consider  $A = \{x \in S : P(x) \text{ is false}\}$

*Question*: Why don't we need a *basic step* here?

p. 620, Theorem 1





# Lattices

- **Definition** A **partial ordered set** in which **every pair of elements** has both a least upper bound and a greatest lower bound is called a ***lattice***.




# Lattices

- **Definition** A **partial ordered set** in which **every pair of elements** has both a least upper bound and a greatest lower bound is called a ***lattice***.



# Lattices

- **Definition** A **partial ordered set** in which **every pair of elements** has both a least upper bound and a greatest lower bound is called a **lattice**.



**Example** Determine whether the posets  $(\{1, 2, 3, 4, 5\}, |)$  and  $(\{1, 2, 4, 8, 16\}, |)$  are lattices.





# Topological Sorting

- Motivation: A project is made up of 20 different tasks. Some tasks can be completed only after others have been finished. **How can an order be found for these tasks?**



# Topological Sorting

- Motivation: A project is made up of 20 different tasks. Some tasks can be completed only after others have been finished. **How can an order be found for these tasks?**

*Topological sorting*: Given a **partial ordering**  $R$ , find a **total ordering**  $\preceq$  such that  $a \preceq b$  whenever  $a R b$ .  $\preceq$  is said *compatible with*  $R$ .



# Topological Sorting for Finite Posets

**procedure** topological\_sort ( $S$ : finite poset)

$k := 1$ ;

**while**  $S \neq \emptyset$

$a_k :=$  a minimal element of  $S$

$S := S \setminus \{a_k\}$


$k := k + 1$

**end while**

//  $\{a_1, a_2, \dots, a_n\}$  is a compatible total ordering of  $S$




# Example



What is the **minimum number** of links to send a message from **B** to **NO**?




# Example



What is the **minimum number** of links to send a message from **B** to **NO**?



# Example




What is the **minimum number** of links to send a message from **B** to **NO**?

**3: B - CH - ME - NO**



# Example




What is the **minimum number** of links to send a message from **B** to **NO**?

**3: B - CH - ME - NO**

Which city/cities has/have the **most** communication links emanating from it/them?



# Example



What is the **minimum number** of links to send a message from **B** to **NO**?


**3: B - CH - ME - NO**

Which city/cities has/have the **most** communication links emanating from it/them?





# Example



What is the **minimum number** of links to send a message from **B** to **NO**?


**3: B - CH - ME - NO**

Which city/cities has/have the **most** communication links emanating from it/them?

**A: 6 links**



# Example



What is the **minimum number** of links to send a message from **B** to **NO**?

**3: B - CH - ME - NO**


Which city/cities has/have the **most** communication links emanating from it/them?

**A: 6 links**

What is the **total** number of communication links?



# Example



What is the **minimum number** of links to send a message from **B** to **NO**?

**3: B - CH - ME - NO**

Which city/cities has/have the **most** communication links emanating from it/them?


**A: 6 links**

What is the **total** number of communication links?


**20 links**



# Graph $G$




# Graph $G$



consists of a set of **vertices**  
 $V$ ,  $|V| = n$

# Graph $G$




consists of a set of **vertices**

$$V, |V| = n$$

and a set of **edges**  $E$ ,

$$|E| = m$$

# Graph $G$




consists of a set of **vertices**  
 $V$ ,  $|V| = n$

and a set of **edges**  $E$ ,  
 $|E| = m$

Each edge has **two endpoints**

# Graph $G$



consists of a set of **vertices**  
 $V$ ,  $|V| = n$


and a set of **edges**  $E$ ,  
 $|E| = m$

Each edge has **two endpoints**

An edge **joins** its endpoints,  
two endpoints are **adjacent**  
if they are joined by an edge



# Graph $G$



consists of a set of **vertices**  $V$ ,  $|V| = n$

and a set of **edges**  $E$ ,  $|E| = m$

Each edge has **two endpoints**

An edge **joins** its endpoints, two endpoints are **adjacent** if they are joined by an edge

When a vertex is an endpoint of an edge, we say that the edge and the vertex are **incident** to each other

# Definition of a Graph

- **Definition.** A *graph*  $G = (V, E)$  consists of a nonempty set  $V$  of *vertices* (or *nodes*) and a set  $E$  of *edges*. Each edge has either one or two vertices associated with it, called its *endpoints*. An edge is said to be *incident to* (or *connect* its endpoints).




# Definition of a Graph

- **Definition.** A *graph*  $G = (V, E)$  consists of a nonempty set  $V$  of *vertices* (or *nodes*) and a set  $E$  of *edges*. Each edge has either one or two vertices associated with it, called its *endpoints*. An edge is said to be *incident to* (or *connect* its endpoints).




a



b



c



d

# More Definitions

- *Simple graph* vs. *multigraph pseudograph*

A graph in which **at most one edge** joins each pair of distinct vertices (vs. **multiple** edges) and **no edge** joins a vertex to itself (= **loop**)



# More Definitions

- *Simple graph* vs. *multigraph pseudograph*

A graph in which **at most one edge** joins each pair of distinct vertices (vs. **multiple** edges) and **no edge** joins a vertex to itself (= **loop**)

*Complete graph*  $K_n$

A graph with  $n$  vertices that has an edge between **each pair** of vertices



# Graphs

- **Graphs** and **graph theory** can be used to model:
  - ◇ Computer networks
  - ◇ Social networks
  - ◇ Communication networks
  - ◇ Information networks
  - ◇ Software design
  - ◇ Transportation networks
  - ◇ Biological networks



# Graph Models

- Computer Networks

Vertices: computers

Edges: connections




# Graph Models

## ■ Computer Networks

Vertices: computers

Edges: connections





# Graph Models

- Social Networks

Vertices: individuals

Edges: relationships



# Graph Models

## ■ Social Networks

Vertices: individuals

Edges: relationships

**Friendship graphs:** undirected graphs where two people are connected if they are friends (in the real world, wechat, or Facebook, etc.)




# Graph Models

## ■ Social Networks

Vertices: individuals

Edges: relationships

**Friendship graphs:** undirected graphs where two people are connected if they are friends (in the real world, wechat, or Facebook, etc.)



# Graph Models

- Influence graphs

**directed** graphs where there is an edge from one person to another if the first person can influence the second one



# Graph Models

- Influence graphs

**directed** graphs where there is an edge from one person to another if the first person can influence the second one

## Collaboration graphs

**undirected** graphs where two people are connected if they collaborate in some way



# Graph Models

## ■ Influence graphs

**directed** graphs where there is an edge from one person to another if the first person can influence the second one

## Collaboration graphs

**undirected** graphs where two people are connected if they collaborate in some way

## Example

the Hollywood graph

the Erdős number





## 3



# The Erdős Number





# The Erdős Number



Erdős number	0	---	1 person
Erdős number	1	---	504 people
Erdős number	2	---	6593 people
Erdős number	3	---	33605 people
Erdős number	4	---	83642 people
Erdős number	5	---	87760 people
Erdős number	6	---	40014 people
Erdős number	7	---	11591 people
Erdős number	8	---	3146 people
Erdős number	9	---	819 people
Erdős number	10	---	244 people
Erdős number	11	---	68 people
Erdős number	12	---	23 people
Erdős number	13	---	5 people



# The Erdős Number



Erdős number 0	---	1 person
Erdős number 1	---	504 people
Erdős number 2	---	6593 people
Erdős number 3	---	33605 people
Erdős number 4	---	83642 people
Erdős number 5	---	87760 people
Erdős number 6	---	40014 people
Erdős number 7	---	11591 people
Erdős number 8	---	3146 people
Erdős number 9	---	819 people
Erdős number 10	---	244 people
Erdős number 11	---	68 people
Erdős number 12	---	23 people
Erdős number 13	---	5 people

Statistics on Mathematical Collaboration, 1903-2016

	◆ #Laureates ◆	#Erdős ◆	%Erdős ◆	Min ◆	Max ◆	Average ◆	Median ◆
Fields Medal	56	56	100.0%	2	6	3.36	3
Nobel Economics	76	47	61.84%	2	8	4.11	4
Nobel Chemistry	172	42	24.42%	3	10	5.48	5
Nobel Medicine	210	58	27.62%	3	12	5.50	5
Nobel Physics	200	159	79.50%	2	12	5.63	5



# Undirected Graphs

- **Definition** Two vertices  $u, v$  in an **undirected** graph  $G$  are called *adjacent* (or *neighbors*) in  $G$  if there is an edge  $e$  between  $u$  and  $v$ . Such an edge  $e$  is called *incident* with the vertices  $u$  and  $v$  and  $e$  is said to connect  $u$  and  $v$ .



# Undirected Graphs

- **Definition** Two vertices  $u, v$  in an **undirected** graph  $G$  are called *adjacent* (or *neighbors*) in  $G$  if there is an edge  $e$  between  $u$  and  $v$ . Such an edge  $e$  is called *incident* with the vertices  $u$  and  $v$  and  $e$  is said to connect  $u$  and  $v$ .

**Definition** The set of all neighbors of a vertex  $v$  of  $G = (V, E)$ , denoted by  $N(v)$ , is called *the neighborhood of  $v$* . If  $A$  is a subset of  $V$ , we denote by  $N(A)$  the set of all vertices in  $G$  that are adjacent to at least one vertex in  $A$ .



# Undirected Graphs

- **Definition** Two vertices  $u, v$  in an **undirected** graph  $G$  are called *adjacent* (or *neighbors*) in  $G$  if there is an edge  $e$  between  $u$  and  $v$ . Such an edge  $e$  is called *incident* with the vertices  $u$  and  $v$  and  $e$  is said to connect  $u$  and  $v$ .


**Definition** The set of all neighbors of a vertex  $v$  of  $G = (V, E)$ , denoted by  $N(v)$ , is called *the neighborhood of  $v$* . If  $A$  is a subset of  $V$ , we denote by  $N(A)$  the set of all vertices in  $G$  that are adjacent to at least one vertex in  $A$ .

**Definition** The *degree of a vertex in an undirected graph* is the number of edges incident with it, except that a loop at a vertex contributes two to the degree of that vertex. The degree of the vertex  $v$  is denoted by  $\deg(v)$ .





# Undirected Graphs

- **Example:** What are the degrees and neighborhoods of the vertices in the graph  $G$ ?



# Undirected Graphs

- **Example:** What are the degrees and neighborhoods of the vertices in the graph  $G$ ?



# Undirected Graphs

- **Theorem 1** (Handshaking Theorem) If  $G = (V, E)$  is an **undirected** graph with  $m$  edges, then

$$2m = \sum_{v \in V} \deg(v)$$

**Proof**





# Undirected Graphs

- **Theorem 2** An **undirected** graph has an **even number** of vertices of **odd degree**.



# Undirected Graphs

- **Theorem 2** An **undirected** graph has an **even number** of vertices of **odd degree**.

**Proof** Let  $V_1$  be the vertices of **even** degrees and  $V_2$  be the vertices of **odd** degree.



# Undirected Graphs

- **Theorem 2** An **undirected** graph has an **even number** of vertices of **odd degree**.

**Proof** Let  $V_1$  be the vertices of **even** degrees and  $V_2$  be the vertices of **odd** degree.

$$2m = \sum_{v \in V} \deg(v) = \sum_{v \in V_1} \deg(v) + \sum_{v \in V_2} \deg(v)$$



# Undirected Graphs

- **Theorem 2** An **undirected** graph has an **even number** of vertices of **odd degree**.

**Proof** Let  $V_1$  be the vertices of **even** degrees and  $V_2$  be the vertices of **odd** degree.

$$2m = \sum_{v \in V} \deg(v) = \boxed{\sum_{v \in V_1} \deg(v)} + \boxed{\sum_{v \in V_2} \deg(v)}$$



# Directed Graphs

- **Definition** An *directed graph*  $G = (V, E)$  consists of  $V$ , a nonempty set of vertices, and  $E$ , a set of directed edges. Each edge is an **ordered** pair of vertices. The directed edge  $(u, v)$  is said to **start at  $u$  and end at  $v$** .



# Directed Graphs

- **Definition** An *directed graph*  $G = (V, E)$  consists of  $V$ , a nonempty set of vertices, and  $E$ , a set of directed edges. Each edge is an **ordered** pair of vertices. The directed edge  $(u, v)$  is said to **start at  $u$  and end at  $v$** .

**Definition** Let  $(u, v)$  be an edge in  $G$ . Then  $u$  is the *initial vertex* of the edge and is *adjacent to  $v$*  and  $v$  is the *terminal vertex* of this edge and is *adjacent from  $u$* . The initial and terminal vertices of a loop are the same.




# Directed Graphs

- **Definition** The *in-degree* of a vertex  $v$ , denoted by  $\deg^-(v)$ , is the number of edges which terminate at  $v$ . The *out-degree* of  $v$ , denoted by  $\deg^+(v)$ , is the number of edges with  $v$  as their initial vertex. Note that a **loop** at a vertex contributes 1 to both the in-degree and the out-degree of the vertex.



# Directed Graphs

- **Definition** The *in-degree* of a vertex  $v$ , denoted by  $\deg^-(v)$ , is the number of edges which terminate at  $v$ . The *out-degree* of  $v$ , denoted by  $\deg^+(v)$ , is the number of edges with  $v$  as their initial vertex. Note that a **loop** at a vertex contributes 1 to both the in-degree and the out-degree of the vertex.





# Directed Graphs

- **Theorem 3** Let  $G = (V, E)$  be a graph with directed edges. Then

$$|E| = \sum_{v \in V} \deg^{-}(v) = \sum_{v \in V} \deg^{+}(v)$$

**Proof**




# Complete Graphs

- A *complete graph* on  $n$  vertices, denoted by  $K_n$ , is the simple graph that contains exactly one edge between **each pair** of distinct vertices.



# Complete Graphs

- A *complete graph* on  $n$  vertices, denoted by  $K_n$ , is the simple graph that contains exactly one edge between **each pair** of distinct vertices.




# Cycles

- A *cycle*  $C_n$  for  $n \geq 3$  consists of  $n$  vertices  $v_1, v_2, \dots, v_n$ , and edges  $\{v_1, v_2\}, \{v_2, v_3\}, \dots, \{v_{n-1}, v_n\}, \{v_n, v_1\}$ .




# Cycles

- A *cycle*  $C_n$  for  $n \geq 3$  consists of  $n$  vertices  $v_1, v_2, \dots, v_n$ , and edges  $\{v_1, v_2\}, \{v_2, v_3\}, \dots, \{v_{n-1}, v_n\}, \{v_n, v_1\}$ .



$C_3$



$C_4$



$C_5$



$C_6$




# Wheels

- A *wheel*  $W_n$  is obtained by adding an additional vertex to a cycle  $C_n$ .




# Wheels


- A *wheel*  $W_n$  is obtained by adding an additional vertex to a cycle  $C_n$ .




$W_3$



$W_4$



$W_5$



$W_6$

# $N$ -dimensional Hypercube

- An  *$n$ -dimensional hypercube*, or  *$n$ -cube*,  $Q_n$  is a graph with  $2^n$  vertices representing all bit strings of length  $n$ , where there is an edge between two vertices that differ in exactly one bit position.





# $N$ -dimensional Hypercube


- An  $n$ -dimensional hypercube, or  $n$ -cube,  $Q_n$  is a graph with  $2^n$  vertices representing all bit strings of length  $n$ , where there is an edge between two vertices that differ in exactly one bit position.



$Q_1$



$Q_2$



$Q_3$




# $N$ -dimensional Hypercube


- An  $n$ -dimensional hypercube, or  $n$ -cube,  $Q_n$  is a graph with  $2^n$  vertices representing all bit strings of length  $n$ , where there is an edge between two vertices that differ in exactly one bit position.



$Q_1$



$Q_2$



$Q_3$

How many vertices? How many edges?



# Bipartite Graphs

- **Definition** A simple graph  $G$  is *bipartite* if  $V$  can be partitioned into two disjoint subsets  $V_1$  and  $V_2$  such that every edge connects a vertex in  $V_1$  and a vertex in  $V_2$ .



# Bipartite Graphs

- **Definition** A simple graph  $G$  is *bipartite* if  $V$  can be partitioned into two disjoint subsets  $V_1$  and  $V_2$  such that every edge connects a vertex in  $V_1$  and a vertex in  $V_2$ .


An equivalent definition of a bipartite graph is a graph where it is possible to color the vertices red or blue so that no two adjacent vertices are of the same color.




# Bipartite Graphs

- **Definition** A simple graph  $G$  is *bipartite* if  $V$  can be partitioned into two disjoint subsets  $V_1$  and  $V_2$  such that every edge connects a vertex in  $V_1$  and a vertex in  $V_2$ .



An equivalent definition of a bipartite graph is a graph where it is possible to color the vertices red or blue so that no two adjacent vertices are of the same color.



# Bipartite Graphs




# Bipartite Graphs



# Bipartite Graphs


- **Example** Show that  $C_6$  is bipartite.





# Bipartite Graphs

- **Example** Show that  $C_6$  is bipartite.



**Example** Show that  $C_3$  is not bipartite.



# Complete Bipartite Graphs

- **Definition** A *complete bipartite graph*  $K_{m,n}$  is a graph that has its vertex set partitioned into two subsets  $V_1$  of size  $m$  and  $V_2$  of size  $n$  such that there is an edge from every vertex in  $V_1$  to every vertex in  $V_2$ .




# Complete Bipartite Graphs


- **Definition** A *complete bipartite graph*  $K_{m,n}$  is a graph that has its vertex set partitioned into two subsets  $V_1$  of size  $m$  and  $V_2$  of size  $n$  such that there is an edge from every vertex in  $V_1$  to every vertex in  $V_2$ .



$K_{2,3}$



$K_{3,3}$



$K_{3,5}$




$K_{2,6}$




# Puzzles using Graphs

- **The eight-circles problem** Place the letters A, B, C, D, E, F, G, H into the eight circles in the figure, in such a way that **no** letter is adjacent to a letter that is next to it in the alphabet.



# Puzzles using Graphs

- **The eight-circles problem** Place the letters A, B, C, D, E, F, G, H into the eight circles in the figure, in such a way that **no** letter is adjacent to a letter that is next to it in the alphabet.



- **Six people at a party** Show that, in any gathering of six people, there are either three people who all know each other, or three people none of which knows either of the other two.

# Next Lecture

- graph theory ...

