



WORKSHEET 5

Student Name: Harsh Khanna

UID: 23BCS10540

Branch: CSE(3rd Year)

Section/Group: Krg-1-A

Semester: 5th

Date of Performance: 25/09/25

Subject Name: ADBMS

Subject Code: 23CSP-333

1. AIM:

i) Performance Benchmarking : Normal View vs. Materialized View (Medium)

1. Create a large dataset: - Create a table names transaction_data (id, value) with 1 million records. - take id 1 and 2, and for each id, generate 1 million records in value column - Use Generate series () and random() to populate the data.
2. Create a normal view and materialized view to for sales summary, which includes total quantity_sold, total sales, and total orders with aggregation.
3. Compare the performance and execution time of both.

ii) Views: Securing Data Access with Views and Role-Based Permissions (Hard) The company TechMart Solutions stores all sales transactions in a central database.

A new reporting team has been formed to analyze sales but they should not have direct access to the base tables for security reasons.

The database administrator has decided to:

1. Create restricted views to display only summarized, non-sensitive data.
2. Assign access to these views to specific users using DCL commands (GRANT, REVOKE).

2. Tools Used : SQL Server Management Studio

Solutions:

Q1) --EXP 05(MEDIUM LEVEL)

```
CREATE TABLE transaction_data (  
id INT, value INT  
);
```

```

-- For id = 1
INSERT INTO transaction_data (id, value)
SELECT 1, random() * 1000
FROM generate_series(1, 1000000);

-- For id = 2
INSERT INTO transaction_data (id, value)
SELECT 2, random() * 1000
FROM generate_series(1, 1000000);

SELECT *FROM transaction_data;

--WITH NORMAL VIEW
CREATE OR REPLACE VIEW sales_summary_view AS SELECT
    id,
    COUNT(*) AS total_orders,
    SUM(value) AS total_sales,
    AVG(value) AS avg_transaction
FROM transaction_data
GROUP BY id;

--WITH MATERIALIZED VIEW
CREATE MATERIALIZED VIEW sales_summary_mv AS SELECT
    id,
    COUNT(*) AS total_orders,
    SUM(value) AS total_sales,
    AVG(value) AS avg_transaction
FROM transaction_data
GROUP BY id;

REFRESH MATERIALIZED VIEW sales_summary_mv;

EXPLAIN ANALYZE SELECT * FROM sales_summary_view;
EXPLAIN ANALYZE SELECT * FROM sales_summary_mv;

```

Q2) --EXP(05) HARD LEVEL

```

CREATE TABLE customer_master (
customer_id VARCHAR(5) PRIMARY KEY,
full_name VARCHAR(50) NOT NULL,
phone VARCHAR(15),
email VARCHAR(50), city
VARCHAR(30)

```

);

```
CREATE TABLE product_catalog (  
product_id VARCHAR(5) PRIMARY KEY,  
product_name VARCHAR (50) NOT  
NULL, brand VARCHAR(30), unit_price  
NUMERIC(10,2) NOT NULL  
);
```

```
CREATE TABLE sales_orders ( order_id SERIAL PRIMARY KEY,  
product_id VARCHAR(5) REFERENCES product_catalog(product_id),  
quantity INT NOT NULL, customer_id VARCHAR(5) REFERENCES  
customer_master(customer_id), discount_percent NUMERIC(5,2),  
order_date DATE NOT NULL  
);
```

```
INSERT INTO customer_master (customer_id, full_name, phone, email, city) VALUES  
( 'C1', 'Amit Sharma', '9876543210', 'amit.sharma@example.com', 'Delhi'),  
( 'C2', 'Priya Verma', '9876501234', 'priya.verma@example.com', 'Mumbai' ),  
( 'C3', 'Ravi Kumar', '9988776655', 'ravi.kumar@example.com' , 'Bangalore' ),  
( 'C4', 'Neha Singh', '9123456789', 'neha.singh@example.com', 'Kolkata'),  
( 'C5', 'Arjun Mehta', '9812345678' , 'arjun.mehta@example.com' , 'Hyderabad' ) ,  
( 'C6', 'Sneha Reddy', '9090909090', 'sneha.reddy@example.com', 'Chennai' ),  
( 'C7', 'Vikram Das', '9123412345' , 'vikram.das@example.com', 'Pune' ),  
( 'C8', 'Rohit Gupta', '9000000001' , 'rohit.gupta@example.com', 'Lucknow' ) ,  
( 'C9', 'Pooja Nair', '9898989898', 'pooja.nair@example.com', 'Kochi'),  
( 'C10', 'Ankit Yadav', '9345678901', 'ankit.yadav@example.com' , 'Ahmedabad' ) ;
```

```
INSERT INTO product_catalog (product_id, product_name, brand, unit_price) VALUES  
( 'P1', 'Smartphone X100', 'Samsung', 25000.00),  
( 'P2', 'Laptop Pro 15', 'Dell', 65000.00),  
( 'P3', 'Wireless Earbuds', 'Sony', 5000.00),  
( 'P4', 'Smartwatch Fit', 'Apple', 30000.00),  
( 'P5', 'Tablet 10.5', 'Lenovo', 22000.00),  
( 'P6', 'Gaming Console', 'Sony', 45000.00),  
( 'P7', 'Bluetooth Speaker', 'JBL', 7000.00),  
( 'P8', 'Digital Camera', 'Canon', 55000.00),  
( 'P9', 'LED TV 55 inch', 'LG', 60000.00),  
( 'P10', 'Power Bank 20000mAh', 'Mi', 2500.00);
```

```
INSERT INTO sales_orders (product_id, quantity, customer_id, discount_percent, order_date)  
VALUES  
( 'P1', 2, 'C1', 5.00, '2025-09-01'),  
( 'P2', 1, 'C2', 10.00, '2025-09-02'),  
( 'P3', 3, 'C3', 0.00, '2025-09-03'),
```

```

('P4', 1, 'C4', 8.00, '2025-09-04'),
('P5', 2, 'C5', 5.00, '2025-09-05'),
('P6', 1, 'C1', 12.00, '2025-09-06'), ('P7',
2, 'C2', 0.00, '2025-09-07'),
('P8', 1, 'C3', 10.00, '2025-09-08'),
('P9', 1, 'C6', 15.00, '2025-09-09'),
('P10', 4, 'C7', 0.00, '2025-09-10'),
('P1', 1, 'C8', 5.00, '2025-09-11'),
('P2', 2, 'C9', 10.00, '2025-09-12') ,
('P3', 2, 'C10', 0.00, '2025-09-13'),
('P4', 1, 'C5', 8.00, '2025-09-14'),
('P5', 3, 'C6', 5.00, '2025-09-15'),
('P6', 1, 'C7', 12.00, '2025-09-16'), ('P7',
2, 'C8', 0.00, '2025-09-17'),
('P8', 1, 'C9', 10.00, '2025-09-18'),
('P9', 1, 'C10', 15.00, '2025-09-19'),
('P10', 5, 'C4', 0.00, '2025-09-20');

```

-- 1. CREATE VIEW (only summarized, non-sensitive data)

```

CREATE VIEW vW_ORDER_SUMMARY AS
SELECT
    O.order_id,
    O.order_date,
    P.product_name,
    C.full_name,
    (P.unit_price * O.quantity)
    - ((P.unit_price * O.quantity) * O.discount_percent / 100) AS final_cost
FROM customer_master AS C
JOIN sales_orders AS O
    ON O.customer_id = C.customer_id
JOIN product_catalog AS P
    ON P.product_id = O.product_id;

```

-- 2. TESTING THE VIEW

```

SELECT * FROM vW_ORDER_SUMMARY;

```

-- 3. CREATE A USER / ROLE FOR THE REPORTING TEAM

-- (syntax may vary depending on DB: PostgreSQL, SQL Server, MySQL etc.)

-- Example for PostgreSQL:

```

CREATE ROLE alok LOGIN PASSWORD 'alok123';

```

-- Example for SQL Server:

```

-- CREATE LOGIN alok WITH PASSWORD = 'alok123';

```

REVOKE SELECT ON vW_ORDER SUMMARY FROM alok;

3. Output:

Data Output

Messages

Notifications

+
≡

SQL

Showing rows: 1 to 18

	QUERY PLAN <small>text</small>	
1	Finalize GroupAggregate (cost=26516.72..26517.25 rows=2 width=52) (actual time=338.588..346.053 rows=2 loops=1)	
2	Group Key: transaction_data.id	
3	-> Gather Merge (cost=26516.72..26517.18 rows=4 width=52) (actual time=337.548..344.990 rows=6 loops=1)	
4	Workers Planned: 2	
5	Workers Launched: 2	
6	-> Sort (cost=25516.69..25516.70 rows=2 width=52) (actual time=204.575..204.578 rows=2 loops=3)	
7	Sort Key: transaction_data.id	
8	Sort Method: quicksort Memory: 25kB	

<div> <div> <div>+</div> <div>📄</div> <div>▼</div> <div>📋</div> <div>▼</div> <div>🗑️</div> <div>🗄️</div> <div>⬇️</div> <div>📈</div> <div>SQL</div> </div> <div>Showing rows: 1 to 3</div> </div>					
<div> <div>QUERY PLAN</div> <div>text</div> <div>🔒</div> </div>					
1	Seq Scan on sales_summary_mv (cost=0.00..20.20 rows=1020 width=52) (actual time=0.009..0.010 rows=2 loops=...				
2	Planning Time: 1.902 ms				
3	Execution Time: 0.020 ms				

<div> <div> <div>+</div> <div>📄</div> <div>▼</div> <div>📋</div> <div>▼</div> <div>🗑️</div> <div>🗄️</div> <div>⬇️</div> <div>📈</div> <div>SQL</div> </div> <div>Showing rows: 1 to 21</div> </div>					
	order_id	order_date	product_name	full_name	final_cost
	integer	date	character varying (50)	character varying (50)	numeric
1	1	2025-09-01	Smartphone X100	Amit Sharma	47500.000000000000000000
2	2	2025-09-02	Laptop Pro 15	Priya Verma	58500.000000000000000000
3	3	2025-09-03	Wireless Earbuds	Ravi Kumar	15000.000000000000000000
4	4	2025-09-04	Smartwatch Fit	Neha Singh	27600.000000000000000000
5	5	2025-09-05	Tablet 10.5	Arjun Mehta	41800.000000000000000000
6	6	2025-09-06	Gaming Console	Amit Sharma	39600.000000000000000000
7	7	2025-09-07	Bluetooth Speaker	Priya Verma	14000.000000000000000000
8	8	2025-09-08	Digital Camera	Ravi Kumar	49500.000000000000000000
9	9	2025-09-09	LED TV 55 inch	Sneha Reddy	51000.000000000000000000

<div> <div> <div>+</div> <div>📄</div> <div>▼</div> <div>📋</div> <div>▼</div> <div>🗑️</div> <div>🗄️</div> <div>⬇️</div> <div>📈</div> <div>SQL</div> </div> </div>			
	empid	name	dept
	integer	text	text
1	1	Clark	Sales
2	3	Ava	Sales

4. Learning Outcomes:

i) Understanding View Creation & Data Security

- ❑ Learned how to create database views to present summarized and non-sensitive data while hiding underlying table details, improving data security for external/reporting users.

ii) Role & Access Control

- ❑ Gained practical knowledge of how to create users/roles and grant or revoke permissions on views to ensure controlled access in multi-user database environments.

iii) Performance Benchmarking of Views

- ❑ Understood the difference between Normal Views (executed dynamically) and Materialized Views (pre-computed and stored), and analyzed their execution time using EXPLAIN ANALYZE.

iv) Efficient Data Aggregation

- Learned to perform aggregation operations (SUM, COUNT, AVG) on large datasets and summarize transactions for analytical reporting.

v) Practical Exposure to Large Dataset Handling

- Acquired experience in generating and managing large-scale synthetic data (using `generate_series()` and `random()`) and applying optimization techniques for query performance improvement.