

MTK: Mimetic Methods Toolkit

Generated by Doxygen 1.8.6

Sun Sep 13 2015 01:58:00

Contents

1	Introduction	1
1.1	MTK Concerns	1
1.2	MTK Flavors	1
1.3	Contact, Support and Credits	2
1.4	Acknowledgements and Contributions	2
2	Programming Tools	3
3	Licensing and Modifications	5
4	Read Me File and Installation Instructions	7
5	Tests and Test Architectures	11
6	Examples	13
7	User Manual, References and Theory	15
8	Todo List	17
9	Bug List	19
10	Module Index	21
10.1	Modules	21
11	Namespace Index	23
11.1	Namespace List	23
12	Class Index	25
12.1	Class List	25
13	File Index	27
13.1	File List	27

14 Module Documentation	29
14.1 Roots.	29
14.1.1 Detailed Description	29
14.1.2 Typedef Documentation	30
14.1.2.1 Real	30
14.1.3 Variable Documentation	30
14.1.3.1 kCriticalOrderAccuracyDiv	30
14.1.3.2 kCriticalOrderAccuracyGrad	30
14.1.3.3 kDefaultMimeticThreshold	30
14.1.3.4 kDefaultOrderAccuracy	30
14.1.3.5 kDefaultTolerance	30
14.1.3.6 kOne	30
14.1.3.7 kZero	30
14.2 Enumerations.	31
14.2.1 Detailed Description	31
14.2.2 Enumeration Type Documentation	31
14.2.2.1 FieldNature	31
14.2.2.2 MatrixOrdering	31
14.2.2.3 MatrixStorage	32
14.3 Execution tools.	33
14.3.1 Detailed Description	33
14.4 Data structures.	34
14.4.1 Detailed Description	34
14.5 Numerical methods.	35
14.5.1 Detailed Description	35
14.6 Grids.	36
14.6.1 Detailed Description	36
14.7 Mimetic operators.	37
14.7.1 Detailed Description	37
15 Namespace Documentation	39
15.1 mtk Namespace Reference	39
15.1.1 Function Documentation	41
15.1.1.1 operator<<	41
15.1.1.2 operator<<	41
15.1.1.3 operator<<	41
15.1.1.4 operator<<	41

15.1.1.5	operator<<	42
15.1.1.6	sgels_	42
15.1.1.7	sgemm_	43
15.1.1.8	sgemv_	43
15.1.1.9	sgeqrf_	44
15.1.1.10	sgesv_	44
15.1.1.11	snrm2_	44
15.1.1.12	sormqr_	44
16	Class Documentation	47
16.1	mtk::BLASAdapter Class Reference	47
16.1.1	Detailed Description	47
16.1.2	Member Function Documentation	48
16.1.2.1	RealDenseMM	48
16.1.2.2	RealDenseMV	49
16.1.2.3	RealNRM2	50
16.2	mtk::DenseMatrix Class Reference	51
16.2.1	Detailed Description	54
16.2.2	Constructor & Destructor Documentation	54
16.2.2.1	DenseMatrix	54
16.2.2.2	DenseMatrix	54
16.2.2.3	DenseMatrix	55
16.2.2.4	DenseMatrix	56
16.2.2.5	DenseMatrix	56
16.2.2.6	~DenseMatrix	57
16.2.3	Member Function Documentation	57
16.2.3.1	data	57
16.2.3.2	GetValue	58
16.2.3.3	Kron	59
16.2.3.4	matrix_properties	60
16.2.3.5	num_cols	60
16.2.3.6	num_rows	61
16.2.3.7	operator=	62
16.2.3.8	OrderColMajor	63
16.2.3.9	OrderRowMajor	63
16.2.3.10	SetOrdering	64
16.2.3.11	SetValue	65

16.2.3.12	Transpose	65
16.2.4	Friends And Related Function Documentation	66
16.2.4.1	operator<<	66
16.2.5	Member Data Documentation	66
16.2.5.1	data_	66
16.2.5.2	matrix_properties_	66
16.3	mtk::Div1D Class Reference	66
16.3.1	Detailed Description	69
16.3.2	Constructor & Destructor Documentation	69
16.3.2.1	Div1D	69
16.3.2.2	Div1D	69
16.3.2.3	~Div1D	69
16.3.3	Member Function Documentation	70
16.3.3.1	AssembleOperator	70
16.3.3.2	ComputePreliminaryApproximations	70
16.3.3.3	ComputeRationalBasisNullSpace	71
16.3.3.4	ComputeStencilBoundaryGrid	71
16.3.3.5	ComputeStencilInteriorGrid	71
16.3.3.6	ComputeWeights	72
16.3.3.7	ConstructDiv1D	73
16.3.3.8	num_bndy_coeffs	73
16.3.3.9	ReturnAsDenseMatrix	74
16.3.3.10	weights_cbs	74
16.3.3.11	weights_crs	74
16.3.4	Friends And Related Function Documentation	75
16.3.4.1	operator<<	75
16.3.5	Member Data Documentation	75
16.3.5.1	coeffs_interior_	75
16.3.5.2	dim_null_	75
16.3.5.3	divergence_	75
16.3.5.4	divergence_length_	75
16.3.5.5	mim_bndy_	75
16.3.5.6	mimetic_threshold_	75
16.3.5.7	minrow_	75
16.3.5.8	num_bndy_coeffs_	76
16.3.5.9	order_accuracy_	76
16.3.5.10	prem_apps_	76

16.3.5.11	rat_basis_null_space_	76
16.3.5.12	row_	76
16.3.5.13	weights_cbs_	76
16.3.5.14	weights_crs_	76
16.4	mtk::GLPKAdapter Class Reference	76
16.4.1	Detailed Description	77
16.4.2	Member Function Documentation	77
16.4.2.1	SolveSimplexAndCompare	77
16.5	mtk::Grad1D Class Reference	79
16.5.1	Detailed Description	82
16.5.2	Constructor & Destructor Documentation	82
16.5.2.1	Grad1D	82
16.5.2.2	Grad1D	82
16.5.2.3	~Grad1D	82
16.5.3	Member Function Documentation	83
16.5.3.1	AssembleOperator	83
16.5.3.2	ComputePreliminaryApproximations	83
16.5.3.3	ComputeRationalBasisNullSpace	84
16.5.3.4	ComputeStencilBoundaryGrid	84
16.5.3.5	ComputeStencilInteriorGrid	84
16.5.3.6	ComputeWeights	85
16.5.3.7	ConstructGrad1D	86
16.5.3.8	num_bndy_coeffs	86
16.5.3.9	ReturnAsDenseMatrix	86
16.5.3.10	weights_cbs	87
16.5.3.11	weights_crs	87
16.5.4	Friends And Related Function Documentation	88
16.5.4.1	operator<<	88
16.5.5	Member Data Documentation	88
16.5.5.1	coeffs_interior_	88
16.5.5.2	dim_null_	88
16.5.5.3	gradient_	88
16.5.5.4	gradient_length_	88
16.5.5.5	mim_bndy_	88
16.5.5.6	mimetic_threshold_	88
16.5.5.7	minrow_	88
16.5.5.8	num_bndy_approxs_	88

16.5.5.9 num_bndy_coeffs_	89
16.5.5.10 order_accuracy_	89
16.5.5.11 prem_apps_	89
16.5.5.12 rat_basis_null_space_	89
16.5.5.13 row_	89
16.5.5.14 weights_cbs_	89
16.5.5.15 weights_crs_	89
16.6 mtk::Lap1D Class Reference	89
16.6.1 Detailed Description	91
16.6.2 Constructor & Destructor Documentation	91
16.6.2.1 Lap1D	91
16.6.2.2 Lap1D	91
16.6.2.3 ~Lap1D	91
16.6.3 Member Function Documentation	91
16.6.3.1 ConstructLap1D	91
16.6.3.2 Data	92
16.6.3.3 ReturnAsDenseMatrix	93
16.6.4 Friends And Related Function Documentation	94
16.6.4.1 operator<<	94
16.6.5 Member Data Documentation	94
16.6.5.1 laplacian_	94
16.6.5.2 laplacian_length_	94
16.6.5.3 mimetic_threshold_	94
16.6.5.4 order_accuracy_	94
16.7 mtk::LAPACKAdapter Class Reference	94
16.7.1 Detailed Description	95
16.7.2 Member Function Documentation	95
16.7.2.1 QRFactorDenseMatrix	95
16.7.2.2 SolveDenseSystem	96
16.7.2.3 SolveDenseSystem	97
16.7.2.4 SolveRectangularDenseSystem	98
16.8 mtk::Matrix Class Reference	99
16.8.1 Detailed Description	102
16.8.2 Constructor & Destructor Documentation	102
16.8.2.1 Matrix	102
16.8.2.2 Matrix	103
16.8.2.3 ~Matrix	104

16.8.3	Member Function Documentation	104
16.8.3.1	abs_density	104
16.8.3.2	abs_sparsity	104
16.8.3.3	bandwidth	104
16.8.3.4	IncreaseNumNull	104
16.8.3.5	IncreaseNumZero	105
16.8.3.6	kl	105
16.8.3.7	ku	105
16.8.3.8	ld	105
16.8.3.9	num_cols	105
16.8.3.10	num_non_null	106
16.8.3.11	num_non_zero	106
16.8.3.12	num_null	106
16.8.3.13	num_rows	107
16.8.3.14	num_values	107
16.8.3.15	num_zero	108
16.8.3.16	ordering	108
16.8.3.17	rel_density	108
16.8.3.18	rel_sparsity	109
16.8.3.19	set_num_cols	109
16.8.3.20	set_num_null	109
16.8.3.21	set_num_rows	110
16.8.3.22	set_num_zero	111
16.8.3.23	set_ordering	111
16.8.3.24	set_storage	112
16.8.3.25	storage	113
16.8.4	Member Data Documentation	114
16.8.4.1	abs_density_	114
16.8.4.2	abs_sparsity_	114
16.8.4.3	bandwidth_	114
16.8.4.4	kl_	114
16.8.4.5	ku_	114
16.8.4.6	ld_	114
16.8.4.7	num_cols_	114
16.8.4.8	num_non_null_	114
16.8.4.9	num_non_zero_	115
16.8.4.10	num_null_	115

16.8.4.11 num_rows_	115
16.8.4.12 num_values_	115
16.8.4.13 num_zero_	115
16.8.4.14 ordering_	115
16.8.4.15 rel_density_	115
16.8.4.16 rel_sparsity_	115
16.8.4.17 storage_	115
16.9 mtk::Quad1D Class Reference	115
16.9.1 Detailed Description	117
16.9.2 Constructor & Destructor Documentation	117
16.9.2.1 Quad1D	117
16.9.2.2 Quad1D	117
16.9.2.3 ~Quad1D	117
16.9.3 Member Function Documentation	117
16.9.3.1 degree_approximation	117
16.9.3.2 Integrate	117
16.9.3.3 weights	118
16.9.4 Friends And Related Function Documentation	118
16.9.4.1 operator<<	118
16.9.5 Member Data Documentation	118
16.9.5.1 degree_approximation_	118
16.9.5.2 weights_	118
16.10 mtk::Tools Class Reference	118
16.10.1 Detailed Description	119
16.10.2 Member Function Documentation	119
16.10.2.1 BeginTestNo	119
16.10.2.2 EndTestNo	120
16.10.2.3 Prevent	120
16.10.3 Member Data Documentation	121
16.10.3.1 begin_time_	121
16.10.3.2 test_number_	121
16.11 mtk::UniStgGrid1D Class Reference	122
16.11.1 Detailed Description	125
16.11.2 Constructor & Destructor Documentation	125
16.11.2.1 UniStgGrid1D	125
16.11.2.2 UniStgGrid1D	125
16.11.2.3 UniStgGrid1D	125

16.11.2.4 ~UniStgGrid1D	125
16.11.3 Member Function Documentation	126
16.11.3.1 BindScalarField	126
16.11.3.2 BindVectorField	126
16.11.3.3 delta_x	127
16.11.3.4 discrete_domain_x	127
16.11.3.5 discrete_field_u	127
16.11.3.6 num_cells_x	127
16.11.3.7 WriteToFile	128
16.11.4 Friends And Related Function Documentation	128
16.11.4.1 operator<<	128
16.11.5 Member Data Documentation	128
16.11.5.1 delta_x_	128
16.11.5.2 discrete_domain_x_	129
16.11.5.3 discrete_field_u_	129
16.11.5.4 east_bndy_x_	129
16.11.5.5 nature_	129
16.11.5.6 num_cells_x_	129
16.11.5.7 west_bndy_x_	129
17 File Documentation	131
17.1 examples/poisson_1d/poisson_1d.cc File Reference	131
17.1.1 Detailed Description	131
17.1.2 Function Documentation	132
17.1.2.1 main	132
17.2 poisson_1d.cc	132
17.3 include/mtk.h File Reference	135
17.3.1 Detailed Description	136
17.4 mtk.h	136
17.5 include/mtk_blas_adapter.h File Reference	137
17.5.1 Detailed Description	138
17.6 mtk_blas_adapter.h	139
17.7 include/mtk_dense_matrix.h File Reference	140
17.7.1 Detailed Description	141
17.8 mtk_dense_matrix.h	141
17.9 include/mtk_div_1d.h File Reference	143
17.9.1 Detailed Description	144

17.10	mtk_div_1d.h	144
17.11	include/mtk_enums.h File Reference	146
17.11.1	Detailed Description	146
17.12	mtk_enums.h	146
17.13	include/mtk_glpk_adapter.h File Reference	147
17.13.1	Detailed Description	148
17.14	mtk_glpk_adapter.h	149
17.15	include/mtk_grad_1d.h File Reference	150
17.15.1	Detailed Description	151
17.16	mtk_grad_1d.h	151
17.17	include/mtk_lap_1d.h File Reference	153
17.17.1	Detailed Description	154
17.18	mtk_lap_1d.h	154
17.19	include/mtk_lapack_adapter.h File Reference	155
17.19.1	Detailed Description	156
17.20	mtk_lapack_adapter.h	156
17.21	include/mtk_matrix.h File Reference	157
17.21.1	Detailed Description	158
17.22	mtk_matrix.h	159
17.23	include/mtk_quad_1d.h File Reference	160
17.23.1	Detailed Description	161
17.24	mtk_quad_1d.h	162
17.25	include/mtk_roots.h File Reference	163
17.25.1	Detailed Description	164
17.26	mtk_roots.h	164
17.27	include/mtk_tools.h File Reference	165
17.27.1	Detailed Description	166
17.28	mtk_tools.h	166
17.29	include/mtk_uni_stg_grid_1d.h File Reference	167
17.29.1	Detailed Description	168
17.30	mtk_uni_stg_grid_1d.h	168
17.31	Makefile.inc File Reference	170
17.32	Makefile.inc	170
17.33	README.md File Reference	172
17.34	README.md	172
17.35	src/mtk_blas_adapter.cc File Reference	174
17.36	mtk_blas_adapter.cc	175

17.37src/mtk_dense_matrix.cc File Reference	178
17.37.1 Detailed Description	178
17.38mtk_dense_matrix.cc	178
17.39src/mtk_div_1d.cc File Reference	185
17.39.1 Detailed Description	186
17.40mtk_div_1d.cc	186
17.41src/mtk_glpk_adapter.cc File Reference	202
17.41.1 Detailed Description	203
17.42mtk_glpk_adapter.cc	203
17.43src/mtk_grad_1d.cc File Reference	207
17.43.1 Detailed Description	208
17.44mtk_grad_1d.cc	208
17.45src/mtk_lap_1d.cc File Reference	225
17.45.1 Detailed Description	226
17.46mtk_lap_1d.cc	226
17.47src/mtk_lapack_adapter.cc File Reference	230
17.47.1 Detailed Description	231
17.48mtk_lapack_adapter.cc	232
17.49src/mtk_matrix.cc File Reference	238
17.49.1 Detailed Description	239
17.50mtk_matrix.cc	239
17.51src/mtk_tools.cc File Reference	243
17.51.1 Detailed Description	243
17.52mtk_tools.cc	243
17.53src/mtk_uni_stg_grid_1d.cc File Reference	245
17.53.1 Detailed Description	245
17.54mtk_uni_stg_grid_1d.cc	246
17.55tests/mtk_blas_adapter_test.cc File Reference	249
17.55.1 Detailed Description	249
17.55.2 Function Documentation	249
17.55.2.1 main	249
17.56mtk_blas_adapter_test.cc	249
17.57tests/mtk_dense_matrix_test.cc File Reference	251
17.57.1 Detailed Description	251
17.57.2 Function Documentation	251
17.57.2.1 main	251
17.58mtk_dense_matrix_test.cc	252

17.59tests/mtk_div_1d_test.cc File Reference	255
17.59.1 Detailed Description	256
17.59.2 Function Documentation	256
17.59.2.1 main	256
17.60mtk_div_1d_test.cc	256
17.61tests/mtk_glpk_adapter_test.cc File Reference	259
17.61.1 Detailed Description	260
17.61.2 Function Documentation	260
17.61.2.1 main	260
17.62mtk_glpk_adapter_test.cc	260
17.63tests/mtk_grad_1d_test.cc File Reference	261
17.63.1 Detailed Description	261
17.63.2 Function Documentation	262
17.63.2.1 main	262
17.64mtk_grad_1d_test.cc	262
17.65tests/mtk_lap_1d_test.cc File Reference	264
17.65.1 Function Documentation	264
17.65.1.1 main	265
17.66mtk_lap_1d_test.cc	265
17.67tests/mtk_lapack_adapter_test.cc File Reference	267
17.67.1 Detailed Description	267
17.67.2 Function Documentation	267
17.67.2.1 main	267
17.68mtk_lapack_adapter_test.cc	268
17.69tests/mtk_uni_stg_grid_1d_test.cc File Reference	269
17.69.1 Detailed Description	269
17.69.2 Function Documentation	269
17.69.2.1 main	269
17.70mtk_uni_stg_grid_1d_test.cc	269

Chapter 1

Introduction

We define numerical methods that are based on discretizations preserving the properties of their continuum counterparts to be **mimetic**.

The **Mimetic Methods Toolkit (MTK)** is a C++ library for mimetic numerical methods. It is a set of classes for **mimetic quadratures**, **mimetic interpolation**, and **mimetic discretization methods** for the numerical solution of ordinary and partial differential equations.

1.1 MTK Concerns

Since collaborative development efforts are definitely important in achieving the level of generality we intend the library to possess, we have divided the library's source code according to the designated purpose the classes possess within the library. These divisions (or concerns) are grouped by layers, and are hierarchically related by the dependence they have among them.

One concern is said to depend on another one, if the classes the first concern includes, rely on the classes the second concern includes.

In order of dependence these are:

1. Roots.
2. Enumerations.
3. Tools.
4. Data Structures.
5. Numerical Methods.
6. Grids.
7. Mimetic Operators.

1.2 MTK Flavors

The MTK collection of wrappers is:

1. MMTK: MATLAB wrappers collection for MTK; intended for sequential computations.

Others are being designed and developed.

1.3 Contact, Support and Credits

The MTK is developed by researchers and adjuncts to the Computational Science Research Center (CSRC) at San Diego State University (SDSU).

Developers are members of:

1. Mimetic Numerical Methods Research and Development Group.
2. Computational Geoscience Research and Development Group.
3. Ocean Modeling Research and Development Group.

Currently the developers are:

1. **Eduardo J. Sanchez, Ph.D. - esanchez at mail dot sdsu dot edu - ejspeiro**
2. Jose E. Castillo, Ph.D. - jcastillo at mail dot sdsu dot edu
3. Guillermo F. Miranda, Ph.D. - unigrav at hotmail dot com
4. Christopher P. Paolini, Ph.D. - paolini at engineering dot sdsu dot edu
5. Angel Boada.
6. Johnny Corbino.
7. Raul Vargas-Navarro.

1.4 Acknowledgements and Contributions

The authors would like to acknowledge valuable advising, contributions and feedback, from research personnel at the Computational Science Research Center at San Diego State University, which were vital to the fruition of this work. Specifically, our thanks go to (alphabetical order):

1. Mohammad Abouali, Ph.D.
2. Dany De Cecchis, Ph.D.
3. Julia Rossi.

Chapter 2

Programming Tools

The development of MTK has been made possible through the use of the following applications:

1. Editor: Kate - KDE Advanced Text Editor. Version 3.13.3. Using KDE Development Platform 4.13.3 (C) 2000-2005 The Kate Authors.
2. Compiler: gcc version 4.4.5 (Ubuntu/Linaro 4.4.4-14ubuntu5). Copyright (C) 2013 Free Software Foundation, Inc.
3. Debugger: GNU gdb (Ubuntu 7.7.1-0ubuntu5~14.04.2) 7.7.1. Copyright (C) 2014 Free Software Foundation, Inc.

Chapter 3

Licensing and Modifications

Copyright (C) 2015, Computational Science Research Center, San Diego State University. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu and a copy of the modified files should be reported once modifications are completed. Documentation related to said modifications should be included.
2. Redistributions of source code must be done through direct downloads from the project's GitHub page: <http://www.csrc.sdsu.edu/mtk>
3. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
4. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
5. Usage of the binary form on proprietary applications shall require explicit prior written permission from the the copyright holders.
6. Neither the name of the copyright holder nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

The copyright holders provide no reassurances that the source code provided does not infringe any patent, copyright, or any other intellectual property rights of third parties. The copyright holders disclaim any liability to any recipient for claims brought against recipient by any third party for infringement of that parties intellectual property rights.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Chapter 4

Read Me File and Installation Instructions

README File for the Mimetic Methods Toolkit (MTK)

By: **Eduardo J. Sanchez, Ph.D. - esanchez at mail dot sdsu dot edu**

1. Description

We define numerical methods that are based on discretizations preserving the properties of their continuum counterparts to be **mimetic**.

The **Mimetic Methods Toolkit (MTK)** is a C++ library for mimetic numerical methods. It is arranged as a set of classes for **mimetic quadratures**, **mimetic interpolation**, and **mimetic discretization** methods for the numerical solution of ordinary and partial differential equations.

2. Dependencies

This README assumes all of these dependencies are installed in the following folder:

`$(HOME)/Libraries/`

In this version, the MTK optionally uses ATLAS-optimized BLAS and LAPACK routines for the internal computation on some of the layers. However, ATLAS requires both BLAS and LAPACK in order to create their optimized distributions. Therefore, the following dependencies tree arises:

For Linux:

1. LAPACK - Available from: <http://www.netlib.org/lapack/>
 1. BLAS - Available from: <http://www.netlib.org/blas/>
2. (Optional) ATLAS - Available from: <http://math-atlas.sourceforge.net/>
 1. BLAS - Available from: <http://www.netlib.org/blas/>
 2. LAPACK - Available from: <http://www.netlib.org/lapack/>
3. (Optional) Valgrind - Available from: <http://valgrind.org/>
4. (Optional) Doxygen - Available from <http://www.stack.nl/~dimitri/doxygen/>

For OS X:

There are no dependences for OS X.

3. Installation

PART 1. CONFIGURATION OF THE MAKEFILE.

The following steps are required to build and test the MTK. Please use the accompanying [Makefile.inc](#) file, which should provide a solid template to start with. The following command provides help on the options for make:

```
$ make help
-----
```

Makefile for the MTK.

Options are:

- make: builds only the library and the examples.
- all: builds the library, the examples and the documentation.
- mtklib: builds the library, i.e. generates the archive files.

```

- test: generates the tests.
- example: generates the examples.
- gendoc: generates the documentation for the library.

- clean: cleans ALL the generated files.
- cleanlib: cleans the generated archive and object files.
- cleantest: cleans the generated tests executables.
- cleanexample: cleans the generated examples executables.
-----

```

PART 2. BUILD THE LIBRARY.

```
$ make
```

If successful you'll read (before building the examples):

```
----- Library created! Check in /home/ejspeiro/Dropbox/MTK/lib
```

Examples and tests will also be built.

4. Frequently Asked Questions

Q: Why haven't you guys implemented GBS to build the library?

A: I'm on it as we speak! ;)

Q: Is there any main reference when it comes to the theory on Mimetic Methods?

A: Yes! Check: <http://www.csrc.sdsu.edu/mimetic-book>

Q: Do I need to generate the documentation myself?

A: You can if you want to... but if you DO NOT want to, just go to our website.

5. Contact, Support, and Credits

The MTK is developed by researchers and adjuncts to the
[Computational Science Research Center \(CSRC\)](#)
 at [San Diego State University \(SDSU\)](#).

Developers are members of:

1. Mimetic Numerical Methods Research and Development Group.
2. Computational Geoscience Research and Development Group.
3. Ocean Modeling Research and Development Group.

Currently the developers are:

Eduardo J. Sanchez, Ph.D. - esanchez at mail dot sdsu dot edu - ejspeiro

2. Jose E. Castillo, Ph.D. - jcastillo at mail dot sdsu dot edu
3. Guillermo F. Miranda, Ph.D. - unigrav at hotmail dot com
4. Christopher P. Paolini, Ph.D. - paolini at engineering dot sdsu dot edu
5. Angel Boada.
6. Johnny Corbino.
7. Raul Vargas-Navarro.

Finally, please feel free to contact me with suggestions or corrections:

Eduardo J. Sanchez, Ph.D. - esanchez at mail dot sdsu dot edu - ejspeiro

Thanks and happy coding!

Chapter 5

Tests and Test Architectures

Tests are given in the `files list` section. They are provided in the `/tests/` folder within the distributed software.

In this page we intend to make a summary of all of the architectures in where the MTK has been tested. The MTK is intended to be as portable as possible throughout architectures. The following architectures have provided flawless installations of the API and correct execution of the examples:

1. Linux 3.2.0-23-generic-pae #36-Ubuntu SMP i386 GNU/Linux
Intel(R) Pentium(R) M processor 1.73GHz 2048 KB of cache and stepping of 8
gcc version 4.6.3 (Ubuntu/Linaro 4.6.3-1ubuntu5)

Further architectures will be tested!

Chapter 6

Examples

Examples are given in the `files list` section. They are provided in the `/examples/` folder within the distributed software.

Chapter 7

User Manual, References and Theory

The main source of references for this work can be found in:

<http://www.csrc.sdsu.edu/mimetic-book/>

However, a .PDF copy of this manual can be found [here](#).

Chapter 8

Todo List

Member [mtk::DenseMatrix::OrderColMajor \(\)](#)

Improve this so that no new arrays have to be created.

Member [mtk::DenseMatrix::OrderRowMajor \(\)](#)

Improve this so that no new arrays have to be created.

Member [mtk::DenseMatrix::Transpose \(\)](#)

Improve this so that no extra arrays have to be created.

Class [mtk::GLPKAdapter](#)

Rescind from the GLPK as the numerical core for CLO problems.

Member [mtk::Matrix::IncreaseNumNull \(\)](#)

Review the definition of sparse matrices properties.

Member [mtk::Matrix::IncreaseNumZero \(\)](#)

Review the definition of sparse matrices properties.

Member [mtk::Tools::Prevent \(const bool condition, const char *fname, int lineno, const char *fxname\)](#)

Check if this is the best way of stalling execution.

Member [mtk::Tools::test_number_](#)

Check usage of static methods and private members.

File [mtk_dense_matrix.h](#)

Add sparse matrices support: Banded and CRS.

Contemplate manipulation of sparse metrics.

Implement Kronecker product using the BLAS.

File [mtk_div_1d.cc](#)

Overload ostream operator as in [mtk::Lap1D](#).

Implement creation of ■ w. [mtk::BLASAdapter](#).

File [mtk_glpk_adapter.cc](#)

Document better this file.

File [mtk_glpk_adapter_test.cc](#)

Test the [mtk::GLPKAdapter](#) class.

File [mtk_grad_1d.cc](#)

Overload ostream operator as in [mtk::Lap1D](#).

Implement creation of ■ w. [mtk::BLASAdapter](#).

File [mtk_lapack_adapter_test.cc](#)

Test the [mtk::LAPACKAdapter](#) class.

File [mtk_quad_1d.h](#)

Implement this class.

File [mtk_roots.h](#)

Documentation should (better?) capture effects from selective compilation.

Test selective precision mechanism.

File [mtk_uni_stg_grid_1d.h](#)

Create overloaded binding routines that read data from files.

Chapter 9

Bug List

Member `mtk::Matrix::set_num_null` (int in)

-nan assigned on construction time due to `num_values_` being 0.

Member `mtk::Matrix::set_num_zero` (int in)

-nan assigned on construction time due to `num_values_` being 0.

Chapter 10

Module Index

10.1 Modules

Here is a list of all modules:

Roots.	29
Enumerations.	31
Execution tools.	33
Data structures.	34
Numerical methods.	35
Grids.	36
Mimetic operators.	37

Chapter 11

Namespace Index

11.1 Namespace List

Here is a list of all namespaces with brief descriptions:

mtk	Mimetic Methods Toolkit namespace	39
---------------------	---	--------------------

Chapter 12

Class Index

12.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

mtk::BLASAdapter	Adapter class for the BLAS API	47
mtk::DenseMatrix	Defines a common dense matrix, using a 1D array	51
mtk::Div1D	Implements a 1D mimetic divergence operator	66
mtk::GLPKAdapter	Adapter class for the GLPK API	76
mtk::Grad1D	Implements a 1D mimetic gradient operator	79
mtk::Lap1D	Implements a 1D mimetic Laplacian operator	89
mtk::LAPACKAdapter	Adapter class for the LAPACK API	94
mtk::Matrix	Definition of the representation of a matrix in the MTK	99
mtk::Quad1D	Implements a 1D mimetic quadrature	115
mtk::Tools	Tool manager class	118
mtk::UniStgGrid1D	Uniform 1D Staggered Grid	122

Chapter 13

File Index

13.1 File List

Here is a list of all files with brief descriptions:

Makefile.inc	170
examples/poisson_1d/ poisson_1d.cc	
Poisson Equation on a 1D Uniform Staggered Grid with Robin BCs	132
include/ mtk.h	
Includes the entire API	136
include/ mtk_blas_adapter.h	
Adapter class for the BLAS API	139
include/ mtk_dense_matrix.h	
Defines a common dense matrix, using a 1D array	141
include/ mtk_div_1d.h	
Includes the definition of the class Div1D	144
include/ mtk_enums.h	
Considered enumeration types in the MTK	146
include/ mtk_glpk_adapter.h	
Adapter class for the GLPK API	149
include/ mtk_grad_1d.h	
Includes the definition of the class Grad1D	151
include/ mtk_lap_1d.h	
Includes the definition of the class Lap1D	154
include/ mtk_lapack_adapter.h	
Adapter class for the LAPACK API	156
include/ mtk_matrix.h	
Definition of the representation of a matrix in the MTK	159
include/ mtk_quad_1d.h	
Includes the definition of the class Quad1D	162
include/ mtk_roots.h	
Fundamental definitions to be used across all classes of the MTK	164
include/ mtk_tools.h	
Tool manager class	166
include/ mtk_uni_stg_grid_1d.h	
Definition of an 1D uniform staggered grid	168
src/ mtk_blas_adapter.cc	175
src/ mtk_dense_matrix.cc	
Implements a common dense matrix, using a 1D array	178

src/mtk_div_1d.cc	Implements the class Div1D	186
src/mtk_glpk_adapter.cc	Adapter class for the GLPK API	203
src/mtk_grad_1d.cc	Implements the class Grad1D	208
src/mtk_lap_1d.cc	Includes the implementation of the class Lap1D	226
src/mtk_lapack_adapter.cc	Adapter class for the LAPACK API	232
src/mtk_matrix.cc	Implementing the representation of a matrix in the MTK	239
src/mtk_tools.cc	Implements a execution tool manager class	243
src/mtk_uni_stg_grid_1d.cc	Implementation of an 1D uniform staggered grid	246
tests/mtk_blas_adapter_test.cc	Test file for the mtk::BLASAdapter class	249
tests/mtk_dense_matrix_test.cc	Test file for the mtk::DenseMatrix class	252
tests/mtk_div_1d_test.cc	Testing the mimetic 1D divergence, constructed with the CBS algorithm	256
tests/mtk_glpk_adapter_test.cc	Test file for the mtk::GLPKAdapter class	260
tests/mtk_grad_1d_test.cc	Testing the mimetic 1D gradient, constructed with the CBS algorithm	262
tests/mtk_lap_1d_test.cc	265
tests/mtk_lapack_adapter_test.cc	Test file for the mtk::LAPACKAdapter class	268
tests/mtk_uni_stg_grid_1d_test.cc	Test file for the mtk::UniStgGrid1D class	269

Chapter 14

Module Documentation

14.1 Roots.

Fundamental execution parameters and defined types.

Typedefs

- typedef float `mtk::Real`

Users can simply change this to build a double- or single-precision MTK.

Variables

- const float `mtk::kZero` {0.0f}
MTK's zero defined according to selective compilation.
- const float `mtk::kOne` {1.0f}
MTK's one defined according to selective compilation.
- const float `mtk::kDefaultTolerance` {1e-7f}
Considered tolerance for comparisons in numerical methods.
- const int `mtk::kDefaultOrderAccuracy` {2}
Default order of accuracy for mimetic operators.
- const float `mtk::kDefaultMimeticThreshold` {1.e-6f}
Default tolerance for higher-order mimetic operators.
- const int `mtk::kCriticalOrderAccuracyDiv` {8}
At this order (and higher) we must use the CBSA to construct.
- const int `mtk::kCriticalOrderAccuracyGrad` {10}
At this order (and higher) we must use the CBSA to construct.

14.1.1 Detailed Description

Fundamental execution parameters and defined types.

14.1.2 Typedef Documentation

14.1.2.1 mtk::Real

Definition at line 83 of file [mtk_roots.h](#).

14.1.3 Variable Documentation

14.1.3.1 mtk::kCriticalOrderAccuracyDiv {8}

Definition at line 157 of file [mtk_roots.h](#).

14.1.3.2 mtk::kCriticalOrderAccuracyGrad {10}

Definition at line 166 of file [mtk_roots.h](#).

14.1.3.3 mtk::kDefaultMimeticThreshold {1.e-6f}

Warning

Declared as double if MTK_PRECISION_DOUBLE is defined.

Definition at line 147 of file [mtk_roots.h](#).

14.1.3.4 mtk::kDefaultOrderAccuracy {2}

Warning

Declared as double if MTK_PRECISION_DOUBLE is defined.

Definition at line 133 of file [mtk_roots.h](#).

14.1.3.5 mtk::kDefaultTolerance {1e-7f}

Definition at line 121 of file [mtk_roots.h](#).

14.1.3.6 mtk::kOne {1.0f}

Warning

Declared as double if MTK_PRECISION_DOUBLE is defined.

Definition at line 108 of file [mtk_roots.h](#).

14.1.3.7 mtk::kZero {0.0f}

Warning

Declared as double if MTK_PRECISION_DOUBLE is defined.

Definition at line 107 of file [mtk_roots.h](#).

14.2 Enumerations.

Enumerations.

Enumerations

- enum `mtk::MatrixStorage` { `mtk::DENSE`, `mtk::BANDED`, `mtk::CRS` }
Considered matrix storage schemes to implement sparse matrices.
- enum `mtk::MatrixOrdering` { `mtk::ROW_MAJOR`, `mtk::COL_MAJOR` }
Considered matrix ordering (for Fortran purposes).
- enum `mtk::FieldNature` { `mtk::SCALAR`, `mtk::VECTOR` }
Nature of the field discretized in a given grid.

14.2.1 Detailed Description

Enumerations.

14.2.2 Enumeration Type Documentation

14.2.2.1 enum `mtk::FieldNature`

Fields can be **scalar** or **vector** in nature.

See Also

https://en.wikipedia.org/wiki/Scalar_field
https://en.wikipedia.org/wiki/Vector_field

Enumerator

SCALAR Scalar-valued field.

VECTOR Vector-valued field.

Definition at line 113 of file `mtk_enums.h`.

14.2.2.2 enum `mtk::MatrixOrdering`

Row-major ordering is used for most application in C/C++. For Fortran purposes, the matrices must be listed in a column-major ordering.

See Also

https://en.wikipedia.org/wiki/Row-major_order

Enumerator

ROW_MAJOR Row-major ordering (C/C++).

COL_MAJOR Column-major ordering (Fortran).

Definition at line 95 of file `mtk_enums.h`.

14.2.2.3 enum mtk::MatrixStorage

The considered sparse storage schemes are selected so that these are compatible with some of the most used mathematical APIs, as follows: DENSE and BANDED for [BLAS](#), [LAPACK](#), and [ScaLAPACK](#). Finally, CRS for [SuperLU](#).

Enumerator

DENSE Dense matrices, implemented as a 1D array: [DenseMatrix](#).

BANDED Banded matrices ala LAPACK and ScaLAPACK: Must be implemented.

CRS Compressed-Rows Storage: Must be implemented.

Definition at line 77 of file [mtk_enums.h](#).

14.3 Execution tools.

Tools to ensure execution correctness.

Classes

- class `mtk::Tools`
Tool manager class.

14.3.1 Detailed Description

Tools to ensure execution correctness.

14.4 Data structures.

Fundamental data structures.

Classes

- class [mtk::DenseMatrix](#)
Defines a common dense matrix, using a 1D array.
- class [mtk::Matrix](#)
Definition of the representation of a matrix in the MTK.

14.4.1 Detailed Description

Fundamental data structures.

14.5 Numerical methods.

Adapter classes and auxiliary numerical methods.

Classes

- class [mtk::BLASAdapter](#)
Adapter class for the BLAS API.
- class [mtk::GLPKAdapter](#)
Adapter class for the GLPK API.
- class [mtk::LAPACKAdapter](#)
Adapter class for the LAPACK API.

14.5.1 Detailed Description

Adapter classes and auxiliary numerical methods.

14.6 Grids.

Uniform rectangular staggered grids.

Classes

- class [mtk::UniStgGrid1D](#)
Uniform 1D Staggered Grid.

14.6.1 Detailed Description

Uniform rectangular staggered grids.

14.7 Mimetic operators.

Mimetic operators.

Classes

- class `mtk::Div1D`
Implements a 1D mimetic divergence operator.
- class `mtk::Grad1D`
Implements a 1D mimetic gradient operator.
- class `mtk::Lap1D`
Implements a 1D mimetic Laplacian operator.
- class `mtk::Quad1D`
Implements a 1D mimetic quadrature.

14.7.1 Detailed Description

Mimetic operators.

Chapter 15

Namespace Documentation

15.1 mtk Namespace Reference

Mimetic Methods Toolkit namespace.

Classes

- class [BLASAdapter](#)
Adapter class for the BLAS API.
- class [DenseMatrix](#)
Defines a common dense matrix, using a 1D array.
- class [Div1D](#)
Implements a 1D mimetic divergence operator.
- class [GLPKAdapter](#)
Adapter class for the GLPK API.
- class [Grad1D](#)
Implements a 1D mimetic gradient operator.
- class [Lap1D](#)
Implements a 1D mimetic Laplacian operator.
- class [LAPACKAdapter](#)
Adapter class for the LAPACK API.
- class [Matrix](#)
Definition of the representation of a matrix in the MTK.
- class [Quad1D](#)
Implements a 1D mimetic quadrature.
- class [Tools](#)
Tool manager class.
- class [UniStgGrid1D](#)
Uniform 1D Staggered Grid.

Typedefs

- typedef float [Real](#)
Users can simply change this to build a double- or single-precision MTK.

Enumerations

- enum [MatrixStorage](#) { [DENSE](#), [BANDED](#), [CRS](#) }
Considered matrix storage schemes to implement sparse matrices.
- enum [MatrixOrdering](#) { [ROW_MAJOR](#), [COL_MAJOR](#) }
Considered matrix ordering (for Fortran purposes).
- enum [FieldNature](#) { [SCALAR](#), [VECTOR](#) }
Nature of the field discretized in a given grid.

Functions

- float [snrm2_](#) (int *n, [Real](#) *x, int *incx)
- void [sgemv_](#) (char *trans, int *m, int *n, [Real](#) *alpha, [Real](#) *a, int *lda, [Real](#) *x, int *incx, [Real](#) *beta, [Real](#) *y, int *incy)
- void [sgemm_](#) (char *transa, char *transb, int *m, int *n, int *k, [Real](#) *alpha, [Real](#) *a, int *lda, [Real](#) *b, aamm int *ldb, [Real](#) *beta, [Real](#) *c, int *ldc)
- std::ostream & [operator<<](#) (std::ostream &stream, [mtk::DenseMatrix](#) &in)
- std::ostream & [operator<<](#) (std::ostream &stream, [mtk::Div1D](#) &in)
- std::ostream & [operator<<](#) (std::ostream &stream, [mtk::Grad1D](#) &in)
- std::ostream & [operator<<](#) (std::ostream &stream, [mtk::Lap1D](#) &in)
- void [sgesv_](#) (int *n, int *nrhs, [Real](#) *a, int *lda, int *ipiv, [Real](#) *b, int *ldb, int *info)
- void [sgels_](#) (char *trans, int *m, int *n, int *nrhs, [Real](#) *a, int *lda, [Real](#) *b, int *ldb, [Real](#) *work, int *lwork, int *info)
Single-precision GEneral matrix Least Squares solver.
- void [sgeqrf_](#) (int *m, int *n, [Real](#) *a, int *lda, [Real](#) *tau, [Real](#) *work, int *lwork, int *info)
Single-precision GEneral matrix QR Factorization.
- void [sormqr_](#) (char *side, char *trans, int *m, int *n, int *k, [Real](#) *a, int *lda, [Real](#) *tau, [Real](#) *c, int *ldc, [Real](#) *work, int *lwork, int *info)
Single-precision Orthogonal [Matrix](#) from QR factorization.
- std::ostream & [operator<<](#) (std::ostream &stream, [mtk::UniStgGrid1D](#) &in)

Variables

- const float [kZero](#) {0.0f}
MTK's zero defined according to selective compilation.
- const float [kOne](#) {1.0f}
MTK's one defined according to selective compilation.
- const float [kDefaultTolerance](#) {1e-7f}
Considered tolerance for comparisons in numerical methods.
- const int [kDefaultOrderAccuracy](#) {2}
Default order of accuracy for mimetic operators.
- const float [kDefaultMimeticThreshold](#) {1.e-6f}
Default tolerance for higher-order mimetic operators.
- const int [kCriticalOrderAccuracyDiv](#) {8}
At this order (and higher) we must use the CBSA to construct.
- const int [kCriticalOrderAccuracyGrad](#) {10}
At this order (and higher) we must use the CBSA to construct.

15.1.1 Function Documentation

15.1.1.1 `std::ostream& mtk::operator<< (std::ostream & stream, mtk::UniStgGrid1D & in)`

1. Print spatial coordinates.

Definition at line 68 of file [mtk_uni_stg_grid_1d.cc](#).

15.1.1.2 `std::ostream& mtk::operator<< (std::ostream & stream, mtk::Lap1D & in)`


1. Print order of accuracy.
2. Print approximating coefficients for the interior.
3. No weights, thus print the mimetic boundary coefficients.

Definition at line 73 of file [mtk_lap_1d.cc](#).

15.1.1.3 `std::ostream& mtk::operator<< (std::ostream & stream, mtk::DenseMatrix & in)`

Definition at line 75 of file [mtk_dense_matrix.cc](#).

Here is the call graph for this function:



15.1.1.4 `std::ostream& mtk::operator<< (std::ostream & stream, mtk::Div1D & in)`

1. Print order of accuracy.
2. Print approximating coefficients for the interior.
3. Print mimetic weights.
4. Print mimetic approximations at the boundary.

Definition at line 79 of file [mtk_div_1d.cc](#).

15.1.1.5 `std::ostream& mtk::operator<< (std::ostream & stream, mtk::Grad1D & in)`

1. Print order of accuracy.
2. Print approximating coefficients for the interior.
3. Print mimetic weights.
4. Print mimetic approximations at the boundary.

Definition at line 79 of file [mtk_grad_1d.cc](#).

15.1.1.6 `void mtk::sgels_(char * trans, int * m, int * n, int * nrhs, Real * a, int * lda, Real * b, int * ldb, Real * work, int * lwork, int * info)`

SGELS solves overdetermined or underdetermined real linear systems involving an M-by-N matrix A, or its transpose, using a QR or LQ factorization of A. It is assumed that A has full rank.

The following options are provided:

1. If TRANS = 'N' and $m \geq n$: find the least squares solution of an overdetermined system, i.e., solve the least squares problem

$$\text{minimize } || B - A * X ||.$$

2. If TRANS = 'N' and $m < n$: find the minimum norm solution of an underdetermined system $A * X = B$.
3. If TRANS = 'T' and $m \geq n$: find the minimum norm solution of an undetermined system $A^{**T} * X = B$.
4. If TRANS = 'T' and $m < n$: find the least squares solution of an overdetermined system, i.e., solve the least squares problem

$$\text{minimize } || B - A^{**T} * X ||.$$

Several right hand side vectors *b* and solution vectors *x* can be handled in a single call; they are stored as the columns of the M-by-NRHS right hand side matrix B and the N-by-NRHS solution matrix X.

See Also


<http://www.math.utah.edu/software/lapack/lapack-s/sgels.html>

Parameters

<i>in</i>	<i>trans</i>	Am I giving the transpose of the matrix?
<i>in</i>	<i>m</i>	The number of rows of the matrix a. $m \geq 0$.
<i>in</i>	<i>n</i>	The number of columns of the matrix a. $n \geq 0$.
<i>in</i>	<i>nrhs</i>	The number of right-hand sides.
<i>in, out</i>	<i>a</i>	On entry, the m-by-n matrix a.
<i>in</i>	<i>lda</i>	The leading dimension of a. $lda \geq \max(1, m)$.
<i>in, out</i>	<i>b</i>	On entry, matrix b of right-hand side vectors.
<i>in</i>	<i>ldb</i>	The leading dimension of b. $ldb \geq \max(1, m, n)$.


<i>in, out</i>	<i>work</i>	On exit, if <i>info</i> = 0, <i>work</i> (1) is optimal <i>lwork</i> .
<i>in, out</i>	<i>lwork</i>	The dimension of the array <i>work</i> .
<i>in, out</i>	<i>info</i>	If <i>info</i> = 0, then successful exit.

Here is the caller graph for this function:




15.1.1.7 `void mtk::sgemm_ (char * transa, char * transb, int * m, int * n, int * k, Real * alpha, Real * a, int * lda, Real * b, aamm int * ldb, Real * beta, Real * c, int * ldc)`

Here is the caller graph for this function:



15.1.1.8 `void mtk::sgemv_ (char * trans, int * m, int * n, Real * alpha, Real * a, int * lda, Real * x, int * incx, Real * beta, Real * y, int * incy)`

Here is the caller graph for this function:



15.1.1.9 void mtk::sgeqrf_ (int * *m*, int * *n*, Real * *a*, int * *lda*, Real * *tau*, Real * *work*, int * *lwork*, int * *info*)

Single-Precision Orthogonal Make Q from QR: dormqr_ overwrites the general real M-by-N matrix C with (Table 1):

SIDE = 'L' SIDE = 'R'

TRANS = 'N': $Q * C * C * Q$ TRANS = 'T': $Q^{**T} * C * C * Q^{**T}$

where Q is a real orthogonal matrix defined as the product of k elementary reflectors

$$Q = H(1) H(2) \dots H(k)$$

as returned by SGEQRF. Q is of order M if SIDE = 'L' and of order N if SIDE = 'R'.

See Also

http://www.netlib.org/lapack/explore-html/df/d97/sgeqrf_8f.html


Parameters

in	<i>m</i>	The number of columns of the matrix a. $n \geq 0$.
in	<i>n</i>	The number of columns of the matrix a. $n \geq 0$.
in, out	<i>a</i>	On entry, the n-by-n matrix a.
in	<i>lda</i>	Leading dimension matrix. $LDA \geq \max(1, M)$.
in, out	<i>tau</i>	Scalars from elementary reflectors. $\min(M, N)$.
in, out	<i>work</i>	Workspace. $info = 0$, $work(1)$ is optimal $lwork$.
in	<i>lwork</i>	The dimension of work. $lwork \geq \max(1, n)$.
in	<i>info</i>	$info = 0$: successful exit.

15.1.1.10 void mtk::sgesv_ (int * *n*, int * *nrhs*, Real * *a*, int * *lda*, int * *ipiv*, Real * *b*, int * *ldb*, int * *info*)

15.1.1.11 float mtk::snrm2_ (int * *n*, Real * *x*, int * *incx*)

Here is the caller graph for this function:



15.1.1.12 void mtk::sormqr_ (char * *side*, char * *trans*, int * *m*, int * *n*, int * *k*, Real * *a*, int * *lda*, Real * *tau*, Real * *c*, int * *ldc*, Real * *work*, int * *lwork*, int * *info*)

Single-Precision Orthogonal Make Q from QR: sormqr_ overwrites the general real M-by-N matrix C with (Table 1):

SIDE = 'L' SIDE = 'R'

TRANS = 'N': $Q * C * C * Q$ TRANS = 'T': $Q^{**T} * C * C * Q^{**T}$

where Q is a real orthogonal matrix defined as the product of k elementary reflectors

$$Q = H(1) \ H(2) \ \dots \ H(k)$$

as returned by SGEQRF. Q is of order M if SIDE = 'L' and of order N if SIDE = 'R'.

See Also

http://www.netlib.org/lapack/explore-html/d0/d98/sormqr_8f_source.html

Parameters

in	<i>side</i>	See Table 1 above.
in	<i>trans</i>	See Table 1 above.
in	<i>m</i>	Number of rows of the C matrix.
in	<i>n</i>	Number of columns of the C matrix.
in	<i>k</i>	Number of reflectors.
in, out	<i>a</i>	The matrix containing the reflectors.
in	<i>lda</i>	The dimension of work. lwork >= max(1,n).
in	<i>tau</i>	Scalar factors of the elementary reflectors.
in	<i>c</i>	Output matrix.
in	<i>ldc</i>	Leading dimension of the output matrix.
in, out	<i>work</i>	Workspace. info = 0, work(1) optimal lwork.
in	<i>lwork</i>	The dimension of work.
in, out	<i>info</i>	info = 0: successful exit.

Chapter 16


Class Documentation

16.1 mtk::BLASAdapter Class Reference

Adapter class for the BLAS API.

```
#include <mtk_blas_adapter.h>
```

Collaboration diagram for mtk::BLASAdapter:



Static Public Member Functions

- static `Real RealINRM2 (Real *in, int &in_length)`
Compute the $\|\mathbf{x}\|_2$ of given array \mathbf{x} .
- static void `RealDenseMV (Real &alpha, DenseMatrix &aa, Real *xx, Real &beta, Real *yy)`
Real-Arithmetic General (Dense matrices) Matrix-Vector Multiplier.
- static `DenseMatrix RealDenseMM (DenseMatrix &aa, DenseMatrix &bb)`
Real-Arithmetic General (Dense matrices) Matrix-Matrix multiplier.

16.1.1 Detailed Description

This class contains a collection of static classes, that posses direct access to the underlying structure of the matrices, thus allowing programmers to exploit some of the numerical methods implemented in the BLAS.

The **BLAS (Basic Linear Algebra Subprograms)** are routines that provide standard building blocks for performing basic vector and matrix operations. The Level 1 BLAS perform scalar, vector and vector-vector operations, the Level 2 BLAS perform matrix-vector operations, and the Level 3 BLAS perform matrix-matrix operations.

See Also

<http://www.netlib.org/blas/>

Definition at line 96 of file [mtk_blas_adapter.h](#).

16.1.2 Member Function Documentation

16.1.2.1 **mtk::DenseMatrix mtk::BLASAdapter::RealDenseMM (mtk::DenseMatrix & *aa*, mtk::DenseMatrix & *bb*)**
[static]

Performs:

$$\mathbf{C} := \mathbf{AB}$$

Parameters


in	<i>aa</i>	First matrix.
in	<i>bb</i>	Second matrix.

See Also


<http://ejspeiro.github.io/Netlib-and-CPP/>

Definition at line 318 of file [mtk_blas_adapter.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



16.1.2.2 `void mtk::BLASAdapter::RealDenseMV (mtk::Real & alpha, mtk::DenseMatrix & aa, mtk::Real * xx, mtk::Real & beta, mtk::Real * yy) [static]`

Performs

$$\mathbf{y} := \alpha \mathbf{A} \mathbf{x} + \beta \mathbf{y}$$

Parameters


in	<i>alpha</i>	First scalar.
in	<i>aa</i>	Given matrix.
in	<i>xx</i>	First vector.
in	<i>beta</i>	Second scalar.
in, out	<i>yy</i>	Second vector (output).

See Also


<http://ejspeiro.github.io/Netlib-and-CPP/>

Definition at line 287 of file [mtk_blas_adapter.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



16.1.2.3 `mtk::Real mtk::BLASAdapter::RealNRM2 (Real * in, int & in_length) [static]`

Parameters


<i>in</i>	<i>in</i>	Input array.
<i>in</i>	<i>in_length</i>	Length of the array.

Definition at line 276 of file [mtk_blas_adapter.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



The documentation for this class was generated from the following files:


- [include/mtk_blas_adapter.h](#)
- [src/mtk_blas_adapter.cc](#)

16.2 mtk::DenseMatrix Class Reference

Defines a common dense matrix, using a 1D array.

```
#include <mtk_dense_matrix.h>
```

Collaboration diagram for mtk::DenseMatrix:



Public Member Functions

- [DenseMatrix](#) & `operator=` (const [DenseMatrix](#) &in)

- Overloaded assignment operator.*
- [DenseMatrix](#) ()
 - Default constructor.*
- [DenseMatrix](#) (const [DenseMatrix](#) &in)
 - Copy constructor.*
- [DenseMatrix](#) (const int &num_rows, const int &num_cols)
 - Construct a dense matrix based on the given dimensions.*
- [DenseMatrix](#) (const int &rank, const bool &padded, const bool &transpose)
 - Construct a zero-rows-padded identity matrix.*
- [DenseMatrix](#) (const [Real](#) *gen, const int &gen_length, const int &pro_length, const bool &transpose)
 - Construct a dense Vandermonde matrix.*
- [~DenseMatrix](#) ()
 - Destructor.*
- [Matrix matrix_properties](#) () const
 - Provides access to the matrix data.*
- int [num_rows](#) () const
 - Gets the number of rows.*
- int [num_cols](#) () const
 - Gets the number of columns.*
- [Real](#) * [data](#) () const
 - Provides access to the matrix value array.*
- void [SetOrdering](#) ([mtk::MatrixOrdering](#) oo)
 - Sets the ordering of the matrix.*
- [Real](#) [GetValue](#) (const int &row_coord, const int &col_coord) const
 - Gets a value on the given coordinates.*
- void [SetValue](#) (const int &row_coord, const int &col_coord, const [Real](#) &val)
 - Sets a value on the given coordinates.*
- void [Transpose](#) ()
 - Transpose this matrix.*
- void [OrderRowMajor](#) ()
 - Make the matrix row-wise ordered.*
- void [OrderColMajor](#) ()
 - Make the matrix column-wise ordered.*

Static Public Member Functions

- static [DenseMatrix](#) [Kron](#) (const [DenseMatrix](#) &aa, const [DenseMatrix](#) &bb)
 - Construct a dense matrix based on the Kronecker product of arguments.*

Private Attributes

- [Matrix matrix_properties_](#)
 - Data related to the matrix nature.*
- [Real](#) * [data_](#)
 - Array holding the data in contiguous position in memory.*

Friends

- `std::ostream & operator<< (std::ostream &stream, DenseMatrix &in)`

Prints the matrix as a block of numbers (standard way).

16.2.1 Detailed Description

For developing purposes, it is better to have a not-so-intricated data structure implementing matrices. This is the purpose of this class: to be used for prototypes of new code for small test cases. In every other instance, this should be replaced by the most appropriate sparse matrix.


Definition at line 98 of file [mtk_dense_matrix.h](#).

16.2.2 Constructor & Destructor Documentation

16.2.2.1 `mtk::DenseMatrix::DenseMatrix ()`

Definition at line 138 of file [mtk_dense_matrix.cc](#).

Here is the call graph for this function:




16.2.2.2 `mtk::DenseMatrix::DenseMatrix (const DenseMatrix &in)`

Parameters

<code>in</code>	<code>in</code>	Given matrix.
-----------------	-----------------	---------------

Definition at line 144 of file [mtk_dense_matrix.cc](#).

Here is the call graph for this function:



16.2.2.3 mtk::DenseMatrix::DenseMatrix (const int & num_rows, const int & num_cols)

Parameters

in	<i>num_rows</i>	Number of rows of the required matrix.
in	<i>num_cols</i>	Number of rows of the required matrix.

Exceptions

<i>std::bad_alloc</i>	
-----------------------	--

Definition at line 177 of file [mtk_dense_matrix.cc](#).

Here is the call graph for this function:



16.2.2.4 mtk::DenseMatrix::DenseMatrix (const int & *rank*, const bool & *padded*, const bool & *transpose*)

Used in the construction of the mimetic operators.

Def**. A **padded matrix** is a matrix with its first and last rows initialized to only zero values:

$$\bar{\mathbf{I}} = \begin{pmatrix} 0 & 0 & 0 & \dots & 0 \\ 1 & 0 & 0 & \dots & 0 \\ 0 & 1 & 0 & \dots & 0 \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & 0 & \dots & 1 \\ 0 & 0 & 0 & \dots & 0 \end{pmatrix}$$

Parameters

in	<i>rank</i>	Rank or number of rows/cols in square matrix.
in	<i>padded</i>	Should it be padded?
in	<i>transpose</i>	Should I return the transpose of the requested matrix?

Exceptions

<i>std::bad_alloc</i>	
-----------------------	--

Definition at line 199 of file [mtk_dense_matrix.cc](#).

Here is the call graph for this function:



16.2.2.5 mtk::DenseMatrix::DenseMatrix (const Real * *gen*, const int & *gen_length*, const int & *pro_length*, const bool & *transpose*)

Def**. In linear algebra, a **Vandermonde matrix** is a matrix with terms of a geometric progression in each row. This progression uses the terms of a given **generator vector**:

$$\mathbf{V} = \begin{pmatrix} 1 & \alpha_1 & \alpha_1^2 & \dots & \alpha_1^{n-1} \\ 1 & \alpha_2 & \alpha_2^2 & \dots & \alpha_2^{n-1} \\ 1 & \alpha_3 & \alpha_3^2 & \dots & \alpha_3^{n-1} \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 1 & \alpha_m & \alpha_m^2 & \dots & \alpha_m^{n-1} \end{pmatrix}$$

This constructor generates a Vandermonde matrix, as defined above.

Obs**. It is important to understand that the generator vectors to be used are nothing but a very particular instance of a grid. These are little chunks, little samples, if you will, of a grid which is rectangular and uniform. So the selected samples, on the [mtk::Div1D](#) and [mtk::Grad1D](#), basically represent the entire space, the entire grid. This is why neither the CRS nor the CBS algorithms may work for irregular geometries, such as curvilinear grids.

Parameters


in	<i>gen</i>	Given generator vector.
in	<i>gen_length</i>	Length generator vector.
in	<i>pro_length</i>	Length the progression.
in	<i>transpose</i>	Should the transpose be created instead?

Exceptions

<i>std::bad_alloc</i>	
-----------------------	--

Definition at line [237](#) of file [mtk_dense_matrix.cc](#).

Here is the call graph for this function:



16.2.2.6 mtk::DenseMatrix::~~DenseMatrix ()

Definition at line [285](#) of file [mtk_dense_matrix.cc](#).

16.2.3 Member Function Documentation


16.2.3.1 mtk::Real * mtk::DenseMatrix::data () const

Returns

Pointer to an array of [mtk::Real](#).

Definition at line 316 of file [mtk_dense_matrix.cc](#).

Here is the caller graph for this function:



16.2.3.2 `mtk::Real mtk::DenseMatrix::GetValue (const int & row_coord, const int & col_coord) const`

Parameters


in	<i>row_coord</i>	Row coordinate.
in	<i>col_coord</i>	Column coordinate.

Returns


The required value at the specified coordinates.

Definition at line 321 of file [mtk_dense_matrix.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



16.2.3.3 mtk::DenseMatrix mtk::DenseMatrix::Kron (const DenseMatrix & *aa*, const DenseMatrix & *bb*) [static]

Parameters


in	<i>aa</i>	First matrix.
in	<i>bb</i>	Second matrix.

Exceptions

<i>std::bad_alloc</i>

Definition at line 463 of file [mtk_dense_matrix.cc](#).

Here is the call graph for this function:




16.2.3.4 `mtk::Matrix mtk::DenseMatrix::matrix_properties () const`

Returns

Pointer to a [Matrix](#).

Definition at line 291 of file [mtk_dense_matrix.cc](#).

Here is the caller graph for this function:




16.2.3.5 `int mtk::DenseMatrix::num_cols () const`

Returns

Number of columns of the matrix.

Definition at line 311 of file [mtk_dense_matrix.cc](#).

Here is the caller graph for this function:




16.2.3.6 int mtk::DenseMatrix::num_rows () const

Returns

Number of rows of the matrix.

Definition at line 306 of file [mtk_dense_matrix.cc](#).


Here is the caller graph for this function:



16.2.3.7 mtk::DenseMatrix & mtk::DenseMatrix::operator= (const DenseMatrix & in)

Definition at line 97 of file [mtk_dense_matrix.cc](#).

Here is the call graph for this function:



16.2.3.8 `void mtk::DenseMatrix::OrderColMajor ()`

Todo Improve this so that no new arrays have to be created.


Definition at line 424 of file `mtk_dense_matrix.cc`.

16.2.3.9 `void mtk::DenseMatrix::OrderRowMajor ()`

Todo Improve this so that no new arrays have to be created.

Definition at line 383 of file `mtk_dense_matrix.cc`.

Here is the caller graph for this function:



16.2.3.10 void mtk::DenseMatrix::SetOrdering (mtk::MatrixOrdering oo)

Parameters


in	oo	Ordering.
----	----	-----------

Returns


The required value at the specified coordinates.

Definition at line 296 of file [mtk_dense_matrix.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:




16.2.3.11 void mtk::DenseMatrix::SetValue (const int & *row_coord*, const int & *col_coord*, const Real & *val*)

Parameters


in	<i>row_coord</i>	Row coordinate.
in	<i>col_coord</i>	Column coordinate.
in	<i>val</i>	Row Actual value to be inserted.

Definition at line 333 of file [mtk_dense_matrix.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:




16.2.3.12 void mtk::DenseMatrix::Transpose ()

Todo Improve this so that no extra arrays have to be created.

Definition at line 346 of file [mtk_dense_matrix.cc](#).

Here is the caller graph for this function:



16.2.4 Friends And Related Function Documentation

16.2.4.1 `std::ostream& operator<< (std::ostream & stream, mtk::DenseMatrix & in)` `[friend]`

Definition at line 75 of file [mtk_dense_matrix.cc](#).

16.2.5 Member Data Documentation

16.2.5.1 `Real* mtk::DenseMatrix::data_` `[private]`

Definition at line 274 of file [mtk_dense_matrix.h](#).

16.2.5.2 `Matrix mtk::DenseMatrix::matrix_properties_` `[private]`

Definition at line 272 of file [mtk_dense_matrix.h](#).

The documentation for this class was generated from the following files:


- [include/mtk_dense_matrix.h](#)
- [src/mtk_dense_matrix.cc](#)

16.3 mtk::Div1D Class Reference

Implements a 1D mimetic divergence operator.

```
#include <mtk_div_1d.h>
```


Collaboration diagram for mtk::Div1D:



Public Member Functions

- [Div1D \(\)](#)

- *Default constructor.*
- [Div1D](#) (const [Div1D](#) &div)
- *Copy constructor.*
- [~Div1D](#) ()
- *Destructor.*
- bool [ConstructDiv1D](#) (int order_accuracy=[kDefaultOrderAccuracy](#), [Real](#) mimetic_threshold=[kDefaultMimetic-Threshold](#))
- *Factory method implementing the CBS Algorithm to build operator.*
- int [num_bndy_coefs](#) ()
- *Returns how many coefficients are approximating at the boundary.*
- [Real](#) * [weights_crs](#) (void)
- *Return collection of weights as computed by the CRSA.*
- [Real](#) * [weights_cbs](#) (void)
- *Return collection of weights as computed by the CBSA.*
- [DenseMatrix](#) [ReturnAsDenseMatrix](#) (const [UniStgGrid1D](#) &grid)
- *Return the operator as a dense matrix.*

Private Member Functions

- bool [ComputeStencilInteriorGrid](#) (void)
- *Stage 1 of the CBS Algorithm.*
- bool [ComputeRationalBasisNullSpace](#) (void)
- *Stage 2.1 of the CBS Algorithm.*
- bool [ComputePreliminaryApproximations](#) (void)
- *Stage 2.2 of the CBS Algorithm.*
- bool [ComputeWeights](#) (void)
- *Stage 2.3 of the CBS Algorithm.*
- bool [ComputeStencilBoundaryGrid](#) (void)
- *Stage 2.4 of the CBS Algorithm.*
- bool [AssembleOperator](#) (void)
- *Stage 3 of the CBS Algorithm.*

Private Attributes

- int [order_accuracy_](#)
- *Order of numerical accuracy of the operator.*
- int [dim_null_](#)
- *Dim. null-space for boundary approximations.*
- int [num_bndy_coefs_](#)
- *Req. coeffs. per bndy pt. uni. order accuracy.*
- int [divergence_length_](#)
- *Length of the output array.*
- int [minrow_](#)
- *Row from the optimizer with the minimum rel. nor.*
- int [row_](#)
- *Row currently processed by the optimizer.*
- [mtk::DenseMatrix](#) [rat_basis_null_space_](#)

Rational b. null-space w. bndy.

- [Real * coeffs_interior_](#)

Interior stencil.

- [Real * prem_apps_](#)

2D array of boundary preliminary approximations.

- [Real * weights_crs_](#)

Array containing weights from CRSA.

- [Real * weights_cbs_](#)

Array containing weights from CBSA.

- [Real * mim_bndy_](#)

Array containing mimetic boundary approximations.

- [Real * divergence_](#)

Output array containing the operator and weights.

- [Real mimetic_threshold_](#)

< Mimetic threshold.

Friends

- `std::ostream & operator<< (std::ostream &stream, Div1D &in)`

Output stream operator for printing.

16.3.1 Detailed Description

This class implements a 1D divergence operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (CBSA).

Definition at line 81 of file [mtk_div_1d.h](#).

16.3.2 Constructor & Destructor Documentation

16.3.2.1 `mtk::Div1D::Div1D ()`

Definition at line 125 of file [mtk_div_1d.cc](#).

16.3.2.2 `mtk::Div1D::Div1D (const Div1D &div)`

Parameters

<code>in</code>	<code>div</code>	Given divergence.
-----------------	------------------	-------------------

Definition at line 140 of file [mtk_div_1d.cc](#).

16.3.2.3 `mtk::Div1D::~~Div1D ()`

Definition at line 155 of file [mtk_div_1d.cc](#).

16.3.3 Member Function Documentation

16.3.3.1 `bool mtk::Div1D::AssembleOperator (void) [private]`

Construct the output array with the operator and its weights.

1. The first entry of the array will contain the order of accuracy.
2. The second entry the collection of coefficients for interior of grid.
3. IF `order_accuracy_ > 2`, then third entry is the collection of weights.
4. IF `order_accuracy_ > 2`, next `dim_null_entries` is approximating coefficients for the west boundary of the grid.

Definition at line 1311 of file [mtk_div_1d.cc](#).


16.3.3.2 `bool mtk::Div1D::ComputePreliminaryApproximations (void) [private]`

Compute the set of preliminary approximations on the boundary neighborhood.

1. Create generator vector for the first approximation.
2. Compute the `dim_null` near-the-boundary columns of the pi matrix.
3. Create the Vandermonde matrix for this iteration.
4. New order-selector vector (gets re-written with LAPACK solutions).
5. Solving $TT*rr = ob$ yields the columns `rr` of the `KK` matrix.
6. Scale the `KK` matrix to make it a rational basis for null-space.
7. Extract the last `dim_null` values of the pre-scaled `ob`.
8. Once we posses the bottom elements, we proceed with the scaling.

Definition at line 667 of file [mtk_div_1d.cc](#).

Here is the call graph for this function:




16.3.3.3 bool mtk::Div1D::ComputeRationalBasisNullSpace (void) [private]

Compute a rational basis for the null-space of the Vandermonde matrix approximating at the west boundary.

1. Create generator vector for the first approximation.
2. Create Vandermonde matrix.
3. QR-factorize the Vandermonde matrix.
4. Extract the basis for the null-space from Q matrix.
5. Scale null-space to make it rational.

Definition at line 491 of file [mtk_div_1d.cc](#).

Here is the call graph for this function:



16.3.3.4 bool mtk::Div1D::ComputeStencilBoundaryGrid (void) [private]

Compute mimetic stencil approximating at boundary.

1. Collect lambda values.
2. Compute alpha values.
3. Compute the mimetic boundary approximations.

Definition at line 1212 of file [mtk_div_1d.cc](#).

16.3.3.5 bool mtk::Div1D::ComputeStencilInteriorGrid (void) [private]


Compute the stencil approximating the interior of the staggered grid.

1. Create vector for interior spatial coordinates.

2. Create Vandermonde matrix (using interior coordinates as generator).
3. Create order-selector vector.
4. Solve dense Vandermonde system to attain the interior coefficients.

Definition at line 392 of file [mtk_div_1d.cc](#).

Here is the call graph for this function:




16.3.3.6 `bool mtk::Div1D::ComputeWeights (void) [private]`

Compute the set of mimetic weights to impose the mimetic condition.

1. Construct the \mathbf{M} matrix.
2. Use interior stencil to build proper RHS vector \mathbf{h} .
3. Get weights (as **CRSA**): $\mathbf{M}\mathbf{q} = \mathbf{h}$.
4. If required order is greater than critical order, start the **CBSA**.
5. Create \mathbf{M} matrix from \mathbf{M} .
6. Prepare constraint vector as in the CBSA: \mathbf{c} .
7. Brute force search through all the rows of the Φ matrix.
8. Apply solution found from brute force search.

Definition at line 887 of file [mtk_div_1d.cc](#).

Here is the call graph for this function:



16.3.3.7 `bool mtk::Div1D::ConstructDiv1D (int order_accuracy = kDefaultOrderAccuracy, mtk::Real mimetic_threshold = kDefaultMimeticThreshold)`

Returns

Success of the construction.

1. Compute stencil for the interior cells.
2. Compute a rational basis for the null-space for the first matrix.
3. Compute preliminary approximation (non-mimetic) on the boundaries.
4. Compute quadrature weights to impose the mimetic conditions.
5. Compute real approximation (mimetic) on the boundaries.
6. Assemble operator.

Definition at line 176 of file [mtk_div_1d.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



16.3.3.8 `int mtk::Div1D::num_bndy_coeffs ()`

Returns

How many coefficients are approximating at the boundary.

Definition at line 315 of file [mtk_div_1d.cc](#).

16.3.3.9 `mtk::DenseMatrix mtk::Div1D::ReturnAsDenseMatrix (const UniStgGrid1D & grid)`


Returns

The operator as a dense matrix.

1. Insert mimetic boundary at the west.
2. Insert coefficients for the interior of the grid.
3. Impose center-skew symmetry by permuting the mimetic boundaries.

Definition at line 330 of file [mtk_div_1d.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



16.3.3.10 `mtk::Real * mtk::Div1D::weights_cbs (void)`

Returns

Collection of weights as computed by the CBSA.

Definition at line 325 of file [mtk_div_1d.cc](#).

16.3.3.11 `mtk::Real * mtk::Div1D::weights_crs (void)`

Returns

Collection of weights as computed by the CRSA.

Definition at line 320 of file [mtk_div_1d.cc](#).

16.3.4 Friends And Related Function Documentation

16.3.4.1 `std::ostream& operator<< (std::ostream & stream, mtk::Div1D & in)` `[friend]`

1. Print order of accuracy.
2. Print approximating coefficients for the interior.
3. Print mimetic weights.
4. Print mimetic approximations at the boundary.

Definition at line 79 of file [mtk_div_1d.cc](#).

16.3.5 Member Data Documentation

16.3.5.1 `Real* mtk::Div1D::coeffs_interior_` `[private]`

Definition at line 189 of file [mtk_div_1d.h](#).

16.3.5.2 `int mtk::Div1D::dim_null_` `[private]`

Definition at line 180 of file [mtk_div_1d.h](#).

16.3.5.3 `Real* mtk::Div1D::divergence_` `[private]`

Definition at line 194 of file [mtk_div_1d.h](#).

16.3.5.4 `int mtk::Div1D::divergence_length_` `[private]`

Definition at line 182 of file [mtk_div_1d.h](#).

16.3.5.5 `Real* mtk::Div1D::mim_bndy_` `[private]`

Definition at line 193 of file [mtk_div_1d.h](#).

16.3.5.6 `Real mtk::Div1D::mimetic_threshold_` `[private]`

Definition at line 196 of file [mtk_div_1d.h](#).

16.3.5.7 `int mtk::Div1D::minrow_` `[private]`

Definition at line 184 of file [mtk_div_1d.h](#).

16.3.5.8 `int mtk::Div1D::num_bndy_coeffs_ [private]`

Definition at line 181 of file [mtk_div_1d.h](#).

16.3.5.9 `int mtk::Div1D::order_accuracy_ [private]`

Definition at line 179 of file [mtk_div_1d.h](#).

16.3.5.10 `Real* mtk::Div1D::prem_apps_ [private]`

Definition at line 190 of file [mtk_div_1d.h](#).

16.3.5.11 `mtk::DenseMatrix mtk::Div1D::rat_basis_null_space_ [private]`

Definition at line 187 of file [mtk_div_1d.h](#).

16.3.5.12 `int mtk::Div1D::row_ [private]`

Definition at line 185 of file [mtk_div_1d.h](#).

16.3.5.13 `Real* mtk::Div1D::weights_cbs_ [private]`

Definition at line 192 of file [mtk_div_1d.h](#).

16.3.5.14 `Real* mtk::Div1D::weights_crs_ [private]`

Definition at line 191 of file [mtk_div_1d.h](#).

The documentation for this class was generated from the following files:


- [include/mtk_div_1d.h](#)
- [src/mtk_div_1d.cc](#)

16.4 mtk::GLPKAdapter Class Reference

Adapter class for the GLPK API.

```
#include <mtk_glpk_adapter.h>
```

Collaboration diagram for mtk::GLPKAdapter:



Static Public Member Functions

- static `mtk::Real SolveSimplexAndCompare (mtk::Real *A, int nrows, int ncols, int kk, mtk::Real *hh, mtk::Real *qq, int robjective, mtk::Real mimetic_tol, int copy)`
Solves a CLO problem and compares the solution to a reference solution.

16.4.1 Detailed Description

This class contains a collection of static classes, that posses direct access to the underlying structure of the matrices, thus allowing programmers to exploit some of the numerical methods implemented in the GLPK.

The **GLPK (GNU Linear Programming Kit)** package is intended for solving large-scale linear programming (LP), mixed integer programming (MIP), and other related problems. It is a set of routines written in ANSI C and organized in the form of a callable library.

Warning

We use the GLPK temporarily in order to test the CBSA, but it will be removed due to licensing issues.

See Also

<http://www.gnu.org/software/glpk/>

Todo Rescind from the GLPK as the numerical core for CLO problems.

Definition at line 101 of file `mtk_glpk_adapter.h`.

16.4.2 Member Function Documentation

- 16.4.2.1 `mtk::Real mtk::GLPKAdapter::SolveSimplexAndCompare (mtk::Real * A, int nrows, int ncols, int kk, mtk::Real * hh, mtk::Real * qq, int robjective, mtk::Real mimetic_tol, int copy) [static]`

This routine is the pivot of the CBSA. It solves a Constrained Linear Optimization (CLO) problem, and it compares the attained solution to a given reference solution. This comparison is done computing the norm-2 relative error.

Parameters

in	<i>alpha</i>	First scalar.
in	<i>AA</i>	Given matrix.
in	<i>xx</i>	First vector.
in	<i>beta</i>	Second scalar.
in	<i>beta</i>	Second scalar.
in, out	<i>yy</i>	Second vector (output).
in	<i>xx</i>	First vector.
in	<i>beta</i>	Second scalar.
in	<i>beta</i>	Second scalar.


Warning

GLPK indexes in $[1,n]$, so we must get the extra space needed.


1. Memory allocation.
2. Fill the problem.
3. Copy the row to the vector objective.
4. Forming the RHS.
5. Setting up the objective function.
6. Setting up constraints.
7. Copy the matrix minus the row objective to the glpk problem.
8. Solve problem.

Definition at line 78 of file [mtk_glpk_adapter.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



The documentation for this class was generated from the following files:

- [include/mtk_glpk_adapter.h](#)


- [src/mtk_glpk_adapter.cc](#)

16.5 mtk::Grad1D Class Reference

Implements a 1D mimetic gradient operator.

```
#include <mtk_grad_1d.h>
```

Collaboration diagram for mtk::Grad1D:



Public Member Functions

- [Grad1D \(\)](#)

- *Default constructor.*
- [Grad1D](#) (const [Grad1D](#) &grad)
- *Copy constructor.*
- [~Grad1D](#) ()
- *Destructor.*
- bool [ConstructGrad1D](#) (int order_accuracy=[kDefaultOrderAccuracy](#), [Real](#) mimetic_threshold=[kDefaultMimeticThreshold](#))
- *Factory method implementing the CBS Algorithm to build operator.*
- int [num_bndy_coeffs](#) ()
- *Returns how many coefficients are approximating at the boundary.*
- [Real](#) * [weights_crs](#) (void)
- *Returns collection of weights as computed by the CRSA.*
- [Real](#) * [weights_cbs](#) (void)
- *Returns collection of weights as computed by the CBSA.*
- [DenseMatrix](#) [ReturnAsDenseMatrix](#) (const [UniStgGrid1D](#) &grid)
- *Returns the operator as a dense matrix.*

Private Member Functions

- bool [ComputeStencilInteriorGrid](#) (void)
- *Stage 1 of the CBS Algorithm.*
- bool [ComputeRationalBasisNullSpace](#) (void)
- *Stage 2.1 of the CBS Algorithm.*
- bool [ComputePreliminaryApproximations](#) (void)
- *Stage 2.2 of the CBS Algorithm.*
- bool [ComputeWeights](#) (void)
- *Stage 2.3 of the CBS Algorithm.*
- bool [ComputeStencilBoundaryGrid](#) (void)
- *Stage 2.4 of the CBS Algorithm.*
- bool [AssembleOperator](#) (void)
- *Stage 3 of the CBS Algorithm.*

Private Attributes

- int [order_accuracy_](#)
- *Order of numerical accuracy of the operator.*
- int [dim_null_](#)
- *Dim. null-space for boundary approximations.*
- int [num_bndy_approxs_](#)
- *Req. approximations at and near the boundary.*
- int [num_bndy_coeffs_](#)
- *Req. coeffs. per bndy pt. uni. order accuracy.*
- int [gradient_length_](#)
- *Length of the output array.*
- int [minrow_](#)
- *Row from the optimizer with the minimum rel. nor.*
- int [row_](#)

- *Row currently processed by the optimizer.*
- [mtk::DenseMatrix rat_basis_null_space_](#)
Rational b. null-space w. bndy.
- [Real * coeffs_interior_](#)
Interior stencil.
- [Real * prem_apps_](#)
2D array of boundary preliminary approximations.
- [Real * weights_crs_](#)
Array containing weights from CRSA.
- [Real * weights_cbs_](#)
Array containing weights from CBSA.
- [Real * mim_bndy_](#)
Array containing mimetic boundary approximations.
- [Real * gradient_](#)
Output array containing the operator and weights.
- [Real mimetic_threshold_](#)
< Mimetic threshold.

Friends

- `std::ostream & operator<< (std::ostream &stream, Grad1D &in)`
Output stream operator for printing.

16.5.1 Detailed Description

This class implements a 1D gradient operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (CB-SA).

Definition at line 81 of file [mtk_grad_1d.h](#).

16.5.2 Constructor & Destructor Documentation

16.5.2.1 `mtk::Grad1D::Grad1D ()`

Definition at line 129 of file [mtk_grad_1d.cc](#).

16.5.2.2 `mtk::Grad1D::Grad1D (const Grad1D &grad)`

Parameters

<code>in</code>	<code>div</code>	Given divergence.
-----------------	------------------	-------------------

Definition at line 145 of file [mtk_grad_1d.cc](#).

16.5.2.3 `mtk::Grad1D::~~Grad1D ()`

Definition at line 161 of file [mtk_grad_1d.cc](#).

16.5.3 Member Function Documentation

16.5.3.1 `bool mtk::Grad1D::AssembleOperator (void) [private]`

Construct the output array with the operator and its weights.

1. The first entry of the array will contain the order of accuracy.
2. The second entry of the array will contain the collection of approximating coefficients for the interior of the grid.
3. The third entry will contain the collection of weights.
4. The next `dim_null + 1` entries will contain the collections of approximating coefficients for the west boundary of the grid.

Definition at line 1349 of file [mtk_grad_1d.cc](#).


16.5.3.2 `bool mtk::Grad1D::ComputePreliminaryApproximations (void) [private]`

Compute the set of preliminary approximations on the boundary neighborhood.

1. Create generator vector for the first approximation.
2. Compute the `dim_null` near-the-boundary columns of the pi matrix.
3. Create the Vandermonde matrix for this iteration.
4. New order-selector vector (gets re-written with LAPACK solutions).
5. Solving $TT*rr = ob$ yields the columns `rr` of the `kk` matrix.
6. Scale the `kk` matrix to make it a rational basis for null-space.
7. Extract the last `dim_null` values of the pre-scaled `ob`.
8. Once we posses the bottom elements, we proceed with the scaling.

Definition at line 685 of file [mtk_grad_1d.cc](#).

Here is the call graph for this function:




16.5.3.3 `bool mtk::Grad1D::ComputeRationalBasisNullSpace (void) [private]`

Compute a rational basis for the null-space of the Vandermonde matrix approximating at the west boundary.

1. Create generator vector for the first approximation.
2. Create Vandermonde matrix.
3. QR-factorize the Vandermonde matrix.
4. Extract the basis for the null-space from Q matrix.
5. Scale null-space to make it rational.

Definition at line 502 of file [mtk_grad_1d.cc](#).

Here is the call graph for this function:



16.5.3.4 `bool mtk::Grad1D::ComputeStencilBoundaryGrid (void) [private]`

Compute mimetic stencil approximating at boundary.

1. Collect lambda values.
2. Compute alpha values.
3. Compute the mimetic boundary approximations.

Definition at line 1243 of file [mtk_grad_1d.cc](#).

16.5.3.5 `bool mtk::Grad1D::ComputeStencilInteriorGrid (void) [private]`

Compute the stencil approximating the interior of the staggered grid.

1. Create vector for interior spatial coordinates.

2. Create Vandermonde matrix (using interior coordinates as generator).
3. Create order-selector vector.
4. Solve dense Vandermonde system to attain the interior coefficients.

Definition at line 406 of file [mtk_grad_1d.cc](#).

Here is the call graph for this function:




16.5.3.6 bool mtk::Grad1D::ComputeWeights (void) [private]

Compute the set of mimetic weights to impose the mimetic condition.

1. Construct the \mathbf{M} matrix.
2. Use interior stencil to build proper RHS vector \mathbf{h} .
3. Get weights (as **CRSA**): $\mathbf{M}\mathbf{q} = \mathbf{h}$.
4. If required order is greater than critical order, start the **CBSA**.
5. Create \mathbf{M} matrix from \mathbf{M} .
6. Prepare constraint vector as in the CBSA: \mathbf{c} .
7. Brute force search through all the rows of the Φ matrix.
8. Apply solution found from brute force search.

Definition at line 905 of file [mtk_grad_1d.cc](#).

Here is the call graph for this function:



16.5.3.7 `bool mtk::Grad1D::ConstructGrad1D (int order_accuracy = kDefaultOrderAccuracy, Real mimetic_threshold = kDefaultMimeticThreshold)`


Returns

Success of the solution.

1. Compute stencil for the interior cells.
2. Compute a rational null-space from the first matrix transposed.
3. Compute preliminary approximation (non-mimetic) on the boundaries.
4. Compute quadrature weights to impose the mimetic conditions.
5. Compute real approximation (mimetic) on the boundaries.
6. Assemble operator.

Definition at line 182 of file [mtk_grad_1d.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



16.5.3.8 `int mtk::Grad1D::num_bndy_coeffs ()`

Returns

How many coefficients are approximating at the boundary.

Definition at line 325 of file [mtk_grad_1d.cc](#).

16.5.3.9 `mtk::DenseMatrix mtk::Grad1D::ReturnAsDenseMatrix (const UniStgGrid1D & grid)`


Returns

The operator as a dense matrix.

1. Insert mimetic boundary at the west.
2. Insert coefficients for the interior of the grid.
3. Impose center-skew symmetry by permuting the mimetic boundaries.

Definition at line 340 of file [mtk_grad_1d.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



16.5.3.10 mtk::Real * mtk::Grad1D::weights_cbs (void)

Returns

Collection of weights as computed by the CBSA.

Definition at line 335 of file [mtk_grad_1d.cc](#).

16.5.3.11 mtk::Real * mtk::Grad1D::weights_crs (void)

Returns

Success of the solution.

Definition at line 330 of file [mtk_grad_1d.cc](#).

16.5.4 Friends And Related Function Documentation

16.5.4.1 `std::ostream& operator<< (std::ostream & stream, mtk::Grad1D & in)` [*friend*]

1. Print order of accuracy.
2. Print approximating coefficients for the interior.
3. Print mimetic weights.
4. Print mimetic approximations at the boundary.

Definition at line 79 of file [mtk_grad_1d.cc](#).

16.5.5 Member Data Documentation

16.5.5.1 `Real* mtk::Grad1D::coeffs_interior_` [*private*]

Definition at line 190 of file [mtk_grad_1d.h](#).

16.5.5.2 `int mtk::Grad1D::dim_null_` [*private*]

Definition at line 180 of file [mtk_grad_1d.h](#).

16.5.5.3 `Real* mtk::Grad1D::gradient_` [*private*]

Definition at line 195 of file [mtk_grad_1d.h](#).

16.5.5.4 `int mtk::Grad1D::gradient_length_` [*private*]

Definition at line 183 of file [mtk_grad_1d.h](#).

16.5.5.5 `Real* mtk::Grad1D::mim_bndy_` [*private*]

Definition at line 194 of file [mtk_grad_1d.h](#).

16.5.5.6 `Real mtk::Grad1D::mimetic_threshold_` [*private*]

Definition at line 197 of file [mtk_grad_1d.h](#).

16.5.5.7 `int mtk::Grad1D::minrow_` [*private*]

Definition at line 185 of file [mtk_grad_1d.h](#).

16.5.5.8 `int mtk::Grad1D::num_bndy_approx_` [*private*]

Definition at line 181 of file [mtk_grad_1d.h](#).

16.5.5.9 `int mtk::Grad1D::num_bndy_coeffs_ [private]`

Definition at line 182 of file [mtk_grad_1d.h](#).

16.5.5.10 `int mtk::Grad1D::order_accuracy_ [private]`

Definition at line 179 of file [mtk_grad_1d.h](#).

16.5.5.11 `Real* mtk::Grad1D::prem_apps_ [private]`

Definition at line 191 of file [mtk_grad_1d.h](#).

16.5.5.12 `mtk::DenseMatrix mtk::Grad1D::rat_basis_null_space_ [private]`

Definition at line 188 of file [mtk_grad_1d.h](#).

16.5.5.13 `int mtk::Grad1D::row_ [private]`

Definition at line 186 of file [mtk_grad_1d.h](#).

16.5.5.14 `Real* mtk::Grad1D::weights_cbs_ [private]`

Definition at line 193 of file [mtk_grad_1d.h](#).

16.5.5.15 `Real* mtk::Grad1D::weights_crs_ [private]`

Definition at line 192 of file [mtk_grad_1d.h](#).

The documentation for this class was generated from the following files:


- [include/mtk_grad_1d.h](#)
- [src/mtk_grad_1d.cc](#)

16.6 mtk::Lap1D Class Reference

Implements a 1D mimetic Laplacian operator.

```
#include <mtk_lap_1d.h>
```

Collaboration diagram for mtk::Lap1D:



Public Member Functions

- [Lap1D](#) ()
Default constructor.
- [Lap1D](#) (const [Lap1D](#) &lap)
Copy constructor.
- [~Lap1D](#) ()
Destructor.
- bool [ConstructLap1D](#) (int order_accuracy=[kDefaultOrderAccuracy](#), [Real](#) mimetic_threshold=[kDefaultMimeticThreshold](#))
Factory method implementing the CBS Algorithm to build operator.
- [DenseMatrix](#) [ReturnAsDenseMatrix](#) (const [UniStgGrid1D](#) &grid)
Return the operator as a dense matrix.
- [mtk::Real](#) * [Data](#) (const [UniStgGrid1D](#) &grid)
Return the operator as a dense array.

Private Attributes

- int [order_accuracy_](#)
Order of numerical accuracy of the operator.
- int [laplacian_length_](#)
Length of the output array.
- [Real](#) * [laplacian_](#)
Output array containing the operator and weights.
- [Real](#) [mimetic_threshold_](#)
< Mimetic threshold.

Friends

- `std::ostream & operator<< (std::ostream &stream, Lap1D &in)`
Output stream operator for printing.

16.6.1 Detailed Description

This class implements a 1D Laplacian operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (CBSA).

Definition at line 76 of file [mtk_lap_1d.h](#).

16.6.2 Constructor & Destructor Documentation

16.6.2.1 mtk::Lap1D::Lap1D ()

Definition at line 108 of file [mtk_lap_1d.cc](#).

16.6.2.2 mtk::Lap1D::Lap1D (const Lap1D & lap)

Parameters

<code>in</code>	<code>lap</code>	Given Laplacian.
-----------------	------------------	------------------

16.6.2.3 mtk::Lap1D::~~Lap1D ()

Definition at line 113 of file [mtk_lap_1d.cc](#).

16.6.3 Member Function Documentation

16.6.3.1 bool mtk::Lap1D::ConstructLap1D (int order_accuracy = kDefaultOrderAccuracy, mtk::Real mimetic_threshold = kDefaultMimeticThreshold)

Returns

Success of the solution.

1. Create gradient operator using specific values for the Laplacian.
2. Create gradient operator using specific values for the Laplacian.
3. Create both operators as matrices.
4. Multiply both operators: $\check{\mathbf{L}}_x^k = \check{\mathbf{D}}_x^k \check{\mathbf{G}}_x^k$
5. Extract the coefficients from the matrix and store them in the array.


Warning

We do not compute weights for this operator.

1. The first entry of the array will contain the order of accuracy.
2. The second entry of the array will contain the collection of approximating coefficients for the interior of the grid.
3. We DO NOT have weights in this operator. Copy mimetic bndy coeffs.

Definition at line 119 of file [mtk_lap_1d.cc](#).

Here is the call graph for this function:



16.6.3.2 `mtk::Real * mtk::Lap1D::Data (const UniStgGrid1D & grid)`

Returns

The operator as a dense array.

Definition at line 332 of file [mtk_lap_1d.cc](#).

Here is the call graph for this function:



16.6.3.3 mtk::DenseMatrix mtk::Lap1D::ReturnAsDenseMatrix (const UniStgGrid1D & grid)

Returns

The operator as a dense matrix.


1. Extract mimetic coefficients from the west boundary.
2. Extract interior coefficients.
3. Extract mimetic coefficients from the west boundary to go east.

Note

We could create two matrices of the requested size and multiply them, but that would be inefficient, since we already have the computed coefficients stored. We just have to set them in place, in a matrix of an adequate size, and multiply them times the inverse of the square of the step size, in order for the matrix to actually represent a differential operator.

Definition at line 265 of file [mtk_lap_1d.cc](#).

Here is the call graph for this function:



16.6.4 Friends And Related Function Documentation

16.6.4.1 `std::ostream& operator<< (std::ostream & stream, mtk::Lap1D & in)` [friend]

1. Print order of accuracy.
2. Print approximating coefficients for the interior.
3. No weights, thus print the mimetic boundary coefficients.

Definition at line 73 of file [mtk_lap_1d.cc](#).

16.6.5 Member Data Documentation

16.6.5.1 `Real* mtk::Lap1D::laplacian_` [private]

Definition at line 120 of file [mtk_lap_1d.h](#).

16.6.5.2 `int mtk::Lap1D::laplacian_length_` [private]

Definition at line 118 of file [mtk_lap_1d.h](#).

16.6.5.3 `Real mtk::Lap1D::mimetic_threshold_` [private]

Definition at line 122 of file [mtk_lap_1d.h](#).

16.6.5.4 `int mtk::Lap1D::order_accuracy_` [private]

Definition at line 117 of file [mtk_lap_1d.h](#).

The documentation for this class was generated from the following files:


- [include/mtk_lap_1d.h](#)
- [src/mtk_lap_1d.cc](#)

16.7 mtk::LAPACKAdapter Class Reference

Adapter class for the LAPACK API.

```
#include <mtk_lapack_adapter.h>
```

Collaboration diagram for mtk::LAPACKAdapter:



Static Public Member Functions

- static int [SolveDenseSystem](#) ([mtk::DenseMatrix](#) &mm, [mtk::Real](#) *rhs)
Solves a dense system of linear equations.
- static int [SolveDenseSystem](#) ([mtk::DenseMatrix](#) &mm, [mtk::DenseMatrix](#) &rr)
Solves a dense system of linear equations.
- static int [SolveRectangularDenseSystem](#) (const [mtk::DenseMatrix](#) &aa, [mtk::Real](#) *ob_, int ob_Id_)
Solves overdetermined or underdetermined real linear systems.
- static [mtk::DenseMatrix](#) [QRFactorDenseMatrix](#) ([DenseMatrix](#) &matrix)
Performs a QR factorization on a dense matrix.

16.7.1 Detailed Description

This class contains a collection of static classes, that posses direct access to the underlying structure of the matrices, thus allowing programmers to exploit the numerical methods implemented in the LAPACK.

The **LAPACK** is written in Fortran 90 and provides routines for solving systems of simultaneous linear equations, least-squares solutions of linear systems of equations, eigenvalue problems, and singular value problems.

See Also

<http://www.netlib.org/lapack/>

Definition at line 89 of file [mtk_lapack_adapter.h](#).

16.7.2 Member Function Documentation

16.7.2.1 [mtk::DenseMatrix](#) [mtk::LAPACKAdapter::QRFactorDenseMatrix](#) ([mtk::DenseMatrix](#) & aa) [static]

Adapts the MTK to LAPACK's routine.

Parameters

<code>in, out</code>	<code>matrix</code>	Input matrix.
----------------------	---------------------	---------------

Returns


Matrix **Q**.

Exceptions


<code>std::bad_alloc</code>

Definition at line 515 of file `mtk_lapack_adapter.cc`.

Here is the call graph for this function:



Here is the caller graph for this function:



16.7.2.2 `int mtk::LAPACKAdapter::SolveDenseSystem (mtk::DenseMatrix & mm, mtk::Real * rhs) [static]`

Adapts the MTK to LAPACK's `dgesv_` routine.

Parameters


in	<i>matrix</i>	Input matrix.
in	<i>rhs</i>	Input right-hand sides vector.

Exceptions


<i>std::bad_alloc</i>	
-----------------------	--

Definition at line 427 of file [mtk_lapack_adapter.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



16.7.2.3 `int mtk::LAPACKAdapter::SolveDenseSystem (mtk::DenseMatrix & mm, mtk::DenseMatrix & rr) [static]`

Adapts the MTK to LAPACK's `dgesv_` routine.

Parameters


in	<i>matrix</i>	Input matrix.
in	<i>rr</i>	Input right-hand sides matrix.

Exceptions

<i>std::bad_alloc</i>	
-----------------------	--

Definition at line 463 of file [mtk_lapack_adapter.cc](#).

Here is the call graph for this function:



16.7.2.4 `int mtk::LAPACKAdapter::SolveRectangularDenseSystem (const mtk::DenseMatrix & aa, mtk::Real * ob_, int ob_ld_) [static]`

Adapts the MTK to LAPACK's routine.

Parameters

in, out	<i>matrix</i>	Input matrix.
---------	---------------	---------------

Returns


Success of the solution.

Exceptions


<code>std::bad_alloc</code>	
-----------------------------	--

Definition at line 716 of file [mtk_lapack_adapter.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



The documentation for this class was generated from the following files:

- [include/mtk_lapack_adapter.h](#)
- [src/mtk_lapack_adapter.cc](#)

16.8 mtk::Matrix Class Reference

Definition of the representation of a matrix in the MTK.

```
#include <mtk_matrix.h>
```

Collaboration diagram for mtk::Matrix:

mtk::Matrix
<ul style="list-style-type: none"> - storage_ - ordering_ - num_rows_ - num_cols_ - num_values_ - ld_ - num_zero_ - num_non_zero_ - num_null_ - num_non_null_ and 7 more...
<ul style="list-style-type: none"> + Matrix() + Matrix() + ~Matrix() + storage() + ordering() + num_rows() + num_cols() + num_values() + ld() + num_zero() and 18 more...

Public Member Functions

- [Matrix](#) ()
Default constructor.
- [Matrix](#) (const [Matrix](#) &in)
Copy constructor.
- [~Matrix](#) ()
Destructor.
- [MatrixStorage](#) storage () const
Gets the type of storage of this matrix.
- [MatrixOrdering](#) ordering () const
Gets the ordering of this matrix.
- int [num_rows](#) () const
Gets the number of rows.
- int [num_cols](#) () const
Gets the number of rows.

- `int num_values () const`
Gets the number of values.
- `int ld () const`
Gets the matrix' leading dimension.
- `int num_zero () const`
Gets the number of zeros.
- `int num_non_zero () const`
Gets the number of non-zero values.
- `int num_null () const`
Gets the number of null values.
- `int num_non_null () const`
Gets the number of non-null values.
- `int kl () const`
Gets the number of lower diagonals.
- `int ku () const`
Gets the number of upper diagonals.
- `int bandwidth () const`
Gets the bandwidth.
- `Real abs_density () const`
Gets the absolute density.
- `Real rel_density () const`
Gets the relative density.
- `Real abs_sparsity () const`
Gets the Absolute sparsity.
- `Real rel_sparsity () const`
Gets the Relative sparsity.
- `void set_storage (const MatrixStorage &tt)`
Sets the storage type of the matrix.
- `void set_ordering (const MatrixOrdering &oo)`
Sets the ordering of the matrix.
- `void set_num_rows (int num_rows)`
Sets the number of rows of the matrix.
- `void set_num_cols (int num_cols)`
Sets the number of columns of the matrix.
- `void set_num_zero (int in)`
Sets the number of zero values of the matrix that matter.
- `void set_num_null (int in)`
Sets the number of zero values of the matrix that DO NOT matter.
- `void IncreaseNumZero ()`
Increases the number of values that equal zero but with meaning.
- `void IncreaseNumNull ()`
Increases the number of values that equal zero but with no meaning.

Private Attributes

- [MatrixStorage storage_](#)
What type of matrix is this?
- [MatrixOrdering ordering_](#)
What kind of ordering is it following?
- int [num_rows_](#)
Number of rows.
- int [num_cols_](#)
Number of columns.
- int [num_values_](#)
Number of total values in matrix.
- int [ld_](#)
Elements between successive rows when row-major.
- int [num_zero_](#)
Number of zeros.
- int [num_non_zero_](#)
Number of non-zero values.
- int [num_null_](#)
Number of null (insignificant) values.
- int [num_non_null_](#)
Number of null (significant) values.
- int [kl_](#)
Number of lower diagonals on a banded matrix.
- int [ku_](#)
Number of upper diagonals on a banded matrix.
- int [bandwidth_](#)
Bandwidth of the matrix.
- [Real abs_density_](#)
Absolute density of matrix.
- [Real rel_density_](#)
Relative density of matrix.
- [Real abs_sparsity_](#)
Absolute sparsity of matrix.
- [Real rel_sparsity_](#)
Relative sparsity of matrix.

16.8.1 Detailed Description

Definition of the representation for the matrices implemented in the MTK.

Definition at line 75 of file [mtk_matrix.h](#).

16.8.2 Constructor & Destructor Documentation

16.8.2.1 `mtk::Matrix::Matrix ()`

Definition at line 72 of file [mtk_matrix.cc](#).

16.8.2.2 mtk::Matrix::Matrix (const Matrix & *in*)

Parameters

<code>in</code>	<code>in</code>	Given matrix.
-----------------	-----------------	---------------

Definition at line 91 of file [mtk_matrix.cc](#).

16.8.2.3 `mtk::Matrix::~Matrix ()`

Definition at line 110 of file [mtk_matrix.cc](#).

16.8.3 Member Function Documentation

16.8.3.1 `Real mtk::Matrix::abs_density () const`

See Also

http://www.csrc.sdsu.edu/research_reports/CSR2013-01.pdf

Returns

Absolute density of the matrix.

16.8.3.2 `mtk::Real mtk::Matrix::abs_sparsity () const`

See Also

http://www.csrc.sdsu.edu/research_reports/CSR2013-01.pdf

Returns

Absolute sparsity of the matrix.

Definition at line 182 of file [mtk_matrix.cc](#).

16.8.3.3 `int mtk::Matrix::bandwidth () const`

Returns

Bandwidth of the matrix.

Definition at line 172 of file [mtk_matrix.cc](#).

16.8.3.4 `void mtk::Matrix::IncreaseNumNull ()`

Todo Review the definition of sparse matrices properties.

Definition at line 279 of file [mtk_matrix.cc](#).

16.8.3.5 void mtk::Matrix::IncreaseNumZero ()

Todo Review the definition of sparse matrices properties.

Definition at line 269 of file [mtk_matrix.cc](#).

16.8.3.6 int mtk::Matrix::kl () const

Returns

Number of lower diagonals.

Definition at line 162 of file [mtk_matrix.cc](#).

16.8.3.7 int mtk::Matrix::ku () const

Returns

Number of upper diagonals.

Definition at line 167 of file [mtk_matrix.cc](#).

16.8.3.8 int mtk::Matrix::ld () const

Leading dimension of the data array is the number of elements between successive rows (for row major storage) in memory. Most of the cases, the leading dimension is the same as the number of columns.

Returns

Leading dimension of the matrix.

Definition at line 137 of file [mtk_matrix.cc](#).


16.8.3.9 int mtk::Matrix::num_cols () const

Returns

Number of rows of the matrix.

Definition at line 127 of file [mtk_matrix.cc](#).

Here is the caller graph for this function:



16.8.3.10 `int mtk::Matrix::num_non_null () const`

See Also

http://www.csrc.sdsu.edu/research_reports/CSR2013-01.pdf

Returns

Number of non-null values of the matrix.

Definition at line 157 of file [mtk_matrix.cc](#).

16.8.3.11 `int mtk::Matrix::num_non_zero () const`

Returns

Number of non-zero values of the matrix.

Definition at line 147 of file [mtk_matrix.cc](#).

16.8.3.12 `int mtk::Matrix::num_null () const`

See Also


http://www.csrc.sdsu.edu/research_reports/CSR2013-01.pdf

Returns

Number of null values of the matrix.

Definition at line 152 of file [mtk_matrix.cc](#).


Here is the caller graph for this function:

**16.8.3.13 int mtk::Matrix::num_rows () const****Returns**

Number of rows of the matrix.

Definition at line 122 of file [mtk_matrix.cc](#).

Here is the caller graph for this function:

**16.8.3.14 int mtk::Matrix::num_values () const****Returns**

Number of values of the matrix.

Definition at line 132 of file [mtk_matrix.cc](#).


16.8.3.15 `int mtk::Matrix::num_zero () const`

Returns

Number of zeros of the matrix.

Definition at line 142 of file [mtk_matrix.cc](#).


Here is the caller graph for this function:



16.8.3.16 `mtk::MatrixOrdering mtk::Matrix::ordering () const`

Definition at line 117 of file [mtk_matrix.cc](#).

Here is the caller graph for this function:



16.8.3.17 `mtk::Real mtk::Matrix::rel_density () const`

See Also

http://www.csrc.sdsu.edu/research_reports/CSR2013-01.pdf

Returns

Relative density of the matrix.

Definition at line 177 of file [mtk_matrix.cc](#).

16.8.3.18 `mtk::Real mtk::Matrix::rel_sparsity () const`

See Also

http://www.csrc.sdsu.edu/research_reports/CSR2013-01.pdf

Returns

Relative sparsity of the matrix.

Definition at line 187 of file [mtk_matrix.cc](#).


16.8.3.19 `void mtk::Matrix::set_num_cols (int num_cols)`

Parameters

<i>in</i>	<i>num_cols</i>	Number of columns.
-----------	-----------------	--------------------

Definition at line 229 of file [mtk_matrix.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



16.8.3.20 `void mtk::Matrix::set_num_null (int in)`

Parameters

<i>in</i>	<i>in</i>	Number of zero values.
-----------	-----------	------------------------

Bug -nan assigned on construction time due to num_values_ being 0.

Definition at line 255 of file [mtk_matrix.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



16.8.3.21 void mtk::Matrix::set_num_rows (int *num_rows*)

Parameters

<i>in</i>	<i>num_rows</i>	Number of rows.
-----------	-----------------	-----------------

Definition at line 217 of file [mtk_matrix.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



16.8.3.22 `void mtk::Matrix::set_num_zero (int in)`


Parameters

<i>in</i>	<i>in</i>	Number of zero values.
-----------	-----------	------------------------

Bug -nan assigned on construction time due to `num_values_` being 0.

Definition at line 241 of file [mtk_matrix.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



16.8.3.23 `void mtk::Matrix::set_ordering (const MatrixOrdering & oo)`

See Also

[MatrixOrdering](#)

Parameters


<code>in</code>	<code>oo</code>	Ordering of the matrix.
-----------------	-----------------	-------------------------

Definition at line 204 of file [mtk_matrix.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



16.8.3.24 `void mtk::Matrix::set_storage (const MatrixStorage & tt)`

See Also

[MatrixStorage](#)

Parameters


<code>in</code>	<code>tt</code>	Type of the matrix storage.
-----------------	-----------------	-----------------------------

Definition at line 192 of file [mtk_matrix.cc](#).

Here is the call graph for this function:




Here is the caller graph for this function:



16.8.3.25 `mtk::MatrixStorage mtk::Matrix::storage () const`

Definition at line 112 of file [mtk_matrix.cc](#).

Here is the caller graph for this function:



16.8.4 Member Data Documentation

16.8.4.1 Real mtk::Matrix::abs_density_ [private]

Definition at line 288 of file [mtk_matrix.h](#).

16.8.4.2 Real mtk::Matrix::abs_sparsity_ [private]

Definition at line 290 of file [mtk_matrix.h](#).

16.8.4.3 int mtk::Matrix::bandwidth_ [private]

Definition at line 286 of file [mtk_matrix.h](#).

16.8.4.4 int mtk::Matrix::kl_ [private]

Definition at line 284 of file [mtk_matrix.h](#).

16.8.4.5 int mtk::Matrix::ku_ [private]

Definition at line 285 of file [mtk_matrix.h](#).

16.8.4.6 int mtk::Matrix::ld_ [private]

Definition at line 277 of file [mtk_matrix.h](#).

16.8.4.7 int mtk::Matrix::num_cols_ [private]

Definition at line 275 of file [mtk_matrix.h](#).

16.8.4.8 int mtk::Matrix::num_non_null_ [private]

Definition at line 282 of file [mtk_matrix.h](#).

16.8.4.9 `int mtk::Matrix::num_non_zero_` [private]

Definition at line 280 of file [mtk_matrix.h](#).

16.8.4.10 `int mtk::Matrix::num_null_` [private]

Definition at line 281 of file [mtk_matrix.h](#).

16.8.4.11 `int mtk::Matrix::num_rows_` [private]

Definition at line 274 of file [mtk_matrix.h](#).

16.8.4.12 `int mtk::Matrix::num_values_` [private]

Definition at line 276 of file [mtk_matrix.h](#).

16.8.4.13 `int mtk::Matrix::num_zero_` [private]

Definition at line 279 of file [mtk_matrix.h](#).

16.8.4.14 `MatrixOrdering mtk::Matrix::ordering_` [private]

Definition at line 272 of file [mtk_matrix.h](#).

16.8.4.15 `Real mtk::Matrix::rel_density_` [private]

Definition at line 289 of file [mtk_matrix.h](#).

16.8.4.16 `Real mtk::Matrix::rel_sparsity_` [private]

Definition at line 291 of file [mtk_matrix.h](#).

16.8.4.17 `MatrixStorage mtk::Matrix::storage_` [private]

Definition at line 270 of file [mtk_matrix.h](#).

The documentation for this class was generated from the following files:


- [include/mtk_matrix.h](#)
- [src/mtk_matrix.cc](#)

16.9 mtk::Quad1D Class Reference

Implements a 1D mimetic quadrature.

```
#include <mtk_quad_1d.h>
```

Collaboration diagram for mtk::Quad1D:



Public Member Functions

- [Quad1D](#) ()
Default constructor.
- [Quad1D](#) (const [Quad1D](#) &quad)
Copy constructor.

- [~Quad1D](#) ()
Destructor.
- int [degree_approximation](#) () const
Get the degree of interpolating polynomial per sub-interval of domain.
- [Real](#) * [weights](#) () const
Return collection of weights.
- [Real](#) [Integrate](#) ([Real](#)(*Integrand)([Real](#) xx), [UniStgGrid1D](#) grid)
Mimetic integration routine.

Private Attributes

- int [degree_approximation_](#)
Degree of the interpolating polynomial.
- std::vector< [Real](#) > [weights_](#)
Collection of weights.

Friends

- std::ostream & [operator<<](#) (std::ostream &stream, [Quad1D](#) &in)
Output stream operator for printing.

16.9.1 Detailed Description

This class implements a 1D quadrature solver based on the mimetic discretization of the gradient operator.

Definition at line 81 of file [mtk_quad_1d.h](#).

16.9.2 Constructor & Destructor Documentation

16.9.2.1 [mtk::Quad1D::Quad1D](#) ()

16.9.2.2 [mtk::Quad1D::Quad1D](#) (const [Quad1D](#) & quad)

Parameters

in	div	Given quadrature.
--------------------	---------------------	-------------------

16.9.2.3 [mtk::Quad1D::~~Quad1D](#) ()

16.9.3 Member Function Documentation

16.9.3.1 int [mtk::Quad1D::degree_approximation](#) () const

Returns

Degree of the interpolating polynomial per sub-interval of the domain.

16.9.3.2 [Real](#) [mtk::Quad1D::Integrate](#) ([Real](#)(*)([Real](#) xx) *Integrand*, [UniStgGrid1D](#) *grid*)

Parameters

in	<i>Integrand</i>	Real-valued function to integrate.
in	<i>grid</i>	Given integration domain.

Returns

Result of the integration.

16.9.3.3 `Real* mtk::Quad1D::weights () const`

Returns

Collection of weights.

16.9.4 Friends And Related Function Documentation

16.9.4.1 `std::ostream& operator<< (std::ostream & stream, Quad1D & in)` [*friend*]

16.9.5 Member Data Documentation

16.9.5.1 `int mtk::Quad1D::degree_approximation_` [*private*]

Definition at line 124 of file [mtk_quad_1d.h](#).

16.9.5.2 `std::vector<Real> mtk::Quad1D::weights_` [*private*]

Definition at line 126 of file [mtk_quad_1d.h](#).

The documentation for this class was generated from the following file:


- [include/mtk_quad_1d.h](#)

16.10 `mtk::Tools` Class Reference

Tool manager class.

```
#include <mtk_tools.h>
```

Collaboration diagram for mtk::Tools:



Static Public Member Functions

- static void [Prevent](#) (const bool condition, const char *fname, int lineno, const char *fxname)
Enforces pre-conditions by preventing their complements from occur.
- static void [BeginTestNo](#) (const int &nn)
Begins the execution of a test.
- static void [EndTestNo](#) (const int &nn)
Ends the execution of a test.

Static Private Attributes

- static int [test_number_](#)
Current test being executed.
- static clock_t [begin_time_](#)
Elapsed time on current test.

16.10.1 Detailed Description

Basic tools to ensure execution correctness.

Definition at line 72 of file [mtk_tools.h](#).

16.10.2 Member Function Documentation

16.10.2.1 void mtk::Tools::BeginTestNo (const int & *nn*) [static]

Parameters

<i>in</i>	<i>nn</i>	Number of the test.
-----------	-----------	---------------------

Definition at line 89 of file [mtk_tools.cc](#).

Here is the call graph for this function:



16.10.2.2 void `mtk::Tools::EndTestNo (const int & nn)` `[static]`

Parameters

<i>in</i>	<i>nn</i>	Number of the test.
-----------	-----------	---------------------

Definition at line 101 of file [mtk_tools.cc](#).

Here is the call graph for this function:



16.10.2.3 void `mtk::Tools::Prevent (const bool condition, const char * fname, int lineno, const char * fxname)` `[static]`

See Also

<http://stackoverflow.com/questions/8884335/print-the-file-name-line-number-and-function>


Parameters

<i>in</i>	<i>condition</i>	Complement of desired pre-condition.
<i>in</i>	<i>fname</i>	Name of the file being checked.
<i>in</i>	<i>lineno</i>	Number of the line where the check is executed.
<i>in</i>	<i>fxname</i>	Name of the module containing the check.

Todo Check if this is the best way of stalling execution.

Definition at line 61 of file [mtk_tools.cc](#).

Here is the caller graph for this function:



16.10.3 Member Data Documentation

16.10.3.1 `clock_t mtk::Tools::begin_time_` `[static]`, `[private]`

Definition at line 106 of file [mtk_tools.h](#).

16.10.3.2 `int mtk::Tools::test_number_` `[static]`, `[private]`

Todo Check usage of static methods and private members.

Definition at line 104 of file [mtk_tools.h](#).

The documentation for this class was generated from the following files:

- [include/mtk_tools.h](#)


- [src/mtk_tools.cc](#)

16.11 mtk::UniStgGrid1D Class Reference

Uniform 1D Staggered Grid.

```
#include <mtk_uni_stg_grid_1d.h>
```


Collaboration diagram for mtk::UniStgGrid1D:



Public Member Functions

- [UniStgGrid1D \(\)](#)

Default constructor.

- [UniStgGrid1D](#) (const [UniStgGrid1D](#) &grid)

Copy constructor.

- [UniStgGrid1D](#) (const [Real](#) &west_bndy_x, const [Real](#) &east_bndy_x, const int &num_cells_x, const [mtk::Field-Nature](#) &nature=[mtk::SCALAR](#))

Construct a grid based on spatial discretization parameters.

- [~UniStgGrid1D](#) ()

Destructor.

- [Real](#) delta_x () const

Provides access to the computed Δx .

- [Real](#) * discrete_domain_x ()

Provides access to the grid spatial data.

- [Real](#) * discrete_field_u ()

Provides access to the grid field data.

- int num_cells_x () const

Provides access to the number of cells of the grid.

- void [BindScalarField](#) ([Real](#)(*ScalarField)([Real](#) xx))

Binds a given scalar field to the grid.

- void [BindVectorField](#) ([Real](#)(*VectorField)([Real](#) xx))

Binds a given vector field to the grid.

- bool [WriteToFile](#) (std::string filename, std::string space_name, std::string field_name)

Writes grid to a file compatible with Gnuplot 4.6.

Private Attributes

- [FieldNature](#) nature_

Nature of the discrete field.

- std::vector< [Real](#) > discrete_domain_x_

Array of spatial data.

- std::vector< [Real](#) > discrete_field_u_

Array of field's data.

- [Real](#) west_bndy_x_

West boundary spatial coordinate.

- [Real](#) east_bndy_x_

East boundary spatial coordinate.

- [Real](#) num_cells_x_

Number of cells discretizing the domain.

- [Real](#) delta_x_

Produced Δx .

Friends

- std::ostream & [operator<<](#) (std::ostream &stream, [UniStgGrid1D](#) &in)

Prints the grid as a tuple of arrays.

16.11.1 Detailed Description

Uniform 1D Staggered Grid.

Definition at line 77 of file [mtk_uni_stg_grid_1d.h](#).

16.11.2 Constructor & Destructor Documentation

16.11.2.1 mtk::UniStgGrid1D::UniStgGrid1D ()

Definition at line 97 of file [mtk_uni_stg_grid_1d.cc](#).

16.11.2.2 mtk::UniStgGrid1D::UniStgGrid1D (const UniStgGrid1D & grid)

Parameters

in	<i>grid</i>	Given grid.
----	-------------	-------------

Definition at line 106 of file [mtk_uni_stg_grid_1d.cc](#).

16.11.2.3 mtk::UniStgGrid1D::UniStgGrid1D (const Real & west_bndy_x, const Real & east_bndy_x, const int & num_cells_x, const mtk::FieldNature & nature = mtk::SCALAR)

Parameters


in	<i>west_bndy_x</i>	Coordinate for the west boundary.
in	<i>east_bndy_x</i>	Coordinate for the east boundary.
in	<i>num_cells_x</i>	Number of cells of the required grid.
in	<i>nature</i>	Nature of the discrete field to hold.

See Also

[mtk::FieldNature](#)

Definition at line 122 of file [mtk_uni_stg_grid_1d.cc](#).

Here is the call graph for this function:



16.11.2.4 mtk::UniStgGrid1D::~~UniStgGrid1D ()

Definition at line 142 of file [mtk_uni_stg_grid_1d.cc](#).

16.11.3 Member Function Documentation

16.11.3.1 void mtk::UniStgGrid1D::BindScalarField (Real(*) (Real xx) *ScalarField*)


Parameters

in	<i>ScalarField</i>	Pointer to the function implementing the scalar field.
----	--------------------	--

1. Create collection of spatial coordinates.
2. Create collection of field samples.

Definition at line 164 of file [mtk_uni_stg_grid_1d.cc](#).

Here is the call graph for this function:



16.11.3.2 void mtk::UniStgGrid1D::BindVectorField (Real(*) (Real xx) *VectorField*)

We assume the field to be of the form:

$$\mathbf{v}(x) = v(x)\hat{\mathbf{i}}$$


Parameters

in	<i>VectorField</i>	Pointer to the function implementing the vector field.
----	--------------------	--

1. Create collection of spatial coordinates.
2. Create collection of field samples.

Definition at line 200 of file [mtk_uni_stg_grid_1d.cc](#).

Here is the call graph for this function:




16.11.3.3 mtk::Real mtk::UniStgGrid1D::delta_x () const

Returns

Computed Δx .

Definition at line 144 of file [mtk_uni_stg_grid_1d.cc](#).

Here is the caller graph for this function:



16.11.3.4 mtk::Real * mtk::UniStgGrid1D::discrete_domain_x ()

Returns

Pointer to the spatial data.

Definition at line 149 of file [mtk_uni_stg_grid_1d.cc](#).

16.11.3.5 mtk::Real * mtk::UniStgGrid1D::discrete_field_u ()

Returns

Pointer to the field data.

Definition at line 154 of file [mtk_uni_stg_grid_1d.cc](#).


16.11.3.6 int mtk::UniStgGrid1D::num_cells_x () const

Returns

Number of cells of the grid.

Definition at line 159 of file [mtk_uni_stg_grid_1d.cc](#).

Here is the caller graph for this function:



16.11.3.7 `bool mtk::UniStgGrid1D::WriteToFile (std::string filename, std::string space_name, std::string field_name)`

Parameters

in	<i>filename</i>	Name of the output file.
in	<i>space_name</i>	Name for the first column of the data.
in	<i>field_name</i>	Name for the second column of the data.

Returns

Success of the file writing process.

See Also

<http://www.gnuplot.info/>

Definition at line 228 of file [mtk_uni_stg_grid_1d.cc](#).

16.11.4 Friends And Related Function Documentation

16.11.4.1 `std::ostream& operator<< (std::ostream & stream, mtk::UniStgGrid1D & in)` `[friend]`

1. Print spatial coordinates.

Definition at line 68 of file [mtk_uni_stg_grid_1d.cc](#).

16.11.5 Member Data Documentation

16.11.5.1 `Real mtk::UniStgGrid1D::delta_x_` `[private]`

Definition at line 182 of file [mtk_uni_stg_grid_1d.h](#).

16.11.5.2 `std::vector<Real> mtk::UniStgGrid1D::discrete_domain_x_` [private]

Definition at line 176 of file [mtk_uni_stg_grid_1d.h](#).

16.11.5.3 `std::vector<Real> mtk::UniStgGrid1D::discrete_field_u_` [private]

Definition at line 177 of file [mtk_uni_stg_grid_1d.h](#).

16.11.5.4 `Real mtk::UniStgGrid1D::east_bndy_x_` [private]

Definition at line 180 of file [mtk_uni_stg_grid_1d.h](#).

16.11.5.5 `FieldNature mtk::UniStgGrid1D::nature_` [private]

Definition at line 174 of file [mtk_uni_stg_grid_1d.h](#).

16.11.5.6 `Real mtk::UniStgGrid1D::num_cells_x_` [private]

Definition at line 181 of file [mtk_uni_stg_grid_1d.h](#).

16.11.5.7 `Real mtk::UniStgGrid1D::west_bndy_x_` [private]

Definition at line 179 of file [mtk_uni_stg_grid_1d.h](#).

The documentation for this class was generated from the following files:

- [include/mtk_uni_stg_grid_1d.h](#)
- [src/mtk_uni_stg_grid_1d.cc](#)

Chapter 17


File Documentation

17.1 examples/poisson_1d/poisson_1d.cc File Reference

Poisson Equation on a 1D Uniform Staggered Grid with Robin BCs.

```
#include <iostream>
```

Include dependency graph for poisson_1d.cc:



Functions

- int `main` ()

17.1.1 Detailed Description

We solve:

$$-\nabla^2 u(x) = s(x),$$

for $x \in \Omega = [0, 1]$.

The source term function is defined as

$$s(x) = \frac{-\lambda^2 \exp(\lambda x)}{\exp(\lambda) - 1}$$

where $\lambda = -1$ is a parameter.

We consider Robin's boundary conditions of the form:

$$\alpha u(a) - \beta u'(a) = \text{west_bndy_cond_val},$$

$$\alpha u(b) + \beta u'(b) = \text{east_bndy_cond_val}.$$

The analytical solution for this problem is given by

$$u(x) = \frac{\exp(\lambda x) - 1}{\exp(\lambda) - 1}.$$

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu
 : Raul Vargas-Navarro - vargasna at rohan dot sdsu dot edu

Definition in file [poisson_1d.cc](#).

17.1.2 Function Documentation

17.1.2.1 int main ()

Definition at line 303 of file [poisson_1d.cc](#).

17.2 poisson_1d.cc

```
00001
00042 /*
00043 Copyright (C) 2015, Computational Science Research Center, San Diego State
00044 University. All rights reserved.
00045
00046 Redistribution and use in source and binary forms, with or without modification,
00047 are permitted provided that the following conditions are met:
00048
00049 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00050 and a copy of the modified files should be reported once modifications are
00051 completed. Documentation related to said modifications should be included.
00052
00053 2. Redistributions of source code must be done through direct
00054 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00055
00056 3. Redistributions of source code must retain the above copyright notice, this
00057 list of conditions and the following disclaimer.
00058
00059 4. Redistributions in binary form must reproduce the above copyright notice,
00060 this list of conditions and the following disclaimer in the documentation and/or
00061 other materials provided with the distribution.
00062
00063 5. Usage of the binary form on proprietary applications shall require explicit
00064 prior written permission from the the copyright holders.
00065
```

```

00066 6. Neither the name of the copyright holder nor the names of its contributors
00067 may be used to endorse or promote products derived from this software without
00068 specific prior written permission.
00069
00070 The copyright holders provide no reassurances that the source code provided does
00071 not infringe any patent, copyright, or any other intellectual property rights of
00072 third parties. The copyright holders disclaim any liability to any recipient for
00073 claims brought against recipient by any third party for infringement of that
00074 parties intellectual property rights.
00075
00076 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00077 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00078 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00079 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00080 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00081 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00082 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00083 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00084 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00085 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00086 */
00087
00088 #if __cplusplus == 201103L
00089
00090 #include <iostream>
00091 #include <fstream>
00092 #include <cmath>
00093
00094 #include <vector>
00095
00096 #include "mtk.h"
00097
00098 namespace mtk {
00099
00100 class BCDesc1D {
00101 public:
00102     static void ImposeOnOperator(DenseMatrix &matrix,
00103                                 const std::vector<Real> &west,
00104                                 const std::vector<Real> &east);
00105
00106     static void ImposeOnGrid(UniStgGrid1D &grid,
00107                             const Real &west_bndy_value,
00108                             const Real &east_bndy_value);
00109 };
00110
00111 void mtk::BCDesc1D::ImposeOnOperator(mtk::DenseMatrix &matrix,
00112                                     const std::vector<mtk::Real> &west,
00113                                     const std::vector<mtk::Real> &east) {
00114
00115     mtk::Tools::Prevent(matrix.num_rows() == 0, __FILE__, __LINE__, __func__);
00116     mtk::Tools::Prevent(west.size() > (unsigned int) matrix.
00117 num_cols(),
00118                         __FILE__, __LINE__, __func__);
00119     mtk::Tools::Prevent(east.size() > (unsigned int) matrix.
00120 num_cols(),
00121                         __FILE__, __LINE__, __func__);
00122
00123     for (unsigned int ii = 0; ii < west.size(); ++ii) {
00124         matrix.SetValue(0, ii, west[ii]);
00125     }
00126
00127     for (unsigned int ii = 0; ii < east.size(); ++ii) {
00128         matrix.SetValue(matrix.num_rows() - 1,
00129                         matrix.num_cols() - east.size() + ii,
00130                         east[ii]);
00131     }
00132 }
00133
00134 void mtk::BCDesc1D::ImposeOnGrid(mtk::UniStgGrid1D &grid,
00135                                  const mtk::Real &west_bndy_value,
00136                                  const mtk::Real &east_bndy_value) {
00137
00138     mtk::Tools::Prevent(grid.num_cells_x() == 0, __FILE__, __LINE__, __func__);
00139
00140     grid.discrete_field_u()[0] = west_bndy_value;
00141
00142
00143
00144
00145
00146
00147
00148

```

```

00149  grid.discrete_field_u()[grid.num_cells_x() - 1] = east_bndy_value;
00150 }
00151
00152 mtk::Real Source(mtk::Real xx) {
00153     mtk::Real lambda = -1.0;
00154     return -lambda*lambda*exp(lambda*xx)/(exp(lambda) - 1.0);
00155 }
00156
00157 mtk::Real KnownSolution(mtk::Real xx) {
00158     mtk::Real lambda = -1.0;
00159     return (exp(lambda*xx) - 1.0)/(exp(lambda) - 1.0);
00160 }
00161
00162 int main () {
00163     std::cout << "Example: Poisson Equation on a 1D Uniform Staggered Grid ";
00164     std::cout << "with Robin BCs." << std::endl;
00165
00166     mtk::Real lambda = -1.0;
00167     mtk::Real alpha = -exp(lambda);
00168     mtk::Real beta = (exp(lambda) - 1.0)/lambda;
00169     mtk::Real west_bndy_value = -1.0;
00170     mtk::Real east_bndy_value = 0.0;
00171
00172     mtk::Real west_bndy_x = 0.0;
00173     mtk::Real east_bndy_x = 1.0;
00174     int num_cells_x = 5;
00175
00176     mtk::UniStgGrid1D comp_sol(west_bndy_x, east_bndy_x, num_cells_x);
00177
00178     int order_of_accuracy = 2;
00179
00180     mtk::Grad1D grad; // Mimetic gradient operator.
00181
00182     mtk::Lapl1D lap; // Mimetic gradient operator.
00183
00184     mtk::Real mimetic_threshold = 1e-6;
00185
00186     if (!lap.ConstructLapl1D(order_of_accuracy, mimetic_threshold)) {
00187         std::cerr << "Mimetic lap could not be built." << std::endl;
00188         return EXIT_FAILURE;
00189     }
00190
00191     mtk::DenseMatrix lapm(lap.ReturnAsDenseMatrix(comp_sol));
00192
00193     std::cout << "Mimetic Laplacian operator: " << std::endl;
00194     std::cout << lapm << std::endl;
00195
00196     if (!grad.ConstructGrad1D(order_of_accuracy, mimetic_threshold)) {
00197         std::cerr << "Mimetic grad could not be built." << std::endl;
00198         return EXIT_FAILURE;
00199     }
00200
00201     mtk::DenseMatrix gradm(grad.ReturnAsDenseMatrix(comp_sol));
00202
00203     std::cout << "Mimetic gradient operator: " << std::endl;
00204     std::cout << gradm << std::endl;
00205
00206     mtk::UniStgGrid1D source(west_bndy_x, east_bndy_x, num_cells_x);
00207
00208     source.BindScalarField(Source);
00209
00210     std::cout << source << std::endl;
00211
00212     source.WriteToFile("poisson_1d_source.dat", "x", "s(x)");
00213
00214     // Since we need to approximate the first derivative times beta, we must use
00215     // the approximation of the gradient at the boundary. We could extract them
00216     // from the gradient operator as packed in the grad object. BUT, since we have
00217     // generated at matrix containing this operator, we can extract these from the
00218     // matrix.
00219
00220
00221
00222
00223
00224
00225
00226
00227
00228
00229
00230
00231
00232
00233
00234

```

```

00235 // Array containing the coefficients for the west boundary condition.
00236 std::vector<mtk::Real> west_coeffs;
00237
00238 for (auto ii = 0; ii < grad.num_bndy_coeffs(); ++ii) {
00239     west_coeffs.push_back(beta*gradm.GetValue(0, ii));
00240 }
00241
00242 // Array containing the coefficients for the east boundary condition.
00243 std::vector<mtk::Real> east_coeffs;
00244
00245 for (auto ii = 0; ii < grad.num_bndy_coeffs(); ++ii) {
00246     east_coeffs.push_back(beta*gradm.GetValue(gradm.num_rows() - 1,
00247                                                gradm.num_cols() - 1 - ii));
00248 }
00249
00250 // To impose the Dirichlet condition, we simple add its coefficient to the
00251 // first entry of the west, and the last entry of the east array.
00252
00253 west_coeffs[0] *= alpha;
00254
00255 east_coeffs[east_coeffs.size() - 1] *= alpha;
00256
00257 // Now that we have the coefficients that should be in the operator, we create
00258 // a boundary condition descriptor object, which will encapsulate the
00259 // complexity of assigning them in the matrix, to complete the construction of
00260 // the mimetic operator.
00261
00262 mtk::BCDesc1D::ImposeOnOperator(lapm, west_coeffs, east_coeffs);
00263
00264 std::cout << "Mimetic differential operator created:" << std::endl;
00265 std::cout << lapm << std::endl;
00266
00267 mtk::BCDesc1D::ImposeOnGrid(source, west_bndy_value, east_bndy_value);
00268
00269 std::cout << "Source term with imposed BCs:" << std::endl;
00270 std::cout << source << std::endl;
00271
00272
00273
00274 int info{mtk::LAPACKAdapter::SolveDenseSystem(lapm,
00275                                                source.discrete_field_u())};
00276
00277 if (!info) {
00278     std::cout << "System solved! Problem solved!" << std::endl;
00279     std::cout << std::endl;
00280 }
00281 else {
00282     std::cerr << "Something wrong solving system! info = " << info << std::endl;
00283     std::cerr << "Exiting..." << std::endl;
00284     return EXIT_FAILURE;
00285 }
00286
00287
00288
00289 mtk::UniStgGrid1D known_sol(west_bndy_x, east_bndy_x, num_cells_x);
00290
00291 known_sol.BindScalarField(KnownSolution);
00292
00293 std::cout << "known_sol =" << std::endl;
00294 std::cout << known_sol << std::endl;
00295
00296 known_sol.WriteToFile("poisson_1d_known_sol.dat", "x", "u(x)");
00297 }
00298
00299 #else
00300 #include <iostream>
00301 using std::cout;
00302 using std::endl;
00303 int main () {
00304     cout << "This code HAS to be compiled with support for C++11." << endl;
00305     cout << "Exiting..." << endl;
00306     return EXIT_SUCCESS;
00307 }
00308 #endif

```

17.3 include/mtk.h File Reference


Includes the entire API.

```

#include "mtk_roots.h"
#include "mtk_enums.h"
#include "mtk_tools.h"
#include "mtk_matrix.h"
#include "mtk_dense_matrix.h"
#include "mtk_blas_adapter.h"
#include "mtk_lapack_adapter.h"
#include "mtk_glpk_adapter.h"
#include "mtk_uni_stg_grid_1d.h"
#include "mtk_grad_1d.h"
#include "mtk_div_1d.h"
#include "mtk_lap_1d.h"
#include "mtk_quad_1d.h"

```

Include dependency graph for mtk.h:



17.3.1 Detailed Description

This file contains every required header file, thus containing the entire API. In this way, client codes only have to instruct `#include "mtk.h"`.

Warning

IT IS EXTREMELY IMPORTANT THAT THE HEADERS ARE ADDED TO THIS FILE IN A SPECIFIC ORDER; THAT IS, CONSIDERING THE DEPENDENCE BETWEEN THE CLASSES THESE CONTAIN!

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk.h](#).

17.4 mtk.h

```

00001
00015 /*
00016 Copyright (C) 2015, Computational Science Research Center, San Diego State
00017 University. All rights reserved.
00018
00019 Redistribution and use in source and binary forms, with or without modification,
00020 are permitted provided that the following conditions are met:
00021
00022 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00023 and a copy of the modified files should be reported once modifications are
00024 completed. Documentation related to said modifications should be included.
00025

```

```

00026 2. Redistributions of source code must be done through direct
00027 downloads from the project's GitHub page: http://www.cs.csrc.sdsu.edu/mtk
00028
00029 3. Redistributions of source code must retain the above copyright notice, this
00030 list of conditions and the following disclaimer.
00031
00032 4. Redistributions in binary form must reproduce the above copyright notice,
00033 this list of conditions and the following disclaimer in the documentation and/or
00034 other materials provided with the distribution.
00035
00036 5. Usage of the binary form on proprietary applications shall require explicit
00037 prior written permission from the the copyright holders.
00038
00039 6. Neither the name of the copyright holder nor the names of its contributors
00040 may be used to endorse or promote products derived from this software without
00041 specific prior written permission.
00042
00043 The copyright holders provide no reassurances that the source code provided does
00044 not infringe any patent, copyright, or any other intellectual property rights of
00045 third parties. The copyright holders disclaim any liability to any recipient for
00046 claims brought against recipient by any third party for infringement of that
00047 parties intellectual property rights.
00048
00049 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00050 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00051 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00052 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00053 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00054 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00055 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00056 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00057 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00058 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00059 */
00360 #ifndef MTK_INCLUDE_MTK_H_
00361 #define MTK_INCLUDE_MTK_H_
00362
00370 #include "mtk_roots.h"
00371
00379 #include "mtk_enums.h"
00380
00388 #include "mtk_tools.h"
00389
00397 #include "mtk_matrix.h"
00398 #include "mtk_dense_matrix.h"
00399
00407 #include "mtk_blas_adapter.h"
00408 #include "mtk_lapack_adapter.h"
00409 #include "mtk_glpk_adapter.h"
00410
00418 #include "mtk_uni_stg_grid_ld.h"
00419
00427 #include "mtk_grad_ld.h"
00428 #include "mtk_div_ld.h"
00429 #include "mtk_lap_ld.h"
00430 #include "mtk_quad_ld.h"
00431
00432 #endif // End of: MTK_INCLUDE_MTK_H_


```

17.5 include/mtk_blas_adapter.h File Reference


Adapter class for the BLAS API.

```
#include "mtk_dense_matrix.h"
```

Include dependency graph for mtk_blas_adapter.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [mtk::BLASAdapter](#)
Adapter class for the BLAS API.

Namespaces

- [mtk](#)
Mimetic Methods Toolkit namespace.

17.5.1 Detailed Description

This class contains a collection of static classes, that posses direct access to the underlying structure of the matrices, thus allowing programmers to exploit some of the numerical methods implemented in the BLAS.

The BLAS (Basic Linear Algebra Subprograms) are routines that provide standard building blocks for performing basic vector and matrix operations. The Level 1 BLAS perform scalar, vector and vector-vector operations, the Level 2 BLAS perform matrix-vector operations, and the Level 3 BLAS perform matrix-matrix operations.

The BLAS can be installed from links given in the See Also section of this page.

See Also

<http://www.netlib.org/blas/>
<https://software.intel.com/en-us/non-commercial-software-development>

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_blas_adapter.h](#).

17.6 mtk_blas_adapter.h

```

00001
00024 /*
00025 Copyright (C) 2015, Computational Science Research Center, San Diego State
00026 University. All rights reserved.
00027
00028 Redistribution and use in source and binary forms, with or without modification,
00029 are permitted provided that the following conditions are met:
00030
00031 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00032 and a copy of the modified files should be reported once modifications are
00033 completed. Documentation related to said modifications should be included.
00034
00035 2. Redistributions of source code must be done through direct
00036 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00037
00038 3. Redistributions of source code must retain the above copyright notice, this
00039 list of conditions and the following disclaimer.
00040
00041 4. Redistributions in binary form must reproduce the above copyright notice,
00042 this list of conditions and the following disclaimer in the documentation and/or
00043 other materials provided with the distribution.
00044
00045 5. Usage of the binary form on proprietary applications shall require explicit
00046 prior written permission from the the copyright holders.
00047
00048 6. Neither the name of the copyright holder nor the names of its contributors
00049 may be used to endorse or promote products derived from this software without
00050 specific prior written permission.
00051
00052 The copyright holders provide no reassurances that the source code provided does
00053 not infringe any patent, copyright, or any other intellectual property rights of
00054 third parties. The copyright holders disclaim any liability to any recipient for
00055 claims brought against recipient by any third party for infringement of that
00056 parties intellectual property rights.
00057
00058 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00059 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00060 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00061 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00062 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00063 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00064 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00065 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00066 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00067 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00068 */
00069
00070 #ifndef MTK_INCLUDE_BLAS_ADAPTER_H_
00071 #define MTK_INCLUDE_BLAS_ADAPTER_H_
00072
00073 #include "mtk_dense_matrix.h"

```

```

00074
00075 namespace mtk {
00076
00096 class BLASAdapter {
00097 public:
00104     static Real RealNRM2(Real *in, int &in_length);
00105
00123     static void RealDenseMV(Real &alpha,
00124                             DenseMatrix &aa,
00125                             Real *xx,
00126                             Real &beta,
00127                             Real *yy);
00128
00143     static DenseMatrix RealDenseMM(DenseMatrix &aa,
00144                                     DenseMatrix &bb);
00145 };
00146 #endif // End of: MTK_INCLUDE_BLAS_ADAPTER_H_

```

17.7 include/mtk_dense_matrix.h File Reference


Defines a common dense matrix, using a 1D array.

```


#include <iostream>
#include "mtk_roots.h"
#include "mtk_enums.h"
#include "mtk_matrix.h"

```

Include dependency graph for mtk_dense_matrix.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [mtk::DenseMatrix](#)
Defines a common dense matrix, using a 1D array.

Namespaces

- [mtk](#)
Mimetic Methods Toolkit namespace.

17.7.1 Detailed Description

For developing purposes, it is better to have a not-so-intricated data structure implementing matrices. This is the purpose of this class: to be used for prototypes of new code for small test cases. In every other instance, this should be replaced by the most appropriate sparse matrix.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Todo Add sparse matrices support: BANDED and CRS.

Todo Contemplate manipulation of sparse metrics.

Todo Implement Kronecker product using the BLAS.

Note

We prefer composition to inheritance [Reedy, 2011]. The main reason for this preference is that inheritance produces a more tightly coupled design. When a class inherits from another type be it public, protected, or private inheritance the subclass gains access to all public and protected members of the base class, whereas with composition, the class is only coupled to the public members of the other class. Furthermore, if you only hold a pointer to the other object, then your interface can use a forward declaration of the class rather than `#include` its full definition. This results in greater compile-time insulation and improves the time it takes to compile your code.

Definition in file [mtk_dense_matrix.h](#).

17.8 mtk_dense_matrix.h

```
00001
00029 /*
00030 Copyright (C) 2015, Computational Science Research Center, San Diego State
00031 University. All rights reserved.
00032
00033 Redistribution and use in source and binary forms, with or without modification,
00034 are permitted provided that the following conditions are met:
00035
00036 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00037 and a copy of the modified files should be reported once modifications are
00038 completed. Documentation related to said modifications should be included.
00039
00040 2. Redistributions of source code must be done through direct
00041 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00042
00043 3. Redistributions of source code must retain the above copyright notice, this
```

```

00044 list of conditions and the following disclaimer.
00045
00046 4. Redistributions in binary form must reproduce the above copyright notice,
00047 this list of conditions and the following disclaimer in the documentation and/or
00048 other materials provided with the distribution.
00049
00050 5. Usage of the binary form on proprietary applications shall require explicit
00051 prior written permission from the the copyright holders.
00052
00053 6. Neither the name of the copyright holder nor the names of its contributors
00054 may be used to endorse or promote products derived from this software without
00055 specific prior written permission.
00056
00057 The copyright holders provide no reassurances that the source code provided does
00058 not infringe any patent, copyright, or any other intellectual property rights of
00059 third parties. The copyright holders disclaim any liability to any recipient for
00060 claims brought against recipient by any third party for infringement of that
00061 parties intellectual property rights.
00062
00063 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00064 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00065 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00066 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00067 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00068 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00069 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00070 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00071 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00072 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00073 */
00074
00075 #ifndef MTK_INCLUDE_DENSE_MATRIX_H_
00076 #define MTK_INCLUDE_DENSE_MATRIX_H_
00077
00078 #include <iostream>
00079
00080 #include "mtk_roots.h"
00081 #include "mtk_enums.h"
00082 #include "mtk_matrix.h"
00083
00084 namespace mtk {
00085
00098 class DenseMatrix {
00099 public:
00101     friend std::ostream& operator <<(std::ostream &stream, DenseMatrix &in);
00102
00104     DenseMatrix& operator =(const DenseMatrix &in);
00105
00107     DenseMatrix();
00108
00114     DenseMatrix(const DenseMatrix &in);
00115
00124     DenseMatrix(const int &num_rows, const int &num_cols);
00125
00151     DenseMatrix(const int &rank, const bool &padded, const bool &transpose);
00152
00186     DenseMatrix(const Real *gen,
00187                 const int &gen_length,
00188                 const int &pro_length,
00189                 const bool &transpose);
00190
00192     ~DenseMatrix();
00193
00199     Matrix matrix_properties() const;
00200
00206     int num_rows() const;
00207
00213     int num_cols() const;
00214
00220     Real* data() const;
00221
00229     void SetOrdering(mtk::MatrixOrdering oo);
00230
00239     Real GetValue(const int &row_coord, const int &col_coord) const;
00240
00248     void SetValue(const int &row_coord,
00249                  const int &col_coord,
00250                  const Real &val);
00251
00253     void Transpose();
00254

```

```

00256 void OrderRowMajor();
00257
00259 void OrderColMajor();
00260
00269 static DenseMatrix Kron(const DenseMatrix &aa, const
DenseMatrix &bb);
00270
00271 private:
00272 Matrix matrix_properties_;
00273
00274 Real *data_;
00275 };
00276 }
00277 #endif // End of: MTK_INCLUDE_MTK_DENSE_MATRIX_H_

```

17.9 include/mtk_div_1d.h File Reference


Includes the definition of the class Div1D.

```


#include <iostream>
#include <iomanip>
#include "glpk.h"
#include "mtk_roots.h"
#include "mtk_dense_matrix.h"
#include "mtk_uni_stg_grid_1d.h"

```

Include dependency graph for mtk_div_1d.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [mtk::Div1D](#)

Implements a 1D mimetic divergence operator.

Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

17.9.1 Detailed Description

This class implements a 1D divergence operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (CBSA).

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_div_1d.h](#).

17.10 mtk_div_1d.h

```

00001
00011 /*
00012 Copyright (C) 2015, Computational Science Research Center, San Diego State
00013 University. All rights reserved.
00014
00015 Redistribution and use in source and binary forms, with or without modification,
00016 are permitted provided that the following conditions are met:
00017
00018 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00019 and a copy of the modified files should be reported once modifications are
00020 completed. Documentation related to said modifications should be included.
00021
00022 2. Redistributions of source code must be done through direct
00023 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00024
00025 3. Redistributions of source code must retain the above copyright notice, this
00026 list of conditions and the following disclaimer.
00027
00028 4. Redistributions in binary form must reproduce the above copyright notice,
00029 this list of conditions and the following disclaimer in the documentation and/or
00030 other materials provided with the distribution.
00031
00032 5. Usage of the binary form on proprietary applications shall require explicit
00033 prior written permission from the the copyright holders.
00034
00035 6. Neither the name of the copyright holder nor the names of its contributors
00036 may be used to endorse or promote products derived from this software without
00037 specific prior written permission.
00038
00039 The copyright holders provide no reassurances that the source code provided does
00040 not infringe any patent, copyright, or any other intellectual property rights of
00041 third parties. The copyright holders disclaim any liability to any recipient for
00042 claims brought against recipient by any third party for infringement of that
00043 parties intellectual property rights.
00044
00045 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00046 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00047 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00048 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00049 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00050 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;

```

```


00051 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00052 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00053 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00054 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00055 */
00056
00057 #ifndef MTK_INCLUDE_DIV_1D_H_
00058 #define MTK_INCLUDE_DIV_1D_H_
00059
00060 #include <iostream>
00061 #include <iomanip>
00062
00063 #include "glpk.h"
00064
00065 #include "mtk_roots.h"
00066 #include "mtk_dense_matrix.h"
00067 #include "mtk_uni_stg_grid_1d.h"
00068
00069 namespace mtk {
00070
00081 class Div1D {
00082 public:
00083     friend std::ostream& operator <<(std::ostream& stream, Div1D &in);
00084
00085     Div1D();
00086
00087     Div1D(const Div1D &div);
00088
00089     ~Div1D();
00090
00091     bool ConstructDiv1D(int order_accuracy = kDefaultOrderAccuracy,
00092                        Real mimetic_threshold = kDefaultMimeticThreshold);
00093
00094     int num_bndy_coeffs();
00095
00096     Real* weights_crs(void);
00097
00098     Real* weights_cbs(void);
00099
00100     DenseMatrix ReturnAsDenseMatrix(const
00101     UniStgGrid1D &grid);
00102
00103 private:
00104     bool ComputeStencilInteriorGrid(void);
00105
00106     bool ComputeRationalBasisNullSpace(void);
00107
00108     bool ComputePreliminaryApproximations(void);
00109
00110     bool ComputeWeights(void);
00111
00112     bool ComputeStencilBoundaryGrid(void);
00113
00114     bool AssembleOperator(void);
00115
00116     int order_accuracy_;
00117     int dim_null_;
00118     int num_bndy_coeffs_;
00119     int divergence_length_;
00120
00121     int minrow_;
00122     int row_;
00123
00124     mtk::DenseMatrix rat_basis_null_space_;
00125
00126     Real *coeffs_interior_;
00127     Real *prem_apps_;
00128     Real *weights_crs_;
00129     Real *weights_cbs_;
00130     Real *mim_bndy_;
00131     Real *divergence_;
00132
00133     Real mimetic_threshold_;
00134 };
00135
00136 #endif // End of: MTK_INCLUDE_DIV_1D_H_

```

17.11 include/mtk_enums.h File Reference

Considered enumeration types in the MTK.

This graph shows which files directly or indirectly include this file:



Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

Enumerations

- enum [mtk::MatrixStorage](#) { [mtk::DENSE](#), [mtk::BANDED](#), [mtk::CRS](#) }
Considered matrix storage schemes to implement sparse matrices.
- enum [mtk::MatrixOrdering](#) { [mtk::ROW_MAJOR](#), [mtk::COL_MAJOR](#) }
Considered matrix ordering (for Fortran purposes).
- enum [mtk::FieldNature](#) { [mtk::SCALAR](#), [mtk::VECTOR](#) }
Nature of the field discretized in a given grid.

17.11.1 Detailed Description

Enumeration types are used throughout the MTK to differentiate instances of derived classes, as well as for mnemonic purposes. In this file, the enumeration types are listed alphabetically.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_enums.h](#).

17.12 mtk_enums.h

```
00001
00012 /*
00013 Copyright (C) 2015, Computational Science Research Center, San Diego State
00014 University. All rights reserved.
00015
00016 Redistribution and use in source and binary forms, with or without modification,
00017 are permitted provided that the following conditions are met:
00018
00019 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
```



```

00020 and a copy of the modified files should be reported once modifications are
00021 completed. Documentation related to said modifications should be included.
00022
00023 2. Redistributions of source code must be done through direct
00024 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00025
00026 3. Redistributions of source code must retain the above copyright notice, this
00027 list of conditions and the following disclaimer.
00028
00029 4. Redistributions in binary form must reproduce the above copyright notice,
00030 this list of conditions and the following disclaimer in the documentation and/or
00031 other materials provided with the distribution.
00032
00033 5. Usage of the binary form on proprietary applications shall require explicit
00034 prior written permission from the the copyright holders.
00035
00036 6. Neither the name of the copyright holder nor the names of its contributors
00037 may be used to endorse or promote products derived from this software without
00038 specific prior written permission.
00039
00040 The copyright holders provide no reassurances that the source code provided does
00041 not infringe any patent, copyright, or any other intellectual property rights of
00042 third parties. The copyright holders disclaim any liability to any recipient for
00043 claims brought against recipient by any third party for infringement of that
00044 parties intellectual property rights.
00045
00046 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00047 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00048 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00049 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00050 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00051 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00052 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00053 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00054 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00055 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00056 */
00057
00058 #ifndef MTK_INCLUDE_ENUMS_H_
00059 #define MTK_INCLUDE_ENUMS_H_
00060
00061 namespace mtk {
00062
00077 enum MatrixStorage {
00078     DENSE,
00079     BANDED,
00080     CRS
00081 };
00082
00095 enum MatrixOrdering {
00096     ROW_MAJOR,
00097     COL_MAJOR
00098 };
00099
00113 enum FieldNature {
00114     SCALAR,
00115     VECTOR
00116 };
00117 }
00118 #endif // End of: MTK_INCLUDE_ENUMS_H_

```

17.13 include/mtk_glpk_adapter.h File Reference


Adapter class for the GLPK API.

```


#include <iostream>
#include <iomanip>
#include "glpk.h"
#include "mtk_roots.h"
#include "mtk_dense_matrix.h"

```

Include dependency graph for `mtk_glpk_adapter.h`:



This graph shows which files directly or indirectly include this file:



Classes

- class `mtk::GLPKAdapter`
Adapter class for the GLPK API.

Namespaces

- `mtk`
Mimetic Methods Toolkit namespace.

17.13.1 Detailed Description

This class contains a collection of static classes, that posses direct access to the underlying structure of the matrices, thus allowing programmers to exploit some of the numerical methods implemented in the GLPK.

The **GLPK (GNU Linear Programming Kit)** package is intended for solving large-scale linear programming (LP), mixed integer programming (MIP), and other related problems. It is a set of routines written in ANSI C and organized in the form of a callable library.

See Also

<http://www.gnu.org/software/glpk/>

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_glpk_adapter.h](#).

17.14 mtk_glpk_adapter.h

```

00001
00019 /*
00020 Copyright (C) 2015, Computational Science Research Center, San Diego State
00021 University. All rights reserved.
00022
00023 Redistribution and use in source and binary forms, with or without modification,
00024 are permitted provided that the following conditions are met:
00025
00026 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00027 and a copy of the modified files should be reported once modifications are
00028 completed. Documentation related to said modifications should be included.
00029
00030 2. Redistributions of source code must be done through direct
00031 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00032
00033 3. Redistributions of source code must retain the above copyright notice, this
00034 list of conditions and the following disclaimer.
00035
00036 4. Redistributions in binary form must reproduce the above copyright notice,
00037 this list of conditions and the following disclaimer in the documentation and/or
00038 other materials provided with the distribution.
00039
00040 5. Usage of the binary form on proprietary applications shall require explicit
00041 prior written permission from the the copyright holders.
00042
00043 6. Neither the name of the copyright holder nor the names of its contributors
00044 may be used to endorse or promote products derived from this software without
00045 specific prior written permission.
00046
00047 The copyright holders provide no reassurances that the source code provided does
00048 not infringe any patent, copyright, or any other intellectual property rights of
00049 third parties. The copyright holders disclaim any liability to any recipient for
00050 claims brought against recipient by any third party for infringement of that
00051 parties intellectual property rights.
00052
00053 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00054 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00055 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00056 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00057 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00058 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00059 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00060 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00061 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00062 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00063 */
00064
00065 #ifndef MTK_INCLUDE_GLPK_ADAPTER_H_
00066 #define MTK_INCLUDE_GLPK_ADAPTER_H_
00067
00068 #include <iostream>
00069 #include <iomanip>
00070
00071 #include "glpk.h"
00072
00073 #include "mtk_roots.h"
00074 #include "mtk_dense_matrix.h"
00075
00076 namespace mtk {
00077
00101 class GLPKAdapter {

```

```

00102 public:
00121 static mtk::Real SolveSimplexAndCompare(
00122     mtk::Real *A,
00123     int nrows,
00124     int ncols,
00125     int kk,
00126     mtk::Real *hh,
00127     mtk::Real *qq,
00128     int robjective,
00129     mtk::Real mimetic_tol,
00130     int copy);
00131 }
00132 #endif // End of: MTK_INCLUDE_MTK_GLPK_ADAPTER_H_

```

17.15 include/mtk_grad_1d.h File Reference


Includes the definition of the class Grad1D.

```


#include <iostream>
#include <iomanip>
#include "glpk.h"
#include "mtk_roots.h"
#include "mtk_dense_matrix.h"
#include "mtk_uni_stg_grid_1d.h"

```

Include dependency graph for mtk_grad_1d.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [mtk::Grad1D](#)

Implements a 1D mimetic gradient operator.

Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

17.15.1 Detailed Description

This class implements a 1D gradient operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (CB-SA).

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_grad_1d.h](#).

17.16 mtk_grad_1d.h

```

00001
00011 /*
00012 Copyright (C) 2015, Computational Science Research Center, San Diego State
00013 University. All rights reserved.
00014
00015 Redistribution and use in source and binary forms, with or without modification,
00016 are permitted provided that the following conditions are met:
00017
00018 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00019 and a copy of the modified files should be reported once modifications are
00020 completed. Documentation related to said modifications should be included.
00021
00022 2. Redistributions of source code must be done through direct
00023 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00024
00025 3. Redistributions of source code must retain the above copyright notice, this
00026 list of conditions and the following disclaimer.
00027
00028 4. Redistributions in binary form must reproduce the above copyright notice,
00029 this list of conditions and the following disclaimer in the documentation and/or
00030 other materials provided with the distribution.
00031
00032 5. Usage of the binary form on proprietary applications shall require explicit
00033 prior written permission from the the copyright holders.
00034
00035 6. Neither the name of the copyright holder nor the names of its contributors
00036 may be used to endorse or promote products derived from this software without
00037 specific prior written permission.
00038
00039 The copyright holders provide no reassurances that the source code provided does
00040 not infringe any patent, copyright, or any other intellectual property rights of
00041 third parties. The copyright holders disclaim any liability to any recipient for
00042 claims brought against recipient by any third party for infringement of that
00043 parties intellectual property rights.
00044
00045 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00046 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00047 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00048 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00049 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00050 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;

```

```


00051 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00052 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00053 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00054 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00055 */
00056
00057 #ifndef MTK_INCLUDE_GRAD_1D_H_
00058 #define MTK_INCLUDE_GRAD_1D_H_
00059
00060 #include <iostream>
00061 #include <iomanip>
00062
00063 #include "glpk.h"
00064
00065 #include "mtk_roots.h"
00066 #include "mtk_dense_matrix.h"
00067 #include "mtk_uni_stg_grid_1d.h"
00068
00069 namespace mtk {
00070
00081 class Grad1D {
00082 public:
00083     friend std::ostream& operator <<(std::ostream& stream, Grad1D &in);
00084
00085     Grad1D();
00086
00087     Grad1D(const Grad1D &grad);
00088
00089     ~Grad1D();
00090
00091     bool ConstructGrad1D(int order_accuracy = kDefaultOrderAccuracy,
00092                         Real mimetic_threshold = kDefaultMimeticThreshold);
00093
00094     int num_bndy_coeffs();
00095
00096     Real *weights_crs(void);
00097
00098     Real *weights_cbs(void);
00099
00100     DenseMatrix ReturnAsDenseMatrix(const
00101     UniStgGrid1D &grid);
00102
00103 private:
00104     bool ComputeStencilInteriorGrid(void);
00105
00106     bool ComputeRationalBasisNullSpace(void);
00107
00108     bool ComputePreliminaryApproximations(void);
00109
00110     bool ComputeWeights(void);
00111
00112     bool ComputeStencilBoundaryGrid(void);
00113
00114     bool AssembleOperator(void);
00115
00116     int order_accuracy_;
00117     int dim_null_;
00118     int num_bndy_approxs_;
00119     int num_bndy_coeffs_;
00120     int gradient_length_;
00121
00122     int minrow_;
00123     int row_;
00124
00125     mtk::DenseMatrix rat_basis_null_space_;
00126
00127     Real *coeffs_interior_;
00128     Real *prem_apps_;
00129     Real *weights_crs_;
00130     Real *weights_cbs_;
00131     Real *mim_bndy_;
00132     Real *gradient_;
00133
00134     Real mimetic_threshold_;
00135 };
00136
00137 #endif // End of: MTK_INCLUDE_GRAD_1D_H_

```


17.17 include/mtk_lap_1d.h File Reference

Includes the definition of the class Lap1D.

```
#include "mtk_dense_matrix.h"
#include "mtk_uni_stg_grid_1d.h"
Include dependency graph for mtk_lap_1d.h:
```



This graph shows which files directly or indirectly include this file:



Classes

- class `mtk::Lap1D`
Implements a 1D mimetic Laplacian operator.

Namespaces

- `mtk`

Mimetic Methods Toolkit namespace.

17.17.1 Detailed Description

This class implements a 1D Laplacian operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (CBSA).

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_lap_1d.h](#).

17.18 mtk_lap_1d.h

```

00001
00011 /*
00012 Copyright (C) 2015, Computational Science Research Center, San Diego State
00013 University. All rights reserved.
00014
00015 Redistribution and use in source and binary forms, with or without modification,
00016 are permitted provided that the following conditions are met:
00017
00018 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00019 and a copy of the modified files should be reported once modifications are
00020 completed. Documentation related to said modifications should be included.
00021
00022 2. Redistributions of source code must be done through direct
00023 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00024
00025 3. Redistributions of source code must retain the above copyright notice, this
00026 list of conditions and the following disclaimer.
00027
00028 4. Redistributions in binary form must reproduce the above copyright notice,
00029 this list of conditions and the following disclaimer in the documentation and/or
00030 other materials provided with the distribution.
00031
00032 5. Usage of the binary form on proprietary applications shall require explicit
00033 prior written permission from the the copyright holders.
00034
00035 6. Neither the name of the copyright holder nor the names of its contributors
00036 may be used to endorse or promote products derived from this software without
00037 specific prior written permission.
00038
00039 The copyright holders provide no reassurances that the source code provided does
00040 not infringe any patent, copyright, or any other intellectual property rights of
00041 third parties. The copyright holders disclaim any liability to any recipient for
00042 claims brought against recipient by any third party for infringement of that
00043 parties intellectual property rights.
00044
00045 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00046 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00047 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00048 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00049 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00050 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00051 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00052 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00053 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00054 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00055 */
00056
00057 #ifndef MTK_INCLUDE_LAP_1D_H_
00058 #define MTK_INCLUDE_LAP_1D_H_
00059
00060 #include "mtk_dense_matrix.h"
00061
00062 #include "mtk_uni_stg_grid_1d.h"
00063
00064 namespace mtk {

```



```

00065
00076 class Lap1D {
00077 public:
00079     friend std::ostream& operator <<(std::ostream& stream, Lap1D &in);
00080
00082     Lap1D();
00083
00089     Lap1D(const Lap1D &lap);
00090
00092     ~Lap1D();
00093
00099     bool ConstructLap1D(int order_accuracy = kDefaultOrderAccuracy,
00100                        Real mimetic_threshold = kDefaultMimeticThreshold);
00101
00107     DenseMatrix ReturnAsDenseMatrix(const
00108     UniStgGrid1D &grid);
00108
00114     mtk::Real* Data(const UniStgGrid1D &grid);
00115
00116 private:
00117     int order_accuracy_;
00118     int laplacian_length_;
00119
00120     Real *laplacian_;
00121
00122     Real mimetic_threshold_;
00123 };
00124 }
00125 #endif // End of: MTK_INCLUDE_LAP_1D_H_

```


17.19 include/mtk_lapack_adapter.h File Reference

Adapter class for the LAPACK API.


```
#include "mtk_roots.h"
```

```
#include "mtk_dense_matrix.h"
```

Include dependency graph for mtk_lapack_adapter.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [mtk::LAPACKAdapter](#)
Adapter class for the LAPACK API.

Namespaces

- [mtk](#)
Mimetic Methods Toolkit namespace.

17.19.1 Detailed Description

This class contains a collection of static classes, that posses direct access to the underlying structure of the matrices, thus allowing programmers to exploit some of the numerical methods implemented in the LAPACK.

The **LAPACK** is written in Fortran 90 and provides routines for solving systems of simultaneous linear equations, least-squares solutions of linear systems of equations, eigenvalue problems, and singular value problems.

See Also

<http://www.netlib.org/lapack/>

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_lapack_adapter.h](#).

17.20 mtk_lapack_adapter.h

```

00001
00018 /*
00019 Copyright (C) 2015, Computational Science Research Center, San Diego State
00020 University. All rights reserved.
00021
00022 Redistribution and use in source and binary forms, with or without modification,
00023 are permitted provided that the following conditions are met:
00024
00025 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00026 and a copy of the modified files should be reported once modifications are
00027 completed. Documentation related to said modifications should be included.
  
```

```

00028
00029 2. Redistributions of source code must be done through direct
00030 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00031
00032 3. Redistributions of source code must retain the above copyright notice, this
00033 list of conditions and the following disclaimer.
00034
00035 4. Redistributions in binary form must reproduce the above copyright notice,
00036 this list of conditions and the following disclaimer in the documentation and/or
00037 other materials provided with the distribution.
00038
00039 5. Usage of the binary form on proprietary applications shall require explicit
00040 prior written permission from the the copyright holders.
00041
00042 6. Neither the name of the copyright holder nor the names of its contributors
00043 may be used to endorse or promote products derived from this software without
00044 specific prior written permission.
00045
00046 The copyright holders provide no reassurances that the source code provided does
00047 not infringe any patent, copyright, or any other intellectual property rights of
00048 third parties. The copyright holders disclaim any liability to any recipient for
00049 claims brought against recipient by any third party for infringement of that
00050 parties intellectual property rights.
00051
00052 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00053 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00054 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00055 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00056 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00057 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00058 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00059 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00060 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00061 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00062 */
00063
00064 #ifndef MTK_INCLUDE_LAPACK_ADAPTER_H_
00065 #define MTK_INCLUDE_LAPACK_ADAPTER_H_
00066
00067 #include "mtk_roots.h"
00068 #include "mtk_dense_matrix.h"
00069
00070 namespace mtk {
00071
00089 class LAPACKAdapter {
00090 public:
00101     static int SolveDenseSystem(mtk::DenseMatrix &mm,
00102                                mtk::Real *rhs);
00103
00114     static int SolveDenseSystem(mtk::DenseMatrix &mm,
00115                                mtk::DenseMatrix &rr);
00116
00128     static int SolveRectangularDenseSystem(const
00129 mtk::DenseMatrix &aa,
00129                                mtk::Real *ob_,
00130                                int ob_ld_);
00131
00143     static mtk::DenseMatrix QRFactorDenseMatrix(
00144 DenseMatrix &matrix);
00144 };
00145 }
00146 #endif // End of: MTK_INCLUDE_LAPACK_ADAPTER_H_

```

17.21 include/mtk_matrix.h File Reference


Definition of the representation of a matrix in the MTK.

```


#include <iostream>
#include "mtk_roots.h"
#include "mtk_enums.h"

```

Include dependency graph for `mtk_matrix.h`:



This graph shows which files directly or indirectly include this file:



Classes

- class [mtk::Matrix](#)

Definition of the representation of a matrix in the MTK.

Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

17.21.1 Detailed Description

Definition of the representation for the matrices implemented in the MTK.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_matrix.h](#).

17.22 mtk_matrix.h

```

00001
00010 /*
00011 Copyright (C) 2015, Computational Science Research Center, San Diego State
00012 University. All rights reserved.
00013
00014 Redistribution and use in source and binary forms, with or without modification,
00015 are permitted provided that the following conditions are met:
00016
00017 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00018 and a copy of the modified files should be reported once modifications are
00019 completed. Documentation related to said modifications should be included.
00020
00021 2. Redistributions of source code must be done through direct
00022 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00023
00024 3. Redistributions of source code must retain the above copyright notice, this
00025 list of conditions and the following disclaimer.
00026
00027 4. Redistributions in binary form must reproduce the above copyright notice,
00028 this list of conditions and the following disclaimer in the documentation and/or
00029 other materials provided with the distribution.
00030
00031 5. Usage of the binary form on proprietary applications shall require explicit
00032 prior written permission from the the copyright holders.
00033
00034 6. Neither the name of the copyright holder nor the names of its contributors
00035 may be used to endorse or promote products derived from this software without
00036 specific prior written permission.
00037
00038 The copyright holders provide no reassurances that the source code provided does
00039 not infringe any patent, copyright, or any other intellectual property rights of
00040 third parties. The copyright holders disclaim any liability to any recipient for
00041 claims brought against recipient by any third party for infringement of that
00042 parties intellectual property rights.
00043
00044 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00045 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00046 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00047 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00048 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00049 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00050 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00051 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00052 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00053 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00054 */
00055
00056 #ifndef MTK_INCLUDE_MATRIX_H_
00057 #define MTK_INCLUDE_MATRIX_H_
00058
00059 #include <iostream>
00060
00061 #include "mtk_roots.h"
00062 #include "mtk_enums.h"
00063
00064 namespace mtk {
00065
00075 class Matrix {
00076 public:
00077     Matrix();
00078
00079     Matrix(const Matrix &in);
00080
00081     ~Matrix();
00082
00083     MatrixStorage storage() const;
00084
00085     MatrixOrdering ordering() const;
00086
00087     int num_rows() const;
00088
00089     int num_cols() const;
00090
00091     int num_values() const;
00092
00093     int ld() const;
00094
00095     int num_zero() const;

```

```

00134
00140     int num_non_zero() const;
00141
00149     int num_null() const;
00150
00158     int num_non_null() const;
00159
00165     int kl() const;
00166
00172     int ku() const;
00173
00179     int bandwidth() const;
00180
00188     Real abs_density() const;
00189
00197     Real rel_density() const;
00198
00206     Real abs_sparsity() const;
00207
00215     Real rel_sparsity() const;
00216
00224     void set_storage(const MatrixStorage &tt);
00225
00233     void set_ordering(const MatrixOrdering &oo);
00234
00240     void set_num_rows(int num_rows);
00241
00247     void set_num_cols(int num_cols);
00248
00254     void set_num_zero(int in);
00255
00261     void set_num_null(int in);
00262
00264     void IncreaseNumZero();
00265
00267     void IncreaseNumNull();
00268
00269 private:
00270     MatrixStorage storage_;
00271
00272     MatrixOrdering ordering_;
00273
00274     int num_rows_;
00275     int num_cols_;
00276     int num_values_;
00277     int ld_;
00278
00279     int num_zero_;
00280     int num_non_zero_;
00281     int num_null_;
00282     int num_non_null_;
00283
00284     int kl_;
00285     int ku_;
00286     int bandwidth_;
00287
00288     Real abs_density_;
00289     Real rel_density_;
00290     Real abs_sparsity_;
00291     Real rel_sparsity_;
00292 };
00293 }
00294 #endif // End of: MTK_INCLUDE_MATRIX_H_

```

17.23 include/mtk_quad_1d.h File Reference


Includes the definition of the class Quad1D.

```


#include <iostream>
#include <iomanip>
#include <vector>

```

Include dependency graph for mtk_quad_1d.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [mtk::Quad1D](#)
Implements a 1D mimetic quadrature.

Namespaces

- [mtk](#)
Mimetic Methods Toolkit namespace.

17.23.1 Detailed Description

This class implements a 1D quadrature solver based on the mimetic discretization of the gradient operator.

See Also

[mtk::Grad1D](#)

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Todo Implement this class.

Definition in file [mtk_quad_1d.h](#).

17.24 mtk_quad_1d.h

```

00001
00015 /*
00016 Copyright (C) 2015, Computational Science Research Center, San Diego State
00017 University. All rights reserved.
00018
00019 Redistribution and use in source and binary forms, with or without modification,
00020 are permitted provided that the following conditions are met:
00021
00022 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00023 and a copy of the modified files should be reported once modifications are
00024 completed. Documentation related to said modifications should be included.
00025
00026 2. Redistributions of source code must be done through direct
00027 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00028
00029 3. Redistributions of source code must retain the above copyright notice, this
00030 list of conditions and the following disclaimer.
00031
00032 4. Redistributions in binary form must reproduce the above copyright notice,
00033 this list of conditions and the following disclaimer in the documentation and/or
00034 other materials provided with the distribution.
00035
00036 5. Usage of the binary form on proprietary applications shall require explicit
00037 prior written permission from the the copyright holders.
00038
00039 6. Neither the name of the copyright holder nor the names of its contributors
00040 may be used to endorse or promote products derived from this software without
00041 specific prior written permission.
00042
00043 The copyright holders provide no reassurances that the source code provided does
00044 not infringe any patent, copyright, or any other intellectual property rights of
00045 third parties. The copyright holders disclaim any liability to any recipient for
00046 claims brought against recipient by any third party for infringement of that
00047 parties intellectual property rights.
00048
00049 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00050 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00051 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00052 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00053 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00054 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00055 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00056 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00057 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00058 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00059 */
00060
00061 #ifndef MTK_INCLUDE_QUAD_1D_H_
00062 #define MTK_INCLUDE_QUAD_1D_H_
00063
00064 #include <iostream>
00065 #include <iomanip>
00066
00067 #include <vector>
00068
00069 namespace mtk {
00070
00081 class Quad1D {
00082 public:
00083     friend std::ostream& operator <<(std::ostream& stream, Quad1D &in);
00084
00085     Quad1D();
00086
00087     Quad1D(const Quad1D &quad);
00088
00089
00090
00091
00092
00093
00094
00095

```



```


00097 ~Quad1D();
00098
00104 int degree_approximation() const;
00105
00111 Real *weights() const;
00112
00121 Real Integrate(Real (*Integrand)(Real xx), UniStgGrid1D grid);
00122
00123 private:
00124 int degree_approximation_;
00125
00126 std::vector<Real> weights_;
00127 };
00128 }
00129 #endif // End of: MTK_INCLUDE_QUAD_1D_H_

```

17.25 include/mtk_roots.h File Reference

Fundamental definitions to be used across all classes of the MTK.

This graph shows which files directly or indirectly include this file:



Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

Typedefs

- typedef float [mtk::Real](#)

Users can simply change this to build a double- or single-precision MTK.

Variables

- const float [mtk::kZero](#) {0.0f}
MTK's zero defined according to selective compilation.
- const float [mtk::kOne](#) {1.0f}
MTK's one defined according to selective compilation.
- const float [mtk::kDefaultTolerance](#) {1e-7f}
Considered tolerance for comparisons in numerical methods.
- const int [mtk::kDefaultOrderAccuracy](#) {2}
Default order of accuracy for mimetic operators.
- const float [mtk::kDefaultMimeticThreshold](#) {1.e-6f}
Default tolerance for higher-order mimetic operators.
- const int [mtk::kCriticalOrderAccuracyDiv](#) {8}

At this order (and higher) we must use the CBSA to construct.

- `const int mtk::kCriticalOrderAccuracyGrad {10}`

At this order (and higher) we must use the CBSA to construct.

17.25.1 Detailed Description

This file contains the fundamental definitions that classes of the MTK rely on to be implemented. Examples of these definitions are the definition of fundamental data types, and global variables affecting the construction of mimetic operators, among others.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at sciences dot sdsu dot edu

Todo Documentation should (better?) capture effects from selective compilation.

Todo Test selective precision mechanism.

Definition in file [mtk_roots.h](#).

17.26 mtk_roots.h

```
00001
00017 /*
00018 Copyright (C) 2015, Computational Science Research Center, San Diego State
00019 University. All rights reserved.
00020
00021 Redistribution and use in source and binary forms, with or without modification,
00022 are permitted provided that the following conditions are met:
00023
00024 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00025 and a copy of the modified files should be reported once modifications are
00026 completed. Documentation related to said modifications should be included.
00027
00028 2. Redistributions of source code must be done through direct
00029 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00030
00031 3. Redistributions of source code must retain the above copyright notice, this
00032 list of conditions and the following disclaimer.
00033
00034 4. Redistributions in binary form must reproduce the above copyright notice,
00035 this list of conditions and the following disclaimer in the documentation and/or
00036 other materials provided with the distribution.
00037
00038 5. Usage of the binary form on proprietary applications shall require explicit
00039 prior written permission from the the copyright holders.
00040
00041 6. Neither the name of the copyright holder nor the names of its contributors
00042 may be used to endorse or promote products derived from this software without
00043 specific prior written permission.
00044
00045 The copyright holders provide no reassurances that the source code provided does
00046 not infringe any patent, copyright, or any other intellectual property rights of
00047 third parties. The copyright holders disclaim any liability to any recipient for
00048 claims brought against recipient by any third party for infringement of that
00049 parties intellectual property rights.
00050
00051 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00052 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00053 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00054 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00055 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00056 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00057 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00058 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00059 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
```

```

00060 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00061 */
00062
00063 #ifndef MTK_INCLUDE_ROOTS_H_
00064 #define MTK_INCLUDE_ROOTS_H_
00065
00071 namespace mtk {
00072
00080 #ifdef MTK_PRECISION_DOUBLE
00081 typedef double Real;
00082 #else
00083 typedef float Real;
00084 #endif
00085
00103 #ifdef MTK_PRECISION_DOUBLE
00104 const double kZero{0.0};
00105 const double kOne{1.0};
00106 #else
00107 const float kZero{0.0f};
00108 const float kOne{1.0f};
00109 #endif
00110
00118 #ifdef MTK_PRECISION_DOUBLE
00119 const double kDefaultTolerance{1e-7};
00120 #else
00121 const float kDefaultTolerance{1e-7f};
00122 #endif
00123
00133 const int kDefaultOrderAccuracy{2};
00134
00144 #ifdef MTK_PRECISION_DOUBLE
00145 const double kDefaultMimeticThreshold{1.e-6};
00146 #else
00147 const float kDefaultMimeticThreshold{1.e-6f};
00148 #endif
00149
00157 const int kCriticalOrderAccuracyDiv{8};
00158
00166 const int kCriticalOrderAccuracyGrad{10};
00167 }
00168 #endif // End of: MTK_INCLUDE_ROOTS_H_


```

17.27 include/mtk_tools.h File Reference


Tool manager class.

```
#include <ctime>
```

Include dependency graph for mtk_tools.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [mtk::Tools](#)
Tool manager class.

Namespaces

- [mtk](#)
Mimetic Methods Toolkit namespace.

17.27.1 Detailed Description

Basic tools to ensure execution correctness.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_tools.h](#).

17.28 mtk_tools.h

```

00001
00010 /*
00011 Copyright (C) 2015, Computational Science Research Center, San Diego State
00012 University. All rights reserved.
00013
00014 Redistribution and use in source and binary forms, with or without modification,
00015 are permitted provided that the following conditions are met:
00016
00017 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00018 and a copy of the modified files should be reported once modifications are
00019 completed. Documentation related to said modifications should be included.
00020
00021 2. Redistributions of source code must be done through direct
00022 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00023
00024 3. Redistributions of source code must retain the above copyright notice, this
00025 list of conditions and the following disclaimer.
00026
00027 4. Redistributions in binary form must reproduce the above copyright notice,
00028 this list of conditions and the following disclaimer in the documentation and/or
00029 other materials provided with the distribution.
00030
00031 5. Usage of the binary form on proprietary applications shall require explicit
00032 prior written permission from the the copyright holders.
00033
00034 6. Neither the name of the copyright holder nor the names of its contributors
00035 may be used to endorse or promote products derived from this software without
00036 specific prior written permission.
00037
00038 The copyright holders provide no reassurances that the source code provided does
  
```

```

00039 not infringe any patent, copyright, or any other intellectual property rights of
00040 third parties. The copyright holders disclaim any liability to any recipient for
00041 claims brought against recipient by any third party for infringement of that
00042 parties intellectual property rights.
00043
00044 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00045 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00046 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00047 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00048 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00049 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00050 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00051 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00052 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00053 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00054 */
00055
00056 #ifndef MTK_INCLUDE_TOOLS_H_
00057 #define MTK_INCLUDE_TOOLS_H_
00058
00059 #include <ctime>
00060
00061 namespace mtk {
00062
00072 class Tools {
00073 public:
00084     static void Prevent(const bool condition,
00085                        const char *fname,
00086                        int lineno,
00087                        const char *fxname);
00088
00094     static void BeginTestNo(const int &nn);
00095
00101     static void EndTestNo(const int &nn);
00102
00103 private:
00104     static int test_number_;
00105
00106     static clock_t begin_time_;
00107 };
00108
00109 #endif // End of: MTK_INCLUDE_TOOLS_H_

```

17.29 include/mtk_uni_stg_grid_1d.h File Reference


Definition of an 1D uniform staggered grid.

```


#include <vector>
#include <string>
#include "mtk_roots.h"

```

Include dependency graph for mtk_uni_stg_grid_1d.h:



This graph shows which files directly or indirectly include this file:



Classes

- class `mtk::UniStgGrid1D`
Uniform 1D Staggered Grid.

Namespaces

- `mtk`
Mimetic Methods Toolkit namespace.

17.29.1 Detailed Description

Definition of an 1D uniform staggered grid.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Todo Create overloaded binding routines that read data from files.

Definition in file `mtk_uni_stg_grid_1d.h`.

17.30 mtk_uni_stg_grid_1d.h

```

00001
00012 /*
00013 Copyright (C) 2015, Computational Science Research Center, San Diego State
00014 University. All rights reserved.
00015
00016 Redistribution and use in source and binary forms, with or without modification,
00017 are permitted provided that the following conditions are met:
00018
00019 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00020 and a copy of the modified files should be reported once modifications are
00021 completed. Documentation related to said modifications should be included.
00022
00023 2. Redistributions of source code must be done through direct
00024 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00025
00026 3. Redistributions of source code must retain the above copyright notice, this
00027 list of conditions and the following disclaimer.
  
```

```

00028
00029 4. Redistributions in binary form must reproduce the above copyright notice,
00030 this list of conditions and the following disclaimer in the documentation and/or
00031 other materials provided with the distribution.
00032
00033 5. Usage of the binary form on proprietary applications shall require explicit
00034 prior written permission from the the copyright holders.
00035
00036 6. Neither the name of the copyright holder nor the names of its contributors
00037 may be used to endorse or promote products derived from this software without
00038 specific prior written permission.
00039
00040 The copyright holders provide no reassurances that the source code provided does
00041 not infringe any patent, copyright, or any other intellectual property rights of
00042 third parties. The copyright holders disclaim any liability to any recipient for
00043 claims brought against recipient by any third party for infringement of that
00044 parties intellectual property rights.
00045
00046 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00047 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00048 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00049 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00050 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00051 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00052 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00053 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00054 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00055 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00056 */
00057
00058 #ifndef MTK_INCLUDE_UNI_STG_GRID_1D_H_
00059 #define MTK_INCLUDE_UNI_STG_GRID_1D_H_
00060
00061 #include <vector>
00062 #include <string>
00063
00064 #include "mtk_roots.h"
00065
00066 namespace mtk {
00067
00077 class UniStgGrid1D {
00078 public:
00080     friend std::ostream& operator <<(std::ostream& stream, UniStgGrid1D &in);
00081
00083     UniStgGrid1D();
00084
00090     UniStgGrid1D(const UniStgGrid1D &grid);
00091
00102     UniStgGrid1D(const Real &west_bndy_x,
00103                  const Real &east_bndy_x,
00104                  const int &num_cells_x,
00105                  const mtk::FieldNature &nature = mtk::SCALAR);
00106
00108     ~UniStgGrid1D();
00109
00115     Real delta_x() const;
00116
00122     Real *discrete_domain_x();
00123
00129     Real *discrete_field_u();
00130
00136     int num_cells_x() const;
00137
00143     void BindScalarField(Real (*ScalarField)(Real xx));
00144
00156     void BindVectorField(Real (*VectorField)(Real xx));
00157
00169     bool WriteToFile(std::string filename,
00170                     std::string space_name,
00171                     std::string field_name);
00172
00173 private:
00174     FieldNature nature_;
00175
00176     std::vector<Real> discrete_domain_x_;
00177     std::vector<Real> discrete_field_u_;
00178
00179     Real west_bndy_x_;
00180     Real east_bndy_x_;
00181     Real num_cells_x_;
00182     Real delta_x_;

```

```

00183 };
00184 }
00185 #endif // End of: MTK_INCLUDE_UNI_STG_GRID_1D_H_

```

17.31 Makefile.inc File Reference

17.32 Makefile.inc

```

00001 # Makefile setup file for MTK.
00002
00003 SHELL := /bin/bash
00004
00005 # Please set the following variables up:
00006
00007 # 2. Absolute path to base directory of the MTK... where is the MTK?
00008 # _____
00009
00010 BASE = /home/ejspeiro/Dropbox/MTK
00011
00012 # 2. The machine (platform) identifier and required precision.
00013 # _____
00014
00015 # Options are:
00016 # - LINUX: A LINUX box installation.
00017 # - OSX: Uses OS X optimized solvers.
00018
00019 PLAT = LINUX
00020
00021 # Options are:
00022 # - SINGLE: Use 4 B floating point numbers.
00023 # - DOUBLE: Use 8 B floating point numbers.
00024
00025 PRECISION = DOUBLE
00026
00027 # 3. Optimized solvers and operations by means of ATLAS in Linux?
00028 # _____
00029
00030 # If you have selected OSX in step 1, then you don't need to worry about this.
00031
00032 # Options are ON xor OFF:
00033
00034 ATL_OPT = OFF
00035
00036 # 4. Paths to dependencies (header files for compiling).
00037 # _____
00038
00039 # GLPK include path (soon to go):
00040
00041 GLPK_INC = $(HOME)/Libraries/glpk-4.55/include
00042
00043 # Linux: If ATLAS optimization is ON, users should only provide the path to
00044 # ATLAS:
00045
00046 ATLAS_INC = $(HOME)/Libraries/ATLAS_3.8.4-CORE/include
00047
00048 # OS X: Do nothing.
00049
00050 # 5. Paths to dependencies (archive files for (static) linking).
00051 # _____
00052
00053 # GLPK linking path (soon to go):
00054
00055 GLPK_LIB = $(HOME)/Libraries/glpk-4.55/lib/libglpk.a
00056
00057 # If optimization is OFF, then provide the paths for:
00058
00059 BLAS_LIB = $(HOME)/Libraries/BLAS/libblas.a
00060 LAPACK_LIB = $(HOME)/Libraries/lapack-3.4.1/liblapack.a
00061
00062 # WARNING: Vendor libraries should be used whenever they are available.
00063
00064 # However, if optimization is ON, please provide the path the ATLAS' archive:
00065
00066 ATLAS_LIB = $(HOME)/Libraries/ATLAS_3.8.4-CORE/ATLAS_3.8.4-BUILD-Citadel/lib
00067

```



```

00068 # 6. Compiler and its flags.
00069 # _____
00070
00071 CC = g++
00072
00073 # Debug Level. Options are:
00074 # 0. NO debug at all NOR any run-time checks... be cautious!
00075 # 1. Verbose (execution messages) AND run-time checks.
00076 # 2. Level 1 plus intermediate scalar-valued results.
00077 # 3. Level 2 plus intermediate array-valued results.
00078
00079 DEBUG_LEVEL = 3
00080
00081 # Flags recommended for release code:
00082
00083 CCFLAGS = -Wall -O2
00084
00085 # Flags recommended for debugging code:
00086
00087 CCFLAGS = -Wall -g
00088
00089 # 7. Archiver, its flags, and ranlib:
00090 # _____
00091
00092 ARCH = ar
00093 ARCHFLAGS = cr
00094
00095 # If your system does not have "ranlib" then set: "RANLIB = echo":
00096
00097 RANLIB = echo
00098
00099 # But, if possible:
00100
00101 RANLIB = ranlib
00102
00103 # 8. Valgrind's memcheck options:
00104 # _____
00105
00106 MEMCHECK_OPTS = -v --tool=memcheck --leak-check=full --show-leak-kinds=all \
00107 --track-origins=yes --freelist-vol=20000000
00108
00109 # Done!
00110
00111 # _____
00112 # _____
00113 # _____
00114
00115 # MTK-related.
00116 # _____
00117
00118 SRC = $(BASE)/src
00119 INCLUDE = $(BASE)/include
00120 LIB = $(BASE)/lib
00121 MTK_LIB = $(LIB)/libmtk.a
00122 TESTS = $(BASE)/tests
00123 EXAMPLES = $(BASE)/examples
00124
00125 # Compiling-related.
00126 # _____
00127
00128 CCFLAGS += -std=c++11 -fPIC -DMTK_DEBUG_LEVEL=$(DEBUG_LEVEL) -I$(INCLUDE) -c
00129
00130 ifeq ($(PRECISION),DOUBLE)
00131 CCFLAGS += -DMTK_PRECISION_DOUBLE
00132 else
00133 CCFLAGS += -DMTK_PRECISION_SINGLE
00134 endif
00135
00136 # Only the GLPK is included because the other dependencies are coded in Fortran.
00137
00138 ifeq ($(ATL_OPT),ON)
00139 CCFLAGS += -I$(GLPK_INC) $(ATLAS_INC)
00140 else
00141 CCFLAGS += -I$(GLPK_INC)
00142 endif
00143
00144 # Linking-related.
00145 # _____
00146
00147 NOOPT_LIBS = $(LAPACK_LIB) $(BLAS_LIB) -lm $(GLPK_LIB) -lstdc++
00148

```

```

00149 OPT_LIBS      = -L$(ATLAS_LIB) -latlas -llapack -lblas -lm -latlas -lstdc++
00150
00151 ifeq ($(PLAT),OSX)
00152     LINKER      = g++
00153     LINKER      += -framework Accelerate $(GLPK_LIB) $(MTK_LIB)
00154 else
00155     ifeq ($(ATL_OPT),ON)
00156         LINKER    = g++
00157         LIBS      = $(MTK_LIB)
00158         LIBS      += $(OPT_LIBS)
00159     else
00160         LINKER    = gfortran
00161         LIBS      = $(MTK_LIB)
00162         LIBS      += $(NOOPT_LIBS)
00163     endif
00164 endif
00165
00166 #      Documentation-related.
00167 #
00168
00169 DOCGEN          = doxygen
00170 DOCFILENAME     = doc_config.dxcf
00171 DOC             = $(BASE)/doc
00172 DOCFILE        = $(BASE)/$(DOCFILENAME)

```

17.33 README.md File Reference

17.34 README.md

```

00001 # The Mimetic Methods Toolkit (MTK)
00002
00003 By: **Eduardo J. Sanchez, Ph.D. - esanchez at mail dot sdsu dot edu**
00004
00005
00006 ## 1. Description
00007
00008 We define numerical methods that are based on discretizations preserving the
00009 properties of their continuum counterparts to be **mimetic**.
00010
00011 The **Mimetic Methods Toolkit (MTK)** is a C++ library for mimetic numerical
00012 methods. It is arranged as a set of classes for **mimetic quadratures**,
00013 **mimetic interpolation**, and **mimetic discretization** methods for the
00014 numerical solution of ordinary and partial differential equations.
00015
00016
00017 ## 2. Dependencies
00018
00019 This README assumes all of these dependencies are installed in the following
00020 folder:
00021
00022 ```
00023 $(HOME)/Libraries/
00024 ```
00025
00026 In this version, the MTK optionally uses ATLAS-optimized BLAS and LAPACK
00027 routines for the internal computation on some of the layers. However, ATLAS
00028 requires both BLAS and LAPACK in order to create their optimized distributions.
00029 Therefore, the following dependencies tree arises:
00030
00031 ### For Linux:
00032
00033 1. LAPACK - Available from: http://www.netlib.org/lapack/
00034 1. BLAS - Available from: http://www.netlib.org/blas/
00035
00036 2. (Optional) ATLAS - Available from: http://math-atlas.sourceforge.net/
00037 1. BLAS - Available from: http://www.netlib.org/blas/
00038 2. LAPACK - Available from: http://www.netlib.org/lapack/
00039
00040 3. (Optional) Valgrind - Available from: http://valgrind.org/
00041
00042 4. (Optional) Doxygen - Available from http://www.stack.nl/~dimitri/doxygen/
00043
00044 ### For OS X:
00045
00046 There are no dependences for OS X.

```

```

00047
00048
00049 ## 3. Installation
00050
00051 ### PART 1. CONFIGURATION OF THE MAKEFILE.
00052
00053 The following steps are required the build and test the MTK. Please use the
00054 accompanying 'Makefile.inc' file, which should provide a solid template to
00055 start with. The following command provides help on the options for make:
00056
00057 ```
00058 $ make help
00059 -----
00060 Makefile for the MTK.
00061
00062 Options are:
00063 - make: builds only the library and the examples.
00064 - all: builds the library, the examples and the documentation.
00065 - mtklib: builds the library, i.e. generates the archive files.
00066 - tests: generates the tests.
00067 - examples: generates the examples.
00068 - gendoc: generates the documentation for the library.
00069 - checkheaders: checks syntax of the header files.
00070
00071 - clean: cleans ALL the generated files.
00072 - cleanlib: cleans the generated archive and object files.
00073 - cleantests: cleans the generated tests executables.
00074 - cleanexamples: cleans the generated examples executables.
00075 -----
00076 ```
00077
00078 ### PART 2. BUILD THE LIBRARY.
00079
00080 ```
00081 $ make
00082 ```
00083
00084 If successful you'll read (before building the tests and examples):
00085
00086 ```
00087 ----- Library created! Check in /home/ejspeiro/Dropbox/MTK/lib
00088 ```
00089
00090 Examples and tests will also be built.
00091
00092
00093 ## 4. Frequently Asked Questions
00094
00095 Q: Why haven't you guys implemented GBS to build the library?
00096 A: I'm on it as we speak! ;)
00097
00098 Q: When will the other flavors be ready?
00099 A: Soon! I'm working on getting help on developing those.
00100
00101 Q: Is there any main reference when it comes to the theory on Mimetic Methods?
00102 A: Yes! Check: http://www.csrc.sdsu.edu/mimetic-book
00103
00104 Q: Do I need to generate the documentation myself?
00105 A: You can if you want to... but if you DO NOT want to, just go to our website.
00106
00107
00108 ## 5. Contact, Support, and Credits
00109
00110 The MTK is developed by researchers and adjuncts to the
00111 [Computational Science Research Center (CSRC)](http://www.csrc.sdsu.edu/)
00112 at [San Diego State University (SDSU)](http://www.sdsu.edu/).
00113
00114 Developers are members of:
00115
00116 1. Mimetic Numerical Methods Research and Development Group.
00117 2. Computational Geoscience Research and Development Group.
00118 3. Ocean Modeling Research and Development Group.
00119
00120 Currently the developers are:
00121
00122 - *Eduardo J. Sanchez, Ph.D. - esanchez@mail.sdsu.edu* - @ejspeiro
00123 - Jose E. Castillo, Ph.D. - jcastillo@mail.sdsu.edu
00124 - Guillermo F. Miranda, Ph.D. - unigrav@hotmail.com
00125 - Christopher P. Paolini, Ph.D. - paolini@engineering.sdsu.edu
00126 - Angel Boada.
00127 - Johnny Corbino.

```

```

00128 - Raul Vargas-Navarro.
00129
00130 Finally, please feel free to contact me with suggestions or corrections:
00131
00132 **Eduardo J. Sanchez, Ph.D. - esanchez at mail dot sdsu dot edu** - @ejspeiro
00133
00134 Thanks and happy coding!

```


17.35 src/mtk_blas_adapter.cc File Reference

```

#include <iostream>
#include <iomanip>
#include <vector>
#include "mtk_roots.h"
#include "mtk_tools.h"
#include "mtk_blas_adapter.h"

```

Include dependency graph for mtk_blas_adapter.cc:



Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

Functions

- float [mtk::snrm2_](#) (int *n, Real *x, int *incx)
- void [mtk::sgemv_](#) (char *trans, int *m, int *n, Real *alpha, Real *a, int *lda, Real *x, int *incx, Real *beta, Real *y, int *incy)
- void [mtk::sgemm_](#) (char *transa, char *transb, int *m, int *n, int *k, Real *alpha, Real *a, int *lda, Real *b, aamm int *ldb, Real *beta, Real *c, int *ldc)

17.36 mtk_blas_adapter.cc

```

00001
00024 /*
00025 Copyright (C) 2015, Computational Science Research Center, San Diego State
00026 University. All rights reserved.
00027
00028 Redistribution and use in source and binary forms, with or without modification,
00029 are permitted provided that the following conditions are met:
00030
00031 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00032 and a copy of the modified files should be reported once modifications are
00033 completed. Documentation related to said modifications should be included.
00034
00035 2. Redistributions of source code must be done through direct
00036 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00037
00038 3. Redistributions of source code must retain the above copyright notice, this
00039 list of conditions and the following disclaimer.
00040
00041 4. Redistributions in binary form must reproduce the above copyright notice,
00042 this list of conditions and the following disclaimer in the documentation and/or
00043 other materials provided with the distribution.
00044
00045 5. Usage of the binary form on proprietary applications shall require explicit
00046 prior written permission from the the copyright holders.
00047
00048 6. Neither the name of the copyright holder nor the names of its contributors
00049 may be used to endorse or promote products derived from this software without
00050 specific prior written permission.
00051
00052 The copyright holders provide no reassurances that the source code provided does
00053 not infringe any patent, copyright, or any other intellectual property rights of
00054 third parties. The copyright holders disclaim any liability to any recipient for
00055 claims brought against recipient by any third party for infringement of that
00056 parties intellectual property rights.
00057
00058 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00059 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00060 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00061 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00062 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00063 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00064 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00065 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00066 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00067 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00068 */
00069
00070 #include <iostream>
00071 #include <iomanip>
00072
00073 #include <vector>
00074
00075 #include "mtk_roots.h"
00076 #include "mtk_tools.h"
00077 #include "mtk_blas_adapter.h"
00078
00079 namespace mtk {
00080
00081 extern "C" {
00082
00083 #ifdef MTK_PRECISION_DOUBLE
00084
00095 double dnorm2_(int *n, Real *x, int *incx);
00096 #else
00097 float snorm2_(int *n, Real *x, int *incx);
00109 #endif
00110
00111 #ifdef MTK_PRECISION_DOUBLE
00112
00140 void dgemv_(char *trans,
00141             int *m,
00142             int *n,
00143             Real *alpha,
00144             Real *a,
00145             int *lda,
00146             Real *x,
00147             int *incx,

```

```

00148         Real *beta,
00149         Real *y,
00150         int *incy);
00151 #else
00152
00180 void sgemv_(char *trans,
00181             int *m,
00182             int *n,
00183             Real *alpha,
00184             Real *a,
00185             int *lda,
00186             Real *x,
00187             int *incx,
00188             Real *beta,
00189             Real *y,
00190             int *incy);
00191 #endif
00192
00193 #ifdef MTK_PRECISION_DOUBLE
00194
00219 void dgemm_(char *transa,
00220             char* transb,
00221             int *m,
00222             int *n,
00223             int *k,
00224             Real *alpha,
00225             Real *a,
00226             int *lda,
00227             Real *b,
00228             int *ldb,
00229             Real *beta,
00230             Real *c,
00231             int *ldc);
00232 }
00233 #else
00234
00259 void sgemm_(char *transa,
00260             char* transb,
00261             int *m,
00262             int *n,
00263             int *k,
00264             Real *alpha,
00265             Real *a,
00266             int *lda,
00267             Real *b, aamm
00268             int *ldb,
00269             Real *beta,
00270             Real *c,
00271             int *ldc);
00272 }
00273 #endif
00274 }
00275
00276 mtk::Real mtk::BLASAdapter::RealNRM2(Real *in, int &in_length) {
00277
00278     int ix{1}; // Increment for the elements of xx. ix >= 0.
00279
00280     #ifdef MTK_PRECISION_DOUBLE
00281         return dnm2_(&in_length, in, &ix);
00282     #else
00283         return snrm2_(&in_length, in, &ix);
00284     #endif
00285 }
00286
00287 void mtk::BLASAdapter::RealDenseMV(mtk::Real &alpha,
00288                                     mtk::DenseMatrix &aa,
00289                                     mtk::Real *xx,
00290                                     mtk::Real &beta,
00291                                     mtk::Real *yy) {
00292
00293     // Make sure input matrices are row-major ordered.
00294
00295     if (aa.matrix_properties().ordering() ==
00296         mtk::COL_MAJOR) {
00297         aa.OrderRowMajor();
00298     }
00299
00300     char transa{'T'}; // State that now, the input WILL be in row-major ordering.
00301
00301     int mm{aa.num_rows()}; // Rows of aa.
00302     int nn{aa.num_cols()}; // Columns of aa.

```

```

00303     int lda{(aa.matrix_properties()).ld()}; // Leading dimension.
00304     int incx{1}; // Increment of values in x.
00305     int incy{1}; // Increment of values in y.
00306
00307     std::swap(mm,nn);
00308     #ifdef MTK_PRECISION_DOUBLE
00309     dgemv_(&transa, &mm, &nn, &alpha, aa.data(), &lda,
00310           xx, &incx, &beta, yy, &incy);
00311     #else
00312     sgemv_(&transa, &mm, &nn, &alpha, aa.data(), &lda,
00313           xx, &incx, &beta, yy, &incy);
00314     #endif
00315     std::swap(mm,nn);
00316 }
00317
00318 mtk::DenseMatrix mtk::BLASAdapter::RealDenseMM(
00319     mtk::DenseMatrix &aa,
00320                                     mtk::DenseMatrix &bb) {
00321
00322     #if MTK_DEBUG_LEVEL > 0
00323     mtk::Tools::Prevent(aa.num_cols() != bb.num_rows(),
00324                         __FILE__, __LINE__, __func__);
00325     #endif
00326     // Make sure input matrices are row-major ordered.
00327
00328     if (aa.matrix_properties().ordering() ==
00329         mtk::COL_MAJOR) {
00330         aa.OrderRowMajor();
00331     }
00332     if (bb.matrix_properties().ordering() ==
00333         mtk::COL_MAJOR) {
00334         bb.OrderRowMajor();
00335     }
00336
00337     char ta{'T'}; // State that input matrix aa is in row-wise ordering.
00338     char tb{'T'}; // State that input matrix bb is in row-wise ordering.
00339
00340     int mm{aa.num_rows()}; // Rows of aa and rows of cc.
00341     int nn{bb.num_cols()}; // Cols of bb and cols of cc.
00342     int kk{aa.num_cols()}; // Cols of aa and rows of bb.
00343
00344     int cc_num_rows{mm}; // Rows of cc.
00345     int cc_num_cols{nn}; // Columns of cc.
00346
00347     int lda{std::max(1, kk)}; // Leading dimension of the aa matrix.
00348     int ldb{std::max(1, nn)}; // Leading dimension of the bb matrix.
00349     int ldc{std::max(1, mm)}; // Leading dimension of the cc matrix.
00350
00351     mtk::Real alpha{1.0}; // First scalar coefficient.
00352     mtk::Real beta{0.0}; // Second scalar coefficient.
00353
00354     mtk::DenseMatrix cc_col_maj_ord(cc_num_rows, cc_num_cols); // Output matrix.
00355
00356     cc_col_maj_ord.SetOrdering(mtk::COL_MAJOR);
00357
00358     #ifdef MTK_PRECISION_DOUBLE
00359     dgemm_(&ta, &tb, &mm, &nn, &kk, &alpha, aa.data(), &lda,
00360           bb.data(), &ldb, &beta, cc_col_maj_ord.data(), &ldc);
00361     #else
00362     sgemm_(&ta, &tb, &mm, &nn, &kk, &alpha, aa.data(), &lda,
00363           bb.data(), &ldb, &beta, cc_col_maj_ord.data(), &ldc);
00364     #endif
00365
00366     #if MTK_DEBUG_LEVEL > 0
00367     std::cout << "cc_col_maj_ord =" << std::endl;
00368     std::cout << cc_col_maj_ord << std::endl;
00369     #endif
00370
00371     cc_col_maj_ord.OrderRowMajor();
00372
00373     return cc_col_maj_ord;
00374 }


```

17.37 src/mtk_dense_matrix.cc File Reference

Implements a common dense matrix, using a 1D array.

```
#include <cstdlib>
#include <cstring>
#include <cmath>
#include <iostream>
#include <iomanip>
#include <typeinfo>
#include <algorithm>
#include "mtk_roots.h"
#include "mtk_dense_matrix.h"
#include "mtk_tools.h"
```

Include dependency graph for mtk_dense_matrix.cc:



Namespaces

- [mtk](#)
Mimetic Methods Toolkit namespace.

Functions

- `std::ostream & mtk::operator<< (std::ostream &stream, mtk::DenseMatrix &in)`

17.37.1 Detailed Description

For developing purposes, it is better to have a not-so-intricated data structure implementing matrices. This is the purpose of this class: to be used for prototypes of new code for small test cases. In every other instance, this should be replaced by the most appropriate sparse matrix.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_dense_matrix.cc](#).

17.38 mtk_dense_matrix.cc

00001


```

00013  /*
00014  Copyright (C) 2015, Computational Science Research Center, San Diego State
00015  University. All rights reserved.
00016
00017  Redistribution and use in source and binary forms, with or without modification,
00018  are permitted provided that the following conditions are met:
00019
00020  1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00021  and a copy of the modified files should be reported once modifications are
00022  completed. Documentation related to said modifications should be included.
00023
00024  2. Redistributions of source code must be done through direct
00025  downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00026
00027  3. Redistributions of source code must retain the above copyright notice, this
00028  list of conditions and the following disclaimer.
00029
00030  4. Redistributions in binary form must reproduce the above copyright notice,
00031  this list of conditions and the following disclaimer in the documentation and/or
00032  other materials provided with the distribution.
00033
00034  5. Usage of the binary form on proprietary applications shall require explicit
00035  prior written permission from the the copyright holders.
00036
00037  6. Neither the name of the copyright holder nor the names of its contributors
00038  may be used to endorse or promote products derived from this software without
00039  specific prior written permission.
00040
00041  The copyright holders provide no reassurances that the source code provided does
00042  not infringe any patent, copyright, or any other intellectual property rights of
00043  third parties. The copyright holders disclaim any liability to any recipient for
00044  claims brought against recipient by any third party for infringement of that
00045  parties intellectual property rights.
00046
00047  THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00048  ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00049  WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00050  DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00051  ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00052  (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00053  LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00054  ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00055  (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00056  SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00057  */
00058
00059  #include <cstdlib>
00060  #include <cstring>
00061  #include <cmath>
00062
00063  #include <iostream>
00064  #include <iomanip>
00065  #include <typeinfo>
00066
00067  #include <algorithm>
00068
00069  #include "mtk_roots.h"
00070  #include "mtk_dense_matrix.h"
00071  #include "mtk_tools.h"
00072
00073  namespace mtk {
00074
00075  std::ostream& operator <<(std::ostream &stream, mtk::DenseMatrix &in) {
00076
00077      int mm{in.matrix_properties_.num_rows()}; // Auxiliary.
00078      int nn{in.matrix_properties_.num_cols()}; // Auxiliary.
00079
00080      if (in.matrix_properties_.ordering() ==
00081          mtk::COL_MAJOR) {
00082          std::swap(mm, nn);
00083      }
00084      for (auto ii = 0; ii < mm; ii++) {
00085          for (auto jj = 0; jj < nn; jj++) {
00086              mtk::Real value = in.data_[ii*nn + jj];
00087              stream << std::setw(13) << value;
00088          }
00089          stream << std::endl;
00090      }
00091      if (in.matrix_properties_.ordering() ==
00092          mtk::COL_MAJOR) {
00093          std::swap(mm, nn);
00094      }
00095  }
00096
00097  }
00098
00099  }

```

```

00092     }
00093     return stream;
00094 }
00095 }
00096
00097 mtk::DenseMatrix& mtk::DenseMatrix::operator =(const
    mtk::DenseMatrix &in) {
00098
00099     if(this == &in) {
00100         return *this;
00101     }
00102
00103     matrix_properties_.set_storage(in.
    matrix_properties_.storage());
00104
00105     matrix_properties_.set_ordering(in.
    matrix_properties_.ordering());
00106
00107     auto aux = in.matrix_properties_.num_rows();
00108     matrix_properties_.set_num_rows(aux);
00109
00110     aux = in.matrix_properties().num_cols();
00111     matrix_properties_.set_num_cols(aux);
00112
00113     aux = in.matrix_properties().num_zero();
00114     matrix_properties_.set_num_zero(aux);
00115
00116     aux = in.matrix_properties().num_null();
00117     matrix_properties_.set_num_null(aux);
00118
00119     auto num_rows = matrix_properties_.num_rows();
00120     auto num_cols = matrix_properties_.num_cols();
00121
00122     delete [] data_;
00123
00124     try {
00125         data_ = new mtk::Real[num_rows*num_cols];
00126     } catch (std::bad_alloc &memory_allocation_exception) {
00127         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00128             std::endl;
00129         std::cerr << memory_allocation_exception.what() << std::endl;
00130     }
00131     memset(data_, mtk::kZero, sizeof(data_[0])*num_rows*
    num_cols);
00132
00133     std::copy(in.data_, in.data_ + num_rows*num_cols, data_);
00134
00135     return *this;
00136 }
00137
00138 mtk::DenseMatrix::DenseMatrix(): data_(nullptr) {
00139
00140     matrix_properties_.set_storage(mtk::DENSE);
00141     matrix_properties_.set_ordering(mtk::ROW_MAJOR);
00142 }
00143
00144 mtk::DenseMatrix::DenseMatrix(const
    mtk::DenseMatrix &in) {
00145
00146     matrix_properties_.set_storage(in.matrix_properties_.storage());
00147
00148     matrix_properties_.set_ordering(in.matrix_properties_.
    ordering());
00149
00150     auto aux = in.matrix_properties_.num_rows();
00151     matrix_properties_.set_num_rows(aux);
00152
00153     aux = in.matrix_properties().num_cols();
00154     matrix_properties_.set_num_cols(aux);
00155
00156     aux = in.matrix_properties().num_zero();
00157     matrix_properties_.set_num_zero(aux);
00158
00159     aux = in.matrix_properties().num_null();
00160     matrix_properties_.set_num_null(aux);
00161
00162     auto num_rows = in.matrix_properties_.num_rows();
00163     auto num_cols = in.matrix_properties_.num_cols();
00164
00165     try {
00166         data_ = new mtk::Real[num_rows*num_cols];

```

```

00167     } catch (std::bad_alloc &memory_allocation_exception) {
00168         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00169             std::endl;
00170         std::cerr << memory_allocation_exception.what() << std::endl;
00171     }
00172     memset(data_, mtk::kZero, sizeof(data_[0])*num_rows*num_cols);
00173     std::copy(in.data_, in.data_ + num_rows*num_cols, data_);
00174 }
00175
00176 mtk::DenseMatrix::DenseMatrix(const int &num_rows, const int &num_cols) {
00177
00178     #if MTK_DEBUG_LEVEL > 0
00179     mtk::Tools::Prevent(num_rows < 1, __FILE__, __LINE__, __func__);
00180     mtk::Tools::Prevent(num_cols < 1, __FILE__, __LINE__, __func__);
00181     #endif
00182
00183     matrix_properties_.set_storage(mtk::DENSE);
00184     matrix_properties_.set_ordering(mtk::ROW_MAJOR);
00185     matrix_properties_.set_num_rows(num_rows);
00186     matrix_properties_.set_num_cols(num_cols);
00187
00188     try {
00189         data_ = new mtk::Real[num_rows*num_cols];
00190     } catch (std::bad_alloc &memory_allocation_exception) {
00191         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00192             std::endl;
00193         std::cerr << memory_allocation_exception.what() << std::endl;
00194     }
00195     memset(data_, mtk::kZero, sizeof(data_[0])*num_rows*num_cols);
00196 }
00197
00198 mtk::DenseMatrix::DenseMatrix(const int &rank,
00199                               const bool &padded,
00200                               const bool &transpose) {
00201
00202     #if MTK_DEBUG_LEVEL > 0
00203     mtk::Tools::Prevent(rank < 1, __FILE__, __LINE__, __func__);
00204     #endif
00205
00206     int aux{}; // Used to control the padding.
00207
00208     if (padded) {
00209         aux = 1;
00210     }
00211
00212     matrix_properties_.set_storage(mtk::DENSE);
00213     matrix_properties_.set_ordering(mtk::ROW_MAJOR);
00214     matrix_properties_.set_num_rows(aux + rank + aux);
00215     matrix_properties_.set_num_cols(rank);
00216
00217     try {
00218         data_ = new mtk::Real[matrix_properties_.num_values()];
00219     } catch (std::bad_alloc &memory_allocation_exception) {
00220         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00221             std::endl;
00222         std::cerr << memory_allocation_exception.what() << std::endl;
00223     }
00224     memset(data_,
00225            mtk::kZero,
00226            sizeof(data_[0])*(matrix_properties_.num_values()));
00227
00228     for (auto ii = 0; ii < matrix_properties_.num_rows(); ++ii) {
00229         for (auto jj = 0; jj < matrix_properties_.num_cols(); ++jj) {
00230             data_[ii*matrix_properties_.num_cols() + jj] =
00231                 (ii == jj + aux) ? mtk::kOne : mtk::kZero;
00232         }
00233     }
00234 }
00235
00236 mtk::DenseMatrix::DenseMatrix(const mtk::Real *gen,
00237                               const int &gen_length,
00238                               const int &pro_length,
00239                               const bool &transpose) {
00240
00241     #if MTK_DEBUG_LEVEL > 0
00242     mtk::Tools::Prevent(gen == nullptr, __FILE__, __LINE__, __func__);
00243     mtk::Tools::Prevent(gen_length < 1, __FILE__, __LINE__, __func__);
00244     mtk::Tools::Prevent(pro_length < 1, __FILE__, __LINE__, __func__);
00245     #endif
00246 }
00247

```

```

00248 matrix_properties_.set_storage(mtk::DENSE);
00249 matrix_properties_.set_ordering(mtk::ROW_MAJOR);
00250 if (!transpose) {
00251     matrix_properties_.set_num_rows(gen_length);
00252     matrix_properties_.set_num_cols(pro_length);
00253 } else {
00254     matrix_properties_.set_num_rows(pro_length);
00255     matrix_properties_.set_num_cols(gen_length);
00256 }
00257
00258 int rr = matrix_properties_.num_rows(); // Used to construct this matrix.
00259 int cc = matrix_properties_.num_cols(); // Used to construct this matrix.
00260
00261 try {
00262     data_ = new mtk::Real[rr*cc];
00263 } catch (std::bad_alloc &memory_allocation_exception) {
00264     std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00265         std::endl;
00266     std::cerr << memory_allocation_exception.what() << std::endl;
00267 }
00268 memset(data_, mtk::kZero, sizeof(data_[0])*rr*cc);
00269
00270 if (!transpose) {
00271     for (auto ii = 0; ii < rr; ii++) {
00272         for (auto jj = 0; jj < cc; jj++) {
00273             data_[ii*cc + jj] = pow(gen[ii], (double) jj);
00274         }
00275     }
00276 } else {
00277     for (auto ii = 0; ii < rr; ii++) {
00278         for (auto jj = 0; jj < cc; jj++) {
00279             data_[ii*cc + jj] = pow(gen[jj], (double) ii);
00280         }
00281     }
00282 }
00283 }
00284
00285 mtk::DenseMatrix::~DenseMatrix() {
00286
00287     delete[] data_;
00288     data_ = nullptr;
00289 }
00290
00291 mtk::Matrix mtk::DenseMatrix::matrix_properties() const {
00292
00293     return matrix_properties_;
00294 }
00295
00296 void mtk::DenseMatrix::SetOrdering(
00297     mtk::MatrixOrdering oo) {
00298
00299     #if MTK_DEBUG_LEVEL > 0
00300     mtk::Tools::Prevent(!(oo == mtk::ROW_MAJOR || oo ==
00301         mtk::COL_MAJOR),
00302         __FILE__, __LINE__, __func__);
00303     #endif
00304     matrix_properties_.set_ordering(oo);
00305 }
00306
00307 int mtk::DenseMatrix::num_rows() const {
00308     return matrix_properties_.num_rows();
00309 }
00310
00311 int mtk::DenseMatrix::num_cols() const {
00312     return matrix_properties_.num_cols();
00313 }
00314
00315 mtk::Real* mtk::DenseMatrix::data() const {
00316     return data_;
00317 }
00318
00319 mtk::Real mtk::DenseMatrix::GetValue(
00320     const int &rr,
00321     const int &cc) const {
00322
00323     #if MTK_DEBUG_LEVEL > 0
00324     mtk::Tools::Prevent(rr < 0, __FILE__, __LINE__, __func__);

```

```

00327     mtk::Tools::Prevent(cc < 0, __FILE__, __LINE__, __func__);
00328     #endif
00329
00330     return data_[rr*matrix_properties_.num_cols() + cc];
00331 }
00332
00333 void mtk::DenseMatrix::SetValue(
00334     const int &rr,
00335     const int &cc,
00336     const mtk::Real &val) {
00337
00338     #if MTK_DEBUG_LEVEL > 0
00339     mtk::Tools::Prevent(rr < 0, __FILE__, __LINE__, __func__);
00340     mtk::Tools::Prevent(cc < 0, __FILE__, __LINE__, __func__);
00341     #endif
00342
00343     data_[rr*matrix_properties_.num_cols() + cc] = val;
00344 }
00345
00346 void mtk::DenseMatrix::Transpose() {
00347
00348     mtk::Real *data_transposed{}; // Buffer.
00349
00350     int rr = matrix_properties_.num_rows(); // Used to construct this matrix.
00351     int cc = matrix_properties_.num_cols(); // Used to construct this matrix.
00352
00353     try {
00354         data_transposed = new mtk::Real[rr*cc];
00355     } catch (std::bad_alloc &memory_allocation_exception) {
00356         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00357             std::endl;
00358         std::cerr << memory_allocation_exception.what() << std::endl;
00359     }
00360
00361     memset(data_transposed,
00362         mtk::kZero,
00363         sizeof(data_transposed[0])*rr*cc);
00364
00365     // Assign the values to their transposed position.
00366     for (auto ii = 0; ii < rr; ++ii) {
00367         for (auto jj = 0; jj < cc; ++jj) {
00368             data_transposed[jj*rr + ii] = data_[ii*cc + jj];
00369         }
00370     }
00371
00372     // Swap pointers.
00373     auto tmp = data_; // Temporal holder.
00374     data_ = data_transposed;
00375     delete [] tmp;
00376     tmp = nullptr;
00377
00378     matrix_properties_.set_num_rows(cc);
00379     matrix_properties_.set_num_cols(rr);
00380 }
00381
00382 void mtk::DenseMatrix::OrderRowMajor() {
00383
00384     if (matrix_properties_.ordering() == mtk::COL_MAJOR) {
00385
00386         mtk::Real *data_transposed{}; // Buffer.
00387
00388         int rr = matrix_properties_.num_rows(); // Used to construct this matrix.
00389         int cc = matrix_properties_.num_cols(); // Used to construct this matrix.
00390
00391         try {
00392             data_transposed = new mtk::Real[rr*cc];
00393         } catch (std::bad_alloc &memory_allocation_exception) {
00394             std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00395                 std::endl;
00396             std::cerr << memory_allocation_exception.what() << std::endl;
00397         }
00398
00399         memset(data_transposed,
00400             mtk::kZero,
00401             sizeof(data_transposed[0])*rr*cc);
00402
00403         // Assign the values to their transposed position.
00404         std::swap(rr, cc);
00405         for (auto ii = 0; ii < rr; ++ii) {
00406             for (auto jj = 0; jj < cc; ++jj) {
00407                 data_transposed[jj*rr + ii] = data_[ii*cc + jj];
00408             }
00409         }
00410     }

```

```

00410     }
00411     }
00412     std::swap(rr, cc);
00413
00414     // Swap pointers.
00415     auto tmp = data_; // Temporal holder.
00416     data_ = data_transposed;
00417     delete [] tmp;
00418     tmp = nullptr;
00419
00420     matrix_properties_.set_ordering(mtk::ROW_MAJOR);
00421 }
00422 }
00423
00424 void mtk::DenseMatrix::OrderColMajor() {
00425
00426     if (matrix_properties_.ordering() == ROW_MAJOR) {
00427
00428
00429         mtk::Real *data_transposed{}; // Buffer.
00430
00431
00432         int rr = matrix_properties_.num_rows(); // Used to construct this matrix.
00433         int cc = matrix_properties_.num_cols(); // Used to construct this matrix.
00434
00435         try {
00436             data_transposed = new mtk::Real[rr*cc];
00437         } catch (std::bad_alloc &memory_allocation_exception) {
00438             std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00439                 std::endl;
00440             std::cerr << memory_allocation_exception.what() << std::endl;
00441         }
00442         memset(data_transposed,
00443             mtk::kZero,
00444             sizeof(data_transposed[0])*rr*cc);
00445
00446         // Assign the values to their transposed position.
00447         for (auto ii = 0; ii < rr; ++ii) {
00448             for (auto jj = 0; jj < cc; ++jj) {
00449                 data_transposed[jj*rr + ii] = data_[ii*cc + jj];
00450             }
00451         }
00452
00453         // Swap pointers.
00454         auto tmp = data_; // Temporal holder.
00455         data_ = data_transposed;
00456         delete [] tmp;
00457         tmp = nullptr;
00458
00459         matrix_properties_.set_ordering(mtk::COL_MAJOR);
00460     }
00461 }
00462
00463 mtk::DenseMatrix mtk::DenseMatrix::Kron(const
    mtk::DenseMatrix &aa,
                                const mtk::DenseMatrix &bb) {
00464
00465     int row_offset{}; // Offset for rows.
00466     int col_offset{}; // Offset for rows.
00467
00468     mtk::Real aa_factor{}; // Used in computation.
00469
00470     // Auxiliary variables:
00471     auto aux1 = aa.matrix_properties_.num_rows()*bb.
matrix_properties_.num_rows();
00472     auto aux2 = aa.matrix_properties_.num_cols()*bb.
matrix_properties_.num_cols();
00473
00474     mtk::DenseMatrix output(aux1,aux2); // Output matrix.
00475
00476     int kk_num_cols(output.matrix_properties_.num_cols()); // Aux.
00477
00478     auto mm = aa.matrix_properties_.num_rows(); // Rows of aa.
00479     auto nn = aa.matrix_properties_.num_cols(); // Cols of aa.
00480     auto pp = bb.matrix_properties_.num_rows(); // Rows of bb.
00481     auto qq = bb.matrix_properties_.num_cols(); // Cols of bb.
00482
00483     for (auto ii = 0; ii < mm; ++ii) {
00484         row_offset = ii*pp;
00485         for (auto jj = 0; jj < nn; ++jj) {
00486             col_offset = jj*qq;
00487             aa_factor = aa.data_[ii*nn + jj];

```

```

00489     for (auto ll = 0; ll < pp; ++ll) {
00490         for (auto oo = 0; oo < qq; ++oo) {
00491             auto index = (ll + row_offset)*kk_num_cols + (oo + col_offset);
00492             output.data_[index] = aa_factor*bb.data_[ll*qq + oo];
00493         }
00494     }
00495 }
00496 }
00497
00498 output.matrix_properties_.set_storage(mtk::DENSE);
00499 output.matrix_properties_.set_ordering(
00500     mtk::ROW_MAJOR);
00501 return output;
00502 }

```

17.39 src/mtk_div_1d.cc File Reference


Implements the class Div1D.

```

#include <cmath>
#include <cstring>
#include <iostream>
#include <iomanip>
#include <limits>
#include <algorithm>
#include "mtk_tools.h"
#include "mtk_blas_adapter.h"
#include "mtk_lapack_adapter.h"
#include "mtk_glpk_adapter.h"
#include "mtk_div_1d.h"

```

Include dependency graph for mtk_div_1d.cc:



Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

Functions

- `std::ostream & mtk::operator<< (std::ostream &stream, mtk::Div1D &in)`

17.39.1 Detailed Description

This class implements a 1D divergence matrix operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Todo Overload ostream operator as in `mtk::Lap1D`.

Todo Implement creation of `■` w. `mtk::BLASAdapter`.

Definition in file `mtk_div_1d.cc`.

17.40 mtk_div_1d.cc

```

00001
00015 /*
00016 Copyright (C) 2015, Computational Science Research Center, San Diego State
00017 University. All rights reserved.
00018
00019 Redistribution and use in source and binary forms, with or without modification,
00020 are permitted provided that the following conditions are met:
00021
00022 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00023 and a copy of the modified files should be reported once modifications are
00024 completed. Documentation related to said modifications should be included.
00025
00026 2. Redistributions of source code must be done through direct
00027 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00028
00029 3. Redistributions of source code must retain the above copyright notice, this
00030 list of conditions and the following disclaimer.
00031
00032 4. Redistributions in binary form must reproduce the above copyright notice,
00033 this list of conditions and the following disclaimer in the documentation and/or
00034 other materials provided with the distribution.
00035
00036 5. Usage of the binary form on proprietary applications shall require explicit
00037 prior written permission from the the copyright holders.
00038
00039 6. Neither the name of the copyright holder nor the names of its contributors
00040 may be used to endorse or promote products derived from this software without
00041 specific prior written permission.
00042
00043 The copyright holders provide no reassurances that the source code provided does
00044 not infringe any patent, copyright, or any other intellectual property rights of
00045 third parties. The copyright holders disclaim any liability to any recipient for
00046 claims brought against recipient by any third party for infringement of that
00047 parties intellectual property rights.
00048
00049 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00050 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00051 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00052 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00053 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00054 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00055 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00056 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00057 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00058 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00059 */
00060
00061 #include <cmath>
00062 #include <cstring>
00063
00064 #include <iostream>
00065 #include <iomanip>
00066 #include <limits>

```



```

00067 #include <algorithm>
00068
00069 #include "mtk_tools.h"
00070
00071 #include "mtk_blas_adapter.h"
00072 #include "mtk_lapack_adapter.h"
00073 #include "mtk_glpk_adapter.h"
00074
00075 #include "mtk_div_1d.h"
00076
00077 namespace mtk {
00078
00079 std::ostream& operator <<(std::ostream &stream, mtk::Div1D &in) {
00080
00082     stream << "divergence_[0] = " << std::setw(9) << in.divergence_[0] <<
00084         std::endl;
00085
00087     stream << "divergence_[1:" << in.order_accuracy_ << "] = ";
00088     for (auto ii = 1; ii <= in.order_accuracy_; ++ii) {
00089         stream << std::setw(9) << in.divergence_[ii] << " ";
00090     }
00091     stream << std::endl;
00092
00093     if (in.order_accuracy_ > 2) {
00094
00096         stream << "divergence_[" << in.order_accuracy_ + 1 << ":" <<
00098             2*in.order_accuracy_ << "] = ";
00099         for (auto ii = in.order_accuracy_ + 1; ii <= 2*in.
00100             order_accuracy_; ++ii) {
00101             stream << std::setw(9) << in.divergence_[ii] << " ";
00102         }
00103         stream << std::endl;
00104
00106         auto offset = (2*in.order_accuracy_ + 1);
00107         int mm{};
00108         for (auto ii = 0; ii < in.dim_null_; ++ii) {
00109             stream << "divergence_[" << offset + mm << ":" <<
00110                 offset + mm + in.num_bndy_coeffs_ - 1 << "] = ";
00111             for (auto jj = 0; jj < in.num_bndy_coeffs_; ++jj) {
00112                 auto value = in.divergence_[offset + mm];
00113                 stream << std::setw(9) << value << " ";
00114                 ++mm;
00115             }
00116             stream << std::endl;
00117         }
00118     }
00119 }
00120
00121 return stream;
00122 }
00123 }
00124
00125 mtk::Div1D::Div1D() :
00126     order_accuracy_(mtk::kDefaultOrderAccuracy),
00127     dim_null_(),
00128     num_bndy_coeffs_(),
00129     divergence_length_(),
00130     minrow_(),
00131     row_(),
00132     coeffs_interior_(),
00133     prem_apps_(),
00134     weights_crs_(),
00135     weights_cbs_(),
00136     mim_bndy_(),
00137     divergence_(),
00138     mimetic_threshold_(mtk::kDefaultMimeticThreshold) {}
00139
00140 mtk::Div1D::Div1D(const Div1D &div) :
00141     order_accuracy_(div.order_accuracy_),
00142     dim_null_(div.dim_null_),
00143     num_bndy_coeffs_(div.num_bndy_coeffs_),
00144     divergence_length_(div.divergence_length_),
00145     minrow_(div.minrow_),
00146     row_(div.row_),
00147     coeffs_interior_(div.coeffs_interior_),
00148     prem_apps_(div.prem_apps_),
00149     weights_crs_(div.weights_crs_),
00150     weights_cbs_(div.weights_cbs_),

```

```

00151     mim_bndy_(div.mim_bndy_),
00152     divergence_(div.divergence_),
00153     mimetic_threshold_(div.mimetic_threshold_) {}
00154
00155 mtk::Div1D::~Div1D() {
00156
00157     delete[] coeffs_interior_;
00158     coeffs_interior_ = nullptr;
00159
00160     delete[] prem_apps_;
00161     prem_apps_ = nullptr;
00162
00163     delete[] weights_crs_;
00164     weights_crs_ = nullptr;
00165
00166     delete[] weights_cbs_;
00167     weights_cbs_ = nullptr;
00168
00169     delete[] mim_bndy_;
00170     mim_bndy_ = nullptr;
00171
00172     delete[] divergence_;
00173     divergence_ = nullptr;
00174 }
00175
00176 bool mtk::Div1D::ConstructDiv1D(int order_accuracy,
00177                                 mtk::Real mimetic_threshold) {
00178
00179     #if MTK_DEBUG_LEVEL > 0
00180     mtk::Tools::Prevent(order_accuracy < 2, __FILE__, __LINE__, __func__);
00181     mtk::Tools::Prevent((order_accuracy%2) != 0, __FILE__, __LINE__, __func__);
00182     mtk::Tools::Prevent(mimetic_threshold <= mtk::kZero,
00183                         __FILE__, __LINE__, __func__);
00184
00185     if (order_accuracy >= mtk::kCriticalOrderAccuracyDiv) {
00186         std::cout << "WARNING: Numerical accuracy is critical." << std::endl;
00187     }
00188
00189     std::cout << "order_accuracy_ = " << order_accuracy << std::endl;
00190     std::cout << "mimetic_threshold_ = " << mimetic_threshold << std::endl;
00191     #endif
00192
00193     order_accuracy_ = order_accuracy;
00194     mimetic_threshold_ = mimetic_threshold;
00195
00196
00197     bool abort_construction = ComputeStencilInteriorGrid();
00198
00199     #if MTK_DEBUG_LEVEL > 0
00200     if (!abort_construction) {
00201         std::cerr << "Could NOT complete stage 1." << std::endl;
00202         std::cerr << "Exiting..." << std::endl;
00203         return false;
00204     }
00205     #endif
00206
00207     // At this point, we already have the values for the interior stencil stored
00208     // in the coeffs_interior_ array.
00209
00210     // It is noteworthy, that the 2nd-order-accurate divergence operator has NO
00211     // approximation at the boundary, thus it has no weights. For this case, the
00212     // dimension of the null-space of the Vandermonde matrices used to compute the
00213     // approximating coefficients at the boundary is 0. Ergo, we compute this
00214     // number first and then decide if we must compute anything at the boundary.
00215
00216     dim_null_ = order_accuracy_/2 - 1;
00217
00218     if (dim_null_ > 0) {
00219
00220         #ifdef MTK_PRECISION_DOUBLE
00221         num_bndy_coeffs_ = (int) (3.0*(mtk::Real) order_accuracy_)/2.0);
00222         #else
00223         num_bndy_coeffs_ = (int) (3.0f*(mtk::Real) order_accuracy_)/2.0f);
00224         #endif
00225
00226
00227         // For this we will follow recommendations given in:
00228         //
00229         // http://icl.cs.utk.edu/lapack-forum/viewtopic.php?f=5&t=4506
00230         //
00231         // We will compute the QR Factorization of the transpose, as in the

```

```

00234 // following (MATLAB) pseudo-code:
00235 //
00236 // [Q,R] = qr(V'); % Full QR as defined in
00237 // % http://www.stanford.edu/class/ee263/notes/qr_matlab.pdf
00238 //
00239 // null-space = Q(:, last (order_accuracy/2 - 1) columns of Q );
00240 //
00241 // However, given the nature of the Vandermonde matrices we've just
00242 // computed, they all possess the same null-space. Therefore, we impose the
00243 // convention of computing the null-space of the first Vandermonde matrix
00244 // (west boundary).
00245
00246 abort_construction = ComputeRationalBasisNullSpace();
00247
00248 #if MTK_DEBUG_LEVEL > 0
00249 if (!abort_construction) {
00250     std::cerr << "Could NOT complete stage 2.1." << std::endl;
00251     std::cerr << "Exiting..." << std::endl;
00252     return false;
00253 }
00254 #endif
00255
00256 abort_construction = ComputePreliminaryApproximations();
00257
00258 #if MTK_DEBUG_LEVEL > 0
00259 if (!abort_construction) {
00260     std::cerr << "Could NOT complete stage 2.2." << std::endl;
00261     std::cerr << "Exiting..." << std::endl;
00262     return false;
00263 }
00264 #endif
00265
00266 abort_construction = ComputeWeights();
00267
00268 #if MTK_DEBUG_LEVEL > 0
00269 if (!abort_construction) {
00270     std::cerr << "Could NOT complete stage 2.3." << std::endl;
00271     std::cerr << "Exiting..." << std::endl;
00272     return false;
00273 }
00274 #endif
00275
00276 abort_construction = ComputeStencilBoundaryGrid();
00277
00278 #if MTK_DEBUG_LEVEL > 0
00279 if (!abort_construction) {
00280     std::cerr << "Could NOT complete stage 2.4." << std::endl;
00281     std::cerr << "Exiting..." << std::endl;
00282     return false;
00283 }
00284 #endif
00285
00286 } // End of: if (dim_null_ > 0);
00287
00288 // Once we have the following three collections of data:
00289 // (a) the coefficients for the interior,
00290 // (b) the coefficients for the boundary (if it applies),
00291 // (c) and the weights (if it applies),
00292 // we will store everything in the output array:
00293
00294 abort_construction = AssembleOperator();
00295
00296 #if MTK_DEBUG_LEVEL > 0
00297 if (!abort_construction) {
00298     std::cerr << "Could NOT complete stage 3." << std::endl;
00299     std::cerr << "Exiting..." << std::endl;
00300     return false;
00301 }
00302 #endif
00303
00304 return true;
00305 }
00306
00307 int mtk::Div1D::num_bndy_coeffs() {
00308     return num_bndy_coeffs_;
00309 }

```

```

00319
00320 mtk::Real *mtk::Div1D::weights_crs() {
00321
00322     return weights_crs_;
00323 }
00324
00325 mtk::Real *mtk::Div1D::weights_cbs() {
00326
00327     return weights_cbs_;
00328 }
00329
00330 mtk::DenseMatrix mtk::Div1D::ReturnAsDenseMatrix(const
    UniStgGrid1D &grid) {
00331
00332     int nn{grid.num_cells_x()}; // Number of cells on the grid.
00333
00334     #if MTK_DEBUG_LEVEL > 0
00335     mtk::Tools::Prevent(order_accuracy_ <= 0, __FILE__, __LINE__, __func__);
00336     mtk::Tools::Prevent(nn < 3*order_accuracy_ - 1, __FILE__, __LINE__, __func__);
00337     #endif
00338
00339     mtk::Real inv_delta_x{mtk::kOne/grid.delta_x()};
00340
00341     int dd_num_rows = nn + 2;
00342     int dd_num_cols = nn + 1;
00343     int elements_per_row = num_bndy_coeffs_;
00344     int num_extra_rows = dim_null_;
00345
00346     // Output matrix featuring sizes for divergence operators.
00347     mtk::DenseMatrix out(dd_num_rows, dd_num_cols);
00348
00349
00350
00351     auto ee_index = 0;
00352     for (auto ii = 1; ii < num_extra_rows + 1; ii++) {
00353         auto cc = 0;
00354         for(auto jj = 0 ; jj < dd_num_rows; jj++) {
00355             if( cc >= elements_per_row) {
00356                 out.SetValue(ii, jj, mtk::kZero);
00357             } else {
00358                 out.SetValue(ii, jj, mim_bndy_[ee_index++]*inv_delta_x);
00359                 cc++;
00360             }
00361         }
00362     }
00363
00364
00365
00366     for (auto ii = num_extra_rows + 1;
00367         ii < dd_num_rows - num_extra_rows - 1; ii++) {
00368         auto jj = ii - num_extra_rows - 1;
00369         for (auto cc = 0; cc < order_accuracy_; cc++, jj++) {
00370             out.SetValue(ii, jj, coeffs_interior_[cc]*inv_delta_x);
00371         }
00372     }
00373
00374
00375
00376     ee_index = 0;
00377     for (auto ii = dd_num_rows - 2; ii >= dd_num_rows - num_extra_rows - 1; ii--) {
00378         auto cc = 0;
00379         for (auto jj = dd_num_cols - 1; jj >= 0; jj--) {
00380             if( cc >= elements_per_row) {
00381                 out.SetValue(ii, jj, 0.0);
00382             } else {
00383                 out.SetValue(ii, jj, -mim_bndy_[ee_index++]*inv_delta_x);
00384                 cc++;
00385             }
00386         }
00387     }
00388
00389     return out;
00390 }
00391
00392 bool mtk::Div1D::ComputeStencilInteriorGrid() {
00393
00394
00395
00396     mtk::Real* pp{}; // Spatial coordinates to create interior stencil.
00397
00398     try {
00399         pp = new mtk::Real[order_accuracy_];
00400     } catch (std::bad_alloc &memory_allocation_exception) {
00401         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00402             std::endl;

```

```

00403     std::cerr << memory_allocation_exception.what() << std::endl;
00404 }
00405 memset(pp, mtk::kZero, sizeof(pp[0])*order_accuracy_);
00406
00407 #ifdef MTK_PRECISION_DOUBLE
00408 pp[0] = 1.0/2.0 - ((mtk::Real) order_accuracy_)/2.0;
00409 #else
00410 pp[0] = 1.0f/2.0f - ((mtk::Real) order_accuracy_)/2.0f;
00411 #endif
00412
00413 for (auto ii = 1; ii < order_accuracy_; ++ii) {
00414     pp[ii] = pp[ii - 1] + mtk::kOne;
00415 }
00416
00417 #if MTK_DEBUG_LEVEL > 0
00418 std::cout << "pp =" << std::endl;
00419 for (auto ii = 0; ii < order_accuracy_; ++ii) {
00420     std::cout << std::setw(12) << pp[ii];
00421 }
00422 std::cout << std::endl << std::endl;
00423 #endif
00424
00426
00427 bool transpose{false};
00428
00429 mtk::DenseMatrix vander_matrix(pp,
00430                                 order_accuracy_,
00431                                 order_accuracy_,
00432                                 transpose);
00433
00434 #if MTK_DEBUG_LEVEL > 0
00435 std::cout << "vander_matrix = " << std::endl;
00436 std::cout << vander_matrix << std::endl;
00437 #endif
00438
00440
00441 try {
00442     coeffs_interior_ = new mtk::Real[order_accuracy_];
00443 } catch (std::bad_alloc &memory_allocation_exception) {
00444     std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00445         std::endl;
00446     std::cerr << memory_allocation_exception.what() << std::endl;
00447 }
00448 memset(coeffs_interior_, mtk::kZero, sizeof(coeffs_interior_[0])*order_accuracy_);
00449
00450 coeffs_interior_[1] = mtk::kOne;
00451
00452 #if MTK_DEBUG_LEVEL > 0
00453 std::cout << "oo =" << std::endl;
00454 for (auto ii = 0; ii < order_accuracy_; ++ii) {
00455     std::cout << std::setw(12) << coeffs_interior_[ii] << std::endl;
00456 }
00457 std::cout << std::endl;
00458 #endif
00459
00461
00462 int info{mtk::LAPACKAdapter::SolveDenseSystem(vander_matrix,
00463                                               coeffs_interior_)};
00464
00465 #if MTK_DEBUG_LEVEL > 0
00466 if (!info) {
00467     std::cout << "System solved! Interior stencil attained!" << std::endl;
00468     std::cout << std::endl;
00469 }
00470 else {
00471     std::cerr << "Something wrong solving system! info = " << info << std::endl;
00472     std::cerr << "Exiting..." << std::endl;
00473     return false;
00474 }
00475 #endif
00476
00477 #if MTK_DEBUG_LEVEL > 0
00478 std::cout << "coeffs_interior_ =" << std::endl;
00479 for (auto ii = 0; ii < order_accuracy_; ++ii) {
00480     std::cout << std::setw(12) << coeffs_interior_[ii];
00481 }
00482 std::cout << std::endl << std::endl;
00483 #endif
00484
00485 delete [] pp;
00486 pp = nullptr;

```

```

00487
00488     return true;
00489 }
00490
00491 bool mtk::Div1D::ComputeRationalBasisNullSpace(void) {
00492
00493     mtk::Real* gg{}; // Generator vector for the first Vandermonde matrix.
00494
00495
00496     try {
00497         gg = new mtk::Real[num_bndy_coeffs_];
00498     } catch (std::bad_alloc &memory_allocation_exception) {
00499         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00500             std::endl;
00501         std::cerr << memory_allocation_exception.what() << std::endl;
00502     }
00503
00504     memset(gg, mtk::kZero, sizeof(gg[0])*num_bndy_coeffs_);
00505
00506     #ifdef MTK_PRECISION_DOUBLE
00507     gg[0] = -1.0/2.0;
00508     #else
00509     gg[0] = -1.0f/2.0f;
00510     #endif
00511     for (auto ii = 1; ii < num_bndy_coeffs_; ++ii) {
00512         gg[ii] = gg[ii - 1] + mtk::kOne;
00513     }
00514
00515     #if MTK_DEBUG_LEVEL > 0
00516     std::cout << "gg =" << std::endl;
00517     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
00518         std::cout << std::setw(12) << gg[ii];
00519     }
00520     std::cout << std::endl << std::endl;
00521     #endif
00522
00523
00524     bool tran{true}; // Should I transpose the Vandermonde matrix.
00525
00526     mtk::DenseMatrix vv_west_t(gg, num_bndy_coeffs_, order_accuracy_ + 1, tran);
00527
00528     #if MTK_DEBUG_LEVEL > 0
00529     std::cout << "vv_west_t =" << std::endl;
00530     std::cout << vv_west_t << std::endl;
00531     #endif
00532
00533
00534     mtk::DenseMatrix qq_t(mtk::LAPACKAdapter::QRFactorDenseMatrix
00535         (vv_west_t));
00536
00537     #if MTK_DEBUG_LEVEL > 0
00538     std::cout << "QQ^T =" << std::endl;
00539     std::cout << qq_t << std::endl;
00540     #endif
00541
00542
00543     int KK_num_rows_{num_bndy_coeffs_};
00544     int KK_num_cols_{dim_null_};
00545
00546     mtk::DenseMatrix KK(KK_num_rows_, KK_num_cols_);
00547
00548     for (auto ii = num_bndy_coeffs_ - dim_null_; ii < num_bndy_coeffs_; ++ii) {
00549         for (auto jj = 0; jj < num_bndy_coeffs_; ++jj) {
00550             KK.data()[jj*dim_null_ + (ii - (num_bndy_coeffs_ - dim_null_))] =
00551                 qq_t.data()[ii*num_bndy_coeffs_ + jj];
00552         }
00553     }
00554
00555     #if MTK_DEBUG_LEVEL > 0
00556     std::cout << "KK =" << std::endl;
00557     std::cout << KK << std::endl;
00558     std::cout << "KK.num_rows() =" << KK.num_rows() << std::endl;
00559     std::cout << "KK.num_cols() =" << KK.num_cols() << std::endl;
00560     std::cout << std::endl;
00561     #endif
00562
00563     // Scale thus requesting that the last entries of the attained basis for the
00564     // null-space, adopt the pattern we require.
00565     // Essentially we will implement the following MATLAB pseudo-code:
00566     // scalers = KK(num_bndy_approxs - (dim_null - 1):num_bndy_approxs,:)\B
00567     // SK = KK*scalers

```

```

00572 // where SK is the scaled null-space.
00573
00574 // In this point, we almost have all the data we need correctly allocated
00575 // in memory. We will create the matrix II_, and elements we wish to scale in
00576 // the KK array. Using the concept of the leading dimension, we could just
00577 // use KK, with the correct leading dimension and that is it. BUT I DO NOT
00578 // GET how does it work. So I will just create a matrix with the content of
00579 // this array that we need, solve for the scalars and then scale the
00580 // whole KK:
00581
00582 // We will then create memory for that sub-matrix of KK (SUBK).
00583
00584 mtk::DenseMatrix SUBK(dim_null_, dim_null_);
00585
00586 for (auto ii = num_bndy_coeffs_ - dim_null_; ii < num_bndy_coeffs_; ++ii) {
00587     for (auto jj = 0; jj < dim_null_; ++jj) {
00588         SUBK.data()[ii - (num_bndy_coeffs_ - dim_null_)*dim_null_ + jj] =
00589             KK.data()[ii*dim_null_ + jj];
00590     }
00591 }
00592
00593 #if MTK_DEBUG_LEVEL > 0
00594 std::cout << "SUBK =" << std::endl;
00595 std::cout << SUBK << std::endl;
00596 #endif
00597
00598 SUBK.Transpose();
00599
00600 #if MTK_DEBUG_LEVEL > 0
00601 std::cout << "SUBK^T =" << std::endl;
00602 std::cout << SUBK << std::endl;
00603 #endif
00604
00605 bool padded{false};
00606 tran = false;
00607
00608 mtk::DenseMatrix II(dim_null_, padded, tran);
00609
00610 #if MTK_DEBUG_LEVEL > 0
00611 std::cout << "II =" << std::endl;
00612 std::cout << II << std::endl;
00613 #endif
00614
00615 // Solve the system to compute the scalars.
00616 // An example of the system to solve, for k = 8, is:
00617 //
00618 // SUBK*scalars = II_ or
00619 //
00620 // | 0.386018 -0.0339244 -0.129478 |           | 1 0 0 |
00621 // | -0.119774 0.0199423 0.0558632 |*scalars = | 0 1 0 |
00622 // | 0.0155708 -0.00349546 -0.00853182 |       | 0 0 1 |
00623 //
00624 // Notice this is a nrhs = 3 system.
00625 // Noteworthy: we do NOT ACTUALLY ALLOCATE space for the scalars... they
00626 // will be stored in the created identity matrix.
00627 // Let us first transpose SUBK (because of LAPACK):
00628
00629 int info{mtk::LAPACKAdapter::SolveDenseSystem(SUBK, II)};
00630
00631 #if MTK_DEBUG_LEVEL > 0
00632 if (!info) {
00633     std::cout << "System successfully solved!" <<
00634         std::endl;
00635 } else {
00636     std::cerr << "Something went wrong solving system! info = " << info <<
00637         std::endl;
00638     std::cerr << "Exiting..." << std::endl;
00639     return false;
00640 }
00641 std::cout << std::endl;
00642 #endif
00643
00644 #if MTK_DEBUG_LEVEL > 0
00645 std::cout << "Computed scalars:" << std::endl;
00646 std::cout << II << std::endl;
00647 #endif
00648
00649 // Multiply the two matrices to attain a scaled basis for null-space.
00650
00651 rat_basis_null_space_ = mtk::BLASAdapter::RealDenseMM(KK, II);
00652

```

```

00653     #if MTK_DEBUG_LEVEL > 0
00654     std::cout << "Rational basis for the null-space:" << std::endl;
00655     std::cout << rat_basis_null_space_ << std::endl;
00656     #endif
00657
00658     // At this point, we have a rational basis for the null-space, with the
00659     // pattern we need! :)
00660
00661     delete [] gg;
00662     gg = nullptr;
00663
00664     return true;
00665 }
00666
00667 bool mtk::Div1D::ComputePreliminaryApproximations(void) {
00668
00669     mtk::Real *gg{}; // Generator vector for the first approximation.
00670
00671     try {
00672         gg = new mtk::Real[num_bndy_coeffs_];
00673     } catch (std::bad_alloc &memory_allocation_exception) {
00674         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00675         std::endl;
00676         std::cerr << memory_allocation_exception.what() << std::endl;
00677     }
00678     memset(gg, mtk::kZero, sizeof(gg[0])*num_bndy_coeffs_);
00679
00680     #ifdef MTK_PRECISION_DOUBLE
00681     gg[0] = -1.0/2.0;
00682     #else
00683     gg[0] = -1.0f/2.0f;
00684     #endif
00685     for (auto ii = 1; ii < num_bndy_coeffs_; ++ii) {
00686         gg[ii] = gg[ii - 1] + mtk::kOne;
00687     }
00688
00689     #if MTK_DEBUG_LEVEL > 0
00690     std::cout << "gg0 =" << std::endl;
00691     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
00692         std::cout << std::setw(12) << gg[ii];
00693     }
00694     std::cout << std::endl << std::endl;
00695     #endif
00696
00697     // Allocate 2D array to store the collection of preliminary approximations.
00698     try {
00699         prem_apps_ = new mtk::Real[num_bndy_coeffs_*dim_null_];
00700     } catch (std::bad_alloc &memory_allocation_exception) {
00701         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00702         std::endl;
00703         std::cerr << memory_allocation_exception.what() << std::endl;
00704     }
00705     memset(prem_apps_,
00706            mtk::kZero,
00707            sizeof(prem_apps_[0])*num_bndy_coeffs_*dim_null_);
00708
00709     for (auto ll = 0; ll < dim_null_; ++ll) {
00710
00711         // Re-check new generator vector for every iteration except for the first.
00712         #if MTK_DEBUG_LEVEL > 0
00713         if (ll > 0) {
00714             std::cout << "gg" << ll << " =" << std::endl;
00715             for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
00716                 std::cout << std::setw(12) << gg[ii];
00717             }
00718             std::cout << std::endl << std::endl;
00719         }
00720         #endif
00721
00722         bool transpose{false};
00723
00724         mtk::DenseMatrix AA_(gg,
00725                               num_bndy_coeffs_, order_accuracy_ + 1,
00726                               transpose);
00727
00728         #if MTK_DEBUG_LEVEL > 0
00729         std::cout << "AA_" << ll << " =" << std::endl;
00730         std::cout << AA_ << std::endl;
00731         #endif
00732     }
00733 }

```



```

00737     #endif
00738
00740
00741     mtk::Real *ob{};
00742
00743     auto ob_ld = num_bndy_coeffs_;
00744
00745     try {
00746         ob = new mtk::Real[ob_ld];
00747     } catch (std::bad_alloc &memory_allocation_exception) {
00748         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00749             std::endl;
00750         std::cerr << memory_allocation_exception.what() << std::endl;
00751     }
00752     memset(ob, mtk::kZero, sizeof(ob[0])*ob_ld);
00753
00754     ob[1] = mtk::kOne;
00755
00756     #if MTK_DEBUG_LEVEL > 0
00757     std::cout << "ob = " << std::endl << std::endl;
00758     for (auto ii = 0; ii < ob_ld; ++ii) {
00759         std::cout << std::setw(12) << ob[ii] << std::endl;
00760     }
00761     std::cout << std::endl;
00762     #endif
00763
00764     // However, this is an under-determined system of equations. So we can not
00765     // use the same LAPACK routine (dgesv_). We will instead use dgels_, through
00766     // our LAPACKAdapter class.
00767
00768     int info_{
00769         mtk::LAPACKAdapter::SolveRectangularDenseSystem(AA_,
00770             ob, ob_ld)};
00771
00772     #if MTK_DEBUG_LEVEL > 0
00773     if (!info_) {
00774         std::cout << "System successfully solved!" << std::endl << std::endl;
00775     } else {
00776         std::cerr << "Error solving system! info = " << info_ << std::endl;
00777     }
00778     #endif
00779
00780     #if MTK_DEBUG_LEVEL > 0
00781     std::cout << "ob = " << std::endl;
00782     for (auto ii = 0; ii < ob_ld; ++ii) {
00783         std::cout << std::setw(12) << ob[ii] << std::endl;
00784     }
00785     std::cout << std::endl;
00786     #endif
00787
00788     // This implies a DAXPY operation. However, we must construct the arguments
00789     // for this operation.
00790
00791     // Save them into the ob_bottom array:
00792
00793     Real *ob_bottom{}; // Bottom part of the attained kernel used to scale it.
00794
00795     try {
00796         ob_bottom = new mtk::Real[dim_null_];
00797     } catch (std::bad_alloc &memory_allocation_exception) {
00798         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00799             std::endl;
00800         std::cerr << memory_allocation_exception.what() << std::endl;
00801     }
00802     memset(ob_bottom, mtk::kZero, sizeof(ob_bottom[0])*dim_null_);
00803
00804     for (auto ii = 0; ii < dim_null_; ++ii) {
00805         ob_bottom[(dim_null_ - 1) - ii] = ob[num_bndy_coeffs_ - ii - 1];
00806     }
00807
00808     #if MTK_DEBUG_LEVEL > 0
00809     std::cout << "ob_bottom =" << std::endl;
00810     for (auto ii = 0; ii < dim_null_; ++ii) {
00811         std::cout << std::setw(12) << ob_bottom[ii] << std::endl;
00812     }
00813     std::cout << std::endl;
00814     #endif
00815
00816
00817
00818
00819
00820
00821

```

```

00822 // We must computed an scaled ob, sob, using the scaled null-space in
00823 // rat_basis_null_space_.
00824 // Such operation is: sob = ob - rat_basis_null_space_*ob_bottom
00825 // or: ob = -1.0*rat_basis_null_space_*ob_bottom + 1.0*ob
00826 // thus: Y = a*A *x + b*Y (DAXPY).
00827
00828 #if MTK_DEBUG_LEVEL > 0
00829 std::cout << "Rational basis for the null-space:" << std::endl;
00830 std::cout << rat_basis_null_space_ << std::endl;
00831 #endif
00832
00833 mtk::Real alpha{-mtk::kOne};
00834 mtk::Real beta{mtk::kOne};
00835
00836 mtk::BLASAdapter::RealDenseMV(alpha, rat_basis_null_space_,
00837                                ob_bottom, beta, ob);
00838
00839 #if MTK_DEBUG_LEVEL > 0
00840 std::cout << "scaled ob:" << std::endl;
00841 for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
00842     std::cout << std::setw(12) << ob[ii] << std::endl;
00843 }
00844 std::cout << std::endl;
00845 #endif
00846
00847 // We save the recently scaled solution, into an array containing these.
00848 // We can NOT start building the pi matrix, simply because I want that part
00849 // to be separated since its construction depends on the algorithm we want
00850 // to implement.
00851
00852 for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
00853     prem_apps_[ii*dim_null_ + 11] = ob[ii];
00854 }
00855
00856 // After the first iteration, simply shift the entries of the last
00857 // generator vector used:
00858 for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
00859     gg[ii]--;
00860 }
00861
00862 // Garbage collection for this loop:
00863 delete[] ob;
00864 ob = nullptr;
00865
00866 delete[] ob_bottom;
00867 ob_bottom = nullptr;
00868 } // End of: for (11 = 0; 11 < dim_null; 11++);
00869
00870 #if MTK_DEBUG_LEVEL > 0
00871 std::cout << "Matrix post-scaled preliminary apps: " << std::endl;
00872 for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
00873     for (auto jj = 0; jj < dim_null_; ++jj) {
00874         std::cout << std::setw(12) << prem_apps_[ii*dim_null_ + jj];
00875     }
00876     std::cout << std::endl;
00877 }
00878 std::cout << std::endl;
00879 #endif
00880
00881 delete[] gg;
00882 gg = nullptr;
00883
00884 return true;
00885 }
00886
00887 bool mtk::Div1D::ComputeWeights(void) {
00888
00889     // Matrix to compute the weights as in the CRSA.
00890     mtk::DenseMatrix pi(num_bndy_coeffs_, num_bndy_coeffs_ - 1);
00891
00892     // Assemble the pi matrix using:
00893     // 1. The collection of scaled preliminary approximations.
00894     // 2. The collection of coefficients approximating at the interior.
00895     // 3. The scaled basis for the null-space.
00896
00897     // 1.1. Process array of scaled preliminary approximations.
00898
00899     // These are queued in scaled_solutions. Each one of these, will be a column
00900     // of the pi matrix:
00901     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {

```

```

00904     for (auto jj = 0; jj < dim_null_; ++jj) {
00905         pi.data()[ii*(2*dim_null_ + (order_accuracy_/2 + 1)) + jj] =
00906             prem_apps_[ii*dim_null_ + jj];
00907     }
00908 }
00909
00910 // 1.2. Add columns from known stencil approximating at the interior.
00911
00912 // However, these must be padded by zeros, according to their position in the
00913 // final pi matrix:
00914 auto mm = 0;
00915 for (auto jj = dim_null_; jj < order_accuracy_; ++jj) {
00916     for (auto ii = 0; ii < order_accuracy_; ++ii) {
00917         pi.data()[ (ii + mm)*(2*dim_null_ + (order_accuracy_/2 + 1)) + jj] =
00918             coeffs_interior_[ii];
00919     }
00920     ++mm;
00921 }
00922
00923 rat_basis_null_space_.OrderColMajor();
00924
00925 #if MTK_DEBUG_LEVEL > 0
00926 std::cout << "Rational basis for the null-space (col. major):" << std::endl;
00927 std::cout << rat_basis_null_space_ << std::endl;
00928 #endif
00929
00930 // 1.3. Add final set of columns: rational basis for null-space.
00931 for (auto jj = dim_null_ + (order_accuracy_/2 + 1); jj < num_bndy_coeffs_ - 1; ++jj) {
00932     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
00933         auto og =
00934             (jj - (dim_null_ + (order_accuracy_/2 + 1)))*num_bndy_coeffs_ + ii;
00935         auto de = ii*(2*dim_null_ + (order_accuracy_/2 + 1)) + jj;
00936         pi.data()[de] = rat_basis_null_space_.data()[og];
00937     }
00938 }
00939
00940 #if MTK_DEBUG_LEVEL > 0
00941 std::cout << "coeffs_interior_ =" << std::endl;
00942 for (auto ii = 0; ii < order_accuracy_; ++ii) {
00943     std::cout << std::setw(12) << coeffs_interior_[ii];
00944 }
00945 std::cout << std::endl << std::endl;
00946 #endif
00947
00948 #if MTK_DEBUG_LEVEL > 0
00949 std::cout << "Constructed pi matrix for CRS Algorithm: " << std::endl;
00950 std::cout << pi << std::endl;
00951 #endif
00952
00953 // This imposes the mimetic condition.
00954
00955 mtk::Real *hh{}; // Right-hand side to compute weights in the C(R,B)SA.
00956
00957 try {
00958     hh = new mtk::Real[num_bndy_coeffs_];
00959 } catch (std::bad_alloc &memory_allocation_exception) {
00960     std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00961         std::endl;
00962     std::cerr << memory_allocation_exception.what() << std::endl;
00963 }
00964 memset(hh, mtk::kZero, sizeof(hh[0])*num_bndy_coeffs_);
00965
00966 hh[0] = -mtk::kOne;
00967 for (auto ii = (order_accuracy_/2 + 2 - 1); ii < num_bndy_coeffs_; ++ii) {
00968     auto aux_xx = mtk::kZero;
00969     for (auto jj = 0; jj < ((ii - (order_accuracy_/2 - 1)) - 1); ++jj) {
00970         aux_xx += coeffs_interior_[jj];
00971     }
00972     hh[ii] = -mtk::kOne*aux_xx;
00973 }
00974
00975 // That is, we construct a system, to solve for the weights.
00976
00977 // Once again we face the challenge of solving with LAPACK. However, for the
00978 // CRSA, this matrix PI is over-determined, since it has more rows than
00979 // unknowns. However, according to the theory, the solution to this system is
00980 // unique. We will use dgels_.
00981
00982 try {

```

```

00987     weights_cbs_ = new mtk::Real[num_bndy_coeffs_];
00988 } catch (std::bad_alloc &memory_allocation_exception) {
00989     std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00990         std::endl;
00991     std::cerr << memory_allocation_exception.what() << std::endl;
00992 }
00993 memset(weights_cbs_, mtk::kZero, sizeof(weights_cbs_[0])*num_bndy_coeffs_);
00994
00995 int weights_ld{pi.num_cols() + 1};
00996
00997 // Preserve hh.
00998 std::copy(hh, hh + weights_ld, weights_cbs_);
00999
01000 pi.Transpose();
01001
01002 int info{mtk::LAPACKAdapter::SolveRectangularDenseSystem(
01003     pi, weights_cbs_, weights_ld)};
01004
01004 #if MTK_DEBUG_LEVEL > 0
01005 if (!info) {
01006     std::cout << "System successfully solved!" << std::endl << std::endl;
01007 } else {
01008     std::cerr << "Error solving system! info = " << info << std::endl;
01009 }
01010 #endif
01011
01012 #if MTK_DEBUG_LEVEL > 0
01013 std::cout << "hh =" << std::endl;
01014 for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
01015     std::cout << std::setw(11) << hh[ii] << std::endl;
01016 }
01017 std::cout << std::endl;
01018 #endif
01019
01020 // Preserve the original weights for research.
01021
01022 try {
01023     weights_crs_ = new mtk::Real[num_bndy_coeffs_];
01024 } catch (std::bad_alloc &memory_allocation_exception) {
01025     std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
01026         std::endl;
01027     std::cerr << memory_allocation_exception.what() << std::endl;
01028 }
01029 memset(weights_crs_, mtk::kZero, sizeof(weights_crs_[0])*num_bndy_coeffs_);
01030
01031 std::copy(weights_cbs_, weights_cbs_ + (weights_ld - 1), weights_crs_);
01032
01033 #if MTK_DEBUG_LEVEL > 0
01034 std::cout << "weights_CRSA + lambda =" << std::endl;
01035 for (auto ii = 0; ii < weights_ld - 1; ++ii) {
01036     std::cout << std::setw(12) << weights_crs_[ii] << std::endl;
01037 }
01038 std::cout << std::endl;
01039 #endif
01040
01042 if (order_accuracy_ >= mtk::kCriticalOrderAccuracyDiv) {
01043     int minrow_{std::numeric_limits<int>::infinity()};
01044
01046     mtk::Real norm_{mtk::BLASAdapter::RealNRM2(weights_cbs_,
01047         order_accuracy_)};
01048     mtk::Real minnorm_{std::numeric_limits<mtk::Real>::infinity()};
01049
01051     mtk::DenseMatrix phi(order_accuracy_ + 1, order_accuracy_);
01052
01053     for (auto ii = 0; ii < order_accuracy_ + 1; ++ii) {
01054         for (auto jj = 0; jj < dim_null_; ++jj) {
01055             phi.data()[ii*(order_accuracy_ + 1) + jj] = prem_apps_[ii*dim_null_ + jj];
01056         }
01057     }
01058
01059     int aux{}; // Auxiliary variable.
01060     for (auto jj = dim_null_; jj < dim_null_ + 2; ++jj) {
01061         for (auto ii = 0; ii < order_accuracy_; ++ii) {
01062             phi.data()[ii*(order_accuracy_ + 1) + jj] = coeffs_interior_[ii];
01063         }
01064         ++aux;
01065     }
01066
01067     for (auto jj = order_accuracy_ - 1; jj >= order_accuracy_ - dim_null_; jj--) {

```

```

01068     for(auto ii=0; ii<order_accuracy_ + 1; ++ii) {
01069         phi.data()[ii*order_accuracy_+jj] = mtk::kZero;
01070     }
01071 }
01072
01073 for (auto jj = 0; jj < order_accuracy_ + 1; ++jj) {
01074     for (auto ii = 0; ii < dim_null_; ++ii) {
01075         phi.data()[(ii + order_accuracy_ - dim_null_ + jj*order_accuracy_)] =
01076             -prem_apps[(dim_null_ - ii - 1 + jj*dim_null_)];
01077     }
01078 }
01079
01080 for(auto ii = 0; ii < order_accuracy_/2; ++ii) {
01081     for (auto jj = dim_null_ + 2; jj < order_accuracy_; ++jj) {
01082         auto swap = phi.data()[ii*order_accuracy_+jj];
01083         phi.data()[ii*order_accuracy_ + jj] =
01084             phi.data()[(order_accuracy_-ii)*order_accuracy_+jj];
01085         phi.data()[(order_accuracy_-ii)*order_accuracy_+jj] = swap;
01086     }
01087 }
01088
01089 #if MTK_DEBUG_LEVEL > 0
01090 std::cout << "Constructed PHI matrix for CBS Algorithm: " << std::endl;
01091 std::cout << phi << std::endl;
01092 #endif
01093
01094
01095 mtk::Real *lamed{}; // Used to build big lambda.
01096
01097 try {
01098     lamed = new mtk::Real[dim_null_];
01099 } catch (std::bad_alloc &memory_allocation_exception) {
01100     std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
01101         std::endl;
01102     std::cerr << memory_allocation_exception.what() << std::endl;
01103 }
01104 memset(lamed, mtk::kZero, sizeof(lamed[0])*dim_null_);
01105
01106 for (auto ii = 0; ii < dim_null_; ++ii) {
01107     lamed[ii] = hh[ii + order_accuracy_ + 1] ;
01108 }
01109
01110 #if MTK_DEBUG_LEVEL > 0
01111 std::cout << "lamed =" << std::endl;
01112 for (auto ii = 0; ii < dim_null_; ++ii) {
01113     std::cout << std::setw(12) << lamed[ii] << std::endl;
01114 }
01115 std::cout << std::endl;
01116 #endif
01117
01118 for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
01119     mtk::Real temp = mtk::kZero;
01120     for(auto jj = 0; jj < dim_null_; ++jj) {
01121         temp = temp +
01122             lamed[jj]*rat_basis_null_space_.data()[jj*num_bndy_coeffs_ + ii];
01123     }
01124     hh[ii] = hh[ii] - temp;
01125 }
01126
01127 #if MTK_DEBUG_LEVEL > 0
01128 std::cout << "big_lambda =" << std::endl;
01129 for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
01130     std::cout << std::setw(12) << hh[ii] << std::endl;
01131 }
01132 std::cout << std::endl;
01133 #endif
01134
01135 int copy_result{};
01136
01137 mtk::Real normerr_; // Norm of the error for the solution on each row.
01138
01139 for(auto row_ = 0; row_ < order_accuracy_ + 1; ++row_) {
01140     normerr_ = mtk::GLPKAdapter::SolveSimplexAndCompare(phi.
01141         data(),
01142             order_accuracy_ + 1,
01143             order_accuracy_,
01144             order_accuracy_,
01145             hh,
01146             weights_cbs_,
01147             row_,

```

```

01150                                     mimetic_threshold_,
01151                                     copy_result);
01152     mtk::Real aux{normerr_/norm_};
01153
01154     #if MTK_DEBUG_LEVEL>0
01155     std::cout << "Relative norm: " << aux << " " << std::endl;
01156     std::cout << std::endl;
01157     #endif
01158
01159     if (aux < minnorm_) {
01160         minnorm_ = aux;
01161         minrow_ = row_;
01162     }
01163 }
01164
01165 #if MTK_DEBUG_LEVEL > 0
01166 std::cout << "weights_CBSA + lambda (after brute force search):" <<
01167 std::endl;
01168 for (auto ii = 0; ii < num_bndy_coeffs_ - 1; ++ii) {
01169     std::cout << std::setw(12) << weights_cbs_[ii] << std::endl;
01170 }
01171 std::cout << std::endl;
01172 #endif
01173
01175
01176 // After we know which row yields the smallest relative norm that row is
01177 // chosen to be the objective function and the result of the optimizer is
01178 // chosen to be the new weights_.
01179
01180 #if MTK_DEBUG_LEVEL > 0
01181 std::cout << "Minimum Relative Norm " << minnorm_ << " found at row " <<
01182 minrow_ + 1 << std::endl;
01183 std::cout << std::endl;
01184 #endif
01185
01186 copy_result = 1;
01187 normerr_ = mtk::GLPKAdapter::SolveSimplexAndCompare(phi.
data(),
01188                                     order_accuracy_ + 1,
01189                                     order_accuracy_,
01190                                     order_accuracy_,
01191                                     hh,
01192                                     weights_cbs_,
01193                                     minrow_,
01194                                     mimetic_threshold_,
01195                                     copy_result);
01196 mtk::Real aux_{normerr_/norm_};
01197 #if MTK_DEBUG_LEVEL > 0
01198 std::cout << "Relative norm: " << aux_ << std::endl;
01199 std::cout << std::endl;
01200 #endif
01201
01202 delete [] lamed;
01203 lamed = nullptr;
01204 }
01205
01206 delete [] hh;
01207 hh = nullptr;
01208
01209 return true;
01210 }
01211
01212 bool mtk::Div1D::ComputeStencilBoundaryGrid(void) {
01213
01214     #if MTK_DEBUG_LEVEL > 0
01215     std::cout << "weights_CBSA + lambda =" << std::endl;
01216     for (auto ii = 0; ii < num_bndy_coeffs_ - 1; ++ii) {
01217         std::cout << std::setw(12) << weights_cbs_[ii] << std::endl;
01218     }
01219     std::cout << std::endl;
01220     #endif
01221
01222
01223
01224     mtk::Real *lambda{}; // Collection of bottom values from weights_.
01225
01226     try {
01227         lambda = new mtk::Real[dim_null_];
01228     } catch (std::bad_alloc &memory_allocation_exception) {
01229         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
01230         std::endl;
01231         std::cerr << memory_allocation_exception.what() << std::endl;

```

```

01232     }
01233     memset(lambda, mtk::kZero, sizeof(lambda[0])*dim_null_);
01234
01235     for (auto ii = 0; ii < dim_null_; ++ii) {
01236         lambda[ii] = weights_cbs_[order_accuracy_ + ii];
01237     }
01238
01239     #if MTK_DEBUG_LEVEL > 0
01240     std::cout << "lambda =" << std::endl;
01241     for (auto ii = 0; ii < dim_null_; ++ii) {
01242         std::cout << std::setw(12) << lambda[ii] << std::endl;
01243     }
01244     std::cout << std::endl;
01245     #endif
01246
01248
01249     mtk::Real *alpha{}; // Collection of alpha values.
01250
01251     try {
01252         alpha = new mtk::Real[dim_null_];
01253     } catch (std::bad_alloc &memory_allocation_exception) {
01254         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
01255             std::endl;
01256         std::cerr << memory_allocation_exception.what() << std::endl;
01257     }
01258     memset(alpha, mtk::kZero, sizeof(alpha[0])*dim_null_);
01259
01260     for (auto ii = 0; ii < dim_null_; ++ii) {
01261         alpha[ii] = lambda[ii]/weights_cbs_[ii];
01262     }
01263
01264     #if MTK_DEBUG_LEVEL > 0
01265     std::cout << "alpha =" << std::endl;
01266     for (auto ii = 0; ii < dim_null_; ++ii) {
01267         std::cout << std::setw(12) << alpha[ii] << std::endl;
01268     }
01269     std::cout << std::endl;
01270     #endif
01271
01273
01274     try {
01275         mim_bndy_ = new mtk::Real[num_bndy_coeffs_*dim_null_];
01276     } catch (std::bad_alloc &memory_allocation_exception) {
01277         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
01278             std::endl;
01279         std::cerr << memory_allocation_exception.what() << std::endl;
01280     }
01281     memset(mim_bndy_, mtk::kZero, sizeof(mim_bndy_[0])*num_bndy_coeffs_*dim_null_);
01282
01283     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
01284         for (auto jj = 0; jj < dim_null_; ++jj) {
01285             mim_bndy_[ii*dim_null_ + jj] =
01286                 prem_apps_[ii*dim_null_ + jj] +
01287                 alpha[jj]*rat_basis_null_space_.data()[jj*num_bndy_coeffs_ + ii];
01288         }
01289     }
01290
01291     #if MTK_DEBUG_LEVEL > 0
01292     std::cout << "Collection of mimetic approximations:" << std::endl;
01293     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
01294         for (auto jj = 0; jj < dim_null_; ++jj) {
01295             std::cout << std::setw(13) << mim_bndy_[ii*dim_null_ + jj];
01296         }
01297         std::cout << std::endl;
01298     }
01299     std::cout << std::endl;
01300     #endif
01301
01302     delete[] lambda;
01303     lambda = nullptr;
01304
01305     delete[] alpha;
01306     alpha = nullptr;
01307
01308     return true;
01309 }
01310
01311 bool mtk::Div1D::AssembleOperator(void) {
01312
01313     // The output array will have this form:
01314     // 1. The first entry of the array will contain the used order order_accuracy_.

```

```

01315 // 2. The second entry of the array will contain the collection of
01316 // approximating coefficients for the interior of the grid.
01317 // 3. IF order_accuracy_ > 2, then the third entry will contain a collection of weights.
01318 // 4. IF order_accuracy_ > 2, the next dim_null_ entries will contain the collections of
01319 // approximating coefficients for the west boundary of the grid.
01320
01321 if (order_accuracy_ > mtk::kDefaultOrderAccuracy) {
01322     divergence_length_ =
01323         1 + order_accuracy_ + order_accuracy_ + dim_null_*num_bndy_coeffs_;
01324 } else {
01325     divergence_length_ = 1 + order_accuracy_;
01326 }
01327
01328 #if MTK_DEBUG_LEVEL > 0
01329 std::cout << "divergence_length_ = " << divergence_length_ << std::endl;
01330 #endif
01331
01332 try {
01333     divergence_ = new double[divergence_length_];
01334 } catch (std::bad_alloc &memory_allocation_exception) {
01335     std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
01336         std::endl;
01337     std::cerr << memory_allocation_exception.what() << std::endl;
01338 }
01339 memset(divergence_, mtk::kZero, sizeof(divergence_[0])*divergence_length_);
01340
01342 divergence_[0] = order_accuracy_;
01344
01346 for (auto ii = 0; ii < order_accuracy_; ++ii) {
01347     divergence_[ii + 1] = coeffs_interior_[ii];
01348 }
01349
01352 if (order_accuracy_ > 2) {
01353     for (auto ii = 0; ii < order_accuracy_; ++ii) {
01354         divergence_[1 + order_accuracy_ + ii] = weights_cbs_[ii];
01355     }
01356 }
01357
01362 if (order_accuracy_ > 2) {
01363     auto offset = (2*order_accuracy_ + 1);
01364     int mm{};
01365     for (auto ii = 0; ii < dim_null_; ++ii) {
01366         for (auto jj = 0; jj < num_bndy_coeffs_; ++jj) {
01367             divergence_[offset + (mm)] = mim_bndy_[jj*dim_null_ + ii];
01368             ++mm;
01369         }
01370     }
01371 }
01372
01373 #if MTK_DEBUG_LEVEL > 0
01374 std::cout << "1D " << order_accuracy_ << "-order div built!" << std::endl;
01375 std::cout << std::endl;
01376 #endif
01377
01378 return true;
01379 }

```

17.41 src/mtk_glpk_adapter.cc File Reference


Adapter class for the GLPK API.

```

#include <cmath>
#include <cstring>
#include <iostream>
#include <iomanip>
#include <limits>
#include "mtk_roots.h"
#include "mtk_blas_adapter.h"
#include "mtk_glpk_adapter.h"

```


Include dependency graph for mtk_glpk_adapter.cc:



17.41.1 Detailed Description

This class contains a collection of static classes, that posses direct access to the underlying structure of the matrices, thus allowing programmers to exploit some of the numerical methods implemented in the GLPK.

The **GLPK (GNU Linear Programming Kit)** package is intended for solving large-scale linear programming (LP), mixed integer programming (MIP), and other related problems. It is a set of routines written in ANSI C and organized in the form of a callable library.

See Also

<http://www.gnu.org/software/glpk/>

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Todo Document better this file.

Definition in file [mtk_glpk_adapter.cc](#).

17.42 mtk_glpk_adapter.cc

```

00001
00021 /*
00022 Copyright (C) 2015, Computational Science Research Center, San Diego State
00023 University. All rights reserved.
00024
00025 Redistribution and use in source and binary forms, with or without modification,
00026 are permitted provided that the following conditions are met:
00027
00028 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00029 and a copy of the modified files should be reported once modifications are
00030 completed. Documentation related to said modifications should be included.
00031
00032 2. Redistributions of source code must be done through direct
00033 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00034
00035 3. Redistributions of source code must retain the above copyright notice, this
  
```

```

00036 list of conditions and the following disclaimer.
00037
00038 4. Redistributions in binary form must reproduce the above copyright notice,
00039 this list of conditions and the following disclaimer in the documentation and/or
00040 other materials provided with the distribution.
00041
00042 5. Usage of the binary form on proprietary applications shall require explicit
00043 prior written permission from the the copyright holders.
00044
00045 6. Neither the name of the copyright holder nor the names of its contributors
00046 may be used to endorse or promote products derived from this software without
00047 specific prior written permission.
00048
00049 The copyright holders provide no reassurances that the source code provided does
00050 not infringe any patent, copyright, or any other intellectual property rights of
00051 third parties. The copyright holders disclaim any liability to any recipient for
00052 claims brought against recipient by any third party for infringement of that
00053 parties intellectual property rights.
00054
00055 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00056 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00057 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00058 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00059 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00060 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00061 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00062 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00063 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00064 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00065 */
00066
00067 #include <cmath>
00068 #include <cstring>
00069
00070 #include <iostream>
00071 #include <iomanip>
00072 #include <limits>
00073
00074 #include "mtk_roots.h"
00075 #include "mtk_blas_adapter.h"
00076 #include "mtk_glpk_adapter.h"
00077
00078 mtk::Real mtk::GLPKAdapter::SolveSimplexAndCompare(
    mtk::Real *A,
00079
00080
00081
00082
00083
00084
00085
00086
00087
00088
00089
00090
00091
00092
00093
00094
00095
00096
00097
00098
00099
00100
00101
00102
00103
00104
00105
00106
00107
00108
00109
00110
00111
00112
00113
00114
00115
    int nrows,
    int ncols,
    int kk,
    mtk::Real *hh,
    mtk::Real *qq,
    int robjective,
    mtk::Real mimetic_threshold,
    int copy) {
    #if MTK_DEBUG_LEVEL > 0
    char mps_file_name[18]; // File name for the MPS files.
    #endif
    char rname[5]; //
    char cname[5]; //
    glp_prob *lp; // Linear programming problem.
    int *ia; //
    int *ja; //
    int problem_size; // Size of the problem.
    int lp_nrows; // Number of rows.
    int lp_ncols; // Number of columns.
    int matsize; //
    int glp_index{1}; // Index of the objective function.
    int ii; //
    int jj; //
    mtk::Real *ar; //
    mtk::Real *objective; //
    mtk::Real *rhs; //
    mtk::Real *err; //
    mtk::Real x1; //
    #if MTK_DEBUG_LEVEL > 0
    mtk::Real obj_value; //
    #endif

```

```

00116
00117     lp_nrows = kk;
00118     lp_ncols = kk;
00119
00120     matsize = lp_nrows*lp_ncols;
00121
00123
00125     problem_size = lp_nrows*lp_ncols + 1;
00126
00127     try {
00128         ia = new int[problem_size];
00129     } catch (std::bad_alloc &memory_allocation_exception) {
00130         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00131             std::endl;
00132         std::cerr << memory_allocation_exception.what() << std::endl;
00133     }
00134     memset(ia, 0, sizeof(ia[0])*problem_size);
00135
00136     try {
00137         ja = new int[problem_size];
00138     } catch (std::bad_alloc &memory_allocation_exception) {
00139         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00140             std::endl;
00141         std::cerr << memory_allocation_exception.what() << std::endl;
00142     }
00143     memset(ja, 0, sizeof(ja[0])*problem_size);
00144
00145     try {
00146         ar = new mtk::Real[problem_size];
00147     } catch (std::bad_alloc &memory_allocation_exception) {
00148         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00149             std::endl;
00150         std::cerr << memory_allocation_exception.what() << std::endl;
00151     }
00152     memset(ar, mtk::kZero, sizeof(ar[0])*problem_size);
00153
00154     try {
00155         objective = new mtk::Real[lp_ncols + 1];
00156     } catch (std::bad_alloc &memory_allocation_exception) {
00157         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00158             std::endl;
00159         std::cerr << memory_allocation_exception.what() << std::endl;
00160     }
00161     memset(objective, mtk::kZero, sizeof(objective[0])*(lp_ncols + 1));
00162
00163     try {
00164         rhs = new mtk::Real[lp_nrows + 1];
00165     } catch (std::bad_alloc &memory_allocation_exception) {
00166         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00167             std::endl;
00168         std::cerr << memory_allocation_exception.what() << std::endl;
00169     }
00170     memset(rhs, mtk::kZero, sizeof(rhs[0])*(lp_nrows + 1));
00171
00172     try {
00173         err = new mtk::Real[lp_nrows];
00174     } catch (std::bad_alloc &memory_allocation_exception) {
00175         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00176             std::endl;
00177         std::cerr << memory_allocation_exception.what() << std::endl;
00178     }
00179     memset(err, mtk::kZero, sizeof(err[0])*(lp_nrows));
00180
00181     #if MTK_DEBUG_LEVEL > 0
00182     std::cout << "Problem size: " << problem_size << std::endl;
00183     std::cout << "lp_nrows = " << lp_nrows << std::endl;
00184     std::cout << "lp_ncols = " << lp_ncols << std::endl;
00185     std::cout << std::endl;
00186     #endif
00187
00188     lp = glp_create_prob();
00189
00190     glp_set_prob_name (lp, "mtk::GLPKAdapter::Simplex");
00191
00192     glp_set_obj_dir (lp, GLP_MIN);
00193
00195     glp_add_rows(lp, lp_nrows);
00196
00197     for (ii = 1; ii <= lp_nrows; ++ii) {
00198         sprintf(rname, "R%02d",ii);
00199

```

```

00200     glp_set_row_name(lp, ii, rname);
00201 }
00202
00203 glp_add_cols(lp, lp_ncols);
00204
00205 for (ii = 1; ii <= lp_ncols; ++ii) {
00206     sprintf(cname, "Q%02d", ii);
00207     glp_set_col_name (lp, ii, cname);
00208 }
00209
00210
00211
00212 #if MTK_DEBUG_LEVEL>0
00213 std::cout << "Using row " << robjective + 1 << " as objective." << std::endl;
00214 #endif
00215 for (jj = 0; jj < kk; ++jj) {
00216     objective[glp_index] = A[jj + robjective * ncols];
00217     glp_index++;
00218 }
00219 #if MTK_DEBUG_LEVEL >0
00220 std::cout << std::endl;
00221 #endif
00222
00223
00224
00225 glp_index = 1;
00226 rhs[0] = mtk::kZero;
00227 for (ii = 0; ii <= lp_nrows; ++ii) {
00228     if (ii != robjective) {
00229         rhs[glp_index] = hh[ii];
00230         glp_set_row_bnds(lp, glp_index, GLP_UP, 0.0, rhs[glp_index]);
00231         glp_index++;
00232     }
00233 }
00234
00235 #if MTK_DEBUG_LEVEL > 0
00236 std::cout << "rhs =" << std::endl;
00237 for (auto ii = 0; ii < lp_nrows; ++ii) {
00238     std::cout << std::setw(15) << rhs[ii] << std::endl;
00239 }
00240 std::cout << std::endl;
00241 #endif
00242
00243
00244
00245 for (ii = 1; ii <= lp_ncols; ++ii) {
00246     glp_set_obj_coef (lp, ii, objective[ii]);
00247 }
00248
00249
00250
00251 for (ii = 1; ii <= lp_ncols; ++ii) {
00252     glp_set_col_bnds (lp, ii, GLP_LO, mimetic_threshold, 0.0);
00253 }
00254
00255
00256
00257 glp_index = 1;
00258 for (ii = 0; ii <= kk; ++ii) {
00259     for (jj = 0; jj < kk; ++jj) {
00260         if (ii != robjective) {
00261             ar[glp_index] = A[jj + ii * ncols];
00262             glp_index++;
00263         }
00264     }
00265 }
00266
00267 glp_index = 0;
00268
00269 for (ii = 1; ii < problem_size; ++ii) {
00270     if (((ii - 1) % lp_ncols) == 0) {
00271         glp_index++;
00272     }
00273     ia[ii] = glp_index;
00274     ja[ii] = (ii - 1) % lp_ncols + 1;
00275 }
00276
00277 glp_load_matrix (lp, matsize, ia, ja, ar);
00278
00279 #if MTK_DEBUG_LEVEL > 0
00280 sprintf(mps_file_name, "LP_MPS_row_%02d.mps", robjective);
00281 glp_write_mps(lp, GLP_MPS_FILE, nullptr, mps_file_name);
00282 #endif
00283
00284
00285
00286 glp_simplex (lp, nullptr);

```

```

00287
00288 // Check status of the solution.
00289
00290 if (glp_get_status(lp) == GLP_OPT) {
00291
00292     for(ii = 1; ii <= lp_ncols; ++ii) {
00293         err[ii - 1] = qq[ii - 1] - glp_get_col_prim(lp,ii);
00294     }
00295
00296     #if MTK_DEBUG_LEVEL > 0
00297     obj_value = glp_get_obj_val (lp);
00298     std::cout << std::setw(12) << "CBS" << std::endl;
00299     for (ii = 0; ii < lp_ncols; ++ii) {
00300         std::cout << "q_" << ii + 1 << " = " << std::setw(12) <<
00301             glp_get_col_prim(lp,ii + 1) << std::endl;
00302     }
00303     std::cout << "Objective function value (row " << robjective + 1 << ") = " <<
00304         obj_value << std::endl;
00305     #endif
00306
00307     if (copy) {
00308         for(ii = 0; ii < lp_ncols; ++ii) {
00309             qq[ii] = glp_get_col_prim(lp,ii + 1);
00310         }
00311         // Preserve the bottom values of qq.
00312     }
00313
00314     x1 = mtk::BLASAdapter::RealNRM2(err,lp_ncols);
00315
00316 } else {
00317     x1 = std::numeric_limits<mtk::Real>::infinity();
00318 }
00319
00320 glp_delete_prob (lp);
00321 glp_free_env ();
00322
00323 delete [] ia;
00324 delete [] ja;
00325 delete [] ar;
00326 delete [] objective;
00327 delete [] rhs;
00328 delete [] err;
00329
00330 return x1;
00331 }

```

17.43 src/mtk_grad_1d.cc File Reference


Implements the class Grad1D.

```

#include <cmath>
#include <cstring>
#include <iostream>
#include <iomanip>
#include <limits>
#include <algorithm>
#include "mtk_tools.h"
#include "mtk_blas_adapter.h"
#include "mtk_lapack_adapter.h"
#include "mtk_glpk_adapter.h"
#include "mtk_grad_1d.h"

```

Include dependency graph for `mtk_grad_1d.cc`:



Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

Functions

- `std::ostream & mtk::operator<< (std::ostream &stream, mtk::Grad1D &in)`

17.43.1 Detailed Description

This class implements a 1D gradient matrix operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Todo Overload ostream operator as in [mtk::Lap1D](#).

Todo Implement creation of `mtk::BLASAdapter`.

Definition in file [mtk_grad_1d.cc](#).

17.44 mtk_grad_1d.cc

```
00001
00015 /*
00016 Copyright (C) 2015, Computational Science Research Center, San Diego State
00017 University. All rights reserved.
00018
00019 Redistribution and use in source and binary forms, with or without modification,
00020 are permitted provided that the following conditions are met:
00021
00022 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00023 and a copy of the modified files should be reported once modifications are
00024 completed. Documentation related to said modifications should be included.
00025
00026 2. Redistributions of source code must be done through direct
00027 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00028
00029 3. Redistributions of source code must retain the above copyright notice, this
00030 list of conditions and the following disclaimer.
```

```

00031
00032 4. Redistributions in binary form must reproduce the above copyright notice,
00033 this list of conditions and the following disclaimer in the documentation and/or
00034 other materials provided with the distribution.
00035
00036 5. Usage of the binary form on proprietary applications shall require explicit
00037 prior written permission from the the copyright holders.
00038
00039 6. Neither the name of the copyright holder nor the names of its contributors
00040 may be used to endorse or promote products derived from this software without
00041 specific prior written permission.
00042
00043 The copyright holders provide no reassurances that the source code provided does
00044 not infringe any patent, copyright, or any other intellectual property rights of
00045 third parties. The copyright holders disclaim any liability to any recipient for
00046 claims brought against recipient by any third party for infringement of that
00047 parties intellectual property rights.
00048
00049 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00050 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00051 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00052 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00053 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00054 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00055 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00056 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00057 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00058 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00059 */
00060
00061 #include <cmath>
00062 #include <cstring>
00063
00064 #include <iostream>
00065 #include <iomanip>
00066 #include <limits>
00067 #include <algorithm>
00068
00069 #include "mtk_tools.h"
00070
00071 #include "mtk_blas_adapter.h"
00072 #include "mtk_lapack_adapter.h"
00073 #include "mtk_glpk_adapter.h"
00074
00075 #include "mtk_grad_1d.h"
00076
00077 namespace mtk {
00078
00079 std::ostream& operator <<(std::ostream &stream, mtk::Grad1D &in) {
00080
00081     stream << "gradient_[0] = " << std::setw(9) << in.gradient_[0] << std::endl;
00082
00083     stream << "gradient_[1:" << in.order_accuracy_ << "] = ";
00084     for (auto ii = 1; ii <= in.order_accuracy_; ++ii) {
00085         stream << std::setw(9) << in.gradient_[ii] << " ";
00086     }
00087     stream << std::endl;
00088
00089     stream << "gradient_[ " << in.order_accuracy_ + 1 << ":" <<
00090         2*in.order_accuracy_ << "] = ";
00091     for (auto ii = in.order_accuracy_ + 1; ii <= 2*in.
00092         order_accuracy_; ++ii) {
00093         stream << std::setw(9) << in.gradient_[ii] << " ";
00094     }
00095     stream << std::endl;
00096
00097     int offset{2*in.order_accuracy_ + 1};
00098     int mm {};
00099
00100     stream << "gradient_[ " << offset + mm << ":" <<
00101         offset + mm + in.num_bndy_coeffs_ - 1 << "] = ";
00102
00103     if (in.order_accuracy_ > mtk::kDefaultOrderAccuracy) {
00104         for (auto ii = 0; ii < in.num_bndy_approxs_ ; ++ii) {
00105             for (auto jj = 0; jj < in.num_bndy_coeffs_ ; ++jj) {
00106                 auto value = in.gradient_[offset + (mm)];
00107                 stream << std::setw(9) << value << " ";
00108             }
00109         }
00110     }
00111 }

```

```

00115         mm++;
00116     }
00117 }
00118 } else {
00119     stream << std::setw(9) << in.gradient_[offset + 0] << ' ';
00120     stream << std::setw(9) << in.gradient_[offset + 1] << ' ';
00121     stream << std::setw(9) << in.gradient_[offset + 2] << ' ';
00122 }
00123 stream << std::endl;
00124
00125 return stream;
00126 }
00127 }
00128
00129 mtk::Grad1D::Grad1D():
00130     order_accuracy_(mtk::kDefaultOrderAccuracy),
00131     dim_null_(),
00132     num_bndy_approxs_(),
00133     num_bndy_coeffs_(),
00134     gradient_length_(),
00135     minrow_(),
00136     row_(),
00137     coeffs_interior_(),
00138     prem_apps_(),
00139     weights_crs_(),
00140     weights_cbs_(),
00141     mim_bndy_(),
00142     gradient_(),
00143     mimetic_threshold_(mtk::kDefaultMimeticThreshold) {}
00144
00145 mtk::Grad1D::Grad1D(const Grad1D &grad):
00146     order_accuracy_(grad.order_accuracy_),
00147     dim_null_(grad.dim_null_),
00148     num_bndy_approxs_(grad.num_bndy_approxs_),
00149     num_bndy_coeffs_(grad.num_bndy_coeffs_),
00150     gradient_length_(grad.gradient_length_),
00151     minrow_(grad.minrow_),
00152     row_(grad.row_),
00153     coeffs_interior_(grad.coeffs_interior_),
00154     prem_apps_(grad.prem_apps_),
00155     weights_crs_(grad.weights_crs_),
00156     weights_cbs_(grad.weights_cbs_),
00157     mim_bndy_(grad.mim_bndy_),
00158     gradient_(grad.gradient_),
00159     mimetic_threshold_(grad.mimetic_threshold_) {}
00160
00161 mtk::Grad1D::~~Grad1D() {
00162
00163     delete[] coeffs_interior_;
00164     coeffs_interior_ = nullptr;
00165
00166     delete[] prem_apps_;
00167     prem_apps_ = nullptr;
00168
00169     delete[] weights_crs_;
00170     weights_crs_ = nullptr;
00171
00172     delete[] weights_cbs_;
00173     weights_cbs_ = nullptr;
00174
00175     delete[] mim_bndy_;
00176     mim_bndy_ = nullptr;
00177
00178     delete[] gradient_;
00179     gradient_ = nullptr;
00180 }
00181
00182 bool mtk::Grad1D::ConstructGrad1D(int order_accuracy,
00183     Real mimetic_threshold) {
00184
00185     #if MTK_DEBUG_LEVEL > 0
00186     mtk::Tools::Prevent(order_accuracy < 2, __FILE__, __LINE__, __func__);
00187     mtk::Tools::Prevent((order_accuracy%2) != 0, __FILE__, __LINE__, __func__);
00188     mtk::Tools::Prevent(mimetic_threshold <= mtk::kZero,
00189         __FILE__, __LINE__, __func__);
00190
00191     if (order_accuracy >= mtk::kCriticalOrderAccuracyGrad) {
00192         std::cout << "WARNING: Numerical accuracy is high." << std::endl;
00193     }
00194     std::cout << "order_accuracy_ = " << order_accuracy << std::endl;

```



```

00195     std::cout << "mimetic_threshold_ = " << mimetic_threshold << std::endl;;
00196     #endif
00197
00198     order_accuracy_ = order_accuracy;
00199     mimetic_threshold_ = mimetic_threshold;
00200
00202
00203     bool abort_construction = ComputeStencilInteriorGrid();
00204
00205     #if MTK_DEBUG_LEVEL > 0
00206     if (!abort_construction) {
00207         std::cerr << "Could NOT complete stage 1." << std::endl;;
00208         std::cerr << "Exiting..." << std::endl;;
00209         return false;
00210     }
00211     #endif
00212
00213     // At this point, we already have the values for the interior stencil stored
00214     // in the coeffs_interior_ array.
00215
00216     dim_null_ = order_accuracy_/2 - 1;
00217
00218     num_bndy_approxs_ = dim_null_ + 1;
00219
00220     #ifdef MTK_PRECISION_DOUBLE
00221     num_bndy_coeffs_ = (int) (3.0*((mtk::Real) order_accuracy_)/2.0);
00222     #else
00223     num_bndy_coeffs_ = (int) (3.0f*((mtk::Real) order_accuracy_)/2.0f);
00224     #endif
00225
00227
00228     // For this we will follow recommendations given in:
00229     //
00230     // http://icl.cs.utk.edu/lapack-forum/viewtopic.php?f=5&t=4506
00231     //
00232     // We will compute the QR Factorization of the transpose, as in the
00233     // following (MATLAB) pseudo-code:
00234     //
00235     // [Q,R] = qr(V'); % Full QR as defined in
00236     // % http://www.stanford.edu/class/ee263/notes/qr\_matlab.pdf
00237     //
00238     // null-space = Q(:, last (order_accuracy_/2 - 1) columns of Q );
00239     //
00240     // However, given the nature of the Vandermonde matrices we've just
00241     // computed, they all possess the same null-space. Therefore, we impose the
00242     // convention of computing the null-space of the first Vandermonde matrix
00243     // (west boundary).
00244
00245     // In the case of the gradient, the first Vandermonde system has a unique
00246     // solution for the case of second-order-accuracy. Ergo, the Vandermonde
00247     // matrix used to assemble said system, will have an empty null-space.
00248
00249     // Therefore, we only compute a rational basis for the case of order higher
00250     // than second.
00251
00252     if (dim_null_ > 0) {
00253
00254         abort_construction = ComputeRationalBasisNullSpace();
00255
00256         #if MTK_DEBUG_LEVEL > 0
00257         if (!abort_construction) {
00258             std::cerr << "Could NOT complete stage 2.1." << std::endl;;
00259             std::cerr << "Exiting..." << std::endl;;
00260             return false;
00261         }
00262         #endif
00263     }
00264
00266
00267     abort_construction = ComputePreliminaryApproximations();
00268
00269     #if MTK_DEBUG_LEVEL > 0
00270     if (!abort_construction) {
00271         std::cerr << "Could NOT complete stage 2.2." << std::endl;;
00272         std::cerr << "Exiting..." << std::endl;;
00273         return false;
00274     }
00275     #endif
00276
00278
00279     abort_construction = ComputeWeights();

```

```

00280
00281 #if MTK_DEBUG_LEVEL > 0
00282 if (!abort_construction) {
00283     std::cerr << "Could NOT complete stage 2.3." << std::endl;;
00284     std::cerr << "Exiting..." << std::endl;;
00285     return false;
00286 }
00287 #endif
00288
00290
00291 if (dim_null_ > 0) {
00292
00293     abort_construction = ComputeStencilBoundaryGrid();
00294
00295     #if MTK_DEBUG_LEVEL > 0
00296     if (!abort_construction) {
00297         std::cerr << "Could NOT complete stage 2.4." << std::endl;;
00298         std::cerr << "Exiting..." << std::endl;;
00299         return false;
00300     }
00301     #endif
00302 }
00303
00305
00306 // Once we have the following three collections of data:
00307 // (a) the coefficients for the interior,
00308 // (b) the coefficients for the boundary (if it applies),
00309 // (c) and the weights (if it applies),
00310 // we will store everything in the output array:
00311
00312 abort_construction = AssembleOperator();
00313
00314 #if MTK_DEBUG_LEVEL > 0
00315 if (!abort_construction) {
00316     std::cerr << "Could NOT complete stage 3." << std::endl;;
00317     std::cerr << "Exiting..." << std::endl;;
00318     return false;
00319 }
00320 #endif
00321
00322 return true;
00323 }
00324
00325 int mtk::Grad1D::num_bndy_coeffs() {
00326     return num_bndy_coeffs_;
00327 }
00328
00329 mtk::Real *mtk::Grad1D::weights_crs() {
00330     return weights_crs_;
00331 }
00332
00333 mtk::Real *mtk::Grad1D::weights_cbs() {
00334     return weights_cbs_;
00335 }
00336
00337 mtk::DenseMatrix mtk::Grad1D::ReturnAsDenseMatrix(const
00338     UniStgGrid1D &grid) {
00339
00340     int nn{grid.num_cells_x()}; // Number of cells on the grid.
00341
00342     #if MTK_DEBUG_LEVEL > 0
00343     mtk::Tools::Prevent(order_accuracy_ <= 0, __FILE__, __LINE__, __func__);
00344
00345     mtk::Tools::Prevent(nn < 3*order_accuracy_ - 2, __FILE__, __LINE__, __func__);
00346     #endif
00347
00348     mtk::Real inv_delta_x{mtk::kOne/grid.delta_x()};
00349
00350     int gg_num_rows = nn + 1;
00351     int gg_num_cols = nn + 2;
00352     int elements_per_row = num_bndy_coeffs_;
00353     int num_extra_rows = order_accuracy_/2;
00354
00355     // Output matrix featuring sizes for gradient operators.
00356     mtk::DenseMatrix out(gg_num_rows, gg_num_cols);
00357
00358
00359
00360
00361
00362

```

```

00364     auto ee_index = 0;
00365     for (auto ii = 0; ii < num_extra_rows; ii++) {
00366         auto cc = 0;
00367         for(auto jj = 0 ; jj < gg_num_cols; jj++) {
00368             if(cc >= elements_per_row) {
00369                 out.SetValue(ii, jj, mtk::kZero);
00370             } else {
00371                 out.SetValue(ii, jj,
00372                     gradient_[2*order_accuracy_ + 1 + ee_index++]*inv_delta_x);
00373                 cc++;
00374             }
00375         }
00376     }
00377
00379     for (auto ii = num_extra_rows; ii < gg_num_rows - num_extra_rows; ii++) {
00380         auto jj = ii - num_extra_rows + 1;
00381         for (auto cc = 0; cc < order_accuracy_; cc++, jj++) {
00382             out.SetValue(ii, jj, coeffs_interior_[cc]*inv_delta_x);
00383         }
00384     }
00385
00386     ee_index = 0;
00387
00389     for (auto ii = gg_num_rows - 1; ii >= gg_num_rows - num_extra_rows; ii--) {
00390         auto cc = 0;
00391         for (auto jj = gg_num_cols - 1; jj >= 0; jj--) {
00392             if(cc >= elements_per_row) {
00393                 out.SetValue(ii, jj, mtk::kZero);
00394             } else {
00395                 out.SetValue(ii, jj,
00396                     -gradient_[2*order_accuracy_ + 1 + ee_index++]*inv_delta_x);
00397                 cc++;
00398             }
00399         }
00400     }
00401
00402     return out;
00403 }
00404
00405 bool mtk::Grad1D::ComputeStencilInteriorGrid() {
00406
00407     mtk::Real* pp{}; // Spatial coordinates to create interior stencil.
00408
00409     try {
00410         pp = new mtk::Real[order_accuracy_];
00411     } catch (std::bad_alloc &memory_allocation_exception) {
00412         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00413             std::endl;
00414         std::cerr << memory_allocation_exception.what() << std::endl;
00415     }
00416     memset(pp, mtk::kZero, sizeof(pp[0])*order_accuracy_);
00417
00418     #ifdef MTK_PRECISION_DOUBLE
00419     pp[0] = 1.0/2.0 - ((mtk::Real) order_accuracy_)/2.0;
00420     #else
00421     pp[0] = 1.0f/2.0f - ((mtk::Real) order_accuracy_)/2.0f;
00422     #endif
00423
00424     for (auto ii = 1; ii < order_accuracy_; ++ii) {
00425         pp[ii] = pp[ii - 1] + mtk::kOne;
00426     }
00427
00428     #if MTK_DEBUG_LEVEL > 0
00429     std::cout << "pp =" << std::endl;
00430     for (auto ii = 0; ii < order_accuracy_; ++ii) {
00431         std::cout << std::setw(12) << pp[ii];
00432     }
00433     std::cout << std::endl << std::endl;
00434     #endif
00435
00436     bool transpose{false};
00437
00438     mtk::DenseMatrix vander_matrix(pp, order_accuracy_, order_accuracy_, transpose);
00439
00440     #if MTK_DEBUG_LEVEL > 0
00441     std::cout << "vander_matrix =" << std::endl;
00442     std::cout << vander_matrix << std::endl << std::endl;
00443     #endif

```

```

00449
00451
00452     try {
00453         coeffs_interior_ = new mtk::Real[order_accuracy_];
00454     } catch (std::bad_alloc &memory_allocation_exception) {
00455         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00456             std::endl;
00457         std::cerr << memory_allocation_exception.what() << std::endl;
00458     }
00459     memset(coeffs_interior_, mtk::kZero, sizeof(coeffs_interior_[0])*order_accuracy_);
00460
00461     coeffs_interior_[1] = mtk::kOne;
00462
00463     #if MTK_DEBUG_LEVEL > 0
00464     std::cout << "oo =" << std::endl;
00465     for (auto ii = 0; ii < order_accuracy_; ++ii) {
00466         std::cout << std::setw(12) << coeffs_interior_[ii] << std::endl;
00467     }
00468     std::cout << std::endl;
00469     #endif
00470
00472
00473     int info{mtk::LAPACKAdapter::SolveDenseSystem(vander_matrix,
00474         coeffs_interior_)};
00475
00476     #if MTK_DEBUG_LEVEL > 0
00477     if (!info) {
00478         std::cout << "System solved! Interior stencil attained!" << std::endl;
00479         std::cout << std::endl;
00480     }
00481     else {
00482         std::cerr << "Something wrong solving system! info = " << info << std::endl;
00483         std::cerr << "Exiting..." << std::endl;
00484         return false;
00485     }
00486     #endif
00487
00488     #if MTK_DEBUG_LEVEL > 0
00489     std::cout << "coeffs_interior_ =" << std::endl;
00490     for (auto ii = 0; ii < order_accuracy_; ++ii) {
00491         std::cout << std::setw(12) << coeffs_interior_[ii];
00492     }
00493     std::cout << std::endl << std::endl;
00494     #endif
00495
00496     delete [] pp;
00497     pp = nullptr;
00498
00499     return true;
00500 }
00501
00502 bool mtk::Grad1D::ComputeRationalBasisNullSpace(void) {
00503
00505
00506     mtk::Real* gg{}; // Generator vector for the first Vandermonde matrix.
00507
00508     try {
00509         gg = new mtk::Real[num_bndy_coeffs_];
00510     } catch (std::bad_alloc &memory_allocation_exception) {
00511         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00512             std::endl;
00513         std::cerr << memory_allocation_exception.what() << std::endl;
00514     }
00515     memset(gg, mtk::kZero, sizeof(gg[0])*num_bndy_coeffs_);
00516
00517     #ifdef MTK_PRECISION_DOUBLE
00518     gg[1] = 1.0/2.0;
00519     #else
00520     gg[1] = 1.0f/2.0f;
00521     #endif
00522     for (auto ii = 2; ii < num_bndy_coeffs_; ++ii) {
00523         gg[ii] = gg[ii - 1] + mtk::kOne;
00524     }
00525
00526     #if MTK_DEBUG_LEVEL > 0
00527     std::cout << "gg =" << std::endl;
00528     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
00529         std::cout << std::setw(12) << gg[ii];
00530     }
00531     std::cout << std::endl << std::endl;
00532     #endif

```

```

00533
00535
00536     bool tran{true}; // Should I transpose the Vandermonde matrix.
00537
00538     mtk::DenseMatrix aa_west_t(gg, num_bndy_coeffs_, order_accuracy_ + 1, tran);
00539
00540     #if MTK_DEBUG_LEVEL > 0
00541         std::cout << "aa_west_t =" << std::endl;
00542         std::cout << aa_west_t << std::endl;
00543     #endif
00544
00546
00547     mtk::DenseMatrix qq_t(mtk::LAPACKAdapter::QRFactorDenseMatrix
00548 (aa_west_t));
00549
00549     #if MTK_DEBUG_LEVEL > 0
00550         std::cout << "qq_t = " << std::endl;
00551         std::cout << qq_t << std::endl;
00552     #endif
00553
00555
00556     int kk_num_rows{num_bndy_coeffs_};
00557     int kk_num_cols{dim_null_};
00558
00559     mtk::DenseMatrix kk(kk_num_rows, kk_num_cols);
00560
00561     // In the case of the gradient, even though we must solve for a null-space
00562     // of dimension 2, we must only extract ONE basis for the kernel.
00563     // We perform this extraction here:
00564
00565     int aux_{kk_num_rows - kk_num_cols};
00566     for (auto ii = kk_num_rows - kk_num_cols; ii < kk_num_rows; ii++) {
00567         aux_--;
00568         for (auto jj = 0; jj < kk_num_rows; jj++) {
00569             kk.data()[jj*kk_num_cols + (kk_num_rows - kk_num_cols - aux_ - 1)] =
00570                 qq_t.data()[ii*num_bndy_coeffs_ + jj];
00571         }
00572     }
00573
00574     #if MTK_DEBUG_LEVEL > 0
00575         std::cout << "kk =" << std::endl;
00576         std::cout << kk << std::endl;
00577         std::cout << "kk.num_rows() = " << kk.num_rows() << std::endl;
00578         std::cout << "kk.num_cols() = " << kk.num_cols() << std::endl;
00579         std::cout << std::endl;
00580     #endif
00581
00583
00584     // Scale thus requesting that the last entries of the attained basis for the
00585     // null-space, adopt the pattern we require.
00586     // Essentially we will implement the following MATLAB pseudo-code:
00587     // scalers = kk(num_bndy_approxs - (dim_null - 1):num_bndy_approxs,:)\B
00588     // SK = kk*scalers
00589     // where SK is the scaled null-space.
00590
00591     // In this point, we almost have all the data we need correctly allocated
00592     // in memory. We will create the matrix iden_, and elements we wish to scale in
00593     // the kk array. Using the concept of the leading dimension, we could just
00594     // use kk, with the correct leading dimension and that is it. BUT I DO NOT
00595     // GET how does it work. So I will just create a matrix with the content of
00596     // this array that we need, solve for the scalers and then scale the
00597     // whole kk:
00598
00599     // We will then create memory for that sub-matrix of kk (subk).
00600
00601     mtk::DenseMatrix subk(dim_null_, dim_null_);
00602
00603     auto zz = 0;
00604     for (auto ii = order_accuracy_ + 1; ii < num_bndy_coeffs_; ii++) {
00605         for (auto jj = 0; jj < dim_null_; jj++) {
00606             subk.data()[zz*(dim_null_) + jj] = kk.data()[ii*(dim_null_) + jj];
00607         }
00608         zz++;
00609     }
00610
00611     #if MTK_DEBUG_LEVEL > 0
00612         std::cout << "subk =" << std::endl;
00613         std::cout << subk << std::endl;
00614     #endif
00615
00616     subk.Transpose();

```

```

00617
00618 #if MTK_DEBUG_LEVEL > 0
00619 std::cout << "subk_t =" << std::endl;
00620 std::cout << subk << std::endl;
00621 #endif
00622
00623 bool padded{false};
00624 tran = false;
00625
00626 mtk::DenseMatrix iden(dim_null_, padded, tran);
00627
00628 #if MTK_DEBUG_LEVEL > 0
00629 std::cout << "iden =" << std::endl;
00630 std::cout << iden << std::endl;
00631 #endif
00632
00633 // Solve the system to compute the scalars.
00634 // An example of the system to solve, for k = 8, is:
00635 //
00636 // subk*scalars = iden or
00637 //
00638 // | 0.386018 -0.0339244 -0.129478 | | 1 0 0 |
00639 // | -0.119774 0.0199423 0.0558632 |*scalars = | 0 1 0 |
00640 // | 0.0155708 -0.00349546 -0.00853182 | | 0 0 1 |
00641 //
00642 // Notice this is a nrhs = 3 system.
00643 // Noteworthy: we do NOT ACTUALLY ALLOCATE space for the scalars... they
00644 // will be stored in the created identity matrix.
00645 // Let us first transpose subk (because of LAPACK):
00646
00647 int info{mtk::LAPACKAdapter::SolveDenseSystem(subk, iden)};
00648
00649 #if MTK_DEBUG_LEVEL > 0
00650 if (!info) {
00651     std::cout << "System successfully solved!" <<
00652         std::endl;
00653 } else {
00654     std::cerr << "Something went wrong solving system! info = " << info <<
00655         std::endl;
00656     std::cerr << "Exiting..." << std::endl;
00657     return false;
00658 }
00659 std::cout << std::endl;
00660 #endif
00661
00662 #if MTK_DEBUG_LEVEL > 0
00663 std::cout << "Computed scalars:" << std::endl;
00664 std::cout << iden << std::endl;
00665 #endif
00666
00667 // Multiply the two matrices to attain a scaled basis for null-space.
00668
00669 rat_basis_null_space_ = mtk::BLASAdapter::RealDenseMM(kk, iden);
00670
00671 #if MTK_DEBUG_LEVEL > 0
00672 std::cout << "Rational basis for the null-space:" << std::endl;
00673 std::cout << rat_basis_null_space_ << std::endl;
00674 #endif
00675
00676 // At this point, we have a rational basis for the null-space, with the
00677 // pattern we need! :)
00678
00679 delete [] gg;
00680 gg = nullptr;
00681
00682 return true;
00683 }
00684
00685 bool mtk::Grad1D::ComputePreliminaryApproximations() {
00686
00687
00688     mtk::Real *gg{}; // Generator vector for the first approximation.
00689
00690     try {
00691         gg = new mtk::Real[num_bndy_coeffs_];
00692     } catch (std::bad_alloc &memory_allocation_exception) {
00693         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00694             std::endl;
00695         std::cerr << memory_allocation_exception.what() << std::endl;
00696     }
00697     memset(gg, mtk::kZero, sizeof(gg[0])*num_bndy_coeffs_);

```

```

00699
00700 #ifdef MTK_PRECISION_DOUBLE
00701 gg[1] = 1.0/2.0;
00702 #else
00703 gg[1] = 1.0f/2.0f;
00704 #endif
00705 for (auto ii = 2; ii < num_bndy_coeffs_; ++ii) {
00706     gg[ii] = gg[ii - 1] + mtk::kOne;
00707 }
00708
00709 #if MTK_DEBUG_LEVEL > 0
00710 std::cout << "gg0 =" << std::endl;
00711 for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
00712     std::cout << std::setw(12) << gg[ii];
00713 }
00714 std::cout << std::endl << std::endl;
00715 #endif
00716
00717 // Allocate 2D array to store the collection of preliminary approximations.
00718 try {
00719     prem_apps_ = new mtk::Real[num_bndy_coeffs_*num_bndy_approxs_];
00720 } catch (std::bad_alloc &memory_allocation_exception) {
00721     std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00722 std::endl;
00723     std::cerr << memory_allocation_exception.what() << std::endl;
00724 }
00725 memset(prem_apps_,
00726         mtk::kZero,
00727         sizeof(prem_apps_[0])*num_bndy_coeffs_*num_bndy_approxs_);
00728
00729 for (auto ll = 0; ll < num_bndy_approxs_; ++ll) {
00730
00731     // Re-check new generator vector for every iteration except for the first.
00732     #if MTK_DEBUG_LEVEL > 0
00733     if (ll > 0) {
00734         std::cout << "gg" << ll << " =" << std::endl;
00735         for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
00736             std::cout << std::setw(12) << gg[ii];
00737         }
00738         std::cout << std::endl << std::endl;
00739     }
00740     #endif
00741
00742     bool transpose{false};
00743
00744     mtk::DenseMatrix aa(gg,
00745                         num_bndy_coeffs_, order_accuracy_ + 1,
00746                         transpose);
00747
00748     #if MTK_DEBUG_LEVEL > 0
00749     std::cout << "aa_" << ll << " =" << std::endl;
00750     std::cout << aa << std::endl;
00751     #endif
00752
00753     mtk::Real *ob{};
00754
00755     auto ob_ld = num_bndy_coeffs_;
00756
00757     try {
00758         ob = new mtk::Real[ob_ld];
00759     } catch (std::bad_alloc &memory_allocation_exception) {
00760         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00761 std::endl;
00762         std::cerr << memory_allocation_exception.what() << std::endl;
00763     }
00764     memset(ob, mtk::kZero, sizeof(ob[0])*ob_ld);
00765
00766     ob[1] = mtk::kOne;
00767
00768     #if MTK_DEBUG_LEVEL > 0
00769     std::cout << "ob =" << std::endl << std::endl;
00770     for (auto ii = 0; ii < ob_ld; ++ii) {
00771         std::cout << std::setw(12) << ob[ii] << std::endl;
00772     }
00773     std::cout << std::endl;
00774     #endif
00775
00776
00777
00778
00779
00780
00781
00782
00783

```

```

00784 // However, this is an under-determined system of equations. So we can not
00785 // use the same LAPACK routine (dgesv_). We will instead use dgels_, through
00786 // our LAPACKAdapter class.
00787
00788 int info_{
00789     mtk::LAPACKAdapter::SolveRectangularDenseSystem(aa, ob
, ob_ld)};
00790
00791 #if MTK_DEBUG_LEVEL > 0
00792 if (!info_) {
00793     std::cout << "System successfully solved!" << std::endl << std::endl;
00794 } else {
00795     std::cerr << "Error solving system! info = " << info_ << std::endl;
00796 }
00797 #endif
00798
00799 #if MTK_DEBUG_LEVEL > 0
00800 std::cout << "ob =" << std::endl;
00801 for (auto ii = 0; ii < ob_ld; ++ii) {
00802     std::cout << std::setw(12) << ob[ii] << std::endl;
00803 }
00804 std::cout << std::endl;
00805 #endif
00806
00808 // This implies a DAXPY operation. However, we must construct the arguments
00809 // for this operation.
00810
00811 // Save them into the ob_bottom array:
00812
00813 Real *ob_bottom{}; // Bottom part of the attained kernel used to scale it.
00814
00815 try {
00816     ob_bottom = new mtk::Real[dim_null_];
00817 } catch (std::bad_alloc &memory_allocation_exception) {
00818     std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
std::endl;
00819     std::cerr << memory_allocation_exception.what() << std::endl;
00820 }
00821 memset(ob_bottom, mtk::kZero, sizeof(ob_bottom[0])*dim_null_);
00822
00823 for (auto ii = 0; ii < dim_null_; ++ii) {
00824     ob_bottom[(dim_null_ - 1) - ii] = ob[num_bndy_coeffs_ - ii - 1];
00825 }
00826
00827 #if MTK_DEBUG_LEVEL > 0
00828 std::cout << "ob_bottom =" << std::endl;
00829 for (auto ii = 0; ii < dim_null_; ++ii) {
00830     std::cout << std::setw(12) << ob_bottom[ii] << std::endl;
00831 }
00832 std::cout << std::endl;
00833 #endif
00834
00835 // We must computed an scaled ob, sob, using the scaled null-space in
00836 // rat_basis_null_space_.
00837 // Such operation is: sob = ob - rat_basis_null_space_*ob_bottom
00838 // or:                      ob = -1.0*rat_basis_null_space_*ob_bottom + 1.0*ob
00839 // thus:                      Y =      a*A      *x      +      b*Y (DAXPY).
00840
00841 #if MTK_DEBUG_LEVEL > 0
00842 std::cout << "Rational basis for the null-space:" << std::endl;
00843 std::cout << rat_basis_null_space_ << std::endl;
00844 #endif
00845
00846 mtk::Real alpha{-mtk::kOne};
00847 mtk::Real beta{mtk::kOne};
00848
00849 mtk::BLASAdapter::RealDenseMV(alpha, rat_basis_null_space_,
                                ob_bottom, beta, ob);
00850
00851 #if MTK_DEBUG_LEVEL > 0
00852 std::cout << "scaled ob:" << std::endl;
00853 for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
00854     std::cout << std::setw(12) << ob[ii] << std::endl;
00855 }
00856 std::cout << std::endl;
00857 #endif
00858
00859 // We save the recently scaled solution, into an array containing these.
00860 // We can NOT start building the pi matrix, simply because I want that part

```



```

00867     // to be separated since its construction depends on the algorithm we want
00868     // to implement.
00869
00870     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
00871         prem_apps_[ii*num_bndy_approxs_ + 11] = ob[ii];
00872     }
00873
00874     // After the first iteration, simply shift the entries of the last
00875     // generator vector used:
00876     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
00877         gg[ii]--;
00878     }
00879
00880     // Garbage collection for this loop:
00881     delete[] ob;
00882     ob = nullptr;
00883
00884     delete[] ob_bottom;
00885     ob_bottom = nullptr;
00886 } // End of: for (ll = 0; ll < dim_null; ll++);
00887
00888 #if MTK_DEBUG_LEVEL > 0
00889 std::cout << "Matrix post-scaled preliminary apps: " << std::endl;
00890 for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
00891     for (auto jj = 0; jj < num_bndy_approxs_; ++jj) {
00892         std::cout << std::setw(12) << prem_apps_[ii*num_bndy_approxs_ + jj];
00893     }
00894     std::cout << std::endl;
00895 }
00896 std::cout << std::endl;
00897 #endif
00898
00899 delete[] gg;
00900 gg = nullptr;
00901
00902 return true;
00903 }
00904
00905 bool mtk::Grad1D::ComputeWeights() {
00906
00907     // Matrix to compute the weights as in the CRSA.
00908     mtk::DenseMatrix pi(num_bndy_coeffs_, num_bndy_coeffs_ - 1);
00909
00910
00911     // Assemble the pi matrix using:
00912     // 1. The collection of scaled preliminary approximations.
00913     // 2. The collection of coefficients approximating at the interior.
00914     // 3. The scaled basis for the null-space.
00915
00916     // 1.1. Process array of scaled preliminary approximations.
00917
00918     // These are queued in scaled_solutions. Each one of these, will be a column
00919     // of the pi matrix:
00920     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
00921         for (auto jj = 0; jj < num_bndy_approxs_; ++jj) {
00922             pi.data()[ii*(2*(num_bndy_approxs_ - 1) + (order_accuracy_/2 + 1)) + jj] =
00923                 prem_apps_[ii*num_bndy_approxs_ + jj];
00924         }
00925     }
00926
00927
00928     // 1.2. Add columns from known stencil approximating at the interior.
00929
00930     // However, these must be padded by zeros, according to their position in the
00931     // final pi matrix:
00932     auto mm = 1;
00933     for (auto jj = num_bndy_approxs_; jj < order_accuracy_; ++jj) {
00934         for (auto ii = 0; ii < order_accuracy_; ++ii) {
00935             auto de = (ii + mm)*(2*(num_bndy_approxs_ - 1) +
00936                 (order_accuracy_/2 + 1)) + jj;
00937             pi.data()[de] = coeffs_interior_[ii];
00938         }
00939         ++mm;
00940     }
00941
00942     rat_basis_null_space_.OrderColMajor();
00943
00944     #if MTK_DEBUG_LEVEL > 0
00945     std::cout << "Rational basis for the null-space (col. major):" << std::endl;
00946     std::cout << rat_basis_null_space_ << std::endl;
00947     #endif
00948

```

```

00949 // 1.3. Add final set of columns: rational basis for null-space.
00950 for (auto jj = dim_null_ + (order_accuracy_/2 + 1);
00951      jj < num_bndy_coeffs_ - 1; ++jj) {
00952     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
00953         auto og =
00954             (jj - (dim_null_ + (order_accuracy_/2 + 1)))*num_bndy_coeffs_ + ii;
00955         auto de = ii*(2*dim_null_ + (order_accuracy_/2 + 1)) + jj;
00956         pi.data()[de] = rat_basis_null_space_.data()[og];
00957     }
00958 }
00959
00960 #if MTK_DEBUG_LEVEL > 0
00961 std::cout << "coeffs_interior_ =" << std::endl;
00962 for (auto ii = 0; ii < order_accuracy_; ++ii) {
00963     std::cout << std::setw(12) << coeffs_interior_[ii];
00964 }
00965 std::cout << std::endl << std::endl;
00966 #endif
00967
00968 #if MTK_DEBUG_LEVEL > 0
00969 std::cout << "Constructed pi matrix for CRS Algorithm: " << std::endl;
00970 std::cout << pi << std::endl;
00971 #endif
00972
00973 // This imposes the mimetic condition.
00974
00975 mtk::Real *hh{}; // Right-hand side to compute weights in the C(R,B)SA.
00976
00977 try {
00978     hh = new mtk::Real[num_bndy_coeffs_];
00979 } catch (std::bad_alloc &memory_allocation_exception) {
00980     std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00981         std::endl;
00982     std::cerr << memory_allocation_exception.what() << std::endl;
00983 }
00984 memset(hh, mtk::kZero, sizeof(hh[0])*num_bndy_coeffs_);
00985
00986 hh[0] = -mtk::kOne;
00987 for (auto ii = (order_accuracy_/2 + 2 - 1); ii < num_bndy_coeffs_; ++ii) {
00988     auto aux_xx = mtk::kZero;
00989     for (auto jj = 0; jj < ((ii - (order_accuracy_/2 - 1)) - 1); ++jj) {
00990         aux_xx += coeffs_interior_[jj];
00991     }
00992     hh[ii] = -mtk::kOne*aux_xx;
00993 }
00994
00995 // That is, we construct a system, to solve for the weights.
00996
00997 // Once again we face the challenge of solving with LAPACK. However, for the
00998 // CRSA, this matrix PI is over-determined, since it has more rows than
00999 // unknowns. However, according to the theory, the solution to this system is
01000 // unique. We will use dgels_.
01001
01002 try {
01003     weights_cbs_ = new mtk::Real[num_bndy_coeffs_];
01004 } catch (std::bad_alloc &memory_allocation_exception) {
01005     std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
01006         std::endl;
01007     std::cerr << memory_allocation_exception.what() << std::endl;
01008 }
01009 memset(weights_cbs_, mtk::kZero, sizeof(weights_cbs_[0])*num_bndy_coeffs_);
01010
01011 int weights_ld{pi.num_cols() + 1};
01012
01013 // Preserve hh.
01014 std::copy(hh, hh + weights_ld, weights_cbs_);
01015
01016 pi.Transpose();
01017
01018 int info{
01019     mtk::LAPACKAdapter::SolveRectangularDenseSystem(pi,
01020         weights_cbs_, weights_ld)
01021 };
01022
01023 #if MTK_DEBUG_LEVEL > 0
01024 if (!info) {
01025     std::cout << "System successfully solved!" << std::endl << std::endl;
01026 } else {
01027     std::cerr << "Error solving system! info = " << info << std::endl;
01028 }
01029 #endif

```

```

01032     }
01033     #endif
01034
01035     #if MTK_DEBUG_LEVEL > 0
01036     std::cout << "hh =" << std::endl;
01037     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
01038         std::cout << std::setw(11) << hh[ii] << std::endl;
01039     }
01040     std::cout << std::endl;
01041     #endif
01042
01043     // Preserve the original weights for research.
01044
01045     try {
01046         weights_crs_ = new mtk::Real[num_bndy_coeffs_];
01047     } catch (std::bad_alloc &memory_allocation_exception) {
01048         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
01049             std::endl;
01050         std::cerr << memory_allocation_exception.what() << std::endl;
01051     }
01052     memset(weights_crs_, mtk::kZero, sizeof(weights_crs_[0])*num_bndy_coeffs_);
01053
01054     std::copy(weights_cbs_, weights_cbs_ + (weights_ld - 1), weights_crs_);
01055
01056     #if MTK_DEBUG_LEVEL > 0
01057     std::cout << "weights_CRSA + lambda =" << std::endl;
01058     for (auto ii = 0; ii < weights_ld - 1; ++ii) {
01059         std::cout << std::setw(12) << weights_crs_[ii] << std::endl;
01060     }
01061     std::cout << std::endl;
01062     #endif
01063
01064     if (order_accuracy_ >= mtk::kCriticalOrderAccuracyGrad) {
01065         int minrow{std::numeric_limits<int>::infinity()};
01066
01067         mtk::Real norm{mtk::BLASAdapter::RealNRM2(weights_cbs_,
01068             order_accuracy_)};
01069         mtk::Real minnorm{std::numeric_limits<mtk::Real>::infinity()};
01070
01071
01072         mtk::DenseMatrix phi(order_accuracy_ + 1, order_accuracy_);
01073
01074         // 6.1. Insert preliminary approximations to first set of columns.
01075
01076         for (auto ii = 0; ii < order_accuracy_ + 1; ++ii) {
01077             for (auto jj = 0; jj < num_bndy_approxs_; ++jj) {
01078                 phi.data()[ii*(order_accuracy_ + 1) + jj] =
01079                     prem_apps_[ii*num_bndy_approxs_ + jj];
01080             }
01081         }
01082
01083         // 6.2. Skip a column and negate preliminary approximations.
01084
01085         for (auto jj = 0; jj < order_accuracy_ + 1; jj++) {
01086             for (auto ii = 1; ii < num_bndy_approxs_; ii++) {
01087                 auto de = (ii + order_accuracy_ - num_bndy_approxs_ + jj*order_accuracy_);
01088                 auto og = (num_bndy_approxs_ - ii + (jj)*num_bndy_approxs_);
01089                 phi.data()[de] = -pre_apps_[og];
01090             }
01091         }
01092
01093         // 6.3. Flip negative columns up-down.
01094
01095         for (auto ii = 0; ii < order_accuracy_/2; ii++) {
01096             for (auto jj = num_bndy_approxs_ + 1; jj < order_accuracy_; jj++) {
01097                 auto aux = phi.data()[ii*order_accuracy_ + jj];
01098                 phi.data()[ii*order_accuracy_ + jj] =
01099                     phi.data()[ (order_accuracy_ - ii)*order_accuracy_ + jj];
01100                 phi.data()[ (order_accuracy_ - ii)*order_accuracy_ + jj] = aux;
01101             }
01102         }
01103
01104         // 6.4. Insert stencil.
01105
01106         auto mm = 0;
01107         for (auto jj = num_bndy_approxs_; jj < num_bndy_approxs_ + 1; jj++) {
01108             for (auto ii = 0; ii < order_accuracy_ + 1; ii++) {
01109                 if (ii == 0) {
01110                     phi.data()[jj] = 0.0;
01111                 } else {

```

```

01114         phi.data()[(ii + mm)*order_accuracy_ + jj] = coeffs_interior_[(ii - 1)];
01115     }
01116 }
01117 mm++;
01118 }
01119
01120 #if MTK_DEBUG_LEVEL > 0
01121 std::cout << "phi =" << std::endl;
01122 std::cout << phi << std::endl;
01123 #endif
01124
01126
01127 mtk::Real *lamed{}; // Used to build big lambda.
01128
01129 try {
01130     lamed = new mtk::Real[num_bndy_approxs_ - 1];
01131 } catch (std::bad_alloc &memory_allocation_exception) {
01132     std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
01133         std::endl;
01134     std::cerr << memory_allocation_exception.what() << std::endl;
01135 }
01136 memset(lamed, mtk::kZero, sizeof(lamed[0])*(num_bndy_approxs_ - 1));
01137
01138 for (auto ii = 0; ii < num_bndy_approxs_ - 1; ++ii) {
01139     lamed[ii] = hh[ii + order_accuracy_ + 1] ;
01140 }
01141
01142 #if MTK_DEBUG_LEVEL > 0
01143 std::cout << "lamed =" << std::endl;
01144 for (auto ii = 0; ii < num_bndy_approxs_ - 1; ++ii) {
01145     std::cout << std::setw(12) << lamed[ii] << std::endl;
01146 }
01147 std::cout << std::endl;
01148 #endif
01149
01150 for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
01151     mtk::Real temp = mtk::kZero;
01152     for (auto jj = 0; jj < num_bndy_approxs_ - 1; ++jj) {
01153         temp = temp +
01154             lamed[jj]*rat_basis_null_space_.data()[jj*num_bndy_coeffs_ + ii];
01155     }
01156     hh[ii] = hh[ii] - temp;
01157 }
01158
01159 #if MTK_DEBUG_LEVEL > 0
01160 std::cout << "big_lambda =" << std::endl;
01161 for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
01162     std::cout << std::setw(12) << hh[ii] << std::endl;
01163 }
01164 std::cout << std::endl;
01165 #endif
01166
01168
01169 int copy_result{}; // Should I replace the solution... not for now.
01170
01171 mtk::Real normerr_; // Norm of the error for the solution on each row.
01172
01173 for (auto row_ = 0; row_ < order_accuracy_ + 1; ++row_) {
01174     normerr_ = mtk::GLPKAdapter::SolveSimplexAndCompare(phi.
data(),
01175                                     order_accuracy_ + 1,
01176                                     order_accuracy_,
01177                                     order_accuracy_,
01178                                     hh,
01179                                     weights_cbs_,
01180                                     row_,
01181                                     mimetic_threshold_,
01182                                     copy_result);
01183     mtk::Real aux(normerr_/norm);
01184
01185     #if MTK_DEBUG_LEVEL>0
01186     std::cout << "Relative norm: " << aux << " " << std::endl;
01187     std::cout << std::endl;
01188     #endif
01189
01190     if (aux < minnorm) {
01191         minnorm = aux;
01192         minrow_ = row_;
01193     }
01194 }
01195

```

```

01196     #if MTK_DEBUG_LEVEL > 0
01197     std::cout << "weights_CBSA + lambda (after brute force search):" <<
01198     std::endl;
01199     for (auto ii = 0; ii < num_bndy_coeffs_ - 1; ++ii) {
01200         std::cout << std::setw(12) << weights_cbs_[ii] << std::endl;
01201     }
01202     std::cout << std::endl;
01203     #endif
01204
01206
01207     // After we know which row yields the smallest relative norm that row is
01208     // chosen to be the objective function and the result of the optimizer is
01209     // chosen to be the new weights_.
01210
01211     #if MTK_DEBUG_LEVEL > 0
01212     std::cout << "Minimum Relative Norm " << minnorm << " found at row " <<
01213     minrow_ + 1 << std::endl;
01214     std::cout << std::endl;
01215     #endif
01216
01217     copy_result = 1;
01218     normerr_ = mtk::GLPKAdapter::SolveSimplexAndCompare(phi.
data(),
01219                                     order_accuracy_ + 1,
01220                                     order_accuracy_,
01221                                     order_accuracy_,
01222                                     hh,
01223                                     weights_cbs_,
01224                                     minrow_,
01225                                     mimetic_threshold_,
01226                                     copy_result);
01227     mtk::Real aux_{normerr_/norm};
01228     #if MTK_DEBUG_LEVEL > 0
01229     std::cout << "Relative norm: " << aux_ << std::endl;
01230     std::cout << std::endl;
01231     #endif
01232
01233     delete [] lamed;
01234     lamed = nullptr;
01235 }
01236
01237 delete [] hh;
01238 hh = nullptr;
01239
01240 return true;
01241 }
01242
01243 bool mtk::Grad1D::ComputeStencilBoundaryGrid(void) {
01244
01245     #if MTK_DEBUG_LEVEL > 0
01246     std::cout << "weights_* + lambda =" << std::endl;
01247     for (auto ii = 0; ii < num_bndy_coeffs_ - 1; ++ii) {
01248         std::cout << std::setw(12) << weights_cbs_[ii] << std::endl;
01249     }
01250     std::cout << std::endl;
01251     #endif
01252
01254
01255     mtk::Real *lambda{}; // Collection of bottom values from weights_.
01256
01257     try {
01258         lambda = new mtk::Real[dim_null_];
01259     } catch (std::bad_alloc &memory_allocation_exception) {
01260         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
01261         std::endl;
01262         std::cerr << memory_allocation_exception.what() << std::endl;
01263     }
01264     memset(lambda, mtk::kZero, sizeof(lambda[0])*dim_null_);
01265
01266     for (auto ii = 0; ii < dim_null_; ++ii) {
01267         lambda[ii] = weights_cbs_[order_accuracy_ + ii];
01268     }
01269
01270     #if MTK_DEBUG_LEVEL > 0
01271     std::cout << "lambda =" << std::endl;
01272     for (auto ii = 0; ii < dim_null_; ++ii) {
01273         std::cout << std::setw(12) << lambda[ii] << std::endl;
01274     }
01275     std::cout << std::endl;
01276     #endif
01277

```

```

01279
01280 mtk::Real *alpha{}; // Collection of alpha values.
01281
01282 try {
01283     alpha = new mtk::Real[dim_null_];
01284 } catch (std::bad_alloc &memory_allocation_exception) {
01285     std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
01286     std::endl;
01287     std::cerr << memory_allocation_exception.what() << std::endl;
01288 }
01289 memset(alpha, mtk::kZero, sizeof(alpha[0])*dim_null_);
01290
01291 for (auto ii = 0; ii < dim_null_; ++ii) {
01292     alpha[ii] = lambda[ii]/weights_cbs_[ii] ;
01293 }
01294
01295 #if MTK_DEBUG_LEVEL > 0
01296 std::cout << "alpha =" << std::endl;
01297 for (auto ii = 0; ii < dim_null_; ++ii) {
01298     std::cout << std::setw(12) << alpha[ii] << std::endl;
01299 }
01300 std::cout << std::endl;
01301 #endif
01302
01303 try {
01304     mim_bndy_ = new mtk::Real[num_bndy_coeffs_*num_bndy_approxs_];
01305 } catch (std::bad_alloc &memory_allocation_exception) {
01306     std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
01307     std::endl;
01308     std::cerr << memory_allocation_exception.what() << std::endl;
01309 }
01310 memset(mim_bndy_,
01311     mtk::kZero,
01312     sizeof(mim_bndy_[0])*num_bndy_coeffs_*num_bndy_approxs_);
01313
01314 for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
01315     for (auto jj = 0; jj < (num_bndy_approxs_ - 1); ++jj) {
01316         mim_bndy_[ii*num_bndy_approxs_ + jj] =
01317         prem_apps_[ii*num_bndy_approxs_ + jj] +
01318         alpha[jj]*rat_basis_null_space_.data()[jj*num_bndy_coeffs_ + ii];
01319     }
01320 }
01321
01322 for(auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
01323     mim_bndy_[ii*num_bndy_approxs_ + (num_bndy_approxs_ - 1)] =
01324     prem_apps_[ii*num_bndy_approxs_ + (num_bndy_approxs_ - 1)];
01325 }
01326
01327 #if MTK_DEBUG_LEVEL > 0
01328 std::cout << "Collection of mimetic approximations:" << std::endl;
01329 for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
01330     for (auto jj = 0; jj < num_bndy_approxs_; ++jj) {
01331         std::cout << std::setw(13) << mim_bndy_[ii*num_bndy_approxs_ + jj];
01332     }
01333     std::cout << std::endl;
01334 }
01335 std::cout << std::endl;
01336 #endif
01337 delete[] lambda;
01338 lambda = nullptr;
01339
01340 delete[] alpha;
01341 alpha = nullptr;
01342
01343 return true;
01344 }
01345
01346 bool mtk::Grad1D::AssembleOperator(void) {
01347
01348     // The output array will have this form:
01349     // 1. The first entry of the array will contain the used order kk.
01350     // 2. The second entry of the array will contain the collection of
01351     // approximating coefficients for the interior of the grid.
01352     // 3. The third entry will contain a collection of weights.
01353     // 4. The next dim_null - 1 entries will contain the collections of
01354     // approximating coefficients for the west boundary of the grid.
01355
01356     gradient_length_ = 1 + order_accuracy_ + order_accuracy_ +
01357     num_bndy_approxs_*num_bndy_coeffs_;

```

```

01361
01362     #if MTK_DEBUG_LEVEL > 0
01363     std::cout << "gradient_length_ = " << gradient_length_ << std::endl;
01364     #endif
01365
01366     try {
01367         gradient_ = new mtk::Real[gradient_length_];
01368     } catch (std::bad_alloc &memory_allocation_exception) {
01369         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
01370             std::endl;
01371         std::cerr << memory_allocation_exception.what() << std::endl;
01372     }
01373     memset(gradient_, mtk::kZero, sizeof(gradient_[0])*gradient_length_);
01374
01375
01376
01377     gradient_[0] = order_accuracy_;
01378
01379
01380
01381     for (auto ii = 0; ii < order_accuracy_; ++ii) {
01382         gradient_[ii + 1] = coeffs_interior_[ii];
01383     }
01384
01385
01386
01387     for (auto ii = 0; ii < order_accuracy_; ++ii) {
01388         gradient_[(order_accuracy_ + 1) + ii] = weights_cbs_[ii];
01389     }
01390
01391
01392
01393
01394     int offset{2*order_accuracy_ + 1};
01395
01396
01397     int aux {}; // Auxiliary variable.
01398
01399     if (order_accuracy_ > mtk::kDefaultOrderAccuracy) {
01400         for (auto ii = 0; ii < num_bndy_approxs_ ; ii++) {
01401             for (auto jj = 0; jj < num_bndy_coeffs_ ; jj++) {
01402                 gradient_[offset + aux] = mim_bndy_[jj*num_bndy_approxs_ + ii];
01403                 aux++;
01404             }
01405         }
01406     } else {
01407         gradient_[offset + 0] = prem_apps_[0];
01408         gradient_[offset + 1] = prem_apps_[1];
01409         gradient_[offset + 2] = prem_apps_[2];
01410     }
01411
01412     #if MTK_DEBUG_LEVEL > 0
01413     std::cout << "1D " << order_accuracy_ << "-order grad built!" << std::endl;
01414     std::cout << std::endl;
01415     #endif
01416
01417     return true;
01418 }

```

17.45 src/mtk_lap_1d.cc File Reference


Includes the implementation of the class Lap1D.

```

#include <cstdlib>
#include <stdio>
#include <cstring>
#include <iostream>
#include <iomanip>
#include "mtk_roots.h"
#include "mtk_tools.h"
#include "mtk_blas_adapter.h"
#include "mtk_grad_1d.h"
#include "mtk_div_1d.h"
#include "mtk_lap_1d.h"

```

Include dependency graph for `mtk_lap_1d.cc`:



Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

Functions

- `std::ostream & mtk::operator<< (std::ostream &stream, mtk::Lap1D &in)`

17.45.1 Detailed Description

This class implements a 1D Laplacian operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (CBSA).

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_lap_1d.cc](#).

17.46 mtk_lap_1d.cc

```

00001
00011 /*
00012 Copyright (C) 2015, Computational Science Research Center, San Diego State
00013 University. All rights reserved.
00014
00015 Redistribution and use in source and binary forms, with or without modification,
00016 are permitted provided that the following conditions are met:
00017
00018 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00019 and a copy of the modified files should be reported once modifications are
00020 completed. Documentation related to said modifications should be included.
00021
00022 2. Redistributions of source code must be done through direct
00023 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00024
00025 3. Redistributions of source code must retain the above copyright notice, this
00026 list of conditions and the following disclaimer.
00027
00028 4. Redistributions in binary form must reproduce the above copyright notice,
00029 this list of conditions and the following disclaimer in the documentation and/or
00030 other materials provided with the distribution.
00031

```



```

00032 5. Usage of the binary form on proprietary applications shall require explicit
00033 prior written permission from the the copyright holders.
00034
00035 6. Neither the name of the copyright holder nor the names of its contributors
00036 may be used to endorse or promote products derived from this software without
00037 specific prior written permission.
00038
00039 The copyright holders provide no reassurances that the source code provided does
00040 not infringe any patent, copyright, or any other intellectual property rights of
00041 third parties. The copyright holders disclaim any liability to any recipient for
00042 claims brought against recipient by any third party for infringement of that
00043 parties intellectual property rights.
00044
00045 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00046 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00047 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00048 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00049 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00050 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00051 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00052 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00053 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00054 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00055 */
00056
00057 #include <cstdlib>
00058 #include <cstdio>
00059 #include <cstring>
00060
00061 #include <iostream>
00062 #include <iomanip>
00063
00064 #include "mtk_roots.h"
00065 #include "mtk_tools.h"
00066 #include "mtk_blas_adapter.h"
00067 #include "mtk_grad_1d.h"
00068 #include "mtk_div_1d.h"
00069 #include "mtk_lap_1d.h"
00070
00071 namespace mtk {
00072
00073 std::ostream& operator <<(std::ostream &stream, mtk::Lap1D &in) {
00074
00075     stream << "laplacian_[0] = " << in.laplacian_[0] << std::endl << std::endl;
00076
00077     stream << "laplacian_[1:" << 2*in.order_accuracy_ - 1 << "]" = " <<
00078         std::endl << std::endl;
00079     for (auto ii = 1; ii <= (2*in.order_accuracy_ - 1); ++ii) {
00080         stream << std::setw(13) << in.laplacian_[ii] << " ";
00081     }
00082     stream << std::endl << std::endl;
00083
00084     auto offset = 1 + (2*in.order_accuracy_ - 1);
00085
00086     stream << "laplacian_[ " << offset << ":" << offset +
00087         (in.order_accuracy_ - 1)*(2*in.order_accuracy_ - 1) << "]" = " <<
00088         std::endl << std::endl;
00089
00090     for (auto ii = 0; ii < in.order_accuracy_ - 1; ++ii) {
00091         for (auto jj = 0; jj < 2*in.order_accuracy_; ++jj) {
00092             stream << std::setw(13) <<
00093                 in.laplacian_[offset + ii*(2*in.order_accuracy_) + jj];
00094         }
00095         stream << std::endl;
00096     }
00097     return stream;
00098 }
00099
00100 mtk::Lap1D::Lap1D() :
00101     order_accuracy_(mtk::kDefaultOrderAccuracy),
00102     laplacian_length_(),
00103     mimetic_threshold_(mtk::kDefaultMimeticThreshold) {}
00104
00105 mtk::Lap1D::~Lap1D() {
00106     delete [] laplacian_;

```

```

00116     laplacian_ = nullptr;
00117 }
00118
00119 bool mtk::LaplD::ConstructLaplD(int order_accuracy,
00120                                mtk::Real mimetic_threshold) {
00121
00122     #if MTK_DEBUG_LEVEL > 0
00123     mtk::Tools::Prevent(order_accuracy < 2, __FILE__, __LINE__, __func__);
00124     mtk::Tools::Prevent((order_accuracy%2) != 0, __FILE__, __LINE__, __func__);
00125     mtk::Tools::Prevent(mimetic_threshold <= mtk::kZero,
00126                         __FILE__, __LINE__, __func__);
00127
00128     if (order_accuracy >= mtk::kCriticalOrderAccuracyDiv) {
00129         std::cout << "WARNING: Numerical accuracy is high." << std::endl;
00130     }
00131
00132     std::cout << "order_accuracy_ = " << order_accuracy << std::endl;
00133     std::cout << "mimetic_threshold_ = " << mimetic_threshold << std::endl;
00134     #endif
00135
00136     order_accuracy_ = order_accuracy;
00137     mimetic_threshold_ = mimetic_threshold;
00138
00139
00140
00141     mtk::Grad1D grad; // Mimetic gradient.
00142
00143     bool info = grad.ConstructGrad1D(order_accuracy_, mimetic_threshold_);
00144
00145     if (!info) {
00146         std::cerr << "Mimetic grad could not be built." << std::endl;
00147         return false;
00148     }
00149
00150
00151     mtk::Div1D div; // Mimetic divergence.
00152
00153     info = div.ConstructDiv1D(order_accuracy_, mimetic_threshold_);
00154
00155     if (!info) {
00156         std::cerr << "Mimetic div could not be built." << std::endl;
00157         return false;
00158     }
00159
00160
00161
00162
00163     // Since these are mimetic operator, we must multiply the matrices arising
00164     // from both the divergence and the Laplacian, in order to get the
00165     // approximating coefficients for the Laplacian operator.
00166
00167     // However, we must choose a grid that implied a step size of 1, so to get
00168     // the approximating coefficients, without being affected from the
00169     // normalization with respect to the grid.
00170
00171     // Also, the grid must be of the minimum size to support the requested order
00172     // of accuracy. We must please the divergence.
00173
00174     mtk::UniStgGrid1D aux(mtk::kZero,
00175                          (mtk::Real) 3*order_accuracy_ - 1,
00176                          3*order_accuracy_ - 1);
00177
00178     #if MTK_DEBUG_LEVEL > 0
00179     std::cout << "aux =" << std::endl;
00180     std::cout << aux << std::endl;
00181     std::cout << "aux.delta_x() = " << aux.delta_x() << std::endl;
00182     std::cout << std::endl;
00183     #endif
00184
00185     mtk::DenseMatrix grad_m(grad.ReturnAsDenseMatrix(aux));
00186
00187     #if MTK_DEBUG_LEVEL > 0
00188     std::cout << "grad_m =" << std::endl;
00189     std::cout << grad_m << std::endl;
00190     #endif
00191
00192     mtk::DenseMatrix div_m(div.ReturnAsDenseMatrix(aux));
00193
00194     #if MTK_DEBUG_LEVEL > 0
00195     std::cout << "div_m =" << std::endl;
00196     std::cout << div_m << std::endl;
00197     #endif
00198
00199
00200

```

```

00203     mtk::DenseMatrix lap; // Laplacian matrix to hold to computed coefficients.
00204
00205     lap = mtk::BLASAdapter::RealDenseMM(div_m, grad_m);
00206
00207     #if MTK_DEBUG_LEVEL > 0
00208         std::cout << "lap =" << std::endl;
00209         std::cout << lap << std::endl;
00210     #endif
00211
00212
00213
00214
00215
00216     // The output array will have this form:
00217     // 1. The first entry of the array will contain the used order kk.
00218     // 2. The second entry of the array will contain the collection of
00219     // approximating coefficients for the interior of the grid.
00220     // 3. The next entries will contain the collections of approximating
00221     // coefficients for the west boundary of the grid.
00222
00223     laplacian_length_ = 1 + (2*order_accuracy_ - 1) +
00224         (order_accuracy_ - 1)*(2*order_accuracy_);
00225
00226     #if MTK_DEBUG_LEVEL > 0
00227         std::cout << "laplacian_length_ = " << laplacian_length_ << std::endl;
00228         std::cout << std::endl;
00229     #endif
00230
00231     try {
00232         laplacian_ = new mtk::Real[laplacian_length_];
00233     } catch (std::bad_alloc &memory_allocation_exception) {
00234         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00235             std::endl;
00236         std::cerr << memory_allocation_exception.what() << std::endl;
00237     }
00238     memset(laplacian_, mtk::kZero, sizeof(laplacian_[0])*laplacian_length_);
00239
00240
00241
00242     laplacian_[0] = order_accuracy_;
00243
00244
00245
00246
00247     for (auto ii = 0; ii < 2*order_accuracy_ - 1; ++ii) {
00248         laplacian_[ii + 1] = lap.GetValue(1 + (order_accuracy_ - 1), ii + 1);
00249     }
00250
00251
00252
00253     auto offset = 1 + (2*order_accuracy_ - 1);
00254
00255     for (auto ii = 0; ii < order_accuracy_ - 1; ++ii) {
00256         for (auto jj = 0; jj < 2*order_accuracy_; ++jj) {
00257             laplacian_[offset + ii*(2*order_accuracy_) + jj] =
00258                 lap.GetValue(1 + ii, jj);
00259         }
00260     }
00261
00262     return true;
00263 }
00264
00265 mtk::DenseMatrix mtk::Lap1D::ReturnAsDenseMatrix(const
    UniStgGrid1D &grid) {
00266
00267     int nn{grid.num_cells_x()}; // Number of cells on the grid.
00268
00269     #if MTK_DEBUG_LEVEL > 0
00270         mtk::Tools::Prevent(nn <= 0, __FILE__, __LINE__, __func__);
00271         mtk::Tools::Prevent(nn < 3*order_accuracy_ - 1, __FILE__, __LINE__, __func__);
00272     #endif
00273
00274     mtk::DenseMatrix lap(nn + 2, nn + 2); // Laplacian matrix to be returned.
00275
00276     mtk::Real idx{mtk::kOne/(grid.delta_x()*grid.delta_x())}; // Inverse of
    dx^2.
00277
00278
00279
00280     auto offset = (1 + 2*order_accuracy_ - 1);
00281
00282     for (auto ii = 0; ii < order_accuracy_ - 1; ++ii) {
00283         for (auto jj = 0; jj < 2*order_accuracy_; ++jj) {
00284             lap.SetValue(1 + ii,
00285                 jj,
00286                 idx*laplacian_[offset + ii*2*order_accuracy_ + jj]);
00287         }
00288     }

```

```

00289
00291
00292     offset = 1 + (order_accuracy_ - 1);
00293
00294     int kk{1};
00295     for (auto ii = order_accuracy_; ii <= nn - (order_accuracy_ - 1); ++ii) {
00296         int mm{1};
00297         for (auto jj = 0; jj < 2*order_accuracy_ - 1; ++jj) {
00298             lap.SetValue(ii, jj + kk, idx*laplacian_[mm]);
00299             mm = mm + 1;
00300         }
00301         kk = kk + 1;
00302     }
00303
00305
00306     offset = (1 + 2*order_accuracy_ - 1);
00307
00308     auto aux = order_accuracy_ + (nn - 2*(order_accuracy_ - 1));
00309
00310     auto ll = 1;
00311     auto rr = 1;
00312     for (auto ii = nn; ii > aux - 1; --ii) {
00313         auto cc = 0;
00314         for (auto jj = nn + 2 - 1; jj >= (nn + 2) - 2*order_accuracy_; --jj) {
00315             lap.SetValue(ii, jj, lap.GetValue(rr, cc));
00316             ++ll;
00317             ++cc;
00318         }
00319         rr++;
00320     }
00321
00328
00329     return lap;
00330 }
00331
00332 mtk::Real* mtk::Lap1D::Data(const UniStgGrid1D &grid) {
00333
00334     mtk::DenseMatrix tmp;
00335
00336     tmp = ReturnAsDenseMatrix(grid);
00337
00338     return tmp.data();
00339 }

```

17.47 src/mtk_lapack_adapter.cc File Reference


Adapter class for the LAPACK API.

```

#include <cstring>
#include <iostream>
#include <iomanip>
#include <algorithm>
#include "mtk_tools.h"
#include "mtk_dense_matrix.h"
#include "mtk_lapack_adapter.h"

```

Include dependency graph for mtk_lapack_adapter.cc:



Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

Functions

- void [mtk::sgesv_](#) (int *n, int *nrhs, Real *a, int *lda, int *ipiv, Real *b, int *ldb, int *info)
- void [mtk::sgels_](#) (char *trans, int *m, int *n, int *nrhs, Real *a, int *lda, Real *b, int *ldb, Real *work, int *lwork, int *info)
Single-precision GEneral matrix Least Squares solver.
- void [mtk::sgeqrf_](#) (int *m, int *n, Real *a, int *lda, Real *tau, Real *work, int *lwork, int *info)
Single-precision GEneral matrix QR Factorization.
- void [mtk::sormqr_](#) (char *side, char *trans, int *m, int *n, int *k, Real *a, int *lda, Real *tau, Real *c, int *ldc, Real *work, int *lwork, int *info)
Single-precision Orthogonal [Matrix](#) from QR factorization.

17.47.1 Detailed Description

This class contains a collection of static classes, that posses direct access to the underlying structure of the matrices, thus allowing programmers to exploit some of the numerical methods implemented in the LAPACK.

The **LAPACK** is written in Fortran 90 and provides routines for solving systems of simultaneous linear equations, least-squares solutions of linear systems of equations, eigenvalue problems, and singular value problems.

See Also

<http://www.netlib.org/lapack/>

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_lapack_adapter.cc](#).

17.48 mtk_lapack_adapter.cc

```

00001
00018 /*
00019 Copyright (C) 2015, Computational Science Research Center, San Diego State
00020 University. All rights reserved.
00021
00022 Redistribution and use in source and binary forms, with or without modification,
00023 are permitted provided that the following conditions are met:
00024
00025 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00026 and a copy of the modified files should be reported once modifications are
00027 completed. Documentation related to said modifications should be included.
00028
00029 2. Redistributions of source code must be done through direct
00030 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00031
00032 3. Redistributions of source code must retain the above copyright notice, this
00033 list of conditions and the following disclaimer.
00034
00035 4. Redistributions in binary form must reproduce the above copyright notice,
00036 this list of conditions and the following disclaimer in the documentation and/or
00037 other materials provided with the distribution.
00038
00039 5. Usage of the binary form on proprietary applications shall require explicit
00040 prior written permission from the the copyright holders.
00041
00042 6. Neither the name of the copyright holder nor the names of its contributors
00043 may be used to endorse or promote products derived from this software without
00044 specific prior written permission.
00045
00046 The copyright holders provide no reassurances that the source code provided does
00047 not infringe any patent, copyright, or any other intellectual property rights of
00048 third parties. The copyright holders disclaim any liability to any recipient for
00049 claims brought against recipient by any third party for infringement of that
00050 parties intellectual property rights.
00051
00052 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00053 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00054 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00055 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00056 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00057 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00058 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00059 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00060 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00061 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00062 */
00063
00064 #include <cstring>
00065
00066 #include <iostream>
00067 #include <iomanip>
00068
00069 #include <algorithm>
00070
00071 #include "mtk_tools.h"
00072 #include "mtk_dense_matrix.h"
00073 #include "mtk_lapack_adapter.h"
00074
00075 namespace mtk {
00076
00077 extern "C" {
00078
00079 #ifdef MTK_PRECISION_DOUBLE
00080
00081 void dgesv_(int* n,
00082             int* nrhs,
00083             Real* a,
00084             int* lda,

```

```
00103         int* ipiv,
00104         Real* b,
00105         int* ldb,
00106         int* info);
00107 #else
00108
00127 void sgesv_(int* n,
00128             int* nrhs,
00129             Real* a,
00130             int* lda,
00131             int* ipiv,
00132             Real* b,
00133             int* ldb,
00134             int* info);
00135 #endif
00136
00137 #ifdef MTK_PRECISION_DOUBLE
00138
00181 void dgels_(char* trans,
00182            int* m,
00183            int* n,
00184            int* nrhs,
00185            Real* a,
00186            int* lda,
00187            Real* b,
00188            int* ldb,
00189            Real* work,
00190            int* lwork,
00191            int* info);
00192 #else
00193
00236 void sgels_(char* trans,
00237            int* m,
00238            int* n,
00239            int* nrhs,
00240            Real* a,
00241            int* lda,
00242            Real* b,
00243            int* ldb,
00244            Real* work,
00245            int* lwork,
00246            int* info);
00247 #endif
00248
00249 #ifdef MTK_PRECISION_DOUBLE
00250
00279 void dgeqrf_(int *m,
00280             int *n,
00281             Real *a,
00282             int *lda,
00283             Real *tau,
00284             Real *work,
00285             int *lwork,
00286             int *info);
00287 #else
00288
00317 void sgeqrf_(int *m,
00318             int *n,
00319             Real *a,
00320             int *lda,
00321             Real *tau,
00322             Real *work,
00323             int *lwork,
00324             int *info);
00325 #endif
00326
00327 #ifdef MTK_PRECISION_DOUBLE
00328
00362 void dormqr_(char *side,
00363             char *trans,
00364             int *m,
00365             int *n,
00366             int *k,
00367             Real *a,
00368             int *lda,
00369             Real *tau,
00370             Real *c,
00371             int *ldc,
00372             Real *work,
00373             int *lwork,
00374             int *info);
```

```

00375 #else
00376
00410 void sormqr_(char *side,
00411             char *trans,
00412             int *m,
00413             int *n,
00414             int *k,
00415             Real *a,
00416             int *lda,
00417             Real *tau,
00418             Real *c,
00419             int *ldc,
00420             Real *work,
00421             int *lwork,
00422             int *info);
00423 #endif
00424 }
00425 }
00426
00427 int mtk::LAPACKAdapter::SolveDenseSystem(
    mtk::DenseMatrix &mm,
    mtk::Real *rhs) {
00428
00429
00430
00431     #if MTK_DEBUG_LEVEL > 0
00432     mtk::Tools::Prevent(rhs == nullptr, __FILE__, __LINE__, __func__);
00433     #endif
00434
00435     int *ipiv{};           // Array for pivoting information.
00436     int nrhs{};           // Number of right-hand sides.
00437     int info{};           // Status of the solution.
00438     int mm_rank{mm.num_rows()}; // Rank of the matrix.
00439
00440     try {
00441         ipiv = new int[mm_rank];
00442     } catch (std::bad_alloc &memory_allocation_exception) {
00443         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00444             std::endl;
00445         std::cerr << memory_allocation_exception.what() << std::endl;
00446     }
00447     memset(ipiv, 0, sizeof(ipiv[0])*mm_rank);
00448
00449     int ldbb = mm_rank;
00450     int mm_ld = mm_rank;
00451
00452     #ifdef MTK_PRECISION_DOUBLE
00453     dgesv_(&mm_rank, &nrhs, mm.data(), &mm_ld, ipiv, rhs, &ldbb, &info);
00454     #else
00455     fgesv_(&mm_rank, &nrhs, mm.data(), &mm_ld, ipiv, rhs, &ldbb, &info);
00456     #endif
00457
00458     delete [] ipiv;
00459
00460     return info;
00461 }
00462
00463 int mtk::LAPACKAdapter::SolveDenseSystem(
    mtk::DenseMatrix &mm,
    mtk::DenseMatrix &bb) {
00464
00465
00466     int nrhs{bb.num_rows()}; // Number of right-hand sides.
00467
00468     #if MTK_DEBUG_LEVEL > 0
00469     mtk::Tools::Prevent(nrhs <= 0, __FILE__, __LINE__, __func__);
00470     #endif
00471
00472     int *ipiv{};           // Array for pivoting information.
00473     int info{};           // Status of the solution.
00474     int mm_rank{mm.num_rows()}; // Rank of the matrix.
00475
00476     try {
00477         ipiv = new int[mm_rank];
00478     } catch (std::bad_alloc &memory_allocation_exception) {
00479         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00480             std::endl;
00481         std::cerr << memory_allocation_exception.what() << std::endl;
00482     }
00483     memset(ipiv, 0, sizeof(ipiv[0])*mm_rank);
00484
00485     int ldbb = mm_rank;
00486     int mm_ld = mm_rank;

```



```

00487
00488 #ifdef MTK_PRECISION_DOUBLE
00489 dgesv_(&mm_rank, &nrhs, mm.data(), &mm_ld, ipiv, bb.data(), &lddb, &info);
00490 #else
00491 fgesv_(&mm_rank, &nrhs, mm.data(), &mm_ld, ipiv, bb.data(), &lddb, &info);
00492 #endif
00493
00494 delete [] ipiv;
00495
00496 // After output, the data in the matrix will be column-major ordered.
00497
00498 bb.SetOrdering(mtk::COL_MAJOR);
00499
00500 #if MTK_DEBUG_LEVEL > 0
00501 std::cout << "bb_col_maj_ord =" << std::endl;
00502 std::cout << bb << std::endl;
00503 #endif
00504
00505 bb.OrderRowMajor();
00506
00507 #if MTK_DEBUG_LEVEL > 0
00508 std::cout << "bb_row_maj_ord =" << std::endl;
00509 std::cout << bb << std::endl;
00510 #endif
00511
00512 return info;
00513 }
00514
00515 mtk::DenseMatrix mtk::LAPACKAdapter::QRFactorDenseMatrix
(mtk::DenseMatrix &aa) {
00516
00517     mtk::Real *work{}; // Working array.
00518     mtk::Real *tau{}; // Array for the Householder scalars.
00519
00520     // Prepare to factorize: allocate and inquire for the value of lwork.
00521     try {
00522         work = new mtk::Real[1];
00523     } catch (std::bad_alloc &memory_allocation_exception) {
00524         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00525             std::endl;
00526         std::cerr << memory_allocation_exception.what() << std::endl;
00527     }
00528     memset(work, mtk::kZero, sizeof(aa.data()[0])*1);
00529
00530     int lwork{-1};
00531     int info{};
00532
00533     int aa_num_cols = aa.num_cols();
00534     int aaT_num_rows = aa.num_cols();
00535     int aaT_num_cols = aa.num_rows();
00536
00537     #if MTK_DEBUG_LEVEL > 0
00538     std::cout << "Input matrix BEFORE QR factorization:" << std::endl;
00539     std::cout << aa << std::endl;
00540     #endif
00541
00542     #ifdef MTK_PRECISION_DOUBLE
00543     dgeqrf_(&aaT_num_rows, &aaT_num_cols, aa.data(), &aaT_num_rows,
00544         tau,
00545         work, &lwork, &info);
00546     #else
00547     fgeqrf_(&aaT_num_rows, &aaT_num_cols, aa.data(), &aaT_num_rows,
00548         tau,
00549         work, &lwork, &info);
00550     #endif
00551
00552     #if MTK_DEBUG_LEVEL > 0
00553     if (info == 0) {
00554         lwork = (int) work[0];
00555     } else {
00556         std::cerr << "Could not get value for lwork on line " << __LINE__ - 5 <<
00557             std::endl;
00558         std::cerr << "Exiting..." << std::endl;
00559     }
00560     #endif
00561
00562     #if MTK_DEBUG_LEVEL>0
00563     std::cout << "lwork = " << std::endl << std::setw(12) << lwork << std::endl
00564         << std::endl;
00565     #endif
00566

```

```

00567     delete [] work;
00568     work = nullptr;
00569
00570     // Once we know lwork, we can actually invoke the factorization:
00571     try {
00572         work = new mtk::Real [lwork];
00573     } catch (std::bad_alloc &memory_allocation_exception) {
00574         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00575             std::endl;
00576         std::cerr << memory_allocation_exception.what() << std::endl;
00577     }
00578     memset(work, mtk::kZero, sizeof(work[0])*lwork);
00579
00580     int ltau = std::min(aaT_num_rows, aaT_num_cols);
00581
00582     try {
00583         tau = new mtk::Real [ltau];
00584     } catch (std::bad_alloc &memory_allocation_exception) {
00585         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00586             std::endl;
00587         std::cerr << memory_allocation_exception.what() << std::endl;
00588     }
00589     memset(tau, mtk::kZero, sizeof(0.0)*ltau);
00590
00591     #ifdef MTK_PRECISION_DOUBLE
00592     dgeqrf_(&aaT_num_rows, &aaT_num_cols, aa.data(), &aaT_num_rows,
00593         tau, work, &lwork, &info);
00594     #else
00595     fgeqrf_(&aaT_num_rows, &aaT_num_cols, aa.data(), &aaT_num_rows,
00596         tau, work, &lwork, &info);
00597     #endif
00598
00599     if (!info) {
00600         #if MTK_DEBUG_LEVEL > 0
00601             std::cout << "QR factorization completed!" << std::endl << std::endl;
00602         #endif
00603     } else {
00604         std::cerr << "Error solving system! info = " << info << std::endl;
00605         std::cerr << "Exiting..." << std::endl;
00606     }
00607
00608     #if MTK_DEBUG_LEVEL > 0
00609     std::cout << "Input matrix AFTER QR factorization:" << std::endl;
00610     std::cout << aa << std::endl;
00611     #endif
00612
00613     // We now generate the real matrix Q with orthonormal columns. This has to
00614     // be done separately since the actual output of dgeqrf_ (AA_) represents
00615     // the orthogonal matrix Q as a product of min(aa_num_rows, aa_num_cols)
00616     // elementary Householder reflectors. Notice that we must re-inquire the new
00617     // value for lwork that is used.
00618
00619     bool padded{false};
00620
00621     bool transpose{false};
00622
00623     mtk::DenseMatrix QQ_(aa.num_cols(), padded, transpose);
00624
00625     #if MTK_DEBUG_LEVEL > 0
00626     std::cout << "Initialized QQ_T: " << std::endl;
00627     std::cout << QQ_ << std::endl;
00628     #endif
00629
00630     // Assemble the QQ_ matrix:
00631     lwork = -1;
00632
00633     delete[] work;
00634     work = nullptr;
00635
00636     try {
00637         work = new mtk::Real[l];
00638     } catch (std::bad_alloc &memory_allocation_exception) {
00639         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00640             std::endl;
00641         std::cerr << memory_allocation_exception.what() <<
00642             std::endl;
00643     }
00644     memset(work, mtk::kZero, sizeof(work[0])*l);
00645
00646     char side_{'L'};
00647     char trans_{'N'};

```

```

00648
00649     int aux = QQ_.num_rows();
00650
00651     #ifdef MTK_PRECISION_DOUBLE
00652     dormqr_(&side_, &trans_,
00653             &aa_num_cols, &aa_num_cols, &lttau, aa.data(), &aaT_num_rows, tau,
00654             QQ_.data(), &aux, work, &lwork, &info);
00655     #else
00656     formqr_(&side_, &trans_,
00657             &aa_num_cols, &aa_num_cols, &lttau, aa.data(), &aaT_num_rows, tau,
00658             QQ_.data(), &aux, work, &lwork, &info);
00659     #endif
00660
00661     #if MTK_DEBUG_LEVEL > 0
00662     if (info == 0) {
00663         lwork = (int) work[0];
00664     } else {
00665         std::cerr << "Could not get lwork on line " << __LINE__ - 5 << std::endl;
00666         std::cerr << "Exiting..." << std::endl;
00667     }
00668     #endif
00669
00670     #if MTK_DEBUG_LEVEL > 0
00671     std::cout << "lwork = " << std::endl << std::setw(12) << lwork <<
00672         std::endl << std::endl;
00673     #endif
00674
00675     delete[] work;
00676     work = nullptr;
00677
00678     try {
00679         work = new mtk::Real[lwork];
00680     } catch (std::bad_alloc &memory_allocation_exception) {
00681         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00682             std::endl;
00683         std::cerr << memory_allocation_exception.what() << std::endl;
00684     }
00685     memset(work, mtk::kZero, sizeof(work[0])*lwork);
00686
00687     #ifdef MTK_PRECISION_DOUBLE
00688     dormqr_(&side_, &trans_,
00689             &aa_num_cols, &aa_num_cols, &lttau, aa.data(), &aaT_num_rows, tau,
00690             QQ_.data(), &aux, work, &lwork, &info);
00691     #else
00692     formqr_(&side_, &trans_,
00693             &aa_num_cols, &aa_num_cols, &lttau, aa.data(), &aaT_num_rows, tau,
00694             QQ_.data(), &aux, work, &lwork, &info);
00695     #endif
00696
00697     if (!info) {
00698         #if MTK_DEBUG_LEVEL>0
00699         std::cout << "Q matrix successfully assembled!" << std::endl << std::endl;
00700         #endif
00701     } else {
00702         std::cerr << "Something went wrong solving system! info = " << info <<
00703             std::endl;
00704         std::cerr << "Exiting..." << std::endl;
00705     }
00706
00707     delete[] work;
00708     work = nullptr;
00709
00710     delete[] tau;
00711     tau = nullptr;
00712
00713     return QQ_;
00714 }
00715
00716 int mtk::LAPACKAdapter::SolveRectangularDenseSystem(const
    mtk::DenseMatrix &aa,
                                mtk::Real *ob_,
                                int ob_ld_) {
00717
00718
00719
00720     // We first invoke the solver to query for the value of lwork. For this,
00721     // we must at least allocate enough space to allow access to WORK(1), or
00722     // work[0]:
00723
00724     // If LWORK = -1, then a workspace query is assumed; the routine only
00725     // calculates the optimal size of the WORK array, returns this value as
00726     // the first entry of the WORK array, and no error message related to
00727     // LWORK is issued by XERBLA.

```

```

00728
00729 mtk::Real *work{}; // Work array.
00730
00731 try {
00732     work = new mtk::Real[1];
00733 } catch (std::bad_alloc &memory_allocation_exception) {
00734     std::cerr << "Memory allocation exception on line " << __LINE__ - 3 << std::endl;
00735     std::cerr << memory_allocation_exception.what() << std::endl;
00736 }
00737 memset(work, mtk::kZero, sizeof(work[0])*1);
00738
00739 char trans_{'N'};
00740 int nrhs_{1};
00741 int info{0};
00742 int lwork{-1};
00743
00744 int AA_num_rows_ = aa.num_cols();
00745 int AA_num_cols_ = aa.num_rows();
00746 int AA_ld_ = std::max(1, aa.num_cols());
00747
00748 #ifdef MTK_PRECISION_DOUBLE
00749 dgels_(&trans_, &AA_num_rows_, &AA_num_cols_, &nrhs_, aa.data(), &AA_ld_,
00750     ob_, &ob_ld_,
00751     work, &lwork, &info);
00752 #else
00753 sgels_(&trans_, &AA_num_rows_, &AA_num_cols_, &nrhs_, aa.data(), &AA_ld_,
00754     ob_, &ob_ld_,
00755     work, &lwork, &info);
00756 #endif
00757
00758 if (info == 0) {
00759     lwork = (int) work[0];
00760 } else {
00761     std::cerr << "Could not get value for lwork on line " << __LINE__ - 2 <<
00762         std::endl;
00763     std::cerr << "Exiting..." << std::endl;
00764     return info;
00765 }
00766
00767 #if MTK_DEBUG_LEVEL > 0
00768 std::cout << "lwork = " << std::endl << std::setw(12)<< lwork <<
00769     std::endl << std::endl;
00770 #endif
00771
00772 // We then use lwork's new value to create the work array:
00773 delete[] work;
00774 work = nullptr;
00775
00776 try {
00777     work = new mtk::Real[lwork];
00778 } catch (std::bad_alloc &memory_allocation_exception) {
00779     std::cerr << "Memory allocation exception on line " << __LINE__ - 3 << std::endl;
00780     std::cerr << memory_allocation_exception.what() << std::endl;
00781 }
00782 memset(work, 0.0, sizeof(work[0])*lwork);
00783
00784 // We now invoke the solver again:
00785 #ifdef MTK_PRECISION_DOUBLE
00786 dgels_(&trans_, &AA_num_rows_, &AA_num_cols_, &nrhs_, aa.data(), &AA_ld_,
00787     ob_, &ob_ld_,
00788     work, &lwork, &info);
00789 #else
00790 sgels_(&trans_, &AA_num_rows_, &AA_num_cols_, &nrhs_, aa.data(), &AA_ld_,
00791     ob_, &ob_ld_,
00792     work, &lwork, &info);
00793 #endif
00794
00795 delete [] work;
00796 work = nullptr;
00797
00798 return info;
00799 }


```

17.49 src/mtk_matrix.cc File Reference

Implementing the representation of a matrix in the MTK.

```
#include <cstdlib>
#include <cstdio>
#include <cstring>
#include <cmath>
#include <iomanip>
#include <iostream>
#include "mtk_tools.h"
#include "mtk_matrix.h"
```

Include dependency graph for mtk_matrix.cc:



17.49.1 Detailed Description

Implementation of the representation for the matrices implemented in the MTK.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_matrix.cc](#).

17.50 mtk_matrix.cc

```
00001
00010 /*
00011 Copyright (C) 2015, Computational Science Research Center, San Diego State
00012 University. All rights reserved.
00013
00014 Redistribution and use in source and binary forms, with or without modification,
00015 are permitted provided that the following conditions are met:
00016
00017 1. Modifications to the source code should be reported to:
00018
00019 esanchez at mail dot sdsu dot edu
00020
00021 A copy of the modified files should be reported once modifications are
00022 completed. Documentation related to said modifications should be included.
00023
00024 2. Redistributions of source code must be done through direct
00025 downloads from the project's GitHub page:
00026
00027 http://www.csrc.sdsu.edu/mtk
00028
00029 3. Redistributions of source code must retain the above copyright notice, this
00030 list of conditions and the following disclaimer.
00031
00032 4. Redistributions in binary form must reproduce the above copyright notice,
00033 this list of conditions and the following disclaimer in the documentation and/or
00034 other materials provided with the distribution.
00035
00036 5. Usage of the binary form on proprietary applications shall require explicit
00037 prior written permission from the the copyright holders.
```

```

00038
00039 6. Neither the name of the copyright holder nor the names of its contributors
00040 may be used to endorse or promote products derived from this software without
00041 specific prior written permission.
00042
00043 The copyright holders provide no reassurances that the source code provided does
00044 not infringe any patent, copyright, or any other intellectual property rights of
00045 third parties. The copyright holders disclaim any liability to any recipient for
00046 claims brought against recipient by any third party for infringement of that
00047 parties intellectual property rights.
00048
00049 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00050 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00051 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00052 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00053 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00054 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00055 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00056 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00057 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00058 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00059 */
00060
00061 #include <cstdlib>
00062 #include <cstdio>
00063 #include <cstring>
00064 #include <cmath>
00065
00066 #include <iomanip>
00067 #include <iostream>
00068
00069 #include "mtk_tools.h"
00070 #include "mtk_matrix.h"
00071
00072 mtk::Matrix::Matrix():
00073     storage_(mtk::DENSE),
00074     ordering_(mtk::ROW_MAJOR),
00075     num_rows_(),
00076     num_cols_(),
00077     num_values_(),
00078     ld_(),
00079     num_zero_(),
00080     num_non_zero_(),
00081     num_null_(),
00082     num_non_null_(),
00083     kl_(),
00084     ku_(),
00085     bandwidth_(),
00086     abs_density_(),
00087     rel_density_(),
00088     abs_sparsity_(),
00089     rel_sparsity_() {}
00090
00091 mtk::Matrix::Matrix(const Matrix &in):
00092     storage_(in.storage_),
00093     ordering_(in.ordering_),
00094     num_rows_(in.num_rows_),
00095     num_cols_(in.num_cols_),
00096     num_values_(in.num_values_),
00097     ld_(in.ld_),
00098     num_zero_(in.num_zero_),
00099     num_non_zero_(in.num_non_zero_),
00100     num_null_(in.num_null_),
00101     num_non_null_(in.num_non_null_),
00102     kl_(in.kl_),
00103     ku_(in.ku_),
00104     bandwidth_(in.bandwidth_),
00105     abs_density_(in.abs_density_),
00106     rel_density_(in.rel_density_),
00107     abs_sparsity_(in.abs_sparsity_),
00108     rel_sparsity_(in.rel_sparsity_) {}
00109
00110 mtk::Matrix::~Matrix() {}
00111
00112 mtk::MatrixStorage mtk::Matrix::storage() const {
00113
00114     return storage_;
00115 }
00116
00117 mtk::MatrixOrdering mtk::Matrix::ordering() const {
00118

```

```

00119     return ordering_;
00120 }
00121
00122 int mtk::Matrix::num_rows() const {
00123
00124     return num_rows_;
00125 }
00126
00127 int mtk::Matrix::num_cols() const {
00128
00129     return num_cols_;
00130 }
00131
00132 int mtk::Matrix::num_values() const {
00133
00134     return num_values_;
00135 }
00136
00137 int mtk::Matrix::ld() const {
00138
00139     return ld_;
00140 }
00141
00142 int mtk::Matrix::num_zero() const {
00143
00144     return num_zero_;
00145 }
00146
00147 int mtk::Matrix::num_non_zero() const {
00148
00149     return num_non_zero_;
00150 }
00151
00152 int mtk::Matrix::num_null() const {
00153
00154     return num_null_;
00155 }
00156
00157 int mtk::Matrix::num_non_null() const {
00158
00159     return num_non_null_;
00160 }
00161
00162 int mtk::Matrix::kl() const {
00163
00164     return kl_;
00165 }
00166
00167 int mtk::Matrix::ku() const {
00168
00169     return ku_;
00170 }
00171
00172 int mtk::Matrix::bandwidth() const {
00173
00174     return bandwidth_;
00175 }
00176
00177 mtk::Real mtk::Matrix::rel_density() const {
00178
00179     return rel_density_;
00180 }
00181
00182 mtk::Real mtk::Matrix::abs_sparsity() const {
00183
00184     return abs_sparsity_;
00185 }
00186
00187 mtk::Real mtk::Matrix::rel_sparsity() const {
00188
00189     return rel_sparsity_;
00190 }
00191
00192 void mtk::Matrix::set_storage(const mtk::MatrixStorage &ss) {
00193
00194     #if MTK_DEBUG_LEVEL > 0
00195     mtk::Tools::Prevent(!(ss == mtk::DENSE ||
00196                          ss == mtk::BANDED ||
00197                          ss == mtk::CRS),
00198                        __FILE__, __LINE__, __func__);
00199     #endif

```

```

00200
00201     storage_ = ss;
00202 }
00203
00204 void mtk::Matrix::set_ordering(const
    mtk::MatrixOrdering &oo) {
00205
00206     #if MTK_DEBUG_LEVEL > 0
00207     mtk::Tools::Prevent(!(oo == mtk::ROW_MAJOR || oo ==
    mtk::COL_MAJOR),
00208                         __FILE__, __LINE__, __func__);
00209     #endif
00210
00211     ordering_ = oo;
00212
00213     ld_ = (ordering_ == mtk::ROW_MAJOR)?
00214         std::max(1,num_cols_): std::max(1,num_rows_);
00215 }
00216
00217 void mtk::Matrix::set_num_rows(int in) {
00218
00219     #if MTK_DEBUG_LEVEL > 0
00220     mtk::Tools::Prevent(in < 1, __FILE__, __LINE__, __func__);
00221     #endif
00222
00223     num_rows_ = in;
00224     num_values_ = num_rows_*num_cols_;
00225     ld_ = (ordering_ == mtk::ROW_MAJOR)?
00226         std::max(1,num_cols_): std::max(1,num_rows_);
00227 }
00228
00229 void mtk::Matrix::set_num_cols(int in) {
00230
00231     #if MTK_DEBUG_LEVEL > 0
00232     mtk::Tools::Prevent(in < 1, __FILE__, __LINE__, __func__);
00233     #endif
00234
00235     num_cols_ = in;
00236     num_values_ = num_rows_*num_cols_;
00237     ld_ = (ordering_ == mtk::ROW_MAJOR)?
00238         std::max(1,num_cols_): std::max(1,num_rows_);
00239 }
00240
00241 void mtk::Matrix::set_num_zero(int in) {
00242
00243     #if MTK_DEBUG_LEVEL > 0
00244     mtk::Tools::Prevent(in < 0, __FILE__, __LINE__, __func__);
00245     #endif
00246
00247     num_zero_ = in;
00248     num_non_zero_ = num_values_ - num_zero_;
00249
00251     rel_density_ = (mtk::Real) num_non_zero_/num_values_;
00252     rel_sparsity_ = 1.0 - rel_density_;
00253 }
00254
00255 void mtk::Matrix::set_num_null(int in) {
00256
00257     #if MTK_DEBUG_LEVEL > 0
00258     mtk::Tools::Prevent(in < 0, __FILE__, __LINE__, __func__);
00259     #endif
00260
00261     num_null_ = in;
00262     num_non_null_ = num_values_ - num_null_;
00263
00265     abs_density_ = (mtk::Real) num_non_null_/num_values_;
00266     abs_sparsity_ = 1.0 - abs_density_;
00267 }
00268
00269 void mtk::Matrix::IncreaseNumZero() {
00270
00272
00273     num_zero_++;
00274     num_non_zero_ = num_values_ - num_zero_;
00275     rel_density_ = (mtk::Real) num_non_zero_/num_values_;
00276     rel_sparsity_ = 1.0 - rel_density_;
00277 }
00278
00279 void mtk::Matrix::IncreaseNumNull() {
00280
00282

```



```

00283     num_null_++;
00284     num_non_null_ = num_values_ - num_null_;
00285     abs_density_ = (mtk::Real) num_non_null_/num_values_;
00286     abs_sparsity_ = 1.0 - abs_density_;
00287 }

```

17.51 src/mtk_tools.cc File Reference


Implements a execution tool manager class.

```

#include <iostream>
#include "mtk_roots.h"
#include "mtk_tools.h"

```

Include dependency graph for mtk_tools.cc:



17.51.1 Detailed Description

Basic tools to ensure execution correctness.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_tools.cc](#).

17.52 mtk_tools.cc

```

00001
00010 /*
00011 Copyright (C) 2015, Computational Science Research Center, San Diego State
00012 University. All rights reserved.
00013
00014 Redistribution and use in source and binary forms, with or without modification,
00015 are permitted provided that the following conditions are met:
00016

```

```

00017 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00018 and a copy of the modified files should be reported once modifications are
00019 completed. Documentation related to said modifications should be included.
00020
00021 2. Redistributions of source code must be done through direct
00022 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00023
00024 3. Redistributions of source code must retain the above copyright notice, this
00025 list of conditions and the following disclaimer.
00026
00027 4. Redistributions in binary form must reproduce the above copyright notice,
00028 this list of conditions and the following disclaimer in the documentation and/or
00029 other materials provided with the distribution.
00030
00031 5. Usage of the binary form on proprietary applications shall require explicit
00032 prior written permission from the the copyright holders.
00033
00034 6. Neither the name of the copyright holder nor the names of its contributors
00035 may be used to endorse or promote products derived from this software without
00036 specific prior written permission.
00037
00038 The copyright holders provide no reassurances that the source code provided does
00039 not infringe any patent, copyright, or any other intellectual property rights of
00040 third parties. The copyright holders disclaim any liability to any recipient for
00041 claims brought against recipient by any third party for infringement of that
00042 parties intellectual property rights.
00043
00044 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00045 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00046 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00047 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00048 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00049 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00050 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00051 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00052 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00053 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00054 */
00055
00056 #include <iostream>
00057
00058 #include "mtk_roots.h"
00059 #include "mtk_tools.h"
00060
00061 void mtk::Tools::Prevent(const bool condition,
00062                          const char *fname,
00063                          int lineno,
00064                          const char *fxname) {
00065
00066     #if MTK_DEBUG_LEVEL > 0
00067     if (lineno < 1) {
00070         std::cerr << __FILE__ << ": " << "Incorrect parameter at line " <<
00071         __LINE__ - 2 << " (" << __func__ << ")" << std::endl;
00072         exit(EXIT_FAILURE);
00073     }
00074     #endif
00075
00076     if (condition) {
00077         std::cerr << fname << ": " << "Incorrect parameter at line " <<
00078         lineno << " (" << fxname << ")" << std::endl;
00079         exit(EXIT_FAILURE);
00080     }
00081 }
00082
00083
00084 int mtk::Tools::test_number_; // Used to control the correctness of the test.
00085
00086 clock_t mtk::Tools::begin_time_; // Used to time tests.
00087
00088 void mtk::Tools::BeginTestNo(const int &nn) {
00089
00090     #if MTK_DEBUG_LEVEL > 0
00091     mtk::Tools::Prevent(nn <= 0, __FILE__, __LINE__, __func__);
00092     #endif
00093
00094     test_number_ = nn;
00095
00096     std::cout << "Test " << nn << "..." << std::endl << std::endl;
00097     begin_time_ = clock();
00098 }

```

```

00100
00101 void mtk::Tools::EndTestNo(const int &nn) {
00102
00103     #if MTK_DEBUG_LEVEL > 0
00104     mtk::Tools::Prevent(test_number_ != nn, __FILE__, __LINE__, __func__);
00105     #endif
00106
00107     auto duration = mtk::Real(clock() - begin_time_)/CLOCKS_PER_SEC;
00108     std::cout << "Test " << test_number_ << " complete! ";
00109     std::cout << "Elapsed: " << duration << " seconds." << std::endl;
00110 }

```

17.53 src/mtk_uni_stg_grid_1d.cc File Reference


Implementation of an 1D uniform staggered grid.

```

#include <iostream>
#include <iomanip>
#include <fstream>
#include "mtk_roots.h"
#include "mtk_enums.h"
#include "mtk_tools.h"
#include "mtk_uni_stg_grid_1d.h"

```

Include dependency graph for mtk_uni_stg_grid_1d.cc:



Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

Functions

- `std::ostream & mtk::operator<< (std::ostream &stream, mtk::UniStgGrid1D &in)`

17.53.1 Detailed Description

Implementation of an 1D uniform staggered grid.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_uni_stg_grid_1d.cc](#).

17.54 mtk_uni_stg_grid_1d.cc

```

00001
00010 /*
00011 Copyright (C) 2015, Computational Science Research Center, San Diego State
00012 University. All rights reserved.
00013
00014 Redistribution and use in source and binary forms, with or without modification,
00015 are permitted provided that the following conditions are met:
00016
00017 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00018 and a copy of the modified files should be reported once modifications are
00019 completed. Documentation related to said modifications should be included.
00020
00021 2. Redistributions of source code must be done through direct
00022 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00023
00024 3. Redistributions of source code must retain the above copyright notice, this
00025 list of conditions and the following disclaimer.
00026
00027 4. Redistributions in binary form must reproduce the above copyright notice,
00028 this list of conditions and the following disclaimer in the documentation and/or
00029 other materials provided with the distribution.
00030
00031 5. Usage of the binary form on proprietary applications shall require explicit
00032 prior written permission from the the copyright holders.
00033
00034 6. Neither the name of the copyright holder nor the names of its contributors
00035 may be used to endorse or promote products derived from this software without
00036 specific prior written permission.
00037
00038 The copyright holders provide no reassurances that the source code provided does
00039 not infringe any patent, copyright, or any other intellectual property rights of
00040 third parties. The copyright holders disclaim any liability to any recipient for
00041 claims brought against recipient by any third party for infringement of that
00042 parties intellectual property rights.
00043
00044 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00045 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00046 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00047 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00048 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00049 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00050 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00051 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00052 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00053 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00054 */
00055
00056 #include <iostream>
00057 #include <iomanip>
00058 #include <fstream>
00059
00060 #include "mtk_roots.h"
00061 #include "mtk_enums.h"
00062 #include "mtk_tools.h"
00063
00064 #include "mtk_uni_stg_grid_1d.h"
00065
00066 namespace mtk {
00067
00068 std::ostream& operator <<(std::ostream &stream, mtk::UniStgGrid1D &in) {
00069
00070     stream << '[' << in.west_bndy_x << ':' << in.num_cells_x << ':' <<
00071     in.east_bndy_x << "]" = " << std::endl << std::endl;
00072
00073
00074
00075     stream << "x:";
00076     for (unsigned int ii = 0; ii < in.discrete_domain_x.size(); ++ii) {
00077         stream << std::setw(10) << in.discrete_domain_x[ii];
00078     }
00079     stream << std::endl;
00080
00081     if (in.nature_ == mtk::SCALAR) {
00082         stream << "u:";
00083     }
00084     else {
00085         stream << "v:";
00086     }
00087     for (unsigned int ii = 0; ii < in.discrete_field_u.size(); ++ii) {

```

```

00088     stream << std::setw(10) << in.discrete_field_u_[ii];
00089 }
00090
00091     stream << std::endl;
00092
00093     return stream;
00094 }
00095 }
00096
00097 mtk::UniStgGrid1D::UniStgGrid1D():
00098     nature_( ),
00099     discrete_domain_x_( ),
00100     discrete_field_u_( ),
00101     west_bndy_x_( ),
00102     east_bndy_x_( ),
00103     num_cells_x_( ),
00104     delta_x_( ) {}
00105
00106 mtk::UniStgGrid1D::UniStgGrid1D(const
00107     UniStgGrid1D &grid):
00108     nature_(grid.nature_),
00109     west_bndy_x_(grid.west_bndy_x_),
00110     east_bndy_x_(grid.east_bndy_x_),
00111     num_cells_x_(grid.num_cells_x_),
00112     delta_x_(grid.delta_x_) {
00113
00114     std::copy(grid.discrete_domain_x_.begin(),
00115         grid.discrete_domain_x_.begin() + grid.
00116         discrete_domain_x_.size(),
00117         discrete_domain_x_.begin());
00118
00119     std::copy(grid.discrete_field_u_.begin(),
00120         grid.discrete_field_u_.begin() + grid.
00121         discrete_field_u_.size(),
00122         discrete_field_u_.begin());
00123 }
00124
00125 mtk::UniStgGrid1D::UniStgGrid1D(const Real &west_bndy_x,
00126     const Real &east_bndy_x,
00127     const int &num_cells_x,
00128     const mtk::FieldNature &nature) {
00129
00130     #if MTK_DEBUG_LEVEL > 0
00131     mtk::Tools::Prevent(west_bndy_x < mtk::kZero, __FILE__, __LINE__, __func__);
00132     mtk::Tools::Prevent(east_bndy_x < mtk::kZero, __FILE__, __LINE__, __func__);
00133     mtk::Tools::Prevent(east_bndy_x <= west_bndy_x, __FILE__, __LINE__, __func__);
00134     mtk::Tools::Prevent(num_cells_x < 0, __FILE__, __LINE__, __func__);
00135     #endif
00136
00137     nature_ = nature;
00138     west_bndy_x_ = west_bndy_x;
00139     east_bndy_x_ = east_bndy_x;
00140     num_cells_x_ = num_cells_x;
00141
00142     delta_x_ = (east_bndy_x - west_bndy_x) / ((mtk::Real) num_cells_x);
00143 }
00144
00145 mtk::UniStgGrid1D::~UniStgGrid1D() {}
00146
00147 mtk::Real mtk::UniStgGrid1D::delta_x() const {
00148
00149     return delta_x_;
00150 }
00151
00152 mtk::Real *mtk::UniStgGrid1D::discrete_domain_x() {
00153
00154     return discrete_domain_x_.data();
00155 }
00156
00157 mtk::Real *mtk::UniStgGrid1D::discrete_field_u() {
00158
00159     return discrete_field_u_.data();
00160 }
00161
00162 int mtk::UniStgGrid1D::num_cells_x() const {
00163
00164     return num_cells_x_;
00165 }
00166
00167 void mtk::UniStgGrid1D::BindScalarField(
00168     mtk::Real (*ScalarField)(mtk::Real xx)) {

```

```

00166
00167 #if MTK_DEBUG_LEVEL > 0
00168 mtk::Tools::Prevent(nature_ == mtk::VECTOR, __FILE__, __LINE__, __func__);
00169 #endif
00170
00172
00173 discrete_domain_x_.reserve(num_cells_x_ + 2);
00174
00175 discrete_domain_x_.push_back(west_bndy_x_);
00176 #ifdef MTK_PRECISION_DOUBLE
00177 auto first_center = west_bndy_x_ + delta_x_/2.0;
00178 #else
00179 auto first_center = west_bndy_x_ + delta_x_/2.0f;
00180 #endif
00181 discrete_domain_x_.push_back(first_center);
00182 for (auto ii = 1; ii < num_cells_x_; ++ii) {
00183     discrete_domain_x_.push_back(first_center + ii*delta_x_);
00184 }
00185 discrete_domain_x_.push_back(east_bndy_x_);
00186
00188
00189 discrete_field_u_.reserve(num_cells_x_ + 2);
00190
00191 discrete_field_u_.push_back(ScalarField(west_bndy_x_));
00192
00193 discrete_field_u_.push_back(ScalarField(first_center));
00194 for (auto ii = 1; ii < num_cells_x_; ++ii) {
00195     discrete_field_u_.push_back(ScalarField(first_center + ii*delta_x_));
00196 }
00197 discrete_field_u_.push_back(ScalarField(east_bndy_x_));
00198 }
00199
00200 void mtk::UniStgGrid1D::BindVectorField(
00201     mtk::Real (*VectorField)(mtk::Real xx)) {
00202
00203     #if MTK_DEBUG_LEVEL > 0
00204     mtk::Tools::Prevent(nature_ == mtk::SCALAR, __FILE__, __LINE__, __func__);
00205     #endif
00206
00208
00209 discrete_domain_x_.reserve(num_cells_x_ + 1);
00210
00211 discrete_domain_x_.push_back(west_bndy_x_);
00212 for (auto ii = 1; ii < num_cells_x_; ++ii) {
00213     discrete_domain_x_.push_back(west_bndy_x_ + ii*delta_x_);
00214 }
00215 discrete_domain_x_.push_back(east_bndy_x_);
00216
00218
00219 discrete_field_u_.reserve(num_cells_x_ + 1);
00220
00221 discrete_field_u_.push_back(VectorField(west_bndy_x_));
00222 for (auto ii = 1; ii < num_cells_x_; ++ii) {
00223     discrete_field_u_.push_back(VectorField(west_bndy_x_ + ii*delta_x_));
00224 }
00225 discrete_field_u_.push_back(VectorField(east_bndy_x_));
00226 }
00227
00228 bool mtk::UniStgGrid1D::WriteToFile(std::string filename,
00229                                     std::string space_name,
00230                                     std::string field_name) {
00231
00232     std::ofstream output_dat_file; // Output file.
00233
00234     output_dat_file.open(filename);
00235
00236     if (!output_dat_file.is_open()) {
00237         return false;
00238     }
00239
00240     output_dat_file << "# " << space_name << ' ' << field_name << std::endl;
00241     for (unsigned int ii = 0; ii < discrete_domain_x_.size(); ++ii) {
00242         output_dat_file << discrete_domain_x_[ii] << ' ' << discrete_field_u_[ii] <<
00243             std::endl;
00244     }
00245
00246     output_dat_file.close();
00247
00248     return true;
00249 }


```

17.55 tests/mtk_blas_adapter_test.cc File Reference

Test file for the [mtk::BLASAdapter](#) class.

```
#include <iostream>
```

Include dependency graph for mtk_blas_adapter_test.cc:



Functions

- int [main](#) ()

17.55.1 Detailed Description

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_blas_adapter_test.cc](#).

17.55.2 Function Documentation

17.55.2.1 int main ()

Definition at line [107](#) of file [mtk_blas_adapter_test.cc](#).

17.56 mtk_blas_adapter_test.cc

```
00001
00008 /*
00009 Copyright (C) 2015, Computational Science Research Center, San Diego State
00010 University. All rights reserved.
00011
00012 Redistribution and use in source and binary forms, with or without modification,
00013 are permitted provided that the following conditions are met:
00014
00015 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00016 and a copy of the modified files should be reported once modifications are
00017 completed. Documentation related to said modifications should be included.
```

```

00018
00019 2. Redistributions of source code must be done through direct
00020 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00021
00022 3. Redistributions of source code must retain the above copyright notice, this
00023 list of conditions and the following disclaimer.
00024
00025 4. Redistributions in binary form must reproduce the above copyright notice,
00026 this list of conditions and the following disclaimer in the documentation and/or
00027 other materials provided with the distribution.
00028
00029 5. Usage of the binary form on proprietary applications shall require explicit
00030 prior written permission from the the copyright holders.
00031
00032 6. Neither the name of the copyright holder nor the names of its contributors
00033 may be used to endorse or promote products derived from this software without
00034 specific prior written permission.
00035
00036 The copyright holders provide no reassurances that the source code provided does
00037 not infringe any patent, copyright, or any other intellectual property rights of
00038 third parties. The copyright holders disclaim any liability to any recipient for
00039 claims brought against recipient by any third party for infringement of that
00040 parties intellectual property rights.
00041
00042 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00043 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00044 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00045 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00046 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00047 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00048 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00049 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00050 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00051 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00052 */
00053
00054 #if __cplusplus == 201103L
00055
00056 #include <iostream>
00057
00058 #include "mtk.h"
00059
00060 void Test1() {
00061
00062     mtk::Tools::BeginTestNo(1);
00063
00064     int rr = 2;
00065     int cc = 3;
00066
00067     mtk::DenseMatrix aa(rr,cc);
00068
00069     aa.SetValue(0,0,1.0);
00070     aa.SetValue(0,1,2.0);
00071     aa.SetValue(0,2,3.0);
00072     aa.SetValue(1,0,4.0);
00073     aa.SetValue(1,1,5.0);
00074     aa.SetValue(1,2,6.0);
00075
00076     std::cout << aa << std::endl;
00077
00078     mtk::DenseMatrix bb(cc,rr);
00079
00080     bb.SetValue(0,0,7.0);
00081     bb.SetValue(0,1,8.0);
00082     bb.SetValue(1,0,9.0);
00083     bb.SetValue(1,1,10.0);
00084     bb.SetValue(2,0,11.0);
00085     bb.SetValue(2,1,12.0);
00086
00087     std::cout << bb << std::endl;
00088
00089     mtk::DenseMatrix pp = mtk::BLASAdapter::RealDenseMM(aa,bb);
00090
00091     std::cout << pp << std::endl;
00092
00093     mtk::Tools::EndTestNo(1);
00094 }
00095
00096 int main () {
00097
00098     std::cout << "Testing mtk::BLASAdapter class." << std::endl;

```




```
00099
00100     Test1();
00101 }
00102
00103 #else
00104 #include <iostream>
00105 using std::cout;
00106 using std::endl;
00107 int main () {
00108     cout << "This code HAS to be compiled with support for C++11." << endl;
00109     cout << "Exiting..." << endl;
00110 }
00111 #endif
```

17.57 tests/mtk_dense_matrix_test.cc File Reference

Test file for the [mtk::DenseMatrix](#) class.

```
#include <iostream>
```

Include dependency graph for mtk_dense_matrix_test.cc:



Functions

- int [main](#) ()

17.57.1 Detailed Description

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_dense_matrix_test.cc](#).

17.57.2 Function Documentation

17.57.2.1 int main ()

Definition at line [285](#) of file [mtk_dense_matrix_test.cc](#).

17.58 mtk_dense_matrix_test.cc

```

00001
00008 /*
00009 Copyright (C) 2015, Computational Science Research Center, San Diego State
00010 University. All rights reserved.
00011
00012 Redistribution and use in source and binary forms, with or without modification,
00013 are permitted provided that the following conditions are met:
00014
00015 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00016 and a copy of the modified files should be reported once modifications are
00017 completed. Documentation related to said modifications should be included.
00018
00019 2. Redistributions of source code must be done through direct
00020 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00021
00022 3. Redistributions of source code must retain the above copyright notice, this
00023 list of conditions and the following disclaimer.
00024
00025 4. Redistributions in binary form must reproduce the above copyright notice,
00026 this list of conditions and the following disclaimer in the documentation and/or
00027 other materials provided with the distribution.
00028
00029 5. Usage of the binary form on proprietary applications shall require explicit
00030 prior written permission from the the copyright holders.
00031
00032 6. Neither the name of the copyright holder nor the names of its contributors
00033 may be used to endorse or promote products derived from this software without
00034 specific prior written permission.
00035
00036 The copyright holders provide no reassurances that the source code provided does
00037 not infringe any patent, copyright, or any other intellectual property rights of
00038 third parties. The copyright holders disclaim any liability to any recipient for
00039 claims brought against recipient by any third party for infringement of that
00040 parties intellectual property rights.
00041
00042 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00043 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00044 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00045 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00046 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00047 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00048 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00049 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00050 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00051 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00052 */
00053
00054 #if __cplusplus == 201103L
00055
00056 #include <iostream>
00057 #include <ctime>
00058
00059 #include "mtk.h"
00060
00061 void Test1() {
00062
00063     mtk::Tools::BeginTestNo(1);
00064
00065     mtk::DenseMatrix m1;
00066
00067     std::cout << m1 << std::endl;
00068
00069     mtk::Tools::EndTestNo(1);
00070 }
00071
00072 void Test2() {
00073
00074     mtk::Tools::BeginTestNo(2);
00075
00076     int rr = 4;
00077     int cc = 7;
00078
00079     mtk::DenseMatrix m2(rr,cc);
00080
00081     std::cout << m2 << std::endl;
00082
00083     mtk::Tools::EndTestNo(2);
00084 }

```

```

00085
00086 void Test3() {
00087
00088     mtk::Tools::BeginTestNo(3);
00089
00090     int rank = 5;
00091     bool padded = true;
00092     bool transpose = false;
00093
00094     mtk::DenseMatrix m3(rank,padded,transpose);
00095
00096     std::cout << m3 << std::endl;
00097
00098     mtk::Tools::EndTestNo(3);
00099 }
00100
00101 void Test4() {
00102
00103     mtk::Tools::BeginTestNo(4);
00104
00105     int rank = 5;
00106     bool padded = false;
00107     bool transpose = false;
00108
00109     mtk::DenseMatrix m4(rank,padded,transpose);
00110
00111     std::cout << m4 << std::endl;
00112
00113     mtk::Tools::EndTestNo(4);
00114 }
00115
00116 void Test5() {
00117
00118     mtk::Tools::BeginTestNo(5);
00119
00120     int rr = 4;
00121     int cc = 7;
00122
00123     mtk::DenseMatrix m5(rr,cc);
00124
00125     for (auto ii = 0; ii < rr; ++ii) {
00126         for (auto jj = 0; jj < cc; ++jj) {
00127             m5.SetValue(ii,jj,(mtk::Real) ii + jj);
00128         }
00129     }
00130
00131     std::cout << m5 << std::endl;
00132
00133     mtk::Real *vals = m5.data();
00134
00135     for (auto ii = 0; ii < rr; ++ii) {
00136         for (auto jj = 0; jj < cc; ++jj) {
00137             std::cout << " " << vals[ii*cc + jj];
00138         }
00139         std::cout << std::endl;
00140     }
00141     std::cout << std::endl;
00142
00143     for (auto ii = 0; ii < rr; ++ii) {
00144         for (auto jj = 0; jj < cc; ++jj) {
00145             std::cout << " " << m5.GetValue(ii,jj);
00146         }
00147         std::cout << std::endl;
00148     }
00149     std::cout << std::endl;
00150
00151     mtk::Tools::EndTestNo(5);
00152 }
00153
00154 void Test6() {
00155
00156     mtk::Tools::BeginTestNo(6);
00157
00158     bool transpose = false;
00159     int generator_length = 3;
00160     int progression_length = 4;
00161
00162     mtk::Real generator[] = {-0.5, 0.5, 1.5};
00163
00164     mtk::DenseMatrix m6(generator,generator_length,progression_length,transpose);
00165

```

```

00166     std::cout << m6 << std::endl;
00167
00168     transpose = true;
00169
00170     mtk::DenseMatrix m7(generator,generator_length,progression_length,transpose);
00171
00172     std::cout << m7 << std::endl;
00173
00174
00175     mtk::Tools::EndTestNo(6);
00176 }
00177
00178 void Test7() {
00179
00180     mtk::Tools::BeginTestNo(7);
00181
00182     bool padded = false;
00183     bool transpose = false;
00184     int lots_of_rows = 2;
00185     int lots_of_cols = 5;
00186     mtk::DenseMatrix m8(lots_of_rows,padded,transpose);
00187
00188     std::cout << m8 << std::endl;
00189
00190     mtk::DenseMatrix m9(lots_of_rows,lots_of_cols);
00191
00192     for (auto ii = 0; ii < lots_of_rows; ++ii) {
00193         for (auto jj = 0; jj < lots_of_cols; ++jj) {
00194             m9.SetValue(ii,jj,(mtk::Real) ii*lots_of_cols + jj + 1);
00195         }
00196     }
00197
00198     std::cout << m9 << std::endl;
00199
00200     mtk::DenseMatrix m10 = mtk::DenseMatrix::Kron(m8,m9);
00201
00202     std::cout << m10 << std::endl;
00203
00204     mtk::Tools::EndTestNo(7);
00205 }
00206
00207 void Test8() {
00208
00209     mtk::Tools::BeginTestNo(8);
00210
00211     int lots_of_rows = 4;
00212     int lots_of_cols = 3;
00213     mtk::DenseMatrix m11(lots_of_rows,lots_of_cols);
00214
00215     for (auto ii = 0; ii < lots_of_rows; ++ii) {
00216         for (auto jj = 0; jj < lots_of_cols; ++jj) {
00217             m11.SetValue(ii,jj,(mtk::Real) ii*lots_of_cols + jj + 1);
00218         }
00219     }
00220
00221     std::cout << m11 << std::endl;
00222
00223     m11.Transpose();
00224
00225     std::cout << m11 << std::endl;
00226
00227     mtk::DenseMatrix m12;
00228
00229     m12 = m11;
00230
00231     std::cout << m12 << std::endl;
00232
00233     mtk::Tools::EndTestNo(8);
00234 }
00235
00236 void Test9() {
00237
00238     mtk::Tools::BeginTestNo(9);
00239
00240     bool transpose = false;
00241     int gg_l = 3;
00242     int progression_length = 4;
00243     mtk::Real gg[] = {-0.5, 0.5, 1.5};
00244
00245     mtk::DenseMatrix m13(gg, gg_l ,progression_length, transpose);
00246

```

```

00247     std::cout << m13 << std::endl;
00248
00249     mtk::DenseMatrix m14;
00250
00251     m14 = m13;
00252
00253     std::cout << m14 << std::endl;
00254
00255     m13.Transpose();
00256
00257     std::cout << m13 << std::endl;
00258
00259     m14 = m13;
00260
00261     std::cout << m14 << std::endl;
00262
00263     mtk::Tools::EndTestNo(9);
00264 }
00265
00266 int main () {
00267
00268     std::cout << "Testing mtk::DenseMatrix class." << std::endl;
00269
00270     Test1();
00271     Test2();
00272     Test3();
00273     Test4();
00274     Test5();
00275     Test6();
00276     Test7();
00277     Test8();
00278     Test9();
00279 }
00280
00281 #else
00282 #include <iostream>
00283 using std::cout;
00284 using std::endl;
00285 int main () {
00286     cout << "This code HAS to be compiled with support for C++11." << endl;
00287     cout << "Exiting..." << endl;
00288 }
00289 #endif


```

17.59 tests/mtk_div_1d_test.cc File Reference

Testing the mimetic 1D divergence, constructed with the CBS algorithm.

```
#include <iostream>
```

Include dependency graph for mtk_div_1d_test.cc:



Functions

- int [main](#) ()

17.59.1 Detailed Description

Author

: Eduardo J. Sanchez (ejspeiro) - [esanchez at mail dot sdsu dot edu](mailto:esanchez@mail.sdsu.edu)

Definition in file [mtk_div_1d_test.cc](#).

17.59.2 Function Documentation

17.59.2.1 int main ()

Definition at line [248](#) of file [mtk_div_1d_test.cc](#).

17.60 mtk_div_1d_test.cc

```
00001
00008 /*
00009 Copyright (C) 2015, Computational Science Research Center, San Diego State
00010 University. All rights reserved.
00011
00012 Redistribution and use in source and binary forms, with or without modification,
00013 are permitted provided that the following conditions are met:
00014
00015 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00016 and a copy of the modified files should be reported once modifications are
00017 completed. Documentation related to said modifications should be included.
00018
00019 2. Redistributions of source code must be done through direct
00020 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00021
00022 3. Redistributions of source code must retain the above copyright notice, this
00023 list of conditions and the following disclaimer.
00024
00025 4. Redistributions in binary form must reproduce the above copyright notice,
00026 this list of conditions and the following disclaimer in the documentation and/or
00027 other materials provided with the distribution.
00028
00029 5. Usage of the binary form on proprietary applications shall require explicit
00030 prior written permission from the the copyright holders.
00031
00032 6. Neither the name of the copyright holder nor the names of its contributors
00033 may be used to endorse or promote products derived from this software without
00034 specific prior written permission.
00035
00036 The copyright holders provide no reassurances that the source code provided does
00037 not infringe any patent, copyright, or any other intellectual property rights of
00038 third parties. The copyright holders disclaim any liability to any recipient for
00039 claims brought against recipient by any third party for infringement of that
00040 parties intellectual property rights.
00041
00042 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00043 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00044 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00045 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00046 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00047 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00048 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00049 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00050 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00051 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00052 */
00053
```

```
00054 #if __cplusplus == 201103L
00055
00056 #include <iostream>
00057
00058 #include "mtk.h"
00059
00060 void Test1() {
00061     mtk::Tools::BeginTestNo(1);
00062     mtk::Div1D div2;
00063     bool info = div2.ConstructDiv1D();
00064     if (!info) {
00065         std::cerr << "Mimetic div (2nd order) could not be built." << std::endl;
00066     }
00067     std::cout << div2 << std::endl;
00068     mtk::Tools::EndTestNo(1);
00069 }
00070
00071 void Test2() {
00072     mtk::Tools::BeginTestNo(2);
00073     mtk::Div1D div4;
00074     bool info = div4.ConstructDiv1D(4);
00075     if (!info) {
00076         std::cerr << "Mimetic div (4th order) could not be built." << std::endl;
00077     }
00078     std::cout << div4 << std::endl;
00079     mtk::Tools::EndTestNo(2);
00080 }
00081
00082 void Test3() {
00083     mtk::Tools::BeginTestNo(3);
00084     mtk::Div1D div6;
00085     bool info = div6.ConstructDiv1D(6);
00086     if (!info) {
00087         std::cerr << "Mimetic div (6th order) could not be built." << std::endl;
00088     }
00089     std::cout << div6 << std::endl;
00090     mtk::Tools::EndTestNo(3);
00091 }
00092
00093 void Test4() {
00094     mtk::Tools::BeginTestNo(4);
00095     mtk::Div1D div8;
00096     bool info = div8.ConstructDiv1D(8);
00097     if (!info) {
00098         std::cerr << "Mimetic div (8th order) could not be built." << std::endl;
00099     }
00100     std::cout << div8 << std::endl;
00101     mtk::Tools::EndTestNo(4);
00102 }
00103
00104 void Test5() {
00105     mtk::Tools::BeginTestNo(5);
00106     mtk::Div1D div10;
00107     bool info = div10.ConstructDiv1D(10);
```

```

00135
00136     if (!info) {
00137         std::cerr << "Mimetic div (10th order) could not be built." << std::endl;
00138     }
00139
00140     std::cout << div10 << std::endl;
00141
00142     mtk::Tools::EndTestNo(5);
00143 }
00144
00145 void Test6() {
00146
00147     mtk::Tools::BeginTestNo(6);
00148
00149     mtk::Div1D div12;
00150
00151     bool info = div12.ConstructDiv1D(12);
00152
00153     if (!info) {
00154         std::cerr << "Mimetic div (12th order) could not be built." << std::endl;
00155     }
00156
00157     std::cout << div12 << std::endl;
00158
00159     mtk::Tools::EndTestNo(6);
00160 }
00161
00162 void Test7() {
00163
00164     mtk::Tools::BeginTestNo(7);
00165
00166     mtk::Div1D div14;
00167
00168     bool info = div14.ConstructDiv1D(14);
00169
00170     if (!info) {
00171         std::cerr << "Mimetic div (14th order) could not be built." << std::endl;
00172     }
00173
00174     std::cout << div14 << std::endl;
00175
00176     mtk::Tools::EndTestNo(7);
00177 }
00178
00179 void Test8() {
00180
00181     mtk::Tools::BeginTestNo(8);
00182
00183     mtk::Div1D div2;
00184
00185     bool info = div2.ConstructDiv1D();
00186
00187     if (!info) {
00188         std::cerr << "Mimetic div (2nd order) could not be built." << std::endl;
00189     }
00190
00191     std::cout << div2 << std::endl;
00192
00193     mtk::UniStgGrid1D grid(0.0, 1.0, 5);
00194
00195     std::cout << grid << std::endl;
00196
00197     mtk::DenseMatrix div2m(div2.ReturnAsDenseMatrix(grid));
00198
00199     std::cout << div2m << std::endl;
00200
00201     mtk::Tools::EndTestNo(8);
00202 }
00203
00204 void Test9() {
00205
00206     mtk::Tools::BeginTestNo(9);
00207
00208     mtk::Div1D div4;
00209
00210     bool info = div4.ConstructDiv1D(4);
00211
00212     if (!info) {
00213         std::cerr << "Mimetic div (4th order) could not be built." << std::endl;
00214     }
00215

```



```

00216     std::cout << div4 << std::endl;
00217
00218     mtk::UniStgGrid1D grid(0.0, 1.0, 11);
00219
00220     std::cout << grid << std::endl;
00221
00222     mtk::DenseMatrix div4m(div4.ReturnAsDenseMatrix(grid));
00223
00224     std::cout << div4m << std::endl;
00225
00226     mtk::Tools::EndTestNo(9);
00227 }
00228
00229 int main () {
00230
00231     std::cout << "Testing mtk::Div1D class." << std::endl;
00232
00233     Test1();
00234     Test2();
00235     Test3();
00236     Test4();
00237     Test5();
00238     Test6();
00239     Test7();
00240     Test8();
00241     Test9();
00242 }
00243
00244 #else
00245 #include <iostream>
00246 using std::cout;
00247 using std::endl;
00248 int main () {
00249     cout << "This code HAS to be compiled with support for C++11." << endl;
00250     cout << "Exiting..." << endl;
00251 }
00252 #endif


```

17.61 tests/mtk_glpk_adapter_test.cc File Reference

Test file for the `mtk::GLPKAdapter` class.

```
#include <iostream>
```

Include dependency graph for `mtk_glpk_adapter_test.cc`:



Functions

- int `main` ()

17.61.1 Detailed Description

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Todo Test the `mtk::GLPKAdapter` class.

Definition in file `mtk_glpk_adapter_test.cc`.

17.61.2 Function Documentation

17.61.2.1 `int main ()`

Definition at line 81 of file `mtk_glpk_adapter_test.cc`.

17.62 `mtk_glpk_adapter_test.cc`

```

00001
00010 /*
00011 Copyright (C) 2015, Computational Science Research Center, San Diego State
00012 University. All rights reserved.
00013
00014 Redistribution and use in source and binary forms, with or without modification,
00015 are permitted provided that the following conditions are met:
00016
00017 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00018 and a copy of the modified files should be reported once modifications are
00019 completed. Documentation related to said modifications should be included.
00020
00021 2. Redistributions of source code must be done through direct
00022 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00023
00024 3. Redistributions of source code must retain the above copyright notice, this
00025 list of conditions and the following disclaimer.
00026
00027 4. Redistributions in binary form must reproduce the above copyright notice,
00028 this list of conditions and the following disclaimer in the documentation and/or
00029 other materials provided with the distribution.
00030
00031 5. Usage of the binary form on proprietary applications shall require explicit
00032 prior written permission from the the copyright holders.
00033
00034 6. Neither the name of the copyright holder nor the names of its contributors
00035 may be used to endorse or promote products derived from this software without
00036 specific prior written permission.
00037
00038 The copyright holders provide no reassurances that the source code provided does
00039 not infringe any patent, copyright, or any other intellectual property rights of
00040 third parties. The copyright holders disclaim any liability to any recipient for
00041 claims brought against recipient by any third party for infringement of that
00042 parties intellectual property rights.
00043
00044 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00045 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00046 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00047 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00048 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00049 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00050 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00051 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00052 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00053 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00054 */
00055
00056 #if __cplusplus == 201103L
00057
00058 #include <iostream>
00059 #include <ctime>

```

```

00060
00061 #include "mtk.h"
00062
00063 void Test1() {
00064     mtk::Tools::BeginTestNo(1);
00065     mtk::Tools::EndTestNo(1);
00066 }
00067
00068
00069 int main () {
00070     std::cout << "Testing mtk::GLPKAdapter class." << std::endl;
00071     Test1();
00072 }
00073
00074 #else
00075 #include <iostream>
00076 using std::cout;
00077 using std::endl;
00078
00079 int main () {
00080     cout << "This code HAS to be compiled with support for C++11." << endl;
00081     cout << "Exiting..." << endl;
00082 }
00083
00084 #endif


```

17.63 tests/mtk_grad_1d_test.cc File Reference

Testing the mimetic 1D gradient, constructed with the CBS algorithm.

```
#include <iostream>
```

Include dependency graph for mtk_grad_1d_test.cc:



Functions

- int [main](#) ()

17.63.1 Detailed Description

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_grad_1d_test.cc](#).

17.63.2 Function Documentation

17.63.2.1 `int main ()`

Definition at line 186 of file [mtk_grad_1d_test.cc](#).

17.64 `mtk_grad_1d_test.cc`

```

00001
00008 /*
00009 Copyright (C) 2015, Computational Science Research Center, San Diego State
00010 University. All rights reserved.
00011
00012 Redistribution and use in source and binary forms, with or without modification,
00013 are permitted provided that the following conditions are met:
00014
00015 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00016 and a copy of the modified files should be reported once modifications are
00017 completed. Documentation related to said modifications should be included.
00018
00019 2. Redistributions of source code must be done through direct
00020 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00021
00022 3. Redistributions of source code must retain the above copyright notice, this
00023 list of conditions and the following disclaimer.
00024
00025 4. Redistributions in binary form must reproduce the above copyright notice,
00026 this list of conditions and the following disclaimer in the documentation and/or
00027 other materials provided with the distribution.
00028
00029 5. Usage of the binary form on proprietary applications shall require explicit
00030 prior written permission from the the copyright holders.
00031
00032 6. Neither the name of the copyright holder nor the names of its contributors
00033 may be used to endorse or promote products derived from this software without
00034 specific prior written permission.
00035
00036 The copyright holders provide no reassurances that the source code provided does
00037 not infringe any patent, copyright, or any other intellectual property rights of
00038 third parties. The copyright holders disclaim any liability to any recipient for
00039 claims brought against recipient by any third party for infringement of that
00040 parties intellectual property rights.
00041
00042 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00043 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00044 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00045 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00046 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00047 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00048 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00049 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00050 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00051 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00052 */
00053
00054 #if __cplusplus == 201103L
00055
00056 #include <iostream>
00057
00058 #include "mtk.h"
00059
00060 void Test1() {
00061
00062     mtk::Tools::BeginTestNo(1);
00063
00064     mtk::Grad1D grad2;
00065
00066     bool info = grad2.ConstructGrad1D();
00067
00068     if (!info) {
00069         std::cerr << "Mimetic grad (2nd order) could not be built." << std::endl;
00070     }
00071
00072     std::cout << grad2 << std::endl;
00073

```

```

00074   mtk::Tools::EndTestNo(1);
00075 }
00076
00077 void Test2() {
00078
00079   mtk::Tools::BeginTestNo(2);
00080
00081   mtk::Grad1D grad4;
00082
00083   bool info = grad4.ConstructGrad1D(4);
00084
00085   if (!info) {
00086     std::cerr << "Mimetic grad (4th order) could not be built." << std::endl;
00087   }
00088
00089   std::cout << grad4 << std::endl;
00090
00091   mtk::Tools::EndTestNo(2);
00092 }
00093
00094 void Test3() {
00095
00096   mtk::Tools::BeginTestNo(3);
00097
00098   mtk::Grad1D grad6;
00099
00100   bool info = grad6.ConstructGrad1D(6);
00101
00102   if (!info) {
00103     std::cerr << "Mimetic grad (6th order) could not be built." << std::endl;
00104   }
00105
00106   std::cout << grad6 << std::endl;
00107
00108   mtk::Tools::EndTestNo(3);
00109 }
00110
00111 void Test4() {
00112
00113   mtk::Tools::BeginTestNo(4);
00114
00115   mtk::Grad1D grad8;
00116
00117   bool info = grad8.ConstructGrad1D(8);
00118
00119   if (!info) {
00120     std::cerr << "Mimetic grad (8th order) could not be built." << std::endl;
00121   }
00122
00123   std::cout << grad8 << std::endl;
00124
00125   mtk::Tools::EndTestNo(4);
00126 }
00127
00128 void Test5() {
00129
00130   mtk::Tools::BeginTestNo(5);
00131
00132   mtk::Grad1D grad10;
00133
00134   bool info = grad10.ConstructGrad1D(10);
00135
00136   if (!info) {
00137     std::cerr << "Mimetic grad (10th order) could not be built." << std::endl;
00138   }
00139
00140   std::cout << grad10 << std::endl;
00141
00142   mtk::Tools::EndTestNo(5);
00143 }
00144
00145 void Test6() {
00146
00147   mtk::Tools::BeginTestNo(6);
00148
00149   mtk::Grad1D grad2;
00150
00151   bool info = grad2.ConstructGrad1D();
00152
00153   if (!info) {
00154     std::cerr << "Mimetic grad (2nd order) could not be built." << std::endl;

```

```


00155     }
00156
00157     std::cout << grad2 << std::endl;
00158
00159     mtk::UniStgGrid1D grid(0.0, 1.0, 5);
00160
00161     std::cout << grid << std::endl;
00162
00163     mtk::DenseMatrix grad2m(grad2.ReturnAsDenseMatrix(grid));
00164
00165     std::cout << grad2m << std::endl;
00166
00167     mtk::Tools::EndTestNo(6);
00168 }
00169
00170 int main () {
00171
00172     std::cout << "Testing mtk::Grad1D class." << std::endl;
00173
00174     Test1();
00175     Test2();
00176     Test3();
00177     Test4();
00178     Test5();
00179     Test6();
00180 }
00181
00182 #else
00183 #include <iostream>
00184 using std::cout;
00185 using std::endl;
00186 int main () {
00187     cout << "This code HAS to be compiled with support for C++11." << endl;
00188     cout << "Exiting..." << endl;
00189 }
00190 #endif

```

17.65 tests/mtk_lap_1d_test.cc File Reference

```
#include <iostream>
```

Include dependency graph for mtk_lap_1d_test.cc:



Functions

- int `main` ()

17.65.1 Function Documentation

17.65.1.1 int main ()

Definition at line 156 of file [mtk_lap_1d_test.cc](#).

17.66 mtk_lap_1d_test.cc

```

00001 #if __cplusplus == 201103L
00002
00003 #include <iostream>
00004
00005 #include "mtk.h"
00006
00007 void Test1() {
00008
00009     mtk::Tools::BeginTestNo(1);
00010
00011     mtk::Lap1D lap2;
00012
00013     bool info = lap2.ConstructLap1D();
00014
00015     if (!info) {
00016         std::cerr << "Mimetic lap (2nd order) could not be built." << std::endl;
00017     }
00018
00019     mtk::Tools::EndTestNo(1);
00020 }
00021
00022 void Test2() {
00023
00024     mtk::Tools::BeginTestNo(2);
00025
00026     mtk::Lap1D lap4;
00027
00028     bool info = lap4.ConstructLap1D(4);
00029
00030     if (!info) {
00031         std::cerr << "Mimetic lap (4th order) could not be built." << std::endl;
00032     }
00033
00034     mtk::Tools::EndTestNo(2);
00035 }
00036
00037 void Test3() {
00038
00039     mtk::Tools::BeginTestNo(3);
00040
00041     mtk::Lap1D lap6;
00042
00043     bool info = lap6.ConstructLap1D(6);
00044
00045     if (!info) {
00046         std::cerr << "Mimetic lap (6th order) could not be built." << std::endl;
00047     }
00048
00049     mtk::Tools::EndTestNo(3);
00050 }
00051
00052 void Test4() {
00053
00054     mtk::Tools::BeginTestNo(4);
00055
00056     mtk::Lap1D lap8;
00057
00058     bool info = lap8.ConstructLap1D(8);
00059
00060     if (!info) {
00061         std::cerr << "Mimetic lap (8th order) could not be built." << std::endl;
00062     }
00063
00064     mtk::Tools::EndTestNo(4);
00065 }
00066
00067 void Test5() {
00068
00069     mtk::Tools::BeginTestNo(5);
00070

```

```

00071     mtk::Lap1D lap10;
00072
00073     bool info = lap10.ConstructLap1D(10);
00074
00075     if (!info) {
00076         std::cerr << "Mimetic lap (10th order) could not be built." << std::endl;
00077     }
00078
00079     mtk::Tools::EndTestNo(5);
00080 }
00081
00082 void Test6() {
00083
00084     mtk::Tools::BeginTestNo(6);
00085
00086     mtk::Lap1D lap12;
00087
00088     bool info = lap12.ConstructLap1D(12);
00089
00090     if (!info) {
00091         std::cerr << "Mimetic lap (12th order) could not be built." << std::endl;
00092     }
00093
00094     mtk::Tools::EndTestNo(6);
00095 }
00096
00097 void Test7() {
00098
00099     mtk::Tools::BeginTestNo(7);
00100
00101     mtk::Lap1D lap4;
00102
00103     bool info = lap4.ConstructLap1D(4);
00104
00105     if (!info) {
00106         std::cerr << "Mimetic lap (4th order) could not be built." << std::endl;
00107     }
00108
00109     std::cout << lap4 << std::endl;
00110     std::cout << std::endl;
00111
00112     mtk::Tools::EndTestNo(7);
00113 }
00114
00115 void Test8() {
00116
00117     mtk::Tools::BeginTestNo(8);
00118
00119     mtk::Lap1D lap4;
00120
00121     bool info = lap4.ConstructLap1D(4);
00122
00123     if (!info) {
00124         std::cerr << "Mimetic lap (4th order) could not be built." << std::endl;
00125     }
00126
00127     std::cout << lap4 << std::endl;
00128     std::cout << std::endl;
00129
00130     mtk::UniStgGrid1D aux(0.0, 1.0, 11);
00131
00132     mtk::DenseMatrix lap4_m(lap4.ReturnAsDenseMatrix(aux));
00133
00134     std::cout << lap4_m << std::endl;
00135     std::cout << std::endl;
00136
00137     mtk::Tools::EndTestNo(8);
00138 }
00139
00140 int main () {
00141
00142     std::cout << "Testing MTK 1D Laplacian" << std::endl;
00143
00144     Test1();
00145     Test2();
00146     Test3();
00147     Test4();
00148     Test5();
00149     Test6();
00150     Test7();
00151     Test8();

```




```
00152 }
00153
00154 #else
00155 #include <iostream>
00156 int main () {
00157     std::cout << "This code HAS to be compiled to support C++11." << std::endl;
00158     std::cout << "Exiting..." << std::endl;
00159 }
00160 #endif
```

17.67 tests/mtk_lapack_adapter_test.cc File Reference

Test file for the [mtk::LAPACKAdapter](#) class.

```
#include <iostream>
```

Include dependency graph for mtk_lapack_adapter_test.cc:



Functions

- `int main ()`

17.67.1 Detailed Description

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Todo Test the [mtk::LAPACKAdapter](#) class.

Definition in file [mtk_lapack_adapter_test.cc](#).

17.67.2 Function Documentation

17.67.2.1 `int main ()`

Definition at line [81](#) of file [mtk_lapack_adapter_test.cc](#).

17.68 mtk_lapack_adapter_test.cc

```

00001
00010 /*
00011 Copyright (C) 2015, Computational Science Research Center, San Diego State
00012 University. All rights reserved.
00013
00014 Redistribution and use in source and binary forms, with or without modification,
00015 are permitted provided that the following conditions are met:
00016
00017 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00018 and a copy of the modified files should be reported once modifications are
00019 completed. Documentation related to said modifications should be included.
00020
00021 2. Redistributions of source code must be done through direct
00022 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00023
00024 3. Redistributions of source code must retain the above copyright notice, this
00025 list of conditions and the following disclaimer.
00026
00027 4. Redistributions in binary form must reproduce the above copyright notice,
00028 this list of conditions and the following disclaimer in the documentation and/or
00029 other materials provided with the distribution.
00030
00031 5. Usage of the binary form on proprietary applications shall require explicit
00032 prior written permission from the the copyright holders.
00033
00034 6. Neither the name of the copyright holder nor the names of its contributors
00035 may be used to endorse or promote products derived from this software without
00036 specific prior written permission.
00037
00038 The copyright holders provide no reassurances that the source code provided does
00039 not infringe any patent, copyright, or any other intellectual property rights of
00040 third parties. The copyright holders disclaim any liability to any recipient for
00041 claims brought against recipient by any third party for infringement of that
00042 parties intellectual property rights.
00043
00044 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00045 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00046 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00047 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00048 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00049 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00050 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00051 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00052 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00053 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00054 */
00055
00056 #if __cplusplus == 201103L
00057
00058 #include <iostream>
00059 #include <ctime>
00060
00061 #include "mtk.h"
00062
00063 void Test1() {
00064
00065     mtk::Tools::BeginTestNo(1);
00066
00067     mtk::Tools::EndTestNo(1);
00068 }
00069
00070 int main () {
00071
00072     std::cout << "Testing mtk::LAPACKAdapter class." << std::endl;
00073
00074     Test1();
00075 }
00076
00077 #else
00078 #include <iostream>
00079 using std::cout;
00080 using std::endl;
00081 int main () {
00082     cout << "This code HAS to be compiled with support for C++11." << endl;
00083     cout << "Exiting..." << endl;
00084 }
00085 #endif


```

17.69 tests/mtk_uni_stg_grid_1d_test.cc File Reference

Test file for the [mtk::UniStgGrid1D](#) class.

```
#include <iostream>
```

Include dependency graph for mtk_uni_stg_grid_1d_test.cc:



Functions

- int [main](#) ()

17.69.1 Detailed Description

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_uni_stg_grid_1d_test.cc](#).

17.69.2 Function Documentation

17.69.2.1 int main ()

Definition at line [164](#) of file [mtk_uni_stg_grid_1d_test.cc](#).

17.70 mtk_uni_stg_grid_1d_test.cc

```
00001
00008 /*
00009 Copyright (C) 2015, Computational Science Research Center, San Diego State
00010 University. All rights reserved.
00011
00012 Redistribution and use in source and binary forms, with or without modification,
00013 are permitted provided that the following conditions are met:
00014
00015 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00016 and a copy of the modified files should be reported once modifications are
00017 completed. Documentation related to said modifications should be included.
```

```

00018
00019 2. Redistributions of source code must be done through direct
00020 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00021
00022 3. Redistributions of source code must retain the above copyright notice, this
00023 list of conditions and the following disclaimer.
00024
00025 4. Redistributions in binary form must reproduce the above copyright notice,
00026 this list of conditions and the following disclaimer in the documentation and/or
00027 other materials provided with the distribution.
00028
00029 5. Usage of the binary form on proprietary applications shall require explicit
00030 prior written permission from the the copyright holders.
00031
00032 6. Neither the name of the copyright holder nor the names of its contributors
00033 may be used to endorse or promote products derived from this software without
00034 specific prior written permission.
00035
00036 The copyright holders provide no reassurances that the source code provided does
00037 not infringe any patent, copyright, or any other intellectual property rights of
00038 third parties. The copyright holders disclaim any liability to any recipient for
00039 claims brought against recipient by any third party for infringement of that
00040 parties intellectual property rights.
00041
00042 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00043 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00044 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00045 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00046 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00047 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00048 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00049 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00050 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00051 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00052 */
00053
00054 #if __cplusplus == 201103L
00055
00056 #include <iostream>
00057 #include <ctime>
00058
00059 #include "mtk.h"
00060
00061 void Test1() {
00062
00063     mtk::Tools::BeginTestNo(1);
00064
00065     mtk::UniStgGrid1D gg;
00066
00067     std::cout << gg << std::endl;
00068
00069     mtk::Tools::EndTestNo(1);
00070 }
00071
00072 mtk::Real ScalarFieldOne(mtk::Real xx) {
00073
00074     return 2.0*xx;
00075 }
00076
00077 void Test2() {
00078
00079     mtk::Tools::BeginTestNo(2);
00080
00081     mtk::Real aa = 0.0;
00082     mtk::Real bb = 1.0;
00083
00084     int nn = 5;
00085
00086     mtk::UniStgGrid1D gg(aa, bb, nn);
00087
00088     std::cout << gg << std::endl;
00089
00090     gg.BindScalarField(ScalarFieldOne);
00091
00092     std::cout << gg << std::endl;
00093
00094     mtk::Tools::EndTestNo(2);
00095 }
00096
00097 void Test3() {
00098

```

```

00099     mtk::Tools::BeginTestNo(3);
00100
00101     mtk::Real aa = 0.0;
00102     mtk::Real bb = 1.0;
00103
00104     int nn = 5;
00105
00106     mtk::UniStgGrid1D gg(aa, bb, nn);
00107
00108     std::cout << gg << std::endl;
00109
00110     gg.BindScalarField(ScalarFieldOne);
00111
00112     std::cout << gg << std::endl;
00113
00114     if(!gg.WriteToFile("mtk_uni_stg_grid_1d_test_03.dat", "x", "u(x)")) {
00115         std::cerr << "Error writing to file." << std::endl;
00116     }
00117
00118     mtk::Tools::EndTestNo(3);
00119 }
00120
00121 mtk::Real VectorFieldXComponentOne(mtk::Real xx) {
00122
00123     return xx*xx;
00124 }
00125
00126 void Test4() {
00127
00128     mtk::Tools::BeginTestNo(4);
00129
00130     mtk::Real aa = 0.0;
00131     mtk::Real bb = 1.0;
00132
00133     int nn = 20;
00134
00135     mtk::UniStgGrid1D gg(aa, bb, nn, mtk::VECTOR);
00136
00137     std::cout << gg << std::endl;
00138
00139     gg.BindVectorField(VectorFieldXComponentOne);
00140
00141     std::cout << gg << std::endl;
00142
00143     if(!gg.WriteToFile("mtk_uni_stg_grid_1d_test_04.dat", "x", "v(x)")) {
00144         std::cerr << "Error writing to file." << std::endl;
00145     }
00146
00147     mtk::Tools::EndTestNo(4);
00148 }
00149
00150 int main () {
00151
00152     std::cout << "Testing mtk::UniStgGrid1D class." << std::endl;
00153
00154     Test1();
00155     Test2();
00156     Test3();
00157     Test4();
00158 }
00159
00160 #else
00161 #include <iostream>
00162 using std::cout;
00163 using std::endl;
00164 int main () {
00165     cout << "This code HAS to be compiled with support for C++11." << endl;
00166     cout << "Exiting..." << endl;
00167 }
00168 #endif

```

Index

- ~DenseMatrix
 - mtk::DenseMatrix, [57](#)
- ~Div1D
 - mtk::Div1D, [69](#)
- ~Grad1D
 - mtk::Grad1D, [82](#)
- ~Lap1D
 - mtk::Lap1D, [91](#)
- ~Matrix
 - mtk::Matrix, [104](#)
- ~Quad1D
 - mtk::Quad1D, [117](#)
- ~UniStgGrid1D
 - mtk::UniStgGrid1D, [125](#)
- abs_density
 - mtk::Matrix, [104](#)
- abs_density_
 - mtk::Matrix, [114](#)
- abs_sparsity
 - mtk::Matrix, [104](#)
- abs_sparsity_
 - mtk::Matrix, [114](#)
- AssembleOperator
 - mtk::Div1D, [70](#)
 - mtk::Grad1D, [83](#)
- BANDED
 - Enumerations., [32](#)
- bandwidth
 - mtk::Matrix, [104](#)
- bandwidth_
 - mtk::Matrix, [114](#)
- begin_time_
 - mtk::Tools, [121](#)
- BeginTestNo
 - mtk::Tools, [119](#)
- BindScalarField
 - mtk::UniStgGrid1D, [126](#)
- BindVectorField
 - mtk::UniStgGrid1D, [126](#)
- COL_MAJOR
 - Enumerations., [31](#)
- CRS
 - Enumerations., [32](#)
- coeffs_interior_
 - mtk::Div1D, [75](#)
 - mtk::Grad1D, [88](#)
- ComputePreliminaryApproximations
 - mtk::Div1D, [70](#)
 - mtk::Grad1D, [83](#)
- ComputeRationalBasisNullSpace
 - mtk::Div1D, [70](#)
 - mtk::Grad1D, [83](#)
- ComputeStencilBoundaryGrid
 - mtk::Div1D, [71](#)
 - mtk::Grad1D, [84](#)
- ComputeStencilInteriorGrid
 - mtk::Div1D, [71](#)
 - mtk::Grad1D, [84](#)
- ComputeWeights
 - mtk::Div1D, [72](#)
 - mtk::Grad1D, [85](#)
- ConstructDiv1D
 - mtk::Div1D, [72](#)
- ConstructGrad1D
 - mtk::Grad1D, [85](#)
- ConstructLap1D
 - mtk::Lap1D, [91](#)
- DENSE
 - Enumerations., [32](#)
- Data
 - mtk::Lap1D, [92](#)
- data
 - mtk::DenseMatrix, [57](#)
- Data structures., [34](#)
- data_
 - mtk::DenseMatrix, [66](#)
- degree_approximation
 - mtk::Quad1D, [117](#)
- degree_approximation_
 - mtk::Quad1D, [118](#)
- delta_x
 - mtk::UniStgGrid1D, [127](#)
- delta_x_
 - mtk::UniStgGrid1D, [128](#)
- DenseMatrix
 - mtk::DenseMatrix, [54–56](#)
- dim_null_
 - mtk::Div1D, [75](#)

- mtk::Grad1D, [88](#)
- discrete_domain_x
 - mtk::UniStgGrid1D, [127](#)
- discrete_domain_x_
 - mtk::UniStgGrid1D, [128](#)
- discrete_field_u
 - mtk::UniStgGrid1D, [127](#)
- discrete_field_u_
 - mtk::UniStgGrid1D, [129](#)
- Div1D
 - mtk::Div1D, [69](#)
- divergence_
 - mtk::Div1D, [75](#)
- divergence_length_
 - mtk::Div1D, [75](#)
- east_bndy_x_
 - mtk::UniStgGrid1D, [129](#)
- EndTestNo
 - mtk::Tools, [120](#)
- Enumerations., [31](#)
 - BANDED, [32](#)
 - COL_MAJOR, [31](#)
 - CRS, [32](#)
 - DENSE, [32](#)
 - FieldNature, [31](#)
 - MatrixOrdering, [31](#)
 - MatrixStorage, [31](#)
 - ROW_MAJOR, [31](#)
 - SCALAR, [31](#)
 - VECTOR, [31](#)
- examples/poisson_1d/poisson_1d.cc, [131](#), [132](#)
- Execution tools., [33](#)
- FieldNature
 - Enumerations., [31](#)
- GetValue
 - mtk::DenseMatrix, [58](#)
- Grad1D
 - mtk::Grad1D, [82](#)
- gradient_
 - mtk::Grad1D, [88](#)
- gradient_length_
 - mtk::Grad1D, [88](#)
- Grids., [36](#)
- include/mtk.h, [135](#), [136](#)
- include/mtk_blas_adapter.h, [137](#), [139](#)
- include/mtk_dense_matrix.h, [140](#), [141](#)
- include/mtk_div_1d.h, [143](#), [144](#)
- include/mtk_enums.h, [146](#)
- include/mtk_glpk_adapter.h, [147](#), [149](#)
- include/mtk_grad_1d.h, [150](#), [151](#)
- include/mtk_lap_1d.h, [153](#), [154](#)
- include/mtk_lapack_adapter.h, [155](#), [156](#)
- include/mtk_matrix.h, [157](#), [159](#)
- include/mtk_quad_1d.h, [160](#), [162](#)
- include/mtk_roots.h, [163](#), [164](#)
- include/mtk_tools.h, [165](#), [166](#)
- include/mtk_uni_stg_grid_1d.h, [167](#), [168](#)
- IncreaseNumNull
 - mtk::Matrix, [104](#)
- IncreaseNumZero
 - mtk::Matrix, [104](#)
- Integrate
 - mtk::Quad1D, [117](#)
- kCriticalOrderAccuracyDiv
 - Roots., [30](#)
- kCriticalOrderAccuracyGrad
 - Roots., [30](#)
- kDefaultMimeticThreshold
 - Roots., [30](#)
- kDefaultOrderAccuracy
 - Roots., [30](#)
- kDefaultTolerance
 - Roots., [30](#)
- kOne
 - Roots., [30](#)
- kZero
 - Roots., [30](#)
- kl
 - mtk::Matrix, [105](#)
- kl_
 - mtk::Matrix, [114](#)
- Kron
 - mtk::DenseMatrix, [59](#)
- ku
 - mtk::Matrix, [105](#)
- ku_
 - mtk::Matrix, [114](#)
- Lap1D
 - mtk::Lap1D, [91](#)
- laplacian_
 - mtk::Lap1D, [94](#)
- laplacian_length_
 - mtk::Lap1D, [94](#)
- ld
 - mtk::Matrix, [105](#)
- ld_
 - mtk::Matrix, [114](#)
- main
 - mtk_blas_adapter_test.cc, [249](#)
 - mtk_dense_matrix_test.cc, [251](#)
 - mtk_div_1d_test.cc, [256](#)
 - mtk_glpk_adapter_test.cc, [260](#)
 - mtk_grad_1d_test.cc, [262](#)

- mtk_lap_1d_test.cc, 264
 - mtk_lapack_adapter_test.cc, 267
 - mtk_uni_stg_grid_1d_test.cc, 269
 - poisson_1d.cc, 132
- Makefile.inc, 170
- Matrix
 - mtk::Matrix, 102
- matrix_properties
 - mtk::DenseMatrix, 60
- matrix_properties_
 - mtk::DenseMatrix, 66
- MatrixOrdering
 - Enumerations., 31
- MatrixStorage
 - Enumerations., 31
- mim_bndy_
 - mtk::Div1D, 75
 - mtk::Grad1D, 88
- Mimetic operators., 37
- mimetic_threshold_
 - mtk::Div1D, 75
 - mtk::Grad1D, 88
 - mtk::Lap1D, 94
- minrow_
 - mtk::Div1D, 75
 - mtk::Grad1D, 88
- mtk, 39
 - operator<<, 41
 - sgels_, 42
 - sgemm_, 43
 - sgemv_, 43
 - sgeqrf_, 43
 - sgesv_, 44
 - snrm2_, 44
 - sormqr_, 44
- mtk::BLASAdapter, 47
 - RealDenseMM, 48
 - RealDenseMV, 49
 - RealNRM2, 50
- mtk::DenseMatrix, 51
 - ~DenseMatrix, 57
 - data, 57
 - data_, 66
 - DenseMatrix, 54–56
 - GetValue, 58
 - Kron, 59
 - matrix_properties, 60
 - matrix_properties_, 66
 - num_cols, 60
 - num_rows, 61
 - operator<<, 66
 - operator=, 62
 - OrderColMajor, 63
 - OrderRowMajor, 63
 - SetOrdering, 64
 - SetValue, 64
 - Transpose, 65
- mtk::Div1D, 66
 - ~Div1D, 69
 - AssembleOperator, 70
 - coeffs_interior_, 75
 - ComputePreliminaryApproximations, 70
 - ComputeRationalBasisNullSpace, 70
 - ComputeStencilBoundaryGrid, 71
 - ComputeStencilInteriorGrid, 71
 - ComputeWeights, 72
 - ConstructDiv1D, 72
 - dim_null_, 75
 - Div1D, 69
 - divergence_, 75
 - divergence_length_, 75
 - mim_bndy_, 75
 - mimetic_threshold_, 75
 - minrow_, 75
 - num_bndy_coeffs, 73
 - num_bndy_coeffs_, 75
 - operator<<, 75
 - order_accuracy_, 76
 - prem_apps_, 76
 - rat_basis_null_space_, 76
 - ReturnAsDenseMatrix, 73
 - row_, 76
 - weights_cbs, 74
 - weights_cbs_, 76
 - weights_crs, 74
 - weights_crs_, 76
- mtk::GLPKAdapter, 76
 - SolveSimplexAndCompare, 77
- mtk::Grad1D, 79
 - ~Grad1D, 82
 - AssembleOperator, 83
 - coeffs_interior_, 88
 - ComputePreliminaryApproximations, 83
 - ComputeRationalBasisNullSpace, 83
 - ComputeStencilBoundaryGrid, 84
 - ComputeStencilInteriorGrid, 84
 - ComputeWeights, 85
 - ConstructGrad1D, 85
 - dim_null_, 88
 - Grad1D, 82
 - gradient_, 88
 - gradient_length_, 88
 - mim_bndy_, 88
 - mimetic_threshold_, 88
 - minrow_, 88
 - num_bndy_approxs_, 88
 - num_bndy_coeffs, 86
 - num_bndy_coeffs_, 88

- operator<<, 88
- order_accuracy_, 89
- prem_apps_, 89
- rat_basis_null_space_, 89
- ReturnAsDenseMatrix, 86
- row_, 89
- weights_cbs, 87
- weights_cbs_, 89
- weights_crs, 87
- weights_crs_, 89
- mtk::LAPACKAdapter, 94
 - QRFactorDenseMatrix, 95
 - SolveDenseSystem, 96, 97
 - SolveRectangularDenseSystem, 98
- mtk::Lap1D, 89
 - ~Lap1D, 91
 - ConstructLap1D, 91
 - Data, 92
 - Lap1D, 91
 - laplacian_, 94
 - laplacian_length_, 94
 - mimetic_threshold_, 94
 - operator<<, 94
 - order_accuracy_, 94
 - ReturnAsDenseMatrix, 93
- mtk::Matrix, 99
 - ~Matrix, 104
 - abs_density, 104
 - abs_density_, 114
 - abs_sparsity, 104
 - abs_sparsity_, 114
 - bandwidth, 104
 - bandwidth_, 114
 - IncreaseNumNull, 104
 - IncreaseNumZero, 104
 - kl, 105
 - kl_, 114
 - ku, 105
 - ku_, 114
 - ld, 105
 - ld_, 114
 - Matrix, 102
 - num_cols, 105
 - num_cols_, 114
 - num_non_null, 106
 - num_non_null_, 114
 - num_non_zero, 106
 - num_non_zero_, 114
 - num_null, 106
 - num_null_, 115
 - num_rows, 107
 - num_rows_, 115
 - num_values, 107
 - num_values_, 115
- num_zero, 107
- num_zero_, 115
- ordering, 108
- ordering_, 115
- rel_density, 108
- rel_density_, 115
- rel_sparsity, 109
- rel_sparsity_, 115
- set_num_cols, 109
- set_num_null, 109
- set_num_rows, 110
- set_num_zero, 111
- set_ordering, 111
- set_storage, 112
- storage, 113
- storage_, 115
- mtk::Quad1D, 115
 - ~Quad1D, 117
 - degree_approximation, 117
 - degree_approximation_, 118
 - Integrate, 117
 - operator<<, 118
 - Quad1D, 117
 - weights, 118
 - weights_, 118
- mtk::Tools, 118
 - begin_time_, 121
 - BeginTestNo, 119
 - EndTestNo, 120
 - Prevent, 120
 - test_number_, 121
- mtk::UniStgGrid1D, 122
 - ~UniStgGrid1D, 125
 - BindScalarField, 126
 - BindVectorField, 126
 - delta_x, 127
 - delta_x_, 128
 - discrete_domain_x, 127
 - discrete_domain_x_, 128
 - discrete_field_u, 127
 - discrete_field_u_, 129
 - east_bndy_x_, 129
 - nature_, 129
 - num_cells_x, 127
 - num_cells_x_, 129
 - operator<<, 128
 - UniStgGrid1D, 125
 - west_bndy_x_, 129
 - WriteToFile, 128
- mtk_blas_adapter_test.cc
 - main, 249
- mtk_dense_matrix_test.cc
 - main, 251
- mtk_div_1d_test.cc

- main, 256
- mtk_glpk_adapter_test.cc
 - main, 260
- mtk_grad_1d_test.cc
 - main, 262
- mtk_lap_1d_test.cc
 - main, 264
- mtk_lapack_adapter_test.cc
 - main, 267
- mtk_uni_stg_grid_1d_test.cc
 - main, 269
- nature_
 - mtk::UniStgGrid1D, 129
- num_bndy_approxs_
 - mtk::Grad1D, 88
- num_bndy_coeffs
 - mtk::Div1D, 73
 - mtk::Grad1D, 86
- num_bndy_coeffs_
 - mtk::Div1D, 75
 - mtk::Grad1D, 88
- num_cells_x
 - mtk::UniStgGrid1D, 127
- num_cells_x_
 - mtk::UniStgGrid1D, 129
- num_cols
 - mtk::DenseMatrix, 60
 - mtk::Matrix, 105
- num_cols_
 - mtk::Matrix, 114
- num_non_null
 - mtk::Matrix, 106
- num_non_null_
 - mtk::Matrix, 114
- num_non_zero
 - mtk::Matrix, 106
- num_non_zero_
 - mtk::Matrix, 114
- num_null
 - mtk::Matrix, 106
- num_null_
 - mtk::Matrix, 115
- num_rows
 - mtk::DenseMatrix, 61
 - mtk::Matrix, 107
- num_rows_
 - mtk::Matrix, 115
- num_values
 - mtk::Matrix, 107
- num_values_
 - mtk::Matrix, 115
- num_zero
 - mtk::Matrix, 107
- num_zero_
 - mtk::Matrix, 115
- Numerical methods., 35
- operator<<
 - mtk, 41
 - mtk::DenseMatrix, 66
 - mtk::Div1D, 75
 - mtk::Grad1D, 88
 - mtk::Lap1D, 94
 - mtk::Quad1D, 118
 - mtk::UniStgGrid1D, 128
- operator=
 - mtk::DenseMatrix, 62
- order_accuracy_
 - mtk::Div1D, 76
 - mtk::Grad1D, 89
 - mtk::Lap1D, 94
- OrderColMajor
 - mtk::DenseMatrix, 63
- OrderRowMajor
 - mtk::DenseMatrix, 63
- ordering
 - mtk::Matrix, 108
- ordering_
 - mtk::Matrix, 115
- poisson_1d.cc
 - main, 132
- prem_apps_
 - mtk::Div1D, 76
 - mtk::Grad1D, 89
- Prevent
 - mtk::Tools, 120
- QRFactorDenseMatrix
 - mtk::LAPACKAdapter, 95
- Quad1D
 - mtk::Quad1D, 117
- ROW_MAJOR
 - Enumerations., 31
- README.md, 172
- rat_basis_null_space_
 - mtk::Div1D, 76
 - mtk::Grad1D, 89
- Real
 - Roots., 30
- RealDenseMM
 - mtk::BLASAdapter, 48
- RealDenseMV
 - mtk::BLASAdapter, 49
- RealNRM2
 - mtk::BLASAdapter, 50
- rel_density

- mtk::Matrix, 108
- rel_density_
 - mtk::Matrix, 115
- rel_sparsity_
 - mtk::Matrix, 109
- rel_sparsity_
 - mtk::Matrix, 115
- ReturnAsDenseMatrix
 - mtk::Div1D, 73
 - mtk::Grad1D, 86
 - mtk::Lap1D, 93
- Roots., 29
 - kCriticalOrderAccuracyDiv, 30
 - kCriticalOrderAccuracyGrad, 30
 - kDefaultMimeticThreshold, 30
 - kDefaultOrderAccuracy, 30
 - kDefaultTolerance, 30
 - kOne, 30
 - kZero, 30
 - Real, 30
- row_
 - mtk::Div1D, 76
 - mtk::Grad1D, 89
- SCALAR
 - Enumerations., 31
- set_num_cols
 - mtk::Matrix, 109
- set_num_null
 - mtk::Matrix, 109
- set_num_rows
 - mtk::Matrix, 110
- set_num_zero
 - mtk::Matrix, 111
- set_ordering
 - mtk::Matrix, 111
- set_storage
 - mtk::Matrix, 112
- SetOrdering
 - mtk::DenseMatrix, 64
- SetValue
 - mtk::DenseMatrix, 64
- sgels_
 - mtk, 42
- sgemm_
 - mtk, 43
- sgemv_
 - mtk, 43
- sgeqrf_
 - mtk, 43
- sgesv_
 - mtk, 44
- snrm2_
 - mtk, 44
- SolveDenseSystem
 - mtk::LAPACKAdapter, 96, 97
- SolveRectangularDenseSystem
 - mtk::LAPACKAdapter, 98
- SolveSimplexAndCompare
 - mtk::GLPKAdapter, 77
- sormqr_
 - mtk, 44
- src/mtk_blas_adapter.cc, 174, 175
- src/mtk_dense_matrix.cc, 178
- src/mtk_div_1d.cc, 185, 186
- src/mtk_glpk_adapter.cc, 202, 203
- src/mtk_grad_1d.cc, 207, 208
- src/mtk_lap_1d.cc, 225, 226
- src/mtk_lapack_adapter.cc, 230, 232
- src/mtk_matrix.cc, 238, 239
- src/mtk_tools.cc, 243
- src/mtk_uni_stg_grid_1d.cc, 245, 246
- storage
 - mtk::Matrix, 113
- storage_
 - mtk::Matrix, 115
- test_number_
 - mtk::Tools, 121
- tests/mtk_blas_adapter_test.cc, 249
- tests/mtk_dense_matrix_test.cc, 251, 252
- tests/mtk_div_1d_test.cc, 255, 256
- tests/mtk_glpk_adapter_test.cc, 259, 260
- tests/mtk_grad_1d_test.cc, 261, 262
- tests/mtk_lap_1d_test.cc, 264, 265
- tests/mtk_lapack_adapter_test.cc, 267, 268
- tests/mtk_uni_stg_grid_1d_test.cc, 269
- Transpose
 - mtk::DenseMatrix, 65
- UniStgGrid1D
 - mtk::UniStgGrid1D, 125
- VECTOR
 - Enumerations., 31
- weights
 - mtk::Quad1D, 118
- weights_
 - mtk::Quad1D, 118
- weights_cbs
 - mtk::Div1D, 74
 - mtk::Grad1D, 87
- weights_cbs_
 - mtk::Div1D, 76
 - mtk::Grad1D, 89
- weights_crs
 - mtk::Div1D, 74
 - mtk::Grad1D, 87

weights_crs_
 mtk::Div1D, [76](#)
 mtk::Grad1D, [89](#)
west_bndy_x_
 mtk::UniStgGrid1D, [129](#)
WriteToFile
 mtk::UniStgGrid1D, [128](#)