

MTK: Mimetic Methods Toolkit

Generated by Doxygen 1.8.8

Thu Dec 17 2015 13:00:51

Contents

1	Introduction	1
1.1	MTK Concerns	1
1.2	MTK Flavors	1
1.3	Contact, Support and Credits	2
1.4	Acknowledgements and Contributions	2
2	Programming Tools	3
3	Licensing and Modifications	5
4	Read Me File and Installation Instructions	7
5	Tests and Test Architectures	11
6	Examples	13
7	User Manual, References and Theory	15
8	Todo List	17
9	Bug List	19
10	Module Index	21
10.1	Modules	21
11	Namespace Index	23
11.1	Namespace List	23
12	Class Index	25
12.1	Class List	25
13	File Index	27
13.1	File List	27

14 Module Documentation	31
14.1 Roots.	31
14.1.1 Detailed Description	31
14.1.2 Typedef Documentation	32
14.1.2.1 Real	32
14.1.3 Variable Documentation	32
14.1.3.1 kCriticalOrderAccuracyDiv	32
14.1.3.2 kCriticalOrderAccuracyGrad	32
14.1.3.3 kDefaultMimeticThreshold	32
14.1.3.4 kDefaultOrderAccuracy	32
14.1.3.5 kDefaultTolerance	32
14.1.3.6 kOne	32
14.1.3.7 kTwo	32
14.1.3.8 kZero	33
14.2 Enumerations.	34
14.2.1 Detailed Description	34
14.2.2 Enumeration Type Documentation	34
14.2.2.1 DirInterp	34
14.2.2.2 FieldNature	34
14.2.2.3 MatrixOrdering	35
14.2.2.4 MatrixStorage	35
14.3 Execution tools.	36
14.3.1 Detailed Description	36
14.4 Data structures.	37
14.4.1 Detailed Description	37
14.5 Numerical methods.	38
14.5.1 Detailed Description	38
14.6 Grids.	39
14.6.1 Detailed Description	39
14.7 Mimetic operators.	40
14.7.1 Detailed Description	41
14.7.2 Typedef Documentation	41
14.7.2.1 CoefficientFunction0D	41
14.7.2.2 CoefficientFunction1D	41
14.7.2.3 CoefficientFunction2D	41
15 Namespace Documentation	43

15.1	mtk Namespace Reference	43
15.1.1	Function Documentation	46
15.1.1.1	operator<<	46
15.1.1.2	operator<<	46
15.1.1.3	operator<<	46
15.1.1.4	operator<<	46
15.1.1.5	operator<<	46
15.1.1.6	operator<<	46
15.1.1.7	operator<<	47
15.1.1.8	operator<<	47
15.1.1.9	saxpy_	47
15.1.1.10	sgels_	48
15.1.1.11	sgemm_	49
15.1.1.12	sgemv_	49
15.1.1.13	sgeqrf_	49
15.1.1.14	sgesv_	50
15.1.1.15	snrm2_	50
15.1.1.16	sormqr_	50
16	Class Documentation	53
16.1	mtk::BLASAdapter Class Reference	53
16.1.1	Detailed Description	54
16.1.2	Member Function Documentation	54
16.1.2.1	RealAXPY	54
16.1.2.2	RealDenseMM	55
16.1.2.3	RealDenseMV	56
16.1.2.4	RealDenseSM	58
16.1.2.5	RealNRM2	59
16.1.2.6	RelNorm2Error	60
16.2	mtk::Curl2D Class Reference	61
16.2.1	Detailed Description	63
16.2.2	Constructor & Destructor Documentation	63
16.2.2.1	Curl2D	63
16.2.2.2	Curl2D	63
16.2.2.3	~Curl2D	63
16.2.3	Member Function Documentation	64
16.2.3.1	ConstructCurl2D	64

16.2.3.2	operator*	64
16.2.3.3	ReturnAsDenseMatrix	64
16.2.4	Member Data Documentation	65
16.2.4.1	curl_	65
16.2.4.2	mimetic_threshold_	65
16.2.4.3	order_accuracy_	65
16.3	mtk::DenseMatrix Class Reference	65
16.3.1	Detailed Description	68
16.3.2	Constructor & Destructor Documentation	68
16.3.2.1	DenseMatrix	68
16.3.2.2	DenseMatrix	68
16.3.2.3	DenseMatrix	69
16.3.2.4	DenseMatrix	70
16.3.2.5	DenseMatrix	70
16.3.2.6	~DenseMatrix	71
16.3.3	Member Function Documentation	71
16.3.3.1	data	71
16.3.3.2	GetValue	72
16.3.3.3	Kron	73
16.3.3.4	matrix_properties	74
16.3.3.5	num_cols	75
16.3.3.6	num_rows	76
16.3.3.7	operator=	77
16.3.3.8	operator==	78
16.3.3.9	OrderColMajor	79
16.3.3.10	OrderRowMajor	79
16.3.3.11	SetOrdering	80
16.3.3.12	SetValue	81
16.3.3.13	Transpose	82
16.3.3.14	WriteToFile	83
16.3.4	Friends And Related Function Documentation	83
16.3.4.1	operator<<	83
16.3.5	Member Data Documentation	83
16.3.5.1	data_	83
16.3.5.2	matrix_properties_	84
16.4	mtk::Div1D Class Reference	84
16.4.1	Detailed Description	87

16.4.2	Constructor & Destructor Documentation	87
16.4.2.1	Div1D	87
16.4.2.2	Div1D	87
16.4.2.3	~Div1D	87
16.4.3	Member Function Documentation	88
16.4.3.1	AssembleOperator	88
16.4.3.2	coeffs_interior	88
16.4.3.3	ComputePreliminaryApproximations	88
16.4.3.4	ComputeRationalBasisNullSpace	89
16.4.3.5	ComputeStencilBoundaryGrid	90
16.4.3.6	ComputeStencilInteriorGrid	90
16.4.3.7	ComputeWeights	91
16.4.3.8	ConstructDiv1D	92
16.4.3.9	mim_bndy	92
16.4.3.10	num_bndy_coeffs	93
16.4.3.11	ReturnAsDenseMatrix	93
16.4.3.12	weights_cbs	94
16.4.3.13	weights_crs	94
16.4.4	Friends And Related Function Documentation	94
16.4.4.1	operator<<	94
16.4.5	Member Data Documentation	94
16.4.5.1	coeffs_interior_	94
16.4.5.2	dim_null_	95
16.4.5.3	divergence_	95
16.4.5.4	divergence_length_	95
16.4.5.5	mim_bndy_	95
16.4.5.6	mimetic_threshold_	95
16.4.5.7	minrow_	95
16.4.5.8	num_bndy_coeffs_	95
16.4.5.9	order_accuracy_	95
16.4.5.10	prem_apps_	95
16.4.5.11	rat_basis_null_space_	95
16.4.5.12	row_	95
16.4.5.13	weights_cbs_	96
16.4.5.14	weights_crs_	96
16.5	mtk::Div2D Class Reference	96
16.5.1	Detailed Description	98

16.5.2	Constructor & Destructor Documentation	98
16.5.2.1	Div2D	98
16.5.2.2	Div2D	98
16.5.2.3	~Div2D	98
16.5.3	Member Function Documentation	99
16.5.3.1	ConstructDiv2D	99
16.5.3.2	ReturnAsDenseMatrix	99
16.5.4	Member Data Documentation	100
16.5.4.1	divergence_	100
16.5.4.2	mimetic_threshold_	100
16.5.4.3	order_accuracy_	100
16.6	mtk::Div3D Class Reference	100
16.6.1	Detailed Description	102
16.6.2	Constructor & Destructor Documentation	102
16.6.2.1	Div3D	102
16.6.2.2	Div3D	102
16.6.2.3	~Div3D	102
16.6.3	Member Function Documentation	103
16.6.3.1	ConstructDiv3D	103
16.6.3.2	ReturnAsDenseMatrix	104
16.6.4	Member Data Documentation	104
16.6.4.1	divergence_	104
16.6.4.2	mimetic_threshold_	104
16.6.4.3	order_accuracy_	104
16.7	mtk::GLPKAdapter Class Reference	105
16.7.1	Detailed Description	105
16.7.2	Member Function Documentation	105
16.7.2.1	SolveSimplexAndCompare	106
16.8	mtk::Grad1D Class Reference	108
16.8.1	Detailed Description	111
16.8.2	Constructor & Destructor Documentation	111
16.8.2.1	Grad1D	111
16.8.2.2	Grad1D	111
16.8.2.3	~Grad1D	112
16.8.3	Member Function Documentation	112
16.8.3.1	AssembleOperator	112
16.8.3.2	coeffs_interior	112

16.8.3.3	ComputePreliminaryApproximations	112
16.8.3.4	ComputeRationalBasisNullSpace	113
16.8.3.5	ComputeStencilBoundaryGrid	114
16.8.3.6	ComputeStencilInteriorGrid	114
16.8.3.7	ComputeWeights	115
16.8.3.8	ConstructGrad1D	115
16.8.3.9	mim_bndy	116
16.8.3.10	num_bndy_coeffs	117
16.8.3.11	ReturnAsDenseMatrix	117
16.8.3.12	ReturnAsDenseMatrix	118
16.8.3.13	ReturnAsDimensionlessDenseMatrix	119
16.8.3.14	weights_cbs	119
16.8.3.15	weights_crs	119
16.8.4	Friends And Related Function Documentation	119
16.8.4.1	operator<<	119
16.8.5	Member Data Documentation	120
16.8.5.1	coeffs_interior_	120
16.8.5.2	dim_null_	120
16.8.5.3	gradient_	120
16.8.5.4	gradient_length_	120
16.8.5.5	mim_bndy_	120
16.8.5.6	mimetic_threshold_	120
16.8.5.7	minrow_	120
16.8.5.8	num_bndy_approxs_	120
16.8.5.9	num_bndy_coeffs_	120
16.8.5.10	order_accuracy_	120
16.8.5.11	prem_apps_	120
16.8.5.12	rat_basis_null_space_	121
16.8.5.13	row_	121
16.8.5.14	weights_cbs_	121
16.8.5.15	weights_crs_	121
16.9	mtk::Grad2D Class Reference	121
16.9.1	Detailed Description	123
16.9.2	Constructor & Destructor Documentation	123
16.9.2.1	Grad2D	123
16.9.2.2	Grad2D	123
16.9.2.3	~Grad2D	123

16.9.3 Member Function Documentation	124
16.9.3.1 ConstructGrad2D	124
16.9.3.2 ReturnAsDenseMatrix	124
16.9.4 Member Data Documentation	125
16.9.4.1 gradient_	125
16.9.4.2 mimetic_threshold_	125
16.9.4.3 order_accuracy_	125
16.10mtk::Grad3D Class Reference	125
16.10.1 Detailed Description	127
16.10.2 Constructor & Destructor Documentation	127
16.10.2.1 Grad3D	127
16.10.2.2 Grad3D	127
16.10.2.3 ~Grad3D	127
16.10.3 Member Function Documentation	128
16.10.3.1 ConstructGrad3D	128
16.10.3.2 ReturnAsDenseMatrix	129
16.10.4 Member Data Documentation	129
16.10.4.1 gradient_	129
16.10.4.2 mimetic_threshold_	129
16.10.4.3 order_accuracy_	129
16.11mtk::Interp1D Class Reference	130
16.11.1 Detailed Description	131
16.11.2 Constructor & Destructor Documentation	131
16.11.2.1 Interp1D	131
16.11.2.2 Interp1D	131
16.11.2.3 ~Interp1D	131
16.11.3 Member Function Documentation	131
16.11.3.1 coeffs_interior	131
16.11.3.2 ConstructInterp1D	131
16.11.3.3 ReturnAsDenseMatrix	132
16.11.4 Friends And Related Function Documentation	132
16.11.4.1 operator<<	132
16.11.5 Member Data Documentation	132
16.11.5.1 coeffs_interior_	132
16.11.5.2 dir_interp_	133
16.11.5.3 order_accuracy_	133
16.12mtk::Interp2D Class Reference	133

16.12.1 Detailed Description	135
16.12.2 Constructor & Destructor Documentation	135
16.12.2.1 Interp2D	135
16.12.2.2 Interp2D	135
16.12.2.3 ~Interp2D	135
16.12.3 Member Function Documentation	135
16.12.3.1 ConstructInterp2D	135
16.12.3.2 ReturnAsDenseMatrix	136
16.12.4 Member Data Documentation	136
16.12.4.1 interpolator_	136
16.12.4.2 mimetic_threshold_	136
16.12.4.3 order_accuracy_	136
16.13mtk::Lap1D Class Reference	136
16.13.1 Detailed Description	138
16.13.2 Constructor & Destructor Documentation	138
16.13.2.1 Lap1D	138
16.13.2.2 Lap1D	138
16.13.2.3 ~Lap1D	138
16.13.3 Member Function Documentation	138
16.13.3.1 ConstructLap1D	138
16.13.3.2 data	140
16.13.3.3 delta	140
16.13.3.4 mimetic_threshold	140
16.13.3.5 order_accuracy	141
16.13.3.6 ReturnAsDenseMatrix	141
16.13.4 Friends And Related Function Documentation	142
16.13.4.1 operator<<	142
16.13.5 Member Data Documentation	142
16.13.5.1 delta_	142
16.13.5.2 laplacian_	142
16.13.5.3 laplacian_length_	142
16.13.5.4 mimetic_threshold_	143
16.13.5.5 order_accuracy_	143
16.14mtk::Lap2D Class Reference	143
16.14.1 Detailed Description	145
16.14.2 Constructor & Destructor Documentation	145
16.14.2.1 Lap2D	145

16.14.2.2 Lap2D	145
16.14.2.3 ~Lap2D	145
16.14.3 Member Function Documentation	146
16.14.3.1 ConstructLap2D	146
16.14.3.2 data	146
16.14.3.3 ReturnAsDenseMatrix	147
16.14.4 Member Data Documentation	147
16.14.4.1 laplacian_	147
16.14.4.2 mimetic_threshold_	147
16.14.4.3 order_accuracy_	147
16.15mtk::Lap3D Class Reference	147
16.15.1 Detailed Description	149
16.15.2 Constructor & Destructor Documentation	149
16.15.2.1 Lap3D	149
16.15.2.2 Lap3D	149
16.15.2.3 ~Lap3D	149
16.15.3 Member Function Documentation	150
16.15.3.1 ConstructLap3D	150
16.15.3.2 data	150
16.15.3.3 operator*	151
16.15.3.4 ReturnAsDenseMatrix	151
16.15.4 Member Data Documentation	151
16.15.4.1 laplacian_	151
16.15.4.2 mimetic_threshold_	151
16.15.4.3 order_accuracy_	151
16.16mtk::LAPACKAdapter Class Reference	151
16.16.1 Detailed Description	152
16.16.2 Member Function Documentation	153
16.16.2.1 QRFactorDenseMatrix	153
16.16.2.2 SolveDenseSystem	154
16.16.2.3 SolveDenseSystem	155
16.16.2.4 SolveDenseSystem	156
16.16.2.5 SolveDenseSystem	157
16.16.2.6 SolveRectangularDenseSystem	158
16.17mtk::Matrix Class Reference	159
16.17.1 Detailed Description	162
16.17.2 Constructor & Destructor Documentation	162

16.17.2.1 Matrix	162
16.17.2.2 Matrix	163
16.17.2.3 ~Matrix	164
16.17.3 Member Function Documentation	164
16.17.3.1 abs_density	164
16.17.3.2 abs_sparsity	164
16.17.3.3 bandwidth	164
16.17.3.4 IncreaseNumNull	164
16.17.3.5 IncreaseNumZero	165
16.17.3.6 kl	165
16.17.3.7 ku	165
16.17.3.8 ld	165
16.17.3.9 num_cols	165
16.17.3.10 num_non_null	166
16.17.3.11 num_non_zero	166
16.17.3.12 num_null	166
16.17.3.13 num_rows	166
16.17.3.14 num_values	167
16.17.3.15 num_zero	167
16.17.3.16 ordering	167
16.17.3.17 rel_density	168
16.17.3.18 rel_sparsity	168
16.17.3.19 set_num_cols	168
16.17.3.20 set_num_null	169
16.17.3.21 set_num_rows	170
16.17.3.22 set_num_zero	170
16.17.3.23 set_ordering	171
16.17.3.24 set_storage	172
16.17.3.25 storage	172
16.17.4 Member Data Documentation	173
16.17.4.1 abs_density_	173
16.17.4.2 abs_sparsity_	173
16.17.4.3 bandwidth_	173
16.17.4.4 kl_	173
16.17.4.5 ku_	173
16.17.4.6 ld_	173
16.17.4.7 num_cols_	173

16.17.4.8 num_non_null_	174
16.17.4.9 num_non_zero_	174
16.17.4.10 num_null_	174
16.17.4.11 num_rows_	174
16.17.4.12 num_values_	174
16.17.4.13 num_zero_	174
16.17.4.14 ordering_	174
16.17.4.15 rel_density_	174
16.17.4.16 rel_sparsity_	174
16.17.4.17 storage_	174
16.18 mtk::Quad1D Class Reference	175
16.18.1 Detailed Description	176
16.18.2 Constructor & Destructor Documentation	176
16.18.2.1 Quad1D	176
16.18.2.2 Quad1D	176
16.18.2.3 ~Quad1D	177
16.18.3 Member Function Documentation	177
16.18.3.1 degree_approximation	177
16.18.3.2 Integrate	177
16.18.3.3 weights	177
16.18.4 Friends And Related Function Documentation	177
16.18.4.1 operator<<	177
16.18.5 Member Data Documentation	177
16.18.5.1 degree_approximation_	177
16.18.5.2 weights_	177
16.19 mtk::RobinBCDescriptor1D Class Reference	177
16.19.1 Detailed Description	179
16.19.2 Constructor & Destructor Documentation	180
16.19.2.1 RobinBCDescriptor1D	180
16.19.2.2 RobinBCDescriptor1D	180
16.19.2.3 ~RobinBCDescriptor1D	180
16.19.3 Member Function Documentation	180
16.19.3.1 highest_order_diff_east	180
16.19.3.2 highest_order_diff_west	180
16.19.3.3 ImposeOnGrid	181
16.19.3.4 ImposeOnLaplacianMatrix	181
16.19.3.5 PushBackEastCoeff	182

16.19.3.6 PushBackWestCoeff	183
16.19.3.7 set_east_condition	183
16.19.3.8 set_west_condition	184
16.19.4 Member Data Documentation	184
16.19.4.1 east_coefficients_	184
16.19.4.2 east_condition_	184
16.19.4.3 highest_order_diff_east_	184
16.19.4.4 highest_order_diff_west_	184
16.19.4.5 west_coefficients_	185
16.19.4.6 west_condition_	185
16.20mtk::RobinBCDescriptor2D Class Reference	185
16.20.1 Detailed Description	189
16.20.2 Constructor & Destructor Documentation	189
16.20.2.1 RobinBCDescriptor2D	189
16.20.2.2 RobinBCDescriptor2D	189
16.20.2.3 ~RobinBCDescriptor2D	189
16.20.3 Member Function Documentation	189
16.20.3.1 highest_order_diff_east	189
16.20.3.2 highest_order_diff_north	190
16.20.3.3 highest_order_diff_south	190
16.20.3.4 highest_order_diff_west	190
16.20.3.5 ImposeOnEastBoundaryNoSpace	190
16.20.3.6 ImposeOnEastBoundaryWithSpace	191
16.20.3.7 ImposeOnGrid	192
16.20.3.8 ImposeOnLaplacianMatrix	194
16.20.3.9 ImposeOnNorthBoundaryNoSpace	194
16.20.3.10ImposeOnNorthBoundaryWithSpace	195
16.20.3.11ImposeOnSouthBoundaryNoSpace	196
16.20.3.12ImposeOnSouthBoundaryWithSpace	197
16.20.3.13ImposeOnWestBoundaryNoSpace	198
16.20.3.14ImposeOnWestBoundaryWithSpace	198
16.20.3.15PushBackEastCoeff	199
16.20.3.16PushBackNorthCoeff	199
16.20.3.17PushBackSouthCoeff	200
16.20.3.18PushBackWestCoeff	200
16.20.3.19set_east_condition	201
16.20.3.20set_north_condition	201

16.20.3.21	set_south_condition	202
16.20.3.22	set_west_condition	202
16.20.4	Member Data Documentation	203
16.20.4.1	east_coefficients_	203
16.20.4.2	east_condition_	203
16.20.4.3	highest_order_diff_east_	203
16.20.4.4	highest_order_diff_north_	203
16.20.4.5	highest_order_diff_south_	203
16.20.4.6	highest_order_diff_west_	203
16.20.4.7	north_coefficients_	203
16.20.4.8	north_condition_	203
16.20.4.9	south_coefficients_	204
16.20.4.10	south_condition_	204
16.20.4.11	west_coefficients_	204
16.20.4.12	west_condition_	204
16.21	mtk::RobinBCDescriptor3D Class Reference	204
16.21.1	Detailed Description	208
16.21.2	Constructor & Destructor Documentation	208
16.21.2.1	RobinBCDescriptor3D	208
16.21.2.2	RobinBCDescriptor3D	208
16.21.2.3	~RobinBCDescriptor3D	208
16.21.3	Member Function Documentation	208
16.21.3.1	highest_order_diff_west	208
16.21.3.2	ImposeOnEastBoundaryNoSpace	208
16.21.3.3	ImposeOnEastBoundaryWithSpace	209
16.21.3.4	ImposeOnGrid	209
16.21.3.5	ImposeOnLaplacianMatrix	209
16.21.3.6	ImposeOnNorthBoundaryNoSpace	209
16.21.3.7	ImposeOnNorthBoundaryWithSpace	209
16.21.3.8	ImposeOnSouthBoundaryNoSpace	210
16.21.3.9	ImposeOnSouthBoundaryWithSpace	210
16.21.3.10	ImposeOnWestBoundaryNoSpace	210
16.21.3.11	ImposeOnWestBoundaryWithSpace	210
16.21.3.12	PushBackWestCoeff	211
16.21.3.13	set_west_condition	211
16.21.4	Member Data Documentation	211
16.21.4.1	bottom_coefficients_	211

16.21.4.2 bottom_condition_	211
16.21.4.3 east_coefficients_	211
16.21.4.4 east_condition_	211
16.21.4.5 highest_order_diff_bottom_	211
16.21.4.6 highest_order_diff_east_	211
16.21.4.7 highest_order_diff_north_	211
16.21.4.8 highest_order_diff_south_	212
16.21.4.9 highest_order_diff_top_	212
16.21.4.10 highest_order_diff_west_	212
16.21.4.11 north_coefficients_	212
16.21.4.12 north_condition_	212
16.21.4.13 south_coefficients_	212
16.21.4.14 south_condition_	212
16.21.4.15 top_coefficients_	212
16.21.4.16 top_condition_	212
16.21.4.17 west_coefficients_	212
16.21.4.18 west_condition_	213
16.22 mtk::Tools Class Reference	213
16.22.1 Detailed Description	214
16.22.2 Member Function Documentation	214
16.22.2.1 Assert	214
16.22.2.2 BeginUnitTestNo	214
16.22.2.3 EndUnitTestNo	214
16.22.2.4 Prevent	215
16.22.3 Member Data Documentation	215
16.22.3.1 begin_time_	215
16.22.3.2 duration_	215
16.22.3.3 test_number_	215
16.23 mtk::UniStgGrid1D Class Reference	216
16.23.1 Detailed Description	218
16.23.2 Constructor & Destructor Documentation	218
16.23.2.1 UniStgGrid1D	218
16.23.2.2 UniStgGrid1D	218
16.23.2.3 UniStgGrid1D	218
16.23.2.4 ~UniStgGrid1D	219
16.23.3 Member Function Documentation	219
16.23.3.1 BindScalarField	219

16.23.3.2 BindVectorField	219
16.23.3.3 delta_x	220
16.23.3.4 discrete_domain_x	220
16.23.3.5 discrete_field	220
16.23.3.6 east_bndy_x	221
16.23.3.7 num_cells_x	221
16.23.3.8 west_bndy_x	222
16.23.3.9 WriteToFile	222
16.23.4 Friends And Related Function Documentation	222
16.23.4.1 operator<<	223
16.23.5 Member Data Documentation	223
16.23.5.1 delta_x_	223
16.23.5.2 discrete_domain_x_	223
16.23.5.3 discrete_field_	223
16.23.5.4 east_bndy_x_	223
16.23.5.5 nature_	223
16.23.5.6 num_cells_x_	223
16.23.5.7 west_bndy_x_	223
16.24mtk::UniStgGrid2D Class Reference	223
16.24.1 Detailed Description	226
16.24.2 Constructor & Destructor Documentation	227
16.24.2.1 UniStgGrid2D	227
16.24.2.2 UniStgGrid2D	227
16.24.2.3 UniStgGrid2D	227
16.24.2.4 ~UniStgGrid2D	227
16.24.3 Member Function Documentation	228
16.24.3.1 BindScalarField	228
16.24.3.2 BindVectorField	228
16.24.3.3 BindVectorFieldPComponent	229
16.24.3.4 BindVectorFieldQComponent	229
16.24.3.5 Bound	229
16.24.3.6 delta_x	230
16.24.3.7 delta_y	230
16.24.3.8 discrete_domain_x	231
16.24.3.9 discrete_domain_y	231
16.24.3.10discrete_field	232
16.24.3.11east_bndy	232

16.24.3.12	nature	233
16.24.3.13	north_bndy	234
16.24.3.14	num_cells_x	234
16.24.3.15	num_cells_y	235
16.24.3.16	Size	236
16.24.3.17	south_bndy	236
16.24.3.18	west_bndy	237
16.24.3.19	WriteToFile	238
16.24.4	Friends And Related Function Documentation	239
16.24.4.1	operator<<	239
16.24.5	Member Data Documentation	239
16.24.5.1	delta_x_	239
16.24.5.2	delta_y_	239
16.24.5.3	discrete_domain_x_	239
16.24.5.4	discrete_domain_y_	239
16.24.5.5	discrete_field_	240
16.24.5.6	east_bndy_	240
16.24.5.7	nature_	240
16.24.5.8	north_bndy_	240
16.24.5.9	num_cells_x_	240
16.24.5.10	num_cells_y_	240
16.24.5.11	south_bndy_	240
16.24.5.12	west_bndy_	240
16.25	mtk::UniStgGrid3D Class Reference	240
16.25.1	Detailed Description	244
16.25.2	Constructor & Destructor Documentation	244
16.25.2.1	UniStgGrid3D	244
16.25.2.2	UniStgGrid3D	244
16.25.2.3	UniStgGrid3D	244
16.25.2.4	~UniStgGrid3D	245
16.25.3	Member Function Documentation	245
16.25.3.1	BindScalarField	245
16.25.3.2	BindVectorField	246
16.25.3.3	BindVectorFieldPComponent	246
16.25.3.4	BindVectorFieldQComponent	247
16.25.3.5	BindVectorFieldRComponent	247
16.25.3.6	bottom_bndy	247

16.25.3.7 Bound	248
16.25.3.8 delta_x	248
16.25.3.9 delta_y	248
16.25.3.10 delta_z	248
16.25.3.11 discrete_domain_x	248
16.25.3.12 discrete_domain_y	248
16.25.3.13 discrete_domain_z	249
16.25.3.14 discrete_field	249
16.25.3.15 east_bndy	249
16.25.3.16 nature	249
16.25.3.17 north_bndy	249
16.25.3.18 num_cells_x	250
16.25.3.19 num_cells_y	250
16.25.3.20 num_cells_z	250
16.25.3.21 operator=	251
16.25.3.22 Size	251
16.25.3.23 south_bndy	251
16.25.3.24 top_bndy	251
16.25.3.25 west_bndy	252
16.25.3.26 WriteToFile	252
16.25.4 Friends And Related Function Documentation	253
16.25.4.1 operator<<	253
16.25.5 Member Data Documentation	253
16.25.5.1 bottom_bndy_	253
16.25.5.2 delta_x_	253
16.25.5.3 delta_y_	253
16.25.5.4 delta_z_	253
16.25.5.5 discrete_domain_x_	253
16.25.5.6 discrete_domain_y_	253
16.25.5.7 discrete_domain_z_	253
16.25.5.8 discrete_field_	254
16.25.5.9 east_bndy_	254
16.25.5.10 nature_	254
16.25.5.11 north_bndy_	254
16.25.5.12 num_cells_x_	254
16.25.5.13 num_cells_y_	254
16.25.5.14 num_cells_z_	254

16.25.5.15south_bndy_	254
16.25.5.16top_bndy_	254
16.25.5.17west_bndy_	254
17 File Documentation	255
17.1 examples/curl_2d_angular_velocity/curl_2d_angular_velocity.cc File Reference	255
17.1.1 Detailed Description	255
17.1.2 Function Documentation	256
17.1.2.1 main	256
17.2 curl_2d_angular_velocity.cc	256
17.3 examples/diffusion_3d/diffusion_3d.cc File Reference	257
17.3.1 Detailed Description	258
17.3.2 Function Documentation	258
17.3.2.1 main	258
17.4 diffusion_3d.cc	258
17.5 examples/minimalistic_poisson_1d/minimalistic_poisson_1d.cc File Reference	260
17.5.1 Detailed Description	260
17.5.2 Function Documentation	261
17.5.2.1 main	261
17.6 minimalistic_poisson_1d.cc	261
17.7 examples/poisson_1d/poisson_1d.cc File Reference	262
17.7.1 Detailed Description	263
17.7.2 Function Documentation	264
17.7.2.1 main	264
17.8 poisson_1d.cc	264
17.9 examples/poisson_2d/poisson_2d.cc File Reference	266
17.9.1 Detailed Description	267
17.9.2 Function Documentation	268
17.9.2.1 main	268
17.10poisson_2d.cc	268
17.11include/mtk.h File Reference	270
17.11.1 Detailed Description	271
17.12mtk.h	272
17.13include/mtk_blas_adapter.h File Reference	273
17.13.1 Detailed Description	274
17.14mtk_blas_adapter.h	274
17.15include/mtk_curl_2d.h File Reference	275

17.15.1 Detailed Description	277
17.16mtk_curl_2d.h	277
17.17include/mtk_dense_matrix.h File Reference	278
17.17.1 Detailed Description	279
17.18mtk_dense_matrix.h	279
17.19include/mtk_div_1d.h File Reference	281
17.19.1 Detailed Description	282
17.20mtk_div_1d.h	282
17.21include/mtk_div_2d.h File Reference	283
17.21.1 Detailed Description	285
17.22mtk_div_2d.h	285
17.23include/mtk_div_3d.h File Reference	286
17.23.1 Detailed Description	287
17.24mtk_div_3d.h	287
17.25include/mtk_enums.h File Reference	288
17.25.1 Detailed Description	289
17.26mtk_enums.h	289
17.27include/mtk_glpk_adapter.h File Reference	290
17.27.1 Detailed Description	291
17.28mtk_glpk_adapter.h	292
17.29include/mtk_grad_1d.h File Reference	293
17.29.1 Detailed Description	294
17.30mtk_grad_1d.h	294
17.31include/mtk_grad_2d.h File Reference	296
17.31.1 Detailed Description	297
17.32mtk_grad_2d.h	297
17.33include/mtk_grad_3d.h File Reference	298
17.33.1 Detailed Description	300
17.34mtk_grad_3d.h	300
17.35include/mtk_interp_1d.h File Reference	301
17.35.1 Detailed Description	302
17.36mtk_interp_1d.h	302
17.37include/mtk_interp_2d.h File Reference	304
17.37.1 Detailed Description	304
17.38mtk_interp_2d.h	305
17.39include/mtk_lap_1d.h File Reference	306
17.39.1 Detailed Description	307

17.40	mtk_lap_1d.h	307
17.41	include/mtk_lap_2d.h File Reference	309
17.41.1	Detailed Description	310
17.42	mtk_lap_2d.h	310
17.43	include/mtk_lap_3d.h File Reference	311
17.43.1	Detailed Description	313
17.44	mtk_lap_3d.h	313
17.45	include/mtk_lapack_adapter.h File Reference	314
17.45.1	Detailed Description	315
17.46	mtk_lapack_adapter.h	315
17.47	include/mtk_matrix.h File Reference	316
17.47.1	Detailed Description	317
17.48	mtk_matrix.h	318
17.49	include/mtk_quad_1d.h File Reference	319
17.49.1	Detailed Description	320
17.50	mtk_quad_1d.h	321
17.51	include/mtk_robin_bc_descriptor_1d.h File Reference	322
17.51.1	Detailed Description	323
17.52	mtk_robin_bc_descriptor_1d.h	324
17.53	include/mtk_robin_bc_descriptor_2d.h File Reference	325
17.53.1	Detailed Description	327
17.54	mtk_robin_bc_descriptor_2d.h	327
17.55	include/mtk_robin_bc_descriptor_3d.h File Reference	329
17.55.1	Detailed Description	331
17.56	mtk_robin_bc_descriptor_3d.h	331
17.57	include/mtk_roots.h File Reference	333
17.57.1	Detailed Description	334
17.58	mtk_roots.h	335
17.59	include/mtk_tools.h File Reference	336
17.59.1	Detailed Description	336
17.60	mtk_tools.h	337
17.61	include/mtk_uni_stg_grid_1d.h File Reference	338
17.61.1	Detailed Description	339
17.62	mtk_uni_stg_grid_1d.h	339
17.63	include/mtk_uni_stg_grid_2d.h File Reference	340
17.63.1	Detailed Description	341
17.64	mtk_uni_stg_grid_2d.h	342

17.65include/mtk_uni_stg_grid_3d.h File Reference	343
17.65.1 Detailed Description	345
17.66mtk_uni_stg_grid_3d.h	345
17.67Makefile.inc File Reference	347
17.68Makefile.inc	347
17.69README.md File Reference	350
17.70README.md	350
17.71src/mtk_blas_adapter.cc File Reference	352
17.71.1 Detailed Description	353
17.72mtk_blas_adapter.cc	353
17.73src/mtk_curl_2d.cc File Reference	357
17.73.1 Detailed Description	358
17.74mtk_curl_2d.cc	358
17.75src/mtk_dense_matrix.cc File Reference	360
17.76mtk_dense_matrix.cc	361
17.77src/mtk_div_1d.cc File Reference	368
17.77.1 Detailed Description	368
17.78mtk_div_1d.cc	369
17.79src/mtk_div_2d.cc File Reference	386
17.79.1 Detailed Description	386
17.80mtk_div_2d.cc	386
17.81src/mtk_div_3d.cc File Reference	388
17.81.1 Detailed Description	389
17.82mtk_div_3d.cc	389
17.83src/mtk_glpk_adapter.cc File Reference	391
17.83.1 Detailed Description	392
17.84mtk_glpk_adapter.cc	392
17.85src/mtk_grad_1d.cc File Reference	396
17.85.1 Detailed Description	397
17.86mtk_grad_1d.cc	397
17.87src/mtk_grad_2d.cc File Reference	416
17.87.1 Detailed Description	417
17.88mtk_grad_2d.cc	417
17.89src/mtk_grad_3d.cc File Reference	419
17.89.1 Detailed Description	419
17.90mtk_grad_3d.cc	420
17.91src/mtk_interp_1d.cc File Reference	422

17.91.1 Detailed Description	423
17.92mtk_interp_1d.cc	423
17.93src/mtk_lap_1d.cc File Reference	425
17.93.1 Detailed Description	426
17.94mtk_lap_1d.cc	426
17.95src/mtk_lap_2d.cc File Reference	430
17.95.1 Detailed Description	431
17.96mtk_lap_2d.cc	431
17.97src/mtk_lap_3d.cc File Reference	433
17.97.1 Detailed Description	433
17.98mtk_lap_3d.cc	433
17.99src/mtk_lapack_adapter.cc File Reference	435
17.99.1 Detailed Description	436
17.100mtk_lapack_adapter.cc	436
17.101src/mtk_matrix.cc File Reference	444
17.101.1 Detailed Description	444
17.102mtk_matrix.cc	445
17.103src/mtk_robin_bc_descriptor_1d.cc File Reference	448
17.103.1 Detailed Description	449
17.104mtk_robin_bc_descriptor_1d.cc	450
17.105src/mtk_robin_bc_descriptor_2d.cc File Reference	452
17.105.1 Detailed Description	453
17.106mtk_robin_bc_descriptor_2d.cc	454
17.107src/mtk_tools.cc File Reference	463
17.107.1 Detailed Description	463
17.108mtk_tools.cc	463
17.109src/mtk_uni_stg_grid_1d.cc File Reference	465
17.109.1 Detailed Description	465
17.110mtk_uni_stg_grid_1d.cc	466
17.111src/mtk_uni_stg_grid_2d.cc File Reference	469
17.111.1 Detailed Description	470
17.112mtk_uni_stg_grid_2d.cc	470
17.113src/mtk_uni_stg_grid_3d.cc File Reference	476
17.113.1 Detailed Description	477
17.114mtk_uni_stg_grid_3d.cc	477
17.115tests/mtk_blas_adapter_test.cc File Reference	483
17.115.1 Detailed Description	483

17.115.2	Function Documentation	483
17.115.2.1	main	483
17.116	mtk_blas_adapter_test.cc	484
17.117	Tests/mtk_dense_matrix_test.cc File Reference	485
17.117.1	Detailed Description	485
17.117.2	Function Documentation	486
17.117.2.1	main	486
17.118	mtk_dense_matrix_test.cc	486
17.119	Tests/mtk_div_1d_test.cc File Reference	490
17.119.1	Detailed Description	490
17.119.2	Function Documentation	491
17.119.2.1	main	491
17.120	mtk_div_1d_test.cc	491
17.121	Tests/mtk_div_2d_test.cc File Reference	494
17.121.1	Detailed Description	495
17.121.2	Function Documentation	495
17.121.2.1	main	495
17.122	mtk_div_2d_test.cc	495
17.123	Tests/mtk_div_3d_test.cc File Reference	497
17.123.1	Detailed Description	498
17.123.2	Function Documentation	498
17.123.2.1	main	498
17.124	mtk_div_3d_test.cc	498
17.125	Tests/mtk_glpk_adapter_test.cc File Reference	500
17.125.1	Detailed Description	500
17.125.2	Function Documentation	500
17.125.2.1	main	500
17.126	mtk_glpk_adapter_test.cc	501
17.127	Tests/mtk_grad_1d_test.cc File Reference	502
17.127.1	Detailed Description	502
17.127.2	Function Documentation	502
17.127.2.1	main	502
17.128	mtk_grad_1d_test.cc	502
17.129	Tests/mtk_grad_2d_test.cc File Reference	506
17.129.1	Detailed Description	507
17.129.2	Function Documentation	507
17.129.2.1	main	507

17.130	mtk_grad_2d_test.cc	507
17.131	tests/mtk_grad_3d_test.cc File Reference	509
17.131.1	Detailed Description	510
17.131.2	Function Documentation	510
17.131.2.1	main	510
17.132	mtk_grad_3d_test.cc	510
17.133	tests/mtk_interp_1d_test.cc File Reference	512
17.133.1	Detailed Description	512
17.133.2	Function Documentation	512
17.133.2.1	main	512
17.134	mtk_interp_1d_test.cc	513
17.135	tests/mtk_lap_1d_test.cc File Reference	514
17.135.1	Detailed Description	514
17.135.2	Function Documentation	515
17.135.2.1	main	515
17.136	mtk_lap_1d_test.cc	515
17.137	tests/mtk_lap_2d_test.cc File Reference	517
17.137.1	Detailed Description	518
17.137.2	Function Documentation	518
17.137.2.1	main	518
17.138	mtk_lap_2d_test.cc	518
17.139	tests/mtk_lap_3d_test.cc File Reference	520
17.139.1	Detailed Description	521
17.139.2	Function Documentation	521
17.139.2.1	main	521
17.140	mtk_lap_3d_test.cc	521
17.141	tests/mtk_lapack_adapter_test.cc File Reference	523
17.141.1	Detailed Description	523
17.141.2	Function Documentation	523
17.141.2.1	main	523
17.142	mtk_lapack_adapter_test.cc	524
17.143	tests/mtk_robin_bc_descriptor_2d_test.cc File Reference	525
17.143.1	Detailed Description	525
17.143.2	Function Documentation	525
17.143.2.1	main	525
17.144	mtk_robin_bc_descriptor_2d_test.cc	525
17.145	tests/mtk_uni_stg_grid_1d_test.cc File Reference	528

17.145.1 Detailed Description	528
17.145.2 Function Documentation	529
17.145.2.1 main	529
17.146 mtk_uni_stg_grid_1d_test.cc	529
17.147 Tests/mtk_uni_stg_grid_2d_test.cc File Reference	531
17.147.1 Detailed Description	531
17.147.2 Function Documentation	532
17.147.2.1 main	532
17.148 mtk_uni_stg_grid_2d_test.cc	532
17.149 Tests/mtk_uni_stg_grid_3d_test.cc File Reference	534
17.149.1 Detailed Description	535
17.149.2 Function Documentation	535
17.149.2.1 main	535
17.150 mtk_uni_stg_grid_3d_test.cc	535
Index	539

Chapter 1

Introduction

We define numerical methods that are based on discretizations preserving the properties of their continuum counterparts to be **mimetic**.

The **Mimetic Methods Toolkit (MTK)** is a C++ library for mimetic numerical methods. It is arranged as a set of classes for **mimetic quadratures**, **mimetic interpolation****, and **mimetic finite differences** methods for the numerical solution of ordinary and partial differential equations.

1.1 MTK Concerns

Since collaborative development efforts are definitely important in achieving the level of generality we intend the library to possess, we have divided the library's source code according to the designated purpose the classes possess within the library. These divisions (or **concerns**) are grouped by layers, and are hierarchically related by the dependence they have among them.

One concern is said to depend on another one, if the classes the first concern includes, rely on the classes the second concern includes.

In order of dependence these are:

1. Roots.
2. Enumerations.
3. Tools.
4. Data Structures.
5. Numerical Methods.
6. Grids.
7. Mimetic Operators.

1.2 MTK Flavors

The MTK collection of wrappers is:

1. MMTK: MATLAB wrappers collection for MTK; intended for sequential computations.

Others are being strongly considered.

1.3 Contact, Support and Credits

The MTK is developed by researchers and adjuncts to the Computational Science Research Center (CSRC) at San Diego State University (SDSU).

Developers are members of:

1. Mimetic Numerical Methods Research and Development Group.
2. Computational Geoscience Research and Development Group.
3. Ocean Modeling Research and Development Group.

Currently the developers are:

1. **Eduardo J. Sanchez, Ph.D.** - **esanchez at mail dot sdsu dot edu** - ejspeiro
2. Jose E. Castillo, Ph.D. - jcastillo at mail dot sdsu dot edu
3. Guillermo F. Miranda, Ph.D. - unigrav at hotmail dot com
4. Christopher P. Paolini, Ph.D. - paolini at engineering dot sdsu dot edu
5. Angel Boada.
6. Johnny Corbino.
7. Raul Vargas–Navarro.

1.4 Acknowledgements and Contributions

The authors would like to acknowledge valuable advising, contributions and feedback, from research personnel at the Computational Science Research Center at San Diego State University, which were vital to the fruition of this work. Specifically, our thanks go to (alphabetical order):

1. Mohammad Abouali, Ph.D.
2. Dany De Cecchis, Ph.D.
3. Otilio Rojas, Ph.D.
4. Julia Rossi.

Chapter 2

Programming Tools

The development of MTK has been made possible through the use of the following applications:

1. Editor: Kate - KDE Advanced Text Editor. Version 3.13.3. Using KDE Development Platform 4.13.3 (C) 2000-2005 The Kate Authors.
2. Debugger: GNU gdb (Ubuntu 7.7.1-0ubuntu5~14.04.2) 7.7.1. Copyright (C) 2014 Free Software Foundation, Inc.
3. Memory Profiler: valgrind-3.10.0.SVN.

See the section on test architectures for information about operating systems and compilers used.

Chapter 3

Licensing and Modifications

Copyright (C) 2015, Computational Science Research Center, San Diego State University. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu and a copy of the modified files should be reported once modifications are completed, unless these modifications are made through the project's GitHub page: <http://www.csrc.sdsu.edu/mtk>. Documentation related to said modifications should be developed and included in any deliverable.
2. Redistributions of source code must be done through direct downloads from the project's GitHub page: <http://www.csrc.sdsu.edu/mtk>
3. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
4. Usage of the binary form on proprietary applications shall require explicit prior written permission from the the copyright holders, and due credit should be given to the copyright holders.
5. Neither the name of the copyright holder nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

The copyright holders provide no reassurances that the source code provided does not infringe any patent, copyright, or any other intellectual property rights of third parties. The copyright holders disclaim any liability to any recipient for claims brought against recipient by any third party for infringement of that parties intellectual property rights.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Chapter 4

Read Me File and Installation Instructions

README File for the Mimetic Methods Toolkit (MTK)

By: **Eduardo J. Sanchez, Ph.D. - esanchez at mail dot sdsu dot edu**

1. Description

We define numerical methods that are based on discretizations preserving the properties of their continuum counterparts to be **mimetic**.

The **Mimetic Methods Toolkit (MTK)** is a C++ library for mimetic numerical methods. It is arranged as a set of classes for **mimetic quadratures**, **mimetic interpolation**, and **mimetic finite differences** methods for the numerical solution of ordinary and partial differential equations.

2. Dependencies

This README assumes all of these dependencies are installed in the following folder:

`$(HOME)/Libraries/`

In this version, the MTK optionally uses ATLAS-optimized BLAS and LAPACK routines for the internal computation on some of the layers. However, ATLAS requires both BLAS and LAPACK in order to create their optimized distributions. Therefore, the following dependencies tree arises:

For Linux:

1. LAPACK - Available from: <http://www.netlib.org/lapack/>
 1. BLAS - Available from: <http://www.netlib.org/blas/>
2. GLPK - Available from: <https://www.gnu.org/software/glpk/>
3. (Optional) ATLAS - Available from: <http://math-atlas.sourceforge.net/>
 1. LAPACK - Available from: <http://www.netlib.org/lapack/>
 1. BLAS - Available from: http://www.netlib.org/blas
4. (Optional) Valgrind - Available from: <http://valgrind.org/>
5. (Optional) Doxygen - Available from <http://www.stack.nl/~dimitri/doxygen/>

For OS X:

1. GLPK - Available from: <https://www.gnu.org/software/glpk/>

3. Installation**PART 1. CONFIGURATION OF THE MAKEFILE.**

The following steps are required to build and test the MTK. Please use the accompanying [Makefile.inc](#) file, which should provide a solid template to start with. The following command provides help on the options for make:

```
$ make help
-----
Makefile for the MTK.

Options are:
- all: builds the library, the tests, and examples.
- mtklib: builds the library.
- test: builds the test files.
- example: builds the examples.

- testall: runs all the tests.

- gendoc: generates the documentation for the library.

- clean: cleans all the generated files.
- cleanlib: cleans the generated archive and object files.
- cleantest: cleans the generated tests executables.
- cleanexample: cleans the generated examples executables.
-----
```

PART 2. BUILD THE LIBRARY.

```
$ make
```

If successful you'll read (before building the examples):

```
----- Library created! Check in /home/ejspeiro/Dropbox/MTK/lib
```

4. Contact, Support, and Credits

The MTK is developed by researchers and adjuncts to the
[Computational Science Research Center \(CSRC\)](#)
 at [San Diego State University \(SDSU\)](#).

Developers are members of:

1. Mimetic Numerical Methods Research and Development Group.
2. Computational Geoscience Research and Development Group.
3. Ocean Modeling Research and Development Group.

Currently the developers are:

Eduardo J. Sanchez, Ph.D. - [esanchez at mail dot sdsu dot edu](mailto:esanchez@mail.sdsu.edu) - ejspeiro

2. Jose E. Castillo, Ph.D. - [jcastillo at mail dot sdsu dot edu](mailto:jcastillo@mail.sdsu.edu)
3. Guillermo F. Miranda, Ph.D. - [unigrav at hotmail dot com](mailto:unigrav@hotmail.com)
4. Christopher P. Paolini, Ph.D. - [paolini at engineering dot sdsu dot edu](mailto:paolini@engineering.sdsu.edu)
5. Angel Boada.
6. Johnny Corbino.
7. Raul Vargas-Navarro.

Finally, please feel free to contact me with suggestions or corrections:

Please reference this work as follows:

```
@article{Sanchez2014308,
  title = "The Mimetic Methods Toolkit: An object-oriented \{API\} for Mimetic
Finite Differences ",
  journal = "Journal of Computational and Applied Mathematics ",
  volume = "270",
  number = "",
  pages = "308 - 322",
  year = "2014",
  note = "Fourth International Conference on Finite Element Methods in
Engineering and Sciences (FEMTEC 2013) ",
  issn = "0377-0427",
  doi = "http://dx.doi.org/10.1016/j.cam.2013.12.046",
  url = "http://www.sciencedirect.com/science/article/pii/S037704271300719X",
```

```
author = "Eduardo J. Sanchez and Christopher P. Paolini and Jose E. Castillo",  
keywords = "Object-oriented development",  
keywords = "Partial differential equations",  
keywords = "Application programming interfaces",  
keywords = "Mimetic Finite Differences "  
}
```

Eduardo J. Sanchez, Ph.D. - esanchez at mail dot sdsu dot edu - ejspeiro

Thanks and happy coding!

Chapter 5

Tests and Test Architectures

Tests are given in the `files list` section. They are provided in the `/tests/` folder within the distributed software.

In this page we intend to make a summary of all of the architectures in where the MTK has been tested. The MTK is intended to be as portable as possible throughout architectures. The following architectures have provided flawless installations of the API and correct execution of the examples:

1. Intel(R) Pentium(R) M CPU 1.73 GHz 2048 KB of cache and stepping of 8.
Linux 3.2.0-23-generic-pae #36-Ubuntu SMP i386 GNU/Linux
gcc version 4.6.3 (Ubuntu/Linaro 4.6.3-1ubuntu5)
2. Intel(R) Core(TM) i7-4700MQ CPU 2.40 GHz 6144 KB of cache and stepping of 3.
Linux 3.13.0-67-generic #110-Ubuntu SMP x86_64 GNU/Linux
gcc version 4.8.4 (Ubuntu 4.4.4-2ubuntu1~14.04)
3. Intel(R) Core(TM) i7-4600U CPU 2.10 GHz 4096 KB of cache and a stepping of 1.
Linux 3.16.7-29-desktop #1 SMP PREEMPT (6be6a97) x86_64 GNU/Linux
openSUSE 13.2 (Harlequin) (x86_64)
gcc (SUSE Linux) 4.8.3 20140627 [gcc-4_8-branch revision 212064]

Further architectures will be tested!

Chapter 6

Examples

Examples are given in the `files list` section. They are provided in the `/examples/` folder within the distributed software.

Chapter 7

User Manual, References and Theory

The main source of references for this work can be found in:

<http://www.csrc.sdsu.edu/mimetic-book/>

However, a .PDF copy of this manual can be found [here](#).

Chapter 8

Todo List

Member `mtk::DenseMatrix::Kron` (`const DenseMatrix &aa, const DenseMatrix &bb`)

Implement Kronecker product using the BLAS.

Member `mtk::DenseMatrix::OrderColMajor` ()

Improve this so that no new arrays have to be created.

Member `mtk::DenseMatrix::OrderRowMajor` ()

Improve this so that no new arrays have to be created.

Member `mtk::DenseMatrix::Transpose` ()

Improve this so that no extra arrays have to be created.

Class `mtk::GLPKAdapter`

Rescind from the GLPK as the numerical core for CLO problems.

Member `mtk::Matrix::IncreaseNumNull` () noexcept

Review the definition of sparse matrices properties.

Member `mtk::Matrix::IncreaseNumZero` () noexcept

Review the definition of sparse matrices properties.

Member `mtk::RobinBCDescriptor2D::ImposeOnGrid` (`UniStgGrid2D &grid, const Real &time=kZero`) const

Implement imposition for vector-valued grids. Need research here!

Member `mtk::RobinBCDescriptor2D::ImposeOnSouthBoundaryNoSpace` (`const Lap2D &lap, const UniStgGrid2D &grid, DenseMatrix &matrix, const Real &time=kZero`) const

Impose the Neumann conditions on every pole, for every scenario.

Member `mtk::RobinBCDescriptor2D::ImposeOnSouthBoundaryWithSpace` (`const Lap2D &lap, const UniStgGrid2D &grid, DenseMatrix &matrix, const Real &time=kZero`) const

Impose Harmonic mean on the corners for the case when the generated space is available, for all poles.

Member `mtk::Tools::Prevent` (`const bool complement, const char *const fname, int lineno, const char *const fxname`) noexcept

Check if this is the best way of stalling execution.

Member `mtk::Tools::test_number_`

Check usage of static methods and private members.

Member `mtk::UniStgGrid1D::discrete_domain_x` () const

Review const-correctness of the pointer we return.

Member [mtk::UniStgGrid1D::discrete_field \(\)](#)

Review const-correctness of the pointer we return. Look at the STL!

Member [mtk::UniStgGrid2D::discrete_domain_x \(\) const](#)

Review const-correctness of the pointer we return.

Member [mtk::UniStgGrid2D::discrete_domain_y \(\) const](#)

Review const-correctness of the pointer we return.

Member [mtk::UniStgGrid3D::discrete_domain_x \(\) const](#)

Review const-correctness of the pointer we return.

Member [mtk::UniStgGrid3D::discrete_domain_y \(\) const](#)

Review const-correctness of the pointer we return.

Member [mtk::UniStgGrid3D::discrete_domain_z \(\) const](#)

Review const-correctness of the pointer we return.

File [mtk_div_1d.cc](#)

Overload ostream operator as in [mtk::Lap1D](#).

Implement creation of ■ w. [mtk::BLASAdapter](#).

File [mtk_glpk_adapter_test.cc](#)

Test the [mtk::GLPKAdapter](#) class.

File [mtk_grad_1d.cc](#)

Overload ostream operator as in [mtk::Lap1D](#).

Implement creation of ■ w. [mtk::BLASAdapter](#).

File [mtk_lapack_adapter.cc](#)

Write documentation using LaTeX.

File [mtk_lapack_adapter_test.cc](#)

Test the [mtk::LAPACKAdapter](#) class.

File [mtk_quad_1d.h](#)

Implement this class.

File [mtk_roots.h](#)

Documentation should (better?) capture effects from selective compilation.

Test selective precision mechanisms.

File [mtk_uni_stg_grid_1d.h](#)

Create overloaded binding routines that read data from files.

File [mtk_uni_stg_grid_2d.h](#)

Create overloaded binding routines that read data from files.

File [mtk_uni_stg_grid_3d.h](#)

Create overloaded binding routines that read data from files.

Chapter 9

Bug List

Member `mtk::Matrix::set_num_null` (`const int &in`) `noexcept`

-nan assigned on construction time due to `num_values_` being 0.

Member `mtk::Matrix::set_num_zero` (`const int &in`) `noexcept`

-nan assigned on construction time due to `num_values_` being 0.

Chapter 10

Module Index

10.1 Modules

Here is a list of all modules:

Roots.	31
Enumerations.	34
Execution tools.	36
Data structures.	37
Numerical methods.	38
Grids.	39
Mimetic operators.	40

Chapter 11

Namespace Index

11.1 Namespace List

Here is a list of all namespaces with brief descriptions:

mtk	Mimetic Methods Toolkit namespace	43
---------------------	---	--------------------

Chapter 12

Class Index

12.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

mtk::BLASAdapter	Adapter class for the BLAS API	53
mtk::Curl2D	Implements a 2D mimetic curl operator	61
mtk::DenseMatrix	Defines a common dense matrix, using a 1D array	65
mtk::Div1D	Implements a 1D mimetic divergence operator	84
mtk::Div2D	Implements a 2D mimetic divergence operator	96
mtk::Div3D	Implements a 3D mimetic divergence operator	100
mtk::GLPKAdapter	Adapter class for the GLPK API	105
mtk::Grad1D	Implements a 1D mimetic gradient operator	108
mtk::Grad2D	Implements a 2D mimetic gradient operator	121
mtk::Grad3D	Implements a 3D mimetic gradient operator	125
mtk::Interp1D	Implements a 1D interpolation operator	130
mtk::Interp2D	Implements a 2D interpolation operator	133
mtk::Lap1D	Implements a 1D mimetic Laplacian operator	136
mtk::Lap2D	Implements a 2D mimetic Laplacian operator	143
mtk::Lap3D	Implements a 3D mimetic Laplacian operator	147
mtk::LAPACKAdapter	Adapter class for the LAPACK API	151
mtk::Matrix	Definition of the representation of a matrix in the MTK	159

mtk::Quad1D	Implements a 1D mimetic quadrature	175
mtk::RobinBCDescriptor1D	Impose Robin boundary conditions on the operators and on the grids	177
mtk::RobinBCDescriptor2D	Impose Robin boundary conditions on the operators and on the grids	185
mtk::RobinBCDescriptor3D	Impose Robin boundary conditions on the operators and on the grids	204
mtk::Tools	Tool manager class	213
mtk::UniStgGrid1D	Uniform 1D Staggered Grid	216
mtk::UniStgGrid2D	Uniform 2D Staggered Grid	223
mtk::UniStgGrid3D	Uniform 3D Staggered Grid	240

Chapter 13

File Index

13.1 File List

Here is a list of all files with brief descriptions:

Makefile.inc	347
examples/curl_2d/angular_velocity/ curl_2d_angular_velocity.cc	
Compute the curl of a 2D angular velocity field	255
examples/diffusion_3d/ diffusion_3d.cc	
Diffusion Equation on a 3D Uniform Staggered Grid with Dirichlet BCs	257
examples/minimalistic_poisson_1d/ minimalistic_poisson_1d.cc	
Poisson Equation on a 1D Uniform Staggered Grid with Robin BCs	260
examples/poisson_1d/ poisson_1d.cc	
Poisson Equation on a 1D Uniform Staggered Grid with Robin BCs	262
examples/poisson_2d/ poisson_2d.cc	
Poisson Equation on a 2D Uniform Staggered Grid with Robin BCs	266
include/ mtk.h	
Includes the entire API	270
include/ mtk_blas_adapter.h	
Adapter class for the BLAS API	273
include/ mtk_curl_2d.h	
Includes the definition of the class Curl2D	275
include/ mtk_dense_matrix.h	
Defines a common dense matrix, using a 1D array	278
include/ mtk_div_1d.h	
Includes the definition of the class Div1D	281
include/ mtk_div_2d.h	
Includes the definition of the class Div2D	283
include/ mtk_div_3d.h	
Includes the definition of the class Div3D	286
include/ mtk_enums.h	
Considered enumeration types in the MTK	288
include/ mtk_glpk_adapter.h	
Adapter class for the GLPK API	290
include/ mtk_grad_1d.h	
Includes the definition of the class Grad1D	293
include/ mtk_grad_2d.h	
Includes the definition of the class Grad2D	296

include/mtk_grad_3d.h	Includes the definition of the class Grad3D	298
include/mtk_interp_1d.h	Includes the definition of the class Interp1D	301
include/mtk_interp_2d.h	Includes the definition of the class Interp2D	304
include/mtk_lap_1d.h	Includes the definition of the class Lap1D	306
include/mtk_lap_2d.h	Includes the implementation of the class Lap2D	309
include/mtk_lap_3d.h	Includes the implementation of the class Lap3D	311
include/mtk_lapack_adapter.h	Adapter class for the LAPACK API	314
include/mtk_matrix.h	Definition of the representation of a matrix in the MTK	316
include/mtk_quad_1d.h	Includes the definition of the class Quad1D	319
include/mtk_robin_bc_descriptor_1d.h	Impose Robin boundary conditions on the operators and on the grids	322
include/mtk_robin_bc_descriptor_2d.h	Impose Robin boundary conditions on the operators and on the grids	325
include/mtk_robin_bc_descriptor_3d.h	Impose Robin boundary conditions on the operators and on the grids	329
include/mtk_roots.h	Fundamental definitions to be used across all classes of the MTK	333
include/mtk_tools.h	Tool manager class	336
include/mtk_uni_stg_grid_1d.h	Definition of an 1D uniform staggered grid	338
include/mtk_uni_stg_grid_2d.h	Definition of an 2D uniform staggered grid	340
include/mtk_uni_stg_grid_3d.h	Definition of an 3D uniform staggered grid	343
src/mtk_blas_adapter.cc	Adapter class for the BLAS API	352
src/mtk_curl_2d.cc	Implements the class Curl2D	357
src/mtk_dense_matrix.cc		360
src/mtk_div_1d.cc	Implements the class Div1D	368
src/mtk_div_2d.cc	Implements the class Div2D	386
src/mtk_div_3d.cc	Implements the class Div3D	388
src/mtk_glpk_adapter.cc	Adapter class for the GLPK API	391
src/mtk_grad_1d.cc	Implements the class Grad1D	396
src/mtk_grad_2d.cc	Implements the class Grad2D	416
src/mtk_grad_3d.cc	Implements the class Grad3D	419

src/mtk_interp_1d.cc	Includes the implementation of the class Interp1D	422
src/mtk_lap_1d.cc	Includes the implementation of the class Lap1D	425
src/mtk_lap_2d.cc	Includes the implementation of the class Lap2D	430
src/mtk_lap_3d.cc	Includes the implementation of the class Lap3D	433
src/mtk_lapack_adapter.cc	Adapter class for the LAPACK API	435
src/mtk_matrix.cc	Implementing the representation of a matrix in the MTK	444
src/mtk_robin_bc_descriptor_1d.cc	Impose Robin boundary conditions on the operators and on the grids	448
src/mtk_robin_bc_descriptor_2d.cc	Impose Robin boundary conditions on the operators and on the grids	452
src/mtk_tools.cc	Implements a execution tool manager class	463
src/mtk_uni_stg_grid_1d.cc	Implementation of an 1D uniform staggered grid	465
src/mtk_uni_stg_grid_2d.cc	Implementation of a 2D uniform staggered grid	469
src/mtk_uni_stg_grid_3d.cc	Implementation of a 2D uniform staggered grid	476
tests/mtk_blas_adapter_test.cc	Test file for the mtk::BLASAdapter class	483
tests/mtk_dense_matrix_test.cc	Test file for the mtk::DenseMatrix class	485
tests/mtk_div_1d_test.cc	Testing the mimetic 1D divergence, constructed with the CBS algorithm	490
tests/mtk_div_2d_test.cc	Test file for the mtk::Div2D class	494
tests/mtk_div_3d_test.cc	Test file for the mtk::Div3D class	497
tests/mtk_glpk_adapter_test.cc	Test file for the mtk::GLPKAdapter class	500
tests/mtk_grad_1d_test.cc	Testing the mimetic 1D gradient, constructed with the CBS algorithm	502
tests/mtk_grad_2d_test.cc	Test file for the mtk::Grad2D class	506
tests/mtk_grad_3d_test.cc	Test file for the mtk::Grad3D class	509
tests/mtk_interp_1d_test.cc	Testing the 1D interpolation	512
tests/mtk_lap_1d_test.cc	Testing the 1D Laplacian operator	514
tests/mtk_lap_2d_test.cc	Test file for the mtk::Lap2D class	517
tests/mtk_lap_3d_test.cc	Test file for the mtk::Lap3D class	520
tests/mtk_lapack_adapter_test.cc	Test file for the mtk::LAPACKAdapter class	523
tests/mtk_robin_bc_descriptor_2d_test.cc	Test file for the mtk::RobinBCDescriptor2D class	525

tests/ mtk_uni_stg_grid_1d_test.cc	
Test file for the mtk::UniStgGrid1D class	528
tests/ mtk_uni_stg_grid_2d_test.cc	
Test file for the mtk::UniStgGrid2D class	531
tests/ mtk_uni_stg_grid_3d_test.cc	
Test file for the mtk::UniStgGrid3D class	534

Chapter 14

Module Documentation

14.1 Roots.

Fundamental execution parameters and defined types.

Typedefs

- typedef float [mtk::Real](#)

Users can simply change this to build a double- or single-precision MTK.

Variables

- const float [mtk::kZero](#) {0.0f}
MTK's zero defined according to selective compilation.
- const float [mtk::kOne](#) {1.0f}
MTK's one defined according to selective compilation.
- const float [mtk::kTwo](#) {2.0f}
MTK's two defined according to selective compilation.
- const float [mtk::kDefaultTolerance](#) {1e-7f}
Considered tolerance for comparisons in numerical methods.
- const int [mtk::kDefaultOrderAccuracy](#) {2}
Default order of accuracy for mimetic operators.
- const float [mtk::kDefaultMimeticThreshold](#) {1e-6f}
Default tolerance for higher-order mimetic operators.
- const int [mtk::kCriticalOrderAccuracyDiv](#) {8}
At this order (and higher) we must use the CBSA to construct.
- const int [mtk::kCriticalOrderAccuracyGrad](#) {10}
At this order (and higher) we must use the CBSA to construct.

14.1.1 Detailed Description

Fundamental execution parameters and defined types.

14.1.2 Typedef Documentation

14.1.2.1 mtk::Real

Definition at line 83 of file [mtk_roots.h](#).

14.1.3 Variable Documentation

14.1.3.1 mtk::kCriticalOrderAccuracyDiv {8}

Definition at line 167 of file [mtk_roots.h](#).

14.1.3.2 mtk::kCriticalOrderAccuracyGrad {10}

Definition at line 176 of file [mtk_roots.h](#).

14.1.3.3 mtk::kDefaultMimeticThreshold {1e-6f}

Warning

Declared as double if MTK_PRECISION_DOUBLE is defined.

Definition at line 157 of file [mtk_roots.h](#).

14.1.3.4 mtk::kDefaultOrderAccuracy {2}

Warning

Declared as double if MTK_PRECISION_DOUBLE is defined.

Definition at line 143 of file [mtk_roots.h](#).

14.1.3.5 mtk::kDefaultTolerance {1e-7f}

Definition at line 131 of file [mtk_roots.h](#).

14.1.3.6 mtk::kOne {1.0f}

Warning

Declared as double if MTK_PRECISION_DOUBLE is defined.

Definition at line 117 of file [mtk_roots.h](#).

14.1.3.7 mtk::kTwo {2.0f}

Warning

Declared as double if MTK_PRECISION_DOUBLE is defined.

Definition at line 118 of file [mtk_roots.h](#).

14.1.3.8 `mtk::kZero {0.0f}`

Warning

Declared as double if `MTK_PRECISION_DOUBLE` is defined.

Definition at line 116 of file [mtk_roots.h](#).

14.2 Enumerations.

Enumerations.

Enumerations

- enum `mtk::MatrixStorage` { `mtk::DENSE`, `mtk::BANDED`, `mtk::CRS` }
Considered matrix storage schemes to implement sparse matrices.
- enum `mtk::MatrixOrdering` { `mtk::ROW_MAJOR`, `mtk::COL_MAJOR` }
Considered matrix ordering (for Fortran purposes).
- enum `mtk::FieldNature` { `mtk::SCALAR`, `mtk::VECTOR` }
Nature of the field discretized in a given grid.
- enum `mtk::DirInterp` { `mtk::SCALAR_TO_VECTOR`, `mtk::VECTOR_TO_SCALAR` }
Interpolation operator.

14.2.1 Detailed Description

Enumerations.

14.2.2 Enumeration Type Documentation

14.2.2.1 enum `mtk::DirInterp`

Used to tag different directions of interpolation supported.

Enumerator

SCALAR_TO_VECTOR Interpolations places scalar on vectors' location.

VECTOR_TO_SCALAR Interpolations places vectors on scalars' location.

Definition at line 127 of file `mtk_enums.h`.

14.2.2.2 enum `mtk::FieldNature`

Fields can be **scalar** or **vector** in nature.

See also

https://en.wikipedia.org/wiki/Scalar_field
https://en.wikipedia.org/wiki/Vector_field

Enumerator

SCALAR Scalar-valued field.

VECTOR Vector-valued field.

Definition at line 113 of file `mtk_enums.h`.

14.2.2.3 enum mtk::MatrixOrdering

Row-major ordering is used for most application in C/C++. For Fortran purposes, the matrices must be listed in a column-major ordering.

See also

https://en.wikipedia.org/wiki/Row-major_order

Enumerator

ROW_MAJOR Row-major ordering (C/C++).

COL_MAJOR Column-major ordering (Fortran).

Definition at line 95 of file [mtk_enums.h](#).

14.2.2.4 enum mtk::MatrixStorage

The considered sparse storage schemes are selected so that these are compatible with some of the most used mathematical APIs, as follows: DENSE and BANDED for [BLAS](#), [LAPACK](#), and [ScaLAPACK](#). Finally, CRS for [SuperLU](#).

Enumerator

DENSE Dense matrices, implemented as a 1D array: [DenseMatrix](#).

BANDED Banded matrices ala LAPACK and ScaLAPACK: Must be implemented.

CRS Compressed-Rows Storage: Must be implemented.

Definition at line 77 of file [mtk_enums.h](#).

14.3 Execution tools.

Tools to ensure execution correctness.

Classes

- class `mtk::Tools`
Tool manager class.

14.3.1 Detailed Description

Tools to ensure execution correctness.

14.4 Data structures.

Fundamental data structures.

Classes

- class [mtk::DenseMatrix](#)
Defines a common dense matrix, using a 1D array.
- class [mtk::Matrix](#)
Definition of the representation of a matrix in the MTK.

14.4.1 Detailed Description

Fundamental data structures.

14.5 Numerical methods.

Adapter classes and auxiliary numerical methods.

Classes

- class [mtk::BLASAdapter](#)
Adapter class for the BLAS API.
- class [mtk::GLPKAdapter](#)
Adapter class for the GLPK API.
- class [mtk::LAPACKAdapter](#)
Adapter class for the LAPACK API.

14.5.1 Detailed Description

Adapter classes and auxiliary numerical methods.

14.6 Grids.

Uniform rectangular staggered grids.

Classes

- class [mtk::UniStgGrid1D](#)
Uniform 1D Staggered Grid.
- class [mtk::UniStgGrid2D](#)
Uniform 2D Staggered Grid.
- class [mtk::UniStgGrid3D](#)
Uniform 3D Staggered Grid.

14.6.1 Detailed Description

Uniform rectangular staggered grids.

14.7 Mimetic operators.

Mimetic operators.

Classes

- class [mtk::Curl2D](#)
Implements a 2D mimetic curl operator.
- class [mtk::Div1D](#)
Implements a 1D mimetic divergence operator.
- class [mtk::Div2D](#)
Implements a 2D mimetic divergence operator.
- class [mtk::Div3D](#)
Implements a 3D mimetic divergence operator.
- class [mtk::Grad1D](#)
Implements a 1D mimetic gradient operator.
- class [mtk::Grad2D](#)
Implements a 2D mimetic gradient operator.
- class [mtk::Grad3D](#)
Implements a 3D mimetic gradient operator.
- class [mtk::Interp1D](#)
Implements a 1D interpolation operator.
- class [mtk::Interp2D](#)
Implements a 2D interpolation operator.
- class [mtk::Lap1D](#)
Implements a 1D mimetic Laplacian operator.
- class [mtk::Lap2D](#)
Implements a 2D mimetic Laplacian operator.
- class [mtk::Lap3D](#)
Implements a 3D mimetic Laplacian operator.
- class [mtk::Quad1D](#)
Implements a 1D mimetic quadrature.
- class [mtk::RobinBCDescriptor1D](#)
Impose Robin boundary conditions on the operators and on the grids.
- class [mtk::RobinBCDescriptor2D](#)
Impose Robin boundary conditions on the operators and on the grids.
- class [mtk::RobinBCDescriptor3D](#)
Impose Robin boundary conditions on the operators and on the grids.

Typedefs

- typedef Real(* [mtk::CoefficientFunction0D](#))(const Real &tt)
A function of a BC coefficient evaluated on a 0D domain and time.
- typedef Real(* [mtk::CoefficientFunction1D](#))(const Real &xx, const Real &tt)
A function of a BC coefficient evaluated on a 1D domain and time.
- typedef Real(* [mtk::CoefficientFunction2D](#))(const Real &xx, const Real &yy, const Real &tt)
A function of a BC coefficient evaluated on a 2D domain and time.

14.7.1 Detailed Description

Mimetic operators.

14.7.2 Typedef Documentation

14.7.2.1 `mtk::CoefficientFunction0D`

Warning

This definition implies that, for now, coefficients will depend on space and time, thus no extra parameters can influence their behavior. We will fix this soon enough.

Definition at line 111 of file [mtk_robin_bc_descriptor_1d.h](#).

14.7.2.2 `mtk::CoefficientFunction1D`

Definition at line 97 of file [mtk_robin_bc_descriptor_2d.h](#).

14.7.2.3 `mtk::CoefficientFunction2D`

Definition at line 97 of file [mtk_robin_bc_descriptor_3d.h](#).

Chapter 15

Namespace Documentation

15.1 mtk Namespace Reference

Mimetic Methods Toolkit namespace.

Classes

- class [BLASAdapter](#)
Adapter class for the BLAS API.
- class [Curl2D](#)
Implements a 2D mimetic curl operator.
- class [DenseMatrix](#)
Defines a common dense matrix, using a 1D array.
- class [Div1D](#)
Implements a 1D mimetic divergence operator.
- class [Div2D](#)
Implements a 2D mimetic divergence operator.
- class [Div3D](#)
Implements a 3D mimetic divergence operator.
- class [GLPKAdapter](#)
Adapter class for the GLPK API.
- class [Grad1D](#)
Implements a 1D mimetic gradient operator.
- class [Grad2D](#)
Implements a 2D mimetic gradient operator.
- class [Grad3D](#)
Implements a 3D mimetic gradient operator.
- class [Interp1D](#)
Implements a 1D interpolation operator.
- class [Interp2D](#)
Implements a 2D interpolation operator.
- class [Lap1D](#)
Implements a 1D mimetic Laplacian operator.

- class [Lap2D](#)
Implements a 2D mimetic Laplacian operator.
- class [Lap3D](#)
Implements a 3D mimetic Laplacian operator.
- class [LAPACKAdapter](#)
Adapter class for the LAPACK API.
- class [Matrix](#)
Definition of the representation of a matrix in the MTK.
- class [Quad1D](#)
Implements a 1D mimetic quadrature.
- class [RobinBCDescriptor1D](#)
Impose Robin boundary conditions on the operators and on the grids.
- class [RobinBCDescriptor2D](#)
Impose Robin boundary conditions on the operators and on the grids.
- class [RobinBCDescriptor3D](#)
Impose Robin boundary conditions on the operators and on the grids.
- class [Tools](#)
Tool manager class.
- class [UniStgGrid1D](#)
Uniform 1D Staggered Grid.
- class [UniStgGrid2D](#)
Uniform 2D Staggered Grid.
- class [UniStgGrid3D](#)
Uniform 3D Staggered Grid.

Typedefs

- typedef [Real](#)(* [CoefficientFunction0D](#))(const [Real](#) &tt)
A function of a BC coefficient evaluated on a 0D domain and time.
- typedef [Real](#)(* [CoefficientFunction1D](#))(const [Real](#) &xx, const [Real](#) &tt)
A function of a BC coefficient evaluated on a 1D domain and time.
- typedef [Real](#)(* [CoefficientFunction2D](#))(const [Real](#) &xx, const [Real](#) &yy, const [Real](#) &tt)
A function of a BC coefficient evaluated on a 2D domain and time.
- typedef float [Real](#)
Users can simply change this to build a double- or single-precision MTK.

Enumerations

- enum [MatrixStorage](#) { [DENSE](#), [BANDED](#), [CRS](#) }
Considered matrix storage schemes to implement sparse matrices.
- enum [MatrixOrdering](#) { [ROW_MAJOR](#), [COL_MAJOR](#) }
Considered matrix ordering (for Fortran purposes).
- enum [FieldNature](#) { [SCALAR](#), [VECTOR](#) }
Nature of the field discretized in a given grid.
- enum [DirInterp](#) { [SCALAR_TO_VECTOR](#), [VECTOR_TO_SCALAR](#) }
Interpolation operator.

Functions

- float [snrm2_](#) (int *n, float *x, int *incx)
- void [saxpy_](#) (int *n, float *sa, float *sx, int *incx, float *sy, int *incy)
- void [sgemv_](#) (char *trans, int *m, int *n, float *alpha, float *a, int *lda, float *x, int *incx, float *beta, float *y, int *incy)
- void [sgemm_](#) (char *transa, char *transb, int *m, int *n, int *k, double *alpha, double *a, int *lda, double *b, aamm int *ldb, double *beta, double *c, int *ldc)
- std::ostream & [operator<<](#) (std::ostream &stream, [mtk::DenseMatrix](#) &in)
- std::ostream & [operator<<](#) (std::ostream &stream, [mtk::Div1D](#) &in)
- std::ostream & [operator<<](#) (std::ostream &stream, [mtk::Grad1D](#) &in)
- std::ostream & [operator<<](#) (std::ostream &stream, [mtk::Interp1D](#) &in)
- std::ostream & [operator<<](#) (std::ostream &stream, [mtk::Lap1D](#) &in)
- void [sgesv_](#) (int *n, int *nrhs, [Real](#) *a, int *lda, int *ipiv, [Real](#) *b, int *ldb, int *info)
- void [sgels_](#) (char *trans, int *m, int *n, int *nrhs, [Real](#) *a, int *lda, [Real](#) *b, int *ldb, [Real](#) *work, int *lwork, int *info)
Single-precision GEneral matrix Least Squares solver.
- void [sgeqrf_](#) (int *m, int *n, [Real](#) *a, int *lda, [Real](#) *tau, [Real](#) *work, int *lwork, int *info)
Single-precision GEneral matrix QR Factorization.
- void [sormqr_](#) (char *side, char *trans, int *m, int *n, int *k, [Real](#) *a, int *lda, [Real](#) *tau, [Real](#) *c, int *ldc, [Real](#) *work, int *lwork, int *info)
Single-precision Orthogonal [Matrix](#) from QR factorization.
- std::ostream & [operator<<](#) (std::ostream &stream, [mtk::UniStgGrid1D](#) &in)
- std::ostream & [operator<<](#) (std::ostream &stream, [mtk::UniStgGrid2D](#) &in)
- std::ostream & [operator<<](#) (std::ostream &stream, [mtk::UniStgGrid3D](#) &in)

Variables

- const float [kZero](#) {0.0f}
MTK's zero defined according to selective compilation.
- const float [kOne](#) {1.0f}
MTK's one defined according to selective compilation.
- const float [kTwo](#) {2.0f}
MTK's two defined according to selective compilation.
- const float [kDefaultTolerance](#) {1e-7f}
Considered tolerance for comparisons in numerical methods.
- const int [kDefaultOrderAccuracy](#) {2}
Default order of accuracy for mimetic operators.
- const float [kDefaultMimeticThreshold](#) {1e-6f}
Default tolerance for higher-order mimetic operators.
- const int [kCriticalOrderAccuracyDiv](#) {8}
At this order (and higher) we must use the CBSA to construct.
- const int [kCriticalOrderAccuracyGrad](#) {10}
At this order (and higher) we must use the CBSA to construct.

15.1.1 Function Documentation

15.1.1.1 `std::ostream& mtk::operator<< (std::ostream & stream, mtk::Interp1D & in)`

1. Print approximating coefficients for the interior.

Definition at line 66 of file [mtk_interp_1d.cc](#).

15.1.1.2 `std::ostream& mtk::operator<< (std::ostream & stream, mtk::UniStgGrid3D & in)`

1. Print spatial coordinates.
2. Print scalar field.

Definition at line 67 of file [mtk_uni_stg_grid_3d.cc](#).

15.1.1.3 `std::ostream& mtk::operator<< (std::ostream & stream, mtk::UniStgGrid2D & in)`

1. Print spatial coordinates.
2. Print scalar field.

Definition at line 67 of file [mtk_uni_stg_grid_2d.cc](#).

15.1.1.4 `std::ostream& mtk::operator<< (std::ostream & stream, mtk::UniStgGrid1D & in)`

1. Print spatial coordinates.
2. Print scalar field.

Definition at line 68 of file [mtk_uni_stg_grid_1d.cc](#).

15.1.1.5 `std::ostream& mtk::operator<< (std::ostream & stream, mtk::Lap1D & in)`


1. Print order of accuracy.
2. Print approximating coefficients for the interior.
3. No weights, thus print the mimetic boundary coefficients.

Definition at line 73 of file [mtk_lap_1d.cc](#).

15.1.1.6 `std::ostream& mtk::operator<< (std::ostream & stream, mtk::DenseMatrix & in)`

Definition at line 77 of file [mtk_dense_matrix.cc](#).

Here is the call graph for this function:



15.1.1.7 `std::ostream& mtk::operator<< (std::ostream & stream, mtk::Grad1D & in)`

1. Print order of accuracy.
2. Print approximating coefficients for the interior.
3. Print mimetic weights.
4. Print mimetic approximations at the boundary.

Definition at line 79 of file [mtk_grad_1d.cc](#).


15.1.1.8 `std::ostream& mtk::operator<< (std::ostream & stream, mtk::Div1D & in)`

1. Print order of accuracy.
2. Print approximating coefficients for the interior.
3. Print mimetic weights.
4. Print mimetic approximations at the boundary.

Definition at line 79 of file [mtk_div_1d.cc](#).

15.1.1.9 `void mtk::saxpy_ (int * n, float * sa, float * sx, int * incx, float * sy, int * incy)`

Here is the caller graph for this function:



15.1.1.10 void mtk::sgels_ (char * *trans*, int * *m*, int * *n*, int * *nrhs*, Real * *a*, int * *lda*, Real * *b*, int * *ldb*, Real * *work*, int * *lwork*, int * *info*)

SGELS solves overdetermined or underdetermined real linear systems involving an M-by-N matrix A, or its transpose, using a QR or LQ factorization of A. It is assumed that A has full rank.

The following options are provided:

1. If TRANS = 'N' and $m \geq n$: find the least squares solution of an overdetermined system, i.e., solve the least squares problem

$$\text{minimize } || B - A * X ||.$$

2. If TRANS = 'N' and $m < n$: find the minimum norm solution of an underdetermined system $A * X = B$.

3. If TRANS = 'T' and $m \geq n$: find the minimum norm solution of an undetermined system $A^{**T} * X = B$.

4. If TRANS = 'T' and $m < n$: find the least squares solution of an overdetermined system, i.e., solve the least squares problem

$$\text{minimize } || B - A^{**T} * X ||.$$

Several right hand side vectors b and solution vectors x can be handled in a single call; they are stored as the columns of the M-by-NRHS right hand side matrix B and the N-by-NRHS solution matrix X.


See also

<http://www.math.utah.edu/software/lapack/lapack-s/sgels.html>

Parameters


in	<i>trans</i>	Am I giving the transpose of the matrix?
in	<i>m</i>	The number of rows of the matrix a. $m \geq 0$.
in	<i>n</i>	The number of columns of the matrix a. $n \geq 0$.
in	<i>nrhs</i>	The number of right-hand sides.
in,out	<i>a</i>	On entry, the m-by-n matrix a.
in	<i>lda</i>	The leading dimension of a. $lda \geq \max(1,m)$.
in,out	<i>b</i>	On entry, matrix b of right-hand side vectors.
in	<i>ldb</i>	The leading dimension of b. $ldb \geq \max(1,m,n)$.
in,out	<i>work</i>	On exit, if <i>info</i> = 0, <i>work</i> (1) is optimal <i>lwork</i> .
in,out	<i>lwork</i>	The dimension of the array work.
in,out	<i>info</i>	If <i>info</i> = 0, then successful exit.

Here is the caller graph for this function:



15.1.1.11 `void mtk::sgemm_ (char * transa, char * transb, int * m, int * n, int * k, double * alpha, double * a, int * lda, double * b, aamm int * ldb, double * beta, double * c, int * ldc)`

Here is the caller graph for this function:



15.1.1.12 `void mtk::sgemv_ (char * trans, int * m, int * n, float * alpha, float * a, int * lda, float * x, int * incx, float * beta, float * y, int * incy)`

Here is the caller graph for this function:



15.1.1.13 `void mtk::sgeqrf_ (int * m, int * n, Real * a, int * lda, Real * tau, Real * work, int * lwork, int * info)`

Single-Precision Orthogonal Make Q from QR: `dormqr_` overwrites the general real M-by-N matrix C with (Table 1):

SIDE = 'L' SIDE = 'R'

TRANS = 'N': $Q * C * Q^T$ TRANS = 'T': $Q^{*T} * C * Q^{*T}$

where Q is a real orthogonal matrix defined as the product of k elementary reflectors

$$Q = H(1) H(2) \dots H(k)$$

as returned by SGEQRF. Q is of order M if SIDE = 'L' and of order N if SIDE = 'R'.

See also

http://www.netlib.org/lapack/explore-html/df/d97/sgeqrf_8f.html


Parameters

in	<i>m</i>	The number of columns of the matrix a. $n \geq 0$.
in	<i>n</i>	The number of columns of the matrix a. $n \geq 0$.
in, out	<i>a</i>	On entry, the n-by-n matrix a.
in	<i>lda</i>	Leading dimension matrix. $LDA \geq \max(1, M)$.
in, out	<i>tau</i>	Scalars from elementary reflectors. $\min(M, N)$.
in, out	<i>work</i>	Workspace. $info = 0$, $work(1)$ is optimal $lwork$.
in	<i>lwork</i>	The dimension of work. $lwork \geq \max(1, n)$.
in	<i>info</i>	$info = 0$: successful exit.

15.1.1.14 void mtk::sgesv_(int * n, int * nrhs, Real * a, int * lda, int * ipiv, Real * b, int * ldb, int * info)

15.1.1.15 float mtk::snrm2_(int * n, float * x, int * incx)

Here is the caller graph for this function:



15.1.1.16 void mtk::sormqr_(char * side, char * trans, int * m, int * n, int * k, Real * a, int * lda, Real * tau, Real * c, int * ldc, Real * work, int * lwork, int * info)

Single-Precision Orthogonal Make Q from QR: sormqr_ overwrites the general real M-by-N matrix C with (Table 1):

SIDE = 'L' SIDE = 'R'

TRANS = 'N': $Q * C * Q^T$ TRANS = 'T': $Q^{*T} * C * Q^{*T}$

where Q is a real orthogonal matrix defined as the product of k elementary reflectors

$$Q = H(1) H(2) \dots H(k)$$

as returned by SGEQRF. Q is of order M if SIDE = 'L' and of order N if SIDE = 'R'.

See also

http://www.netlib.org/lapack/explore-html/d0/d98/sormqr_8f_source.html

Parameters

in	<i>side</i>	See Table 1 above.
in	<i>trans</i>	See Table 1 above.
in	<i>m</i>	Number of rows of the C matrix.
in	<i>n</i>	Number of columns of the C matrix.
in	<i>k</i>	Number of reflectors.
in,out	<i>a</i>	The matrix containing the reflectors.
in	<i>lda</i>	The dimension of work. $lwork \geq \max(1,n)$.
in	<i>tau</i>	Scalar factors of the elementary reflectors.
in	<i>c</i>	Output matrix.
in	<i>ldc</i>	Leading dimension of the output matrix.
in,out	<i>work</i>	Workspace. $info = 0$, $work(1)$ optimal $lwork$.
in	<i>lwork</i>	The dimension of work.
in,out	<i>info</i>	$info = 0$: successful exit.

Chapter 16


Class Documentation

16.1 mtk::BLASAdapter Class Reference

Adapter class for the BLAS API.

```
#include <mtk_blas_adapter.h>
```

Collaboration diagram for mtk::BLASAdapter:



Static Public Member Functions

- static `Real RealNRM2 (Real *in, int &in_length)`
Compute the $\|x\|_2$ of given array `x`.
- static void `RealAXPY (Real alpha, Real *xx, Real *yy, int &in_length)`
Real-Arithmetic Scalar-Vector plus a Vector.
- static `Real RelNorm2Error (Real *computed, Real *known, int length)`
Computes the relative norm-2 of the error.
- static void `RealDenseMV (Real &alpha, DenseMatrix &aa, Real *xx, Real &beta, Real *yy)`
Real-Arithmetic General (Dense matrices) Matrix-Vector Multiplier.

- static `DenseMatrix RealDenseMM (DenseMatrix &aa, DenseMatrix &bb)`

Real-Arithmetic General (Dense matrices) Matrix-Matrix multiplier.

- static `DenseMatrix RealDenseSM (Real alpha, DenseMatrix &aa)`

Real-Arithmetic General (Dense matrices) Scalar-Matrix multiplier.

16.1.1 Detailed Description

This class contains a collection of static classes, that posses direct access to the underlying structure of the matrices, thus allowing programmers to exploit some of the numerical methods implemented in the BLAS.

The **BLAS (Basic Linear Algebra Subprograms)** are routines that provide standard building blocks for performing basic vector and matrix operations. The Level 1 BLAS perform scalar, vector and vector-vector operations, the Level 2 BLAS perform matrix-vector operations, and the Level 3 BLAS perform matrix-matrix operations.

See also

<http://www.netlib.org/blas/>

Definition at line 96 of file `mtk_blas_adapter.h`.

16.1.2 Member Function Documentation

16.1.2.1 `void mtk::BLASAdapter::RealAXPY (mtk::Real alpha, mtk::Real * xx, mtk::Real * yy, int & in_length)`
[static]

Performs

$$\mathbf{y} := \alpha \mathbf{A} \mathbf{x} + \mathbf{y}$$

Parameters


in	<i>alpha</i>	Scalar of the first array.
in	<i>xx</i>	First array.
in	<i>yy</i>	Second array.
in	<i>in_length</i>	Lengths of the given arrays.

Returns


Norm-2 of the given array.

Definition at line 339 of file [mtk_blas_adapter.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



16.1.2.2 `mtk::DenseMatrix mtk::BLASAdapter::RealDenseMM (mtk::DenseMatrix & aa, mtk::DenseMatrix & bb)` `[static]`

Performs:

$$\mathbf{C} := \mathbf{AB}$$

Parameters

in	<i>aa</i>	First matrix.
in	<i>bb</i>	Second matrix.


See also

<http://ejspeiro.github.io/Netlib-and-CPP/>


1. Make sure input matrices are row-major ordered.
2. Setup the problem.
3. Perform multiplication.

Definition at line 409 of file [mtk_blas_adapter.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



16.1.2.3 `void mtk::BLASAdapter::RealDenseMV (mtk::Real & alpha, mtk::DenseMatrix & aa, mtk::Real * xx, mtk::Real & beta, mtk::Real * yy) [static]`

Performs

$$\mathbf{y} := \alpha \mathbf{A}\mathbf{x} + \beta \mathbf{y}$$

Parameters


in	<i>alpha</i>	First scalar.
in	<i>aa</i>	Given matrix.
in	<i>xx</i>	First vector.
in	<i>beta</i>	Second scalar.
in, out	<i>yy</i>	Second vector (output).

See also


<http://ejspeiro.github.io/Netlib-and-CPP/>

Definition at line 378 of file `mtk_blas_adapter.cc`.

Here is the call graph for this function:



Here is the caller graph for this function:



16.1.2.4 `mtk::DenseMatrix mtk::BLASAdapter::RealDenseSM (mtk::Real alpha, mtk::DenseMatrix & aa) [static]`

Performs:

$$\mathbf{B} := \alpha \mathbf{A}$$

Parameters

in	<i>alpha</i>	Input scalar.
in	<i>aa</i>	Input matrix.


See also

<http://ejspeiro.github.io/Netlib-and-CPP/>

1. Make sure input matrices are row-major ordered.
2. Setup the problem.
3. Perform multiplication.

Definition at line 466 of file `mtk_blas_adapter.cc`.

Here is the call graph for this function:



16.1.2.5 `mtk::Real mtk::BLASAdapter::RealNRM2 (Real * in, int & in_length) [static]`

Parameters


<code>in</code>	<code>in</code>	Input array.
<code>in</code>	<code>in_length</code>	Length of the array.

Returns


Norm-2 of the given array.

Definition at line 324 of file [mtk_blas_adapter.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



16.1.2.6 `mtk::Real mtk::BLASAdapter::RelNorm2Error (mtk::Real * computed, mtk::Real * known, int length)`
 [static]

We compute

$$\frac{\|\tilde{\mathbf{x}} - \mathbf{x}\|_2}{\|\mathbf{x}\|_2}.$$

Parameters


<i>in</i>	<i>known</i>	Array containing the computed solution.
<i>in</i>	<i>computed</i>	Array containing the known solution (ref. solution).

Returns

Relative norm-2 of the error, aka, the difference between the arrays.

Definition at line 358 of file [mtk_blas_adapter.cc](#).

Here is the call graph for this function:



The documentation for this class was generated from the following files:


- [include/mtk_blas_adapter.h](#)
- [src/mtk_blas_adapter.cc](#)

16.2 mtk::Curl2D Class Reference

Implements a 2D mimetic curl operator.

```
#include <mtk_curl_2d.h>
```

Collaboration diagram for mtk::Curl2D:



Public Member Functions

- [UniStgGrid3D operator*](#) (const [UniStgGrid2D](#) &grid) const

Operator application operator on a grid.

- [Curl2D](#) ()

Default constructor.

- [Curl2D](#) (const [Curl2D](#) &curl)

Copy constructor.

- [~Curl2D](#) ()

Destructor.

- bool [ConstructCurl2D](#) (const [UniStgGrid2D](#) &grid, int order_accuracy=kDefaultOrderAccuracy, [Real](#) mimetic_↔ threshold=kDefaultMimeticThreshold)

Factory method implementing the CBS Algorithm to build operator.

- [DenseMatrix ReturnAsDenseMatrix](#) () const

Return the operator as a dense matrix.

Private Attributes

- [DenseMatrix](#) curl_

Actual operator.

- int [order_accuracy_](#)

Order of accuracy.

- [Real](#) [mimetic_threshold_](#)

Mimetic Threshold.

16.2.1 Detailed Description

This class implements a 2D curl operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (CBSA).

Definition at line 77 of file [mtk_curl_2d.h](#).

16.2.2 Constructor & Destructor Documentation

16.2.2.1 mtk::Curl2D::Curl2D ()

Definition at line 79 of file [mtk_curl_2d.cc](#).

16.2.2.2 mtk::Curl2D::Curl2D (const [Curl2D](#) &curl)

Parameters

in	curl	Given curl.
--------------------	----------------------	-------------

Definition at line 83 of file [mtk_curl_2d.cc](#).

16.2.2.3 mtk::Curl2D::~~Curl2D ()

Definition at line 87 of file [mtk_curl_2d.cc](#).

16.2.3 Member Function Documentation


16.2.3.1 `bool mtk::Curl2D::ConstructCurl2D (const UniStgGrid2D & grid, int order_accuracy = kDefaultOrderAccuracy, mtk::Real mimetic_threshold = kDefaultMimeticThreshold)`

Returns

Success of the construction.

Definition at line 89 of file [mtk_curl_2d.cc](#).

Here is the call graph for this function:



16.2.3.2 `mtk::UniStgGrid3D mtk::Curl2D::operator* (const UniStgGrid2D & grid) const`

1. Convert given vector field, into the required auxiliary vector field.

Definition at line 70 of file [mtk_curl_2d.cc](#).

16.2.3.3 `mtk::DenseMatrix mtk::Curl2D::ReturnAsDenseMatrix () const`

Returns

The operator as a dense matrix.

Definition at line 157 of file [mtk_curl_2d.cc](#).

16.2.4 Member Data Documentation

16.2.4.1 DenseMatrix mtk::Curl2D::curl_ [private]

Definition at line 112 of file [mtk_curl_2d.h](#).

16.2.4.2 Real mtk::Curl2D::mimetic_threshold_ [private]

Definition at line 116 of file [mtk_curl_2d.h](#).

16.2.4.3 int mtk::Curl2D::order_accuracy_ [private]

Definition at line 114 of file [mtk_curl_2d.h](#).

The documentation for this class was generated from the following files:


- [include/mtk_curl_2d.h](#)
- [src/mtk_curl_2d.cc](#)

16.3 mtk::DenseMatrix Class Reference

Defines a common dense matrix, using a 1D array.

```
#include <mtk_dense_matrix.h>
```

Collaboration diagram for mtk::DenseMatrix:



Public Member Functions

- [DenseMatrix](#) & [operator=](#) (const [DenseMatrix](#) &in)

Overloaded assignment operator.

- `bool operator== (const DenseMatrix &in)`
Am I equal to the in matrix?
- `DenseMatrix ()`
Default constructor.
- `DenseMatrix (const DenseMatrix &in)`
Copy constructor.
- `DenseMatrix (const int &num_rows, const int &num_cols)`
Construct a dense matrix based on the given dimensions.
- `DenseMatrix (const int &rank, const bool &padded, const bool &transpose)`
Construct a zero-rows-padded identity matrix.
- `DenseMatrix (const Real *const gen, const int &gen_length, const int &pro_length, const bool &transpose)`
Construct a dense Vandermonde matrix.
- `~DenseMatrix ()`
Destructor.
- `Matrix matrix_properties () const noexcept`
Provides access to the matrix data.
- `int num_rows () const noexcept`
Gets the number of rows.
- `int num_cols () const noexcept`
Gets the number of columns.
- `Real * data () const noexcept`
Provides access to the matrix value array.
- `void SetOrdering (mtk::MatrixOrdering oo) noexcept`
Sets the ordering of the matrix.
- `Real GetValue (const int &row_coord, const int &col_coord) const noexcept`
Gets a value on the given coordinates.
- `void SetValue (const int &row_coord, const int &col_coord, const Real &val) noexcept`
Sets a value on the given coordinates.
- `void Transpose ()`
Transpose this matrix.
- `void OrderRowMajor ()`
Make the matrix row-wise ordered.
- `void OrderColMajor ()`
Make the matrix column-wise ordered.
- `bool WriteToFile (const std::string &filename) const`
Writes matrix to a file compatible with Gnuplot 4.6.

Static Public Member Functions

- `static DenseMatrix Kron (const DenseMatrix &aa, const DenseMatrix &bb)`
Construct a dense matrix based on the Kronecker product of arguments.

Private Attributes

- [Matrix](#) `matrix_properties_`

Data related to the matrix nature.

- [Real](#) * `data_`

Array holding the data in contiguous position in memory.

Friends

- `std::ostream & operator<< (std::ostream &stream, DenseMatrix &in)`

Prints the matrix as a block of numbers (standard way).

16.3.1 Detailed Description

For developing purposes, it is better to have a not-so-intricated data structure implementing matrices. This is the purpose of this class: to be used for prototypes of new code for small test cases. In every other instance, this should be replaced by the most appropriate sparse matrix.


Definition at line 92 of file [mtk_dense_matrix.h](#).

16.3.2 Constructor & Destructor Documentation

16.3.2.1 `mtk::DenseMatrix::DenseMatrix ()`

Definition at line 162 of file [mtk_dense_matrix.cc](#).

Here is the call graph for this function:




16.3.2.2 `mtk::DenseMatrix::DenseMatrix (const DenseMatrix &in)`

Parameters

<code>in</code>	<i>in</i>	Given matrix.
-----------------	-----------	---------------

Definition at line 168 of file [mtk_dense_matrix.cc](#).

Here is the call graph for this function:



16.3.2.3 mtk::DenseMatrix::DenseMatrix (const int & *num_rows*, const int & *num_cols*)

Parameters


in	<i>num_rows</i>	Number of rows of the required matrix.
in	<i>num_cols</i>	Number of rows of the required matrix.

Exceptions

<i>std::bad_alloc</i>	
-----------------------	--

Definition at line 201 of file [mtk_dense_matrix.cc](#).

Here is the call graph for this function:



16.3.2.4 mtk::DenseMatrix::DenseMatrix (const int & *rank*, const bool & *padded*, const bool & *transpose*)

Used in the construction of the mimetic operators.

Def**. A **padded matrix** is a matrix with its first and last rows initialized to only zero values:

$$\bar{\mathbf{I}} = \begin{pmatrix} 0 & 0 & 0 & \dots & 0 \\ 1 & 0 & 0 & \dots & 0 \\ 0 & 1 & 0 & \dots & 0 \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & 0 & \dots & 1 \\ 0 & 0 & 0 & \dots & 0 \end{pmatrix}$$

Parameters

in	<i>rank</i>	Rank or number of rows/cols in square matrix.
in	<i>padded</i>	Should it be padded?
in	<i>transpose</i>	Should I return the transpose of the requested matrix?

Exceptions

<i>std::bad_alloc</i>	
-----------------------	--

Definition at line 223 of file [mtk_dense_matrix.cc](#).

Here is the call graph for this function:



16.3.2.5 mtk::DenseMatrix::DenseMatrix (const Real *const *gen*, const int & *gen_length*, const int & *pro_length*, const bool & *transpose*)

Def**. In linear algebra, a **Vandermonde matrix** is a matrix with terms of a geometric progression in each row. This progression uses the terms of a given **generator vector**:

$$\mathbf{V} = \begin{pmatrix} 1 & \alpha_1 & \alpha_1^2 & \dots & \alpha_1^{n-1} \\ 1 & \alpha_2 & \alpha_2^2 & \dots & \alpha_2^{n-1} \\ 1 & \alpha_3 & \alpha_3^2 & \dots & \alpha_3^{n-1} \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 1 & \alpha_m & \alpha_m^2 & \dots & \alpha_m^{n-1} \end{pmatrix}$$

This constructor generates a Vandermonde matrix, as defined above.

Obs**. It is important to understand that the generator vectors to be used are nothing but a very particular instance of a grid. These are little chunks, little samples, if you will, of a grid which is rectangular and uniform. So the selected samples, on the [mtk::Div1D](#) and [mtk::Grad1D](#), basically represent the entire space, the entire grid. This is why neither the CRS nor the CBS algorithms may work for irregular geometries, such as curvilinear grids.

Parameters

in	<i>gen</i>	Given generator vector.
in	<i>gen_length</i>	Length generator vector.
in	<i>pro_length</i>	Length the progression.
in	<i>transpose</i>	Should the transpose be created instead?

Exceptions

<i>std::bad_alloc</i>	
-----------------------	--

Definition at line 264 of file [mtk_dense_matrix.cc](#).

Here is the call graph for this function:



16.3.2.6 mtk::DenseMatrix::~~DenseMatrix ()

Definition at line 312 of file [mtk_dense_matrix.cc](#).

16.3.3 Member Function Documentation


16.3.3.1 mtk::Real * mtk::DenseMatrix::data () const [noexcept]

Returns

Pointer to an array of [mtk::Real](#).

Definition at line 343 of file [mtk_dense_matrix.cc](#).

Here is the caller graph for this function:



16.3.3.2 `mtk::Real mtk::DenseMatrix::GetValue (const int & row_coord, const int & col_coord) const` [noexcept]

Parameters


in	<i>row_coord</i>	Row coordinate.
in	<i>col_coord</i>	Column coordinate.

Returns


The required value at the specified coordinates.

Definition at line 348 of file [mtk_dense_matrix.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



16.3.3.3 `mtk::DenseMatrix mtk::DenseMatrix::Kron (const DenseMatrix & aa, const DenseMatrix & bb) [static]`

Parameters

<code>in</code>	<code>aa</code>	First matrix.
-----------------	-----------------	---------------

<code>in</code>	<code>bb</code>	Second matrix.
-----------------	-----------------	----------------


Exceptions

<code>std::bad_alloc</code>


Todo Implement Kronecker product using the BLAS.

Definition at line 490 of file `mtk_dense_matrix.cc`.

Here is the call graph for this function:



Here is the caller graph for this function:




16.3.3.4 `mtk::Matrix mtk::DenseMatrix::matrix_properties () const [noexcept]`

Returns

Pointer to a [Matrix](#).

Definition at line 318 of file [mtk_dense_matrix.cc](#).

Here is the caller graph for this function:




16.3.3.5 `int mtk::DenseMatrix::num_cols () const [noexcept]`

Returns

Number of columns of the matrix.

Definition at line 338 of file [mtk_dense_matrix.cc](#).

Here is the caller graph for this function:




16.3.3.6 `int mtk::DenseMatrix::num_rows () const [noexcept]`

Returns

Number of rows of the matrix.

Definition at line 333 of file [mtk_dense_matrix.cc](#).

Here is the caller graph for this function:



16.3.3.7 mtk::DenseMatrix & mtk::DenseMatrix::operator= (const DenseMatrix & in)

Parameters


<i>in</i>	<i>in</i>	Given matrix.
-----------	-----------	---------------

Returns

Copy of the given matrix.

Definition at line 100 of file [mtk_dense_matrix.cc](#).


Here is the call graph for this function:



16.3.3.8 `bool mtk::DenseMatrix::operator==(const DenseMatrix & in)`

Definition at line 141 of file [mtk_dense_matrix.cc](#).

Here is the call graph for this function:




16.3.3.9 `void mtk::DenseMatrix::OrderColMajor ()`

Todo Improve this so that no new arrays have to be created.

Definition at line 451 of file [mtk_dense_matrix.cc](#).

Here is the caller graph for this function:




16.3.3.10 `void mtk::DenseMatrix::OrderRowMajor ()`

Todo Improve this so that no new arrays have to be created.

Definition at line 410 of file [mtk_dense_matrix.cc](#).

Here is the caller graph for this function:



16.3.3.11 void mtk::DenseMatrix::SetOrdering (mtk::MatrixOrdering oo) [noexcept]

Parameters


in	oo	Ordering.
----	----	-----------

Returns


The required value at the specified coordinates.

Definition at line 323 of file [mtk_dense_matrix.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:




16.3.3.12 `void mtk::DenseMatrix::SetValue (const int & row_coord, const int & col_coord, const Real & val)` [noexcept]

Parameters


in	<i>row_coord</i>	Row coordinate.
in	<i>col_coord</i>	Column coordinate.
in	<i>val</i>	Row Actual value to be inserted.

Definition at line 360 of file `mtk_dense_matrix.cc`.

Here is the call graph for this function:



Here is the caller graph for this function:




16.3.3.13 void mtk::DenseMatrix::Transpose ()

Todo Improve this so that no extra arrays have to be created.

Definition at line 373 of file [mtk_dense_matrix.cc](#).

Here is the caller graph for this function:



16.3.3.14 `bool mtk::DenseMatrix::WriteToFile (const std::string & filename) const`

Parameters

<code>in</code>	<code>filename</code>	Name of the output file.
-----------------	-----------------------	--------------------------

Returns

Success of the file writing process.

See also

<http://www.gnuplot.info/>

Definition at line 531 of file `mtk_dense_matrix.cc`.

16.3.4 Friends And Related Function Documentation

16.3.4.1 `std::ostream& operator<< (std::ostream & stream, mtk::DenseMatrix & in)` `[friend]`

Definition at line 77 of file `mtk_dense_matrix.cc`.

16.3.5 Member Data Documentation

16.3.5.1 `Real* mtk::DenseMatrix::data_` `[private]`

Definition at line 291 of file `mtk_dense_matrix.h`.

16.3.5.2 Matrix `mtk::DenseMatrix::matrix_properties_` [private]

Definition at line 289 of file [mtk_dense_matrix.h](#).

The documentation for this class was generated from the following files:


- [include/mtk_dense_matrix.h](#)
- [src/mtk_dense_matrix.cc](#)

16.4 `mtk::Div1D` Class Reference

Implements a 1D mimetic divergence operator.

```
#include <mtk_div_1d.h>
```


Collaboration diagram for mtk::Div1D:



Public Member Functions

- [Div1D\(\)](#)

- *Default constructor.*
- `Div1D` (const `Div1D` &div)
- *Copy constructor.*
- `~Div1D` ()
- *Destructor.*
- bool `ConstructDiv1D` (int order_accuracy=`kDefaultOrderAccuracy`, Real mimetic_threshold=`kDefaultMimeticThreshold`)
- *Factory method implementing the CBS Algorithm to build operator.*
- int `num_bndy_coefs` () const
- *Returns how many coefficients are approximating at the boundary.*
- Real * `coefs_interior` () const
- *Returns coefficients for the interior of the grid.*
- Real * `weights_crs` (void) const
- *Return collection of weights as computed by the CRSA.*
- Real * `weights_cbs` (void) const
- *Return collection of weights as computed by the CBSA.*
- `DenseMatrix mim_bndy` () const
- *Return collection of mimetic approximations at the boundary.*
- `DenseMatrix ReturnAsDenseMatrix` (const `UniStgGrid1D` &grid) const
- *Return the operator as a dense matrix.*

Private Member Functions

- bool `ComputeStencilInteriorGrid` (void)
- *Stage 1 of the CBS Algorithm.*
- bool `ComputeRationalBasisNullSpace` (void)
- *Stage 2.1 of the CBS Algorithm.*
- bool `ComputePreliminaryApproximations` (void)
- *Stage 2.2 of the CBS Algorithm.*
- bool `ComputeWeights` (void)
- *Stage 2.3 of the CBS Algorithm.*
- bool `ComputeStencilBoundaryGrid` (void)
- *Stage 2.4 of the CBS Algorithm.*
- bool `AssembleOperator` (void)
- *Stage 3 of the CBS Algorithm.*

Private Attributes

- int `order_accuracy_`
- *Order of numerical accuracy of the operator.*
- int `dim_null_`
- *Dim. null-space for boundary approximations.*
- int `num_bndy_coefs_`
- *Req. coefs. per bndy pt. uni. order accuracy.*
- int `divergence_length_`
- *Length of the output array.*
- int `minrow_`

- *Row from the optimizer with the minimum rel. nor.*
- `int row_`
Row currently processed by the optimizer.
- `DenseMatrix rat_basis_null_space_`
Rational b. null-space w. bndy.
- `Real * coeffs_interior_`
Interior stencil.
- `Real * prem_apps_`
2D array of boundary preliminary approximations.
- `Real * weights_crs_`
Array containing weights from CRSA.
- `Real * weights_cbs_`
Array containing weights from CBSA.
- `Real * mim_bndy_`
Array containing mimetic boundary approximations.
- `Real * divergence_`
Output array containing the operator and weights.
- `Real mimetic_threshold_`
< Mimetic threshold.

Friends

- `std::ostream & operator<< (std::ostream &stream, Div1D &in)`
Output stream operator for printing.

16.4.1 Detailed Description

This class implements a 1D divergence operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (CBSA).

Definition at line 81 of file `mtk_div_1d.h`.

16.4.2 Constructor & Destructor Documentation

16.4.2.1 `mtk::Div1D::Div1D ()`

Definition at line 125 of file `mtk_div_1d.cc`.

16.4.2.2 `mtk::Div1D::Div1D (const Div1D &div)`

Parameters

<code>in</code>	<code>div</code>	Given divergence.
-----------------	------------------	-------------------

Definition at line 140 of file `mtk_div_1d.cc`.

16.4.2.3 `mtk::Div1D::~~Div1D ()`

Definition at line 155 of file `mtk_div_1d.cc`.

16.4.3 Member Function Documentation

16.4.3.1 `bool mtk::Div1D::AssembleOperator (void) [private]`

Construct the output array with the operator and its weights.

1. The first entry of the array will contain the order of accuracy.
2. The second entry the collection of coefficients for interior of grid.
3. If `order_accuracy_ > 2`, then third entry is the collection of weights.
4. If `order_accuracy_ > 2`, next `dim_null_` entries is approximating coefficients for the west boundary of the grid.

Definition at line [1342](#) of file [mtk_div_1d.cc](#).

16.4.3.2 `mtk::Real * mtk::Div1D::coeffs_interior () const`

Returns

Coefficients for the interior of the grid.

Definition at line [320](#) of file [mtk_div_1d.cc](#).


16.4.3.3 `bool mtk::Div1D::ComputePreliminaryApproximations (void) [private]`

Compute the set of preliminary approximations on the boundary neighborhood.

1. Create generator vector for the first approximation.
2. Compute the `dim_null` near-the-boundary columns of the pi matrix.
3. Create the Vandermonde matrix for this iteration.
4. New order-selector vector (gets re-written with LAPACK solutions).
5. Solving $TT*rr = ob$ yields the columns `rr` of the `KK` matrix.
6. Scale the `KK` matrix to make it a rational basis for null-space.
7. Extract the last `dim_null` values of the pre-scaled `ob`.
8. Once we posses the bottom elements, we proceed with the scaling.

Definition at line [691](#) of file [mtk_div_1d.cc](#).

Here is the call graph for this function:




16.4.3.4 `bool mtk::Div1D::ComputeRationalBasisNullSpace (void) [private]`

Compute a rational basis for the null-space of the Vandermonde matrix approximating at the west boundary.

1. Create generator vector for the first approximation.
2. Create Vandermonde matrix.
3. QR-factorize the Vandermonde matrix.
4. Extract the basis for the null-space from Q matrix.
5. Scale null-space to make it rational.

Definition at line 515 of file `mtk_div_1d.cc`.

Here is the call graph for this function:



16.4.3.5 `bool mtk::Div1D::ComputeStencilBoundaryGrid (void) [private]`

Compute mimetic stencil approximating at boundary.

1. Collect lambda values.
2. Compute alpha values.
3. Compute the mimetic boundary approximations.

Definition at line 1241 of file [mtk_div_1d.cc](#).


16.4.3.6 `bool mtk::Div1D::ComputeStencilInteriorGrid (void) [private]`

Compute the stencil approximating the interior of the staggered grid.

1. Create vector for interior spatial coordinates.
2. Create Vandermonde matrix (using interior coordinates as generator).
3. Create order-selector vector.
4. Solve dense Vandermonde system to attain the interior coefficients.

Definition at line 414 of file [mtk_div_1d.cc](#).

Here is the call graph for this function:




16.4.3.7 bool mtk::Div1D::ComputeWeights (void) [private]

Compute the set of mimetic weights to impose the mimetic condition.

1. Construct the \mathbf{A} matrix.
2. Use interior stencil to build proper RHS vector \mathbf{h} .
3. Get weights (as **CRSA**): $\mathbf{A}\mathbf{q} = \mathbf{h}$.
4. If required order is greater than critical order, start the **CBSA**.
5. Create \mathbf{B} matrix from \mathbf{A} .
6. Prepare constraint vector as in the CBSA: \mathbf{c} .
7. Brute force search through all the rows of the Φ matrix.
8. Apply solution found from brute force search.

Definition at line 911 of file [mtk_div_1d.cc](#).

Here is the call graph for this function:



16.4.3.8 `bool mtk::Div1D::ConstructDiv1D (int order_accuracy = kDefaultOrderAccuracy, mtk::Real mimetic_threshold = kDefaultMimeticThreshold)`

Returns

Success of the construction.


1. Compute stencil for the interior cells.
2. Compute a rational basis for the null-space for the first matrix.
3. Compute preliminary approximation (non-mimetic) on the boundaries.
4. Compute quadrature weights to impose the mimetic conditions.
5. Compute real approximation (mimetic) on the boundaries.
6. Assemble operator.

Definition at line 176 of file [mtk_div_1d.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:




16.4.3.9 `mtk::DenseMatrix mtk::Div1D::mim_bndy () const`

Returns

Collection of mimetic approximations at the boundary.

Definition at line 335 of file [mtk_div_1d.cc](#).

Here is the call graph for this function:

**16.4.3.10 int mtk::Div1D::num_bndy_coeffs () const****Returns**

How many coefficients are approximating at the boundary.

Definition at line 315 of file [mtk_div_1d.cc](#).


16.4.3.11 mtk::DenseMatrix mtk::Div1D::ReturnAsDenseMatrix (const UniStgGrid1D & grid) const**Returns**

The operator as a dense matrix.


1. Insert mimetic boundary at the west.
2. Insert coefficients for the interior of the grid.
3. Impose center-skew symmetry by permuting the mimetic boundaries.

Definition at line 350 of file [mtk_div_1d.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



16.4.3.12 `mtk::Real * mtk::Div1D::weights_cbs (void) const`

Returns

Collection of weights as computed by the CBSA.

Definition at line 330 of file [mtk_div_1d.cc](#).

16.4.3.13 `mtk::Real * mtk::Div1D::weights_crs (void) const`

Returns

Collection of weights as computed by the CRSA.

Definition at line 325 of file [mtk_div_1d.cc](#).

16.4.4 Friends And Related Function Documentation

16.4.4.1 `std::ostream& operator<< (std::ostream & stream, mtk::Div1D & in) [friend]`

1. Print order of accuracy.
2. Print approximating coefficients for the interior.
3. Print mimetic weights.
4. Print mimetic approximations at the boundary.

Definition at line 79 of file [mtk_div_1d.cc](#).

16.4.5 Member Data Documentation

16.4.5.1 `Real* mtk::Div1D::coeffs_interior_ [private]`

Definition at line 202 of file [mtk_div_1d.h](#).

16.4.5.2 `int mtk::Div1D::dim_null_ [private]`

Definition at line 194 of file [mtk_div_1d.h](#).

16.4.5.3 `Real* mtk::Div1D::divergence_ [private]`

Definition at line 207 of file [mtk_div_1d.h](#).

16.4.5.4 `int mtk::Div1D::divergence_length_ [private]`

Definition at line 196 of file [mtk_div_1d.h](#).

16.4.5.5 `Real* mtk::Div1D::mim_bndy_ [private]`

Definition at line 206 of file [mtk_div_1d.h](#).

16.4.5.6 `Real mtk::Div1D::mimetic_threshold_ [private]`

Definition at line 209 of file [mtk_div_1d.h](#).

16.4.5.7 `int mtk::Div1D::minrow_ [private]`

Definition at line 197 of file [mtk_div_1d.h](#).

16.4.5.8 `int mtk::Div1D::num_bndy_coeffs_ [private]`

Definition at line 195 of file [mtk_div_1d.h](#).

16.4.5.9 `int mtk::Div1D::order_accuracy_ [private]`

Definition at line 193 of file [mtk_div_1d.h](#).

16.4.5.10 `Real* mtk::Div1D::prem_apps_ [private]`

Definition at line 203 of file [mtk_div_1d.h](#).

16.4.5.11 `DenseMatrix mtk::Div1D::rat_basis_null_space_ [private]`

Definition at line 200 of file [mtk_div_1d.h](#).

16.4.5.12 `int mtk::Div1D::row_ [private]`

Definition at line 198 of file [mtk_div_1d.h](#).

16.4.5.13 **Real*** mtk::Div1D::weights_cbs_ [private]

Definition at line 205 of file [mtk_div_1d.h](#).

16.4.5.14 **Real*** mtk::Div1D::weights_crs_ [private]

Definition at line 204 of file [mtk_div_1d.h](#).

The documentation for this class was generated from the following files:


- [include/mtk_div_1d.h](#)
- [src/mtk_div_1d.cc](#)

16.5 mtk::Div2D Class Reference

Implements a 2D mimetic divergence operator.

```
#include <mtk_div_2d.h>
```

Collaboration diagram for mtk::Div2D:



Public Member Functions

- [Div2D\(\)](#)

Default constructor.

- [Div2D](#) (const [Div2D](#) &div)

Copy constructor.

- [~Div2D](#) ()

Destructor.

- bool [ConstructDiv2D](#) (const [UniStgGrid2D](#) &grid, int order_accuracy=[kDefaultOrderAccuracy](#), [Real](#) mimetic_↔ threshold=[kDefaultMimeticThreshold](#))

Factory method implementing the CBS Algorithm to build operator.

- [DenseMatrix ReturnAsDenseMatrix](#) () const

Return the operator as a dense matrix.

Private Attributes

- [DenseMatrix divergence_](#)

Actual operator.

- int [order_accuracy_](#)

Order of accuracy.

- [Real mimetic_threshold_](#)

Mimetic Threshold.

16.5.1 Detailed Description

This class implements a 2D divergence operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (CBSA).

Definition at line 76 of file [mtk_div_2d.h](#).

16.5.2 Constructor & Destructor Documentation

16.5.2.1 [mtk::Div2D::Div2D](#) ()

Definition at line 69 of file [mtk_div_2d.cc](#).

16.5.2.2 [mtk::Div2D::Div2D](#) (const [Div2D](#) &div)

Parameters

in	div	Given divergence.
--------------------	---------------------	-------------------

Definition at line 73 of file [mtk_div_2d.cc](#).

16.5.2.3 [mtk::Div2D::~~Div2D](#) ()

Definition at line 77 of file [mtk_div_2d.cc](#).

16.5.3 Member Function Documentation


16.5.3.1 `bool mtk::Div2D::ConstructDiv2D (const UniStgGrid2D & grid, int order_accuracy = kDefaultOrderAccuracy, mtk::Real mimetic_threshold = kDefaultMimeticThreshold)`

Returns

Success of the construction.

Definition at line 79 of file [mtk_div_2d.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



16.5.3.2 `mtk::DenseMatrix mtk::Div2D::ReturnAsDenseMatrix () const`

Returns

The operator as a dense matrix.

Definition at line 147 of file [mtk_div_2d.cc](#).

Here is the caller graph for this function:

**16.5.4 Member Data Documentation****16.5.4.1 DenseMatrix mtk::Div2D::divergence_ [private]**

Definition at line 108 of file [mtk_div_2d.h](#).

16.5.4.2 Real mtk::Div2D::mimetic_threshold_ [private]

Definition at line 112 of file [mtk_div_2d.h](#).

16.5.4.3 int mtk::Div2D::order_accuracy_ [private]

Definition at line 110 of file [mtk_div_2d.h](#).

The documentation for this class was generated from the following files:


- [include/mtk_div_2d.h](#)
- [src/mtk_div_2d.cc](#)

16.6 mtk::Div3D Class Reference

Implements a 3D mimetic divergence operator.

```
#include <mtk_div_3d.h>
```


Collaboration diagram for mtk::Div3D:



Public Member Functions

- [Div3D \(\)](#)

Default constructor.

- [Div3D](#) (const [Div3D](#) &div)

Copy constructor.

- [~Div3D](#) ()

Destructor.

- bool [ConstructDiv3D](#) (const [UniStgGrid3D](#) &grid, int order_accuracy=[kDefaultOrderAccuracy](#), [Real](#) mimetic_↔ threshold=[kDefaultMimeticThreshold](#))

Factory method implementing the CBS Algorithm to build operator.

- [DenseMatrix ReturnAsDenseMatrix](#) () const

Return the operator as a dense matrix.

Private Attributes

- [DenseMatrix](#) divergence_

Actual operator.

- int [order_accuracy_](#)

Order of accuracy.

- [Real](#) [mimetic_threshold_](#)

Mimetic Threshold.

16.6.1 Detailed Description

This class implements a 3D divergence operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (CBSA).

Definition at line 76 of file [mtk_div_3d.h](#).

16.6.2 Constructor & Destructor Documentation

16.6.2.1 [mtk::Div3D::Div3D](#) ()

Definition at line 67 of file [mtk_div_3d.cc](#).

16.6.2.2 [mtk::Div3D::Div3D](#) (const [Div3D](#) &div)

Parameters

in	div	Given divergence.
--------------------	---------------------	-------------------

Definition at line 71 of file [mtk_div_3d.cc](#).

16.6.2.3 [mtk::Div3D::~~Div3D](#) ()

Definition at line 75 of file [mtk_div_3d.cc](#).

16.6.3 Member Function Documentation

16.6.3.1 `bool mtk::Div3D::ConstructDiv3D (const UniStgGrid3D & grid, int order_accuracy = kDefaultOrderAccuracy, mtk::Real mimetic_threshold = kDefaultMimeticThreshold)`


Returns

Success of the construction.

1. Build preliminary staggering through the x direction.
2. Build preliminary staggering through the y direction.
3. Build preliminary staggering through the z direction.
4. Actual operator: $DD_{xyz} = [dx \ dy \ dz]$.

Definition at line 77 of file [mtk_div_3d.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



16.6.3.2 `mtk::DenseMatrix mtk::Div3D::ReturnAsDenseMatrix () const`

Returns

The operator as a dense matrix.

Definition at line 186 of file [mtk_div_3d.cc](#).

Here is the caller graph for this function:



16.6.4 Member Data Documentation

16.6.4.1 `DenseMatrix mtk::Div3D::divergence_ [private]`

Definition at line 108 of file [mtk_div_3d.h](#).

16.6.4.2 `Real mtk::Div3D::mimetic_threshold_ [private]`

Definition at line 112 of file [mtk_div_3d.h](#).

16.6.4.3 `int mtk::Div3D::order_accuracy_ [private]`

Definition at line 110 of file [mtk_div_3d.h](#).

The documentation for this class was generated from the following files:


- [include/mtk_div_3d.h](#)
- [src/mtk_div_3d.cc](#)

16.7 mtk::GLPKAdapter Class Reference

Adapter class for the GLPK API.

```
#include <mtk_glpk_adapter.h>
```

Collaboration diagram for mtk::GLPKAdapter:



Static Public Member Functions

- static `mtk::Real SolveSimplexAndCompare` (`mtk::Real *A`, `int nrows`, `int ncols`, `int kk`, `mtk::Real *hh`, `mtk::Real *qq`, `int robjective`, `mtk::Real mimetic_tol`, `int copy`)

Solves a CLO problem and compares the solution to a reference solution.

16.7.1 Detailed Description

This class contains a collection of static classes, that posses direct access to the underlying structure of the matrices, thus allowing programmers to exploit some of the numerical methods implemented in the GLPK.

The **GLPK (GNU Linear Programming Kit)** package is intended for solving large-scale linear programming (LP), mixed integer programming (MIP), and other related problems. It is a set of routines written in ANSI C and organized in the form of a callable library.

Warning

We use the GLPK temporarily in order to test the CBSA, but it will be removed due to potential licensing issues.

See also

<http://www.gnu.org/software/glpk/>

Todo Rescind from the GLPK as the numerical core for CLO problems.

Definition at line 101 of file `mtk_glpk_adapter.h`.

16.7.2 Member Function Documentation

16.7.2.1 `mtk::Real mtk::GLPKAdapter::SolveSimplexAndCompare (mtk::Real * A, int nrows, int ncols, int kk, mtk::Real * hh, mtk::Real * qq, int robjective, mtk::Real mimetic_tol, int copy) [static]`

This routine is the pivot of the CBSA. It solves a Constrained Linear Optimization (CLO) problem, and it compares the attained solution to a given reference solution. This comparison is done computing the norm-2 relative error.

Parameters

in	<i>alpha</i>	First scalar.
in	<i>AA</i>	Given matrix.
in	<i>xx</i>	First vector.
in	<i>beta</i>	Second scalar.
in	<i>beta</i>	Second scalar.
in, out	<i>yy</i>	Second vector (output).
in	<i>xx</i>	First vector.
in	<i>beta</i>	Second scalar.
in	<i>beta</i>	Second scalar.

Returns

Relative error computed between attained solution and provided ref.

Warning

GLPK indexes in $[1, n]$, so we must get the extra space needed.


1. Memory allocation.
2. Fill the problem.
3. Copy the row to the vector objective.
4. Forming the RHS.
5. Setting up the objective function.
6. Setting up constraints.
7. Copy the matrix minus the row objective to the glpk problem.
8. Solve problem.

Definition at line 76 of file [mtk_glpk_adapter.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



The documentation for this class was generated from the following files:


- [include/mtk_glpk_adapter.h](#)
- [src/mtk_glpk_adapter.cc](#)

16.8 mtk::Grad1D Class Reference

Implements a 1D mimetic gradient operator.

```
#include <mtk_grad_1d.h>
```


Collaboration diagram for mtk::Grad1D:



Public Member Functions

- [Grad1D \(\)](#)

- *Default constructor.*
- [Grad1D](#) (const [Grad1D](#) &grad)
- *Copy constructor.*
- [~Grad1D](#) ()
- *Destructor.*
- bool [ConstructGrad1D](#) (int order_accuracy=[kDefaultOrderAccuracy](#), [Real](#) mimetic_threshold=[kDefaultMimeticThreshold](#))
- *Factory method implementing the CBS Algorithm to build operator.*
- int [num_bndy_coeffs](#) () const
- *Returns how many coefficients are approximating at the boundary.*
- [Real](#) * [coeffs_interior](#) () const
- *Returns coefficients for the interior of the grid.*
- [Real](#) * [weights_crs](#) (void) const
- *Returns collection of weights as computed by the CRSA.*
- [Real](#) * [weights_cbs](#) (void) const
- *Returns collection of weights as computed by the CBSA.*
- [DenseMatrix](#) [mim_bndy](#) () const
- *Return collection of mimetic approximations at the boundary.*
- [DenseMatrix](#) [ReturnAsDenseMatrix](#) ([Real](#) west, [Real](#) east, int num_cells_x) const
- *Returns the operator as a dense matrix.*
- [DenseMatrix](#) [ReturnAsDenseMatrix](#) (const [UniStgGrid1D](#) &grid) const
- *Returns the operator as a dense matrix.*
- [DenseMatrix](#) [ReturnAsDimensionlessDenseMatrix](#) (int num_cells_x) const
- *Returns the operator as a dimensionless dense matrix.*

Private Member Functions

- bool [ComputeStencilInteriorGrid](#) (void)
- *Stage 1 of the CBS Algorithm.*
- bool [ComputeRationalBasisNullSpace](#) (void)
- *Stage 2.1 of the CBS Algorithm.*
- bool [ComputePreliminaryApproximations](#) (void)
- *Stage 2.2 of the CBS Algorithm.*
- bool [ComputeWeights](#) (void)
- *Stage 2.3 of the CBS Algorithm.*
- bool [ComputeStencilBoundaryGrid](#) (void)
- *Stage 2.4 of the CBS Algorithm.*
- bool [AssembleOperator](#) (void)
- *Stage 3 of the CBS Algorithm.*

Private Attributes

- int [order_accuracy_](#)
- *Order of numerical accuracy of the operator.*
- int [dim_null_](#)
- *Dim. null-space for boundary approximations.*
- int [num_bndy_approxs_](#)

- *Req. approximations at and near the boundary.*
- int [num_bndy_coeffs_](#)
Req. coeffs. per bndy pt. uni. order accuracy.
- int [gradient_length_](#)
Length of the output array.
- int [minrow_](#)
Row from the optimizer with the minimum rel. nor.
- int [row_](#)
Row currently processed by the optimizer.
- [DenseMatrix](#) [rat_basis_null_space_](#)
Rational b. null-space w. bndy.
- [Real](#) * [coeffs_interior_](#)
Interior stencil.
- [Real](#) * [prem_apps_](#)
2D array of boundary preliminary approximations.
- [Real](#) * [weights_crs_](#)
Array containing weights from CRSA.
- [Real](#) * [weights_cbs_](#)
Array containing weights from CBSA.
- [Real](#) * [mim_bndy_](#)
Array containing mimetic boundary approximations.
- [Real](#) * [gradient_](#)
Output array containing the operator and weights.
- [Real](#) [mimetic_threshold_](#)
< Mimetic threshold.

Friends

- [std::ostream](#) & [operator<<](#) ([std::ostream](#) &stream, [Grad1D](#) &in)
Output stream operator for printing.

16.8.1 Detailed Description

This class implements a 1D gradient operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (C↔BSA).

Definition at line 81 of file [mtk_grad_1d.h](#).

16.8.2 Constructor & Destructor Documentation

16.8.2.1 mtk::Grad1D::Grad1D ()

Definition at line 129 of file [mtk_grad_1d.cc](#).

16.8.2.2 mtk::Grad1D::Grad1D (const Grad1D & grad)

Parameters

<i>in</i>	<i>div</i>	Given divergence.
-----------	------------	-------------------

Definition at line 145 of file [mtk_grad_1d.cc](#).

16.8.2.3 mtk::Grad1D::~~Grad1D ()

Definition at line 161 of file [mtk_grad_1d.cc](#).

16.8.3 Member Function Documentation

16.8.3.1 bool mtk::Grad1D::AssembleOperator (void) [private]

Construct the output array with the operator and its weights.

1. The first entry of the array will contain the order of accuracy.
2. The second entry of the array will contain the collection of approximating coefficients for the interior of the grid.
3. The third entry will contain the collection of weights.
4. The next $\text{dim_null} + 1$ entries will contain the collections of approximating coefficients for the west boundary of the grid.

Definition at line 1499 of file [mtk_grad_1d.cc](#).

16.8.3.2 mtk::Real * mtk::Grad1D::coeffs_interior () const

Returns

Coefficients for the interior of the grid.

Definition at line 326 of file [mtk_grad_1d.cc](#).


16.8.3.3 bool mtk::Grad1D::ComputePreliminaryApproximations (void) [private]

Compute the set of preliminary approximations on the boundary neighborhood.

1. Create generator vector for the first approximation.
2. Compute the dim_null near-the-boundary columns of the pi matrix.
3. Create the Vandermonde matrix for this iteration.
4. New order-selector vector (gets re-written with LAPACK solutions).
5. Solving $\text{TT} * \text{rr} = \text{ob}$ yields the columns rr of the kk matrix.
6. Scale the kk matrix to make it a rational basis for null-space.
7. Extract the last dim_null values of the pre-scaled ob .
8. Once we possess the bottom elements, we proceed with the scaling.

Definition at line 831 of file [mtk_grad_1d.cc](#).

Here is the call graph for this function:




16.8.3.4 `bool mtk::Grad1D::ComputeRationalBasisNullSpace(void) [private]`

Compute a rational basis for the null-space of the Vandermonde matrix approximating at the west boundary.

1. Create generator vector for the first approximation.
2. Create Vandermonde matrix.
3. QR-factorize the Vandermonde matrix.
4. Extract the basis for the null-space from Q matrix.
5. Scale null-space to make it rational.

Definition at line 648 of file [mtk_grad_1d.cc](#).

Here is the call graph for this function:



16.8.3.5 `bool mtk::Grad1D::ComputeStencilBoundaryGrid (void) [private]`

Compute mimetic stencil approximating at boundary.

1. Collect lambda values.
2. Compute alpha values.
3. Compute the mimetic boundary approximations.

Definition at line 1393 of file [mtk_grad_1d.cc](#).

16.8.3.6 `bool mtk::Grad1D::ComputeStencilInteriorGrid (void) [private]`

Compute the stencil approximating the interior of the staggered grid.

1. Create vector for interior spatial coordinates.
2. Create Vandermonde matrix (using interior coordinates as generator).
3. Create order-selector vector.
4. Solve dense Vandermonde system to attain the interior coefficients.

Definition at line 551 of file [mtk_grad_1d.cc](#).

Here is the call graph for this function:




16.8.3.7 bool mtk::Grad1D::ComputeWeights (void) [private]

Compute the set of mimetic weights to impose the mimetic condition.

1. Construct the \mathbf{A} matrix.
2. Use interior stencil to build proper RHS vector \mathbf{h} .
3. Get weights (as **CRSA**): $\mathbf{w} \mathbf{q} = \mathbf{h}$.
4. If required order is greater than critical order, start the **CBSA**.
5. Create \mathbf{B} matrix from \mathbf{A} .
6. Prepare constraint vector as in the CBSA: \mathbf{c} .
7. Brute force search through all the rows of the Φ matrix.
8. Apply solution found from brute force search.

Definition at line 1052 of file [mtk_grad_1d.cc](#).

Here is the call graph for this function:



16.8.3.8 bool mtk::Grad1D::ConstructGrad1D (int order_accuracy = kDefaultOrderAccuracy, Real mimetic_threshold = kDefaultMimeticThreshold)


Returns

Success of the solution.


1. Compute stencil for the interior cells.
2. Compute a rational null-space from the first matrix transposed.
3. Compute preliminary approximation (non-mimetic) on the boundaries.
4. Compute quadrature weights to impose the mimetic conditions.
5. Compute real approximation (mimetic) on the boundaries.
6. Assemble operator.

Definition at line 182 of file [mtk_grad_1d.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



16.8.3.9 `mtk::DenseMatrix mtk::Grad1D::mim_bndy () const`

Returns

Collection of mimetic approximations at the boundary.

Definition at line 341 of file [mtk_grad_1d.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



16.8.3.10 `int mtk::Grad1D::num_bndy_coeffs () const`

Returns

How many coefficients are approximating at the boundary.

Definition at line 321 of file [mtk_grad_1d.cc](#).

16.8.3.11 `mtk::DenseMatrix mtk::Grad1D::ReturnAsDenseMatrix (mtk::Real west, mtk::Real east, int num_cells_x) const`


Returns

The operator as a dense matrix.


1. Insert mimetic boundary at the west.
2. Insert coefficients for the interior of the grid.
3. Impose center-skew symmetry by permuting the mimetic boundaries.

Definition at line 356 of file [mtk_grad_1d.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



16.8.3.12 mtk::DenseMatrix mtk::Grad1D::ReturnAsDenseMatrix (const UniStgGrid1D & grid) const


Returns

The operator as a dense matrix.

1. Insert mimetic boundary at the west.
2. Insert coefficients for the interior of the grid.
3. Impose center-skew symmetry by permuting the mimetic boundaries.

Definition at line [425](#) of file [mtk_grad_1d.cc](#).

Here is the call graph for this function:



16.8.3.13 mtk::DenseMatrix mtk::Grad1D::ReturnAsDimensionlessDenseMatrix (int *num_cells_x*) const

Returns

The operator as a dimensionless dense matrix.

1. Insert mimetic boundary at the west.
2. Insert coefficients for the interior of the grid.
3. Impose center-skew symmetry by permuting the mimetic boundaries.

Definition at line 489 of file [mtk_grad_1d.cc](#).

Here is the call graph for this function:



16.8.3.14 mtk::Real * mtk::Grad1D::weights_cbs (void) const

Returns

Collection of weights as computed by the CBSA.

Definition at line 336 of file [mtk_grad_1d.cc](#).

16.8.3.15 mtk::Real * mtk::Grad1D::weights_crs (void) const

Returns

Success of the solution.

Definition at line 331 of file [mtk_grad_1d.cc](#).

16.8.4 Friends And Related Function Documentation

16.8.4.1 std::ostream& operator<< (std::ostream & *stream*, mtk::Grad1D & *in*) [friend]

1. Print order of accuracy.
2. Print approximating coefficients for the interior.
3. Print mimetic weights.
4. Print mimetic approximations at the boundary.

Definition at line 79 of file [mtk_grad_1d.cc](#).

16.8.5 Member Data Documentation

16.8.5.1 `Real* mtk::Grad1D::coeffs_interior_` [private]

Definition at line 217 of file [mtk_grad_1d.h](#).

16.8.5.2 `int mtk::Grad1D::dim_null_` [private]

Definition at line 208 of file [mtk_grad_1d.h](#).

16.8.5.3 `Real* mtk::Grad1D::gradient_` [private]

Definition at line 222 of file [mtk_grad_1d.h](#).

16.8.5.4 `int mtk::Grad1D::gradient_length_` [private]

Definition at line 211 of file [mtk_grad_1d.h](#).

16.8.5.5 `Real* mtk::Grad1D::mim_bndy_` [private]

Definition at line 221 of file [mtk_grad_1d.h](#).

16.8.5.6 `Real mtk::Grad1D::mimetic_threshold_` [private]

Definition at line 224 of file [mtk_grad_1d.h](#).

16.8.5.7 `int mtk::Grad1D::minrow_` [private]

Definition at line 212 of file [mtk_grad_1d.h](#).

16.8.5.8 `int mtk::Grad1D::num_bndy_approx_` [private]

Definition at line 209 of file [mtk_grad_1d.h](#).

16.8.5.9 `int mtk::Grad1D::num_bndy_coeffs_` [private]

Definition at line 210 of file [mtk_grad_1d.h](#).

16.8.5.10 `int mtk::Grad1D::order_accuracy_` [private]

Definition at line 207 of file [mtk_grad_1d.h](#).

16.8.5.11 `Real* mtk::Grad1D::prem_apps_` [private]

Definition at line 218 of file [mtk_grad_1d.h](#).

16.8.5.12 **DenseMatrix** mtk::Grad1D::rat_basis_null_space_ [private]

Definition at line 215 of file [mtk_grad_1d.h](#).

16.8.5.13 **int** mtk::Grad1D::row_ [private]

Definition at line 213 of file [mtk_grad_1d.h](#).

16.8.5.14 **Real*** mtk::Grad1D::weights_cbs_ [private]

Definition at line 220 of file [mtk_grad_1d.h](#).

16.8.5.15 **Real*** mtk::Grad1D::weights_crs_ [private]

Definition at line 219 of file [mtk_grad_1d.h](#).

The documentation for this class was generated from the following files:


- [include/mtk_grad_1d.h](#)
- [src/mtk_grad_1d.cc](#)

16.9 mtk::Grad2D Class Reference

Implements a 2D mimetic gradient operator.

```
#include <mtk_grad_2d.h>
```

Collaboration diagram for mtk::Grad2D:



Public Member Functions

- [Grad2D \(\)](#)

Default constructor.

- [Grad2D](#) (const [Grad2D](#) &grad)

Copy constructor.

- [~Grad2D](#) ()

Destructor.

- bool [ConstructGrad2D](#) (const [UniStgGrid2D](#) &grid, int order_accuracy=[kDefaultOrderAccuracy](#), [Real](#) mimetic_↔ threshold=[kDefaultMimeticThreshold](#))

Factory method implementing the CBS Algorithm to build operator.

- [DenseMatrix ReturnAsDenseMatrix](#) () const

Return the operator as a dense matrix.

Private Attributes

- [DenseMatrix](#) gradient_

Actual operator.

- int [order_accuracy_](#)

Order of accuracy.

- [Real](#) [mimetic_threshold_](#)

Mimetic Threshold.

16.9.1 Detailed Description

This class implements a 2D gradient operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (C↔BSA).

Definition at line 76 of file [mtk_grad_2d.h](#).

16.9.2 Constructor & Destructor Documentation

16.9.2.1 mtk::Grad2D::Grad2D ()

Definition at line 67 of file [mtk_grad_2d.cc](#).

16.9.2.2 mtk::Grad2D::Grad2D (const Grad2D & grad)

Parameters

in	div	Given divergence.
--------------------	---------------------	-------------------

Definition at line 71 of file [mtk_grad_2d.cc](#).

16.9.2.3 mtk::Grad2D::~~Grad2D ()

Definition at line 75 of file [mtk_grad_2d.cc](#).

16.9.3 Member Function Documentation


16.9.3.1 `bool mtk::Grad2D::ConstructGrad2D (const UniStgGrid2D & grid, int order_accuracy = kDefaultOrderAccuracy, mtk::Real mimetic_threshold = kDefaultMimeticThreshold)`

Returns

Success of the construction.

Definition at line 77 of file [mtk_grad_2d.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



16.9.3.2 `mtk::DenseMatrix mtk::Grad2D::ReturnAsDenseMatrix () const`

Returns

The operator as a dense matrix.

Definition at line 145 of file [mtk_grad_2d.cc](#).

Here is the caller graph for this function:

**16.9.4 Member Data Documentation****16.9.4.1 DenseMatrix mtk::Grad2D::gradient_ [private]**

Definition at line 108 of file [mtk_grad_2d.h](#).

16.9.4.2 Real mtk::Grad2D::mimetic_threshold_ [private]

Definition at line 112 of file [mtk_grad_2d.h](#).

16.9.4.3 int mtk::Grad2D::order_accuracy_ [private]

Definition at line 110 of file [mtk_grad_2d.h](#).

The documentation for this class was generated from the following files:


- [include/mtk_grad_2d.h](#)
- [src/mtk_grad_2d.cc](#)

16.10 mtk::Grad3D Class Reference

Implements a 3D mimetic gradient operator.

```
#include <mtk_grad_3d.h>
```

Collaboration diagram for mtk::Grad3D:



Public Member Functions

- [Grad3D \(\)](#)

Default constructor.

- [Grad3D](#) (const [Grad3D](#) &grad)

Copy constructor.

- [~Grad3D](#) ()

Destructor.

- bool [ConstructGrad3D](#) (const [UniStgGrid3D](#) &grid, int order_accuracy=[kDefaultOrderAccuracy](#), [Real](#) mimetic_↔ threshold=[kDefaultMimeticThreshold](#))

Factory method implementing the CBS Algorithm to build operator.

- [DenseMatrix ReturnAsDenseMatrix](#) () const

Return the operator as a dense matrix.

Private Attributes

- [DenseMatrix](#) gradient_

Actual operator.

- int [order_accuracy_](#)

Order of accuracy.

- [Real](#) [mimetic_threshold_](#)

Mimetic Threshold.

16.10.1 Detailed Description

This class implements a 3D gradient operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (C↔BSA).

Definition at line 76 of file [mtk_grad_3d.h](#).

16.10.2 Constructor & Destructor Documentation

16.10.2.1 mtk::Grad3D::Grad3D ()

Definition at line 67 of file [mtk_grad_3d.cc](#).

16.10.2.2 mtk::Grad3D::Grad3D (const Grad3D & grad)

Parameters

in	div	Given divergence.
--------------------	---------------------	-------------------

Definition at line 71 of file [mtk_grad_3d.cc](#).

16.10.2.3 mtk::Grad3D::~~Grad3D ()

Definition at line 75 of file [mtk_grad_3d.cc](#).

16.10.3 Member Function Documentation

16.10.3.1 `bool mtk::Grad3D::ConstructGrad3D (const UniStgGrid3D & grid, int order_accuracy = kDefaultOrderAccuracy, mtk::Real mimetic_threshold = kDefaultMimeticThreshold)`


Returns

Success of the construction.

1. Build preliminary staggering through the x direction.
2. Build preliminary staggering through the y direction.
3. Build preliminary staggering through the z direction.
4. Actual operator: $GG_{xyz} = [gx; gy; gz]$.

Definition at line 77 of file [mtk_grad_3d.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



16.10.3.2 `mtk::DenseMatrix mtk::Grad3D::ReturnAsDenseMatrix () const`

Returns

The operator as a dense matrix.

Definition at line 185 of file [mtk_grad_3d.cc](#).

Here is the caller graph for this function:



16.10.4 Member Data Documentation

16.10.4.1 `DenseMatrix mtk::Grad3D::gradient_ [private]`

Definition at line 108 of file [mtk_grad_3d.h](#).

16.10.4.2 `Real mtk::Grad3D::mimetic_threshold_ [private]`

Definition at line 112 of file [mtk_grad_3d.h](#).

16.10.4.3 `int mtk::Grad3D::order_accuracy_ [private]`

Definition at line 110 of file [mtk_grad_3d.h](#).

The documentation for this class was generated from the following files:


- [include/mtk_grad_3d.h](#)
- [src/mtk_grad_3d.cc](#)

16.11 mtk::Interp1D Class Reference

Implements a 1D interpolation operator.

```
#include <mtk_interp_1d.h>
```

Collaboration diagram for mtk::Interp1D:



Public Member Functions

- [Interp1D \(\)](#)
Default constructor.
- [Interp1D \(const \[Interp1D\]\(#\) &interp\)](#)
Copy constructor.
- [~Interp1D \(\)](#)
Destructor.
- [bool ConstructInterp1D \(int order_accuracy=kDefaultOrderAccuracy, mtk::DirInterp dir=SCALAR_TO_VECTOR\)](#)
Factory method to build operator.
- [Real * coeffs_interior \(\) const](#)
Returns coefficients for the interior of the grid.
- [DenseMatrix ReturnAsDenseMatrix \(const \[UniStgGrid1D\]\(#\) &grid\) const](#)
Returns the operator as a dense matrix.

Private Attributes

- [DirInterp dir_interp_](#)
Direction of interpolation.
- [int order_accuracy_](#)
Order of numerical accuracy of the operator.
- [Real * coeffs_interior_](#)
Interior stencil.

Friends

- `std::ostream & operator<< (std::ostream &stream, Interp1D &in)`
Output stream operator for printing.

16.11.1 Detailed Description

This class implements a 1D interpolation operator.

Definition at line 82 of file [mtk_interp_1d.h](#).

16.11.2 Constructor & Destructor Documentation

16.11.2.1 `mtk::Interp1D::Interp1D ()`

Definition at line 80 of file [mtk_interp_1d.cc](#).

16.11.2.2 `mtk::Interp1D::Interp1D (const Interp1D &interp)`

Parameters

<code>in</code>	<code>interp</code>	Given interpolation operator.
-----------------	---------------------	-------------------------------

Definition at line 85 of file [mtk_interp_1d.cc](#).

16.11.2.3 `mtk::Interp1D::~~Interp1D ()`

Definition at line 90 of file [mtk_interp_1d.cc](#).

16.11.3 Member Function Documentation

16.11.3.1 `mtk::Real * mtk::Interp1D::coeffs_interior () const`

Returns

Coefficients for the interior of the grid.

Definition at line 132 of file [mtk_interp_1d.cc](#).

16.11.3.2 `bool mtk::Interp1D::ConstructInterp1D (int order_accuracy = kDefaultOrderAccuracy, mtk::DirInterp dir = SCALAR_TO_VECTOR)`


Returns

Success of the solution.

1. Compute stencil for the interior cells.

Definition at line 96 of file [mtk_interp_1d.cc](#).

Here is the call graph for this function:



16.11.3.3 `mtk::DenseMatrix mtk::Interp1D::ReturnAsDenseMatrix (const UniStgGrid1D & grid) const`


Returns

The operator as a dense matrix.

1. Preserve values at the boundary.
2. Insert coefficients for the interior of the grid.
3. Impose center-skew symmetry by permuting the boundaries.

Definition at line 137 of file [mtk_interp_1d.cc](#).

Here is the call graph for this function:



16.11.4 Friends And Related Function Documentation

16.11.4.1 `std::ostream& operator<< (std::ostream & stream, mtk::Interp1D & in) [friend]`

1. Print approximating coefficients for the interior.

Definition at line 66 of file [mtk_interp_1d.cc](#).

16.11.5 Member Data Documentation

16.11.5.1 `Real* mtk::Interp1D::coeffs_interior_ [private]`

Definition at line 127 of file [mtk_interp_1d.h](#).

16.11.5.2 DirInterp mtk::Interp1D::dir_interp_ [private]

Definition at line 123 of file [mtk_interp_1d.h](#).

16.11.5.3 int mtk::Interp1D::order_accuracy_ [private]

Definition at line 125 of file [mtk_interp_1d.h](#).

The documentation for this class was generated from the following files:


- [include/mtk_interp_1d.h](#)
- [src/mtk_interp_1d.cc](#)

16.12 mtk::Interp2D Class Reference

Implements a 2D interpolation operator.

```
#include <mtk_interp_2d.h>
```

Collaboration diagram for mtk::Interp2D:



Public Member Functions

- [Interp2D \(\)](#)

Default constructor.

- [Interp2D](#) (const [Interp2D](#) &interp)

Copy constructor.

- [~Interp2D](#) ()

Destructor.

- [DenseMatrix ConstructInterp2D](#) (const [UniStgGrid2D](#) &grid, int order_accuracy=[kDefaultOrderAccuracy](#), [Real](#) mimetic_threshold=[kDefaultMimeticThreshold](#))

Factory method implementing the CBS Algorithm to build operator.

- [DenseMatrix ReturnAsDenseMatrix](#) ()

Return the operator as a dense matrix.

Private Attributes

- [DenseMatrix interpolator_](#)

Actual operator.

- int [order_accuracy_](#)

Order of accuracy.

- [Real mimetic_threshold_](#)

Mimetic Threshold.

16.12.1 Detailed Description

This class implements a 2D interpolation operator.

Definition at line 76 of file [mtk_interp_2d.h](#).

16.12.2 Constructor & Destructor Documentation

16.12.2.1 [mtk::Interp2D::Interp2D](#) ()

16.12.2.2 [mtk::Interp2D::Interp2D](#) (const [Interp2D](#) & *interp*)

Parameters

in	lap	Given Laplacian.
--------------------	---------------------	------------------

16.12.2.3 [mtk::Interp2D::~~Interp2D](#) ()

16.12.3 Member Function Documentation

16.12.3.1 [DenseMatrix mtk::Interp2D::ConstructInterp2D](#) (const [UniStgGrid2D](#) & *grid*, int *order_accuracy* = [kDefaultOrderAccuracy](#), [Real](#) *mimetic_threshold* = [kDefaultMimeticThreshold](#))

Returns

Success of the construction.

16.12.3.2 DenseMatrix mtk::Interp2D::ReturnAsDenseMatrix ()

Returns

The operator as a dense matrix.

16.12.4 Member Data Documentation

16.12.4.1 DenseMatrix mtk::Interp2D::interpolator_ [private]

Definition at line 108 of file [mtk_interp_2d.h](#).

16.12.4.2 Real mtk::Interp2D::mimetic_threshold_ [private]

Definition at line 112 of file [mtk_interp_2d.h](#).

16.12.4.3 int mtk::Interp2D::order_accuracy_ [private]

Definition at line 110 of file [mtk_interp_2d.h](#).

The documentation for this class was generated from the following file:


- [include/mtk_interp_2d.h](#)

16.13 mtk::Lap1D Class Reference

Implements a 1D mimetic Laplacian operator.

```
#include <mtk_lap_1d.h>
```

Collaboration diagram for mtk::Lap1D:



Public Member Functions

- [Lap1D](#) ()
Default constructor.
- [Lap1D](#) (const [Lap1D](#) &lap)
Copy constructor.
- [~Lap1D](#) ()
Destructor.
- int [order_accuracy](#) () const
Order of accuracy of the operator.
- [Real](#) [mimetic_threshold](#) () const
Mimetic threshold used in the CBS algorithm to construct this operator.
- [Real](#) [delta](#) () const
Value of Δx used be scaled. If 0, then dimensionless.
- bool [ConstructLap1D](#) (int [order_accuracy](#)=kDefaultOrderAccuracy, [Real](#) [mimetic_threshold](#)=kDefaultMimeticThreshold)
Factory method implementing the CBS Algorithm to build operator.
- [DenseMatrix](#) [ReturnAsDenseMatrix](#) (const [UniStgGrid1D](#) &grid) const
Return the operator as a dense matrix.
- const [mtk::Real](#) * [data](#) (const [UniStgGrid1D](#) &grid) const
Return the operator as a dense array.

Private Attributes

- int [order_accuracy_](#)
Order of numerical accuracy of the operator.
- int [laplacian_length_](#)
Length of the output array.
- [Real](#) * [laplacian_](#)
Output array containing the operator and weights.
- [Real](#) [delta_](#)
< If 0.0, then this Laplacian is dimensionless.
- [Real](#) [mimetic_threshold_](#)
< Mimetic threshold.

Friends

- [std::ostream](#) & [operator<<](#) ([std::ostream](#) &stream, [Lap1D](#) &in)
Output stream operator for printing.

16.13.1 Detailed Description

This class implements a 1D Laplacian operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (CBSA).

Definition at line 76 of file [mtk_lap_1d.h](#).

16.13.2 Constructor & Destructor Documentation

16.13.2.1 [mtk::Lap1D::Lap1D \(\)](#)

Definition at line 108 of file [mtk_lap_1d.cc](#).

16.13.2.2 [mtk::Lap1D::Lap1D \(const Lap1D & lap \)](#)

Parameters

in	lap	Given Laplacian.
--------------------	---------------------	------------------

16.13.2.3 [mtk::Lap1D::~~Lap1D \(\)](#)

Definition at line 114 of file [mtk_lap_1d.cc](#).

16.13.3 Member Function Documentation

16.13.3.1 [bool mtk::Lap1D::ConstructLap1D \(int order_accuracy = kDefaultOrderAccuracy, mtk::Real mimetic_threshold = kDefaultMimeticThreshold \)](#)

Returns

Success of the solution.

1. Create gradient operator using specific values for the Laplacian.
2. Create gradient operator using specific values for the Laplacian.
3. Create both operators as matrices.
4. Multiply both operators: $\check{\mathbf{L}}_x^k = \check{\mathbf{D}}_x^k \check{\mathbf{G}}_x^k$
5. Extract the coefficients from the matrix and store them in the array.


Warning

We do not compute weights for this operator... no need to!

1. The first entry of the array will contain the order of accuracy.
2. The second entry of the array will contain the collection of approximating coefficients for the interior of the grid.
3. We DO NOT have weights in this operator. Copy mimetic bndy coeffs.

Definition at line 135 of file [mtk_lap_1d.cc](#).

Here is the call graph for this function:




16.13.3.2 `const mtk::Real * mtk::Lap1D::data (const UniStgGrid1D & grid) const`

Returns

The operator as a dense array.

Definition at line 356 of file [mtk_lap_1d.cc](#).

Here is the call graph for this function:



16.13.3.3 `mtk::Real mtk::Lap1D::delta () const`

Returns

Value of Δx used be scaled. If 0, then dimensionless.

Definition at line 130 of file [mtk_lap_1d.cc](#).

Here is the caller graph for this function:




16.13.3.4 `mtk::Real mtk::Lap1D::mimetic_threshold () const`

Returns

Mimetic threshold used in the CBS algorithm to construct operator.

Definition at line 125 of file [mtk_lap_1d.cc](#).


Here is the caller graph for this function:

**16.13.3.5 int mtk::Lap1D::order_accuracy () const****Returns**

Order of accuracy of the operator.

Definition at line 120 of file [mtk_lap_1d.cc](#).

Here is the caller graph for this function:

**16.13.3.6 mtk::DenseMatrix mtk::Lap1D::ReturnAsDenseMatrix (const UniStgGrid1D & grid) const****Returns**

The operator as a dense matrix.


1. Extract mimetic coefficients from the west boundary.
2. Extract interior coefficients.
3. Extract mimetic coefficients from the west boundary to go east.

Note

We could create two matrices of the requested size and multiply them, but that would be inefficient, since we already have the computed coefficients stored. We just have to set them in place, in a matrix of an adequate size, and multiply them times the inverse of the square of the step size, in order for the matrix to actually represent a differential operator.

Definition at line 286 of file [mtk_lap_1d.cc](#).

Here is the call graph for this function:



16.13.4 Friends And Related Function Documentation

16.13.4.1 `std::ostream& operator<<(std::ostream & stream, mtk::Lap1D & in)` [[friend](#)]

1. Print order of accuracy.
2. Print approximating coefficients for the interior.
3. No weights, thus print the mimetic boundary coefficients.

Definition at line 73 of file [mtk_lap_1d.cc](#).

16.13.5 Member Data Documentation

16.13.5.1 `Real mtk::Lap1D::delta_` [[mutable](#)], [[private](#)]

Definition at line 143 of file [mtk_lap_1d.h](#).

16.13.5.2 `Real* mtk::Lap1D::laplacian_` [[private](#)]

Definition at line 141 of file [mtk_lap_1d.h](#).

16.13.5.3 `int mtk::Lap1D::laplacian_length_` [[private](#)]

Definition at line 139 of file [mtk_lap_1d.h](#).

16.13.5.4 Real mtk::Lap1D::mimetic_threshold_ [private]

Definition at line 145 of file [mtk_lap_1d.h](#).

16.13.5.5 int mtk::Lap1D::order_accuracy_ [private]

Definition at line 138 of file [mtk_lap_1d.h](#).

The documentation for this class was generated from the following files:


- [include/mtk_lap_1d.h](#)
- [src/mtk_lap_1d.cc](#)

16.14 mtk::Lap2D Class Reference

Implements a 2D mimetic Laplacian operator.

```
#include <mtk_lap_2d.h>
```

Collaboration diagram for mtk::Lap2D:



Public Member Functions

- [Lap2D \(\)](#)

Default constructor.

- [Lap2D](#) (const [Lap2D](#) &lap)

Copy constructor.

- [~Lap2D](#) ()

Destructor.

- bool [ConstructLap2D](#) (const [UniStgGrid2D](#) &grid, int order_accuracy=[kDefaultOrderAccuracy](#), [Real](#) mimetic_↔ threshold=[kDefaultMimeticThreshold](#))

Factory method implementing the CBS Algorithm to build operator.

- [DenseMatrix](#) [ReturnAsDenseMatrix](#) () const

Return the operator as a dense matrix.

- [Real](#) * [data](#) () const

Return the operator as a dense array.

Private Attributes

- [DenseMatrix](#) [laplacian_](#)

Actual operator.

- int [order_accuracy_](#)

Order of accuracy.

- [Real](#) [mimetic_threshold_](#)

Mimetic Threshold.

16.14.1 Detailed Description

This class implements a 2D Laplacian operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (CBSA).

Definition at line 76 of file [mtk_lap_2d.h](#).

16.14.2 Constructor & Destructor Documentation

16.14.2.1 mtk::Lap2D::Lap2D ()

Definition at line 69 of file [mtk_lap_2d.cc](#).

16.14.2.2 mtk::Lap2D::Lap2D (const Lap2D & lap)

Parameters

in	lap	Given Laplacian.
--------------------	---------------------	------------------

Definition at line 71 of file [mtk_lap_2d.cc](#).

16.14.2.3 mtk::Lap2D::~~Lap2D ()

Definition at line 75 of file [mtk_lap_2d.cc](#).

16.14.3 Member Function Documentation


16.14.3.1 `bool mtk::Lap2D::ConstructLap2D (const UniStgGrid2D & grid, int order_accuracy = kDefaultOrderAccuracy, mtk::Real mimetic_threshold = kDefaultMimeticThreshold)`

Returns

Success of the construction.

Definition at line 77 of file [mtk_lap_2d.cc](#).

Here is the call graph for this function:



16.14.3.2 `mtk::Real * mtk::Lap2D::data () const`

Returns

The operator as a dense array.

Definition at line 115 of file [mtk_lap_2d.cc](#).

16.14.3.3 **mtk::DenseMatrix** mtk::Lap2D::ReturnAsDenseMatrix () const

Returns

The operator as a dense matrix.

Definition at line 110 of file [mtk_lap_2d.cc](#).

16.14.4 Member Data Documentation

16.14.4.1 **DenseMatrix** mtk::Lap2D::laplacian_ [private]

Definition at line 115 of file [mtk_lap_2d.h](#).

16.14.4.2 **Real** mtk::Lap2D::mimetic_threshold_ [private]

Definition at line 119 of file [mtk_lap_2d.h](#).

16.14.4.3 **int** mtk::Lap2D::order_accuracy_ [private]

Definition at line 117 of file [mtk_lap_2d.h](#).

The documentation for this class was generated from the following files:


- [include/mtk_lap_2d.h](#)
- [src/mtk_lap_2d.cc](#)

16.15 mtk::Lap3D Class Reference

Implements a 3D mimetic Laplacian operator.

```
#include <mtk_lap_3d.h>
```

Collaboration diagram for mtk::Lap3D:



Public Member Functions

- [UniStgGrid3D operator*](#) (const [UniStgGrid3D](#) &grid) const

Operator application operator on a grid.

- [Lap3D](#) ()

Default constructor.

- [Lap3D](#) (const [Lap3D](#) &lap)

Copy constructor.

- [~Lap3D](#) ()

Destructor.

- bool [ConstructLap3D](#) (const [UniStgGrid3D](#) &grid, int order_accuracy=[kDefaultOrderAccuracy](#), [Real](#) mimetic_↔ threshold=[kDefaultMimeticThreshold](#))

Factory method implementing the CBS Algorithm to build operator.

- [DenseMatrix ReturnAsDenseMatrix](#) () const

Return the operator as a dense matrix.

- [Real * data](#) () const

Return the operator as a dense array.

Private Attributes

- [DenseMatrix laplacian_](#)

Actual operator.

- int [order_accuracy_](#)

Order of accuracy.

- [Real mimetic_threshold_](#)

Mimetic Threshold.

16.15.1 Detailed Description

This class implements a 3D Laplacian operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (CBSA).

Definition at line 76 of file [mtk_lap_3d.h](#).

16.15.2 Constructor & Destructor Documentation

16.15.2.1 mtk::Lap3D::Lap3D ()

Definition at line 76 of file [mtk_lap_3d.cc](#).

16.15.2.2 mtk::Lap3D::Lap3D (const Lap3D & lap)

Parameters

in	lap	Given Laplacian.
--------------------	---------------------	------------------

Definition at line 78 of file [mtk_lap_3d.cc](#).

16.15.2.3 mtk::Lap3D::~~Lap3D ()

Definition at line 82 of file [mtk_lap_3d.cc](#).

16.15.3 Member Function Documentation


16.15.3.1 `bool mtk::Lap3D::ConstructLap3D (const UniStgGrid3D & grid, int order_accuracy = kDefaultOrderAccuracy, mtk::Real mimetic_threshold = kDefaultMimeticThreshold)`

Returns

Success of the construction.

Definition at line 84 of file `mtk_lap_3d.cc`.

Here is the call graph for this function:



16.15.3.2 `mtk::Real * mtk::Lap3D::data () const`

Returns

The operator as a dense array.

Definition at line 122 of file [mtk_lap_3d.cc](#).

16.15.3.3 `mtk::UniStgGrid3D mtk::Lap3D::operator* (const UniStgGrid3D & grid) const`

Definition at line 69 of file [mtk_lap_3d.cc](#).

16.15.3.4 `mtk::DenseMatrix mtk::Lap3D::ReturnAsDenseMatrix () const`

Returns

The operator as a dense matrix.

Definition at line 117 of file [mtk_lap_3d.cc](#).

16.15.4 Member Data Documentation

16.15.4.1 `DenseMatrix mtk::Lap3D::laplacian_ [private]`

Definition at line 118 of file [mtk_lap_3d.h](#).

16.15.4.2 `Real mtk::Lap3D::mimetic_threshold_ [private]`

Definition at line 122 of file [mtk_lap_3d.h](#).

16.15.4.3 `int mtk::Lap3D::order_accuracy_ [private]`

Definition at line 120 of file [mtk_lap_3d.h](#).

The documentation for this class was generated from the following files:


- [include/mtk_lap_3d.h](#)
- [src/mtk_lap_3d.cc](#)

16.16 mtk::LAPACKAdapter Class Reference

Adapter class for the LAPACK API.

```
#include <mtk_lapack_adapter.h>
```

Collaboration diagram for mtk::LAPACKAdapter:



Static Public Member Functions

- static int [SolveDenseSystem](#) ([mtk::DenseMatrix](#) &mm, [mtk::Real](#) *rhs)
Solves a dense system of linear equations.
- static int [SolveDenseSystem](#) ([mtk::DenseMatrix](#) &mm, [mtk::DenseMatrix](#) &rr)
Solves a dense system of linear equations.
- static int [SolveDenseSystem](#) ([mtk::DenseMatrix](#) &mm, [mtk::UniStgGrid1D](#) &rhs)
Solves a dense system of linear equations.
- static int [SolveDenseSystem](#) ([mtk::DenseMatrix](#) &mm, [mtk::UniStgGrid2D](#) &rhs)
Solves a dense system of linear equations.
- static int [SolveRectangularDenseSystem](#) (const [mtk::DenseMatrix](#) &aa, [mtk::Real](#) *ob_, int ob_Id_)
Solves overdetermined or underdetermined real linear systems.
- static [mtk::DenseMatrix](#) [QRFactorDenseMatrix](#) ([DenseMatrix](#) &matrix)
Performs a QR factorization on a dense matrix.

16.16.1 Detailed Description

This class contains a collection of static classes, that posses direct access to the underlying structure of the matrices, thus allowing programmers to exploit the numerical methods implemented in the LAPACK.

The **LAPACK (Linear Algebra PACKage)** is written in Fortran 90 and provides routines for solving systems of simultaneous linear equations, least-squares solutions of linear systems of equations, eigenvalue problems, and singular value problems.

See also

<http://www.netlib.org/lapack/>

Definition at line 93 of file [mtk_lapack_adapter.h](#).

16.16.2 Member Function Documentation

16.16.2.1 `mtk::DenseMatrix mtk::LAPACKAdapter::QRFactorDenseMatrix (mtk::DenseMatrix & aa) [static]`

Adapts the MTK to LAPACK's routine.

Parameters

<code>in, out</code>	<code>matrix</code>	Input matrix.
----------------------	---------------------	---------------

Returns


Matrix **Q**.

Exceptions


<code>std::bad_alloc</code>

Definition at line 593 of file `mtk_lapack_adapter.cc`.

Here is the call graph for this function:



Here is the caller graph for this function:



16.16.2.2 `int mtk::LAPACKAdapter::SolveDenseSystem (mtk::DenseMatrix & mm, mtk::Real * rhs) [static]`

Adapts the MTK to LAPACK's `dgesv_` routine.

Parameters


in	<i>matrix</i>	Input matrix.
in	<i>rhs</i>	Input right-hand sides vector.

Exceptions


<i>std::bad_alloc</i>	
-----------------------	--

Definition at line 430 of file [mtk_lapack_adapter.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



16.16.2.3 `int mtk::LAPACKAdapter::SolveDenseSystem (mtk::DenseMatrix & mm, mtk::DenseMatrix & rr) [static]`

Adapts the MTK to LAPACK's `dgesv_` routine.

Parameters


in	<i>matrix</i>	Input matrix.
in	<i>rr</i>	Input right-hand sides matrix.

Exceptions

<i>std::bad_alloc</i>	
-----------------------	--

Definition at line 465 of file [mtk_lapack_adapter.cc](#).

Here is the call graph for this function:



16.16.2.4 `int mtk::LAPACKAdapter::SolveDenseSystem (mtk::DenseMatrix & mm, mtk::UniStgGrid1D & rhs)`
`[static]`

Adapts the MTK to LAPACK's `dgesv_` routine.

Parameters


in	<i>matrix</i>	Input matrix.
in	<i>rhs</i>	Input right-hand side from info on a grid.

Exceptions

<i>std::bad_alloc</i>	
-----------------------	--

Definition at line 517 of file [mtk_lapack_adapter.cc](#).

Here is the call graph for this function:



16.16.2.5 `int mtk::LAPACKAdapter::SolveDenseSystem (mtk::DenseMatrix & mm, mtk::UniStgGrid2D & rhs)`
`[static]`

Adapts the MTK to LAPACK's `dgesv_` routine.

Parameters


<code>in</code>	<code>matrix</code>	Input matrix.
<code>in</code>	<code>rhs</code>	Input right-hand side from info on a grid.

Exceptions

<code>std::bad_alloc</code>	
-----------------------------	--

Definition at line 555 of file [mtk_lapack_adapter.cc](#).

Here is the call graph for this function:



16.16.2.6 `int mtk::LAPACKAdapter::SolveRectangularDenseSystem (const mtk::DenseMatrix & aa, mtk::Real * ob_, int ob_id_) [static]`

Adapts the MTK to LAPACK's routine.

Parameters

<code>in, out</code>	<code>matrix</code>	Input matrix.
----------------------	---------------------	---------------

Returns


Success of the solution.

Exceptions


<code>std::bad_alloc</code>	
-----------------------------	--

Definition at line 790 of file [mtk_lapack_adapter.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



The documentation for this class was generated from the following files:

- [include/mtk_lapack_adapter.h](#)
- [src/mtk_lapack_adapter.cc](#)

16.17 mtk::Matrix Class Reference

Definition of the representation of a matrix in the MTK.

```
#include <mtk_matrix.h>
```

Collaboration diagram for mtk::Matrix:

mtk::Matrix
<ul style="list-style-type: none"> - storage_ - ordering_ - num_rows_ - num_cols_ - num_values_ - ld_ - num_zero_ - num_non_zero_ - num_null_ - num_non_null_ and 7 more...
<ul style="list-style-type: none"> + Matrix() + Matrix() + ~Matrix() + storage() + ordering() + num_rows() + num_cols() + num_values() + ld() + num_zero() and 18 more...

Public Member Functions

- [Matrix](#) ()
Default constructor.
- [Matrix](#) (const [Matrix](#) &in)
Copy constructor.
- [~Matrix](#) () noexcept
Destructor.
- [MatrixStorage](#) storage () const noexcept
Gets the type of storage of this matrix.
- [MatrixOrdering](#) ordering () const noexcept
Gets the type of ordering of this matrix.
- int [num_rows](#) () const noexcept
Gets the number of rows.
- int [num_cols](#) () const noexcept
Gets the number of rows.

- int [num_values](#) () const noexcept
Gets the number of values.
- int [ld](#) () const noexcept
Gets the matrix' leading dimension.
- int [num_zero](#) () const noexcept
Gets the number of zeros.
- int [num_non_zero](#) () const noexcept
Gets the number of non-zero values.
- int [num_null](#) () const noexcept
Gets the number of null values.
- int [num_non_null](#) () const noexcept
Gets the number of non-null values.
- int [kl](#) () const noexcept
Gets the number of lower diagonals.
- int [ku](#) () const noexcept
Gets the number of upper diagonals.
- int [bandwidth](#) () const noexcept
Gets the bandwidth.
- [Real abs_density](#) () const noexcept
Gets the absolute density.
- [Real rel_density](#) () const noexcept
Gets the relative density.
- [Real abs_sparsity](#) () const noexcept
Gets the Absolute sparsity.
- [Real rel_sparsity](#) () const noexcept
Gets the Relative sparsity.
- void [set_storage](#) (const [MatrixStorage](#) &tt) noexcept
Sets the storage type of the matrix.
- void [set_ordering](#) (const [MatrixOrdering](#) &oo) noexcept
Sets the ordering of the matrix.
- void [set_num_rows](#) (const int &num_rows) noexcept
Sets the number of rows of the matrix.
- void [set_num_cols](#) (const int &num_cols) noexcept
Sets the number of columns of the matrix.
- void [set_num_zero](#) (const int &in) noexcept
Sets the number of zero values of the matrix that matter.
- void [set_num_null](#) (const int &in) noexcept
Sets the number of zero values of the matrix that DO NOT matter.
- void [IncreaseNumZero](#) () noexcept
Increases the number of values that equal zero but with meaning.
- void [IncreaseNumNull](#) () noexcept
Increases the number of values that equal zero but with no meaning.

Private Attributes

- [MatrixStorage storage_](#)
What type of matrix is this?
- [MatrixOrdering ordering_](#)
What kind of ordering is it following?
- int [num_rows_](#)
Number of rows.
- int [num_cols_](#)
Number of columns.
- int [num_values_](#)
Number of total values in matrix.
- int [ld_](#)
Elements between successive rows when row-major.
- int [num_zero_](#)
Number of zeros.
- int [num_non_zero_](#)
Number of non-zero values.
- int [num_null_](#)
Number of null (insignificant) values.
- int [num_non_null_](#)
Number of null (significant) values.
- int [kl_](#)
Number of lower diagonals on a banded matrix.
- int [ku_](#)
Number of upper diagonals on a banded matrix.
- int [bandwidth_](#)
Bandwidth of the matrix.
- [Real abs_density_](#)
Absolute density of matrix.
- [Real rel_density_](#)
Relative density of matrix.
- [Real abs_sparsity_](#)
Absolute sparsity of matrix.
- [Real rel_sparsity_](#)
Relative sparsity of matrix.

16.17.1 Detailed Description

Definition of the representation for the matrices implemented in the MTK.

Definition at line 75 of file [mtk_matrix.h](#).

16.17.2 Constructor & Destructor Documentation

16.17.2.1 `mtk::Matrix::Matrix ()`

Definition at line 67 of file [mtk_matrix.cc](#).

16.17.2.2 mtk::Matrix::Matrix (const Matrix & *in*)

Parameters

<i>in</i>	<i>in</i>	Given matrix.
-----------	-----------	---------------

Definition at line 86 of file [mtk_matrix.cc](#).

16.17.2.3 mtk::Matrix::~~Matrix () [noexcept]

Definition at line 105 of file [mtk_matrix.cc](#).

16.17.3 Member Function Documentation

16.17.3.1 Real mtk::Matrix::abs_density () const [noexcept]

See also

http://www.csrc.sdsu.edu/research_reports/CSR2013-01.pdf

Returns

Absolute density of the matrix.

16.17.3.2 mtk::Real mtk::Matrix::abs_sparsity () const [noexcept]

See also

http://www.csrc.sdsu.edu/research_reports/CSR2013-01.pdf

Returns

Absolute sparsity of the matrix.

Definition at line 177 of file [mtk_matrix.cc](#).

16.17.3.3 int mtk::Matrix::bandwidth () const [noexcept]

Returns

Bandwidth of the matrix.

Definition at line 167 of file [mtk_matrix.cc](#).

16.17.3.4 void mtk::Matrix::IncreaseNumNull () [noexcept]

Todo Review the definition of sparse matrices properties.

Definition at line 274 of file [mtk_matrix.cc](#).

16.17.3.5 void mtk::Matrix::IncreaseNumZero () [noexcept]

Todo Review the definition of sparse matrices properties.

Definition at line 264 of file [mtk_matrix.cc](#).

16.17.3.6 int mtk::Matrix::kl () const [noexcept]

Returns

Number of lower diagonals.

Definition at line 157 of file [mtk_matrix.cc](#).

16.17.3.7 int mtk::Matrix::ku () const [noexcept]

Returns

Number of upper diagonals.

Definition at line 162 of file [mtk_matrix.cc](#).

16.17.3.8 int mtk::Matrix::ld () const [noexcept]

Leading dimension of the data array is the number of elements between successive rows (for row major storage) in memory. Most of the cases, the leading dimension is the same as the number of columns.

Returns

Leading dimension of the matrix.

Definition at line 132 of file [mtk_matrix.cc](#).


16.17.3.9 int mtk::Matrix::num_cols () const [noexcept]

Returns

Number of rows of the matrix.

Definition at line 122 of file [mtk_matrix.cc](#).

Here is the caller graph for this function:



16.17.3.10 `int mtk::Matrix::num_non_null () const` [noexcept]

See also

http://www.csrc.sdsu.edu/research_reports/CSR2013-01.pdf

Returns

Number of non-null values of the matrix.

Definition at line 152 of file [mtk_matrix.cc](#).

16.17.3.11 `int mtk::Matrix::num_non_zero () const` [noexcept]

Returns

Number of non-zero values of the matrix.

Definition at line 142 of file [mtk_matrix.cc](#).

16.17.3.12 `int mtk::Matrix::num_null () const` [noexcept]

See also


http://www.csrc.sdsu.edu/research_reports/CSR2013-01.pdf

Returns

Number of null values of the matrix.

Definition at line 147 of file [mtk_matrix.cc](#).

Here is the caller graph for this function:




16.17.3.13 `int mtk::Matrix::num_rows () const` [noexcept]

Returns

Number of rows of the matrix.

Definition at line 117 of file [mtk_matrix.cc](#).

Here is the caller graph for this function:



16.17.3.14 int mtk::Matrix::num_values () const [noexcept]

Returns

Number of values of the matrix.

Definition at line 127 of file [mtk_matrix.cc](#).


16.17.3.15 int mtk::Matrix::num_zero () const [noexcept]

Returns

Number of zeros of the matrix.

Definition at line 137 of file [mtk_matrix.cc](#).

Here is the caller graph for this function:




16.17.3.16 mtk::MatrixOrdering mtk::Matrix::ordering () const [noexcept]

Returns

Type of ordering of this matrix.

Definition at line 112 of file [mtk_matrix.cc](#).

Here is the caller graph for this function:



16.17.3.17 `mtk::Real mtk::Matrix::rel_density () const` [noexcept]

See also

http://www.csrc.sdsu.edu/research_reports/CSR2013-01.pdf

Returns

Relative density of the matrix.

Definition at line 172 of file [mtk_matrix.cc](#).

16.17.3.18 `mtk::Real mtk::Matrix::rel_sparsity () const` [noexcept]

See also

http://www.csrc.sdsu.edu/research_reports/CSR2013-01.pdf

Returns

Relative sparsity of the matrix.

Definition at line 182 of file [mtk_matrix.cc](#).

16.17.3.19 `void mtk::Matrix::set_num_cols (const int & num_cols)` [noexcept]

Parameters

<i>in</i>	<i>num_cols</i>	Number of columns.
-----------	-----------------	--------------------

Definition at line 224 of file [mtk_matrix.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



16.17.3.20 `void mtk::Matrix::set_num_null (const int & in) [noexcept]`


Parameters

<i>in</i>	<i>in</i>	Number of zero values.
-----------	-----------	------------------------

Bug -nan assigned on construction time due to `num_values_` being 0.

Definition at line 250 of file [mtk_matrix.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



16.17.3.21 `void mtk::Matrix::set_num_rows (const int & num_rows) [noexcept]`

Parameters

<code>in</code>	<code>num_rows</code>	Number of rows.
-----------------	-----------------------	-----------------

Definition at line 212 of file [mtk_matrix.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



16.17.3.22 `void mtk::Matrix::set_num_zero (const int & in) [noexcept]`


Parameters

<code>in</code>	<code>in</code>	Number of zero values.
-----------------	-----------------	------------------------

Bug -nan assigned on construction time due to `num_values_` being 0.

Definition at line 236 of file [mtk_matrix.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



16.17.3.23 `void mtk::Matrix::set_ordering (const MatrixOrdering & oo) [noexcept]`

See also

[MatrixOrdering](#)

Parameters


<code>in</code>	<code>oo</code>	Ordering of the matrix.
-----------------	-----------------	-------------------------

Definition at line 199 of file [mtk_matrix.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:



16.17.3.24 `void mtk::Matrix::set_storage (const MatrixStorage & tt) [noexcept]`

See also

[MatrixStorage](#)

Parameters


in	tt	Type of the matrix storage.
----	----	-----------------------------

Definition at line 187 of file [mtk_matrix.cc](#).

Here is the call graph for this function:



Here is the caller graph for this function:




16.17.3.25 `mtk::MatrixStorage mtk::Matrix::storage () const [noexcept]`

Returns

Type of storage of this matrix.

Definition at line 107 of file [mtk_matrix.cc](#).

Here is the caller graph for this function:



16.17.4 Member Data Documentation

16.17.4.1 Real mtk::Matrix::abs_density_ [private]

Definition at line 296 of file [mtk_matrix.h](#).

16.17.4.2 Real mtk::Matrix::abs_sparsity_ [private]

Definition at line 298 of file [mtk_matrix.h](#).

16.17.4.3 int mtk::Matrix::bandwidth_ [private]

Definition at line 294 of file [mtk_matrix.h](#).

16.17.4.4 int mtk::Matrix::kl_ [private]

Definition at line 292 of file [mtk_matrix.h](#).

16.17.4.5 int mtk::Matrix::ku_ [private]

Definition at line 293 of file [mtk_matrix.h](#).

16.17.4.6 int mtk::Matrix::ld_ [private]

Definition at line 285 of file [mtk_matrix.h](#).

16.17.4.7 int mtk::Matrix::num_cols_ [private]

Definition at line 283 of file [mtk_matrix.h](#).

16.17.4.8 `int mtk::Matrix::num_non_null_ [private]`

Definition at line 290 of file [mtk_matrix.h](#).

16.17.4.9 `int mtk::Matrix::num_non_zero_ [private]`

Definition at line 288 of file [mtk_matrix.h](#).

16.17.4.10 `int mtk::Matrix::num_null_ [private]`

Definition at line 289 of file [mtk_matrix.h](#).

16.17.4.11 `int mtk::Matrix::num_rows_ [private]`

Definition at line 282 of file [mtk_matrix.h](#).

16.17.4.12 `int mtk::Matrix::num_values_ [private]`

Definition at line 284 of file [mtk_matrix.h](#).

16.17.4.13 `int mtk::Matrix::num_zero_ [private]`

Definition at line 287 of file [mtk_matrix.h](#).

16.17.4.14 **MatrixOrdering** `mtk::Matrix::ordering_ [private]`

Definition at line 280 of file [mtk_matrix.h](#).

16.17.4.15 **Real** `mtk::Matrix::rel_density_ [private]`

Definition at line 297 of file [mtk_matrix.h](#).

16.17.4.16 **Real** `mtk::Matrix::rel_sparsity_ [private]`

Definition at line 299 of file [mtk_matrix.h](#).

16.17.4.17 **MatrixStorage** `mtk::Matrix::storage_ [private]`

Definition at line 278 of file [mtk_matrix.h](#).

The documentation for this class was generated from the following files:


- [include/mtk_matrix.h](#)
- [src/mtk_matrix.cc](#)

16.18 mtk::Quad1D Class Reference

Implements a 1D mimetic quadrature.

```
#include <mtk_quad_1d.h>
```

Collaboration diagram for mtk::Quad1D:



Public Member Functions

- [Quad1D](#) ()
Default constructor.
- [Quad1D](#) (const [Quad1D](#) &quad)
Copy constructor.
- [~Quad1D](#) ()
Destructor.
- int [degree_approximation](#) () const
Get the degree of interpolating polynomial per sub-interval of domain.
- [Real](#) * [weights](#) () const
Return collection of weights.
- [Real](#) [Integrate](#) ([Real](#)(*Integrand)([Real](#) xx), [UniStgGrid1D](#) grid) const
Mimetic integration routine.

Private Attributes

- int [degree_approximation_](#)
Degree of the interpolating polynomial.
- std::vector< [Real](#) > [weights_](#)
Collection of weights.

Friends

- std::ostream & [operator<<](#) (std::ostream &stream, [Quad1D](#) &in)
Output stream operator for printing.

16.18.1 Detailed Description

This class implements a 1D quadrature solver based on the mimetic discretization of the gradient operator.

Definition at line 81 of file [mtk_quad_1d.h](#).

16.18.2 Constructor & Destructor Documentation

16.18.2.1 [mtk::Quad1D::Quad1D](#) ()

16.18.2.2 [mtk::Quad1D::Quad1D](#) (const [Quad1D](#) & *quad*)

Parameters

<i>in</i>	<i>div</i>	Given quadrature.
-----------	------------	-------------------

16.18.2.3 mtk::Quad1D::~~Quad1D ()

16.18.3 Member Function Documentation

16.18.3.1 int mtk::Quad1D::degree_approximation () const

Returns

Degree of the interpolating polynomial per sub-interval of the domain.

16.18.3.2 Real mtk::Quad1D::Integrate (Real(*) (Real xx) *Integrand*, UniStgGrid1D *grid*) const

Parameters

in	<i>Integrand</i>	Real-valued function to integrate.
in	<i>grid</i>	Given integration domain.

Returns

Result of the integration.

16.18.3.3 Real* mtk::Quad1D::weights () const

Returns

Collection of weights.

16.18.4 Friends And Related Function Documentation

16.18.4.1 std::ostream& operator<< (std::ostream & *stream*, Quad1D & *in*) [friend]

16.18.5 Member Data Documentation

16.18.5.1 int mtk::Quad1D::degree_approximation_ [private]

Definition at line 124 of file [mtk_quad_1d.h](#).

16.18.5.2 std::vector<Real> mtk::Quad1D::weights_ [private]

Definition at line 126 of file [mtk_quad_1d.h](#).

The documentation for this class was generated from the following file:


- [include/mtk_quad_1d.h](#)

16.19 mtk::RobinBCDescriptor1D Class Reference

Impose Robin boundary conditions on the operators and on the grids.

```
#include <mtk_robin_bc_descriptor_1d.h>
```

Collaboration diagram for `mtk::RobinBCDescriptor1D`:



Public Member Functions

- [RobinBCDescriptor1D \(\)](#)

Default constructor.

- [RobinBCDescriptor1D](#) (const [RobinBCDescriptor1D](#) &desc)

Copy constructor.

- [~RobinBCDescriptor1D](#) () noexcept

Destructor.

- int [highest_order_diff_west](#) () const noexcept

Getter for the highest order of differentiation in the west boundary.

- int [highest_order_diff_east](#) () const noexcept

Getter for the highest order of differentiation in the east boundary.

- void [PushBackWestCoeff](#) ([CoefficientFunction0D](#) cw)

Push back coefficient function at west of lowest order diff. available.

- void [PushBackEastCoeff](#) ([CoefficientFunction0D](#) ce)

Push back coefficient function at east of lowest order diff. available.

- void [set_west_condition](#) ([Real](#)(*west_condition)(const [Real](#) &tt)) noexcept

Set boundary condition at west.

- void [set_east_condition](#) ([Real](#)(*east_condition)(const [Real](#) &tt)) noexcept

Set boundary condition at east.

- bool [ImposeOnLaplacianMatrix](#) (const [Lap1D](#) &lap, [DenseMatrix](#) &matrix, const [Real](#) &time=[mtk::kZero](#)) const

Imposes the condition on the operator represented as matrix.

- void [ImposeOnGrid](#) ([UniStgGrid1D](#) &grid, const [Real](#) &time=[mtk::kZero](#)) const

Imposes the condition on the grid.

Private Attributes

- int [highest_order_diff_west_](#)

Highest order of differentiation for west.

- int [highest_order_diff_east_](#)

Highest order of differentiation for east.

- std::vector

< [CoefficientFunction0D](#) > [west_coefficients_](#)

Coeffs. west.

- std::vector

< [CoefficientFunction0D](#) > [east_coefficients_](#)

Coeffs. east.

- [Real](#)(* [west_condition_](#))(const [Real](#) &tt)

Condition for west.

- [Real](#)(* [east_condition_](#))(const [Real](#) &tt)

Condition for east.

16.19.1 Detailed Description

This class presents an interface for the user to specify Robin boundary conditions on 1D mimetic operators and the grids they are acting on.

Def. Let $u(\mathbf{x}, t) : \Omega \times [t_0, t_n] \mapsto \mathbb{R}$ be the solution to an ordinary or partial differential equation of interest. We say that u satisfies a **Robin boundary condition** on $\partial\Omega$ if and only if there exists $\beta(\mathbf{x}, t) : \Omega \times [t_0, t_n] \mapsto \mathbb{R}$ so that:

$$\forall t \in [t_0, t_n] \forall \mathbf{x} \in \partial\Omega : \delta(\mathbf{x}, t)u(\mathbf{x}, t) + \eta(\mathbf{x}, t)(\hat{\mathbf{n}} \cdot \nabla u) = \beta(\mathbf{x}, t).$$

Intuitively, a **Robin boundary condition** is a constraint that must be satisfied by any linear combination of any scalar field u and its first normal derivative, in order for u to represent a unique solution to a given ordinary or partial differential equation of interest.

In a 1D context ($\partial\Omega = \{a, b\} \subset \mathbb{R}$), this condition can be written as follows:

$$\begin{aligned}\delta_a(a, t)u(a, t) - \eta_a(a, t)u'(a, t) &= \beta_a(a, t), \\ \delta_b(b, t)u(b, t) + \eta_b(b, t)u'(b, t) &= \beta_b(b, t).\end{aligned}$$

Instances of this class receive information about the coefficient functions and each condition for any subset of the boundary (west and east, in 1D). These instances then handle the complexity of placing the coefficients in the differentiation matrices and the conditions in the grids.

See also

<http://mathworld.wolfram.com/NormalVector.html>

Definition at line 155 of file [mtk_robin_bc_descriptor_1d.h](#).

16.19.2 Constructor & Destructor Documentation

16.19.2.1 mtk::RobinBCDescriptor1D::RobinBCDescriptor1D ()

Definition at line 93 of file [mtk_robin_bc_descriptor_1d.cc](#).

16.19.2.2 mtk::RobinBCDescriptor1D::RobinBCDescriptor1D (const RobinBCDescriptor1D & desc)

Parameters

<i>in</i>	<i>desc</i>	Given 1D descriptor.
-----------	-------------	----------------------

Definition at line 99 of file [mtk_robin_bc_descriptor_1d.cc](#).

16.19.2.3 mtk::RobinBCDescriptor1D::~~RobinBCDescriptor1D () [noexcept]

Definition at line 106 of file [mtk_robin_bc_descriptor_1d.cc](#).

16.19.3 Member Function Documentation

16.19.3.1 int mtk::RobinBCDescriptor1D::highest_order_diff_east () const [noexcept]

Returns

Integer highest order of differentiation in the east boundary.

Definition at line 113 of file [mtk_robin_bc_descriptor_1d.cc](#).

16.19.3.2 int mtk::RobinBCDescriptor1D::highest_order_diff_west () const [noexcept]

Returns

Integer highest order of differentiation in the west boundary.

Definition at line 108 of file [mtk_robin_bc_descriptor_1d.cc](#).


16.19.3.3 void mtk::RobinBCDescriptor1D::ImposeOnGrid (UniStgGrid1D & *grid*, const Real & *time* = mtk::kZero) const

Parameters

in, out	<i>grid</i>	Grid upon which impose the desired boundary condition.
in	<i>time</i>	Current time snapshot. Default is kZero.

Definition at line 246 of file [mtk_robin_bc_descriptor_1d.cc](#).

Here is the call graph for this function:



16.19.3.4 bool mtk::RobinBCDescriptor1D::ImposeOnLaplacianMatrix (const Lap1D & *lap*, mtk::DenseMatrix & *matrix*, const Real & *time* = mtk::kZero) const

Parameters

in	<i>lap</i>	Operator in the Matrix .
in, out	<i>matrix</i>	Input Laplacian operator.
in	<i>time</i>	Current time snapshot. Default is kZero.

Returns

Success of the imposition.

1. Impose Dirichlet coefficients.
 - 1.1. Impose Dirichlet condition at the west.
 - 1.2. Impose Dirichlet condition at the east.
 1. Impose Neumann coefficients.
- 2.1. Create a mimetic gradient to approximate the first derivative.
- 2.2. Extract the coefficients approximating the boundary.

Warning

Coefficients returned by the `mim_bndy` getter are dimensionless! Therefore we must scale them by `delta_x` (from the grid), before adding to the matrix! But this information is in the given lap!

2.3. Impose Neumann condition at the west.

2.3.1. Get gradient coefficient and scale it.

2.3.2. Multiply times the coefficient for this boundary, times the unit normal for this boundary.

2.3.3. Set the final value summing it with what is on the matrix.

2.4. Impose Neumann condition at the east.

Warning

The Coefficients returned by the `mim_bndy` getter are those intended for the west boundary. We must enforce the center-skew-symmetry of the resulting operator by permuting their location in the matrix, and changing their sign.


2.4.1. Get gradient coefficient and scale it.

2.4.2. Multiply times the coefficient for this boundary, times the unit normal for this boundary, and change the sign to enforce center-skew-symmetry.

2.4.3. Set the final value summing it with what is on the matrix.

Definition at line 166 of file [mtk_robin_bc_descriptor_1d.cc](#).

Here is the call graph for this function:




16.19.3.5 void `mtk::RobinBCDescriptor1D::PushBackEastCoeff` (`mtk::CoefficientFunction0D ce`)

Parameters

<i>in</i>	<i>ce</i>	Function $c_e(x, y) : \Omega \mapsto \mathbb{R}$.
-----------	-----------	--

Definition at line 132 of file [mtk_robin_bc_descriptor_1d.cc](#).

Here is the call graph for this function:




16.19.3.6 void mtk::RobinBCDescriptor1D::PushBackWestCoeff (mtk::CoefficientFunction0D *cw*)

Parameters

<i>in</i>	<i>cw</i>	Function $c_w(x, y) : \Omega \mapsto \mathbb{R}$.
-----------	-----------	--

Definition at line 118 of file [mtk_robin_bc_descriptor_1d.cc](#).

Here is the call graph for this function:




16.19.3.7 void mtk::RobinBCDescriptor1D::set_east_condition (Real(*) (const Real &tt) *east_condition*) [noexcept]

Parameters

<i>in</i>	<i>east_condition</i>	$\beta_e(y, t) : \Omega \mapsto \mathbb{R}$.
-----------	-----------------------	---

Definition at line 156 of file [mtk_robin_bc_descriptor_1d.cc](#).

Here is the call graph for this function:




16.19.3.8 void mtk::RobinBCDescriptor1D::set_west_condition (Real(*) (const Real &tt) *west_condition*) [noexcept]

Parameters

in	<i>west_condition</i>	$\beta_w(y, t) : \Omega \mapsto \mathbb{R}.$
----	-----------------------	--

Definition at line 146 of file [mtk_robin_bc_descriptor_1d.cc](#).

Here is the call graph for this function:



16.19.4 Member Data Documentation

16.19.4.1 std::vector<CoefficientFunction0D> mtk::RobinBCDescriptor1D::east_coefficients_ [private]

Definition at line 237 of file [mtk_robin_bc_descriptor_1d.h](#).

16.19.4.2 Real(*) mtk::RobinBCDescriptor1D::east_condition_ (const Real &tt) [private]

Definition at line 240 of file [mtk_robin_bc_descriptor_1d.h](#).

16.19.4.3 int mtk::RobinBCDescriptor1D::highest_order_diff_east_ [private]

Definition at line 234 of file [mtk_robin_bc_descriptor_1d.h](#).

16.19.4.4 int mtk::RobinBCDescriptor1D::highest_order_diff_west_ [private]

Definition at line 233 of file [mtk_robin_bc_descriptor_1d.h](#).

16.19.4.5 `std::vector<CoefficientFunction0D> mtk::RobinBCDescriptor1D::west_coefficients_` [private]

Definition at line 236 of file [mtk_robin_bc_descriptor_1d.h](#).

16.19.4.6 `Real(* mtk::RobinBCDescriptor1D::west_condition_)(const Real &tt)` [private]

Definition at line 239 of file [mtk_robin_bc_descriptor_1d.h](#).

The documentation for this class was generated from the following files:


- [include/mtk_robin_bc_descriptor_1d.h](#)
- [src/mtk_robin_bc_descriptor_1d.cc](#)

16.20 mtk::RobinBCDescriptor2D Class Reference

Impose Robin boundary conditions on the operators and on the grids.

```
#include <mtk_robin_bc_descriptor_2d.h>
```

Collaboration diagram for `mtk::RobinBCDescriptor2D`:



Public Member Functions

- [RobinBCDescriptor2D](#) ()

Default constructor.

- [RobinBCDescriptor2D](#) (const [RobinBCDescriptor2D](#) &desc)

Copy constructor.

- [~RobinBCDescriptor2D](#) () noexcept

Destructor.

- int [highest_order_diff_west](#) () const noexcept

Getter for the highest order of differentiation in the west boundary.

- int [highest_order_diff_east](#) () const noexcept

Getter for the highest order of differentiation in the east boundary.

- int [highest_order_diff_south](#) () const noexcept

Getter for the highest order of differentiation in the south boundary.

- int [highest_order_diff_north](#) () const noexcept

Getter for the highest order of differentiation in the north boundary.

- void [PushBackWestCoeff](#) ([CoefficientFunction1D](#) cw)

Push back coefficient function at west of lowest order diff. available.

- void [PushBackEastCoeff](#) ([CoefficientFunction1D](#) ce)

Push back coefficient function at east of lowest order diff. available.

- void [PushBackSouthCoeff](#) ([CoefficientFunction1D](#) cs)

Push back coefficient function south of lowest order diff. available.

- void [PushBackNorthCoeff](#) ([CoefficientFunction1D](#) cn)

Push back coefficient function north of lowest order diff. available.

- void [set_west_condition](#) ([Real](#)(*west_condition)(const [Real](#) &yy, const [Real](#) &tt)) noexcept

Set boundary condition at west.

- void [set_east_condition](#) ([Real](#)(*east_condition)(const [Real](#) &yy, const [Real](#) &tt)) noexcept

Set boundary condition at east.

- void [set_south_condition](#) ([Real](#)(*south_condition)(const [Real](#) &xx, const [Real](#) &tt)) noexcept

Set boundary condition at south.

- void [set_north_condition](#) ([Real](#)(*north_condition)(const [Real](#) &xx, const [Real](#) &tt)) noexcept

Set boundary condition at north.

- bool [ImposeOnLaplacianMatrix](#) (const [Lap2D](#) &lap, const [UniStgGrid2D](#) &grid, [DenseMatrix](#) &matrix, const [Real](#) &time=kZero) const

Imposes the condition on the operator represented as matrix.

- void [ImposeOnGrid](#) ([UniStgGrid2D](#) &grid, const [Real](#) &time=kZero) const

Imposes the condition on the grid.

Private Member Functions

- bool [ImposeOnSouthBoundaryNoSpace](#) (const [Lap2D](#) &lap, const [UniStgGrid2D](#) &grid, [DenseMatrix](#) &matrix, const [Real](#) &time=kZero) const

Imposes the condition on the south boundary.

- bool [ImposeOnNorthBoundaryNoSpace](#) (const [Lap2D](#) &lap, const [UniStgGrid2D](#) &grid, [DenseMatrix](#) &matrix, const [Real](#) &time=kZero) const

Imposes the condition on the north boundary.

- bool [ImposeOnWestBoundaryNoSpace](#) (const [Lap2D](#) &lap, const [UniStgGrid2D](#) &grid, [DenseMatrix](#) &matrix, const [Real](#) &time=kZero) const

Imposes the condition on the west boundary.

- bool [ImposeOnEastBoundaryNoSpace](#) (const [Lap2D](#) &lap, const [UniStgGrid2D](#) &grid, [DenseMatrix](#) &matrix, const [Real](#) &time=kZero) const

Imposes the condition on the east boundary.

- bool [ImposeOnSouthBoundaryWithSpace](#) (const [Lap2D](#) &lap, const [UniStgGrid2D](#) &grid, [DenseMatrix](#) &matrix, const [Real](#) &time=[kZero](#)) const

Imposes the condition on the south boundary.

- bool [ImposeOnNorthBoundaryWithSpace](#) (const [Lap2D](#) &lap, const [UniStgGrid2D](#) &grid, [DenseMatrix](#) &matrix, const [Real](#) &time=[kZero](#)) const

Imposes the condition on the north boundary.

- bool [ImposeOnWestBoundaryWithSpace](#) (const [Lap2D](#) &lap, const [UniStgGrid2D](#) &grid, [DenseMatrix](#) &matrix, const [Real](#) &time=[kZero](#)) const

Imposes the condition on the west boundary.

- bool [ImposeOnEastBoundaryWithSpace](#) (const [Lap2D](#) &lap, const [UniStgGrid2D](#) &grid, [DenseMatrix](#) &matrix, const [Real](#) &time=[kZero](#)) const

Imposes the condition on the east boundary.

Private Attributes

- int [highest_order_diff_west_](#)

Highest order of differentiation west.

- int [highest_order_diff_east_](#)

Highest order of differentiation east.

- int [highest_order_diff_south_](#)

Highest order differentiation for south.

- int [highest_order_diff_north_](#)

Highest order differentiation for north.

- std::vector
< [CoefficientFunction1D](#) > [west_coefficients_](#)
Coeffs. west.

- std::vector
< [CoefficientFunction1D](#) > [east_coefficients_](#)
Coeffs. east.

- std::vector
< [CoefficientFunction1D](#) > [south_coefficients_](#)
Coeffs. south.

- std::vector
< [CoefficientFunction1D](#) > [north_coefficients_](#)
Coeffs. north.

- [Real](#)(* [west_condition_](#))(const [Real](#) &xx, const [Real](#) &tt)
Condition west.

- [Real](#)(* [east_condition_](#))(const [Real](#) &xx, const [Real](#) &tt)
Condition east.

- [Real](#)(* [south_condition_](#))(const [Real](#) &yy, const [Real](#) &tt)
Cond. south.

- [Real](#)(* [north_condition_](#))(const [Real](#) &yy, const [Real](#) &tt)
Cond. north.

16.20.1 Detailed Description

This class presents an interface for the user to specify Robin boundary conditions on 2D mimetic operators and the grids they are acting on.

Def. Let $u(\mathbf{x}, t) : \Omega \times [t_0, t_n] \mapsto \mathbb{R}$ be the solution to an ordinary or partial differential equation of interest. We say that u satisfies a **Robin boundary condition** on $\partial\Omega$ if and only if there exists $\beta(\mathbf{x}, t) : \Omega \times [t_0, t_n] \mapsto \mathbb{R}$ so that:

$$\forall t \in [t_0, t_n] \forall \mathbf{x} \in \partial\Omega : \delta(\mathbf{x}, t)u(\mathbf{x}, t) + \eta(\mathbf{x}, t)(\hat{\mathbf{n}} \cdot \nabla u) = \beta(\mathbf{x}, t).$$

Intuitively, a **Robin boundary condition** is a constraint that must be satisfied by any linear combination of any scalar field u and its first normal derivative, in order for u to represent a unique solution to a given ordinary or partial differential equation of interest.

Instances of this class receive information about the coefficient functions and each condition for any subset of the boundary (west, east, south and north in 2D). These instances then handle the complexity of placing the coefficients in the differentiation matrices and the conditions in the grids.

See also

<http://mathworld.wolfram.com/NormalVector.html>

Definition at line 132 of file [mtk_robin_bc_descriptor_2d.h](#).

16.20.2 Constructor & Destructor Documentation

16.20.2.1 mtk::RobinBCDescriptor2D::RobinBCDescriptor2D ()

Definition at line 84 of file [mtk_robin_bc_descriptor_2d.cc](#).

16.20.2.2 mtk::RobinBCDescriptor2D::RobinBCDescriptor2D (const RobinBCDescriptor2D & desc)

Parameters

<i>in</i>	<i>desc</i>	Given 2D descriptor.
-----------	-------------	----------------------

Definition at line 94 of file [mtk_robin_bc_descriptor_2d.cc](#).

16.20.2.3 mtk::RobinBCDescriptor2D::~~RobinBCDescriptor2D () [noexcept]

Definition at line 105 of file [mtk_robin_bc_descriptor_2d.cc](#).

16.20.3 Member Function Documentation

16.20.3.1 int mtk::RobinBCDescriptor2D::highest_order_diff_east () const [noexcept]

Returns

Integer highest order of differentiation in the east boundary.

Definition at line 112 of file [mtk_robin_bc_descriptor_2d.cc](#).

16.20.3.2 `int mtk::RobinBCDescriptor2D::highest_order_diff_north () const` `[noexcept]`

Returns

Integer highest order of differentiation in the north boundary.

Definition at line 122 of file [mtk_robin_bc_descriptor_2d.cc](#).

16.20.3.3 `int mtk::RobinBCDescriptor2D::highest_order_diff_south () const` `[noexcept]`

Returns

Integer highest order of differentiation in the south boundary.

Definition at line 117 of file [mtk_robin_bc_descriptor_2d.cc](#).

16.20.3.4 `int mtk::RobinBCDescriptor2D::highest_order_diff_west () const` `[noexcept]`

Returns

Integer highest order of differentiation in the west boundary.

Definition at line 107 of file [mtk_robin_bc_descriptor_2d.cc](#).

16.20.3.5 `bool mtk::RobinBCDescriptor2D::ImposeOnEastBoundaryNoSpace (const Lap2D & lap, const UniStgGrid2D & grid, mtk::DenseMatrix & matrix, const Real & time = kZero) const` `[private]`

Parameters


<i>in</i>	<i>lap</i>	Laplacian operator on the matrix.
<i>in</i>	<i>grid</i>	Grid upon which impose the desired boundary condition.
<i>in, out</i>	<i>matrix</i>	Input matrix with the Laplacian operator.
<i>in</i>	<i>time</i>	Current time snapshot. Default is kZero.

1. Impose the Dirichlet condition first.

2. Impose the Neumann condition.

Definition at line 495 of file [mtk_robin_bc_descriptor_2d.cc](#).

Here is the call graph for this function:



16.20.3.6 `bool mtk::RobinBCDescriptor2D::ImposeOnEastBoundaryWithSpace (const Lap2D & lap, const UniStgGrid2D & grid, mtk::DenseMatrix & matrix, const Real & time = kZero) const [private]`

Parameters


in	<i>lap</i>	Laplacian operator on the matrix.
in	<i>grid</i>	Grid upon which impose the desired boundary condition.
in, out	<i>matrix</i>	Input matrix with the Laplacian operator.
in	<i>time</i>	Current time snapshot. Default is kZero.

1. Impose the Dirichlet condition first.

2. Impose the Neumann condition.

Definition at line 564 of file `mtk_robin_bc_descriptor_2d.cc`.

Here is the call graph for this function:



16.20.3.7 void mtk::RobinBCDescriptor2D::ImposeOnGrid (mtk::UniStgGrid2D & *grid*, const Real & *time* = kZero) const

Parameters

in, out	<i>grid</i>	Grid upon which impose the desired boundary condition.
in	<i>time</i>	Current time snapshot. Default is kZero.

1. Impose assuming an scalar grid.

1.1. Impose south condition.

1.1.1. Impose south-west corner.

1.1.2. Impose south border.

1.1.3. Impose south-east corner.

1.2. Impose north condition.

1.2.1. Impose north-west corner.

1.2.2. Impose north border.

1.2.3. Impose north-east corner.

1.3. Impose west condition.

1.3.1. Impose south-west corner.

Note

As per discussion with Otilio, we will take the **arithmetic mean** of the values of the BCs at the corners.

1.3.2. Impose west border.

1.3.3. Impose north-west corner.

1.4. Impose east condition.

1.4.1. Impose south-east corner.

1.4.2. Impose east border.


1.4.3. Impose north-east corner.

1. Impose assuming a vector grid.

Todo Implement imposition for vector-valued grids. Need research here!

Definition at line 674 of file [mtk_robin_bc_descriptor_2d.cc](#).

Here is the call graph for this function:



16.20.3.8 `bool mtk::RobinBCDescriptor2D::ImposeOnLaplacianMatrix (const Lap2D & lap, const UniStgGrid2D & grid, mtk::DenseMatrix & matrix, const Real & time = kZero) const`


Parameters

in	<i>lap</i>	Laplacian operator on the matrix.
in	<i>grid</i>	Grid upon which impose the desired boundary condition.
in, out	<i>matrix</i>	Input matrix with the Laplacian operator.
in	<i>time</i>	Current time snapshot. Default is kZero.

If we have not bound anything to the grid, then we have to generate our collection of spatial coordinates, as we evaluate the coefficients.

Definition at line 591 of file [mtk_robin_bc_descriptor_2d.cc](#).

Here is the call graph for this function:



16.20.3.9 `bool mtk::RobinBCDescriptor2D::ImposeOnNorthBoundaryNoSpace (const Lap2D & lap, const UniStgGrid2D & grid, mtk::DenseMatrix & matrix, const Real & time = kZero) const [private]`


Parameters

in	<i>lap</i>	Laplacian operator on the matrix.
in	<i>grid</i>	Grid upon which impose the desired boundary condition.
in, out	<i>matrix</i>	Input matrix with the Laplacian operator.
in	<i>time</i>	Current time snapshot. Default is kZero.

1. Impose the Dirichlet condition first.
2. Impose the Neumann condition.

Definition at line 312 of file [mtk_robin_bc_descriptor_2d.cc](#).

Here is the call graph for this function:



16.20.3.10 `bool mtk::RobinBCDescriptor2D::ImposeOnNorthBoundaryWithSpace (const Lap2D & lap, const UniStgGrid2D & grid, mtk::DenseMatrix & matrix, const Real & time = kZero) const` [private]

Parameters

in	<i>lap</i>	Laplacian operator on the matrix.
in	<i>grid</i>	Grid upon which impose the desired boundary condition.
in, out	<i>matrix</i>	Input matrix with the Laplacian operator.
in	<i>time</i>	Current time snapshot. Default is kZero.

1. Impose Dirichlet condition.

For each entry on the diagonal:


Evaluate next set spatial coordinates to evaluate the coefficient.

Evaluate and assign the Dirichlet coefficient.

1. Impose the Neumann condition.

Definition at line 372 of file [mtk_robin_bc_descriptor_2d.cc](#).

Here is the call graph for this function:



16.20.3.11 `bool mtk::RobinBCDescriptor2D::ImposeOnSouthBoundaryNoSpace (const Lap2D & lap, const UniStgGrid2D & grid, mtk::DenseMatrix & matrix, const Real & time = kZero) const [private]`

Parameters


in	<i>lap</i>	Laplacian operator on the matrix.
in	<i>grid</i>	Grid upon which impose the desired boundary condition.
in, out	<i>matrix</i>	Input matrix with the Laplacian operator.
in	<i>time</i>	Current time snapshot. Default is kZero.

1. Impose the Dirichlet condition first.
2. Impose the Neumann condition.

Todo Impose the Neumann conditions on every pole, for every scenario.

Definition at line 229 of file [mtk_robin_bc_descriptor_2d.cc](#).

Here is the call graph for this function:



16.20.3.12 `bool mtk::RobinBCDescriptor2D::ImposeOnSouthBoundaryWithSpace (const Lap2D & lap, const UniStgGrid2D & grid, mtk::DenseMatrix & matrix, const Real & time = kZero) const [private]`

Parameters

in	<i>lap</i>	Laplacian operator on the matrix.
in	<i>grid</i>	Grid upon which impose the desired boundary condition.
in, out	<i>matrix</i>	Input matrix with the Laplacian operator.
in	<i>time</i>	Current time snapshot. Default is kZero.


1. Impose the Dirichlet condition first.

Todo Impose Harmonic mean on the corners for the case when the generated space is available, for all poles.

1. Impose the Neumann condition.

Definition at line 284 of file `mtk_robin_bc_descriptor_2d.cc`.

Here is the call graph for this function:



16.20.3.13 `bool mtk::RobinBCDescriptor2D::ImposeOnWestBoundaryNoSpace (const Lap2D & lap, const UniStgGrid2D & grid, mtk::DenseMatrix & matrix, const Real & time = kZero) const [private]`

Parameters

in	<i>lap</i>	Laplacian operator on the matrix.
in	<i>grid</i>	Grid upon which impose the desired boundary condition.
in, out	<i>matrix</i>	Input matrix with the Laplacian operator.
in	<i>time</i>	Current time snapshot. Default is kZero.

1. Impose the Dirichlet condition first.


Note

As it can be seen, we must adopt a convention about how to treat the corners. Based on a reasoning with Otilio, we will take the **harmonic mean**.

1. Impose the Neumann condition.

Definition at line 399 of file [mtk_robin_bc_descriptor_2d.cc](#).

Here is the call graph for this function:



16.20.3.14 `bool mtk::RobinBCDescriptor2D::ImposeOnWestBoundaryWithSpace (const Lap2D & lap, const UniStgGrid2D & grid, mtk::DenseMatrix & matrix, const Real & time = kZero) const [private]`


Parameters

in	<i>lap</i>	Laplacian operator on the matrix.
in	<i>grid</i>	Grid upon which impose the desired boundary condition.
in, out	<i>matrix</i>	Input matrix with the Laplacian operator.
in	<i>time</i>	Current time snapshot. Default is kZero.

1. Impose the Dirichlet condition first.
2. Impose the Neumann condition.

Definition at line 468 of file [mtk_robin_bc_descriptor_2d.cc](#).

Here is the call graph for this function:




16.20.3.15 void mtk::RobinBCDescriptor2D::PushBackEastCoeff (mtk::CoefficientFunction1D ce)

Parameters

in	<i>cw</i>	Coeff. $c_e(y, t) : \partial\Omega \times [t_0, t_n] \mapsto \mathbb{R}$.
----	-----------	--

Definition at line 141 of file [mtk_robin_bc_descriptor_2d.cc](#).

Here is the call graph for this function:




16.20.3.16 void mtk::RobinBCDescriptor2D::PushBackNorthCoeff (mtk::CoefficientFunction1D cn)

Parameters

in	cw	Coeff. $c_n(x, t) : \partial\Omega \times [t_0, t_n] \mapsto \mathbb{R}$.
----	----	--

Definition at line 169 of file [mtk_robin_bc_descriptor_2d.cc](#).

Here is the call graph for this function:




16.20.3.17 void `mtk::RobinBCDescriptor2D::PushBackSouthCoeff (mtk::CoefficientFunction1D cs)`

Parameters

in	cw	Coeff. $c_s(x, t) : \partial\Omega \times [t_0, t_n] \mapsto \mathbb{R}$.
----	----	--

Definition at line 155 of file [mtk_robin_bc_descriptor_2d.cc](#).

Here is the call graph for this function:




16.20.3.18 void `mtk::RobinBCDescriptor2D::PushBackWestCoeff (mtk::CoefficientFunction1D cw)`

Parameters

in	cw	Coeff. $c_w(y, t) : \partial\Omega \times [t_0, t_n] \mapsto \mathbb{R}$.
----	----	--

Definition at line 127 of file [mtk_robin_bc_descriptor_2d.cc](#).

Here is the call graph for this function:




16.20.3.19 void mtk::RobinBCDescriptor2D::set_east_condition (Real(*) (const Real &yy, const Real &tt) east_condition)
[noexcept]

Parameters

in	east_condition	$\beta_e(y, t) : \partial\Omega \times [t_0, t_n] \mapsto \mathbb{R}.$
----	----------------	--

Definition at line 194 of file [mtk_robin_bc_descriptor_2d.cc](#).

Here is the call graph for this function:




16.20.3.20 void mtk::RobinBCDescriptor2D::set_north_condition (Real(*) (const Real &xx, const Real &tt) north_condition)
[noexcept]

Parameters

in	north_condition	$\beta_n(x, t) : \partial\Omega \times [t_0, t_n] \mapsto \mathbb{R}.$
----	-----------------	--

Definition at line 217 of file [mtk_robin_bc_descriptor_2d.cc](#).

Here is the call graph for this function:




16.20.3.21 void mtk::RobinBCDescriptor2D::set_south_condition (Real(*) (const Real &xx, const Real &tt) south_condition)
[noexcept]

Parameters

in	south_condition	$\beta_s(x, t) : \partial\Omega \times [t_0, t_n] \mapsto \mathbb{R}.$
----	-----------------	--

Definition at line 205 of file [mtk_robin_bc_descriptor_2d.cc](#).

Here is the call graph for this function:




16.20.3.22 void mtk::RobinBCDescriptor2D::set_west_condition (Real(*) (const Real &yy, const Real &tt) west_condition)
[noexcept]

Parameters

in	west_condition	$\beta_w(y, t) : \partial\Omega \times [t_0, t_n] \mapsto \mathbb{R}.$
----	----------------	--

Definition at line 183 of file [mtk_robin_bc_descriptor_2d.cc](#).

Here is the call graph for this function:



16.20.4 Member Data Documentation

16.20.4.1 `std::vector<CoefficientFunction1D> mtk::RobinBCDescriptor2D::east_coefficients_` [private]

Definition at line 367 of file [mtk_robin_bc_descriptor_2d.h](#).

16.20.4.2 `Real(* mtk::RobinBCDescriptor2D::east_condition_)(const Real &xx, const Real &tt)` [private]

Definition at line 372 of file [mtk_robin_bc_descriptor_2d.h](#).

16.20.4.3 `int mtk::RobinBCDescriptor2D::highest_order_diff_east_` [private]

Definition at line 362 of file [mtk_robin_bc_descriptor_2d.h](#).

16.20.4.4 `int mtk::RobinBCDescriptor2D::highest_order_diff_north_` [private]

Definition at line 364 of file [mtk_robin_bc_descriptor_2d.h](#).

16.20.4.5 `int mtk::RobinBCDescriptor2D::highest_order_diff_south_` [private]

Definition at line 363 of file [mtk_robin_bc_descriptor_2d.h](#).

16.20.4.6 `int mtk::RobinBCDescriptor2D::highest_order_diff_west_` [private]

Definition at line 361 of file [mtk_robin_bc_descriptor_2d.h](#).

16.20.4.7 `std::vector<CoefficientFunction1D> mtk::RobinBCDescriptor2D::north_coefficients_` [private]

Definition at line 369 of file [mtk_robin_bc_descriptor_2d.h](#).

16.20.4.8 `Real(* mtk::RobinBCDescriptor2D::north_condition_)(const Real &yy, const Real &tt)` [private]

Definition at line 374 of file [mtk_robin_bc_descriptor_2d.h](#).

16.20.4.9 `std::vector<CoefficientFunction1D> mtk::RobinBCDescriptor2D::south_coefficients_` [private]

Definition at line 368 of file [mtk_robin_bc_descriptor_2d.h](#).

16.20.4.10 `Real(* mtk::RobinBCDescriptor2D::south_condition_)(const Real &yy, const Real &tt)` [private]

Definition at line 373 of file [mtk_robin_bc_descriptor_2d.h](#).

16.20.4.11 `std::vector<CoefficientFunction1D> mtk::RobinBCDescriptor2D::west_coefficients_` [private]

Definition at line 366 of file [mtk_robin_bc_descriptor_2d.h](#).

16.20.4.12 `Real(* mtk::RobinBCDescriptor2D::west_condition_)(const Real &xx, const Real &tt)` [private]

Definition at line 371 of file [mtk_robin_bc_descriptor_2d.h](#).

The documentation for this class was generated from the following files:


- [include/mtk_robin_bc_descriptor_2d.h](#)
- [src/mtk_robin_bc_descriptor_2d.cc](#)

16.21 mtk::RobinBCDescriptor3D Class Reference

Impose Robin boundary conditions on the operators and on the grids.

```
#include <mtk_robin_bc_descriptor_3d.h>
```


Collaboration diagram for mtk::RobinBCDescriptor3D:



Public Member Functions

- [RobinBCDescriptor3D \(\)](#)

Default constructor.

- [RobinBCDescriptor3D](#) (const [RobinBCDescriptor3D](#) &desc)

Copy constructor.

- [~RobinBCDescriptor3D](#) () noexcept

Destructor.

- int [highest_order_diff_west](#) () const noexcept

*Getter for highest order of differentiation in the * face.*

- void [PushBackWestCoeff](#) ([CoefficientFunction2D](#) cw)

Push back coefficient function at west lowest order diff. available.

- void [set_west_condition](#) ([Real](#)(*west_condition)(const [Real](#) &xx, const [Real](#) &yy, const [Real](#) &tt)) noexcept

Set boundary condition at west.

- bool [ImposeOnLaplacianMatrix](#) (const [Lap3D](#) &lap, const [UniStgGrid3D](#) &grid, [DenseMatrix](#) &matrix, const [Real](#) &time=[kZero](#)) const

Imposes the condition on the operator represented as matrix.

- void [ImposeOnGrid](#) ([UniStgGrid3D](#) &grid, const [Real](#) &time=[kZero](#)) const

Imposes the condition on the grid.

Private Member Functions

- bool [ImposeOnSouthBoundaryNoSpace](#) (const [Lap2D](#) &lap, const [UniStgGrid2D](#) &grid, [DenseMatrix](#) &matrix, const [Real](#) &time=[kZero](#)) const

Imposes the condition on the south boundary.

- bool [ImposeOnNorthBoundaryNoSpace](#) (const [Lap2D](#) &lap, const [UniStgGrid2D](#) &grid, [DenseMatrix](#) &matrix, const [Real](#) &time=[kZero](#)) const

Imposes the condition on the north boundary.

- bool [ImposeOnWestBoundaryNoSpace](#) (const [Lap2D](#) &lap, const [UniStgGrid2D](#) &grid, [DenseMatrix](#) &matrix, const [Real](#) &time=[kZero](#)) const

Imposes the condition on the west boundary.

- bool [ImposeOnEastBoundaryNoSpace](#) (const [Lap2D](#) &lap, const [UniStgGrid2D](#) &grid, [DenseMatrix](#) &matrix, const [Real](#) &time=[kZero](#)) const

Imposes the condition on the east boundary.

- bool [ImposeOnSouthBoundaryWithSpace](#) (const [Lap2D](#) &lap, const [UniStgGrid2D](#) &grid, [DenseMatrix](#) &matrix, const [Real](#) &time=[kZero](#)) const

Imposes the condition on the south boundary.

- bool [ImposeOnNorthBoundaryWithSpace](#) (const [Lap2D](#) &lap, const [UniStgGrid2D](#) &grid, [DenseMatrix](#) &matrix, const [Real](#) &time=[kZero](#)) const

Imposes the condition on the north boundary.

- bool [ImposeOnWestBoundaryWithSpace](#) (const [Lap2D](#) &lap, const [UniStgGrid2D](#) &grid, [DenseMatrix](#) &matrix, const [Real](#) &time=[kZero](#)) const

Imposes the condition on the west boundary.

- bool [ImposeOnEastBoundaryWithSpace](#) (const [Lap2D](#) &lap, const [UniStgGrid2D](#) &grid, [DenseMatrix](#) &matrix, const [Real](#) &time=[kZero](#)) const

Imposes the condition on the east boundary.

Private Attributes

- int [highest_order_diff_west_](#)
Highest order of differentiation west.
- int [highest_order_diff_east_](#)
Highest order of differentiation east.
- int [highest_order_diff_south_](#)
Highest order differentiation for south.
- int [highest_order_diff_north_](#)
Highest order differentiation for north.
- int [highest_order_diff_bottom_](#)
Highest order differentiation bottom.
- int [highest_order_diff_top_](#)
Highest order differentiation for top.
- std::vector
< [CoefficientFunction2D](#) > [west_coefficients_](#)
Coeffs. west.
- std::vector
< [CoefficientFunction2D](#) > [east_coefficients_](#)
Coeffs. east.
- std::vector
< [CoefficientFunction2D](#) > [south_coefficients_](#)
Coeffs. south.
- std::vector
< [CoefficientFunction2D](#) > [north_coefficients_](#)
Coeffs. north.
- std::vector
< [CoefficientFunction2D](#) > [bottom_coefficients_](#)
Coeffs. bottom.
- std::vector
< [CoefficientFunction2D](#) > [top_coefficients_](#)
Coeffs. top.
- [Real](#)(* [west_condition_](#))(const [Real](#) &xx, const [Real](#) &yy, const [Real](#) &tt)
Condition west.
- [Real](#)(* [east_condition_](#))(const [Real](#) &xx, const [Real](#) &yy, const [Real](#) &tt)
Condition east.
- [Real](#)(* [south_condition_](#))(const [Real](#) &xx, const [Real](#) &yy, const [Real](#) &tt)
Cond. south.
- [Real](#)(* [north_condition_](#))(const [Real](#) &xx, const [Real](#) &yy, const [Real](#) &tt)
Cond. north.
- [Real](#)(* [bottom_condition_](#))(const [Real](#) &xx, const [Real](#) &yy, const [Real](#) &tt)
Cond. bottom.
- [Real](#)(* [top_condition_](#))(const [Real](#) &xx, const [Real](#) &yy, const [Real](#) &tt)
Cond. top.

16.21.1 Detailed Description

This class presents an interface for the user to specify Robin boundary conditions on 3D mimetic operators and the grids they are acting on.

Def. Let $u(\mathbf{x}, t) : \Omega \times [t_0, t_n] \mapsto \mathbb{R}$ be the solution to an ordinary or partial differential equation of interest. We say that u satisfies a **Robin boundary condition** on $\partial\Omega$ if and only if there exists $\beta(\mathbf{x}, t) : \Omega \times [t_0, t_n] \mapsto \mathbb{R}$ so that:

$$\forall t \in [t_0, t_n] \forall \mathbf{x} \in \partial\Omega : \delta(\mathbf{x}, t)u(\mathbf{x}, t) + \eta(\mathbf{x}, t)(\hat{\mathbf{n}} \cdot \nabla u) = \beta(\mathbf{x}, t).$$

Intuitively, a **Robin boundary condition** is a constraint that must be satisfied by any linear combination of any scalar field u and its first normal derivative, in order for u to represent a unique solution to a given ordinary or partial differential equation of interest.

Instances of this class receive information about the coefficient functions and each condition for any subset of the boundary. These instances then handle the complexity of placing the coefficients in the differentiation matrices and the conditions in the grids.

See also

<http://mathworld.wolfram.com/NormalVector.html>

Definition at line 134 of file [mtk_robin_bc_descriptor_3d.h](#).

16.21.2 Constructor & Destructor Documentation

16.21.2.1 `mtk::RobinBCDescriptor3D::RobinBCDescriptor3D ()`

16.21.2.2 `mtk::RobinBCDescriptor3D::RobinBCDescriptor3D (const RobinBCDescriptor3D & desc)`

Parameters

<i>in</i>	<i>desc</i>	Given 2D descriptor.
-----------	-------------	----------------------

16.21.2.3 `mtk::RobinBCDescriptor3D::~~RobinBCDescriptor3D () [noexcept]`

16.21.3 Member Function Documentation

16.21.3.1 `int mtk::RobinBCDescriptor3D::highest_order_diff_west () const [noexcept]`

Returns

Integer highest order of differentiation in the * face.

16.21.3.2 `bool mtk::RobinBCDescriptor3D::ImposeOnEastBoundaryNoSpace (const Lap2D & lap, const UniStgGrid2D & grid, DenseMatrix & matrix, const Real & time = kZero) const [private]`

Parameters

in	<i>lap</i>	Laplacian operator on the matrix.
in	<i>grid</i>	Grid upon which impose the desired boundary condition.
in, out	<i>matrix</i>	Input matrix with the Laplacian operator.
in	<i>time</i>	Current time snapshot. Default is kZero.

16.21.3.3 **bool** mtk::RobinBCDescriptor3D::ImposeOnEastBoundaryWithSpace (**const** Lap2D & *lap*, **const** UniStgGrid2D & *grid*, DenseMatrix & *matrix*, **const** Real & *time* = kZero) **const** [private]

Parameters

in	<i>lap</i>	Laplacian operator on the matrix.
in	<i>grid</i>	Grid upon which impose the desired boundary condition.
in, out	<i>matrix</i>	Input matrix with the Laplacian operator.
in	<i>time</i>	Current time snapshot. Default is kZero.

16.21.3.4 **void** mtk::RobinBCDescriptor3D::ImposeOnGrid (UniStgGrid3D & *grid*, **const** Real & *time* = kZero) **const**

Parameters

in, out	<i>grid</i>	Grid upon which impose the desired boundary condition.
in	<i>time</i>	Current time snapshot. Default is kZero.

16.21.3.5 **bool** mtk::RobinBCDescriptor3D::ImposeOnLaplacianMatrix (**const** Lap3D & *lap*, **const** UniStgGrid3D & *grid*, DenseMatrix & *matrix*, **const** Real & *time* = kZero) **const**

Parameters

in	<i>lap</i>	Laplacian operator on the matrix.
in	<i>grid</i>	Grid upon which impose the desired boundary condition.
in, out	<i>matrix</i>	Input matrix with the Laplacian operator.
in	<i>time</i>	Current time snapshot. Default is kZero.

16.21.3.6 **bool** mtk::RobinBCDescriptor3D::ImposeOnNorthBoundaryNoSpace (**const** Lap2D & *lap*, **const** UniStgGrid2D & *grid*, DenseMatrix & *matrix*, **const** Real & *time* = kZero) **const** [private]

Parameters

in	<i>lap</i>	Laplacian operator on the matrix.
in	<i>grid</i>	Grid upon which impose the desired boundary condition.
in, out	<i>matrix</i>	Input matrix with the Laplacian operator.
in	<i>time</i>	Current time snapshot. Default is kZero.

16.21.3.7 **bool** mtk::RobinBCDescriptor3D::ImposeOnNorthBoundaryWithSpace (**const** Lap2D & *lap*, **const** UniStgGrid2D & *grid*, DenseMatrix & *matrix*, **const** Real & *time* = kZero) **const** [private]

Parameters

in	<i>lap</i>	Laplacian operator on the matrix.
in	<i>grid</i>	Grid upon which impose the desired boundary condition.
in, out	<i>matrix</i>	Input matrix with the Laplacian operator.
in	<i>time</i>	Current time snapshot. Default is kZero.

16.21.3.8 `bool mtk::RobinBCDescriptor3D::ImposeOnSouthBoundaryNoSpace (const Lap2D & lap, const UniStgGrid2D & grid, DenseMatrix & matrix, const Real & time = kZero) const [private]`

Parameters

in	<i>lap</i>	Laplacian operator on the matrix.
in	<i>grid</i>	Grid upon which impose the desired boundary condition.
in, out	<i>matrix</i>	Input matrix with the Laplacian operator.
in	<i>time</i>	Current time snapshot. Default is kZero.

16.21.3.9 `bool mtk::RobinBCDescriptor3D::ImposeOnSouthBoundaryWithSpace (const Lap2D & lap, const UniStgGrid2D & grid, DenseMatrix & matrix, const Real & time = kZero) const [private]`

Parameters

in	<i>lap</i>	Laplacian operator on the matrix.
in	<i>grid</i>	Grid upon which impose the desired boundary condition.
in, out	<i>matrix</i>	Input matrix with the Laplacian operator.
in	<i>time</i>	Current time snapshot. Default is kZero.

16.21.3.10 `bool mtk::RobinBCDescriptor3D::ImposeOnWestBoundaryNoSpace (const Lap2D & lap, const UniStgGrid2D & grid, DenseMatrix & matrix, const Real & time = kZero) const [private]`

Parameters

in	<i>lap</i>	Laplacian operator on the matrix.
in	<i>grid</i>	Grid upon which impose the desired boundary condition.
in, out	<i>matrix</i>	Input matrix with the Laplacian operator.
in	<i>time</i>	Current time snapshot. Default is kZero.

16.21.3.11 `bool mtk::RobinBCDescriptor3D::ImposeOnWestBoundaryWithSpace (const Lap2D & lap, const UniStgGrid2D & grid, DenseMatrix & matrix, const Real & time = kZero) const [private]`

Parameters

in	<i>lap</i>	Laplacian operator on the matrix.
in	<i>grid</i>	Grid upon which impose the desired boundary condition.
in, out	<i>matrix</i>	Input matrix with the Laplacian operator.

<i>in</i>	<i>time</i>	Current time snapshot. Default is kZero.
-----------	-------------	--

16.21.3.12 void mtk::RobinBCDescriptor3D::PushBackWestCoeff (CoefficientFunction2D *cw*)

Parameters

<i>in</i>	<i>cw</i>	Coeff. $c_w(x, y, t) : \partial\Omega \times [t_0, t_n] \mapsto \mathbb{R}$.
-----------	-----------	---

16.21.3.13 void mtk::RobinBCDescriptor3D::set_west_condition (Real(*) (const Real &xx, const Real &yy, const Real &tt) *west_condition*) [noexcept]

Parameters

<i>in</i>	<i>west_condition</i>	$\beta_w(x, y, t) : \partial\Omega \times [t_0, t_n] \mapsto \mathbb{R}$.
-----------	-----------------------	--

16.21.4 Member Data Documentation

16.21.4.1 std::vector<CoefficientFunction2D> mtk::RobinBCDescriptor3D::bottom_coefficients_ [private]

Definition at line 309 of file [mtk_robin_bc_descriptor_3d.h](#).

16.21.4.2 Real(* mtk::RobinBCDescriptor3D::bottom_condition_)(const Real &xx, const Real &yy, const Real &tt) [private]

Definition at line 324 of file [mtk_robin_bc_descriptor_3d.h](#).

16.21.4.3 std::vector<CoefficientFunction2D> mtk::RobinBCDescriptor3D::east_coefficients_ [private]

Definition at line 306 of file [mtk_robin_bc_descriptor_3d.h](#).

16.21.4.4 Real(* mtk::RobinBCDescriptor3D::east_condition_)(const Real &xx, const Real &yy, const Real &tt) [private]

Definition at line 315 of file [mtk_robin_bc_descriptor_3d.h](#).

16.21.4.5 int mtk::RobinBCDescriptor3D::highest_order_diff_bottom_ [private]

Definition at line 302 of file [mtk_robin_bc_descriptor_3d.h](#).

16.21.4.6 int mtk::RobinBCDescriptor3D::highest_order_diff_east_ [private]

Definition at line 299 of file [mtk_robin_bc_descriptor_3d.h](#).

16.21.4.7 int mtk::RobinBCDescriptor3D::highest_order_diff_north_ [private]

Definition at line 301 of file [mtk_robin_bc_descriptor_3d.h](#).

16.21.4.8 `int mtk::RobinBCDescriptor3D::highest_order_diff_south_ [private]`

Definition at line 300 of file [mtk_robin_bc_descriptor_3d.h](#).

16.21.4.9 `int mtk::RobinBCDescriptor3D::highest_order_diff_top_ [private]`

Definition at line 303 of file [mtk_robin_bc_descriptor_3d.h](#).

16.21.4.10 `int mtk::RobinBCDescriptor3D::highest_order_diff_west_ [private]`

Definition at line 298 of file [mtk_robin_bc_descriptor_3d.h](#).

16.21.4.11 `std::vector<CoefficientFunction2D> mtk::RobinBCDescriptor3D::north_coefficients_ [private]`

Definition at line 308 of file [mtk_robin_bc_descriptor_3d.h](#).

16.21.4.12 `Real(* mtk::RobinBCDescriptor3D::north_condition_)(const Real &xx, const Real &yy, const Real &tt) [private]`

Definition at line 321 of file [mtk_robin_bc_descriptor_3d.h](#).

16.21.4.13 `std::vector<CoefficientFunction2D> mtk::RobinBCDescriptor3D::south_coefficients_ [private]`

Definition at line 307 of file [mtk_robin_bc_descriptor_3d.h](#).

16.21.4.14 `Real(* mtk::RobinBCDescriptor3D::south_condition_)(const Real &xx, const Real &yy, const Real &tt) [private]`

Definition at line 318 of file [mtk_robin_bc_descriptor_3d.h](#).

16.21.4.15 `std::vector<CoefficientFunction2D> mtk::RobinBCDescriptor3D::top_coefficients_ [private]`

Definition at line 310 of file [mtk_robin_bc_descriptor_3d.h](#).

16.21.4.16 `Real(* mtk::RobinBCDescriptor3D::top_condition_)(const Real &xx, const Real &yy, const Real &tt) [private]`

Definition at line 327 of file [mtk_robin_bc_descriptor_3d.h](#).

16.21.4.17 `std::vector<CoefficientFunction2D> mtk::RobinBCDescriptor3D::west_coefficients_ [private]`

Definition at line 305 of file [mtk_robin_bc_descriptor_3d.h](#).

16.21.4.18 `Real(* mtk::RobinBCDescriptor3D::west_condition_)(const Real &xx, const Real &yy, const Real &tt)`
`[private]`

Definition at line 312 of file [mtk_robin_bc_descriptor_3d.h](#).

The documentation for this class was generated from the following file:


- [include/mtk_robin_bc_descriptor_3d.h](#)

16.22 mtk::Tools Class Reference

Tool manager class.

```
#include <mtk_tools.h>
```

Collaboration diagram for mtk::Tools:



Static Public Member Functions

- static void [Prevent](#) (const bool complement, const char *const fname, int lineno, const char *const fxname) noexcept
Enforces preconditions by preventing their complements from occur.
- static void [BeginUnitTestNo](#) (const int &nn) noexcept
Begins the execution of a unit test. Starts a timer.
- static void [EndUnitTestNo](#) (const int &nn) noexcept
Ends the execution of a unit test. Stops and reports wall-clock time.
- static void [Assert](#) (const bool &condition) noexcept
Asserts if the condition required to pass the unit test occurs.

Static Private Attributes

- static int [test_number_](#)
Current test being executed.

- static [Real duration_](#)
Duration of the current test.
- static clock_t [begin_time_](#)
Elapsed time on current test.

16.22.1 Detailed Description

Basic tools to ensure execution correctness.

Definition at line 78 of file [mtk_tools.h](#).

16.22.2 Member Function Documentation

16.22.2.1 void `mtk::Tools::Assert (const bool & condition)` `[static]`, `[noexcept]`

Parameters

<code>in</code>	<code><i>condition</i></code>	Condition to be asserted.
-----------------	-------------------------------	---------------------------

Definition at line 109 of file [mtk_tools.cc](#).


16.22.2.2 void `mtk::Tools::BeginUnitTestNo (const int & nn)` `[static]`, `[noexcept]`

Parameters

<code>in</code>	<code><i>nn</i></code>	Number of the test.
-----------------	------------------------	---------------------

Definition at line 88 of file [mtk_tools.cc](#).

Here is the call graph for this function:




16.22.2.3 void `mtk::Tools::EndUnitTestNo (const int & nn)` `[static]`, `[noexcept]`

Parameters

<code>in</code>	<code><i>nn</i></code>	Number of the test.
-----------------	------------------------	---------------------

Definition at line 100 of file [mtk_tools.cc](#).

Here is the call graph for this function:



16.22.2.4 `void mtk::Tools::Prevent (const bool complement, const char *const fname, int lineno, const char *const fxname)`
`[static], [noexcept]`

See also

<http://stackoverflow.com/questions/8884335/print-the-file-name-line-number-and-function>

Parameters

in	<i>complement</i>	Complement of desired pre-condition.
in	<i>fname</i>	Name of the file being checked.
in	<i>lineno</i>	Number of the line where the check is executed.
in	<i>fxname</i>	Name of the module containing the check.

Todo Check if this is the best way of stalling execution.

Definition at line 61 of file [mtk_tools.cc](#).

16.22.3 Member Data Documentation

16.22.3.1 `clock_t mtk::Tools::begin_time_ [static], [private]`

Definition at line 121 of file [mtk_tools.h](#).

16.22.3.2 `mtk::Real mtk::Tools::duration_ [static], [private]`

Definition at line 119 of file [mtk_tools.h](#).

16.22.3.3 `int mtk::Tools::test_number_ [static], [private]`

Todo Check usage of static methods and private members.

Definition at line 117 of file [mtk_tools.h](#).

The documentation for this class was generated from the following files:


- [include/mtk_tools.h](#)
- [src/mtk_tools.cc](#)

16.23 mtk::UniStgGrid1D Class Reference

Uniform 1D Staggered Grid.

```
#include <mtk_uni_stg_grid_1d.h>
```

Collaboration diagram for mtk::UniStgGrid1D:



Public Member Functions

- [UniStgGrid1D](#) ()
Default constructor.
- [UniStgGrid1D](#) (const [UniStgGrid1D](#) &grid)
Copy constructor.
- [UniStgGrid1D](#) (const [Real](#) &west_bndy_x, const [Real](#) &east_bndy_x, const int &num_cells_x, const [mtk::Field](#) &nature=mtk::SCALAR)
Construct a grid based on spatial discretization parameters.
- [~UniStgGrid1D](#) ()
Destructor.
- [Real west_bndy_x](#) () const
Provides access to west boundary spatial coordinate.
- [Real east_bndy_x](#) () const
Provides access to east boundary spatial coordinate.
- [Real delta_x](#) () const
Provides access to the computed Δx .
- const [Real](#) * [discrete_domain_x](#) () const
Provides access to the grid spatial data.
- [Real](#) * [discrete_field](#) ()
Provides access to the grid field data.
- int [num_cells_x](#) () const
Provides access to the number of cells of the grid.
- void [BindScalarField](#) ([Real](#)(*ScalarField)(const [Real](#) &xx))
Binds a given scalar field to the grid.
- void [BindVectorField](#) ([Real](#)(*VectorField)([Real](#) xx))
Binds a given vector field to the grid.
- bool [WriteToFile](#) (std::string filename, std::string space_name, std::string field_name) const
Writes grid to a file compatible with gnuplot 4.6.

Private Attributes

- [FieldNature nature_](#)
Nature of the discrete field.
- std::vector< [Real](#) > [discrete_domain_x_](#)
Array of spatial data.
- std::vector< [Real](#) > [discrete_field_](#)
Array of field's data.
- [Real west_bndy_x_](#)
West boundary spatial coordinate.
- [Real east_bndy_x_](#)
East boundary spatial coordinate.
- [Real num_cells_x_](#)
Number of cells discretizing the domain.
- [Real delta_x_](#)
Produced Δx .

Friends

- `std::ostream & operator<< (std::ostream &stream, UniStgGrid1D &in)`
Prints the grid as a tuple of arrays.

16.23.1 Detailed Description

Uniform 1D Staggered Grid.

Definition at line 77 of file [mtk_uni_stg_grid_1d.h](#).

16.23.2 Constructor & Destructor Documentation

16.23.2.1 `mtk::UniStgGrid1D::UniStgGrid1D ()`

Definition at line 99 of file [mtk_uni_stg_grid_1d.cc](#).

16.23.2.2 `mtk::UniStgGrid1D::UniStgGrid1D (const UniStgGrid1D &grid)`

Parameters

<code>in</code>	<code>grid</code>	Given grid.
-----------------	-------------------	-------------

Definition at line 108 of file [mtk_uni_stg_grid_1d.cc](#).

16.23.2.3 `mtk::UniStgGrid1D::UniStgGrid1D (const Real &west_bndy_x, const Real &east_bndy_x, const int &num_cells_x, const mtk::FieldNature &nature = mtk::SCALAR)`

Parameters


<code>in</code>	<code>west_bndy_x</code>	Coordinate for the west boundary.
<code>in</code>	<code>east_bndy_x</code>	Coordinate for the east boundary.
<code>in</code>	<code>num_cells_x</code>	Number of cells of the required grid.
<code>in</code>	<code>nature</code>	Nature of the discrete field to hold.

See also

[mtk::FieldNature](#)

Definition at line 124 of file [mtk_uni_stg_grid_1d.cc](#).

Here is the call graph for this function:



16.23.2.4 mtk::UniStgGrid1D::~~UniStgGrid1D ()

Definition at line 144 of file [mtk_uni_stg_grid_1d.cc](#).

16.23.3 Member Function Documentation

16.23.3.1 void mtk::UniStgGrid1D::BindScalarField (*Real*(*) (const *Real* &xx) *ScalarField*)


Parameters

in	<i>ScalarField</i>	Pointer to the function implementing the scalar field.
----	--------------------	--

1. Create collection of spatial coordinates.
2. Create collection of field samples.

Definition at line 176 of file [mtk_uni_stg_grid_1d.cc](#).

Here is the call graph for this function:

16.23.3.2 void mtk::UniStgGrid1D::BindVectorField (*Real*(*)(*Real* xx) *VectorField*)

We assume the field to be of the form:

$$\mathbf{v}(\mathbf{x}) = v(x)\hat{\mathbf{i}}$$


Parameters

in	<i>VectorField</i>	Pointer to the function implementing the vector field.
----	--------------------	--

1. Create collection of spatial coordinates.
2. Create collection of field samples.

Definition at line 212 of file [mtk_uni_stg_grid_1d.cc](#).

Here is the call graph for this function:




16.23.3.3 `mtk::Real mtk::UniStgGrid1D::delta_x () const`

Returns

Computed Δx .

Definition at line 156 of file [mtk_uni_stg_grid_1d.cc](#).

Here is the caller graph for this function:



16.23.3.4 `const mtk::Real * mtk::UniStgGrid1D::discrete_domain_x () const`

Returns

Pointer to the spatial data.

Todo Review const-correctness of the pointer we return.

Definition at line 161 of file [mtk_uni_stg_grid_1d.cc](#).

16.23.3.5 `mtk::Real * mtk::UniStgGrid1D::discrete_field ()`


Returns

Pointer to the field data.

Todo Review const-correctness of the pointer we return. Look at the STL!

Definition at line 166 of file [mtk_uni_stg_grid_1d.cc](#).

Here is the caller graph for this function:

**16.23.3.6 mtk::Real mtk::UniStgGrid1D::east_bndy_x () const****Returns**

East boundary spatial coordinate.

Definition at line 151 of file [mtk_uni_stg_grid_1d.cc](#).


16.23.3.7 int mtk::UniStgGrid1D::num_cells_x () const

Returns

Number of cells of the grid.

Definition at line 171 of file [mtk_uni_stg_grid_1d.cc](#).

Here is the caller graph for this function:



16.23.3.8 `mtk::Real mtk::UniStgGrid1D::west_bndy_x () const`

Returns

West boundary spatial coordinate.

Definition at line 146 of file [mtk_uni_stg_grid_1d.cc](#).

16.23.3.9 `bool mtk::UniStgGrid1D::WriteToFile (std::string filename, std::string space_name, std::string field_name) const`

Parameters

in	<i>filename</i>	Name of the output file.
in	<i>space_name</i>	Name for the first column of the data.
in	<i>field_name</i>	Name for the second column of the data.

Returns

Success of the file writing process.

See also

<http://www.gnuplot.info/>

Definition at line 240 of file [mtk_uni_stg_grid_1d.cc](#).

16.23.4 Friends And Related Function Documentation

16.23.4.1 `std::ostream& operator<< (std::ostream & stream, mtk::UniStgGrid1D & in)` [friend]

1. Print spatial coordinates.
2. Print scalar field.

Definition at line 68 of file [mtk_uni_stg_grid_1d.cc](#).

16.23.5 Member Data Documentation

16.23.5.1 **Real** `mtk::UniStgGrid1D::delta_x_` [private]

Definition at line 199 of file [mtk_uni_stg_grid_1d.h](#).

16.23.5.2 `std::vector<Real>` `mtk::UniStgGrid1D::discrete_domain_x_` [private]

Definition at line 193 of file [mtk_uni_stg_grid_1d.h](#).

16.23.5.3 `std::vector<Real>` `mtk::UniStgGrid1D::discrete_field_` [private]

Definition at line 194 of file [mtk_uni_stg_grid_1d.h](#).

16.23.5.4 **Real** `mtk::UniStgGrid1D::east_bndy_x_` [private]

Definition at line 197 of file [mtk_uni_stg_grid_1d.h](#).

16.23.5.5 **FieldNature** `mtk::UniStgGrid1D::nature_` [private]

Definition at line 191 of file [mtk_uni_stg_grid_1d.h](#).

16.23.5.6 **Real** `mtk::UniStgGrid1D::num_cells_x_` [private]

Definition at line 198 of file [mtk_uni_stg_grid_1d.h](#).

16.23.5.7 **Real** `mtk::UniStgGrid1D::west_bndy_x_` [private]

Definition at line 196 of file [mtk_uni_stg_grid_1d.h](#).

The documentation for this class was generated from the following files:


- [include/mtk_uni_stg_grid_1d.h](#)
- [src/mtk_uni_stg_grid_1d.cc](#)

16.24 mtk::UniStgGrid2D Class Reference

Uniform 2D Staggered Grid.

```
#include <mtk_uni_stg_grid_2d.h>
```

Collaboration diagram for `mtk::UniStgGrid2D`:



Public Member Functions

- [UniStgGrid2D](#) ()

Default constructor.

- **UniStgGrid2D** (const **UniStgGrid2D** &grid)

Copy constructor.

- **UniStgGrid2D** (const **Real** &west_bndy_x, const **Real** &east_bndy_x, const int &num_cells_x, const **Real** &south_bndy_y, const **Real** &north_bndy_y, const int &num_cells_y, const **mtk::FieldNature** &nature=**mtk::S↔**
CALAR)

Construct a grid based on spatial discretization parameters.

- **~UniStgGrid2D** ()

Destructor.

- const **Real** * **discrete_domain_x** () const

Provides access to the grid spatial data.

- const **Real** * **discrete_domain_y** () const

Provides access to the grid spatial data.

- **Real** * **discrete_field** ()

Provides access to the grid field data.

- **FieldNature** **nature** () const

Physical nature of the data bound to the grid.

- **Real** **west_bndy** () const

Provides access to west boundary spatial coordinate.

- **Real** **east_bndy** () const

Provides access to east boundary spatial coordinate.

- int **num_cells_x** () const

Provides access to the number of cells of the grid.

- **Real** **delta_x** () const

Provides access to the computed Δx .

- **Real** **south_bndy** () const

Provides access to south boundary spatial coordinate.

- **Real** **north_bndy** () const

Provides access to north boundary spatial coordinate.

- int **num_cells_y** () const

Provides access to the number of cells of the grid.

- **Real** **delta_y** () const

Provides access to the computed Δy .

- bool **Bound** () const

Have any field been bound to the grid?

- int **Size** () const

Total number of samples in the grid.

- void **BindScalarField** (**Real**(*ScalarField)(const **Real** &xx, const **Real** &yy))

Binds a given scalar field to the grid.

- void **BindVectorField** (**Real**(*VectorFieldPComponent)(const **Real** &xx, const **Real** &yy), **Real**(*VectorFieldQ↔
Component)(const **Real** &xx, const **Real** &yy))

Binds a given vector field to the grid.

- bool **WriteToFile** (std::string filename, std::string space_name_x, std::string space_name_y, std::string field_↔
name) const

Writes grid to a file compatible with Gnuplot 4.6.

Private Member Functions

- void `BindVectorFieldPComponent` (`Real`(*VectorFieldPComponent)(const `Real` &xx, const `Real` &yy))
Binds a given component of a vector field to the grid.
- void `BindVectorFieldQComponent` (`Real`(*VectorFieldQComponent)(const `Real` &xx, const `Real` &yy))
Binds a given component of a vector field to the grid.

Private Attributes

- `std::vector< Real > discrete_domain_x_`
Array of spatial data.
- `std::vector< Real > discrete_domain_y_`
Array of spatial data.
- `std::vector< Real > discrete_field_`
Array of field's data.
- `FieldNature nature_`
Nature of the discrete field.
- `Real west_bndy_`
West boundary spatial coordinate.
- `Real east_bndy_`
East boundary spatial coordinate.
- `int num_cells_x_`
Number of cells discretizing the domain.
- `Real delta_x_`
Computed Δx .
- `Real south_bndy_`
West boundary spatial coordinate.
- `Real north_bndy_`
East boundary spatial coordinate.
- `int num_cells_y_`
Number of cells discretizing the domain.
- `Real delta_y_`
Computed Δy .

Friends

- `std::ostream & operator<<` (`std::ostream` &stream, `UniStgGrid2D` &in)
Prints the grid as a tuple of arrays.

16.24.1 Detailed Description

Uniform 2D Staggered Grid.

Definition at line 79 of file `mtk_uni_stg_grid_2d.h`.

16.24.2 Constructor & Destructor Documentation

16.24.2.1 mtk::UniStgGrid2D::UniStgGrid2D ()

Definition at line 131 of file [mtk_uni_stg_grid_2d.cc](#).

16.24.2.2 mtk::UniStgGrid2D::UniStgGrid2D (const UniStgGrid2D & grid)

Parameters

in	<i>grid</i>	Given grid.
----	-------------	-------------

Definition at line 145 of file [mtk_uni_stg_grid_2d.cc](#).

16.24.2.3 mtk::UniStgGrid2D::UniStgGrid2D (const Real & west_bndy_x, const Real & east_bndy_x, const int & num_cells_x, const Real & south_bndy_y, const Real & north_bndy_y, const int & num_cells_y, const mtk::FieldNature & nature = mtk::SCALAR)

Parameters

in	<i>west_bndy_x</i>	Coordinate for the west boundary.
in	<i>east_bndy_x</i>	Coordinate for the east boundary.
in	<i>num_cells_x</i>	Number of cells of the required grid.
in	<i>south_bndy_y</i>	Coordinate for the west boundary.
in	<i>north_bndy_y</i>	Coordinate for the east boundary.
in	<i>num_cells_y</i>	Number of cells of the required grid.
in	<i>nature</i>	Nature of the discrete field to hold.

See also

[mtk::FieldNature](#)

Definition at line 169 of file [mtk_uni_stg_grid_2d.cc](#).

Here is the call graph for this function:



16.24.2.4 mtk::UniStgGrid2D::~~UniStgGrid2D ()

Definition at line 203 of file [mtk_uni_stg_grid_2d.cc](#).

16.24.3 Member Function Documentation

16.24.3.1 void mtk::UniStgGrid2D::BindScalarField (Real(*) (const Real &xx, const Real &yy) *ScalarField*)

Parameters

in	<i>ScalarField</i>	Pointer to the function implementing the scalar field.
----	--------------------	--

1. Create collection of spatial coordinates for x .
2. Create collection of spatial coordinates for y .
3. Create collection of field samples.

Definition at line 275 of file [mtk_uni_stg_grid_2d.cc](#).

Here is the call graph for this function:



16.24.3.2 void mtk::UniStgGrid2D::BindVectorField (Real(*) (const Real &xx, const Real &yy) *VectorFieldPComponent*, Real(*) (const Real &xx, const Real &yy) *VectorFieldQComponent*)

We assume the field to be of the form:


$$\mathbf{v}(\mathbf{x}) = p(x, y) \hat{\mathbf{i}} + q(x, y) \hat{\mathbf{j}}$$

Parameters

in	<i>VectorFieldPComponent</i>	Pointer to the function implementing the p component of the vector field.
in	<i>VectorFieldQComponent</i>	Pointer to the function implementing the q component of the vector field.

Definition at line 423 of file [mtk_uni_stg_grid_2d.cc](#).

Here is the call graph for this function:



16.24.3.3 void mtk::UniStgGrid2D::BindVectorFieldPComponent (Real(*) (const Real &xx, const Real &yy) VectorFieldPComponent) [private]

We assume the field to be of the form:

$$\mathbf{v}(\mathbf{x}) = p(x, y)\hat{\mathbf{i}} + q(x, y)\hat{\mathbf{j}}$$

Parameters

in	<i>BindVectorFieldPComponent</i>	Pointer to the function implementing the \$ p \$ component of the vector field.
----	----------------------------------	---

1. Create collection of spatial coordinates for x .
2. Create collection of spatial coordinates for y .
3. Allocate space for discrete vector field and bind \$ p \$ component.

Definition at line 330 of file [mtk_uni_stg_grid_2d.cc](#).

16.24.3.4 void mtk::UniStgGrid2D::BindVectorFieldQComponent (Real(*) (const Real &xx, const Real &yy) VectorFieldQComponent) [private]

We assume the field to be of the form:

$$\mathbf{v}(\mathbf{x}) = p(x, y)\hat{\mathbf{i}} + q(x, y)\hat{\mathbf{j}}$$

Parameters

in	<i>BindVectorFieldQComponent</i>	Pointer to the function implementing the \$ q \$ component of the vector field.
----	----------------------------------	---

1. Bind \$ q \$ component, since \$ p \$ component has already been bound.

Definition at line 395 of file [mtk_uni_stg_grid_2d.cc](#).

16.24.3.5 bool mtk::UniStgGrid2D::Bound () const

Returns

True is a field has been bound.

Definition at line 255 of file [mtk_uni_stg_grid_2d.cc](#).


Here is the caller graph for this function:

**16.24.3.6 mtk::Real mtk::UniStgGrid2D::delta_x () const****Returns**

Computed Δx .

Definition at line 225 of file [mtk_uni_stg_grid_2d.cc](#).

Here is the caller graph for this function:


**16.24.3.7 mtk::Real mtk::UniStgGrid2D::delta_y () const**

Returns

Computed Δy .

Definition at line 250 of file [mtk_uni_stg_grid_2d.cc](#).

Here is the caller graph for this function:



16.24.3.8 `const mtk::Real * mtk::UniStgGrid2D::discrete_domain_x () const`


Returns

Pointer to the spatial data.

Todo Review const-correctness of the pointer we return.

Definition at line 230 of file [mtk_uni_stg_grid_2d.cc](#).

Here is the caller graph for this function:



16.24.3.9 `const mtk::Real * mtk::UniStgGrid2D::discrete_domain_y () const`


Returns

Pointer to the spatial data.

Todo Review const-correctness of the pointer we return.

Definition at line 260 of file [mtk_uni_stg_grid_2d.cc](#).

Here is the caller graph for this function:




16.24.3.10 `mtk::Real * mtk::UniStgGrid2D::discrete_field ()`

Returns

Pointer to the field data.

Definition at line 265 of file [mtk_uni_stg_grid_2d.cc](#).

Here is the caller graph for this function:




16.24.3.11 `mtk::Real mtk::UniStgGrid2D::east_bndy () const`

Returns

East boundary spatial coordinate.

Definition at line 215 of file [mtk_uni_stg_grid_2d.cc](#).

Here is the caller graph for this function:



16.24.3.12 mtk::FieldNature mtk::UniStgGrid2D::nature () const

Returns


Value of an enumeration.

See also

[mtk::FieldNature](#)

Definition at line 205 of file [mtk_uni_stg_grid_2d.cc](#).

Here is the caller graph for this function:




16.24.3.13 `mtk::Real mtk::UniStgGrid2D::north_bndy () const`

Returns

North boundary spatial coordinate.

Definition at line [240](#) of file [mtk_uni_stg_grid_2d.cc](#).

Here is the caller graph for this function:




16.24.3.14 `int mtk::UniStgGrid2D::num_cells_x () const`

Returns

Number of cells of the grid.

Definition at line [220](#) of file [mtk_uni_stg_grid_2d.cc](#).

Here is the caller graph for this function:




16.24.3.15 `int mtk::UniStgGrid2D::num_cells_y () const`

Returns

Number of cells of the grid.

Definition at line 245 of file [mtk_uni_stg_grid_2d.cc](#).

Here is the caller graph for this function:



16.24.3.16 `int mtk::UniStgGrid2D::Size () const`

Returns

Total number of samples in the grid.

Definition at line 270 of file [mtk_uni_stg_grid_2d.cc](#).


16.24.3.17 `mtk::Real mtk::UniStgGrid2D::south_bndy () const`

Returns

South boundary spatial coordinate.

Definition at line 235 of file [mtk_uni_stg_grid_2d.cc](#).

Here is the caller graph for this function:




16.24.3.18 mtk::Real mtk::UniStgGrid2D::west_bndy () const

Returns

West boundary spatial coordinate.

Definition at line 210 of file [mtk_uni_stg_grid_2d.cc](#).

Here is the caller graph for this function:



16.24.3.19 `bool mtk::UniStgGrid2D::WriteToFile (std::string filename, std::string space_name_x, std::string space_name_y,
std::string field_name) const`

Parameters

in	<i>filename</i>	Name of the output file.
in	<i>space_name_x</i>	Name for the first column of the (spatial) data.
in	<i>space_name_y</i>	Name for the second column of the (spatial) data.
in	<i>field_name</i>	Name for the second column of the (physical field) data.

Returns

Success of the file writing process.

See also

<http://www.gnuplot.info/>

Write the values of the p component, with a null q component.

Write the values of the q component, with a null p component.

Definition at line 435 of file [mtk_uni_stg_grid_2d.cc](#).

16.24.4 Friends And Related Function Documentation

16.24.4.1 `std::ostream& operator<< (std::ostream & stream, mtk::UniStgGrid2D & in)` `[friend]`

1. Print spatial coordinates.

2. Print scalar field.

Definition at line 67 of file [mtk_uni_stg_grid_2d.cc](#).

16.24.5 Member Data Documentation

16.24.5.1 `Real mtk::UniStgGrid2D::delta_x_` `[private]`

Definition at line 302 of file [mtk_uni_stg_grid_2d.h](#).

16.24.5.2 `Real mtk::UniStgGrid2D::delta_y_` `[private]`

Definition at line 307 of file [mtk_uni_stg_grid_2d.h](#).

16.24.5.3 `std::vector<Real> mtk::UniStgGrid2D::discrete_domain_x_` `[private]`

Definition at line 293 of file [mtk_uni_stg_grid_2d.h](#).

16.24.5.4 `std::vector<Real> mtk::UniStgGrid2D::discrete_domain_y_` `[private]`

Definition at line 294 of file [mtk_uni_stg_grid_2d.h](#).

16.24.5.5 `std::vector<Real> mtk::UniStgGrid2D::discrete_field_` [private]

Definition at line 295 of file [mtk_uni_stg_grid_2d.h](#).

16.24.5.6 `Real mtk::UniStgGrid2D::east_bndy_` [private]

Definition at line 300 of file [mtk_uni_stg_grid_2d.h](#).

16.24.5.7 `FieldNature mtk::UniStgGrid2D::nature_` [private]

Definition at line 297 of file [mtk_uni_stg_grid_2d.h](#).

16.24.5.8 `Real mtk::UniStgGrid2D::north_bndy_` [private]

Definition at line 305 of file [mtk_uni_stg_grid_2d.h](#).

16.24.5.9 `int mtk::UniStgGrid2D::num_cells_x_` [private]

Definition at line 301 of file [mtk_uni_stg_grid_2d.h](#).

16.24.5.10 `int mtk::UniStgGrid2D::num_cells_y_` [private]

Definition at line 306 of file [mtk_uni_stg_grid_2d.h](#).

16.24.5.11 `Real mtk::UniStgGrid2D::south_bndy_` [private]

Definition at line 304 of file [mtk_uni_stg_grid_2d.h](#).

16.24.5.12 `Real mtk::UniStgGrid2D::west_bndy_` [private]

Definition at line 299 of file [mtk_uni_stg_grid_2d.h](#).

The documentation for this class was generated from the following files:


- [include/mtk_uni_stg_grid_2d.h](#)
- [src/mtk_uni_stg_grid_2d.cc](#)

16.25 mtk::UniStgGrid3D Class Reference

Uniform 3D Staggered Grid.

```
#include <mtk_uni_stg_grid_3d.h>
```

Collaboration diagram for mtk::UniStgGrid3D:



Public Member Functions

- [UniStgGrid3D operator=](#) (const [UniStgGrid3D](#) &in)

Overloaded assignment operator.

- [UniStgGrid3D](#) ()

Default constructor.

- [UniStgGrid3D](#) (const [UniStgGrid3D](#) &grid)

Copy constructor.

- [UniStgGrid3D](#) (const [Real](#) &west_bndy_x, const [Real](#) &east_bndy_x, const int &num_cells_x, const [Real](#) &south_bndy_y, const [Real](#) &north_bndy_y, const int &num_cells_y, const [Real](#) &bottom_bndy_z, const [Real](#) &top_bndy_z, const int &num_cells_z, const [mtk::FieldNature](#) &nature=[mtk::SCALAR](#))

Construct a grid based on spatial discretization parameters.

- [~UniStgGrid3D](#) ()

Destructor.

- const [Real](#) * [discrete_domain_x](#) () const

Provides access to the grid spatial data.

- const [Real](#) * [discrete_domain_y](#) () const

Provides access to the grid spatial data.

- const [Real](#) * [discrete_domain_z](#) () const

Provides access to the grid spatial data.

- [Real](#) * [discrete_field](#) ()

Provides access to the grid field data.

- [FieldNature](#) nature () const

Physical nature of the data bound to the grid.

- [Real](#) west_bndy () const

Provides access to west boundary spatial coordinate.

- [Real](#) east_bndy () const

Provides access to east boundary spatial coordinate.

- int num_cells_x () const

Provides access to the number of cells of the grid.

- [Real](#) delta_x () const

Provides access to the computed Δx .

- [Real](#) south_bndy () const

Provides access to south boundary spatial coordinate.

- [Real](#) north_bndy () const

Provides access to north boundary spatial coordinate.

- int num_cells_y () const

Provides access to the number of cells of the grid.

- [Real](#) delta_y () const

Provides access to the computed Δy .

- [Real](#) bottom_bndy () const

Provides access to bottom boundary spatial coordinate.

- [Real](#) top_bndy () const

Provides access to top boundary spatial coordinate.

- int num_cells_z () const

Provides access to the number of cells of the grid.

- [Real](#) delta_z () const

Provides access to the computed Δz .

- bool Bound () const

Have any field been bound to the grid?

- int [Size](#) () const
Total number of samples in the grid.
- void [BindScalarField](#) ([Real](#)(*ScalarField)(const [Real](#) &xx, const [Real](#) &yy, const [Real](#) &zz))
Binds a given scalar field to the grid.
- void [BindVectorField](#) ([Real](#)(*VectorFieldPComponent)(const [Real](#) &xx, const [Real](#) &yy, const [Real](#) &zz), [Real](#)(*VectorFieldQComponent)(const [Real](#) &xx, const [Real](#) &yy, const [Real](#) &zz), [Real](#)(*VectorFieldRComponent)(const [Real](#) &xx, const [Real](#) &yy, const [Real](#) &zz))
Binds a given vector field to the grid.
- bool [WriteToFile](#) (std::string filename, std::string space_name_x, std::string space_name_y, std::string space_name_z, std::string field_name) const
Writes grid to a file compatible with Gnuplot 4.6.

Private Member Functions

- void [BindVectorFieldPComponent](#) ([Real](#)(*VectorFieldPComponent)(const [Real](#) &xx, const [Real](#) &yy, const [Real](#) &zz))
Binds a given component of a vector field to the grid.
- void [BindVectorFieldQComponent](#) ([Real](#)(*VectorFieldQComponent)(const [Real](#) &xx, const [Real](#) &yy, const [Real](#) &zz))
Binds a given component of a vector field to the grid.
- void [BindVectorFieldRComponent](#) ([Real](#)(*VectorFieldRComponent)(const [Real](#) &xx, const [Real](#) &yy, const [Real](#) &zz))
Binds a given component of a vector field to the grid.

Private Attributes

- std::vector< [Real](#) > [discrete_domain_x_](#)
Array of spatial data.
- std::vector< [Real](#) > [discrete_domain_y_](#)
Array of spatial data.
- std::vector< [Real](#) > [discrete_domain_z_](#)
Array of spatial data.
- std::vector< [Real](#) > [discrete_field_](#)
Array of field's data.
- [FieldNature](#) [nature_](#)
Nature of the discrete field.
- [Real](#) [west_bndy_](#)
West boundary spatial coordinate.
- [Real](#) [east_bndy_](#)
East boundary spatial coordinate.
- int [num_cells_x_](#)
Number of cells discretizing the domain.
- [Real](#) [delta_x_](#)
Computed Δx .
- [Real](#) [south_bndy_](#)
West boundary spatial coordinate.
- [Real](#) [north_bndy_](#)

- East boundary spatial coordinate.*
- int [num_cells_y_](#)
Number of cells discretizing the domain.
- [Real delta_y_](#)
Computed Δy .
- [Real bottom_bndy_](#)
Bottom boundary spatial coordinate.
- [Real top_bndy_](#)
Top boundary spatial coordinate.
- int [num_cells_z_](#)
Number of cells discretizing the domain.
- [Real delta_z_](#)
Computed Δz .

Friends

- std::ostream & [operator<<](#) (std::ostream &stream, [UniStgGrid3D](#) &in)
Prints the grid as a tuple of arrays.

16.25.1 Detailed Description

Uniform 3D Staggered Grid.

Definition at line 79 of file [mtk_uni_stg_grid_3d.h](#).

16.25.2 Constructor & Destructor Documentation

16.25.2.1 mtk::UniStgGrid3D::UniStgGrid3D ()

Definition at line 123 of file [mtk_uni_stg_grid_3d.cc](#).

16.25.2.2 mtk::UniStgGrid3D::UniStgGrid3D (const UniStgGrid3D &grid)

Parameters

in	grid	Given grid.
--------------------	----------------------	-------------

Definition at line 142 of file [mtk_uni_stg_grid_3d.cc](#).

16.25.2.3 mtk::UniStgGrid3D::UniStgGrid3D (const Real &west_bndy_x, const Real &east_bndy_x, const int &num_cells_x, const Real &south_bndy_y, const Real &north_bndy_y, const int &num_cells_y, const Real &bottom_bndy_z, const Real &top_bndy_z, const int &num_cells_z, const mtk::FieldNature &nature = mtk::SCALAR)

Parameters

in	<i>west_bndy_x</i>	Coordinate for the west boundary.
in	<i>east_bndy_x</i>	Coordinate for the east boundary.
in	<i>num_cells_x</i>	Number of cells of the required grid.
in	<i>south_bndy_y</i>	Coordinate for the west boundary.
in	<i>north_bndy_y</i>	Coordinate for the east boundary.
in	<i>num_cells_y</i>	Number of cells of the required grid.
in	<i>bottom_bndy_z</i>	Coordinate for the bottom boundary.
in	<i>top_bndy_z</i>	Coordinate for the top boundary.
in	<i>num_cells_z</i>	Number of cells of the required grid.
in	<i>nature</i>	Nature of the discrete field to hold.

See also

[mtk::FieldNature](#)

Definition at line 174 of file [mtk_uni_stg_grid_3d.cc](#).

Here is the call graph for this function:



16.25.2.4 mtk::UniStgGrid3D::~~UniStgGrid3D ()

Definition at line 221 of file [mtk_uni_stg_grid_3d.cc](#).

16.25.3 Member Function Documentation

16.25.3.1 void mtk::UniStgGrid3D::BindScalarField (Real(*) (const Real &xx, const Real &yy, const Real &zz) *ScalarField*)


Parameters

in	<i>ScalarField</i>	Pointer to the function implementing the scalar field.
----	--------------------	--

1. Create collection of spatial coordinates for x .
2. Create collection of spatial coordinates for y .
3. Create collection of spatial coordinates for z .
4. Create collection of field samples.

Definition at line 318 of file [mtk_uni_stg_grid_3d.cc](#).

Here is the call graph for this function:



16.25.3.2 void mtk::UniStgGrid3D::BindVectorField (Real(*) (const Real &xx, const Real &yy, const Real &zz) VectorFieldPComponent, Real(*) (const Real &xx, const Real &yy, const Real &zz) VectorFieldQComponent, Real(*) (const Real &xx, const Real &yy, const Real &zz) VectorFieldRComponent)

We assume the field to be of the form:


$$\mathbf{v}(\mathbf{x}) = p(x, y, z)\hat{\mathbf{i}} + q(x, y, z)\hat{\mathbf{j}} + r(x, y, z)\hat{\mathbf{k}}$$

Parameters

in	<i>VectorFieldPComponent</i>	Pointer to the function implementing the \$ p \$ component of the vector field.
in	<i>VectorFieldQComponent</i>	Pointer to the function implementing the \$ q \$ component of the vector field.
in	<i>VectorFieldRComponent</i>	Pointer to the function implementing the \$ r \$ component of the vector field.

Definition at line 414 of file [mtk_uni_stg_grid_3d.cc](#).

Here is the call graph for this function:



16.25.3.3 void mtk::UniStgGrid3D::BindVectorFieldPComponent (Real(*) (const Real &xx, const Real &yy, const Real &zz) VectorFieldPComponent) [private]

We assume the field to be of the form:

$$\mathbf{v}(\mathbf{x}) = p(x, y, z)\hat{\mathbf{i}} + q(x, y, z)\hat{\mathbf{j}} + r(x, y, z)\hat{\mathbf{k}}$$

Parameters

in	<i>BindVectorFieldPComponent</i>	Pointer to the function implementing the \$ p \$ component of the vector field.
----	----------------------------------	---

Definition at line 393 of file [mtk_uni_stg_grid_3d.cc](#).

16.25.3.4 void mtk::UniStgGrid3D::BindVectorFieldQComponent (Real(*) (const Real &xx, const Real &yy, const Real &zz) VectorFieldQComponent) [private]

We assume the field to be of the form:

$$\mathbf{v}(\mathbf{x}) = p(x, y, z)\hat{\mathbf{i}} + q(x, y, z)\hat{\mathbf{j}} + r(x, y, z)\hat{\mathbf{k}}$$

Parameters

in	<i>BindVectorFieldQComponent</i>	Pointer to the function implementing the \$ q \$ component of the vector field.
----	----------------------------------	---

Definition at line 400 of file [mtk_uni_stg_grid_3d.cc](#).

16.25.3.5 void mtk::UniStgGrid3D::BindVectorFieldRComponent (Real(*) (const Real &xx, const Real &yy, const Real &zz) VectorFieldRComponent) [private]

We assume the field to be of the form:

$$\mathbf{v}(\mathbf{x}) = p(x, y, z)\hat{\mathbf{i}} + q(x, y, z)\hat{\mathbf{j}} + r(x, y, z)\hat{\mathbf{k}}$$

Parameters

in	<i>BindVectorFieldRComponent</i>	Pointer to the function implementing the \$ r \$ component of the vector field.
----	----------------------------------	---

Definition at line 407 of file [mtk_uni_stg_grid_3d.cc](#).


16.25.3.6 mtk::Real mtk::UniStgGrid3D::bottom_bndy () const

Returns

Bottom boundary spatial coordinate.

Definition at line 278 of file [mtk_uni_stg_grid_3d.cc](#).

Here is the caller graph for this function:



16.25.3.7 `bool mtk::UniStgGrid3D::Bound () const`

Returns

True is a field has been bound.

Definition at line 308 of file [mtk_uni_stg_grid_3d.cc](#).

16.25.3.8 `mtk::Real mtk::UniStgGrid3D::delta_x () const`

Returns

Computed Δx .

Definition at line 243 of file [mtk_uni_stg_grid_3d.cc](#).

16.25.3.9 `mtk::Real mtk::UniStgGrid3D::delta_y () const`

Returns

Computed Δy .

Definition at line 268 of file [mtk_uni_stg_grid_3d.cc](#).

16.25.3.10 `mtk::Real mtk::UniStgGrid3D::delta_z () const`

Returns

Computed Δz .

Definition at line 293 of file [mtk_uni_stg_grid_3d.cc](#).

16.25.3.11 `const mtk::Real * mtk::UniStgGrid3D::discrete_domain_x () const`

Returns

Pointer to the spatial data.

Todo Review const-correctness of the pointer we return.

Definition at line 248 of file [mtk_uni_stg_grid_3d.cc](#).

16.25.3.12 `const mtk::Real * mtk::UniStgGrid3D::discrete_domain_y () const`

Returns

Pointer to the spatial data.

Todo Review const-correctness of the pointer we return.

Definition at line 273 of file [mtk_uni_stg_grid_3d.cc](#).

16.25.3.13 `const mtk::Real * mtk::UniStgGrid3D::discrete_domain_z () const`

Returns

Pointer to the spatial data.

Todo Review const-correctness of the pointer we return.

Definition at line 298 of file [mtk_uni_stg_grid_3d.cc](#).

16.25.3.14 `mtk::Real * mtk::UniStgGrid3D::discrete_field ()`

Returns

Pointer to the field data.

Definition at line 303 of file [mtk_uni_stg_grid_3d.cc](#).


16.25.3.15 `mtk::Real mtk::UniStgGrid3D::east_bndy () const`

Returns

East boundary spatial coordinate.

Definition at line 233 of file [mtk_uni_stg_grid_3d.cc](#).

Here is the caller graph for this function:



16.25.3.16 `mtk::FieldNature mtk::UniStgGrid3D::nature () const`

Returns

Value of an enumeration.

See also

[mtk::FieldNature](#)

Definition at line 223 of file [mtk_uni_stg_grid_3d.cc](#).

16.25.3.17 `mtk::Real mtk::UniStgGrid3D::north_bndy () const`

Returns

North boundary spatial coordinate.

Definition at line 258 of file [mtk_uni_stg_grid_3d.cc](#).


16.25.3.18 `int mtk::UniStgGrid3D::num_cells_x () const`

Returns

Number of cells of the grid.

Definition at line 238 of file [mtk_uni_stg_grid_3d.cc](#).

Here is the caller graph for this function:




16.25.3.19 `int mtk::UniStgGrid3D::num_cells_y () const`

Returns

Number of cells of the grid.

Definition at line 263 of file [mtk_uni_stg_grid_3d.cc](#).

Here is the caller graph for this function:




16.25.3.20 `int mtk::UniStgGrid3D::num_cells_z () const`

Returns

Number of cells of the grid.

Definition at line 288 of file [mtk_uni_stg_grid_3d.cc](#).

Here is the caller graph for this function:



16.25.3.21 `mtk::UniStgGrid3D mtk::UniStgGrid3D::operator= (const UniStgGrid3D & in)`

Parameters

<code>in</code>	<code>in</code>	Given grid.
-----------------	-----------------	-------------

Returns

Copy of the given grid.

Definition at line 116 of file [mtk_uni_stg_grid_3d.cc](#).

16.25.3.22 `int mtk::UniStgGrid3D::Size () const`

Returns

Total number of samples in the grid.

Definition at line 313 of file [mtk_uni_stg_grid_3d.cc](#).


16.25.3.23 `mtk::Real mtk::UniStgGrid3D::south_bndy () const`

Returns

South boundary spatial coordinate.

Definition at line 253 of file [mtk_uni_stg_grid_3d.cc](#).

Here is the caller graph for this function:




16.25.3.24 `mtk::Real mtk::UniStgGrid3D::top_bndy () const`

Returns

Top boundary spatial coordinate.

Definition at line 283 of file [mtk_uni_stg_grid_3d.cc](#).

Here is the caller graph for this function:




16.25.3.25 `mtk::Real mtk::UniStgGrid3D::west_bndy () const`

Returns

West boundary spatial coordinate.

Definition at line 228 of file [mtk_uni_stg_grid_3d.cc](#).

Here is the caller graph for this function:



16.25.3.26 `bool mtk::UniStgGrid3D::WriteToFile (std::string filename, std::string space_name_x, std::string space_name_y, std::string space_name_z, std::string field_name) const`

Parameters

in	<i>filename</i>	Name of the output file.
in	<i>space_name_x</i>	Name for the first column of the (spatial) data.
in	<i>space_name_y</i>	Name for the second column of the (spatial) data.
in	<i>space_name_z</i>	Name for the third column of the (spatial) data.
in	<i>field_name</i>	Name for the second column of the (physical field) data.

Returns

Success of the file writing process.

See also

<http://www.gnuplot.info/>

Definition at line 433 of file [mtk_uni_stg_grid_3d.cc](#).

16.25.4 Friends And Related Function Documentation

16.25.4.1 `std::ostream& operator<< (std::ostream & stream, mtk::UniStgGrid3D & in)` [friend]

1. Print spatial coordinates.
2. Print scalar field.

Definition at line 67 of file [mtk_uni_stg_grid_3d.cc](#).

16.25.5 Member Data Documentation

16.25.5.1 `Real mtk::UniStgGrid3D::bottom_bndy_` [private]

Definition at line 396 of file [mtk_uni_stg_grid_3d.h](#).

16.25.5.2 `Real mtk::UniStgGrid3D::delta_x_` [private]

Definition at line 389 of file [mtk_uni_stg_grid_3d.h](#).

16.25.5.3 `Real mtk::UniStgGrid3D::delta_y_` [private]

Definition at line 394 of file [mtk_uni_stg_grid_3d.h](#).

16.25.5.4 `Real mtk::UniStgGrid3D::delta_z_` [private]

Definition at line 399 of file [mtk_uni_stg_grid_3d.h](#).

16.25.5.5 `std::vector<Real> mtk::UniStgGrid3D::discrete_domain_x_` [private]

Definition at line 379 of file [mtk_uni_stg_grid_3d.h](#).

16.25.5.6 `std::vector<Real> mtk::UniStgGrid3D::discrete_domain_y_` [private]

Definition at line 380 of file [mtk_uni_stg_grid_3d.h](#).

16.25.5.7 `std::vector<Real> mtk::UniStgGrid3D::discrete_domain_z_` [private]

Definition at line 381 of file [mtk_uni_stg_grid_3d.h](#).

16.25.5.8 `std::vector<Real> mtk::UniStgGrid3D::discrete_field_` [private]

Definition at line 382 of file [mtk_uni_stg_grid_3d.h](#).

16.25.5.9 `Real mtk::UniStgGrid3D::east_bndy_` [private]

Definition at line 387 of file [mtk_uni_stg_grid_3d.h](#).

16.25.5.10 `FieldNature mtk::UniStgGrid3D::nature_` [private]

Definition at line 384 of file [mtk_uni_stg_grid_3d.h](#).

16.25.5.11 `Real mtk::UniStgGrid3D::north_bndy_` [private]

Definition at line 392 of file [mtk_uni_stg_grid_3d.h](#).

16.25.5.12 `int mtk::UniStgGrid3D::num_cells_x_` [private]

Definition at line 388 of file [mtk_uni_stg_grid_3d.h](#).

16.25.5.13 `int mtk::UniStgGrid3D::num_cells_y_` [private]

Definition at line 393 of file [mtk_uni_stg_grid_3d.h](#).

16.25.5.14 `int mtk::UniStgGrid3D::num_cells_z_` [private]

Definition at line 398 of file [mtk_uni_stg_grid_3d.h](#).

16.25.5.15 `Real mtk::UniStgGrid3D::south_bndy_` [private]

Definition at line 391 of file [mtk_uni_stg_grid_3d.h](#).

16.25.5.16 `Real mtk::UniStgGrid3D::top_bndy_` [private]

Definition at line 397 of file [mtk_uni_stg_grid_3d.h](#).

16.25.5.17 `Real mtk::UniStgGrid3D::west_bndy_` [private]

Definition at line 386 of file [mtk_uni_stg_grid_3d.h](#).

The documentation for this class was generated from the following files:

- [include/mtk_uni_stg_grid_3d.h](#)
- [src/mtk_uni_stg_grid_3d.cc](#)

Chapter 17


File Documentation

17.1 examples/curl_2d_angular_velocity/curl_2d_angular_velocity.cc File Reference

Compute the curl of a 2D angular velocity field.

```
#include <iostream>
```

Include dependency graph for curl_2d_angular_velocity.cc:



Functions

- int `main` ()

17.1.1 Detailed Description

We compute the curl of:

$$\mathbf{v}(x,y) = -y\hat{\mathbf{i}} + x\hat{\mathbf{j}}.$$

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [curl_2d_angular_velocity.cc](#).

17.1.2 Function Documentation**17.1.2.1 int main ()**

Definition at line 106 of file [curl_2d_angular_velocity.cc](#).

17.2 curl_2d_angular_velocity.cc

```
00001
00013 /*
00014 Copyright (C) 2015, Computational Science Research Center, San Diego State
00015 University. All rights reserved.
00016
00017 Redistribution and use in source and binary forms, with or without modification,
00018 are permitted provided that the following conditions are met:
00019
00020 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00021 and a copy of the modified files should be reported once modifications are
00022 completed, unless these modifications are made through the project's GitHub
00023 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00024 should be developed and included in any deliverable.
00025
00026 2. Redistributions of source code must be done through direct
00027 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00028
00029 3. Redistributions in binary form must reproduce the above copyright notice,
00030 this list of conditions and the following disclaimer in the documentation and/or
00031 other materials provided with the distribution.
00032
00033 4. Usage of the binary form on proprietary applications shall require explicit
00034 prior written permission from the the copyright holders, and due credit should
00035 be given to the copyright holders.
00036
00037 5. Neither the name of the copyright holder nor the names of its contributors
00038 may be used to endorse or promote products derived from this software without
00039 specific prior written permission.
00040
00041 The copyright holders provide no reassurances that the source code provided does
00042 not infringe any patent, copyright, or any other intellectual property rights of
00043 third parties. The copyright holders disclaim any liability to any recipient for
00044 claims brought against recipient by any third party for infringement of that
00045 parties intellectual property rights.
00046
00047 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00048 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00049 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00050 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00051 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00052 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00053 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00054 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00055 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00056 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00057 */
00058
00059 #if __cplusplus == 201103L
00060
00061 #include <iostream>
00062 #include <fstream>
00063 #include <cmath>
00064
00065 #include <vector>
00066
00067 #include "mtk.h"
00068
```

```

00069 mtk::Real VectorFieldPComponent(const mtk::Real &xx, const
    mtk::Real &yy) {
00070
00071     return -yy;
00072 }
00073
00074 mtk::Real VectorFieldQComponent(const mtk::Real &xx, const
    mtk::Real &yy) {
00075
00076     return xx;
00077 }
00078
00079 int main () {
00080
00081     std::cout << "Example: Curl of a angular velocity field." << std::endl;
00082
00083     mtk::Real aa = 0.0;
00084     mtk::Real bb = 4.0;
00085     mtk::Real cc = 0.0;
00086     mtk::Real dd = 4.0;
00087
00088     int nn = 10;
00089     int mm = 10;
00090
00091     mtk::UniStgGrid2D gg(aa, bb, nn, cc, dd, mm, mtk::VECTOR);
00092
00093     gg.BindVectorField(VectorFieldPComponent, VectorFieldQComponent);
00094
00095     if(!gg.WriteToFile("curl_2d_angular_velocity_gg.dat", "x", "y", "v(x,y)")) {
00096         std::cerr << "Angular field could not be written to disk." << std::endl;
00097         return EXIT_FAILURE;
00098     }
00099 }
00100
00101 #else
00102 #include <iostream>
00103 using std::cout;
00104 using std::endl;
00105 int main () {
00106     cout << "This code HAS to be compiled with support for C++11." << endl;
00107     cout << "Exiting..." << endl;
00108     return EXIT_SUCCESS;
00109 }
00110 #endif


```

17.3 examples/diffusion_3d/diffusion_3d.cc File Reference

Diffusion Equation on a 3D Uniform Staggered Grid with Dirichlet BCs.

```
#include <iostream>
```

Include dependency graph for diffusion_3d.cc:



Functions

- `int main ()`

17.3.1 Detailed Description

We solve:

$$\frac{\partial u}{\partial t} = \nabla^2 u(\mathbf{x}),$$

for $\mathbf{x} \in \Omega = [0, 1]^3$.

We consider autonomous homogeneous Dirichlet boundary conditions.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [diffusion_3d.cc](#).

17.3.2 Function Documentation

17.3.2.1 `int main ()`

Definition at line 122 of file [diffusion_3d.cc](#).

17.4 `diffusion_3d.cc`

```

00001
00016 /*
00017 Copyright (C) 2015, Computational Science Research Center, San Diego State
00018 University. All rights reserved.
00019
00020 Redistribution and use in source and binary forms, with or without modification,
00021 are permitted provided that the following conditions are met:
00022
00023 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00024 and a copy of the modified files should be reported once modifications are
00025 completed, unless these modifications are made through the project's GitHub
00026 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00027 should be developed and included in any deliverable.
00028
00029 2. Redistributions of source code must be done through direct
00030 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00031
00032 3. Redistributions in binary form must reproduce the above copyright notice,
00033 this list of conditions and the following disclaimer in the documentation and/or
00034 other materials provided with the distribution.
00035
00036 4. Usage of the binary form on proprietary applications shall require explicit
00037 prior written permission from the the copyright holders, and due credit should
00038 be given to the copyright holders.
00039
00040 5. Neither the name of the copyright holder nor the names of its contributors
00041 may be used to endorse or promote products derived from this software without
00042 specific prior written permission.
00043
00044 The copyright holders provide no reassurances that the source code provided does
00045 not infringe any patent, copyright, or any other intellectual property rights of
00046 third parties. The copyright holders disclaim any liability to any recipient for
00047 claims brought against recipient by any third party for infringement of that
00048 parties intellectual property rights.
00049
00050 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND

```

```

00051 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00052 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00053 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00054 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00055 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00056 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00057 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00058 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00059 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00060 */
00061
00062 #if __cplusplus == 201103L
00063
00064 #include <iostream>
00065 #include <fstream>
00066 #include <cmath>
00067
00068 #include <vector>
00069
00070 #include "mtk.h"
00071
00072 mtk::Real InitialCondition(const mtk::Real &xx,
00073                           const mtk::Real &yy,
00074                           const mtk::Real &zz) {
00075
00076     mtk::Real rr{0.3};
00077
00078     mtk::Real aux{xx*xx + yy*yy + zz*zz};
00079
00080     return (aux < rr? rr - aux: mtk::kZero);
00081 }
00082
00083 int main () {
00084
00085     std::cout << "Example: Diffusion Equation in 3D "
00086               << "with Dirichlet BCs." << std::endl;
00087
00088     mtk::Real west_bndy_x{0.0};
00089     mtk::Real east_bndy_x{1.0};
00090     mtk::Real south_bndy_y{0.0};
00091     mtk::Real north_bndy_y{1.0};
00092     mtk::Real bottom_bndy_z{0.0};
00093     mtk::Real top_bndy_z{1.0};
00094
00095     int num_cells_x{50};
00096     int num_cells_y{50};
00097     int num_cells_z{50};
00098
00099     mtk::UniStgGrid3D comp_sol(west_bndy_x, east_bndy_x, num_cells_x,
00100                               south_bndy_y, north_bndy_y, num_cells_y,
00101                               bottom_bndy_z, top_bndy_z, num_cells_z);
00102
00103     comp_sol.BindScalarField(InitialCondition);
00104
00105     if(!comp_sol.WriteToFile("diffusion_3d_comp_sol.dat",
00106                             "x",
00107                             "y",
00108                             "z",
00109                             "Initial u(x,y,z)")) {
00110         std::cerr << "Error writing to file." << std::endl;
00111     }
00112 }
00113
00114 #else
00115 #include <iostream>
00116 using std::cout;
00117 using std::endl;
00118 int main () {
00119     cout << "This code HAS to be compiled with support for C++11." << endl;
00120     cout << "Exiting..." << endl;
00121     return EXIT_SUCCESS;
00122 }
00123 #endif


```

17.5 examples/minimalistic_poisson_1d/minimalistic_poisson_1d.cc File Reference

Poisson Equation on a 1D Uniform Staggered Grid with Robin BCs.

```
#include <iostream>
```

Include dependency graph for minimalistic_poisson_1d.cc:



Functions

- int [main](#) ()

17.5.1 Detailed Description

We solve:

$$-\nabla^2 p(x) = s(x),$$

for $x \in \Omega = [a, b] = [0, 1]$.

The source term function is defined as:

$$s(x) = -\frac{\lambda^2 \exp(\lambda x)}{\exp(\lambda) - 1},$$

where $\lambda = -1$ is a real-valued parameter.

We consider Robin's boundary conditions of the form:

$$\alpha p(a) - \beta p'(a) = \omega,$$

$$\alpha p(b) + \beta p'(b) = \varepsilon,$$

where $\alpha = -\exp(\lambda)$, $\beta = (\exp(\lambda) - 1.0)/\lambda$, $\omega = -1$, and $\varepsilon = 0$.

The analytical solution for this problem is given by:

$$p(x) = \frac{\exp(\lambda x) - 1}{\exp(\lambda) - 1}.$$

The mimetic counterpart of this equation is:

$$-\check{\mathbf{L}}_x^k \tilde{p} = \tilde{s}.$$

Finally, we will solve this problem considering $k = 2$.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [minimalistic_poisson_1d.cc](#).

17.5.2 Function Documentation**17.5.2.1 int main ()**

Definition at line 164 of file [minimalistic_poisson_1d.cc](#).

17.6 minimalistic_poisson_1d.cc

```

00001
00043 /*
00044 Copyright (C) 2015, Computational Science Research Center, San Diego State
00045 University. All rights reserved.
00046
00047 Redistribution and use in source and binary forms, with or without modification,
00048 are permitted provided that the following conditions are met:
00049
00050 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00051 and a copy of the modified files should be reported once modifications are
00052 completed, unless these modifications are made through the project's GitHub
00053 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00054 should be developed and included in any deliverable.
00055
00056 2. Redistributions of source code must be done through direct
00057 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00058
00059 3. Redistributions in binary form must reproduce the above copyright notice,
00060 this list of conditions and the following disclaimer in the documentation and/or
00061 other materials provided with the distribution.
00062
00063 4. Usage of the binary form on proprietary applications shall require explicit
00064 prior written permission from the the copyright holders, and due credit should
00065 be given to the copyright holders.
00066
00067 5. Neither the name of the copyright holder nor the names of its contributors
00068 may be used to endorse or promote products derived from this software without
00069 specific prior written permission.
00070
00071 The copyright holders provide no reassurances that the source code provided does
00072 not infringe any patent, copyright, or any other intellectual property rights of
00073 third parties. The copyright holders disclaim any liability to any recipient for
00074 claims brought against recipient by any third party for infringement of that
00075 parties intellectual property rights.
00076
00077 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00078 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00079 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00080 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00081 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00082 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00083 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00084 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00085 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00086 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00087 */
00088
00089 #if __cplusplus == 201103L
00090
00091 #include <iostream>
00092 #include <fstream>
00093 #include <cmath>
00094 #include <vector>
00095
00096 #include "mtk.h"
00097
00098 mtk::Real Alpha(const mtk::Real &tt) {

```

```

00099     mtk::Real lambda = -1.0;
00100     return -exp(lambda);
00101 }
00102
00103 mtk::Real Beta(const mtk::Real &tt) {
00104     mtk::Real lambda = -1.0;
00105     return (exp(lambda) - 1.0)/lambda;
00106 };
00107
00108 mtk::Real Omega(const mtk::Real &tt) { return -1.0; };
00109
00110 mtk::Real Epsilon(const mtk::Real &tt) { return 0.0; };
00111
00112 mtk::Real Source(const mtk::Real &xx) {
00113     mtk::Real lambda = -1.0;
00114     return lambda*lambda*exp(lambda*xx)/(exp(lambda) - 1.0);
00115 }
00116
00117 mtk::Real KnownSolution(const mtk::Real &xx) {
00118     mtk::Real lambda = -1.0;
00119     return (exp(lambda*xx) - 1.0)/(exp(lambda) - 1.0);
00120 }
00121
00122 int main () {
00123
00124     mtk::Real west_bndy_x{};
00125     mtk::Real east_bndy_x{1.0};
00126     int num_cells_x{5};
00127     mtk::LaplD lap;
00128     if (!lap.ConstructLaplD()) {
00129         return EXIT_FAILURE;
00130     }
00131     mtk::UniStgGrid1D source(west_bndy_x, east_bndy_x, num_cells_x);
00132     mtk::UniStgGrid1D comp_sol(west_bndy_x, east_bndy_x, num_cells_x);
00133     mtk::UniStgGrid1D known_sol(west_bndy_x, east_bndy_x, num_cells_x);
00134     mtk::DenseMatrix lapm(lap.ReturnAsDenseMatrix(comp_sol));
00135     source.BindScalarField(Source);
00136     mtk::RobinBCDescriptor1D bcs;
00137     bcs.PushBackWestCoeff(Alpha);
00138     bcs.PushBackWestCoeff(Beta);
00139     bcs.PushBackEastCoeff(Alpha);
00140     bcs.PushBackEastCoeff(Beta);
00141     bcs.set_west_condition(Omega);
00142     bcs.set_east_condition(Epsilon);
00143     if (!bcs.ImposeOnLaplacianMatrix(lap, lapm)) {
00144         return EXIT_FAILURE;
00145     }
00146     bcs.ImposeOnGrid(source);
00147     int info{mtk::LAPACKAdapter::SolveDenseSystem(lapm, source)};
00148     if (info != 0) {
00149         return EXIT_FAILURE;
00150     }
00151     source.WriteToFile("minimalistic_poisson_1d_comp_sol.dat", "x", "~u(x)");
00152     known_sol.BindScalarField(KnownSolution);
00153     known_sol.WriteToFile("minimalistic_poisson_1d_known_sol.dat", "x", "u(x)");
00154     mtk::Real relative_norm_2_error =
00155         mtk::BLASAdapter::RelNorm2Error(source.discrete_field(),
00156                                         known_sol.discrete_field(),
00157                                         known_sol.num_cells_x());
00158     std::cout << relative_norm_2_error << std::endl;
00159 }
00160 #else
00161 #include <iostream>
00162 using std::cout;
00163 using std::endl;
00164 int main () {
00165     cout << "This code HAS to be compiled with support for C++11." << endl;
00166     cout << "Exiting..." << endl;
00167     return EXIT_SUCCESS;
00168 }
00169 #endif


```

17.7 examples/poisson_1d/poisson_1d.cc File Reference

Poisson Equation on a 1D Uniform Staggered Grid with Robin BCs.

```
#include <iostream>
```

Include dependency graph for poisson_1d.cc:



Functions

- int [main](#) ()

17.7.1 Detailed Description

We solve:

$$-\nabla^2 p(x) = s(x),$$

for $x \in \Omega = [a, b] = [0, 1]$.

The source term function is defined as:

$$s(x) = -\frac{\lambda^2 \exp(\lambda x)}{\exp(\lambda) - 1},$$

where $\lambda = -1$ is a real-valued parameter.

We consider Robin's boundary conditions of the form:

$$\alpha p(a) - \beta p'(a) = \omega,$$

$$\alpha p(b) + \beta p'(b) = \varepsilon,$$

where $\alpha = -\exp(\lambda)$, $\beta = (\exp(\lambda) - 1.0)/\lambda$, $\omega = -1$, and $\varepsilon = 0$.

The analytical solution for this problem is given by:

$$p(x) = \frac{\exp(\lambda x) - 1}{\exp(\lambda) - 1}.$$

The mimetic counterpart of this equation is:

$$-\check{\mathbf{L}}_x^k \tilde{p} = \tilde{s}.$$

Finally, we will solve this problem considering $k = 2$.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [poisson_1d.cc](#).

17.7.2 Function Documentation

17.7.2.1 `int main ()`

Definition at line 263 of file [poisson_1d.cc](#).

17.8 `poisson_1d.cc`

```

00001
00043 /*
00044 Copyright (C) 2015, Computational Science Research Center, San Diego State
00045 University. All rights reserved.
00046
00047 Redistribution and use in source and binary forms, with or without modification,
00048 are permitted provided that the following conditions are met:
00049
00050 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00051 and a copy of the modified files should be reported once modifications are
00052 completed, unless these modifications are made through the project's GitHub
00053 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00054 should be developed and included in any deliverable.
00055
00056 2. Redistributions of source code must be done through direct
00057 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00058
00059 3. Redistributions in binary form must reproduce the above copyright notice,
00060 this list of conditions and the following disclaimer in the documentation and/or
00061 other materials provided with the distribution.
00062
00063 4. Usage of the binary form on proprietary applications shall require explicit
00064 prior written permission from the the copyright holders, and due credit should
00065 be given to the copyright holders.
00066
00067 5. Neither the name of the copyright holder nor the names of its contributors
00068 may be used to endorse or promote products derived from this software without
00069 specific prior written permission.
00070
00071 The copyright holders provide no reassurances that the source code provided does
00072 not infringe any patent, copyright, or any other intellectual property rights of
00073 third parties. The copyright holders disclaim any liability to any recipient for
00074 claims brought against recipient by any third party for infringement of that
00075 parties intellectual property rights.
00076
00077 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00078 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00079 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00080 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00081 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00082 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00083 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00084 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00085 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00086 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00087 */
00088
00089 #if __cplusplus == 201103L
00090
00091 #include <iostream>
00092 #include <fstream>
00093 #include <cmath>
00094
00095 #include <vector>
00096
00097 #include "mtk.h"
00098
00099 mtk::Real Alpha(const mtk::Real &tt) {
00100
00101     mtk::Real lambda{-1.0};
00102
00103     return -exp(lambda);
00104 }
00105
00106 mtk::Real Beta(const mtk::Real &tt) {
00107
00108     mtk::Real lambda{-1.0};

```

```

00109
00110     return (exp(lambda) - 1.0)/lambda;
00111 };
00112
00113 mtk::Real Omega(const mtk::Real &tt) {
00114
00115     return -1.0;
00116 };
00117
00118 mtk::Real Epsilon(const mtk::Real &tt) {
00119
00120     return 0.0;
00121 };
00122
00123 mtk::Real Source(const mtk::Real &xx) {
00124
00125     mtk::Real lambda{-1.0};
00126
00127     return -lambda*lambda*exp(lambda*xx)/(exp(lambda) - 1.0);
00128 }
00129
00130 mtk::Real KnownSolution(const mtk::Real &xx) {
00131
00132     mtk::Real lambda{-1.0};
00133
00134     return (exp(lambda*xx) - 1.0)/(exp(lambda) - 1.0);
00135 }
00136
00137 int main () {
00138
00139     std::cout << "Example: Poisson Equation with Robin BCs on a";
00140     std::cout << "1D Uniform Staggered Grid." << std::endl;
00141
00142     mtk::Real west_bndy_x{0.0};
00143     mtk::Real east_bndy_x{1.0};
00144     int num_cells_x{5};
00145
00146     mtk::UniStgGrid1D comp_sol(west_bndy_x, east_bndy_x, num_cells_x);
00147
00148     mtk::Lapl1D lap;
00149
00150     if (!lap.ConstructLapl1D()) {
00151         std::cerr << "Mimetic Laplacian could not be built." << std::endl;
00152         return EXIT_FAILURE;
00153     }
00154
00155     std::cout << "lap=" << std::endl;
00156     std::cout << lap << std::endl;
00157
00158     mtk::DenseMatrix lapm(lap.ReturnAsDenseMatrix(comp_sol));
00159
00160     std::cout << "lapm =" << std::endl;
00161     std::cout << lapm << std::endl;
00162
00163     lapm = mtk::BLASAdapter::RealDenseSM(-1.0, lapm);
00164
00165     std::cout << "-lapm =" << std::endl;
00166     std::cout << lapm << std::endl;
00167
00168     mtk::UniStgGrid1D source(west_bndy_x, east_bndy_x, num_cells_x);
00169
00170     source.BindScalarField(Source);
00171
00172     std::cout << "source =" << std::endl;
00173     std::cout << source << std::endl;
00174
00175     mtk::RobinBCDescriptor1D robin_bc_desc_ld;
00176
00177     robin_bc_desc_ld.PushBackWestCoeff(Alpha);
00178     robin_bc_desc_ld.PushBackWestCoeff(Beta);
00179
00180     robin_bc_desc_ld.PushBackEastCoeff(Alpha);
00181     robin_bc_desc_ld.PushBackEastCoeff(Beta);
00182
00183     robin_bc_desc_ld.set_west_condition(Omega);
00184     robin_bc_desc_ld.set_east_condition(Epsilon);
00185
00186     if (!robin_bc_desc_ld.ImposeOnLaplacianMatrix(lap, lapm)) {
00187         std::cerr << "BCs could not be bound to the matrix." << std::endl;
00188         return EXIT_FAILURE;
00189     }

```

```

00195     }
00196
00197     std::cout << "Mimetic Laplacian operator with imposed BCs:" << std::endl;
00198     std::cout << lapm << std::endl;
00199
00200     if (!lapm.WriteToFile("poisson_ld_lapm.dat")) {
00201         std::cerr << "Laplacian matrix could not be written to disk." << std::endl;
00202         return EXIT_FAILURE;
00203     }
00204
00205     robin_bc_desc_ld.ImposeOnGrid(source);
00206
00207
00208     std::cout << "source =" << std::endl;
00209     std::cout << source << std::endl;
00210
00211     if (!source.WriteToFile("poisson_ld_source.dat", "x", "s(x)")) {
00212         std::cerr << "Source term could not be written to disk." << std::endl;
00213         return EXIT_FAILURE;
00214     }
00215
00216     int info{mtk::LAPACKAdapter::SolveDenseSystem(lapm, source)};
00217
00218     if (!info) {
00219         std::cout << "System solved." << std::endl;
00220         std::cout << std::endl;
00221     } else {
00222         std::cerr << "Something wrong solving system! info = " << info << std::endl;
00223         std::cerr << "Exiting..." << std::endl;
00224         return EXIT_FAILURE;
00225     }
00226
00227     std::cout << "Computed solution:" << std::endl;
00228     std::cout << source << std::endl;
00229
00230     if (!source.WriteToFile("poisson_ld_comp_sol.dat", "x", "~u(x)")) {
00231         std::cerr << "Solution could not be written to file." << std::endl;
00232         return EXIT_FAILURE;
00233     }
00234
00235
00236     mtk::UniStgGrid1D known_sol(west_bndy_x, east_bndy_x, num_cells_x);
00237
00238     known_sol.BindScalarField(KnownSolution);
00239
00240     std::cout << "known_sol =" << std::endl;
00241     std::cout << known_sol << std::endl;
00242
00243     if (!known_sol.WriteToFile("poisson_ld_known_sol.dat", "x", "u(x)")) {
00244         std::cerr << "Known solution could not be written to file." << std::endl;
00245         return EXIT_FAILURE;
00246     }
00247
00248     mtk::Real relative_norm_2_error{};
00249
00250     relative_norm_2_error =
00251         mtk::BLASAdapter::RelNorm2Error(source.discrete_field(),
00252             known_sol.discrete_field(),
00253             known_sol.num_cells_x());
00254
00255     std::cout << "relative_norm_2_error = ";
00256     std::cout << relative_norm_2_error << std::endl;
00257
00258 }
00259 #else
00260 #include <iostream>
00261 using std::cout;
00262 using std::endl;
00263 int main () {
00264     cout << "This code HAS to be compiled with support for C++11." << endl;
00265     cout << "Exiting..." << endl;
00266     return EXIT_SUCCESS;
00267 }
00268 #endif


```

17.9 examples/poisson_2d/poisson_2d.cc File Reference

Poisson Equation on a 2D Uniform Staggered Grid with Robin BCs.

```
#include <iostream>
```

Include dependency graph for poisson_2d.cc:



Functions

- int [main](#) ()

17.9.1 Detailed Description

We solve:

$$\nabla^2 u(\mathbf{x}) = s(\mathbf{x}),$$

for $\mathbf{x} \in \Omega = [0, 1]^2$.

The source term function is defined as

$$s(x, y) = xye^{-0.5(x^2+y^2)}(x^2 + y^2 - 6).$$

Let $\partial\Omega = S \cup N \cup W \cup E$. We consider Dirichlet boundary conditions of the following form:

$$\forall \mathbf{x} \in W : u(\mathbf{x}) = 0.$$

$$\forall \mathbf{x} \in E : u(1, y) = -e^{-0.5(1-y^2)}(1 - y^2).$$

$$\forall \mathbf{x} \in S : u(\mathbf{x}) = 0.$$

$$\forall \mathbf{x} \in N : u(x, 1) = -e^{-0.5(x^2-1)}(x^2 - 1).$$

The analytical solution for this problem is given by

$$u(x, y) = xye^{-0.5(x^2+y^2)}.$$

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [poisson_2d.cc](#).

17.9.2 Function Documentation

17.9.2.1 `int main ()`

Definition at line 241 of file [poisson_2d.cc](#).

17.10 `poisson_2d.cc`

```

00001
00039 /*
00040 Copyright (C) 2015, Computational Science Research Center, San Diego State
00041 University. All rights reserved.
00042
00043 Redistribution and use in source and binary forms, with or without modification,
00044 are permitted provided that the following conditions are met:
00045
00046 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00047 and a copy of the modified files should be reported once modifications are
00048 completed, unless these modifications are made through the project's GitHub
00049 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00050 should be developed and included in any deliverable.
00051
00052 2. Redistributions of source code must be done through direct
00053 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00054
00055 3. Redistributions in binary form must reproduce the above copyright notice,
00056 this list of conditions and the following disclaimer in the documentation and/or
00057 other materials provided with the distribution.
00058
00059 4. Usage of the binary form on proprietary applications shall require explicit
00060 prior written permission from the the copyright holders, and due credit should
00061 be given to the copyright holders.
00062
00063 5. Neither the name of the copyright holder nor the names of its contributors
00064 may be used to endorse or promote products derived from this software without
00065 specific prior written permission.
00066
00067 The copyright holders provide no reassurances that the source code provided does
00068 not infringe any patent, copyright, or any other intellectual property rights of
00069 third parties. The copyright holders disclaim any liability to any recipient for
00070 claims brought against recipient by any third party for infringement of that
00071 parties intellectual property rights.
00072
00073 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00074 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00075 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00076 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00077 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00078 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00079 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00080 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00081 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00082 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00083 */
00084
00085 #if __cplusplus == 201103L
00086
00087 #include <iostream>
00088 #include <fstream>
00089 #include <cmath>
00090
00091 #include <vector>
00092
00093 #include "mtk.h"
00094
00095 mtk::Real Source(const mtk::Real &xx, const mtk::Real &yy) {
00096
00097     mtk::Real x_squared{xx*xx};
00098     mtk::Real y_squared{yy*yy};
00099     mtk::Real aux{-0.5*(x_squared + y_squared)};
00100
00101     return xx*yy*exp(aux)*(x_squared + y_squared - 6.0);
00102 }
00103
00104 mtk::Real BCCoeff(const mtk::Real &xx, const mtk::Real &yy) {

```



```

00105
00106     return mtk::kOne;
00107 }
00108
00109 mtk::Real WestBC(const mtk::Real &xx, const mtk::Real &tt) {
00110
00111     return mtk::kZero;
00112 }
00113
00114 mtk::Real EastBC(const mtk::Real &yy, const mtk::Real &tt) {
00115
00116     return yy*exp(-0.5*(mtk::kOne + yy*yy));
00117 }
00118
00119 mtk::Real SouthBC(const mtk::Real &xx, const mtk::Real &tt) {
00120
00121     return mtk::kZero;
00122 }
00123
00124 mtk::Real NorthBC(const mtk::Real &xx, const mtk::Real &tt) {
00125
00126     return xx*exp(-0.5*(xx*xx + mtk::kOne));
00127 }
00128
00129 mtk::Real KnownSolution(const mtk::Real &xx, const mtk::Real &yy) {
00130
00131     mtk::Real x_squared{xx*xx};
00132     mtk::Real y_squared{yy*yy};
00133     mtk::Real aux{-0.5*(x_squared + y_squared)};
00134
00135     return xx*yy*exp(aux);
00136 }
00137
00138 int main () {
00139
00140     std::cout << "Example: Poisson Equation on a 2D Uniform Staggered Grid ";
00141     std::cout << "with Dirichlet and Neumann BCs." << std::endl;
00142
00143     mtk::Real west_bndy_x{0.0};
00144     mtk::Real east_bndy_x{1.0};
00145     mtk::Real south_bndy_y{0.0};
00146     mtk::Real north_bndy_y{1.0};
00147     int num_cells_x{5};
00148     int num_cells_y{5};
00149
00150     mtk::UniStgGrid2D comp_sol(west_bndy_x, east_bndy_x, num_cells_x,
00151                               south_bndy_y, north_bndy_y, num_cells_y);
00152
00153     mtk::Lap2D lap;
00154
00155     if (!lap.ConstructLap2D(comp_sol)) {
00156         std::cerr << "Mimetic Laplacian could not be built." << std::endl;
00157         return EXIT_FAILURE;
00158     }
00159
00160     mtk::DenseMatrix lapm(lap.ReturnAsDenseMatrix());
00161
00162     mtk::UniStgGrid2D source(west_bndy_x, east_bndy_x, num_cells_x,
00163                              south_bndy_y, north_bndy_y, num_cells_y);
00164
00165     source.BindScalarField(Source);
00166
00167     mtk::RobinBCDescriptor2D bcd;
00168
00169     bcd.PushBackWestCoeff(BCCoeff);
00170     bcd.PushBackEastCoeff(BCCoeff);
00171     bcd.PushBackSouthCoeff(BCCoeff);
00172     bcd.PushBackNorthCoeff(BCCoeff);
00173
00174     bcd.ImposeOnLaplacianMatrix(lap, comp_sol, lapm);
00175
00176     if (!lapm.WriteToFile("poisson_2d_lapm.dat")) {
00177         std::cerr << "Laplacian matrix could not be written to disk." << std::endl;
00178         return EXIT_FAILURE;
00179     }
00180
00181     bcd.set_west_condition(WestBC);
00182     bcd.set_east_condition(EastBC);
00183     bcd.set_south_condition(SouthBC);
00184     bcd.set_north_condition(NorthBC);
00185
00186
00187
00188
00189
00190

```

```

00191     bcd.ImposeOnGrid(source);
00192
00193     if(!source.WriteToFile("poisson_2d_source.dat", "x", "y", "s(x,y)")) {
00194         std::cerr << "Source term could not be written to disk." << std::endl;
00195         return EXIT_FAILURE;
00196     }
00197
00199     int info{mtk::LAPACKAdapter::SolveDenseSystem(lapm, source)};
00200
00201     if (!info) {
00202         std::cout << "System solved." << std::endl;
00203         std::cout << std::endl;
00204     } else {
00205         std::cerr << "Something wrong solving system! info = " << info << std::endl;
00206         std::cerr << "Exiting..." << std::endl;
00207         return EXIT_FAILURE;
00208     }
00209
00210     if (!source.WriteToFile("poisson_2d_comp_sol.dat", "x", "y", "~u(x,y)")) {
00211         std::cerr << "Solution could not be written to file." << std::endl;
00212         return EXIT_FAILURE;
00213     }
00214
00216     mtk::UniStgGrid2D known_sol(west_bndy_x, east_bndy_x, num_cells_x,
00217                                 south_bndy_y, north_bndy_y, num_cells_y);
00218
00219     known_sol.BindScalarField(KnownSolution);
00220
00221     if (!known_sol.WriteToFile("poisson_2d_known_sol.dat", "x", "y", "u(x,y)")) {
00222         std::cerr << "Known solution could not be written to file." << std::endl;
00223         return EXIT_FAILURE;
00224     }
00225
00226     mtk::Real relative_norm_2_error{};
00227
00228     relative_norm_2_error =
00229         mtk::BLASAdapter::RelNorm2Error(source.discrete_field(),
00230                                         known_sol.discrete_field(),
00231                                         known_sol.Size());
00232
00233     std::cout << "relative_norm_2_error = ";
00234     std::cout << relative_norm_2_error << std::endl;
00235 }
00236
00237 #else
00238 #include <iostream>
00239 using std::cout;
00240 using std::endl;
00241 int main () {
00242     cout << "This code HAS to be compiled with support for C++11." << endl;
00243     cout << "Exiting..." << endl;
00244     return EXIT_SUCCESS;
00245 }
00246 #endif

```

17.11 include/mtk.h File Reference


Includes the entire API.

```

#include "mtk_roots.h"
#include "mtk_enums.h"
#include "mtk_tools.h"
#include "mtk_matrix.h"
#include "mtk_dense_matrix.h"
#include "mtk_blas_adapter.h"
#include "mtk_lapack_adapter.h"
#include "mtk_glpk_adapter.h"
#include "mtk_uni_stg_grid_1d.h"
#include "mtk_uni_stg_grid_2d.h"
#include "mtk_uni_stg_grid_3d.h"
#include "mtk_grad_1d.h"
#include "mtk_div_1d.h"
#include "mtk_lap_1d.h"
#include "mtk_robin_bc_descriptor_1d.h"
#include "mtk_quad_1d.h"
#include "mtk_interp_1d.h"
#include "mtk_grad_2d.h"
#include "mtk_div_2d.h"
#include "mtk_curl_2d.h"
#include "mtk_lap_2d.h"
#include "mtk_robin_bc_descriptor_2d.h"
#include "mtk_grad_3d.h"
#include "mtk_div_3d.h"
#include "mtk_lap_3d.h"
#include "mtk_robin_bc_descriptor_3d.h"

```

Include dependency graph for mtk.h:



17.11.1 Detailed Description

This file contains every required header file, thus containing the entire API. In this way, client codes only have to instruct `#include "mtk.h"`.

Warning

It is extremely important that the headers are added to this file in a specific order; that is, considering the dependence between the classes these contain.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk.h](#).

17.12 mtk.h

```

00001
00015 /*
00016 Copyright (C) 2015, Computational Science Research Center, San Diego State
00017 University. All rights reserved.
00018
00019 Redistribution and use in source and binary forms, with or without modification,
00020 are permitted provided that the following conditions are met:
00021
00022 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00023 and a copy of the modified files should be reported once modifications are
00024 completed, unless these modifications are made through the project's GitHub
00025 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00026 should be developed and included in any deliverable.
00027
00028 2. Redistributions of source code must be done through direct
00029 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00030
00031 3. Redistributions in binary form must reproduce the above copyright notice,
00032 this list of conditions and the following disclaimer in the documentation and/or
00033 other materials provided with the distribution.
00034
00035 4. Usage of the binary form on proprietary applications shall require explicit
00036 prior written permission from the the copyright holders, and due credit should
00037 be given to the copyright holders.
00038
00039 5. Neither the name of the copyright holder nor the names of its contributors
00040 may be used to endorse or promote products derived from this software without
00041 specific prior written permission.
00042
00043 The copyright holders provide no reassurances that the source code provided does
00044 not infringe any patent, copyright, or any other intellectual property rights of
00045 third parties. The copyright holders disclaim any liability to any recipient for
00046 claims brought against recipient by any third party for infringement of that
00047 parties intellectual property rights.
00048
00049 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00050 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00051 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00052 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00053 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00054 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00055 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00056 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00057 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00058 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00059 */
00381 #ifndef MTK_INCLUDE_MTK_H_
00382 #define MTK_INCLUDE_MTK_H_
00383
00391 #include "mtk_roots.h"
00392
00400 #include "mtk_enums.h"
00401
00409 #include "mtk_tools.h"
00410
00418 #include "mtk_matrix.h"
00419 #include "mtk_dense_matrix.h"
00420
00428 #include "mtk_blas_adapter.h"
00429 #include "mtk_lapack_adapter.h"
00430 #include "mtk_glpk_adapter.h"
00431
00439 #include "mtk_uni_stg_grid_1d.h"
00440 #include "mtk_uni_stg_grid_2d.h"
00441 #include "mtk_uni_stg_grid_3d.h"
00442
00450 #include "mtk_grad_1d.h"
00451 #include "mtk_div_1d.h"
00452 #include "mtk_lap_1d.h"
00453 #include "mtk_robin_bc_descriptor_1d.h"
00454 #include "mtk_quad_1d.h"
00455 #include "mtk_interp_1d.h"
00456
00457 #include "mtk_grad_2d.h"
00458 #include "mtk_div_2d.h"
00459 #include "mtk_curl_2d.h"
00460 #include "mtk_lap_2d.h"
00461 #include "mtk_robin_bc_descriptor_2d.h"

```

```

00462
00463 #include "mtk_grad_3d.h"
00464 #include "mtk_div_3d.h"
00465 #include "mtk_lap_3d.h"
00466 #include "mtk_robin_bc_descriptor_3d.h"
00467
00468 #endif // End of: MTK_INCLUDE_MTK_H_


```

17.13 include/mtk_blas_adapter.h File Reference

Adapter class for the BLAS API.

```
#include "mtk_dense_matrix.h"
```

Include dependency graph for mtk_blas_adapter.h:



This graph shows which files directly or indirectly include this file:



Classes

- class `mtk::BLASAdapter`

Adapter class for the BLAS API.

Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

17.13.1 Detailed Description

This class contains a collection of static classes, that posses direct access to the underlying structure of the matrices, thus allowing programmers to exploit some of the numerical methods implemented in the BLAS.

The **BLAS (Basic Linear Algebra Subprograms)** are routines that provide standard building blocks for performing basic vector and matrix operations. The Level 1 BLAS perform scalar, vector and vector-vector operations, the Level 2 BLAS perform matrix-vector operations, and the Level 3 BLAS perform matrix-matrix operations.

The BLAS can be installed from links given in the See Also section of this page.

See also

<http://www.netlib.org/blas/>
<https://software.intel.com/en-us/non-commercial-software-development>

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_blas_adapter.h](#).

17.14 mtk_blas_adapter.h

```

00001
00024 /*
00025 Copyright (C) 2015, Computational Science Research Center, San Diego State
00026 University. All rights reserved.
00027
00028 Redistribution and use in source and binary forms, with or without modification,
00029 are permitted provided that the following conditions are met:
00030
00031 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00032 and a copy of the modified files should be reported once modifications are
00033 completed, unless these modifications are made through the project's GitHub
00034 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00035 should be developed and included in any deliverable.
00036
00037 2. Redistributions of source code must be done through direct
00038 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00039
00040 3. Redistributions in binary form must reproduce the above copyright notice,
00041 this list of conditions and the following disclaimer in the documentation and/or
00042 other materials provided with the distribution.
00043
00044 4. Usage of the binary form on proprietary applications shall require explicit
00045 prior written permission from the the copyright holders, and due credit should
00046 be given to the copyright holders.
00047
00048 5. Neither the name of the copyright holder nor the names of its contributors
00049 may be used to endorse or promote products derived from this software without
00050 specific prior written permission.
00051
00052 The copyright holders provide no reassurances that the source code provided does
00053 not infringe any patent, copyright, or any other intellectual property rights of
00054 third parties. The copyright holders disclaim any liability to any recipient for
00055 claims brought against recipient by any third party for infringement of that
00056 parties intellectual property rights.
00057

```

```

00058 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00059 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00060 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00061 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00062 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00063 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00064 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00065 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00066 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00067 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00068 */
00069
00070 #ifndef MTK_INCLUDE_BLAS_ADAPTER_H_
00071 #define MTK_INCLUDE_BLAS_ADAPTER_H_
00072
00073 #include "mtk_dense_matrix.h"
00074
00075 namespace mtk {
00076
00096 class BLASAdapter {
00097 public:
00106     static Real RealNRM2(Real *in, int &in_length);
00107
00124     static void RealAXPY(Real alpha, Real *xx, Real *yy, int &in_length);
00125
00140     static Real RelNorm2Error(Real *computed, Real *known, int length);
00141
00159     static void RealDenseMV(Real &alpha,
00160                             DenseMatrix &aa,
00161                             Real *xx,
00162                             Real &beta,
00163                             Real *yy);
00164
00179     static DenseMatrix RealDenseMM(DenseMatrix &aa,
DenseMatrix &bb);
00180
00195     static DenseMatrix RealDenseSM(Real alpha,
DenseMatrix &aa);
00196 };
00197 }
00198 #endif // End of: MTK_INCLUDE_BLAS_ADAPTER_H_

```

17.15 include/mtk_curl_2d.h File Reference


Includes the definition of the class Curl2D.

```


#include "mtk_roots.h"
#include "mtk_dense_matrix.h"
#include "mtk_uni_stg_grid_2d.h"
#include "mtk_uni_stg_grid_3d.h"

```

Include dependency graph for `mtk_curl_2d.h`:



This graph shows which files directly or indirectly include this file:



Classes

- class [mtk::Curl2D](#)
Implements a 2D mimetic curl operator.

Namespaces

- [mtk](#)
Mimetic Methods Toolkit namespace.

17.15.1 Detailed Description

This class implements a 2D curl operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (CBSA).

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_curl_2d.h](#).

17.16 mtk_curl_2d.h

```

00001
00011 /*
00012 Copyright (C) 2015, Computational Science Research Center, San Diego State
00013 University. All rights reserved.
00014
00015 Redistribution and use in source and binary forms, with or without modification,
00016 are permitted provided that the following conditions are met:
00017
00018 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00019 and a copy of the modified files should be reported once modifications are
00020 completed, unless these modifications are made through the project's GitHub
00021 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00022 should be developed and included in any deliverable.
00023
00024 2. Redistributions of source code must be done through direct
00025 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00026
00027 3. Redistributions in binary form must reproduce the above copyright notice,
00028 this list of conditions and the following disclaimer in the documentation and/or
00029 other materials provided with the distribution.
00030
00031 4. Usage of the binary form on proprietary applications shall require explicit
00032 prior written permission from the the copyright holders, and due credit should
00033 be given to the copyright holders.
00034
00035 5. Neither the name of the copyright holder nor the names of its contributors
00036 may be used to endorse or promote products derived from this software without
00037 specific prior written permission.
00038
00039 The copyright holders provide no reassurances that the source code provided does
00040 not infringe any patent, copyright, or any other intellectual property rights of
00041 third parties. The copyright holders disclaim any liability to any recipient for
00042 claims brought against recipient by any third party for infringement of that
00043 parties intellectual property rights.
00044
00045 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00046 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00047 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00048 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00049 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00050 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00051 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00052 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00053 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00054 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00055 */
00056
00057 #ifndef MTK_INCLUDE_MTK_CURL_2D_H_
00058 #define MTK_INCLUDE_MTK_CURL_2D_H_
00059
00060 #include "mtk_roots.h"
00061 #include "mtk_dense_matrix.h"
00062 #include "mtk_uni_stg_grid_2d.h"
00063 #include "mtk_uni_stg_grid_3d.h"
00064
00065 namespace mtk{
00066
00077 class Curl2D {
00078 public:
00080     UniStgGrid3D operator*(const UniStgGrid2D &grid) const;
00081

```

```

00083  Curl2D();
00084
00090  Curl2D(const Curl2D &curl);
00091
00093  ~Curl2D();
00094
00100  bool ConstructCurl2D(const UniStgGrid2D &grid,
00101                      int order_accuracy = kDefaultOrderAccuracy,
00102                      Real mimetic_threshold = kDefaultMimeticThreshold);
00103
00109  DenseMatrix ReturnAsDenseMatrix() const;
00110
00111 private:
00112  DenseMatrix curl_;
00113
00114  int order_accuracy_;
00115
00116  Real mimetic_threshold_;
00117 };
00118 }
00119 #endif // End of: MTK_INCLUDE_MTK_CURL_2D_H_

```

17.17 include/mtk_dense_matrix.h File Reference


Defines a common dense matrix, using a 1D array.

```


#include <iostream>
#include "mtk_roots.h"
#include "mtk_enums.h"
#include "mtk_matrix.h"

```

Include dependency graph for mtk_dense_matrix.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [mtk::DenseMatrix](#)

Defines a common dense matrix, using a 1D array.

Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

17.17.1 Detailed Description

For developing purposes, it is better to have a not-so-intricated data structure implementing matrices. This is the purpose of this class: to be used for prototypes of new code for small test cases. In every other instance, this should be replaced by the most appropriate sparse matrix.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Note

We prefer composition to inheritance [Reedy, 2011]. The main reason for this preference is that inheritance produces a more tightly coupled design. When a class inherits from another type be it public, protected, or private inheritance the subclass gains access to all public and protected members of the base class, whereas with composition, the class is only coupled to the public members of the other class. Furthermore, if you only hold a pointer to the other object, then your interface can use a forward declaration of the class rather than #include its full definition. This results in greater compile-time insulation and improves the time it takes to compile your code.

Definition in file [mtk_dense_matrix.h](#).

17.18 mtk_dense_matrix.h

```
00001
00023 /*
00024 Copyright (C) 2015, Computational Science Research Center, San Diego State
00025 University. All rights reserved.
00026
00027 Redistribution and use in source and binary forms, with or without modification,
00028 are permitted provided that the following conditions are met:
00029
00030 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00031 and a copy of the modified files should be reported once modifications are
00032 completed, unless these modifications are made through the project's GitHub
00033 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00034 should be developed and included in any deliverable.
00035
00036 2. Redistributions of source code must be done through direct
00037 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00038
00039 3. Redistributions in binary form must reproduce the above copyright notice,
00040 this list of conditions and the following disclaimer in the documentation and/or
00041 other materials provided with the distribution.
00042
00043 4. Usage of the binary form on proprietary applications shall require explicit
00044 prior written permission from the the copyright holders, and due credit should
00045 be given to the copyright holders.
00046
00047 5. Neither the name of the copyright holder nor the names of its contributors
```

```

00048 may be used to endorse or promote products derived from this software without
00049 specific prior written permission.
00050
00051 The copyright holders provide no reassurances that the source code provided does
00052 not infringe any patent, copyright, or any other intellectual property rights of
00053 third parties. The copyright holders disclaim any liability to any recipient for
00054 claims brought against recipient by any third party for infringement of that
00055 parties intellectual property rights.
00056
00057 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00058 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00059 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00060 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00061 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00062 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00063 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00064 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00065 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00066 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00067 */
00068
00069 #ifndef MTK_INCLUDE_DENSE_MATRIX_H_
00070 #define MTK_INCLUDE_DENSE_MATRIX_H_
00071
00072 #include <iostream>
00073
00074 #include "mtk_roots.h"
00075 #include "mtk_enums.h"
00076 #include "mtk_matrix.h"
00077
00078 namespace mtk {
00079
00092 class DenseMatrix {
00093 public:
00095     friend std::ostream& operator <<(std::ostream &stream, DenseMatrix &in);
00096
00104     DenseMatrix& operator =(const DenseMatrix &in);
00105
00107     bool operator ==(const DenseMatrix &in);
00108
00110     DenseMatrix();
00111
00117     DenseMatrix(const DenseMatrix &in);
00118
00127     DenseMatrix(const int &num_rows, const int &num_cols);
00128
00154     DenseMatrix(const int &rank, const bool &padded, const bool &transpose);
00155
00189     DenseMatrix(const Real *const gen,
00190                 const int &gen_length,
00191                 const int &pro_length,
00192                 const bool &transpose);
00193
00195     ~DenseMatrix();
00196
00202     Matrix matrix_properties() const noexcept;
00203
00209     int num_rows() const noexcept;
00210
00216     int num_cols() const noexcept;
00217
00223     Real* data() const noexcept;
00224
00232     void SetOrdering(mtk::MatrixOrdering oo) noexcept;
00233
00242     Real GetValue(const int &row_coord, const int &col_coord) const noexcept;
00243
00251     void SetValue(const int &row_coord,
00252                  const int &col_coord,
00253                  const Real &val) noexcept;
00254
00256     void Transpose();
00257
00259     void OrderRowMajor();
00260
00262     void OrderColMajor();
00263
00274     static DenseMatrix Kron(const DenseMatrix &aa,
00275                             const DenseMatrix &bb);
00276
00286     bool WriteToFile(const std::string &filename) const;

```

```

00287
00288 private:
00289     Matrix matrix_properties;
00290
00291     Real *data_;
00292 };
00293 }
00294 #endif // End of: MTK_INCLUDE_MTK_DENSE_MATRIX_H_

```

17.19 include/mtk_div_1d.h File Reference


Includes the definition of the class Div1D.

```


#include <iostream>
#include <iomanip>
#include "glpk.h"
#include "mtk_roots.h"
#include "mtk_dense_matrix.h"
#include "mtk_uni_stg_grid_1d.h"

```

Include dependency graph for mtk_div_1d.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [mtk::Div1D](#)
Implements a 1D mimetic divergence operator.

Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

17.19.1 Detailed Description

This class implements a 1D divergence operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (CBSA).

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_div_1d.h](#).

17.20 mtk_div_1d.h

```

00001
00011 /*
00012 Copyright (C) 2015, Computational Science Research Center, San Diego State
00013 University. All rights reserved.
00014
00015 Redistribution and use in source and binary forms, with or without modification,
00016 are permitted provided that the following conditions are met:
00017
00018 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00019 and a copy of the modified files should be reported once modifications are
00020 completed, unless these modifications are made through the project's GitHub
00021 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00022 should be developed and included in any deliverable.
00023
00024 2. Redistributions of source code must be done through direct
00025 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00026
00027 3. Redistributions in binary form must reproduce the above copyright notice,
00028 this list of conditions and the following disclaimer in the documentation and/or
00029 other materials provided with the distribution.
00030
00031 4. Usage of the binary form on proprietary applications shall require explicit
00032 prior written permission from the the copyright holders, and due credit should
00033 be given to the copyright holders.
00034
00035 5. Neither the name of the copyright holder nor the names of its contributors
00036 may be used to endorse or promote products derived from this software without
00037 specific prior written permission.
00038
00039 The copyright holders provide no reassurances that the source code provided does
00040 not infringe any patent, copyright, or any other intellectual property rights of
00041 third parties. The copyright holders disclaim any liability to any recipient for
00042 claims brought against recipient by any third party for infringement of that
00043 parties intellectual property rights.
00044
00045 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00046 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00047 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00048 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00049 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00050 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00051 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00052 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00053 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00054 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00055 */
00056
00057 #ifndef MTK_INCLUDE_DIV_1D_H_
00058 #define MTK_INCLUDE_DIV_1D_H_
00059
00060 #include <iostream>
00061 #include <iomanip>
00062
00063 #include "glpk.h"
00064

```

```

00065 #include "mtk_roots.h"
00066 #include "mtk_dense_matrix.h"
00067 #include "mtk_uni_stg_grid_1d.h"
00068
00069 namespace mtk {
00070
00081 class Div1D {
00082 public:
00084     friend std::ostream& operator <<(std::ostream& stream, Div1D &in);
00085
00087     Div1D();
00088
00094     Div1D(const Div1D &div);
00095
00097     ~Div1D();
00098
00104     bool ConstructDiv1D(int order_accuracy = kDefaultOrderAccuracy,
00105                        Real mimetic_threshold = kDefaultMimeticThreshold);
00106
00112     int num_bndy_coeffs() const;
00113
00119     Real *coeffs_interior() const;
00120
00126     Real *weights_crs(void) const;
00127
00133     Real *weights_cbs(void) const;
00134
00140     DenseMatrix mim_bndy() const;
00141
00147     DenseMatrix ReturnAsDenseMatrix(const
UniStgGrid1D &grid) const;
00148
00149 private:
00155     bool ComputeStencilInteriorGrid(void);
00156
00163     bool ComputeRationalBasisNullSpace(void);
00164
00170     bool ComputePreliminaryApproximations(void);
00171
00177     bool ComputeWeights(void);
00178
00184     bool ComputeStencilBoundaryGrid(void);
00185
00191     bool AssembleOperator(void);
00192
00193     int order_accuracy_;
00194     int dim_null_;
00195     int num_bndy_coeffs_;
00196     int divergence_length_;
00197     int minrow_;
00198     int row_;
00199
00200     DenseMatrix rat_basis_null_space_;
00201
00202     Real *coeffs_interior_;
00203     Real *prem_apps_;
00204     Real *weights_crs_;
00205     Real *weights_cbs_;
00206     Real *mim_bndy_;
00207     Real *divergence_;
00208
00209     Real mimetic_threshold_;
00210 };
00211 }
00212 #endif // End of: MTK_INCLUDE_DIV_1D_H_

```

17.21 include/mtk_div_2d.h File Reference


Includes the definition of the class Div2D.

```


#include "mtk_roots.h"
#include "mtk_dense_matrix.h"
#include "mtk_uni_stg_grid_2d.h"

```

Include dependency graph for `mtk_div_2d.h`:



This graph shows which files directly or indirectly include this file:



Classes

- class `mtk::Div2D`
Implements a 2D mimetic divergence operator.

Namespaces

- `mtk`
Mimetic Methods Toolkit namespace.

17.21.1 Detailed Description

This class implements a 2D divergence operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (CBSA).

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_div_2d.h](#).

17.22 mtk_div_2d.h

```

00001
00011 /*
00012 Copyright (C) 2015, Computational Science Research Center, San Diego State
00013 University. All rights reserved.
00014
00015 Redistribution and use in source and binary forms, with or without modification,
00016 are permitted provided that the following conditions are met:
00017
00018 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00019 and a copy of the modified files should be reported once modifications are
00020 completed, unless these modifications are made through the project's GitHub
00021 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00022 should be developed and included in any deliverable.
00023
00024 2. Redistributions of source code must be done through direct
00025 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00026
00027 3. Redistributions in binary form must reproduce the above copyright notice,
00028 this list of conditions and the following disclaimer in the documentation and/or
00029 other materials provided with the distribution.
00030
00031 4. Usage of the binary form on proprietary applications shall require explicit
00032 prior written permission from the the copyright holders, and due credit should
00033 be given to the copyright holders.
00034
00035 5. Neither the name of the copyright holder nor the names of its contributors
00036 may be used to endorse or promote products derived from this software without
00037 specific prior written permission.
00038
00039 The copyright holders provide no reassurances that the source code provided does
00040 not infringe any patent, copyright, or any other intellectual property rights of
00041 third parties. The copyright holders disclaim any liability to any recipient for
00042 claims brought against recipient by any third party for infringement of that
00043 parties intellectual property rights.
00044
00045 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00046 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00047 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00048 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00049 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00050 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00051 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00052 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00053 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00054 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00055 */
00056
00057 #ifndef MTK_INCLUDE_MTK_DIV_2D_H_
00058 #define MTK_INCLUDE_MTK_DIV_2D_H_
00059
00060 #include "mtk_roots.h"
00061 #include "mtk_dense_matrix.h"
00062 #include "mtk_uni_stg_grid_2d.h"
00063
00064 namespace mtk{
00065
00076 class Div2D {
00077 public:
00079     Div2D();
00080

```

```

00086   Div2D(const Div2D &div);
00087
00088   ~Div2D();
00089
00090   bool ConstructDiv2D(const UniStgGrid2D &grid,
00091                      int order_accuracy = kDefaultOrderAccuracy,
00092                      Real mimetic_threshold = kDefaultMimeticThreshold);
00093
00094   DenseMatrix ReturnAsDenseMatrix() const;
00095
00096 private:
00097   DenseMatrix divergence_;
00098   int order_accuracy_;
00099   Real mimetic_threshold_;
00100 };
00101 }
00102 #endif // End of: MTK_INCLUDE_MTK_DIV_2D_H_

```

17.23 include/mtk_div_3d.h File Reference


Includes the definition of the class Div3D.

```


#include "mtk_roots.h"
#include "mtk_dense_matrix.h"
#include "mtk_uni_stg_grid_3d.h"

```

Include dependency graph for mtk_div_3d.h:



This graph shows which files directly or indirectly include this file:



Classes

- class `mtk::Div3D`
Implements a 3D mimetic divergence operator.

Namespaces

- `mtk`
Mimetic Methods Toolkit namespace.

17.23.1 Detailed Description

This class implements a 3D divergence operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (CBSA).

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_div_3d.h](#).

17.24 mtk_div_3d.h

```

00001
00011 /*
00012 Copyright (C) 2015, Computational Science Research Center, San Diego State
00013 University. All rights reserved.
00014
00015 Redistribution and use in source and binary forms, with or without modification,
00016 are permitted provided that the following conditions are met:
00017
00018 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00019 and a copy of the modified files should be reported once modifications are
00020 completed, unless these modifications are made through the project's GitHub
00021 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00022 should be developed and included in any deliverable.
00023
00024 2. Redistributions of source code must be done through direct
00025 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00026

```

```


00027 3. Redistributions in binary form must reproduce the above copyright notice,
00028 this list of conditions and the following disclaimer in the documentation and/or
00029 other materials provided with the distribution.
00030
00031 4. Usage of the binary form on proprietary applications shall require explicit
00032 prior written permission from the the copyright holders, and due credit should
00033 be given to the copyright holders.
00034
00035 5. Neither the name of the copyright holder nor the names of its contributors
00036 may be used to endorse or promote products derived from this software without
00037 specific prior written permission.
00038
00039 The copyright holders provide no reassurances that the source code provided does
00040 not infringe any patent, copyright, or any other intellectual property rights of
00041 third parties. The copyright holders disclaim any liability to any recipient for
00042 claims brought against recipient by any third party for infringement of that
00043 parties intellectual property rights.
00044
00045 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00046 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00047 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00048 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00049 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00050 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00051 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00052 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00053 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00054 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00055 */
00056
00057 #ifndef MTK_INCLUDE_MTK_DIV_3D_H_
00058 #define MTK_INCLUDE_MTK_DIV_3D_H_
00059
00060 #include "mtk_roots.h"
00061 #include "mtk_dense_matrix.h"
00062 #include "mtk_uni_stg_grid_3d.h"
00063
00064 namespace mtk{
00065
00066 class Div3D {
00067 public:
00068     Div3D();
00069
00070     Div3D(const Div3D &div);
00071
00072     ~Div3D();
00073
00074     bool ConstructDiv3D(const UniStgGrid3D &grid,
00075                        int order_accuracy = kDefaultOrderAccuracy,
00076                        Real mimetic_threshold = kDefaultMimeticThreshold);
00077
00078     DenseMatrix ReturnAsDenseMatrix() const;
00079
00080 private:
00081     DenseMatrix divergence_;
00082
00083     int order_accuracy_;
00084
00085     Real mimetic_threshold_;
00086 };
00087
00088 #endif // End of: MTK_INCLUDE_MTK_DIV_3D_H_

```

17.25 include/mtk_enums.h File Reference

Considered enumeration types in the MTK.

This graph shows which files directly or indirectly include this file:



Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

Enumerations

- enum [mtk::MatrixStorage](#) { [mtk::DENSE](#), [mtk::BANDED](#), [mtk::CRS](#) }
Considered matrix storage schemes to implement sparse matrices.
- enum [mtk::MatrixOrdering](#) { [mtk::ROW_MAJOR](#), [mtk::COL_MAJOR](#) }
Considered matrix ordering (for Fortran purposes).
- enum [mtk::FieldNature](#) { [mtk::SCALAR](#), [mtk::VECTOR](#) }
Nature of the field discretized in a given grid.
- enum [mtk::DirInterp](#) { [mtk::SCALAR_TO_VECTOR](#), [mtk::VECTOR_TO_SCALAR](#) }
Interpolation operator.

17.25.1 Detailed Description

Enumeration types are used throughout the MTK to differentiate instances of derived classes, as well as for mnemonic purposes. In this file, the enumeration types are listed alphabetically.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_enums.h](#).

17.26 mtk_enums.h

```

00001
00012 /*
00013 Copyright (C) 2015, Computational Science Research Center, San Diego State
00014 University. All rights reserved.
00015
00016 Redistribution and use in source and binary forms, with or without modification,
00017 are permitted provided that the following conditions are met:
00018
00019 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00020 and a copy of the modified files should be reported once modifications are
00021 completed, unless these modifications are made through the project's GitHub
00022 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00023 should be developed and included in any deliverable.
00024
00025 2. Redistributions of source code must be done through direct
00026 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00027

```

```

00028 3. Redistributions in binary form must reproduce the above copyright notice,
00029 this list of conditions and the following disclaimer in the documentation and/or
00030 other materials provided with the distribution.
00031
00032 4. Usage of the binary form on proprietary applications shall require explicit
00033 prior written permission from the the copyright holders, and due credit should
00034 be given to the copyright holders.
00035
00036 5. Neither the name of the copyright holder nor the names of its contributors
00037 may be used to endorse or promote products derived from this software without
00038 specific prior written permission.
00039
00040 The copyright holders provide no reassurances that the source code provided does
00041 not infringe any patent, copyright, or any other intellectual property rights of
00042 third parties. The copyright holders disclaim any liability to any recipient for
00043 claims brought against recipient by any third party for infringement of that
00044 parties intellectual property rights.
00045
00046 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00047 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00048 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00049 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00050 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00051 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00052 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00053 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00054 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00055 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00056 */
00057
00058 #ifndef MTK_INCLUDE_ENUMS_H_
00059 #define MTK_INCLUDE_ENUMS_H_
00060
00061 namespace mtk {
00062
00077 enum MatrixStorage {
00078     DENSE,
00079     BANDED,
00080     CRS
00081 };
00082
00095 enum MatrixOrdering {
00096     ROW_MAJOR,
00097     COL_MAJOR
00098 };
00099
00113 enum FieldNature {
00114     SCALAR,
00115     VECTOR
00116 };
00117
00127 enum DirInterp {
00128     SCALAR_TO_VECTOR,
00129     VECTOR_TO_SCALAR
00130 };
00131 }
00132 #endif // End of: MTK_INCLUDE_ENUMS_H_

```

17.27 include/mtk_glpk_adapter.h File Reference


Adapter class for the GLPK API.

```


#include <iostream>
#include <iomanip>
#include "glpk.h"
#include "mtk_roots.h"
#include "mtk_dense_matrix.h"

```

Include dependency graph for mtk_glpk_adapter.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [mtk::GLPKAdapter](#)
Adapter class for the GLPK API.

Namespaces

- [mtk](#)
Mimetic Methods Toolkit namespace.

17.27.1 Detailed Description

This class contains a collection of static classes, that posses direct access to the underlying structure of the matrices, thus allowing programmers to exploit some of the numerical methods implemented in the GLPK.

The **GLPK (GNU Linear Programming Kit)** package is intended for solving large-scale linear programming (LP), mixed integer programming (MIP), and other related problems. It is a set of routines written in ANSI C and organized in the form of a callable library.

See also

<http://www.gnu.org/software/glpk/>

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_glpk_adapter.h](#).

17.28 mtk_glpk_adapter.h

```

00001
00019 /*
00020 Copyright (C) 2015, Computational Science Research Center, San Diego State
00021 University. All rights reserved.
00022
00023 Redistribution and use in source and binary forms, with or without modification,
00024 are permitted provided that the following conditions are met:
00025
00026 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00027 and a copy of the modified files should be reported once modifications are
00028 completed, unless these modifications are made through the project's GitHub
00029 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00030 should be developed and included in any deliverable.
00031
00032 2. Redistributions of source code must be done through direct
00033 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00034
00035 3. Redistributions in binary form must reproduce the above copyright notice,
00036 this list of conditions and the following disclaimer in the documentation and/or
00037 other materials provided with the distribution.
00038
00039 4. Usage of the binary form on proprietary applications shall require explicit
00040 prior written permission from the the copyright holders, and due credit should
00041 be given to the copyright holders.
00042
00043 5. Neither the name of the copyright holder nor the names of its contributors
00044 may be used to endorse or promote products derived from this software without
00045 specific prior written permission.
00046
00047 The copyright holders provide no reassurances that the source code provided does
00048 not infringe any patent, copyright, or any other intellectual property rights of
00049 third parties. The copyright holders disclaim any liability to any recipient for
00050 claims brought against recipient by any third party for infringement of that
00051 parties intellectual property rights.
00052
00053 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00054 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00055 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00056 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00057 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00058 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00059 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00060 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00061 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00062 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00063 */
00064
00065 #ifndef MTK_INCLUDE_GLPK_ADAPTER_H_
00066 #define MTK_INCLUDE_GLPK_ADAPTER_H_
00067
00068 #include <iostream>
00069 #include <iomanip>
00070
00071 #include "glpk.h"
00072
00073 #include "mtk_roots.h"
00074 #include "mtk_dense_matrix.h"
00075
00076 namespace mtk {
00077
00101 class GLPKAdapter {

```



```

00102 public:
00123     static mtk::Real SolveSimplexAndCompare(
00124         mtk::Real *A,
00125         int nrows,
00126         int ncols,
00127         int kk,
00128         mtk::Real *hh,
00129         mtk::Real *qq,
00130         int robjective,
00131         mtk::Real mimetic_tol,
00132         int copy);
00133 }
00134 #endif // End of: MTK_INCLUDE_MTK_GLPK_ADAPTER_H_

```

17.29 include/mtk_grad_1d.h File Reference


Includes the definition of the class Grad1D.

```


#include <iostream>
#include <iomanip>
#include "glpk.h"
#include "mtk_roots.h"
#include "mtk_dense_matrix.h"
#include "mtk_uni_stg_grid_1d.h"

```

Include dependency graph for mtk_grad_1d.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [mtk::Grad1D](#)

Implements a 1D mimetic gradient operator.

Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

17.29.1 Detailed Description

This class implements a 1D gradient operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (C↔BSA).

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_grad_1d.h](#).

17.30 mtk_grad_1d.h

```

00001
00011 /*
00012 Copyright (C) 2015, Computational Science Research Center, San Diego State
00013 University. All rights reserved.
00014
00015 Redistribution and use in source and binary forms, with or without modification,
00016 are permitted provided that the following conditions are met:
00017
00018 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00019 and a copy of the modified files should be reported once modifications are
00020 completed, unless these modifications are made through the project's GitHub
00021 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00022 should be developed and included in any deliverable.
00023
00024 2. Redistributions of source code must be done through direct
00025 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00026
00027 3. Redistributions in binary form must reproduce the above copyright notice,
00028 this list of conditions and the following disclaimer in the documentation and/or
00029 other materials provided with the distribution.
00030
00031 4. Usage of the binary form on proprietary applications shall require explicit
00032 prior written permission from the the copyright holders, and due credit should
00033 be given to the copyright holders.
00034
00035 5. Neither the name of the copyright holder nor the names of its contributors
00036 may be used to endorse or promote products derived from this software without
00037 specific prior written permission.
00038
00039 The copyright holders provide no reassurances that the source code provided does
00040 not infringe any patent, copyright, or any other intellectual property rights of
00041 third parties. The copyright holders disclaim any liability to any recipient for
00042 claims brought against recipient by any third party for infringement of that
00043 parties intellectual property rights.
00044
00045 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00046 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00047 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00048 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00049 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00050 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00051 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00052 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00053 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00054 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00055 */
00056
00057 #ifndef MTK_INCLUDE_GRAD_1D_H_
00058 #define MTK_INCLUDE_GRAD_1D_H_
00059
00060 #include <iostream>

```

```

00061 #include <iomanip>
00062
00063 #include "glpk.h"
00064
00065 #include "mtk_roots.h"
00066 #include "mtk_dense_matrix.h"
00067 #include "mtk_uni_stg_grid_1d.h"
00068
00069 namespace mtk {
00070
00071 class Grad1D {
00072 public:
00073     friend std::ostream& operator <<(std::ostream& stream, Grad1D &in);
00074
00075     Grad1D();
00076
00077     Grad1D(const Grad1D &grad);
00078
00079     ~Grad1D();
00080
00081     bool ConstructGrad1D(int order_accuracy = kDefaultOrderAccuracy,
00082                         Real mimetic_threshold = kDefaultMimeticThreshold);
00083
00084     int num_bndy_coeffs() const;
00085
00086     Real *coeffs_interior() const;
00087
00088     Real *weights_crs(void) const;
00089
00090     Real *weights_cbs(void) const;
00091
00092     DenseMatrix mim_bndy() const;
00093
00094     DenseMatrix ReturnAsDenseMatrix(Real west,
00095                                     Real east, int num_cells_x) const;
00096
00097     DenseMatrix ReturnAsDenseMatrix(const
00098                                     UniStgGrid1D &grid) const;
00099
00100     DenseMatrix ReturnAsDimensionlessDenseMatrix(int num_cells_x)
00101     const;
00102
00103 private:
00104     bool ComputeStencilInteriorGrid(void);
00105
00106     bool ComputeRationalBasisNullSpace(void);
00107
00108     bool ComputePreliminaryApproximations(void);
00109
00110     bool ComputeWeights(void);
00111
00112     bool ComputeStencilBoundaryGrid(void);
00113
00114     bool AssembleOperator(void);
00115
00116     int order_accuracy_;
00117     int dim_null_;
00118     int num_bndy_approxs_;
00119     int num_bndy_coeffs_;
00120     int gradient_length_;
00121     int minrow_;
00122     int row_;
00123
00124     DenseMatrix rat_basis_null_space_;
00125
00126     Real *coeffs_interior_;
00127     Real *prem_apps_;
00128     Real *weights_crs_;
00129     Real *weights_cbs_;
00130     Real *mim_bndy_;
00131     Real *gradient_;
00132
00133     Real mimetic_threshold_;
00134 };
00135
00136 #endif // End of: MTK_INCLUDE_GRAD_1D_H_


```

17.31 include/mtk_grad_2d.h File Reference


Includes the definition of the class Grad2D.

```
#include "mtk_roots.h"
#include "mtk_dense_matrix.h"
#include "mtk_uni_stg_grid_2d.h"
```

Include dependency graph for mtk_grad_2d.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [mtk::Grad2D](#)

Implements a 2D mimetic gradient operator.

Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

17.31.1 Detailed Description

This class implements a 2D gradient operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (C↵BSA).

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_grad_2d.h](#).

17.32 mtk_grad_2d.h

```

00001
00011 /*
00012 Copyright (C) 2015, Computational Science Research Center, San Diego State
00013 University. All rights reserved.
00014
00015 Redistribution and use in source and binary forms, with or without modification,
00016 are permitted provided that the following conditions are met:
00017
00018 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00019 and a copy of the modified files should be reported once modifications are
00020 completed, unless these modifications are made through the project's GitHub
00021 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00022 should be developed and included in any deliverable.
00023
00024 2. Redistributions of source code must be done through direct
00025 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00026
00027 3. Redistributions in binary form must reproduce the above copyright notice,
00028 this list of conditions and the following disclaimer in the documentation and/or
00029 other materials provided with the distribution.
00030
00031 4. Usage of the binary form on proprietary applications shall require explicit
00032 prior written permission from the the copyright holders, and due credit should
00033 be given to the copyright holders.
00034
00035 5. Neither the name of the copyright holder nor the names of its contributors
00036 may be used to endorse or promote products derived from this software without
00037 specific prior written permission.
00038
00039 The copyright holders provide no reassurances that the source code provided does
00040 not infringe any patent, copyright, or any other intellectual property rights of
00041 third parties. The copyright holders disclaim any liability to any recipient for
00042 claims brought against recipient by any third party for infringement of that
00043 parties intellectual property rights.
00044
00045 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00046 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00047 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00048 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00049 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00050 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00051 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00052 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00053 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00054 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00055 */

```

```

00056
00057 #ifndef MTK_INCLUDE_MTK_GRAD_2D_H_
00058 #define MTK_INCLUDE_MTK_GRAD_2D_H_
00059
00060 #include "mtk_roots.h"
00061 #include "mtk_dense_matrix.h"
00062 #include "mtk_uni_stg_grid_2d.h"
00063
00064 namespace mtk{
00065
00076 class Grad2D {
00077 public:
00078     Grad2D();
00080
00086     Grad2D(const Grad2D &grad);
00087
00089     ~Grad2D();
00090
00096     bool ConstructGrad2D(const UniStgGrid2D &grid,
00097                         int order_accuracy = kDefaultOrderAccuracy,
00098                         Real mimetic_threshold = kDefaultMimeticThreshold);
00099
00105     DenseMatrix ReturnAsDenseMatrix() const;
00106
00107 private:
00108     DenseMatrix gradient_;
00109
00110     int order_accuracy_;
00111
00112     Real mimetic_threshold_;
00113 };
00114 }
00115 #endif // End of: MTK_INCLUDE_MTK_GRAD_2D_H_

```

17.33 include/mtk_grad_3d.h File Reference


Includes the definition of the class Grad3D.

```


#include "mtk_roots.h"
#include "mtk_dense_matrix.h"
#include "mtk_uni_stg_grid_3d.h"

```

Include dependency graph for mtk_grad_3d.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [mtk::Grad3D](#)
Implements a 3D mimetic gradient operator.

Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

17.33.1 Detailed Description

This class implements a 3D gradient operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (C↔BSA).

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_grad_3d.h](#).

17.34 mtk_grad_3d.h

```

00001
00011 /*
00012 Copyright (C) 2015, Computational Science Research Center, San Diego State
00013 University. All rights reserved.
00014
00015 Redistribution and use in source and binary forms, with or without modification,
00016 are permitted provided that the following conditions are met:
00017
00018 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00019 and a copy of the modified files should be reported once modifications are
00020 completed, unless these modifications are made through the project's GitHub
00021 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00022 should be developed and included in any deliverable.
00023
00024 2. Redistributions of source code must be done through direct
00025 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00026
00027 3. Redistributions in binary form must reproduce the above copyright notice,
00028 this list of conditions and the following disclaimer in the documentation and/or
00029 other materials provided with the distribution.
00030
00031 4. Usage of the binary form on proprietary applications shall require explicit
00032 prior written permission from the the copyright holders, and due credit should
00033 be given to the copyright holders.
00034
00035 5. Neither the name of the copyright holder nor the names of its contributors
00036 may be used to endorse or promote products derived from this software without
00037 specific prior written permission.
00038
00039 The copyright holders provide no reassurances that the source code provided does
00040 not infringe any patent, copyright, or any other intellectual property rights of
00041 third parties. The copyright holders disclaim any liability to any recipient for
00042 claims brought against recipient by any third party for infringement of that
00043 parties intellectual property rights.
00044
00045 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00046 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00047 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00048 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00049 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00050 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00051 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00052 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00053 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00054 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00055 */
00056
00057 #ifndef MTK_INCLUDE_MTK_GRAD_3D_H_
00058 #define MTK_INCLUDE_MTK_GRAD_3D_H_
00059
00060 #include "mtk_roots.h"
00061 #include "mtk_dense_matrix.h"
00062 #include "mtk_uni_stg_grid_3d.h"
00063
00064 namespace mtk{

```



```

00065
00076 class Grad3D {
00077 public:
00079     Grad3D();
00080
00086     Grad3D(const Grad3D &grad);
00087
00089     ~Grad3D();
00090
00096     bool ConstructGrad3D(const UniStgGrid3D &grid,
00097                         int order_accuracy = kDefaultOrderAccuracy,
00098                         Real mimetic_threshold = kDefaultMimeticThreshold);
00099
00105     DenseMatrix ReturnAsDenseMatrix() const;
00106
00107 private:
00108     DenseMatrix gradient_;
00109
00110     int order_accuracy_;
00111
00112     Real mimetic_threshold_;
00113 };
00114 }
00115 #endif // End of: MTK_INCLUDE_MTK_GRAD_3D_H_

```

17.35 include/mtk_interp_1d.h File Reference


Includes the definition of the class Interp1D.

```


#include <iostream>
#include <iomanip>
#include "glpk.h"
#include "mtk_roots.h"
#include "mtk_enums.h"
#include "mtk_dense_matrix.h"
#include "mtk_uni_stg_grid_1d.h"

```

Include dependency graph for mtk_interp_1d.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [mtk::Interp1D](#)
Implements a 1D interpolation operator.

Namespaces

- [mtk](#)
Mimetic Methods Toolkit namespace.

17.35.1 Detailed Description

This class implements a 1D interpolation operator.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu
: Johnny Corbino - jcorbino at mail dot sdsu dot edu

Definition in file [mtk_interp_1d.h](#).

17.36 mtk_interp_1d.h

```

00001
00012 /*
00013 Copyright (C) 2015, Computational Science Research Center, San Diego State
00014 University. All rights reserved.
00015
00016 Redistribution and use in source and binary forms, with or without modification,
00017 are permitted provided that the following conditions are met:
00018
00019 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00020 and a copy of the modified files should be reported once modifications are
00021 completed, unless these modifications are made through the project's GitHub
00022 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00023 should be developed and included in any deliverable.
00024

```

```

00025 2. Redistributions of source code must be done through direct
00026 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00027
00028 3. Redistributions in binary form must reproduce the above copyright notice,
00029 this list of conditions and the following disclaimer in the documentation and/or
00030 other materials provided with the distribution.
00031
00032 4. Usage of the binary form on proprietary applications shall require explicit
00033 prior written permission from the the copyright holders, and due credit should
00034 be given to the copyright holders.
00035
00036 5. Neither the name of the copyright holder nor the names of its contributors
00037 may be used to endorse or promote products derived from this software without
00038 specific prior written permission.
00039
00040 The copyright holders provide no reassurances that the source code provided does
00041 not infringe any patent, copyright, or any other intellectual property rights of
00042 third parties. The copyright holders disclaim any liability to any recipient for
00043 claims brought against recipient by any third party for infringement of that
00044 parties intellectual property rights.
00045
00046 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00047 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00048 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00049 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00050 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00051 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00052 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00053 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00054 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00055 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00056 */
00057
00058 #ifndef MTK_INCLUDE_INTERP_1D_H_
00059 #define MTK_INCLUDE_INTERP_1D_H_
00060
00061 #include <iostream>
00062 #include <iomanip>
00063
00064 #include "glpk.h"
00065
00066 #include "mtk_roots.h"
00067 #include "mtk_enums.h"
00068 #include "mtk_dense_matrix.h"
00069 #include "mtk_uni_stg_grid_1d.h"
00070
00071 namespace mtk {
00072
00082 class Interp1D {
00083 public:
00085     friend std::ostream& operator <<(std::ostream& stream, Interp1D &in);
00086
00088     Interp1D();
00089
00095     Interp1D(const Interp1D &interp);
00096
00098     ~Interp1D();
00099
00105     bool ConstructInterp1D(int order_accuracy =
kDefaultOrderAccuracy,
00106                             mtk::DirInterp dir = SCALAR_TO_VECTOR);
00107
00113     Real *coeffs_interior() const;
00114
00120     DenseMatrix ReturnAsDenseMatrix(const
UniStgGrid1D &grid) const;
00121
00122 private:
00123     DirInterp dir_interp_;
00124
00125     int order_accuracy_;
00126
00127     Real *coeffs_interior_;
00128 };
00129 }
00130 #endif // End of: MTK_INCLUDE_INTERP_1D_H_


```

17.37 include/mtk_interp_2d.h File Reference

Includes the definition of the class Interp2D.

```
#include "mtk_roots.h"
#include "mtk_dense_matrix.h"
#include "mtk_uni_stg_grid_2d.h"
```

Include dependency graph for mtk_interp_2d.h:



Classes

- class [mtk::Interp2D](#)
Implements a 2D interpolation operator.

Namespaces

- [mtk](#)
Mimetic Methods Toolkit namespace.

17.37.1 Detailed Description

This class implements a 2D interpolation operator.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu
 : Johnny Corbino - jcorbino at mail dot sdsu dot edu

Definition in file [mtk_interp_2d.h](#).

17.38 mtk_interp_2d.h

```

00001
00012 /*
00013 Copyright (C) 2015, Computational Science Research Center, San Diego State
00014 University. All rights reserved.
00015
00016 Redistribution and use in source and binary forms, with or without modification,
00017 are permitted provided that the following conditions are met:
00018
00019 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00020 and a copy of the modified files should be reported once modifications are
00021 completed, unless these modifications are made through the project's GitHub
00022 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00023 should be developed and included in any deliverable.
00024
00025 2. Redistributions of source code must be done through direct
00026 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00027
00028 3. Redistributions in binary form must reproduce the above copyright notice,
00029 this list of conditions and the following disclaimer in the documentation and/or
00030 other materials provided with the distribution.
00031
00032 4. Usage of the binary form on proprietary applications shall require explicit
00033 prior written permission from the the copyright holders, and due credit should
00034 be given to the copyright holders.
00035
00036 5. Neither the name of the copyright holder nor the names of its contributors
00037 may be used to endorse or promote products derived from this software without
00038 specific prior written permission.
00039
00040 The copyright holders provide no reassurances that the source code provided does
00041 not infringe any patent, copyright, or any other intellectual property rights of
00042 third parties. The copyright holders disclaim any liability to any recipient for
00043 claims brought against recipient by any third party for infringement of that
00044 parties intellectual property rights.
00045
00046 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00047 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00048 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00049 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00050 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00051 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00052 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00053 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00054 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00055 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00056 */
00057
00058 #ifndef MTK_INCLUDE_MTK_INTERP_2D_H_
00059 #define MTK_INCLUDE_MTK_INTERP_2D_H_
00060
00061 #include "mtk_roots.h"
00062 #include "mtk_dense_matrix.h"
00063 #include "mtk_uni_stg_grid_2d.h"
00064
00065 namespace mtk{
00066
00076 class Interp2D {
00077 public:
00079   Interp2D();
00080
00086   Interp2D(const Interp2D &interp);
00087
00089   ~Interp2D();
00090
00096   DenseMatrix ConstructInterp2D(const UniStgGrid2D &grid,
00097                                int order_accuracy = kDefaultOrderAccuracy,

```

```

00098                                     Real mimetic_threshold =
00099                                     kDefaultMimeticThreshold);
00105     DenseMatrix ReturnAsDenseMatrix();
00106
00107     private:
00108     DenseMatrix interpolator_;
00109
00110     int order_accuracy_;
00111
00112     Real mimetic_threshold_;
00113 };
00114 }
00115 #endif // End of: MTK_INCLUDE_MTK_INTERP_2D_H_

```

17.39 include/mtk_lap_1d.h File Reference


Includes the definition of the class Lap1D.

```


#include "mtk_dense_matrix.h"
#include "mtk_uni_stg_grid_1d.h"

```

Include dependency graph for mtk_lap_1d.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [mtk::Lap1D](#)
Implements a 1D mimetic Laplacian operator.

Namespaces

- [mtk](#)
Mimetic Methods Toolkit namespace.

17.39.1 Detailed Description

This class implements a 1D Laplacian operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (CBSA).

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_lap_1d.h](#).

17.40 mtk_lap_1d.h

```

00001
00011 /*
00012 Copyright (C) 2015, Computational Science Research Center, San Diego State
00013 University. All rights reserved.
00014
00015 Redistribution and use in source and binary forms, with or without modification,
00016 are permitted provided that the following conditions are met:
00017

```

```

00018 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00019 and a copy of the modified files should be reported once modifications are
00020 completed, unless these modifications are made through the project's GitHub
00021 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00022 should be developed and included in any deliverable.
00023
00024 2. Redistributions of source code must be done through direct
00025 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00026
00027 3. Redistributions in binary form must reproduce the above copyright notice,
00028 this list of conditions and the following disclaimer in the documentation and/or
00029 other materials provided with the distribution.
00030
00031 4. Usage of the binary form on proprietary applications shall require explicit
00032 prior written permission from the the copyright holders, and due credit should
00033 be given to the copyright holders.
00034
00035 5. Neither the name of the copyright holder nor the names of its contributors
00036 may be used to endorse or promote products derived from this software without
00037 specific prior written permission.
00038
00039 The copyright holders provide no reassurances that the source code provided does
00040 not infringe any patent, copyright, or any other intellectual property rights of
00041 third parties. The copyright holders disclaim any liability to any recipient for
00042 claims brought against recipient by any third party for infringement of that
00043 parties intellectual property rights.
00044
00045 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00046 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00047 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00048 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00049 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00050 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00051 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00052 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00053 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00054 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00055 */
00056
00057 #ifndef MTK_INCLUDE_LAP_1D_H_
00058 #define MTK_INCLUDE_LAP_1D_H_
00059
00060 #include "mtk_dense_matrix.h"
00061
00062 #include "mtk_uni_stg_grid_1d.h"
00063
00064 namespace mtk {
00065
00066 class Lap1D {
00067 public:
00068     friend std::ostream& operator <<(std::ostream& stream, Lap1D &in);
00069
00070     Lap1D();
00071
00072     Lap1D(const Lap1D &lap);
00073
00074     ~Lap1D();
00075
00076     int order_accuracy() const;
00077
00078     Real mimetic_threshold() const;
00079
00080     Real delta() const;
00081
00082     bool ConstructLap1D(int order_accuracy = kDefaultOrderAccuracy,
00083                        Real mimetic_threshold = kDefaultMimeticThreshold);
00084
00085     DenseMatrix ReturnAsDenseMatrix(const
00086     UniStgGrid1D &grid) const;
00087
00088     const mtk::Real* data(const UniStgGrid1D &grid) const;
00089
00090 private:
00091     int order_accuracy_;
00092     int laplacian_length_;
00093
00094     Real *laplacian_;
00095
00096     mutable Real delta_;
00097
00098     Real mimetic_threshold_;

```



```

00146 };
00147 }
00148 #endif // End of: MTK_INCLUDE_LAP_1D_H_

```

17.41 include/mtk_lap_2d.h File Reference


Includes the implementation of the class Lap2D.

```


#include "mtk_roots.h"
#include "mtk_dense_matrix.h"
#include "mtk_uni_stg_grid_2d.h"

```

Include dependency graph for mtk_lap_2d.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [mtk::Lap2D](#)
Implements a 2D mimetic Laplacian operator.

Namespaces

- [mtk](#)
Mimetic Methods Toolkit namespace.

17.41.1 Detailed Description

This class implements a 2D Laplacian operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (CBSA).

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_lap_2d.h](#).

17.42 mtk_lap_2d.h

```

00001
00011 /*
00012 Copyright (C) 2015, Computational Science Research Center, San Diego State
00013 University. All rights reserved.
00014
00015 Redistribution and use in source and binary forms, with or without modification,
00016 are permitted provided that the following conditions are met:
00017
00018 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00019 and a copy of the modified files should be reported once modifications are
00020 completed, unless these modifications are made through the project's GitHub
00021 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications

```

```


00022 should be developed and included in any deliverable.
00023
00024 2. Redistributions of source code must be done through direct
00025 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00026
00027 3. Redistributions in binary form must reproduce the above copyright notice,
00028 this list of conditions and the following disclaimer in the documentation and/or
00029 other materials provided with the distribution.
00030
00031 4. Usage of the binary form on proprietary applications shall require explicit
00032 prior written permission from the the copyright holders, and due credit should
00033 be given to the copyright holders.
00034
00035 5. Neither the name of the copyright holder nor the names of its contributors
00036 may be used to endorse or promote products derived from this software without
00037 specific prior written permission.
00038
00039 The copyright holders provide no reassurances that the source code provided does
00040 not infringe any patent, copyright, or any other intellectual property rights of
00041 third parties. The copyright holders disclaim any liability to any recipient for
00042 claims brought against recipient by any third party for infringement of that
00043 parties intellectual property rights.
00044
00045 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00046 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00047 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00048 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00049 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00050 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00051 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00052 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00053 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00054 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00055 */
00056
00057 #ifndef MTK_INCLUDE_MTK_LAP_2D_H_
00058 #define MTK_INCLUDE_MTK_LAP_2D_H_
00059
00060 #include "mtk_roots.h"
00061 #include "mtk_dense_matrix.h"
00062 #include "mtk_uni_stg_grid_2d.h"
00063
00064 namespace mtk{
00065
00076 class Lap2D {
00077 public:
00078     Lap2D();
00079
00080     Lap2D(const Lap2D &lap);
00081
00082     ~Lap2D();
00083
00084     bool ConstructLap2D(const UniStgGrid2D &grid,
00085                        int order_accuracy = kDefaultOrderAccuracy,
00086                        Real mimetic_threshold = kDefaultMimeticThreshold);
00087
00088     DenseMatrix ReturnAsDenseMatrix() const;
00089
00090     Real *data() const;
00091
00092 private:
00093     DenseMatrix laplacian_;
00094
00095     int order_accuracy_;
00096     Real mimetic_threshold_;
00097 };
00098
00099 #endif // End of: MTK_INCLUDE_MTK_LAP_2D_H_

```


17.43 include/mtk_lap_3d.h File Reference

Includes the implementation of the class Lap3D.

```
#include "mtk_roots.h"
#include "mtk_dense_matrix.h"
#include "mtk_uni_stg_grid_2d.h"
Include dependency graph for mtk_lap_3d.h:
```



This graph shows which files directly or indirectly include this file:



Classes

- class `mtk::Lap3D`

Implements a 3D mimetic Laplacian operator.

Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

17.43.1 Detailed Description

This class implements a 3D Laplacian operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (CBSA).

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_lap_3d.h](#).

17.44 mtk_lap_3d.h

```

00001
00011 /*
00012 Copyright (C) 2015, Computational Science Research Center, San Diego State
00013 University. All rights reserved.
00014
00015 Redistribution and use in source and binary forms, with or without modification,
00016 are permitted provided that the following conditions are met:
00017
00018 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00019 and a copy of the modified files should be reported once modifications are
00020 completed, unless these modifications are made through the project's GitHub
00021 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00022 should be developed and included in any deliverable.
00023
00024 2. Redistributions of source code must be done through direct
00025 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00026
00027 3. Redistributions in binary form must reproduce the above copyright notice,
00028 this list of conditions and the following disclaimer in the documentation and/or
00029 other materials provided with the distribution.
00030
00031 4. Usage of the binary form on proprietary applications shall require explicit
00032 prior written permission from the the copyright holders, and due credit should
00033 be given to the copyright holders.
00034
00035 5. Neither the name of the copyright holder nor the names of its contributors
00036 may be used to endorse or promote products derived from this software without
00037 specific prior written permission.
00038
00039 The copyright holders provide no reassurances that the source code provided does
00040 not infringe any patent, copyright, or any other intellectual property rights of
00041 third parties. The copyright holders disclaim any liability to any recipient for
00042 claims brought against recipient by any third party for infringement of that
00043 parties intellectual property rights.
00044
00045 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00046 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00047 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00048 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00049 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00050 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00051 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00052 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00053 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00054 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00055 */
00056
00057 #ifndef MTK_INCLUDE_MTK_LAP_3D_H_
00058 #define MTK_INCLUDE_MTK_LAP_3D_H_
00059
00060 #include "mtk_roots.h"

```

```

00061 #include "mtk_dense_matrix.h"
00062 #include "mtk_uni_stg_grid_2d.h"
00063
00064 namespace mtk{
00065
00076 class Lap3D {
00077 public:
00079     UniStgGrid3D operator*(const UniStgGrid3D &grid) const;
00080
00082     Lap3D();
00083
00089     Lap3D(const Lap3D &lap);
00090
00092     ~Lap3D();
00093
00099     bool ConstructLap3D(const UniStgGrid3D &grid,
00100                        int order_accuracy = kDefaultOrderAccuracy,
00101                        Real mimetic_threshold = kDefaultMimeticThreshold);
00102
00108     DenseMatrix ReturnAsDenseMatrix() const;
00109
00115     Real *data() const;
00116
00117 private:
00118     DenseMatrix laplacian_;
00119
00120     int order_accuracy_;
00121
00122     Real mimetic_threshold_;
00123 };
00124 }
00125 #endif // End of: MTK_INCLUDE_MTK_LAP_3D_H_

```

17.45 include/mtk_lapack_adapter.h File Reference


Adapter class for the LAPACK API.

```


#include "mtk_roots.h"
#include "mtk_dense_matrix.h"
#include "mtk_uni_stg_grid_1d.h"
#include "mtk_uni_stg_grid_2d.h"

```

Include dependency graph for mtk_lapack_adapter.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [mtk::LAPACKAdapter](#)
Adapter class for the LAPACK API.

Namespaces

- [mtk](#)
Mimetic Methods Toolkit namespace.

17.45.1 Detailed Description

This class contains a collection of static classes, that posses direct access to the underlying structure of the matrices, thus allowing programmers to exploit some of the numerical methods implemented in the LAPACK.

The **LAPACK (Linear Algebra PACKage)** is written in Fortran 90 and provides routines for solving systems of simultaneous linear equations, least-squares solutions of linear systems of equations, eigenvalue problems, and singular value problems.

See also

<http://www.netlib.org/lapack/>

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_lapack_adapter.h](#).

17.46 mtk_lapack_adapter.h

```

00001
00019 /*
00020 Copyright (C) 2015, Computational Science Research Center, San Diego State
00021 University. All rights reserved.
00022
00023 Redistribution and use in source and binary forms, with or without modification,
00024 are permitted provided that the following conditions are met:
00025
00026 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00027 and a copy of the modified files should be reported once modifications are
  
```

```

00028 completed, unless these modifications are made through the project's GitHub
00029 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00030 should be developed and included in any deliverable.
00031
00032 2. Redistributions of source code must be done through direct
00033 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00034
00035 3. Redistributions in binary form must reproduce the above copyright notice,
00036 this list of conditions and the following disclaimer in the documentation and/or
00037 other materials provided with the distribution.
00038
00039 4. Usage of the binary form on proprietary applications shall require explicit
00040 prior written permission from the the copyright holders, and due credit should
00041 be given to the copyright holders.
00042
00043 5. Neither the name of the copyright holder nor the names of its contributors
00044 may be used to endorse or promote products derived from this software without
00045 specific prior written permission.
00046
00047 The copyright holders provide no reassurances that the source code provided does
00048 not infringe any patent, copyright, or any other intellectual property rights of
00049 third parties. The copyright holders disclaim any liability to any recipient for
00050 claims brought against recipient by any third party for infringement of that
00051 parties intellectual property rights.
00052
00053 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00054 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00055 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00056 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00057 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00058 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00059 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00060 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00061 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00062 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00063 */
00064
00065 #ifndef MTK_INCLUDE_LAPACK_ADAPTER_H_
00066 #define MTK_INCLUDE_LAPACK_ADAPTER_H_
00067
00068 #include "mtk_roots.h"
00069 #include "mtk_dense_matrix.h"
00070 #include "mtk_uni_stg_grid_ld.h"
00071 #include "mtk_uni_stg_grid_2d.h"
00072
00073 namespace mtk {
00074
00093 class LAPACKAdapter {
00094 public:
00105     static int SolveDenseSystem(mtk::DenseMatrix &mm,
00106                               mtk::Real *rhs);
00107
00118     static int SolveDenseSystem(mtk::DenseMatrix &mm,
00119                               mtk::DenseMatrix &rr);
00120
00131     static int SolveDenseSystem(mtk::DenseMatrix &mm,
00132                               mtk::UniStgGrid1D &rhs);
00133
00145     static int SolveDenseSystem(mtk::DenseMatrix &mm,
00146                               mtk::UniStgGrid2D &rhs);
00147
00159     static int SolveRectangularDenseSystem(const
mtk::DenseMatrix &aa,
00160                                           mtk::Real *ob_,
00161                                           int ob_ld_);
00162
00174     static mtk::DenseMatrix QRFactorDenseMatrix(
DenseMatrix &matrix);
00175 };
00176 }
00177 #endif // End of: MTK_INCLUDE_LAPACK_ADAPTER_H_


```

17.47 include/mtk_matrix.h File Reference

Definition of the representation of a matrix in the MTK.


```
#include <iostream>
#include "mtk_roots.h"
#include "mtk_enums.h"
```

Include dependency graph for mtk_matrix.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [mtk::Matrix](#)

Definition of the representation of a matrix in the MTK.

Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

17.47.1 Detailed Description

Definition of the representation for the matrices implemented in the MTK.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_matrix.h](#).

17.48 mtk_matrix.h

```

00001
00010 /*
00011 Copyright (C) 2015, Computational Science Research Center, San Diego State
00012 University. All rights reserved.
00013
00014 Redistribution and use in source and binary forms, with or without modification,
00015 are permitted provided that the following conditions are met:
00016
00017 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00018 and a copy of the modified files should be reported once modifications are
00019 completed, unless these modifications are made through the project's GitHub
00020 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00021 should be developed and included in any deliverable.
00022
00023 2. Redistributions of source code must be done through direct
00024 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00025
00026 3. Redistributions in binary form must reproduce the above copyright notice,
00027 this list of conditions and the following disclaimer in the documentation and/or
00028 other materials provided with the distribution.
00029
00030 4. Usage of the binary form on proprietary applications shall require explicit
00031 prior written permission from the the copyright holders, and due credit should
00032 be given to the copyright holders.
00033
00034 5. Neither the name of the copyright holder nor the names of its contributors
00035 may be used to endorse or promote products derived from this software without
00036 specific prior written permission.
00037
00038 The copyright holders provide no reassurances that the source code provided does
00039 not infringe any patent, copyright, or any other intellectual property rights of
00040 third parties. The copyright holders disclaim any liability to any recipient for
00041 claims brought against recipient by any third party for infringement of that
00042 parties intellectual property rights.
00043
00044 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00045 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00046 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00047 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00048 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00049 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00050 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00051 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00052 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00053 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00054 */
00055
00056 #ifndef MTK_INCLUDE_MATRIX_H_
00057 #define MTK_INCLUDE_MATRIX_H_
00058
00059 #include <iostream>
00060
00061 #include "mtk_roots.h"
00062 #include "mtk_enums.h"
00063
00064 namespace mtk {
00065
00075 class Matrix {
00076 public:
00077     Matrix();
00078
00079     Matrix(const Matrix &in);
00080
00081     ~Matrix() noexcept ;
00082
00083     MatrixStorage storage() const noexcept;
00084
00085     MatrixOrdering ordering() const noexcept;
00086
00087     int num_rows() const noexcept;
00088
00089     int num_cols() const noexcept;
00090
00091     int num_values() const noexcept;
00092
00093     int ld() const noexcept;
00094
00095     int num_zero() const noexcept;

```

```

00142
00148     int num_non_zero() const noexcept;
00149
00157     int num_null() const noexcept;
00158
00166     int num_non_null() const noexcept;
00167
00173     int kl() const noexcept;
00174
00180     int ku() const noexcept;
00181
00187     int bandwidth() const noexcept;
00188
00196     Real abs_density() const noexcept;
00197
00205     Real rel_density() const noexcept;
00206
00214     Real abs_sparsity() const noexcept;
00215
00223     Real rel_sparsity() const noexcept;
00224
00232     void set_storage(const MatrixStorage &tt) noexcept;
00233
00241     void set_ordering(const MatrixOrdering &oo) noexcept;
00242
00248     void set_num_rows(const int &num_rows) noexcept;
00249
00255     void set_num_cols(const int &num_cols) noexcept;
00256
00262     void set_num_zero(const int &in) noexcept;
00263
00269     void set_num_null(const int &in) noexcept;
00270
00272     void IncreaseNumZero() noexcept;
00273
00275     void IncreaseNumNull() noexcept;
00276
00277 private:
00278     MatrixStorage storage_;
00279
00280     MatrixOrdering ordering_;
00281
00282     int num_rows_;
00283     int num_cols_;
00284     int num_values_;
00285     int ld_;
00286
00287     int num_zero_;
00288     int num_non_zero_;
00289     int num_null_;
00290     int num_non_null_;
00291
00292     int kl_;
00293     int ku_;
00294     int bandwidth_;
00295
00296     Real abs_density_;
00297     Real rel_density_;
00298     Real abs_sparsity_;
00299     Real rel_sparsity_;
00300 };
00301 }
00302 #endif // End of: MTK_INCLUDE_MATRIX_H_

```

17.49 include/mtk_quad_1d.h File Reference


Includes the definition of the class Quad1D.

```


#include <iostream>
#include <iomanip>
#include <vector>

```

Include dependency graph for `mtk_quad_1d.h`:



This graph shows which files directly or indirectly include this file:



Classes

- class [mtk::Quad1D](#)
Implements a 1D mimetic quadrature.

Namespaces

- [mtk](#)
Mimetic Methods Toolkit namespace.

17.49.1 Detailed Description

This class implements a 1D quadrature solver based on the mimetic discretization of the gradient operator.

See also

[mtk::Grad1D](#)

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Todo Implement this class.

Definition in file [mtk_quad_1d.h](#).

17.50 mtk_quad_1d.h

```

00001
00015 /*
00016 Copyright (C) 2015, Computational Science Research Center, San Diego State
00017 University. All rights reserved.
00018
00019 Redistribution and use in source and binary forms, with or without modification,
00020 are permitted provided that the following conditions are met:
00021
00022 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00023 and a copy of the modified files should be reported once modifications are
00024 completed, unless these modifications are made through the project's GitHub
00025 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00026 should be developed and included in any deliverable.
00027
00028 2. Redistributions of source code must be done through direct
00029 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00030
00031 3. Redistributions in binary form must reproduce the above copyright notice,
00032 this list of conditions and the following disclaimer in the documentation and/or
00033 other materials provided with the distribution.
00034
00035 4. Usage of the binary form on proprietary applications shall require explicit
00036 prior written permission from the the copyright holders, and due credit should
00037 be given to the copyright holders.
00038
00039 5. Neither the name of the copyright holder nor the names of its contributors
00040 may be used to endorse or promote products derived from this software without
00041 specific prior written permission.
00042
00043 The copyright holders provide no reassurances that the source code provided does
00044 not infringe any patent, copyright, or any other intellectual property rights of
00045 third parties. The copyright holders disclaim any liability to any recipient for
00046 claims brought against recipient by any third party for infringement of that
00047 parties intellectual property rights.
00048
00049 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00050 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00051 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00052 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00053 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00054 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00055 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00056 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00057 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00058 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00059 */
00060
00061 #ifndef MTK_INCLUDE_QUAD_1D_H_
00062 #define MTK_INCLUDE_QUAD_1D_H_
00063
00064 #include <iostream>
00065 #include <iomanip>
00066
00067 #include <vector>
00068
00069 namespace mtk {
00070
00081 class Quad1D {
00082 public:
00084     friend std::ostream& operator <<(std::ostream& stream, Quad1D &in);
00085
00087     Quad1D();
00088
00094     Quad1D(const Quad1D &quad);
00095

```

```

00097 ~Quad1D();
00098
00104 int degree_approximation() const;
00105
00111 Real *weights() const;
00112
00121 Real Integrate(Real (*Integrand)(Real xx), UniStgGrid1D grid) const;
00122
00123 private:
00124 int degree_approximation_;
00125
00126 std::vector<Real> weights_;
00127 };
00128 }
00129 #endif // End of: MTK_INCLUDE_QUAD_1D_H_

```

17.51 include/mtk_robin_bc_descriptor_1d.h File Reference


Impose Robin boundary conditions on the operators and on the grids.

```


#include <vector>
#include "mtk_roots.h"
#include "mtk_dense_matrix.h"
#include "mtk_uni_stg_grid_1d.h"
#include "mtk_lap_1d.h"

```

Include dependency graph for mtk_robin_bc_descriptor_1d.h:



This graph shows which files directly or indirectly include this file:



Classes

- class `mtk::RobinBCDescriptor1D`
Impose Robin boundary conditions on the operators and on the grids.

Namespaces

- `mtk`
Mimetic Methods Toolkit namespace.

Typedefs

- typedef `Real(* mtk::CoefficientFunction0D)(const Real &tt)`
A function of a BC coefficient evaluated on a 0D domain and time.

17.51.1 Detailed Description

This class presents an interface for the user to specify Robin boundary conditions on 1D mimetic operators and the grids they are acting on.

Def. Let $u(\mathbf{x}, t) : \Omega \times [t_0, t_n] \mapsto \mathbb{R}$ be the solution to an ordinary or partial differential equation of interest. We say that u satisfies a **Robin boundary condition** on $\partial\Omega$ if and only if there exists $\beta(\mathbf{x}, t) : \Omega \times [t_0, t_n] \mapsto \mathbb{R}$ so that:

$$\forall t \in [t_0, t_n] \forall \mathbf{x} \in \partial\Omega : \delta(\mathbf{x}, t)u(\mathbf{x}, t) + \eta(\mathbf{x}, t)(\hat{\mathbf{n}} \cdot \nabla u) = \beta(\mathbf{x}, t).$$

Intuitively, a **Robin boundary condition** is a constraint that must be satisfied by any linear combination of any scalar field u and its first normal derivative, in order for u to represent a unique solution to a given ordinary or partial differential equation of interest.

In a 1D context ($\partial\Omega = \{a, b\} \subset \mathbb{R}$), this condition can be written as follows:

$$\delta_a(a, t)u(a, t) - \eta_a(a, t)u'(a, t) = \beta_a(a, t),$$

$$\delta_b(b,t)u(b,t) + \eta_b(b,t)u'(b,t) = \beta_b(b,t).$$

Instances of this class receive information about the coefficient functions and each condition for any subset of the boundary (west and east, in 1D). These instances then handle the complexity of placing the coefficients in the differentiation matrices and the condition in the grids.

See also

<http://mathworld.wolfram.com/NormalVector.html>

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_robin_bc_descriptor_1d.h](#).

17.52 mtk_robin_bc_descriptor_1d.h

```

00001
00043 /*
00044 Copyright (C) 2015, Computational Science Research Center, San Diego State
00045 University. All rights reserved.
00046
00047 Redistribution and use in source and binary forms, with or without modification,
00048 are permitted provided that the following conditions are met:
00049
00050 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00051 and a copy of the modified files should be reported once modifications are
00052 completed, unless these modifications are made through the project's GitHub
00053 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00054 should be developed and included in any deliverable.
00055
00056 2. Redistributions of source code must be done through direct
00057 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00058
00059 3. Redistributions in binary form must reproduce the above copyright notice,
00060 this list of conditions and the following disclaimer in the documentation and/or
00061 other materials provided with the distribution.
00062
00063 4. Usage of the binary form on proprietary applications shall require explicit
00064 prior written permission from the the copyright holders, and due credit should
00065 be given to the copyright holders.
00066
00067 5. Neither the name of the copyright holder nor the names of its contributors
00068 may be used to endorse or promote products derived from this software without
00069 specific prior written permission.
00070
00071 The copyright holders provide no reassurances that the source code provided does
00072 not infringe any patent, copyright, or any other intellectual property rights of
00073 third parties. The copyright holders disclaim any liability to any recipient for
00074 claims brought against recipient by any third party for infringement of that
00075 parties intellectual property rights.
00076
00077 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00078 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00079 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00080 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00081 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00082 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00083 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00084 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00085 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00086 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00087 */
00088
00089 #include <vector>
00090
00091 #include "mtk_roots.h"
00092 #include "mtk_dense_matrix.h"
00093 #include "mtk_uni_stg_grid_1d.h"

```



```

00094 #include "mtk_lap_1d.h"
00095
00096 #ifndef MTK_INCLUDE_ROBIN_BC_DESCRIPTOR_1D_H_
00097 #define MTK_INCLUDE_ROBIN_BC_DESCRIPTOR_1D_H_
00098
00099 namespace mtk {
00111 typedef Real (*CoefficientFunction0D)(const Real &tt);
00112
00155 class RobinBCDescriptor1D {
00156 public:
00158     RobinBCDescriptor1D();
00159
00165     RobinBCDescriptor1D(const RobinBCDescriptor1D &desc);
00166
00168     ~RobinBCDescriptor1D() noexcept;
00169
00175     int highest_order_diff_west() const noexcept;
00176
00182     int highest_order_diff_east() const noexcept;
00183
00189     void PushBackWestCoeff(CoefficientFunction0D cw);
00190
00196     void PushBackEastCoeff(CoefficientFunction0D ce);
00197
00203     void set_west_condition(Real (*west_condition)(const
Real &tt)) noexcept;
00204
00210     void set_east_condition(Real (*east_condition)(const
Real &tt)) noexcept;
00211
00221     bool ImposeOnLaplacianMatrix(const Lap1D &lap,
00222                                 DenseMatrix &matrix,
00223                                 const Real &time = mtk::kZero) const;
00230     void ImposeOnGrid(UniStgGrid1D &grid, const Real &time =
mtk::kZero) const;
00231
00232 private:
00233     int highest_order_diff_west_;
00234     int highest_order_diff_east_;
00235
00236     std::vector<CoefficientFunction0D> west_coefficients_;
00237     std::vector<CoefficientFunction0D> east_coefficients_;
00238
00239     Real (*west_condition_)(const Real &tt);
00240     Real (*east_condition_)(const Real &tt);
00241 };
00242
00243 #endif // End of: MTK_INCLUDE_ROBIN_BC_DESCRIPTOR_1D_H_

```

17.53 include/mtk_robin_bc_descriptor_2d.h File Reference


Impose Robin boundary conditions on the operators and on the grids.

```


#include "mtk_roots.h"
#include "mtk_dense_matrix.h"
#include "mtk_lap_2d.h"
#include "mtk_uni_stg_grid_2d.h"

```

Include dependency graph for `mtk_robin_bc_descriptor_2d.h`:



This graph shows which files directly or indirectly include this file:



Classes

- class [mtk::RobinBCDescriptor2D](#)

Impose Robin boundary conditions on the operators and on the grids.

Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

Typedefs

- typedef Real(* [mtk::CoefficientFunction1D](#))(const Real &xx, const Real &tt)

A function of a BC coefficient evaluated on a 1D domain and time.

17.53.1 Detailed Description

This class presents an interface for the user to specify Robin boundary conditions on 2D mimetic operators and the grids they are acting on.

Def. Let $u(\mathbf{x}, t) : \Omega \times [t_0, t_n] \mapsto \mathbb{R}$ be the solution to an ordinary or partial differential equation of interest. We say that u satisfies a **Robin boundary condition** on $\partial\Omega$ if and only if there exists $\beta(\mathbf{x}, t) : \Omega \times [t_0, t_n] \mapsto \mathbb{R}$ so that:

$$\forall t \in [t_0, t_n] \forall \mathbf{x} \in \partial\Omega : \delta(\mathbf{x}, t)u(\mathbf{x}, t) + \eta(\mathbf{x}, t)(\hat{\mathbf{n}} \cdot \nabla u) = \beta(\mathbf{x}, t).$$

Intuitively, a **Robin boundary condition** is a constraint that must be satisfied by any linear combination of any scalar field u and its first normal derivative, in order for u to represent a unique solution to a given ordinary or partial differential equation of interest.

Instances of this class receive information about the coefficient functions and each condition for any subset of the boundary (west, east, south and north in 2D). These instances then handle the complexity of placing the coefficients in the differentiation matrices and the conditions in the grids.

See also

<http://mathworld.wolfram.com/NormalVector.html>

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_robin_bc_descriptor_2d.h](#).

17.54 mtk_robin_bc_descriptor_2d.h

```
00001
00034 /*
00035 Copyright (C) 2015, Computational Science Research Center, San Diego State
00036 University. All rights reserved.
00037
00038 Redistribution and use in source and binary forms, with or without modification,
00039 are permitted provided that the following conditions are met:
00040
00041 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00042 and a copy of the modified files should be reported once modifications are
00043 completed, unless these modifications are made through the project's GitHub
00044 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00045 should be developed and included in any deliverable.
00046
00047 2. Redistributions of source code must be done through direct
00048 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00049
```

```

00050 3. Redistributions in binary form must reproduce the above copyright notice,
00051 this list of conditions and the following disclaimer in the documentation and/or
00052 other materials provided with the distribution.
00053
00054 4. Usage of the binary form on proprietary applications shall require explicit
00055 prior written permission from the the copyright holders, and due credit should
00056 be given to the copyright holders.
00057
00058 5. Neither the name of the copyright holder nor the names of its contributors
00059 may be used to endorse or promote products derived from this software without
00060 specific prior written permission.
00061
00062 The copyright holders provide no reassurances that the source code provided does
00063 not infringe any patent, copyright, or any other intellectual property rights of
00064 third parties. The copyright holders disclaim any liability to any recipient for
00065 claims brought against recipient by any third party for infringement of that
00066 parties intellectual property rights.
00067
00068 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00069 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00070 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00071 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00072 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00073 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00074 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00075 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00076 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00077 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00078 */
00079
00080 #ifndef MTK_INCLUDE_ROBIN_BC_DESCRIPTOR_2D_H_
00081 #define MTK_INCLUDE_ROBIN_BC_DESCRIPTOR_2D_H_
00082
00083 #include "mtk_roots.h"
00084 #include "mtk_dense_matrix.h"
00085 #include "mtk_lap_2d.h"
00086 #include "mtk_uni_stg_grid_2d.h"
00087
00088 namespace mtk{
00089
00097 typedef Real (*CoefficientFunction1D)(const Real &xx, const
    Real &tt);
00098
00132 class RobinBCDescriptor2D {
00133 public:
00135     RobinBCDescriptor2D();
00136
00142     RobinBCDescriptor2D(const RobinBCDescriptor2D &desc);
00143
00145     ~RobinBCDescriptor2D() noexcept;
00146
00152     int highest_order_diff_west() const noexcept;
00153
00159     int highest_order_diff_east() const noexcept;
00160
00166     int highest_order_diff_south() const noexcept;
00167
00173     int highest_order_diff_north() const noexcept;
00174
00181     void PushBackWestCoeff(CoefficientFunction1D cw);
00182
00189     void PushBackEastCoeff(CoefficientFunction1D ce);
00190
00197     void PushBackSouthCoeff(CoefficientFunction1D cs);
00198
00205     void PushBackNorthCoeff(CoefficientFunction1D cn);
00206
00213     void set_west_condition(Real (*west_condition)(const
    Real &yy,
00214                                     const Real &tt)) noexcept;
00215
00222     void set_east_condition(Real (*east_condition)(const
    Real &yy,
00223                                     const Real &tt)) noexcept;
00224
00231     void set_south_condition(Real (*south_condition)(const
    Real &xx,
00232                                     const Real &tt)) noexcept;
00233
00240     void set_north_condition(Real (*north_condition)(const
    Real &xx,

```

```

00241                                     const Real &tt)) noexcept;
00242
00251 bool ImposeOnLaplacianMatrix(const Lap2D &lap,
00252                             const UniStgGrid2D &grid,
00253                             DenseMatrix &matrix,
00254                             const Real &time = kZero) const;
00261 void ImposeOnGrid(UniStgGrid2D &grid, const Real &time =
    kZero) const;
00262
00263 private:
00272 bool ImposeOnSouthBoundaryNoSpace(const Lap2D &lap,
00273                                   const UniStgGrid2D &grid,
00274                                   DenseMatrix &matrix,
00275                                   const Real &time = kZero) const;
00284 bool ImposeOnNorthBoundaryNoSpace(const Lap2D &lap,
00285                                   const UniStgGrid2D &grid,
00286                                   DenseMatrix &matrix,
00287                                   const Real &time = kZero) const;
00296 bool ImposeOnWestBoundaryNoSpace(const Lap2D &lap,
00297                                   const UniStgGrid2D &grid,
00298                                   DenseMatrix &matrix,
00299                                   const Real &time = kZero) const;
00308 bool ImposeOnEastBoundaryNoSpace(const Lap2D &lap,
00309                                   const UniStgGrid2D &grid,
00310                                   DenseMatrix &matrix,
00311                                   const Real &time = kZero) const;
00320 bool ImposeOnSouthBoundaryWithSpace(const Lap2D &lap,
00321                                     const UniStgGrid2D &grid,
00322                                     DenseMatrix &matrix,
00323                                     const Real &time = kZero) const;
00332 bool ImposeOnNorthBoundaryWithSpace(const Lap2D &lap,
00333                                     const UniStgGrid2D &grid,
00334                                     DenseMatrix &matrix,
00335                                     const Real &time = kZero) const;
00344 bool ImposeOnWestBoundaryWithSpace(const Lap2D &lap,
00345                                     const UniStgGrid2D &grid,
00346                                     DenseMatrix &matrix,
00347                                     const Real &time = kZero) const;
00356 bool ImposeOnEastBoundaryWithSpace(const Lap2D &lap,
00357                                     const UniStgGrid2D &grid,
00358                                     DenseMatrix &matrix,
00359                                     const Real &time = kZero) const;
00360
00361 int highest_order_diff_west_;
00362 int highest_order_diff_east_;
00363 int highest_order_diff_south_;
00364 int highest_order_diff_north_;
00365
00366 std::vector<CoefficientFunction1D> west_coefficients_;
00367 std::vector<CoefficientFunction1D> east_coefficients_;
00368 std::vector<CoefficientFunction1D> south_coefficients_;
00369 std::vector<CoefficientFunction1D> north_coefficients_;
00370
00371 Real (*west_condition_)(const Real &xx, const Real &tt);
00372 Real (*east_condition_)(const Real &xx, const Real &tt);
00373 Real (*south_condition_)(const Real &yy, const Real &tt);
00374 Real (*north_condition_)(const Real &yy, const Real &tt);
00375 };
00376 }
00377 #endif // End of: MTK_INCLUDE_ROBIN_BC_DESCRIPTOR_2D_H_

```

17.55 include/mtk_robin_bc_descriptor_3d.h File Reference


Impose Robin boundary conditions on the operators and on the grids.

```


#include "mtk_roots.h"
#include "mtk_dense_matrix.h"
#include "mtk_lap_2d.h"
#include "mtk_uni_stg_grid_2d.h"

```

Include dependency graph for `mtk_robin_bc_descriptor_3d.h`:



This graph shows which files directly or indirectly include this file:



Classes

- class [mtk::RobinBCDescriptor3D](#)

Impose Robin boundary conditions on the operators and on the grids.

Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

Typedefs

- typedef Real(* [mtk::CoefficientFunction2D](#))(const Real &xx, const Real &yy, const Real &tt)

A function of a BC coefficient evaluated on a 2D domain and time.

17.55.1 Detailed Description

This class presents an interface for the user to specify Robin boundary conditions on 3D mimetic operators and the grids they are acting on.

Def. Let $u(\mathbf{x}, t) : \Omega \times [t_0, t_n] \mapsto \mathbb{R}$ be the solution to an ordinary or partial differential equation of interest. We say that u satisfies a **Robin boundary condition** on $\partial\Omega$ if and only if there exists $\beta(\mathbf{x}, t) : \Omega \times [t_0, t_n] \mapsto \mathbb{R}$ so that:

$$\forall t \in [t_0, t_n] \forall \mathbf{x} \in \partial\Omega : \delta(\mathbf{x}, t)u(\mathbf{x}, t) + \eta(\mathbf{x}, t)(\hat{\mathbf{n}} \cdot \nabla u) = \beta(\mathbf{x}, t).$$

Intuitively, a **Robin boundary condition** is a constraint that must be satisfied by any linear combination of any scalar field u and its first normal derivative, in order for u to represent a unique solution to a given ordinary or partial differential equation of interest.

Instances of this class receive information about the coefficient functions and each condition for any subset of the boundary. These instances then handle the complexity of placing the coefficients in the differentiation matrices and the conditions in the grids.

See also

<http://mathworld.wolfram.com/NormalVector.html>

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_robin_bc_descriptor_3d.h](#).

17.56 mtk_robin_bc_descriptor_3d.h

```
00001
00034 /*
00035 Copyright (C) 2015, Computational Science Research Center, San Diego State
00036 University. All rights reserved.
00037
00038 Redistribution and use in source and binary forms, with or without modification,
00039 are permitted provided that the following conditions are met:
00040
00041 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00042 and a copy of the modified files should be reported once modifications are
00043 completed, unless these modifications are made through the project's GitHub
00044 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00045 should be developed and included in any deliverable.
00046
00047 2. Redistributions of source code must be done through direct
00048 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00049
```

```

00050 3. Redistributions in binary form must reproduce the above copyright notice,
00051 this list of conditions and the following disclaimer in the documentation and/or
00052 other materials provided with the distribution.
00053
00054 4. Usage of the binary form on proprietary applications shall require explicit
00055 prior written permission from the the copyright holders, and due credit should
00056 be given to the copyright holders.
00057
00058 5. Neither the name of the copyright holder nor the names of its contributors
00059 may be used to endorse or promote products derived from this software without
00060 specific prior written permission.
00061
00062 The copyright holders provide no reassurances that the source code provided does
00063 not infringe any patent, copyright, or any other intellectual property rights of
00064 third parties. The copyright holders disclaim any liability to any recipient for
00065 claims brought against recipient by any third party for infringement of that
00066 parties intellectual property rights.
00067
00068 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00069 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00070 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00071 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00072 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00073 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00074 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00075 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00076 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00077 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00078 */
00079
00080 #ifndef MTK_INCLUDE_ROBIN_BC_DESCRIPTOR_3D_H_
00081 #define MTK_INCLUDE_ROBIN_BC_DESCRIPTOR_3D_H_
00082
00083 #include "mtk_roots.h"
00084 #include "mtk_dense_matrix.h"
00085 #include "mtk_lap_2d.h"
00086 #include "mtk_uni_stg_grid_2d.h"
00087
00088 namespace mtk{
00089
00097 typedef Real (*CoefficientFunction2D) (const Real &xx,
00098                                       const Real &yy,
00099                                       const Real &tt);
00100
00134 class RobinBCDescriptor3D {
00135 public:
00137   RobinBCDescriptor3D();
00138
00144   RobinBCDescriptor3D(const RobinBCDescriptor3D &desc);
00145
00147   ~RobinBCDescriptor3D() noexcept;
00148
00154   int highest_order_diff_west() const noexcept;
00155
00156   // ...
00157
00164   void PushBackWestCoeff(CoefficientFunction2D cw);
00165
00166   // ...
00167
00174   void set_west_condition(Real (*west_condition) (const
Real &xx,
00175                                                         const Real &yy,
00176                                                         const Real &tt)) noexcept;
00177
00178   // ...
00179
00188   bool ImposeOnLaplacianMatrix(const Lap3D &lap,
00189                                const UniStgGrid3D &grid,
00190                                DenseMatrix &matrix,
00191                                const Real &time = kZero) const;
00198   void ImposeOnGrid(UniStgGrid3D &grid, const Real &time =
kZero) const;
00199
00200 private:
00209   bool ImposeOnSouthBoundaryNoSpace(const Lap2D &lap,
00210                                     const UniStgGrid2D &grid,
00211                                     DenseMatrix &matrix,
00212                                     const Real &time = kZero) const;
00221   bool ImposeOnNorthBoundaryNoSpace(const Lap2D &lap,
00222                                     const UniStgGrid2D &grid,

```



```


00223         DenseMatrix &matrix,
00224         const Real &time = kZero) const;
00233 bool ImposeOnWestBoundaryNoSpace(const Lap2D &lap,
00234         const UniStgGrid2D &grid,
00235         DenseMatrix &matrix,
00236         const Real &time = kZero) const;
00245 bool ImposeOnEastBoundaryNoSpace(const Lap2D &lap,
00246         const UniStgGrid2D &grid,
00247         DenseMatrix &matrix,
00248         const Real &time = kZero) const;
00257 bool ImposeOnSouthBoundaryWithSpace(const Lap2D &lap,
00258         const UniStgGrid2D &grid,
00259         DenseMatrix &matrix,
00260         const Real &time = kZero) const;
00269 bool ImposeOnNorthBoundaryWithSpace(const Lap2D &lap,
00270         const UniStgGrid2D &grid,
00271         DenseMatrix &matrix,
00272         const Real &time = kZero) const;
00281 bool ImposeOnWestBoundaryWithSpace(const Lap2D &lap,
00282         const UniStgGrid2D &grid,
00283         DenseMatrix &matrix,
00284         const Real &time = kZero) const;
00293 bool ImposeOnEastBoundaryWithSpace(const Lap2D &lap,
00294         const UniStgGrid2D &grid,
00295         DenseMatrix &matrix,
00296         const Real &time = kZero) const;
00297
00298 int highest_order_diff_west_;
00299 int highest_order_diff_east_;
00300 int highest_order_diff_south_;
00301 int highest_order_diff_north_;
00302 int highest_order_diff_bottom_;
00303 int highest_order_diff_top_;
00304
00305 std::vector<CoefficientFunction2D> west_coefficients_;
00306 std::vector<CoefficientFunction2D> east_coefficients_;
00307 std::vector<CoefficientFunction2D> south_coefficients_;
00308 std::vector<CoefficientFunction2D> north_coefficients_;
00309 std::vector<CoefficientFunction2D> bottom_coefficients_;
00310 std::vector<CoefficientFunction2D> top_coefficients_;
00311
00312 Real (*west_condition_)(const Real &xx,
00313         const Real &yy,
00314         const Real &tt);
00315 Real (*east_condition_)(const Real &xx,
00316         const Real &yy,
00317         const Real &tt);
00318 Real (*south_condition_)(const Real &xx,
00319         const Real &yy,
00320         const Real &tt);
00321 Real (*north_condition_)(const Real &xx,
00322         const Real &yy,
00323         const Real &tt);
00324 Real (*bottom_condition_)(const Real &xx,
00325         const Real &yy,
00326         const Real &tt);
00327 Real (*top_condition_)(const Real &xx,
00328         const Real &yy,
00329         const Real &tt);
00330 };
00331 }
00332 #endif // End of: MTK_INCLUDE_ROBIN_BC_DESCRIPTOR_3D_H_

```

17.57 include/mtk_roots.h File Reference

Fundamental definitions to be used across all classes of the MTK.

This graph shows which files directly or indirectly include this file:



Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

Typedefs

- typedef float [mtk::Real](#)

Users can simply change this to build a double- or single-precision MTK.

Variables

- const float [mtk::kZero](#) {0.0f}
MTK's zero defined according to selective compilation.
- const float [mtk::kOne](#) {1.0f}
MTK's one defined according to selective compilation.
- const float [mtk::kTwo](#) {2.0f}
MTK's two defined according to selective compilation.
- const float [mtk::kDefaultTolerance](#) {1e-7f}
Considered tolerance for comparisons in numerical methods.
- const int [mtk::kDefaultOrderAccuracy](#) {2}
Default order of accuracy for mimetic operators.
- const float [mtk::kDefaultMimeticThreshold](#) {1e-6f}
Default tolerance for higher-order mimetic operators.
- const int [mtk::kCriticalOrderAccuracyDiv](#) {8}
At this order (and higher) we must use the CBSA to construct.
- const int [mtk::kCriticalOrderAccuracyGrad](#) {10}
At this order (and higher) we must use the CBSA to construct.

17.57.1 Detailed Description

This file contains the fundamental definitions that classes of the MTK rely on to be implemented. Examples of these definitions are the definition of fundamental data types, and global variables affecting the construction of mimetic operators, among others.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at sciences dot sdsu dot edu

Todo Documentation should (better?) capture effects from selective compilation.

Todo Test selective precision mechanisms.

Definition in file [mtk_roots.h](#).

17.58 mtk_roots.h

```

00001
00017 /*
00018 Copyright (C) 2015, Computational Science Research Center, San Diego State
00019 University. All rights reserved.
00020
00021 Redistribution and use in source and binary forms, with or without modification,
00022 are permitted provided that the following conditions are met:
00023
00024 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00025 and a copy of the modified files should be reported once modifications are
00026 completed, unless these modifications are made through the project's GitHub
00027 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00028 should be developed and included in any deliverable.
00029
00030 2. Redistributions of source code must be done through direct
00031 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00032
00033 3. Redistributions in binary form must reproduce the above copyright notice,
00034 this list of conditions and the following disclaimer in the documentation and/or
00035 other materials provided with the distribution.
00036
00037 4. Usage of the binary form on proprietary applications shall require explicit
00038 prior written permission from the the copyright holders, and due credit should
00039 be given to the copyright holders.
00040
00041 5. Neither the name of the copyright holder nor the names of its contributors
00042 may be used to endorse or promote products derived from this software without
00043 specific prior written permission.
00044
00045 The copyright holders provide no reassurances that the source code provided does
00046 not infringe any patent, copyright, or any other intellectual property rights of
00047 third parties. The copyright holders disclaim any liability to any recipient for
00048 claims brought against recipient by any third party for infringement of that
00049 parties intellectual property rights.
00050
00051 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00052 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00053 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00054 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00055 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00056 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00057 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00058 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00059 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00060 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00061 */
00062
00063 #ifndef MTK_INCLUDE_ROOTS_H_
00064 #define MTK_INCLUDE_ROOTS_H_
00065
00071 namespace mtk {
00072
00080 #ifdef MTK_PRECISION_DOUBLE
00081 typedef double Real;
00082 #else
00083 typedef float Real;
00084 #endif
00085
00111 #ifdef MTK_PRECISION_DOUBLE
00112 const double kZero{0.0};
00113 const double kOne{1.0};
00114 const double kTwo{2.0};
00115 #else
00116 const float kZero{0.0f};
00117 const float kOne{1.0f};
00118 const float kTwo{2.0f};
00119 #endif
00120
00128 #ifdef MTK_PRECISION_DOUBLE
00129 const double kDefaultTolerance{1e-7};
00130 #else
00131 const float kDefaultTolerance{1e-7f};
00132 #endif
00133
00143 const int kDefaultOrderAccuracy{2};
00144
00154 #ifdef MTK_PRECISION_DOUBLE
00155 const double kDefaultMimeticThreshold{1e-6};

```

```

00156 #else
00157 const float kDefaultMimeticThreshold{1e-6f};
00158 #endif
00159
00167 const int kCriticalOrderAccuracyDiv{8};
00168
00176 const int kCriticalOrderAccuracyGrad{10};
00177 }
00178 #endif // End of: MTK_INCLUDE_ROOTS_H_

```

17.59 include/mtk_tools.h File Reference


Tool manager class.

```


#include <ctime>
#include "mtk_roots.h"

```

Include dependency graph for mtk_tools.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [mtk::Tools](#)
Tool manager class.

Namespaces

- [mtk](#)
Mimetic Methods Toolkit namespace.

17.59.1 Detailed Description

Basic utilities.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Note

Performance Tip 8.1. If they do not need to be modified by the called function, pass large objects using pointers to constant data or references to constant data, to obtain the performance benefits of pass-by-reference.

Definition in file [mtk_tools.h](#).

17.60 mtk_tools.h

```

00001
00014 /*
00015 Copyright (C) 2015, Computational Science Research Center, San Diego State
00016 University. All rights reserved.
00017
00018 Redistribution and use in source and binary forms, with or without modification,
00019 are permitted provided that the following conditions are met:
00020
00021 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00022 and a copy of the modified files should be reported once modifications are
00023 completed, unless these modifications are made through the project's GitHub
00024 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00025 should be developed and included in any deliverable.
00026
00027 2. Redistributions of source code must be done through direct
00028 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00029
00030 3. Redistributions in binary form must reproduce the above copyright notice,
00031 this list of conditions and the following disclaimer in the documentation and/or
00032 other materials provided with the distribution.
00033
00034 4. Usage of the binary form on proprietary applications shall require explicit
00035 prior written permission from the the copyright holders, and due credit should
00036 be given to the copyright holders.
00037
00038 5. Neither the name of the copyright holder nor the names of its contributors
00039 may be used to endorse or promote products derived from this software without
00040 specific prior written permission.
00041
00042 The copyright holders provide no reassurances that the source code provided does
00043 not infringe any patent, copyright, or any other intellectual property rights of
00044 third parties. The copyright holders disclaim any liability to any recipient for
00045 claims brought against recipient by any third party for infringement of that
00046 parties intellectual property rights.
00047
00048 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00049 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00050 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00051 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00052 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00053 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00054 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00055 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00056 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00057 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00058 */
00059
00060 #ifndef MTK_INCLUDE_TOOLS_H_
00061 #define MTK_INCLUDE_TOOLS_H_
00062
00063 #include <ctime>
00064
00065 #include "mtk_roots.h"
00066
00067 namespace mtk {
00068
00078 class Tools {
00079 public:
00090     static void Prevent(const bool complement,
00091                        const char *const fname,


```

```
00092         int lineno,
00093         const char *const filename) noexcept;
00094
00100     static void BeginUnitTestNo(const int &nn) noexcept;
00101
00107     static void EndUnitTestNo(const int &nn) noexcept;
00108
00114     static void Assert(const bool &condition) noexcept;
00115
00116 private:
00117     static int test_number_;
00118
00119     static Real duration_;
00120
00121     static clock_t begin_time_;
00122 };
00123
00124 #endif // End of: MTK_INCLUDE_TOOLS_H_
```


17.61 include/mtk_uni_stg_grid_1d.h File Reference

Definition of an 1D uniform staggered grid.

```
#include <vector>
#include <string>
#include "mtk_roots.h"
Include dependency graph for mtk_uni_stg_grid_1d.h:
```



This graph shows which files directly or indirectly include this file:



Classes

- class `mtk::UniStgGrid1D`
Uniform 1D Staggered Grid.

Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

17.61.1 Detailed Description

Definition of an 1D uniform staggered grid.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Todo Create overloaded binding routines that read data from files.

Definition in file [mtk_uni_stg_grid_1d.h](#).

17.62 mtk_uni_stg_grid_1d.h

```

00001
00012 /*
00013 Copyright (C) 2015, Computational Science Research Center, San Diego State
00014 University. All rights reserved.
00015
00016 Redistribution and use in source and binary forms, with or without modification,
00017 are permitted provided that the following conditions are met:
00018
00019 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00020 and a copy of the modified files should be reported once modifications are
00021 completed, unless these modifications are made through the project's GitHub
00022 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00023 should be developed and included in any deliverable.
00024
00025 2. Redistributions of source code must be done through direct
00026 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00027
00028 3. Redistributions in binary form must reproduce the above copyright notice,
00029 this list of conditions and the following disclaimer in the documentation and/or
00030 other materials provided with the distribution.
00031
00032 4. Usage of the binary form on proprietary applications shall require explicit
00033 prior written permission from the the copyright holders, and due credit should
00034 be given to the copyright holders.
00035
00036 5. Neither the name of the copyright holder nor the names of its contributors
00037 may be used to endorse or promote products derived from this software without
00038 specific prior written permission.
00039
00040 The copyright holders provide no reassurances that the source code provided does
00041 not infringe any patent, copyright, or any other intellectual property rights of
00042 third parties. The copyright holders disclaim any liability to any recipient for
00043 claims brought against recipient by any third party for infringement of that
00044 parties intellectual property rights.
00045
00046 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00047 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00048 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00049 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00050 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00051 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00052 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00053 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00054 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00055 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00056 */
00057
00058 #ifndef MTK_INCLUDE_UNI_STG_GRID_1D_H_
00059 #define MTK_INCLUDE_UNI_STG_GRID_1D_H_

```

```

00060
00061 #include <vector>
00062 #include <string>
00063
00064 #include "mtk_roots.h"
00065
00066 namespace mtk {
00067
00077 class UniStgGrid1D {
00078 public:
00080     friend std::ostream& operator <<(std::ostream& stream, UniStgGrid1D &in);
00081
00083     UniStgGrid1D();
00084
00090     UniStgGrid1D(const UniStgGrid1D &grid);
00091
00102     UniStgGrid1D(const Real &west_bndy_x,
00103                  const Real &east_bndy_x,
00104                  const int &num_cells_x,
00105                  const mtk::FieldNature &nature = mtk::SCALAR);
00106
00108     ~UniStgGrid1D();
00109
00115     Real west_bndy_x() const;
00116
00122     Real east_bndy_x() const;
00123
00129     Real delta_x() const;
00130
00138     const Real *discrete_domain_x() const;
00139
00147     Real *discrete_field();
00148
00154     int num_cells_x() const;
00155
00161     void BindScalarField(Real (*ScalarField)(const Real &xx));
00162
00173     void BindVectorField(Real (*VectorField)(Real xx));
00174
00186     bool WriteToFile(std::string filename,
00187                     std::string space_name,
00188                     std::string field_name) const;
00189
00190 private:
00191     FieldNature nature_;
00192
00193     std::vector<Real> discrete_domain_x_;
00194     std::vector<Real> discrete_field_;
00195
00196     Real west_bndy_x_;
00197     Real east_bndy_x_;
00198     Real num_cells_x_;
00199     Real delta_x_;
00200 };
00201 }
00202 #endif // End of: MTK_INCLUDE_UNI_STG_GRID_1D_H_

```

17.63 include/mtk_uni_stg_grid_2d.h File Reference

Definition of an 2D uniform staggered grid.

```

#include <vector>
#include <string>
#include "mtk_roots.h"
#include "mtk_enums.h"
#include "mtk_dense_matrix.h"

```



```

graph TD
    A[include/mtk_uni_stg_grid_2d.h] --> B[vector]
    A --> C[string]
    A --> D[mtk_dense_matrix.h]
    A --> E[mtk_roots.h]
    A --> F[iostream]
    A --> G[mtk_enums.h]
    A --> H[mtk_matrix.h]
    D --> E
    D --> F
    D --> H
    H --> F
    H --> G
  
```

- class `mtk::UniStgGrid2D`
Uniform 2D Staggered Grid.

- `mtk`
Mimetic Methods Toolkit namespace.

Definition of an 2D uniform staggered grid.

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_uni_stg_grid_2d.h](#).

17.64 mtk_uni_stg_grid_2d.h

```

00001
00012 /*
00013 Copyright (C) 2015, Computational Science Research Center, San Diego State
00014 University. All rights reserved.
00015
00016 Redistribution and use in source and binary forms, with or without modification,
00017 are permitted provided that the following conditions are met:
00018
00019 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00020 and a copy of the modified files should be reported once modifications are
00021 completed, unless these modifications are made through the project's GitHub
00022 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00023 should be developed and included in any deliverable.
00024
00025 2. Redistributions of source code must be done through direct
00026 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00027
00028 3. Redistributions in binary form must reproduce the above copyright notice,
00029 this list of conditions and the following disclaimer in the documentation and/or
00030 other materials provided with the distribution.
00031
00032 4. Usage of the binary form on proprietary applications shall require explicit
00033 prior written permission from the the copyright holders, and due credit should
00034 be given to the copyright holders.
00035
00036 5. Neither the name of the copyright holder nor the names of its contributors
00037 may be used to endorse or promote products derived from this software without
00038 specific prior written permission.
00039
00040 The copyright holders provide no reassurances that the source code provided does
00041 not infringe any patent, copyright, or any other intellectual property rights of
00042 third parties. The copyright holders disclaim any liability to any recipient for
00043 claims brought against recipient by any third party for infringement of that
00044 parties intellectual property rights.
00045
00046 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00047 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00048 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00049 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00050 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00051 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00052 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00053 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00054 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00055 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00056 */
00057
00058 #ifndef MTK_INCLUDE_UNI_STG_GRID_2D_H_
00059 #define MTK_INCLUDE_UNI_STG_GRID_2D_H_
00060
00061 #include <vector>
00062 #include <string>
00063
00064 #include "mtk_roots.h"
00065 #include "mtk_enums.h"
00066 #include "mtk_dense_matrix.h"
00067
00068 namespace mtk {
00069
00070 class UniStgGrid2D {
00080 public:
00082     friend std::ostream& operator <<(std::ostream& stream, UniStgGrid2D &in);
00083
00085     UniStgGrid2D();
00086
00092     UniStgGrid2D(const UniStgGrid2D &grid);
00093
00107     UniStgGrid2D(const Real &west_bndy_x,
00108                  const Real &east_bndy_x,
00109                  const int &num_cells_x,
00110                  const Real &south_bndy_y,
00111                  const Real &north_bndy_y,
00112                  const int &num_cells_y,
00113                  const mtk::FieldNature &nature =
00114                      mtk::SCALAR);
00116     ~UniStgGrid2D();
00117

```

```


00125     const Real *discrete_domain_x() const;
00126
00134     const Real *discrete_domain_y() const;
00135
00141     Real *discrete_field();
00142
00150     FieldNature nature() const;
00151
00157     Real west_bndy() const;
00158
00164     Real east_bndy() const;
00165
00171     int num_cells_x() const;
00172
00178     Real delta_x() const;
00179
00185     Real south_bndy() const;
00186
00192     Real north_bndy() const;
00193
00199     int num_cells_y() const;
00200
00206     Real delta_y() const;
00207
00213     bool Bound() const;
00214
00220     int Size() const;
00221
00227     void BindScalarField(Real (*ScalarField)(const Real &xx, const
Real &yy));
00228
00242     void BindVectorField(Real (*VectorFieldPComponent)(const
Real &xx,
00243                                     const Real &yy),
00244                             Real (*VectorFieldQComponent)(const Real &xx,
00245                                     const Real &yy));
00246
00259     bool WriteToFile(std::string filename,
00260                      std::string space_name_x,
00261                      std::string space_name_y,
00262                      std::string field_name) const;
00263
00264 private:
00276     void BindVectorFieldPComponent(
00277         Real (*VectorFieldPComponent)(const Real &xx, const Real &yy));
00278
00290     void BindVectorFieldQComponent(
00291         Real (*VectorFieldQComponent)(const Real &xx, const Real &yy));
00292
00293     std::vector<Real> discrete_domain_x;
00294     std::vector<Real> discrete_domain_y;
00295     std::vector<Real> discrete_field;
00296
00297     FieldNature nature_;
00298
00299     Real west_bndy_;
00300     Real east_bndy_;
00301     int num_cells_x_;
00302     Real delta_x_;
00303
00304     Real south_bndy_;
00305     Real north_bndy_;
00306     int num_cells_y_;
00307     Real delta_y_;
00308 };
00309 }
00310 #endif // End of: MTK_INCLUDE_UNI_STG_GRID_2D_H_

```


17.65 include/mtk_uni_stg_grid_3d.h File Reference

Definition of an 3D uniform staggered grid.

```
#include <vector>
#include <string>
#include "mtk_roots.h"
#include "mtk_enums.h"
#include "mtk_dense_matrix.h"
Include dependency graph for mtk_uni_stg_grid_3d.h:
```



This graph shows which files directly or indirectly include this file:



Classes

- class [mtk::UniStgGrid3D](#)
Uniform 3D Staggered Grid.

Namespaces

- [mtk](#)
Mimetic Methods Toolkit namespace.

17.65.1 Detailed Description

Definition of an 3D uniform staggered grid.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Todo Create overloaded binding routines that read data from files.

Definition in file [mtk_uni_stg_grid_3d.h](#).

17.66 mtk_uni_stg_grid_3d.h

```

00001
00012 /*
00013 Copyright (C) 2015, Computational Science Research Center, San Diego State
00014 University. All rights reserved.
00015
00016 Redistribution and use in source and binary forms, with or without modification,
00017 are permitted provided that the following conditions are met:
00018
00019 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00020 and a copy of the modified files should be reported once modifications are
00021 completed, unless these modifications are made through the project's GitHub
00022 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00023 should be developed and included in any deliverable.
00024
00025 2. Redistributions of source code must be done through direct
00026 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00027
00028 3. Redistributions in binary form must reproduce the above copyright notice,
00029 this list of conditions and the following disclaimer in the documentation and/or
00030 other materials provided with the distribution.
00031
00032 4. Usage of the binary form on proprietary applications shall require explicit
00033 prior written permission from the the copyright holders, and due credit should
00034 be given to the copyright holders.
00035
00036 5. Neither the name of the copyright holder nor the names of its contributors
00037 may be used to endorse or promote products derived from this software without
00038 specific prior written permission.
00039
00040 The copyright holders provide no reassurances that the source code provided does
00041 not infringe any patent, copyright, or any other intellectual property rights of
00042 third parties. The copyright holders disclaim any liability to any recipient for
00043 claims brought against recipient by any third party for infringement of that
00044 parties intellectual property rights.
00045
00046 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00047 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00048 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00049 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00050 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00051 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00052 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00053 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00054 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00055 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00056 */
00057
00058 #ifndef MTK_INCLUDE_UNI_STG_GRID_3D_H_
00059 #define MTK_INCLUDE_UNI_STG_GRID_3D_H_
00060
00061 #include <vector>
00062 #include <string>
00063
00064 #include "mtk_roots.h"
00065 #include "mtk_enums.h"
00066 #include "mtk_dense_matrix.h"
00067
00068 namespace mtk {

```

```

00069
00079 class UniStgGrid3D {
00080 public:
00082     friend std::ostream& operator <<(std::ostream& stream, UniStgGrid3D &in);
00083
00091     UniStgGrid3D operator=(const UniStgGrid3D &in);
00092
00094     UniStgGrid3D();
00095
00101     UniStgGrid3D(const UniStgGrid3D &grid);
00102
00119     UniStgGrid3D(const Real &west_bndy_x,
00120                  const Real &east_bndy_x,
00121                  const int &num_cells_x,
00122                  const Real &south_bndy_y,
00123                  const Real &north_bndy_y,
00124                  const int &num_cells_y,
00125                  const Real &bottom_bndy_z,
00126                  const Real &top_bndy_z,
00127                  const int &num_cells_z,
00128                  const mtk::FieldNature &nature =
mtk::SCALAR);
00129
00131     ~UniStgGrid3D();
00132
00140     const Real *discrete_domain_x() const;
00141
00149     const Real *discrete_domain_y() const;
00150
00158     const Real *discrete_domain_z() const;
00159
00165     Real *discrete_field();
00166
00174     FieldNature nature() const;
00175
00181     Real west_bndy() const;
00182
00188     Real east_bndy() const;
00189
00195     int num_cells_x() const;
00196
00202     Real delta_x() const;
00203
00209     Real south_bndy() const;
00210
00216     Real north_bndy() const;
00217
00223     int num_cells_y() const;
00224
00230     Real delta_y() const;
00231
00237     Real bottom_bndy() const;
00238
00244     Real top_bndy() const;
00245
00251     int num_cells_z() const;
00252
00258     Real delta_z() const;
00259
00265     bool Bound() const;
00266
00272     int Size() const;
00273
00279     void BindScalarField(
00280         Real (*ScalarField)(const Real &xx, const Real &yy, const Real &zz));
00281
00298     void BindVectorField(Real (*VectorFieldPComponent)(const
Real &xx,
00299                                     const Real &yy,
00300                                     const Real &zz),
00301                          Real (*VectorFieldQComponent)(const Real &xx,
00302                                                         const Real &yy,
00303                                                         const Real &zz),
00304                          Real (*VectorFieldRComponent)(const Real &xx,
00305                                                         const Real &yy,
00306                                                         const Real &zz));
00307
00321     bool WriteToFile(std::string filename,
00322                     std::string space_name_x,
00323                     std::string space_name_y,
00324                     std::string space_name_z,

```

```

00325         std::string field_name) const;
00326
00327 private:
00340 void BindVectorFieldPComponent (
00341     Real (*VectorFieldPComponent) (const Real &xx,
00342                                     const Real &yy,
00343                                     const Real &zz));
00344
00357 void BindVectorFieldQComponent (
00358     Real (*VectorFieldQComponent) (const Real &xx,
00359                                     const Real &yy,
00360                                     const Real &zz));
00361
00374 void BindVectorFieldRComponent (
00375     Real (*VectorFieldRComponent) (const Real &xx,
00376                                     const Real &yy,
00377                                     const Real &zz));
00378
00379 std::vector<Real> discrete_domain_x_;
00380 std::vector<Real> discrete_domain_y_;
00381 std::vector<Real> discrete_domain_z_;
00382 std::vector<Real> discrete_field_;
00383
00384 FieldNature nature_;
00385
00386 Real west_bndy_;
00387 Real east_bndy_;
00388 int num_cells_x_;
00389 Real delta_x_;
00390
00391 Real south_bndy_;
00392 Real north_bndy_;
00393 int num_cells_y_;
00394 Real delta_y_;
00395
00396 Real bottom_bndy_;
00397 Real top_bndy_;
00398 int num_cells_z_;
00399 Real delta_z_;
00400 };
00401 }
00402 #endif // End of: MTK_INCLUDE_UNI_STG_GRID_3D_H_

```

17.67 Makefile.inc File Reference

17.68 Makefile.inc

```

00001 # Makefile setup file for the MTK.
00002
00003 SHELL := /bin/bash
00004
00005 # Please set the following variables up:
00006
00007 # 1. Absolute path to base directory of the MTK.
00008 # _____
00009
00010 BASE = /home/esanchez/Dropbox/MTK
00011
00012 # 2. The machine (platform) identifier and required machine precision.
00013 # _____
00014
00015 # Options are:
00016 # - LINUX: A LINUX box installation.
00017 # - OSX: Uses OS X optimized solvers.
00018
00019 PLAT = LINUX
00020
00021 # Options are:
00022 # - SINGLE: Use 4 B floating point numbers.
00023 # - DOUBLE: Use 8 B floating point numbers.
00024
00025 PRECISION = DOUBLE
00026
00027 # 3. Optimized solvers and operations by means of ATLAS in Linux?
00028 # _____

```

```

00029
00030 # If you have selected OSX in step 1, then you don't need to worry about this.
00031
00032 # Options are ON xor OFF:
00033
00034 ATL_OPT = OFF
00035
00036 # 4. Paths to dependencies (header files for compiling).
00037 # _____
00038
00039 # GLPK include path (soon to go):
00040
00041 GLPK_INC = $(HOME)/Libraries/glpk-4.35/include
00042
00043 # Linux: If ATLAS optimization is ON, users should only provide the path to
00044 # ATLAS:
00045
00046 ATLAS_INC = $(HOME)/Libraries/ATLAS_3.8.4-CORE/include
00047
00048 # OS X: Do nothing.
00049
00050 # 5. Paths to dependencies (archive files for (static) linking).
00051 # _____
00052
00053 # GLPK linking path (soon to go):
00054
00055 GLPK_LIB = $(HOME)/Libraries/glpk-4.35/lib/lib64/libglpk.a
00056
00057 # If optimization is OFF, then provide the paths for:
00058
00059 BLAS_LIB = $(HOME)/Libraries/BLAS-3.5.0/libblas.a
00060 LAPACK_LIB = $(HOME)/Libraries/lapack-3.5.0/liblapack.a
00061
00062 # WARNING: Vendor libraries should be used whenever they are available.
00063
00064 # However, if optimization is ON, please provide the path the ATLAS' archive:
00065
00066 ATLAS_LIB = $(HOME)/Libraries/ATLAS_3.8.4-CORE/ATLAS_3.8.4-BUILD-Citadel/lib
00067
00068 # 6. Compiler and its flags.
00069 # _____
00070
00071 CC = g++
00072
00073 # Selective Verbose Execution for Quick Debugging. Options are defined per
00074 # concern, and per data hierarchy on each concern.
00075
00076 # 0: NO verbose at all.
00077
00078 # 1: Enable verbose down to the 7th concern: messages.
00079 # 2: Enable verbose down to the 7th concern: messages + scalar results.
00080 # 3: Enable verbose down to the 7th concern. 1.1. + array results.
00081 # 4: Enable verbose down to the 7th concern. 1.2. + matrix results.
00082
00083 # 5: Enable verbose down to the 6th concern: messages.
00084 # 6: Enable verbose down to the 6th concern: messages + scalar results.
00085 # 7: Enable verbose down to the 6th concern. 2.1. + array results.
00086 # 8: Enable verbose down to the 6th concern. 2.2. + matrix results.
00087
00088 # 9: Enable verbose down to the 5th concern: messages.
00089 # 10: Enable verbose down to the 5th concern: messages + scalar results.
00090 # 11: Enable verbose down to the 5th concern. 3.1. + array results.
00091 # 12: Enable verbose down to the 5th concern. 3.2. + matrix results.
00092
00093 # 13: Enable verbose down to the 4th concern: messages.
00094 # 14: Enable verbose down to the 4th concern: messages + scalar results.
00095 # 15: Enable verbose down to the 4th concern. 4.1. + array results.
00096 # 16: Enable verbose down to the 4th concern. 4.2. + matrix results.
00097
00098 VERBOSE_LEVEL = 16
00099
00100 # Enable preventions. In the MTK, methods first validate their required
00101 # pre-conditions in run-time. Similarly, in many points throughout the MTK
00102 # codebase, different sanity checks are performed, as well. If this symbol is
00103 # defined to be 0, the MTK will # perform no validations to enhance execution
00104 # performance. Options are:
00105 # - YES.
00106 # - NO.
00107
00108 PERFORM_PREVENTIONS = YES
00109

```



```

00110 # Flags recommended for release code:
00111
00112 CCFLAGS = -Wall -Werror -O3
00113
00114 # Flags recommended for debugging code:
00115
00116 CCFLAGS = -Wall -Werror -g
00117
00118 # 7. Archiver, its flags, and ranlib:
00119 #
00120
00121 ARCH      = ar
00122 ARCHFLAGS = cr
00123
00124 # If your system does not have "ranlib" then set: "RANLIB = echo":
00125
00126 RANLIB = echo
00127
00128 # But, if possible:
00129
00130 RANLIB = ranlib
00131
00132 # 8. Valgrind's memcheck options (optional):
00133 #
00134
00135 MEMCHECK_OPTS = -v --tool=memcheck --leak-check=full --show-leak-kinds=all \
00136 --track-origins=yes --freelist-vol=20000000
00137
00138 # Done! User, please, do not mess with the definitions from this point on.
00139
00140 #
00141 #
00142 #
00143
00144 # MTK-related.
00145 #
00146
00147 SRC      = $(BASE)/src
00148 INCLUDE  = $(BASE)/include
00149 LIB      = $(BASE)/lib
00150 MTK_LIB  = $(LIB)/libmtk.a
00151 TESTS    = $(BASE)/tests
00152 EXAMPLES = $(BASE)/examples
00153
00154 # Compiling-related.
00155 #
00156
00157 CCFLAGS += -std=c++11 -fPIC \
00158 -DMTK_VERBOSE_LEVEL=$(VERBOSE_LEVEL) -I$(INCLUDE) -c
00159
00160 ifeq ($(PRECISION),DOUBLE)
00161 CCFLAGS += -DMTK_PRECISION_DOUBLE
00162 else
00163 CCFLAGS += -DMTK_PRECISION_SINGLE
00164 endif
00165
00166 ifeq ($(PERFORM_PREVENTIONS),YES)
00167 CCFLAGS += -DMTK_PERFORM_PREVENTIONS
00168 endif
00169
00170 # Only the GLPK is included because the other dependencies are coded in Fortran.
00171
00172 ifeq ($(ATL_OPT),ON)
00173 CCFLAGS += -I$(GLPK_INC) $(ATLAS_INC)
00174 else
00175 CCFLAGS += -I$(GLPK_INC)
00176 endif
00177
00178 # Linking-related.
00179 #
00180
00181 NOOPT_LIBS = $(LAPACK_LIB) $(BLAS_LIB) -lm $(GLPK_LIB) -lstdc++
00182
00183 OPT_LIBS   = -L$(ATLAS_LIB) -latlas -llapack -lblas -lm -latlas -lstdc++
00184
00185 ifeq ($(PLAT),OSX)
00186 LINKER = g++
00187 LINKER += -framework Accelerate $(GLPK_LIB) $(MTK_LIB)
00188 else
00189 ifeq ($(ATL_OPT),ON)
00190 LINKER = g++

```

```

00191     LIBS = $(MTK_LIB)
00192     LIBS += $(OPT_LIBS)
00193 else
00194     LINKER = gfortran
00195     LIBS = $(MTK_LIB)
00196     LIBS += $(NOOPT_LIBS)
00197 endif
00198 endif
00199
00200 # Documentation-related.
00201 # -----
00202
00203 DOCGEN      = doxygen
00204 DOCFEILNAME = doc_config.dxc
00205 DOC         = $(BASE)/doc
00206 DOCFEIL     = $(BASE)/$(DOCFEILNAME)

```

17.69 README.md File Reference

17.70 README.md

```

00001 # The Mimetic Methods Toolkit (MTK)
00002
00003 By: **Eduardo J. Sanchez, Ph.D. - esanchez at mail dot sdsu dot edu**
00004
00005 ## 1. Description
00006
00007 We define numerical methods that are based on discretizations preserving the
00008 properties of their continuum counterparts to be mimetic.
00009
00010 The Mimetic Methods Toolkit (MTK) is a C++ library for mimetic numerical
00011 methods. It is arranged as a set of classes for mimetic quadratures,
00012 mimetic interpolation, and mimetic finite differences methods for the
00013 numerical solution of ordinary and partial differential equations.
00014
00015 ## 2. Dependencies
00016
00017 This README assumes all of these dependencies are installed in the following
00018 folder:
00019
00020 ```
00021 $(HOME)/Libraries/
00022 ```
00023
00024 In this version, the MTK optionally uses ATLAS-optimized BLAS and LAPACK
00025 routines for the internal computation on some of the layers. However, ATLAS
00026 requires both BLAS and LAPACK in order to create their optimized distributions.
00027 Therefore, the following dependencies tree arises:
00028
00029 ### For Linux:
00030
00031 1. LAPACK - Available from: http://www.netlib.org/lapack/
00032 1. BLAS - Available from: http://www.netlib.org/blas/
00033
00034 2. GLPK - Available from: https://www.gnu.org/software/glpk/
00035
00036 3. (Optional) ATLAS - Available from: http://math-atlas.sourceforge.net/
00037 1. LAPACK - Available from: http://www.netlib.org/lapack/
00038 1. BLAS - Available from: http://www.netlib.org/blas/
00039
00040 4. (Optional) Valgrind - Available from: http://valgrind.org/
00041
00042 5. (Optional) Doxygen - Available from http://www.stack.nl/~dimitri/doxygen/
00043
00044 ### For OS X:
00045
00046 1. GLPK - Available from: https://www.gnu.org/software/glpk/
00047
00048 ## 3. Installation
00049
00050 ### PART 1. CONFIGURATION OF THE MAKEFILE.
00051
00052 The following steps are required to build and test the MTK. Please use the
00053 accompanying 'Makefile.inc' file, which should provide a solid template to
00054 start with. The following command provides help on the options for make:

```

```

00055
00056 ```
00057 $ make help
00058 -----
00059 Makefile for the MTK.
00060
00061 Options are:
00062 - all: builds the library, the tests, and examples.
00063 - mtklib: builds the library.
00064 - test: builds the test files.
00065 - example: builds the examples.
00066
00067 - testall: runs all the tests.
00068
00069 - gendoc: generates the documentation for the library.
00070
00071 - clean: cleans all the generated files.
00072 - cleanlib: cleans the generated archive and object files.
00073 - cleantest: cleans the generated tests executables.
00074 - cleanexample: cleans the generated examples executables.
00075 -----
00076 ```
00077
00078 ### PART 2. BUILD THE LIBRARY.
00079
00080 ```
00081 $ make
00082 ```
00083
00084 If successful you'll read (before building the tests and examples):
00085
00086 ```
00087 ----- Library created! Check in /home/ejspeiro/Dropbox/MTK/lib
00088 ```
00089
00090 ## 4. Contact, Support, and Credits
00091
00092 The MTK is developed by researchers and adjuncts to the
00093 [Computational Science Research Center (CSRC)] (http://www.csrc.sdsu.edu/)
00094 at [San Diego State University (SDSU)] (http://www.sdsu.edu/).
00095
00096 Developers are members of:
00097
00098 1. Mimetic Numerical Methods Research and Development Group.
00099 2. Computational Geoscience Research and Development Group.
00100 3. Ocean Modeling Research and Development Group.
00101
00102 Currently the developers are:
00103
00104 - *Eduardo J. Sanchez, Ph.D. - esanchez at mail dot sdsu dot edu* - @ejspeiro
00105 - Jose E. Castillo, Ph.D. - jcastillo at mail dot sdsu dot edu
00106 - Guillermo F. Miranda, Ph.D. - unigrav at hotmail dot com
00107 - Christopher P. Paolini, Ph.D. - paolini at engineering dot sdsu dot edu
00108 - Angel Boada.
00109 - Johnny Corbino.
00110 - Raul Vargas-Navarro.
00111
00112 Please reference this work as follows:
00113 ```
00114 @article{Sanchez2014308,
00115   title = "The Mimetic Methods Toolkit: An object-oriented \{API\} for Mimetic
00116 Finite Differences ",
00117   journal = "Journal of Computational and Applied Mathematics ",
00118   volume = "270",
00119   number = "",
00120   pages = "308 - 322",
00121   year = "2014",
00122   note = "Fourth International Conference on Finite Element Methods in
00123 Engineering and Sciences (FEMTEC 2013) ",
00124   issn = "0377-0427",
00125   doi = "http://dx.doi.org/10.1016/j.cam.2013.12.046",
00126   url = "http://www.sciencedirect.com/science/article/pii/S037704271300719X",
00127   author = "Eduardo J. Sanchez and Christopher P. Paolini and Jose E. Castillo",
00128   keywords = "Object-oriented development",
00129   keywords = "Partial differential equations",
00130   keywords = "Application programming interfaces",
00131   keywords = "Mimetic Finite Differences "
00132 }
00133 ```
00134
00135 Finally, please feel free to contact me with suggestions or corrections:

```

```

00136
00137 **Eduardo J. Sanchez, Ph.D. - esanchez at mail dot sdsu dot edu** - @ejspeiro
00138
00139 Thanks and happy coding!

```

17.71 src/mtk_blas_adapter.cc File Reference


Adapter class for the BLAS API.

```

#include <iostream>
#include <iomanip>
#include <vector>
#include "mtk_roots.h"
#include "mtk_tools.h"
#include "mtk_blas_adapter.h"

```

Include dependency graph for mtk_blas_adapter.cc:



Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

Functions

- float [mtk::snrm2_](#) (int *n, float *x, int *incx)
- void [mtk::saxpy_](#) (int *n, float *sa, float *sx, int *incx, float *sy, int *incy)
- void [mtk::sgemv_](#) (char *trans, int *m, int *n, float *alpha, float *a, int *lda, float *x, int *incx, float *beta, float *y, int *incy)
- void [mtk::sgemm_](#) (char *transa, char *transb, int *m, int *n, int *k, double *alpha, double *a, int *lda, double *b, aamm int *ldb, double *beta, double *c, int *ldc)

17.71.1 Detailed Description

This class contains a collection of static classes, that posses direct access to the underlying structure of the matrices, thus allowing programmers to exploit some of the numerical methods implemented in the BLAS.

The **BLAS (Basic Linear Algebra Subprograms)** are routines that provide standard building blocks for performing basic vector and matrix operations. The Level 1 BLAS perform scalar, vector and vector-vector operations, the Level 2 BLAS perform matrix-vector operations, and the Level 3 BLAS perform matrix-matrix operations.

The BLAS can be installed from links given in the See Also section of this page.

See also

<http://www.netlib.org/blas/>
<https://software.intel.com/en-us/non-commercial-software-development>

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_blas_adapter.cc](#).

17.72 mtk_blas_adapter.cc

```
00001
00024 /*
00025 Copyright (C) 2015, Computational Science Research Center, San Diego State
00026 University. All rights reserved.
00027
00028 Redistribution and use in source and binary forms, with or without modification,
00029 are permitted provided that the following conditions are met:
00030
00031 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00032 and a copy of the modified files should be reported once modifications are
00033 completed, unless these modifications are made through the project's GitHub
00034 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00035 should be developed and included in any deliverable.
00036
00037 2. Redistributions of source code must be done through direct
00038 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00039
00040 3. Redistributions in binary form must reproduce the above copyright notice,
00041 this list of conditions and the following disclaimer in the documentation and/or
00042 other materials provided with the distribution.
00043
00044 4. Usage of the binary form on proprietary applications shall require explicit
00045 prior written permission from the the copyright holders, and due credit should
00046 be given to the copyright holders.
00047
00048 5. Neither the name of the copyright holder nor the names of its contributors
00049 may be used to endorse or promote products derived from this software without
00050 specific prior written permission.
00051
00052 The copyright holders provide no reassurances that the source code provided does
00053 not infringe any patent, copyright, or any other intellectual property rights of
00054 third parties. The copyright holders disclaim any liability to any recipient for
00055 claims brought against recipient by any third party for infringement of that
00056 parties intellectual property rights.
00057
00058 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00059 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00060 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00061 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00062 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00063 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00064 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00065 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00066 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
```

```
00067 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00068 */
00069
00070 #include <iostream>
00071 #include <iomanip>
00072
00073 #include <vector>
00074
00075 #include "mtk_roots.h"
00076 #include "mtk_tools.h"
00077 #include "mtk_blas_adapter.h"
00078
00079 namespace mtk {
00080
00081 extern "C" {
00082
00083 #ifdef MTK_PRECISION_DOUBLE
00084
00097 double dnm2_(int *n, double *x, int *incx);
00098 #else
00099
00112 float snrm2_(int *n, float *x, int *incx);
00113 #endif
00114
00115 #ifdef MTK_PRECISION_DOUBLE
00116
00135 void daxpy_(int *n, double *da, double *dx, int *incx, double *dy, int *incy);
00136 #else
00137
00156 void saxpy_(int *n, float *sa, float *sx, int *incx, float *sy, int *incy);
00157 #endif
00158
00159 #ifdef MTK_PRECISION_DOUBLE
00160
00188 void dgemv_(char *trans,
00189             int *m,
00190             int *n,
00191             double *alpha,
00192             double *a,
00193             int *lda,
00194             double *x,
00195             int *incx,
00196             double *beta,
00197             double *y,
00198             int *incy);
00199 #else
00200
00228 void sgemv_(char *trans,
00229             int *m,
00230             int *n,
00231             float *alpha,
00232             float *a,
00233             int *lda,
00234             float *x,
00235             int *incx,
00236             float *beta,
00237             float *y,
00238             int *incy);
00239 #endif
00240
00241 #ifdef MTK_PRECISION_DOUBLE
00242
00267 void dgemm_(char *transa,
00268            char* transb,
00269            int *m,
00270            int *n,
00271            int *k,
00272            double *alpha,
00273            double *a,
00274            int *lda,
00275            double *b,
00276            int *ldb,
00277            double *beta,
00278            double *c,
00279            int *ldc);
00280 }
00281 #else
00282
00307 void sgemm_(char *transa,
00308            char* transb,
00309            int *m,
```

```

00310         int *n,
00311         int *k,
00312         double *alpha,
00313         double *a,
00314         int *lda,
00315         double *b, aamm
00316         int *ldb,
00317         double *beta,
00318         double *c,
00319         int *ldc);
00320 }
00321 #endif
00322 }
00323
00324 mtk::Real mtk::BLASAdapter::RealNRM2(Real *in, int &in_length) {
00325
00326     #ifdef MTK_PERFORM_PREVENTIONS
00327     mtk::Tools::Prevent(in_length <= 0, __FILE__, __LINE__, __func__);
00328     #endif
00329
00330     int incx{1}; // Increment for the elements of xx. ix >= 0.
00331
00332     #ifdef MTK_PRECISION_DOUBLE
00333     return dnorm2_(&in_length, in, &incx);
00334     #else
00335     return snrm2_(&in_length, in, &incx);
00336     #endif
00337 }
00338
00339 void mtk::BLASAdapter::RealAXPY(mtk::Real alpha,
00340                                mtk::Real *xx,
00341                                mtk::Real *yy,
00342                                int &in_length) {
00343
00344     #ifdef MTK_PERFORM_PREVENTIONS
00345     mtk::Tools::Prevent(xx == nullptr, __FILE__, __LINE__, __func__);
00346     mtk::Tools::Prevent(yy == nullptr, __FILE__, __LINE__, __func__);
00347     #endif
00348
00349     int incx{1}; // Increment for the elements of xx. ix >= 0.
00350
00351     #ifdef MTK_PRECISION_DOUBLE
00352     daxpy_(&in_length, &alpha, xx, &incx, yy, &incx);
00353     #else
00354     saxpy_(&in_length, &alpha, xx, &incx, yy, &incx);
00355     #endif
00356 }
00357
00358 mtk::Real mtk::BLASAdapter::RelNorm2Error(
00359     mtk::Real *computed,
00360     mtk::Real *known,
00361     int length) {
00362
00363     #ifdef MTK_PERFORM_PREVENTIONS
00364     mtk::Tools::Prevent(computed == nullptr, __FILE__, __LINE__, __func__);
00365     mtk::Tools::Prevent(known == nullptr, __FILE__, __LINE__, __func__);
00366     #endif
00367
00368     mtk::Real norm_2_computed{mtk::BLASAdapter::RealNRM2(known, length)};
00369
00370     mtk::Real alpha{-mtk::kOne};
00371
00372     mtk::BLASAdapter::RealAXPY(alpha, known, computed, length);
00373
00374     mtk::Real norm_2_difference{mtk::BLASAdapter::RealNRM2(computed,
00375     length)};
00376
00377     return norm_2_difference/norm_2_computed;
00378 }
00379
00380 void mtk::BLASAdapter::RealDenseMV(mtk::Real &alpha,
00381                                    mtk::DenseMatrix &aa,
00382                                    mtk::Real *xx,
00383                                    mtk::Real &beta,
00384                                    mtk::Real *yy) {
00385
00386     // Make sure input matrices are row-major ordered.
00387
00388     if (aa.matrix_properties().ordering() ==
00389         mtk::COL_MAJOR) {
00390         aa.OrderRowMajor();
00391     }

```

```

00388     }
00389
00390     char transa{'T'}; // State that now, the input WILL be in row-major ordering.
00391
00392     int mm{aa.num_rows()}; // Rows of aa.
00393     int nn{aa.num_cols()}; // Columns of aa.
00394     int lda{(aa.matrix_properties()).ld()}; // Leading dimension.
00395     int incx{1}; // Increment of values in x.
00396     int incy{1}; // Increment of values in y.
00397
00398     std::swap(mm,nn);
00399     #ifdef MTK_PRECISION_DOUBLE
00400     dgemv_(&transa, &mm, &nn, &alpha, aa.data(), &lda,
00401           xx, &incx, &beta, yy, &incy);
00402     #else
00403     sgemv_(&transa, &mm, &nn, &alpha, aa.data(), &lda,
00404           xx, &incx, &beta, yy, &incy);
00405     #endif
00406     std::swap(mm,nn);
00407 }
00408
00409 mtk::DenseMatrix mtk::BLASAdapter::RealDenseMM(
00410     mtk::DenseMatrix &aa,
00411                                     mtk::DenseMatrix &bb) {
00412     #ifdef MTK_PERFORM_PREVENTIONS
00413     mtk::Tools::Prevent(aa.num_cols() != bb.num_rows(),
00414                         __FILE__, __LINE__, __func__);
00415     #endif
00416
00417     if (aa.matrix_properties().ordering() ==
00418         mtk::COL_MAJOR) {
00419         aa.OrderRowMajor();
00420     }
00421     if (bb.matrix_properties().ordering() ==
00422         mtk::COL_MAJOR) {
00423         bb.OrderRowMajor();
00424     }
00425
00426     char ta{'T'}; // State that input matrix aa is in row-wise ordering.
00427     char tb{'T'}; // State that input matrix bb is in row-wise ordering.
00428
00429     int mm{aa.num_rows()}; // Rows of aa and rows of cc.
00430     int nn{bb.num_cols()}; // Cols of bb and cols of cc.
00431     int kk{aa.num_cols()}; // Cols of aa and rows of bb.
00432
00433     int cc_num_rows{mm}; // Rows of cc.
00434     int cc_num_cols{nn}; // Columns of cc.
00435
00436     int lda{std::max(1, kk)}; // Leading dimension of the aa matrix.
00437     int ldb{std::max(1, nn)}; // Leading dimension of the bb matrix.
00438     int ldc{std::max(1, mm)}; // Leading dimension of the cc matrix.
00439
00440     mtk::Real alpha{mtk::kOne}; // First scalar coefficient.
00441     mtk::Real beta{mtk::kZero}; // Second scalar coefficient.
00442
00443     mtk::DenseMatrix cc_col_maj_ord(cc_num_rows, cc_num_cols); // Output matrix.
00444
00445     cc_col_maj_ord.SetOrdering(mtk::COL_MAJOR);
00446
00447     #ifdef MTK_PRECISION_DOUBLE
00448     dgemm_(&ta, &tb, &mm, &nn, &kk, &alpha, aa.data(), &lda,
00449           bb.data(), &ldb, &beta, cc_col_maj_ord.data(), &ldc);
00450     #else
00451     sgemm_(&ta, &tb, &mm, &nn, &kk, &alpha, aa.data(), &lda,
00452           bb.data(), &ldb, &beta, cc_col_maj_ord.data(), &ldc);
00453     #endif
00454
00455     #if MTK_VERBOSE_LEVEL > 12
00456     std::cout << "cc_col_maj_ord =" << std::endl;
00457     std::cout << cc_col_maj_ord << std::endl;
00458     #endif
00459
00460     cc_col_maj_ord.OrderRowMajor();
00461
00462     return cc_col_maj_ord;
00463 }
00464
00465
00466 mtk::DenseMatrix mtk::BLASAdapter::RealDenseSM(
00467     mtk::Real alpha,
00468                                     mtk::DenseMatrix &aa) {

```



```

00468
00469 #ifdef MTK_PERFORM_PREVENTIONS
00470 mtk::Tools::Prevent(aa.num_rows() == 0, __FILE__, __LINE__, __func__);
00471 mtk::Tools::Prevent(aa.num_cols() == 0, __FILE__, __LINE__, __func__);
00472 #endif
00473
00475 if (aa.matrix_properties().ordering() ==
mtk::COL_MAJOR) {
00476     aa.OrderRowMajor();
00477 }
00478
00480 char ta{'T'}; // State that input matrix aa is in row-wise ordering.
00481 char tb{'T'}; // State that input matrix bb is in row-wise ordering.
00482
00483 int mm{aa.num_rows()}; // Rows of aa and rows of cc.
00484 int nn{aa.num_cols()}; // Cols of bb and cols of cc.
00485 int kk{aa.num_cols()}; // Cols of aa and rows of bb.
00486
00487 int lda{std::max(1, kk)}; // Leading dimension of the aa matrix.
00488 int ldb{std::max(1, nn)}; // Leading dimension of the bb matrix.
00489 int ldc{std::max(1, mm)}; // Leading dimension of the cc matrix.
00490
00491 mtk::Real beta{alpha}; // Second scalar coefficient.
00492
00493 alpha = mtk::kZero;
00494
00495 mtk::DenseMatrix alpha_aa(aa); // Output matrix.
00496
00498 #ifdef MTK_PRECISION_DOUBLE
00499 dgemm_(&ta, &tb, &mm, &nn, &kk, &alpha, aa.data(), &lda,
00500     aa.data(), &ldb, &beta, alpha_aa.data(), &ldc);
00501 #else
00502 sgemm_(&ta, &tb, &mm, &nn, &kk, &alpha, aa.data(), &lda,
00503     aa.data(), &ldb, &beta, alpha_aa.data(), &ldc);
00504 #endif
00505
00506 #if MTK_VERBOSE_LEVEL > 12
00507 std::cout << "alpha_aa =" << std::endl;
00508 std::cout << alpha_aa << std::endl;
00509 #endif
00510
00511 return alpha_aa;
00512 }

```

17.73 src/mtk_curl_2d.cc File Reference


Implements the class Curl2D.

```

#include <cstdlib>
#include <cstdio>
#include <iostream>
#include <iomanip>
#include "mtk_roots.h"
#include "mtk_enums.h"
#include "mtk_uni_stg_grid_1d.h"
#include "mtk_div_1d.h"
#include "mtk_div_2d.h"
#include "mtk_curl_2d.h"

```

Include dependency graph for `mtk_curl_2d.cc`:



17.73.1 Detailed Description

This class implements a 2D curl matrix operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_curl_2d.cc](#).

17.74 mtk_curl_2d.cc

```

00001
00011 /*
00012 Copyright (C) 2015, Computational Science Research Center, San Diego State
00013 University. All rights reserved.
00014
00015 Redistribution and use in source and binary forms, with or without modification,
00016 are permitted provided that the following conditions are met:
00017
00018 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00019 and a copy of the modified files should be reported once modifications are
00020 completed, unless these modifications are made through the project's GitHub
00021 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00022 should be developed and included in any deliverable.
00023
00024 2. Redistributions of source code must be done through direct
00025 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00026
00027 3. Redistributions in binary form must reproduce the above copyright notice,
00028 this list of conditions and the following disclaimer in the documentation and/or
00029 other materials provided with the distribution.
00030
00031 4. Usage of the binary form on proprietary applications shall require explicit
00032 prior written permission from the the copyright holders, and due credit should
00033 be given to the copyright holders.
00034
00035 5. Neither the name of the copyright holder nor the names of its contributors
00036 may be used to endorse or promote products derived from this software without
00037 specific prior written permission.
00038
00039 The copyright holders provide no reassurances that the source code provided does
00040 not infringe any patent, copyright, or any other intellectual property rights of
00041 third parties. The copyright holders disclaim any liability to any recipient for
00042 claims brought against recipient by any third party for infringement of that
00043 parties intellectual property rights.
00044
00045 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00046 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00047 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00048 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR

```

```

00049 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00050 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00051 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00052 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00053 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00054 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00055 */
00056
00057 #include <cstdlib>
00058 #include <cstdio>
00059
00060 #include <iostream>
00061 #include <iomanip>
00062
00063 #include "mtk_roots.h"
00064 #include "mtk_enums.h"
00065 #include "mtk_uni_stg_grid_1d.h"
00066 #include "mtk_div_1d.h"
00067 #include "mtk_div_2d.h"
00068 #include "mtk_curl_2d.h"
00069
00070 mtk::UniStgGrid3D mtk::Curl2D::operator*(const
mtk::UniStgGrid2D &grid) const {
00071
00073
00074     mtk::UniStgGrid3D output;
00075
00076     return output;
00077 }
00078
00079 mtk::Curl2D::Curl2D():
00080     order_accuracy_(),
00081     mimetic_threshold_() {}
00082
00083 mtk::Curl2D::Curl2D(const Curl2D &curl):
00084     order_accuracy_(curl.order_accuracy_),
00085     mimetic_threshold_(curl.mimetic_threshold_) {}
00086
00087 mtk::Curl2D::~Curl2D() {}
00088
00089 bool mtk::Curl2D::ConstructCurl2D(const
mtk::UniStgGrid2D &grid,
00090                                     int order_accuracy,
00091                                     mtk::Real mimetic_threshold) {
00092
00093     int num_cells_x = grid.num_cells_x();
00094     int num_cells_y = grid.num_cells_y();
00095
00096     int mx = num_cells_x + 2; // Dx vertical dimension.
00097     int nx = num_cells_x + 1; // Dx horizontal dimension.
00098     int my = num_cells_y + 2; // Dy vertical dimension.
00099     int ny = num_cells_y + 1; // Dy horizontal dimension.
00100
00101     mtk::Div1D div;
00102
00103     bool info = div.ConstructDiv1D(order_accuracy, mimetic_threshold);
00104
00105     #ifdef MTK_PERFORM_PREVENTIONS
00106     if (!info) {
00107         std::cerr << "Mimetic div could not be built." << std::endl;
00108         return info;
00109     }
00110     #endif
00111
00112     auto west = grid.west_bndy();
00113     auto east = grid.east_bndy();
00114     auto south = grid.south_bndy();
00115     auto north = grid.east_bndy();
00116
00117     mtk::UniStgGrid1D grid_x(west, east, num_cells_x);
00118     mtk::UniStgGrid1D grid_y(south, north, num_cells_y);
00119
00120     mtk::DenseMatrix dx(div.ReturnAsDenseMatrix(grid_x));
00121     mtk::DenseMatrix dy(div.ReturnAsDenseMatrix(grid_y));
00122
00123     bool padded{true};
00124     bool transpose{false};
00125
00126     mtk::DenseMatrix ix(num_cells_x, padded, transpose);
00127     mtk::DenseMatrix iy(num_cells_y, padded, transpose);
00128

```

```

00129 mtk::DenseMatrix dxy(mtk::DenseMatrix::Kron(iy, dx));
00130 mtk::DenseMatrix dyx(mtk::DenseMatrix::Kron(dy, ix));
00131
00132 #if MTK_VERBOSE_LEVEL > 2
00133 std::cout << "Dx: " << mx << " by " << nx << std::endl;
00134 std::cout << "Iy : " << num_cells_y << " by " << ny << std::endl;
00135 std::cout << "Dy: " << my << " by " << ny << std::endl;
00136 std::cout << "Ix : " << num_cells_x << " by " << nx << std::endl;
00137 std::cout << "Curl 2D: " << mx*num_cells_y + my*num_cells_x << " by " <<
00138     nx*ny << std::endl;
00139 #endif
00140
00141 mtk::DenseMatrix d2d(mx*my, nx*num_cells_y + ny*num_cells_x);
00142
00143 for (auto ii = 0; ii < mx*my; ii++) {
00144     for (auto jj = 0; jj < nx*num_cells_y; jj++) {
00145         d2d.SetValue(ii, jj, dxy.GetValue(ii, jj));
00146     }
00147     for (auto kk=0; kk<ny*num_cells_x; kk++) {
00148         d2d.SetValue(ii, kk + nx*num_cells_y, dyx.GetValue(ii, kk));
00149     }
00150 }
00151
00152 curl_ = d2d;
00153
00154 return info;
00155 }
00156
00157 mtk::DenseMatrix mtk::Curl2D::ReturnAsDenseMatrix() const {
00158
00159     return curl_;
00160 }

```


17.75 src/mtk_dense_matrix.cc File Reference

```

#include <cstdlib>
#include <cstring>
#include <cmath>
#include <iostream>
#include <iomanip>
#include <fstream>
#include <typeinfo>
#include <algorithm>
#include "mtk_roots.h"
#include "mtk_dense_matrix.h"
#include "mtk_tools.h"

```

Include dependency graph for mtk_dense_matrix.cc:



Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

Functions

- `std::ostream & mtk::operator<< (std::ostream &stream, mtk::DenseMatrix &in)`

17.76 mtk_dense_matrix.cc

```

00001
00013 /*
00014 Copyright (C) 2015, Computational Science Research Center, San Diego State
00015 University. All rights reserved.
00016
00017 Redistribution and use in source and binary forms, with or without modification,
00018 are permitted provided that the following conditions are met:
00019
00020 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00021 and a copy of the modified files should be reported once modifications are
00022 completed, unless these modifications are made through the project's GitHub
00023 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00024 should be developed and included in any deliverable.
00025
00026 2. Redistributions of source code must be done through direct
00027 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00028
00029 3. Redistributions in binary form must reproduce the above copyright notice,
00030 this list of conditions and the following disclaimer in the documentation and/or
00031 other materials provided with the distribution.
00032
00033 4. Usage of the binary form on proprietary applications shall require explicit
00034 prior written permission from the the copyright holders, and due credit should
00035 be given to the copyright holders.
00036
00037 5. Neither the name of the copyright holder nor the names of its contributors
00038 may be used to endorse or promote products derived from this software without
00039 specific prior written permission.
00040
00041 The copyright holders provide no reassurances that the source code provided does
00042 not infringe any patent, copyright, or any other intellectual property rights of
00043 third parties. The copyright holders disclaim any liability to any recipient for
00044 claims brought against recipient by any third party for infringement of that
00045 parties intellectual property rights.
00046
00047 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00048 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00049 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00050 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00051 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00052 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00053 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00054 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00055 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00056 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00057 */
00058
00059 #include <cstdlib>
00060 #include <cstring>
00061 #include <cmath>
00062
00063 #include <iostream>
00064 #include <iomanip>
00065 #include <fstream>
00066
00067 #include <typeinfo>
00068
00069 #include <algorithm>
00070
00071 #include "mtk_roots.h"
00072 #include "mtk_dense_matrix.h"
00073 #include "mtk_tools.h"
00074
00075 namespace mtk {
00076
00077 std::ostream& operator <<(std::ostream &stream, mtk::DenseMatrix &in) {

```

```

00078
00079     int mm{in.matrix_properties_.num_rows()}; // Auxiliary.
00080     int nn{in.matrix_properties_.num_cols()}; // Auxiliary.
00081
00082     if (in.matrix_properties_.ordering() ==
mtk::COL_MAJOR) {
00083         std::swap(mm, nn);
00084     }
00085     for (int ii = 0; ii < mm; ii++) {
00086         int offset{ii*nn};
00087         for (int jj = 0; jj < nn; jj++) {
00088             mtk::Real value = in.data_[offset + jj];
00089             stream << std::setw(9) << value;
00090         }
00091         stream << std::endl;
00092     }
00093     if (in.matrix_properties_.ordering() ==
mtk::COL_MAJOR) {
00094         std::swap(mm, nn);
00095     }
00096     return stream;
00097 }
00098 }
00099
00100 mtk::DenseMatrix& mtk::DenseMatrix::operator =(const
mtk::DenseMatrix &in) {
00101
00102     if(this == &in) {
00103         return *this;
00104     }
00105
00106     matrix_properties_.set_storage(in.
matrix_properties_.storage());
00107
00108     matrix_properties_.set_ordering(in.
matrix_properties_.ordering());
00109
00110     auto aux = in.matrix_properties_.num_rows();
00111     matrix_properties_.set_num_rows(aux);
00112
00113     aux = in.matrix_properties().num_cols();
00114     matrix_properties_.set_num_cols(aux);
00115
00116     aux = in.matrix_properties().num_zero();
00117     matrix_properties_.set_num_zero(aux);
00118
00119     aux = in.matrix_properties().num_null();
00120     matrix_properties_.set_num_null(aux);
00121
00122     auto num_rows = matrix_properties_.num_rows();
00123     auto num_cols = matrix_properties_.num_cols();
00124
00125     delete [] data_;
00126
00127     try {
00128         data_ = new mtk::Real[num_rows*num_cols];
00129     } catch (std::bad_alloc &memory_allocation_exception) {
00130         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00131             std::endl;
00132         std::cerr << memory_allocation_exception.what() << std::endl;
00133     }
00134     memset(data_, mtk::kZero, sizeof(data_[0])*num_rows*
num_cols);
00135
00136     std::copy(in.data_, in.data_ + num_rows*num_cols, data_);
00137
00138     return *this;
00139 }
00140
00141 bool mtk::DenseMatrix::operator ==(const
DenseMatrix &in) {
00142
00143     bool ans{true};
00144
00145     auto mm = in.num_rows();
00146     auto nn = in.num_cols();
00147
00148     if (mm != matrix_properties_.num_rows() ||
00149         nn != matrix_properties_.num_cols()) {
00150         return false;
00151     }

```

```

00152
00153     for (int ii = 0; ii < mm && ans; ++ii) {
00154         for (int jj = 0; jj < nn && ans; ++jj) {
00155             ans = ans &&
00156                 abs(data_[ii*nn + jj] - in.data()[ii*nn + jj]) <
mtk::kDefaultTolerance;
00157         }
00158     }
00159     return ans;
00160 }
00161
00162 mtk::DenseMatrix::DenseMatrix(): data_(nullptr) {
00163
00164     matrix_properties_.set_storage(mtk::DENSE);
00165     matrix_properties_.set_ordering(mtk::ROW_MAJOR);
00166 }
00167
00168 mtk::DenseMatrix::DenseMatrix(const
mtk::DenseMatrix &in) {
00169
00170     matrix_properties_.set_storage(in.matrix_properties_.storage());
00171
00172     matrix_properties_.set_ordering(in.matrix_properties_.
ordering());
00173
00174     auto aux = in.matrix_properties_.num_rows();
00175     matrix_properties_.set_num_rows(aux);
00176
00177     aux = in.matrix_properties().num_cols();
00178     matrix_properties_.set_num_cols(aux);
00179
00180     aux = in.matrix_properties().num_zero();
00181     matrix_properties_.set_num_zero(aux);
00182
00183     aux = in.matrix_properties().num_null();
00184     matrix_properties_.set_num_null(aux);
00185
00186     auto num_rows = in.matrix_properties_.num_rows();
00187     auto num_cols = in.matrix_properties_.num_cols();
00188
00189     try {
00190         data_ = new mtk::Real[num_rows*num_cols];
00191     } catch (std::bad_alloc &memory_allocation_exception) {
00192         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00193             std::endl;
00194         std::cerr << memory_allocation_exception.what() << std::endl;
00195     }
00196     memset(data_, mtk::kZero, sizeof(data_[0])*num_rows*num_cols);
00197
00198     std::copy(in.data_, in.data_ + num_rows*num_cols, data_);
00199 }
00200
00201 mtk::DenseMatrix::DenseMatrix(const int &num_rows, const int &num_cols) {
00202
00203     #ifdef MTK_PERFORM_PREVENTIONS
00204     mtk::Tools::Prevent(num_rows < 1, __FILE__, __LINE__, __func__);
00205     mtk::Tools::Prevent(num_cols < 1, __FILE__, __LINE__, __func__);
00206     #endif
00207
00208     matrix_properties_.set_storage(mtk::DENSE);
00209     matrix_properties_.set_ordering(mtk::ROW_MAJOR);
00210     matrix_properties_.set_num_rows(num_rows);
00211     matrix_properties_.set_num_cols(num_cols);
00212
00213     try {
00214         data_ = new mtk::Real[num_rows*num_cols];
00215     } catch (std::bad_alloc &memory_allocation_exception) {
00216         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00217             std::endl;
00218         std::cerr << memory_allocation_exception.what() << std::endl;
00219     }
00220     memset(data_, mtk::kZero, sizeof(data_[0])*num_rows*num_cols);
00221 }
00222
00223 mtk::DenseMatrix::DenseMatrix(const int &rank,
00224                               const bool &padded,
00225                               const bool &transpose) {
00226
00227     #ifdef MTK_PERFORM_PREVENTIONS
00228     mtk::Tools::Prevent(rank < 1, __FILE__, __LINE__, __func__);
00229     #endif

```

```

00230
00231     int aux{}; // Used to control the padding.
00232
00233     if (padded) {
00234         aux = 1;
00235     }
00236
00237     matrix_properties_.set_storage(mtk::DENSE);
00238     matrix_properties_.set_ordering(mtk::ROW_MAJOR);
00239     matrix_properties_.set_num_rows(aux + rank + aux);
00240     matrix_properties_.set_num_cols(rank);
00241
00242     try {
00243         data_ = new mtk::Real[matrix_properties_.num_values()];
00244     } catch (std::bad_alloc &memory_allocation_exception) {
00245         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00246             std::endl;
00247         std::cerr << memory_allocation_exception.what() << std::endl;
00248     }
00249     memset(data_,
00250         mtk::kZero,
00251         sizeof(data_[0])*(matrix_properties_.num_values()));
00252
00253     for (auto ii = 0; ii < matrix_properties_.num_rows(); ++ii) {
00254         for (auto jj = 0; jj < matrix_properties_.num_cols(); ++jj) {
00255             data_[ii*matrix_properties_.num_cols() + jj] =
00256                 (ii == jj + aux)? mtk::kOne: mtk::kZero;
00257         }
00258     }
00259     if (transpose) {
00260         Transpose();
00261     }
00262 }
00263
00264 mtk::DenseMatrix::DenseMatrix(const mtk::Real *const gen,
00265     const int &gen_length,
00266     const int &pro_length,
00267     const bool &transpose) {
00268
00269     #ifdef MTK_PERFORM_PREVENTIONS
00270     mtk::Tools::Prevent(gen == nullptr, __FILE__, __LINE__, __func__);
00271     mtk::Tools::Prevent(gen_length < 1, __FILE__, __LINE__, __func__);
00272     mtk::Tools::Prevent(pro_length < 1, __FILE__, __LINE__, __func__);
00273     #endif
00274
00275     matrix_properties_.set_storage(mtk::DENSE);
00276     matrix_properties_.set_ordering(mtk::ROW_MAJOR);
00277     if (!transpose) {
00278         matrix_properties_.set_num_rows(gen_length);
00279         matrix_properties_.set_num_cols(pro_length);
00280     } else {
00281         matrix_properties_.set_num_rows(pro_length);
00282         matrix_properties_.set_num_cols(gen_length);
00283     }
00284
00285     int mm = matrix_properties_.num_rows(); // Used to construct this matrix.
00286     int nn = matrix_properties_.num_cols(); // Used to construct this matrix.
00287
00288     try {
00289         data_ = new mtk::Real[mm*nn];
00290     } catch (std::bad_alloc &memory_allocation_exception) {
00291         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00292             std::endl;
00293         std::cerr << memory_allocation_exception.what() << std::endl;
00294     }
00295     memset(data_, mtk::kZero, sizeof(data_[0])*mm*nn);
00296
00297     if (!transpose) {
00298         for (auto ii = 0; ii < mm; ii++) {
00299             for (auto jj = 0; jj < nn; jj++) {
00300                 data_[ii*nn + jj] = pow(gen[ii], (double) jj);
00301             }
00302         }
00303     } else {
00304         for (auto ii = 0; ii < mm; ii++) {
00305             for (auto jj = 0; jj < nn; jj++) {
00306                 data_[ii*nn + jj] = pow(gen[jj], (double) ii);
00307             }
00308         }
00309     }
00310 }

```



```

00311
00312 mtk::DenseMatrix::~DenseMatrix() {
00313
00314     delete [] data_;
00315     data_ = nullptr;
00316 }
00317
00318 mtk::Matrix mtk::DenseMatrix::matrix_properties() const
noexcept {
00319
00320     return matrix_properties_;
00321 }
00322
00323 void mtk::DenseMatrix::SetOrdering(
    mtk::MatrixOrdering oo) noexcept {
00324
00325     #ifdef MTK_PERFORM_PREVENTIONS
00326     mtk::Tools::Prevent(!(oo == mtk::ROW_MAJOR || oo ==
    mtk::COL_MAJOR),
00327                         __FILE__, __LINE__, __func__);
00328     #endif
00329
00330     matrix_properties_.set_ordering(oo);
00331 }
00332
00333 int mtk::DenseMatrix::num_rows() const noexcept {
00334
00335     return matrix_properties_.num_rows();
00336 }
00337
00338 int mtk::DenseMatrix::num_cols() const noexcept {
00339
00340     return matrix_properties_.num_cols();
00341 }
00342
00343 mtk::Real* mtk::DenseMatrix::data() const noexcept {
00344
00345     return data_;
00346 }
00347
00348 mtk::Real mtk::DenseMatrix::GetValue(
    const int &mm,
00349     const int &nn) const noexcept {
00350
00351     #ifdef MTK_PERFORM_PREVENTIONS
00352     mtk::Tools::Prevent(mm < 0, __FILE__, __LINE__, __func__);
00353     mtk::Tools::Prevent(nn < 0, __FILE__, __LINE__, __func__);
00354     #endif
00355
00356     return data_[mm*matrix_properties_.num_cols() + nn];
00357 }
00358
00359 void mtk::DenseMatrix::SetValue(
    const int &mm,
00360     const int &nn,
00361     const mtk::Real &val) noexcept {
00362
00363     #ifdef MTK_PERFORM_PREVENTIONS
00364     mtk::Tools::Prevent(mm < 0, __FILE__, __LINE__, __func__);
00365     mtk::Tools::Prevent(nn < 0, __FILE__, __LINE__, __func__);
00366     #endif
00367
00368     data_[mm*matrix_properties_.num_cols() + nn] = val;
00369 }
00370
00371 void mtk::DenseMatrix::Transpose() {
00372
00373     mtk::Real *data_transposed{}; // Buffer.
00374
00375     int mm = matrix_properties_.num_rows(); // Used to construct this matrix.
00376     int nn = matrix_properties_.num_cols(); // Used to construct this matrix.
00377
00378     try {
00379         data_transposed = new mtk::Real[mm*nn];
00380     } catch (std::bad_alloc &memory_allocation_exception) {
00381         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00382             std::endl;
00383         std::cerr << memory_allocation_exception.what() << std::endl;
00384     }
00385
00386     memset(data_transposed,

```

```

00390         mtk::kZero,
00391         sizeof(data_transposed[0])*mm*nn);
00392
00393 // Assign the values to their transposed position.
00394 for (auto ii = 0; ii < mm; ++ii) {
00395     for (auto jj = 0; jj < nn; ++jj) {
00396         data_transposed[jj*mm + ii] = data_[ii*nn + jj];
00397     }
00398 }
00399
00400 // Swap pointers.
00401 auto tmp = data_; // Temporal holder.
00402 data_ = data_transposed;
00403 delete [] tmp;
00404 tmp = nullptr;
00405
00406 matrix_properties_.set_num_rows(nn);
00407 matrix_properties_.set_num_cols(mm);
00408 }
00409
00410 void mtk::DenseMatrix::OrderRowMajor() {
00411
00412     if (matrix_properties_.ordering() == mtk::COL_MAJOR) {
00413
00414         mtk::Real *data_transposed{}; // Buffer.
00415
00416         int mm = matrix_properties_.num_rows(); // Used to construct this matrix.
00417         int nn = matrix_properties_.num_cols(); // Used to construct this matrix.
00418
00419         try {
00420             data_transposed = new mtk::Real[mm*nn];
00421         } catch (std::bad_alloc &memory_allocation_exception) {
00422             std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00423                 std::endl;
00424             std::cerr << memory_allocation_exception.what() << std::endl;
00425         }
00426         memset(data_transposed,
00427             mtk::kZero,
00428             sizeof(data_transposed[0])*mm*nn);
00429
00430         // Assign the values to their transposed position.
00431         std::swap(mm, nn);
00432         for (auto ii = 0; ii < mm; ++ii) {
00433             for (auto jj = 0; jj < nn; ++jj) {
00434                 data_transposed[jj*mm + ii] = data_[ii*nn + jj];
00435             }
00436         }
00437         std::swap(mm, nn);
00438
00439         // Swap pointers.
00440         auto tmp = data_; // Temporal holder.
00441         data_ = data_transposed;
00442         delete [] tmp;
00443         tmp = nullptr;
00444
00445         matrix_properties_.set_ordering(mtk::ROW_MAJOR);
00446     }
00447 }
00448
00449 void mtk::DenseMatrix::OrderColMajor() {
00450
00451     if (matrix_properties_.ordering() == ROW_MAJOR) {
00452
00453         mtk::Real *data_transposed{}; // Buffer.
00454
00455         int mm = matrix_properties_.num_rows(); // Used to construct this matrix.
00456         int nn = matrix_properties_.num_cols(); // Used to construct this matrix.
00457
00458         try {
00459             data_transposed = new mtk::Real[mm*nn];
00460         } catch (std::bad_alloc &memory_allocation_exception) {
00461             std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00462                 std::endl;
00463             std::cerr << memory_allocation_exception.what() << std::endl;
00464         }
00465         memset(data_transposed,
00466             mtk::kZero,
00467             sizeof(data_transposed[0])*mm*nn);
00468
00469         // Assign the values to their transposed position.
00470         std::swap(mm, nn);
00471         for (auto ii = 0; ii < mm; ++ii) {
00472             for (auto jj = 0; jj < nn; ++jj) {
00473                 data_transposed[jj*mm + ii] = data_[ii*nn + jj];
00474             }
00475         }
00476         std::swap(mm, nn);
00477
00478         // Swap pointers.
00479         auto tmp = data_; // Temporal holder.
00480         data_ = data_transposed;
00481         delete [] tmp;
00482         tmp = nullptr;
00483
00484         matrix_properties_.set_ordering(mtk::COL_MAJOR);
00485     }
00486 }

```

```

00473     // Assign the values to their transposed position.
00474     for (auto ii = 0; ii < mm; ++ii) {
00475         for (auto jj = 0; jj < nn; ++jj) {
00476             data_transposed[jj*mm + ii] = data_[ii*nn + jj];
00477         }
00478     }
00479     // Swap pointers.
00480     auto tmp = data_; // Temporal holder.
00481     data_ = data_transposed;
00482     delete [] tmp;
00483     tmp = nullptr;
00484
00485     matrix_properties_.set_ordering(mtk::COL_MAJOR);
00486 }
00487 }
00488 }
00489
00490 mtk::DenseMatrix mtk::DenseMatrix::Kron(const
    mtk::DenseMatrix &aa,
00491                                         const mtk::DenseMatrix &bb) {
00492
00493     int row_offset{}; // Offset for rows.
00494     int col_offset{}; // Offset for rows.
00495
00496     mtk::Real aa_factor{}; // Used in computation.
00497
00498     // Auxiliary variables:
00499     auto aux1 = aa.matrix_properties_.num_rows()*bb.
matrix_properties_.num_rows();
00500     auto aux2 = aa.matrix_properties_.num_cols()*bb.
matrix_properties_.num_cols();
00501
00502     mtk::DenseMatrix output(aux1,aux2); // Output matrix.
00503
00504     int kk_num_cols(output.matrix_properties_.num_cols()); // Aux.
00505
00506     auto mm = aa.matrix_properties_.num_rows(); // Rows of aa.
00507     auto nn = aa.matrix_properties_.num_cols(); // Cols of aa.
00508     auto pp = bb.matrix_properties_.num_rows(); // Rows of bb.
00509     auto qq = bb.matrix_properties_.num_cols(); // Cols of bb.
00510
00511     for (auto ii = 0; ii < mm; ++ii) {
00512         row_offset = ii*pp;
00513         for (auto jj = 0; jj < nn; ++jj) {
00514             col_offset = jj*qq;
00515             aa_factor = aa.data_[ii*nn + jj];
00516             for (auto ll = 0; ll < pp; ++ll) {
00517                 for (auto oo = 0; oo < qq; ++oo) {
00518                     auto index = (ll + row_offset)*kk_num_cols + (oo + col_offset);
00519                     output.data_[index] = aa_factor*bb.data_[ll*qq + oo];
00520                 }
00521             }
00522         }
00523     }
00524
00525     output.matrix_properties_.set_storage(mtk::DENSE);
00526     output.matrix_properties_.set_ordering(
mtk::ROW_MAJOR);
00527
00528     return output;
00529 }
00530
00531 bool mtk::DenseMatrix::WriteToFile(const std::string &filename) const {
00532
00533     std::ofstream output_dat_file; // Output file.
00534
00535     output_dat_file.open(filename);
00536
00537     if (!output_dat_file.is_open()) {
00538         return false;
00539     }
00540
00541     int mm(matrix_properties_.num_rows());
00542     int nn(matrix_properties_.num_cols());
00543
00544     for (int ii = 0; ii < mm; ++ii) {
00545         int offset(ii*nn);
00546         for (int jj = 0; jj < nn; ++jj) {
00547             output_dat_file << ii << ' ' << jj << ' ' << data_[offset + jj] <<
std::endl;
00548         }
00549     }

```

```

00550     }
00551
00552     output_dat_file.close();
00553
00554     return true;
00555 }

```

17.77 src/mtk_div_1d.cc File Reference


Implements the class Div1D.

```

#include <cmath>
#include <cstring>
#include <iostream>
#include <iomanip>
#include <limits>
#include <algorithm>
#include "mtk_tools.h"
#include "mtk_blas_adapter.h"
#include "mtk_lapack_adapter.h"
#include "mtk_glpk_adapter.h"
#include "mtk_div_1d.h"

```

Include dependency graph for mtk_div_1d.cc:



Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

Functions

- `std::ostream & mtk::operator<< (std::ostream &stream, mtk::Div1D &in)`

17.77.1 Detailed Description

This class implements a 1D divergence matrix operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Todo Overload ostream operator as in `mtk::Lap1D`.

Todo Implement creation of `■ w. mtk::BLASAdapter`.

Definition in file `mtk_div_1d.cc`.

17.78 mtk_div_1d.cc

```

00001
00015 /*
00016 Copyright (C) 2015, Computational Science Research Center, San Diego State
00017 University. All rights reserved.
00018
00019 Redistribution and use in source and binary forms, with or without modification,
00020 are permitted provided that the following conditions are met:
00021
00022 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00023 and a copy of the modified files should be reported once modifications are
00024 completed, unless these modifications are made through the project's GitHub
00025 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00026 should be developed and included in any deliverable.
00027
00028 2. Redistributions of source code must be done through direct
00029 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00030
00031 3. Redistributions in binary form must reproduce the above copyright notice,
00032 this list of conditions and the following disclaimer in the documentation and/or
00033 other materials provided with the distribution.
00034
00035 4. Usage of the binary form on proprietary applications shall require explicit
00036 prior written permission from the the copyright holders, and due credit should
00037 be given to the copyright holders.
00038
00039 5. Neither the name of the copyright holder nor the names of its contributors
00040 may be used to endorse or promote products derived from this software without
00041 specific prior written permission.
00042
00043 The copyright holders provide no reassurances that the source code provided does
00044 not infringe any patent, copyright, or any other intellectual property rights of
00045 third parties. The copyright holders disclaim any liability to any recipient for
00046 claims brought against recipient by any third party for infringement of that
00047 parties intellectual property rights.
00048
00049 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00050 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00051 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00052 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00053 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00054 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00055 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00056 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00057 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00058 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00059 */
00060
00061 #include <cmath>
00062 #include <cstring>
00063
00064 #include <iostream>
00065 #include <iomanip>
00066 #include <limits>
00067 #include <algorithm>
00068
00069 #include "mtk_tools.h"
00070
00071 #include "mtk_blas_adapter.h"
00072 #include "mtk_lapack_adapter.h"
00073 #include "mtk_glpk_adapter.h"
00074

```

```

00075 #include "mtk_div_1d.h"
00076
00077 namespace mtk {
00078
00079 std::ostream& operator <<(std::ostream &stream, mtk::Div1D &in) {
00080
00082
00083     stream << "divergence_[0] = " << std::setw(9) << in.divergence_[0] <<
00084         std::endl;
00085
00087
00088     stream << "divergence_[1:" << in.order_accuracy_ << "] = ";
00089     for (auto ii = 1; ii <= in.order_accuracy_; ++ii) {
00090         stream << std::setw(9) << in.divergence_[ii] << " ";
00091     }
00092     stream << std::endl;
00093
00094     if (in.order_accuracy_ > 2) {
00095
00097
00098         stream << "divergence_[" << in.order_accuracy_ + 1 << ":" <<
00099             2*in.order_accuracy_ << "] = ";
00100         for (auto ii = in.order_accuracy_ + 1; ii <= 2*in.
00101             order_accuracy_; ++ii) {
00102             stream << std::setw(9) << in.divergence_[ii] << " ";
00103         }
00104         stream << std::endl;
00105
00107         auto offset = (2*in.order_accuracy_ + 1);
00108         int mm{};
00109         for (auto ii = 0; ii < in.dim_null_; ++ii) {
00110             stream << "divergence_[" << offset + mm << ":" <<
00111                 offset + mm + in.num_bndy_coeffs_ - 1 << "] = ";
00112             for (auto jj = 0; jj < in.num_bndy_coeffs_; ++jj) {
00113                 auto value = in.divergence_[offset + mm];
00114                 stream << std::setw(9) << value << " ";
00115                 ++mm;
00116             }
00117             stream << std::endl;
00118         }
00119     }
00120
00121     return stream;
00122 }
00123 }
00124
00125 mtk::Div1D::Div1D():
00126     order_accuracy_(mtk::kDefaultOrderAccuracy),
00127     dim_null_(),
00128     num_bndy_coeffs_(),
00129     divergence_length_(),
00130     minrow_(),
00131     row_(),
00132     coeffs_interior_(),
00133     prem_apps_(),
00134     weights_crs_(),
00135     weights_cbs_(),
00136     mim_bndy_(),
00137     divergence_(),
00138     mimetic_threshold_(mtk::kDefaultMimeticThreshold) {}
00139
00140 mtk::Div1D::Div1D(const Div1D &div):
00141     order_accuracy_(div.order_accuracy_),
00142     dim_null_(div.dim_null_),
00143     num_bndy_coeffs_(div.num_bndy_coeffs_),
00144     divergence_length_(div.divergence_length_),
00145     minrow_(div.minrow_),
00146     row_(div.row_),
00147     coeffs_interior_(div.coeffs_interior_),
00148     prem_apps_(div.prem_apps_),
00149     weights_crs_(div.weights_crs_),
00150     weights_cbs_(div.weights_cbs_),
00151     mim_bndy_(div.mim_bndy_),
00152     divergence_(div.divergence_),
00153     mimetic_threshold_(div.mimetic_threshold_) {}
00154
00155 mtk::Div1D::~Div1D() {
00156
00157     delete[] coeffs_interior_;
00158     coeffs_interior_ = nullptr;

```

```

00159
00160 delete[] prem_apps_;
00161 prem_apps_ = nullptr;
00162
00163 delete[] weights_crs_;
00164 weights_crs_ = nullptr;
00165
00166 delete[] weights_cbs_;
00167 weights_cbs_ = nullptr;
00168
00169 delete[] mim_bndy_;
00170 mim_bndy_ = nullptr;
00171
00172 delete[] divergence_;
00173 divergence_ = nullptr;
00174 }
00175
00176 bool mtk::Div1D::ConstructDiv1D(int order_accuracy,
00177                                 mtk::Real mimetic_threshold) {
00178
00179     #ifdef MTK_PERFORM_PREVENTIONS
00180     mtk::Tools::Prevent(order_accuracy < 2, __FILE__, __LINE__, __func__);
00181     mtk::Tools::Prevent((order_accuracy%2) != 0, __FILE__, __LINE__, __func__);
00182     mtk::Tools::Prevent(mimetic_threshold <= mtk::kZero,
00183                         __FILE__, __LINE__, __func__);
00184
00185     if (order_accuracy >= mtk::kCriticalOrderAccuracyDiv) {
00186         std::cout << "WARNING: Numerical accuracy is critical." << std::endl;
00187     }
00188
00189     std::cout << "order_accuracy_ = " << order_accuracy << std::endl;
00190     std::cout << "mimetic_threshold_ = " << mimetic_threshold << std::endl;
00191     #endif
00192
00193     order_accuracy_ = order_accuracy;
00194     mimetic_threshold_ = mimetic_threshold;
00195
00196     bool abort_construction = ComputeStencilInteriorGrid();
00197
00198     #ifdef MTK_PERFORM_PREVENTIONS
00199     if (!abort_construction) {
00200         std::cerr << "Could NOT complete stage 1." << std::endl;
00201         std::cerr << "Exiting..." << std::endl;
00202         return false;
00203     }
00204     #endif
00205
00206     // At this point, we already have the values for the interior stencil stored
00207     // in the coeffs_interior_ array.
00208
00209     // It is noteworthy, that the 2nd-order-accurate divergence operator has NO
00210     // approximation at the boundary, thus it has no weights. For this case, the
00211     // dimension of the null-space of the Vandermonde matrices used to compute the
00212     // approximating coefficients at the boundary is 0. Ergo, we compute this
00213     // number first and then decide if we must compute anything at the boundary.
00214
00215     dim_null_ = order_accuracy/2 - 1;
00216
00217     if (dim_null_ > 0) {
00218
00219         #ifdef MTK_PRECISION_DOUBLE
00220         num_bndy_coeffs_ = (int) (3.0*((mtk::Real) order_accuracy)/2.0);
00221         #else
00222         num_bndy_coeffs_ = (int) (3.0f*((mtk::Real) order_accuracy)/2.0f);
00223         #endif
00224
00225         // For this we will follow recommendations given in:
00226         //
00227         // http://icl.cs.utk.edu/lapack-forum/viewtopic.php?f=5&t=4506
00228         //
00229         // We will compute the QR Factorization of the transpose, as in the
00230         // following (MATLAB) pseudo-code:
00231         //
00232         // [Q,R] = qr(V'); % Full QR as defined in
00233         // % http://www.stanford.edu/class/ee263/notes/qr_matlab.pdf
00234         //
00235         // null-space = Q(:, last (order_accuracy/2 - 1) columns of Q );
00236         //
00237         // However, given the nature of the Vandermonde matrices we've just

```

```

00242 // computed, they all posses the same null-space. Therefore, we impose the
00243 // convention of computing the null-space of the first Vandermonde matrix
00244 // (west boundary).
00245
00246 abort_construction = ComputeRationalBasisNullSpace();
00247
00248 #ifdef MTK_PERFORM_PREVENTIONS
00249 if (!abort_construction) {
00250     std::cerr << "Could NOT complete stage 2.1." << std::endl;
00251     std::cerr << "Exiting..." << std::endl;
00252     return false;
00253 }
00254 #endif
00255
00257 abort_construction = ComputePreliminaryApproximations();
00259
00260 #ifdef MTK_PERFORM_PREVENTIONS
00261 if (!abort_construction) {
00262     std::cerr << "Could NOT complete stage 2.2." << std::endl;
00263     std::cerr << "Exiting..." << std::endl;
00264     return false;
00265 }
00266 #endif
00267
00269 abort_construction = ComputeWeights();
00271
00272 #ifdef MTK_PERFORM_PREVENTIONS
00273 if (!abort_construction) {
00274     std::cerr << "Could NOT complete stage 2.3." << std::endl;
00275     std::cerr << "Exiting..." << std::endl;
00276     return false;
00277 }
00278 #endif
00279
00281 abort_construction = ComputeStencilBoundaryGrid();
00283
00284 #ifdef MTK_PERFORM_PREVENTIONS
00285 if (!abort_construction) {
00286     std::cerr << "Could NOT complete stage 2.4." << std::endl;
00287     std::cerr << "Exiting..." << std::endl;
00288     return false;
00289 }
00290 #endif
00291
00292 } // End of: if (dim_null_ > 0);
00293
00295 // Once we have the following three collections of data:
00296 // (a) the coefficients for the interior,
00297 // (b) the coefficients for the boundary (if it applies),
00298 // (c) and the weights (if it applies),
00299 // we will store everything in the output array:
00300
00301 abort_construction = AssembleOperator();
00303
00304 #ifdef MTK_PERFORM_PREVENTIONS
00305 if (!abort_construction) {
00306     std::cerr << "Could NOT complete stage 3." << std::endl;
00307     std::cerr << "Exiting..." << std::endl;
00308     return false;
00309 }
00310 #endif
00311
00312 return true;
00313 }
00314
00315 int mtk::Div1D::num_bndy_coeffs() const {
00316     return num_bndy_coeffs_;
00317 }
00318
00319 mtk::Real *mtk::Div1D::coeffs_interior() const {
00320     return coeffs_interior_;
00321 }
00322
00323 mtk::Real *mtk::Div1D::weights_crs() const {
00324

```



```

00327     return weights_crs_;
00328 }
00329
00330 mtk::Real *mtk::Div1D::weights_cbs() const {
00331
00332     return weights_cbs_;
00333 }
00334
00335 mtk::DenseMatrix mtk::Div1D::mim_bndy() const {
00336
00337     mtk::DenseMatrix xx(dim_null_, 3*order_accuracy_/2);
00338
00339     auto counter = 0;
00340     for (auto ii = 0; ii < dim_null_; ++ii) {
00341         for (auto jj = 0; jj < 3*order_accuracy_/2; ++jj) {
00342             xx.SetValue(ii, jj, divergence_[2*order_accuracy_ + 1 + counter]);
00343             counter++;
00344         }
00345     }
00346
00347     return xx;
00348 }
00349
00350 mtk::DenseMatrix mtk::Div1D::ReturnAsDenseMatrix(
00351     const UniStgGrid1D &grid) const {
00352
00353     int nn{grid.num_cells_x()}; // Number of cells on the grid.
00354
00355     #ifdef MTK_PERFORM_PREVENTIONS
00356     mtk::Tools::Prevent(nn <= 0, __FILE__, __LINE__, __func__);
00357     mtk::Tools::Prevent(nn < 3*order_accuracy_ - 1, __FILE__, __LINE__, __func__);
00358     #endif
00359
00360     mtk::Real inv_delta_x{mtk::kOne/grid.delta_x()};
00361
00362     int dd_num_rows = nn + 2;
00363     int dd_num_cols = nn + 1;
00364     int elements_per_row = num_bndy_coeffs_;
00365     int num_extra_rows = dim_null_;
00366
00367     // Output matrix featuring sizes for divergence operators.
00368     mtk::DenseMatrix out(dd_num_rows, dd_num_cols);
00369
00370
00371     auto ee_index = 0;
00372     for (auto ii = 1; ii < num_extra_rows + 1; ii++) {
00373         auto cc = 0;
00374         for (auto jj = 0; jj < dd_num_rows; jj++) {
00375             if (cc >= elements_per_row) {
00376                 out.SetValue(ii, jj, mtk::kZero);
00377             } else {
00378                 out.SetValue(ii, jj, mim_bndy_[ee_index++] * inv_delta_x);
00379                 cc++;
00380             }
00381         }
00382     }
00383
00384
00385     for (auto ii = num_extra_rows + 1;
00386          ii < dd_num_rows - num_extra_rows - 1; ii++) {
00387         auto jj = ii - num_extra_rows - 1;
00388         for (auto cc = 0; cc < order_accuracy_; cc++, jj++) {
00389             out.SetValue(ii, jj, coeffs_interior_[cc] * inv_delta_x);
00390         }
00391     }
00392
00393
00394
00395     ee_index = 0;
00396     for (auto ii = dd_num_rows - 2; ii >= dd_num_rows - num_extra_rows - 1; ii--) {
00397         auto cc = 0;
00398         for (auto jj = dd_num_cols - 1; jj >= 0; jj--) {
00399             if (cc >= elements_per_row) {
00400                 out.SetValue(ii, jj, 0.0);
00401             } else {
00402                 out.SetValue(ii, jj, -mim_bndy_[ee_index++] * inv_delta_x);
00403                 cc++;
00404             }
00405         }
00406     }
00407
00408
00409 }
00410

```

```

00411     return out;
00412 }
00413
00414 bool mtk::Div1D::ComputeStencilInteriorGrid() {
00415
00416
00417
00418     mtk::Real* pp{}; // Spatial coordinates to create interior stencil.
00419
00420     try {
00421         pp = new mtk::Real[order_accuracy_];
00422     } catch (std::bad_alloc &memory_allocation_exception) {
00423         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00424             std::endl;
00425         std::cerr << memory_allocation_exception.what() << std::endl;
00426     }
00427     memset(pp, mtk::kZero, sizeof(pp[0])*order_accuracy_);
00428
00429     #ifdef MTK_PRECISION_DOUBLE
00430     pp[0] = 1.0/2.0 - ((mtk::Real) order_accuracy_)/2.0;
00431     #else
00432     pp[0] = 1.0f/2.0f - ((mtk::Real) order_accuracy_)/2.0f;
00433     #endif
00434
00435     for (auto ii = 1; ii < order_accuracy_; ++ii) {
00436         pp[ii] = pp[ii - 1] + mtk::kOne;
00437     }
00438
00439     #if MTK_VERBOSE_LEVEL > 3
00440     std::cout << "pp =" << std::endl;
00441     for (auto ii = 0; ii < order_accuracy_; ++ii) {
00442         std::cout << std::setw(12) << pp[ii];
00443     }
00444     std::cout << std::endl << std::endl;
00445     #endif
00446
00447
00448
00449     bool transpose{false};
00450
00451     mtk::DenseMatrix vander_matrix(pp,
00452                                     order_accuracy_,
00453                                     order_accuracy_,
00454                                     transpose);
00455
00456     #if MTK_VERBOSE_LEVEL > 4
00457     std::cout << "vander_matrix = " << std::endl;
00458     std::cout << vander_matrix << std::endl;
00459     #endif
00460
00461
00462
00463     try {
00464         coeffs_interior_ = new mtk::Real[order_accuracy_];
00465     } catch (std::bad_alloc &memory_allocation_exception) {
00466         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00467             std::endl;
00468         std::cerr << memory_allocation_exception.what() << std::endl;
00469     }
00470     memset(coeffs_interior_,
00471            mtk::kZero,
00472            sizeof(coeffs_interior_[0])*order_accuracy_);
00473
00474     coeffs_interior_[1] = mtk::kOne;
00475
00476     #if MTK_VERBOSE_LEVEL > 3
00477     std::cout << "oo =" << std::endl;
00478     for (auto ii = 0; ii < order_accuracy_; ++ii) {
00479         std::cout << std::setw(12) << coeffs_interior_[ii] << std::endl;
00480     }
00481     std::cout << std::endl;
00482     #endif
00483
00484
00485
00486     int info{mtk::LAPACKAdapter::SolveDenseSystem(vander_matrix,
00487                                                    coeffs_interior_)};
00488
00489     #ifdef MTK_PERFORM_PREVENTIONS
00490     if (!info) {
00491         std::cout << "System solved! Interior stencil attained!" << std::endl;
00492         std::cout << std::endl;
00493     }
00494     else {
00495         std::cerr << "Something wrong solving system! info = " << info << std::endl;

```

```

00496     std::cerr << "Exiting..." << std::endl;
00497     return false;
00498 }
00499 #endif
00500
00501 #if MTK_VERBOSE_LEVEL > 3
00502 std::cout << "coeffs_interior_" << std::endl;
00503 for (auto ii = 0; ii < order_accuracy_; ++ii) {
00504     std::cout << std::setw(12) << coeffs_interior_[ii];
00505 }
00506 std::cout << std::endl << std::endl;
00507 #endif
00508 delete [] pp;
00509 pp = nullptr;
00510
00511 return true;
00512 }
00513 }
00514
00515 bool mtk::Div1D::ComputeRationalBasisNullSpace(void) {
00516
00517     mtk::Real* gg{}; // Generator vector for the first Vandermonde matrix.
00518
00519
00520
00521     try {
00522         gg = new mtk::Real[num_bndy_coeffs_];
00523     } catch (std::bad_alloc &memory_allocation_exception) {
00524         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00525             std::endl;
00526         std::cerr << memory_allocation_exception.what() << std::endl;
00527     }
00528     memset(gg, mtk::kZero, sizeof(gg[0])*num_bndy_coeffs_);
00529
00530     #ifdef MTK_PRECISION_DOUBLE
00531     gg[0] = -1.0/2.0;
00532     #else
00533     gg[0] = -1.0f/2.0f;
00534     #endif
00535     for (auto ii = 1; ii < num_bndy_coeffs_; ++ii) {
00536         gg[ii] = gg[ii - 1] + mtk::kOne;
00537     }
00538
00539     #if MTK_VERBOSE_LEVEL > 3
00540     std::cout << "gg =" << std::endl;
00541     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
00542         std::cout << std::setw(12) << gg[ii];
00543     }
00544     std::cout << std::endl << std::endl;
00545     #endif
00546
00547
00548
00549     bool tran{true}; // Should I transpose the Vandermonde matrix.
00550
00551     mtk::DenseMatrix vv_west_t(gg, num_bndy_coeffs_, order_accuracy_ + 1, tran);
00552
00553     #if MTK_VERBOSE_LEVEL > 4
00554     std::cout << "vv_west_t =" << std::endl;
00555     std::cout << vv_west_t << std::endl;
00556     #endif
00557
00558
00559
00560     mtk::DenseMatrix qq_t(mtk::LAPACKAdapter::QRFactorDenseMatrix
(vv_west_t));
00561
00562     #if MTK_VERBOSE_LEVEL > 4
00563     std::cout << "QQ^T =" << std::endl;
00564     std::cout << qq_t << std::endl;
00565     #endif
00566
00567
00568
00569     int KK_num_rows_{num_bndy_coeffs_};
00570     int KK_num_cols_{dim_null_};
00571
00572     mtk::DenseMatrix KK(KK_num_rows_, KK_num_cols_);
00573
00574     for (auto ii = num_bndy_coeffs_ - dim_null_; ii < num_bndy_coeffs_; ++ii) {
00575         for (auto jj = 0; jj < num_bndy_coeffs_; ++jj) {
00576             KK.data()[jj*dim_null_ + (ii - (num_bndy_coeffs_ - dim_null_))] =
00577                 qq_t.data()[ii*num_bndy_coeffs_ + jj];
00578         }
00579     }

```

```

00580
00581 #if MTK_VERBOSE_LEVEL > 2
00582 std::cout << "KK =" << std::endl;
00583 std::cout << KK << std::endl;
00584 std::cout << "KK.num_rows() = " << KK.num_rows() << std::endl;
00585 std::cout << "KK.num_cols() = " << KK.num_cols() << std::endl;
00586 std::cout << std::endl;
00587 #endif
00588
00590
00591 // Scale thus requesting that the last entries of the attained basis for the
00592 // null-space, adopt the pattern we require.
00593 // Essentially we will implement the following MATLAB pseudo-code:
00594 // scalers = KK(num_bndy_approx - (dim_null - 1):num_bndy_approx,:)\B
00595 // SK = KK*scalers
00596 // where SK is the scaled null-space.
00597
00598 // In this point, we almost have all the data we need correctly allocated
00599 // in memory. We will create the matrix II_, and elements we wish to scale in
00600 // the KK array. Using the concept of the leading dimension, we could just
00601 // use KK, with the correct leading dimension and that is it. BUT I DO NOT
00602 // GET how does it work. So I will just create a matrix with the content of
00603 // this array that we need, solve for the scalers and then scale the
00604 // whole KK:
00605
00606 // We will then create memory for that sub-matrix of KK (SUBK).
00607
00608 mtk::DenseMatrix SUBK(dim_null_,dim_null_);
00609
00610 for (auto ii = num_bndy_coeffs_ - dim_null_; ii < num_bndy_coeffs_; ++ii) {
00611     for (auto jj = 0; jj < dim_null_; ++jj) {
00612         SUBK.data()[ (ii - (num_bndy_coeffs_ - dim_null_))*dim_null_ + jj] =
00613             KK.data()[ii*dim_null_ + jj];
00614     }
00615 }
00616
00617 #if MTK_VERBOSE_LEVEL > 4
00618 std::cout << "SUBK =" << std::endl;
00619 std::cout << SUBK << std::endl;
00620 #endif
00621
00622 SUBK.Transpose();
00623
00624 #if MTK_VERBOSE_LEVEL > 4
00625 std::cout << "SUBK^T =" << std::endl;
00626 std::cout << SUBK << std::endl;
00627 #endif
00628
00629 bool padded{false};
00630 tran = false;
00631
00632 mtk::DenseMatrix II(dim_null_, padded, tran);
00633
00634 #if MTK_VERBOSE_LEVEL > 4
00635 std::cout << "II =" << std::endl;
00636 std::cout << II << std::endl;
00637 #endif
00638
00639 // Solve the system to compute the scalers.
00640 // An example of the system to solve, for k = 8, is:
00641 //
00642 // SUBK*scalers = II_ or
00643 //
00644 // | 0.386018 -0.0339244 -0.129478 | | 1 0 0 |
00645 // | -0.119774 0.0199423 0.0558632 |*scalers = | 0 1 0 |
00646 // | 0.0155708 -0.00349546 -0.00853182 | | 0 0 1 |
00647 //
00648 // Notice this is a nrhs = 3 system.
00649 // Noteworthy: we do NOT ACTUALLY ALLOCATE space for the scalers... they
00650 // will be stored in the created identity matrix.
00651 // Let us first transpose SUBK (because of LAPACK):
00652
00653 int info{mtk::LAPACKAdapter::SolveDenseSystem(SUBK, II)};
00654
00655 #ifdef MTK_PERFORM_PREVENTIONS
00656 if (!info) {
00657     std::cout << "System successfully solved!" <<
00658         std::endl;
00659 } else {
00660     std::cerr << "Something went wrong solving system! info = " << info <<
00661         std::endl;

```

```

00662     std::cerr << "Exiting..." << std::endl;
00663     return false;
00664 }
00665 std::cout << std::endl;
00666 #endif
00667
00668 #if MTK_VERBOSE_LEVEL > 4
00669 std::cout << "Computed scalars:" << std::endl;
00670 std::cout << II << std::endl;
00671 #endif
00672
00673 // Multiply the two matrices to attain a scaled basis for null-space.
00674
00675 rat_basis_null_space_ = mtk::BLASAdapter::RealDenseMM(KK, II);
00676
00677 #if MTK_VERBOSE_LEVEL > 4
00678 std::cout << "Rational basis for the null-space:" << std::endl;
00679 std::cout << rat_basis_null_space_ << std::endl;
00680 #endif
00681
00682 // At this point, we have a rational basis for the null-space, with the
00683 // pattern we need! :)
00684
00685 delete [] gg;
00686 gg = nullptr;
00687
00688 return true;
00689 }
00690
00691 bool mtk::Div1D::ComputePreliminaryApproximations(void) {
00692
00693     mtk::Real *gg{}; // Generator vector for the first approximation.
00694
00695     try {
00696         gg = new mtk::Real[num_bndy_coeffs_];
00697     } catch (std::bad_alloc &memory_allocation_exception) {
00698         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00699         std::endl;
00700         std::cerr << memory_allocation_exception.what() << std::endl;
00701     }
00702     memset(gg, mtk::kZero, sizeof(gg[0])*num_bndy_coeffs_);
00703
00704     #ifdef MTK_PRECISION_DOUBLE
00705     gg[0] = -1.0/2.0;
00706     #else
00707     gg[0] = -1.0f/2.0f;
00708     #endif
00709     for (auto ii = 1; ii < num_bndy_coeffs_; ++ii) {
00710         gg[ii] = gg[ii - 1] + mtk::kOne;
00711     }
00712
00713     #if MTK_VERBOSE_LEVEL > 3
00714     std::cout << "gg0 =" << std::endl;
00715     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
00716         std::cout << std::setw(12) << gg[ii];
00717     }
00718     std::cout << std::endl << std::endl;
00719     #endif
00720
00721     // Allocate 2D array to store the collection of preliminary approximations.
00722
00723     try {
00724         prem_apps_ = new mtk::Real[num_bndy_coeffs_*dim_null_];
00725     } catch (std::bad_alloc &memory_allocation_exception) {
00726         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00727         std::endl;
00728         std::cerr << memory_allocation_exception.what() << std::endl;
00729     }
00730     memset(prem_apps_,
00731            mtk::kZero,
00732            sizeof(prem_apps_[0])*num_bndy_coeffs_*dim_null_);
00733
00734     for (auto ll = 0; ll < dim_null_; ++ll) {
00735
00736         // Re-check new generator vector for every iteration except for the first.
00737         #if MTK_VERBOSE_LEVEL > 3
00738         if (ll > 0) {
00739             std::cout << "gg" << ll << " =" << std::endl;
00740             for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
00741                 std::cout << std::setw(12) << gg[ii];

```

```

00745     }
00746     std::cout << std::endl << std::endl;
00747 }
00748 #endif
00749
00751
00752 bool transpose{false};
00753
00754 mtk::DenseMatrix AA_(gg,
00755     num_bndy_coeffs_, order_accuracy_ + 1,
00756     transpose);
00757
00758 #if MTK_VERBOSE_LEVEL > 4
00759 std::cout << "AA_" << ll << " =" << std::endl;
00760 std::cout << AA_ << std::endl;
00761 #endif
00762
00764
00765 mtk::Real *ob{};
00766
00767 auto ob_ld = num_bndy_coeffs_;
00768
00769 try {
00770     ob = new mtk::Real[ob_ld];
00771 } catch (std::bad_alloc &memory_allocation_exception) {
00772     std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00773         std::endl;
00774     std::cerr << memory_allocation_exception.what() << std::endl;
00775 }
00776 memset(ob, mtk::kZero, sizeof(ob[0])*ob_ld);
00777
00778 ob[1] = mtk::kOne;
00779
00780 #if MTK_VERBOSE_LEVEL > 4
00781 std::cout << "ob =" << std::endl << std::endl;
00782 for (auto ii = 0; ii < ob_ld; ++ii) {
00783     std::cout << std::setw(12) << ob[ii] << std::endl;
00784 }
00785 std::cout << std::endl;
00786 #endif
00787
00789
00790 // However, this is an under-determined system of equations. So we can not
00791 // use the same LAPACK routine (dgesv_). We will instead use dgels_, through
00792 // our LAPACKAdapter class.
00793
00794 int info_{
00795     mtk::LAPACKAdapter::SolveRectangularDenseSystem(AA_,
00796 ob, ob_ld)};
00797
00798 #ifdef MTK_PERFORM_PREVENTIONS
00799 if (!info_) {
00800     std::cout << "System successfully solved!" << std::endl << std::endl;
00801 } else {
00802     std::cerr << "Error solving system! info = " << info_ << std::endl;
00803 }
00804 #endif
00805
00806 #if MTK_VERBOSE_LEVEL > 3
00807 std::cout << "ob =" << std::endl;
00808 for (auto ii = 0; ii < ob_ld; ++ii) {
00809     std::cout << std::setw(12) << ob[ii] << std::endl;
00810 }
00811 std::cout << std::endl;
00812 #endif
00814
00815 // This implies a DAXPY operation. However, we must construct the arguments
00816 // for this operation.
00817
00819 // Save them into the ob_bottom array:
00820
00821 Real *ob_bottom{}; // Bottom part of the attained kernel used to scale it.
00822
00823 try {
00824     ob_bottom = new mtk::Real[dim_null_];
00825 } catch (std::bad_alloc &memory_allocation_exception) {
00826     std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00827         std::endl;
00828     std::cerr << memory_allocation_exception.what() << std::endl;
00829 }

```

```

00830     memset(ob_bottom, mtk::kZero, sizeof(ob_bottom[0])*dim_null_);
00831
00832     for (auto ii = 0; ii < dim_null_; ++ii) {
00833         ob_bottom[(dim_null_ - 1) - ii] = ob[num_bndy_coeffs_ - ii - 1];
00834     }
00835
00836     #if MTK_VERBOSE_LEVEL > 3
00837     std::cout << "ob_bottom =" << std::endl;
00838     for (auto ii = 0; ii < dim_null_; ++ii) {
00839         std::cout << std::setw(12) << ob_bottom[ii] << std::endl;
00840     }
00841     std::cout << std::endl;
00842     #endif
00843
00844
00845     // We must computed an scaled ob, sob, using the scaled null-space in
00846     // rat_basis_null_space_.
00847     // Such operation is: sob = ob - rat_basis_null_space_*ob_bottom
00848     // or:
00849     // thus:
00850     //      Y =      a*A      *x      +      b*Y (DAXPY).
00851
00852     #if MTK_VERBOSE_LEVEL > 3
00853     std::cout << "Rational basis for the null-space:" << std::endl;
00854     std::cout << rat_basis_null_space_ << std::endl;
00855     #endif
00856
00857     mtk::Real alpha{-mtk::kOne};
00858     mtk::Real beta{mtk::kOne};
00859
00860     mtk::BLASAdapter::RealDenseMV(alpha, rat_basis_null_space_,
00861                                     ob_bottom, beta, ob);
00862
00863     #if MTK_VERBOSE_LEVEL > 3
00864     std::cout << "scaled ob:" << std::endl;
00865     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
00866         std::cout << std::setw(12) << ob[ii] << std::endl;
00867     }
00868     std::cout << std::endl;
00869     #endif
00870
00871     // We save the recently scaled solution, into an array containing these.
00872     // We can NOT start building the pi matrix, simply because I want that part
00873     // to be separated since its construction depends on the algorithm we want
00874     // to implement.
00875
00876     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
00877         prem_apps_[ii*dim_null_ + 11] = ob[ii];
00878     }
00879
00880     // After the first iteration, simply shift the entries of the last
00881     // generator vector used:
00882     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
00883         gg[ii]--;
00884     }
00885
00886     // Garbage collection for this loop:
00887     delete[] ob;
00888     ob = nullptr;
00889
00890     delete[] ob_bottom;
00891     ob_bottom = nullptr;
00892 } // End of: for (ll = 0; ll < dim_null; ll++);
00893
00894 #if MTK_VERBOSE_LEVEL > 4
00895 std::cout << "Matrix post-scaled preliminary apps: " << std::endl;
00896 for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
00897     for (auto jj = 0; jj < dim_null_; ++jj) {
00898         std::cout << std::setw(12) << prem_apps_[ii*dim_null_ + jj];
00899     }
00900     std::cout << std::endl;
00901 }
00902 std::cout << std::endl;
00903 #endif
00904
00905 delete[] gg;
00906 gg = nullptr;
00907
00908 return true;
00909 }
00910
00911 bool mtk::Div1D::ComputeWeights(void) {

```

```

00912
00913 // Matrix to compute the weights as in the CRSA.
00914 mtk::DenseMatrix pi(num_bndy_coeffs_, num_bndy_coeffs_ - 1);
00915
00916
00917 // Assemble the pi matrix using:
00918 // 1. The collection of scaled preliminary approximations.
00919 // 2. The collection of coefficients approximating at the interior.
00920 // 3. The scaled basis for the null-space.
00921
00922 // 1.1. Process array of scaled preliminary approximations.
00923
00924 // These are queued in scaled_solutions. Each one of these, will be a column
00925 // of the pi matrix:
00926 for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
00927     for (auto jj = 0; jj < dim_null_; ++jj) {
00928         pi.data()[ii*(2*dim_null_ + (order_accuracy_/2 + 1)) + jj] =
00929             prem_apps_[ii*dim_null_ + jj];
00930     }
00931 }
00932
00933 // 1.2. Add columns from known stencil approximating at the interior.
00934
00935 // However, these must be padded by zeros, according to their position in the
00936 // final pi matrix:
00937 auto mm = 0;
00938 for (auto jj = dim_null_; jj < order_accuracy_; ++jj) {
00939     for (auto ii = 0; ii < order_accuracy_; ++ii) {
00940         pi.data()[ii*(2*dim_null_ + (order_accuracy_/2 + 1)) + jj] =
00941             coeffs_interior_[ii];
00942     }
00943     ++mm;
00944 }
00945
00946 rat_basis_null_space_.OrderColMajor();
00947
00948 #if MTK_VERBOSE_LEVEL > 4
00949 std::cout << "Rational basis for the null-space (col. major):" << std::endl;
00950 std::cout << rat_basis_null_space_ << std::endl;
00951 #endif
00952
00953 // 1.3. Add final set of columns: rational basis for null-space.
00954 for (auto jj = dim_null_ + (order_accuracy_/2 + 1);
00955      jj < num_bndy_coeffs_ - 1;
00956      ++jj) {
00957     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
00958         auto og =
00959             (jj - (dim_null_ + (order_accuracy_/2 + 1)))*num_bndy_coeffs_ + ii;
00960         auto de = ii*(2*dim_null_ + (order_accuracy_/2 + 1)) + jj;
00961         pi.data()[de] = rat_basis_null_space_.data()[og];
00962     }
00963 }
00964
00965 #if MTK_VERBOSE_LEVEL > 3
00966 std::cout << "coeffs_interior_" << std::endl;
00967 for (auto ii = 0; ii < order_accuracy_; ++ii) {
00968     std::cout << std::setw(12) << coeffs_interior_[ii];
00969 }
00970 std::cout << std::endl << std::endl;
00971 #endif
00972
00973 #if MTK_VERBOSE_LEVEL > 4
00974 std::cout << "Constructed pi matrix for CRS Algorithm: " << std::endl;
00975 std::cout << pi << std::endl;
00976 #endif
00977
00978 // This imposes the mimetic condition.
00979
00980 mtk::Real *hh{}; // Right-hand side to compute weights in the C{R,B}SA.
00981
00982 try {
00983     hh = new mtk::Real[num_bndy_coeffs_];
00984 } catch (std::bad_alloc &memory_allocation_exception) {
00985     std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00986         std::endl;
00987     std::cerr << memory_allocation_exception.what() << std::endl;
00988 }
00989
00990 memset(hh, mtk::kZero, sizeof(hh[0])*num_bndy_coeffs_);
00991
00992 hh[0] = -mtk::kOne;

```



```

00995     for (auto ii = (order_accuracy_/2 + 2 - 1); ii < num_bndy_coeffs_; ++ii) {
00996         auto aux_xx = mtk::kZero;
00997         for (auto jj = 0; jj < ((ii - (order_accuracy_/2 - 1)) - 1); ++jj) {
00998             aux_xx += coeffs_interior_[jj];
00999         }
01000         hh[ii] = -mtk::kOne*aux_xx;
01001     }
01002
01003
01004
01005     // That is, we construct a system, to solve for the weights.
01006
01007     // Once again we face the challenge of solving with LAPACK. However, for the
01008     // CRSA, this matrix PI is over-determined, since it has more rows than
01009     // unknowns. However, according to the theory, the solution to this system is
01010     // unique. We will use dgels_.
01011
01012     try {
01013         weights_cbs_ = new mtk::Real[num_bndy_coeffs_];
01014     } catch (std::bad_alloc &memory_allocation_exception) {
01015         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
01016             std::endl;
01017         std::cerr << memory_allocation_exception.what() << std::endl;
01018     }
01019     memset(weights_cbs_, mtk::kZero, sizeof(weights_cbs_[0])*num_bndy_coeffs_);
01020
01021     int weights_ld{pi.num_cols() + 1};
01022
01023     // Preserve hh.
01024     std::copy(hh, hh + weights_ld, weights_cbs_);
01025
01026     pi.Transpose();
01027
01028     int info{mtk::LAPACKAdapter::SolveRectangularDenseSystem(
01029         pi,
01030         weights_cbs_,
01031         weights_ld)};
01032
01033     #ifdef MTK_PERFORM_PREVENTIONS
01034     if (!info) {
01035         std::cout << "System successfully solved!" << std::endl << std::endl;
01036     } else {
01037         std::cerr << "Error solving system! info = " << info << std::endl;
01038     }
01039     #endif
01040
01041     #if MTK_VERBOSE_LEVEL > 3
01042     std::cout << "hh =" << std::endl;
01043     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
01044         std::cout << std::setw(11) << hh[ii] << std::endl;
01045     }
01046     std::cout << std::endl;
01047     #endif
01048
01049     // Preserve the original weights for research.
01050
01051     try {
01052         weights_crs_ = new mtk::Real[num_bndy_coeffs_];
01053     } catch (std::bad_alloc &memory_allocation_exception) {
01054         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
01055             std::endl;
01056         std::cerr << memory_allocation_exception.what() << std::endl;
01057     }
01058     memset(weights_crs_, mtk::kZero, sizeof(weights_crs_[0])*num_bndy_coeffs_);
01059
01060     std::copy(weights_cbs_, weights_cbs_ + (weights_ld - 1), weights_crs_);
01061
01062     #if MTK_VERBOSE_LEVEL > 3
01063     std::cout << "weights_CRSA + lambda =" << std::endl;
01064     for (auto ii = 0; ii < weights_ld - 1; ++ii) {
01065         std::cout << std::setw(12) << weights_crs_[ii] << std::endl;
01066     }
01067     std::cout << std::endl;
01068     #endif
01069
01070
01071     if (order_accuracy_ >= mtk::kCriticalOrderAccuracyDiv) {
01072         int minrow{std::numeric_limits<int>::infinity()};
01073
01074         mtk::Real norm{mtk::BLASAdapter::RealNRM2(weights_cbs_,
01075             order_accuracy_)};

```

```

01076     mtk::Real minnorm_{std::numeric_limits<mtk::Real>::infinity()};
01077
01079     mtk::DenseMatrix phi(order_accuracy_ + 1, order_accuracy_);
01080
01081     for (auto ii = 0; ii < order_accuracy_ + 1; ++ii) {
01082         for (auto jj = 0; jj < dim_null_; ++jj) {
01083             phi.data()[ii*(order_accuracy_ + 1) + jj] = prem_apps_[ii*dim_null_ + jj];
01084         }
01085     }
01086
01087     int aux{}; // Auxiliary variable.
01088     for (auto jj = dim_null_; jj < dim_null_ + 2; ++jj) {
01089         for (auto ii = 0; ii < order_accuracy_; ++ii) {
01090             phi.data()[ii*(order_accuracy_ + 1) + jj] = coeffs_interior[ii];
01091         }
01092         ++aux;
01093     }
01094
01095     for (auto jj = order_accuracy_ - 1; jj >= order_accuracy_ - dim_null_; jj--) {
01096         for (auto ii = 0; ii < order_accuracy_ + 1; ++ii) {
01097             phi.data()[ii*(order_accuracy_ + 1) + jj] = mtk::kZero;
01098         }
01099     }
01100
01101     for (auto jj = 0; jj < order_accuracy_ + 1; ++jj) {
01102         for (auto ii = 0; ii < dim_null_; ++ii) {
01103             phi.data()[ii*(order_accuracy_ + 1) + jj] =
01104                 -premi_apps_[ii*(order_accuracy_ + 1) + jj];
01105         }
01106     }
01107
01108     for (auto ii = 0; ii < order_accuracy_/2; ++ii) {
01109         for (auto jj = dim_null_ + 2; jj < order_accuracy_; ++jj) {
01110             auto swap = phi.data()[ii*(order_accuracy_ + 1) + jj];
01111             phi.data()[ii*(order_accuracy_ + 1) + jj] =
01112                 phi.data()[ii*(order_accuracy_ + 1) + jj];
01113             phi.data()[ii*(order_accuracy_ + 1) + jj] = swap;
01114         }
01115     }
01116
01117     #if MTK_VERBOSE_LEVEL > 4
01118     std::cout << "Constructed PHI matrix for CBS Algorithm: " << std::endl;
01119     std::cout << phi << std::endl;
01120     #endif
01121
01122     mtk::Real *lamed{}; // Used to build big lambda.
01123
01124     try {
01125         lamed = new mtk::Real[dim_null_];
01126     } catch (std::bad_alloc &memory_allocation_exception) {
01127         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
01128             std::endl;
01129         std::cerr << memory_allocation_exception.what() << std::endl;
01130     }
01131     memset(lamed, mtk::kZero, sizeof(lamed[0])*dim_null_);
01132
01133     for (auto ii = 0; ii < dim_null_; ++ii) {
01134         lamed[ii] = hh[ii + order_accuracy_ + 1];
01135     }
01136
01137     #if MTK_VERBOSE_LEVEL > 3
01138     std::cout << "lamed =" << std::endl;
01139     for (auto ii = 0; ii < dim_null_; ++ii) {
01140         std::cout << std::setw(12) << lamed[ii] << std::endl;
01141     }
01142     std::cout << std::endl;
01143     #endif
01144
01145     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
01146         mtk::Real temp = mtk::kZero;
01147         for (auto jj = 0; jj < dim_null_; ++jj) {
01148             temp = temp +
01149                 lamed[jj]*rat_basis_null_space_.data()[jj*num_bndy_coeffs_ + ii];
01150         }
01151         hh[ii] = hh[ii] - temp;
01152     }
01153
01154     #if MTK_VERBOSE_LEVEL > 3
01155     std::cout << "big_lambda =" << std::endl;
01156

```

```

01159     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
01160         std::cout << std::setw(12) << hh[ii] << std::endl;
01161     }
01162     std::cout << std::endl;
01163     #endif
01164
01165     int copy_result{};
01166
01167     mtk::Real normerr_; // Norm of the error for the solution on each row.
01168
01169     for(auto row_ = 0; row_ < order_accuracy_ + 1; ++row_) {
01170         normerr_ = mtk::GLPKAdapter::SolveSimplexAndCompare(phi.
01171 data(),
01172                                     order_accuracy_ + 1,
01173                                     order_accuracy_,
01174                                     order_accuracy_,
01175                                     hh,
01176                                     weights_cbs_,
01177                                     row_,
01178                                     mimetic_threshold_,
01179                                     copy_result);
01180
01181         mtk::Real aux{normerr_/norm_};
01182
01183         #if MTK_VERBOSE_LEVEL > 2
01184             std::cout << "Relative norm: " << aux << " " << std::endl;
01185             std::cout << std::endl;
01186         #endif
01187
01188         if (aux < minnorm_) {
01189             minnorm_ = aux;
01190             minrow_ = row_;
01191         }
01192     }
01193
01194     #if MTK_VERBOSE_LEVEL > 3
01195     std::cout << "weights_CBSA + lambda (after brute force search):" <<
01196     std::endl;
01197     for (auto ii = 0; ii < num_bndy_coeffs_ - 1; ++ii) {
01198         std::cout << std::setw(12) << weights_cbs_[ii] << std::endl;
01199     }
01200     std::cout << std::endl;
01201     #endif
01202
01203     // After we know which row yields the smallest relative norm that row is
01204     // chosen to be the objective function and the result of the optimizer is
01205     // chosen to be the new weights_.
01206
01207     #if MTK_VERBOSE_LEVEL > 2
01208     std::cout << "Minimum Relative Norm " << minnorm_ << " found at row " <<
01209     minrow_ + 1 << std::endl;
01210     std::cout << std::endl;
01211     #endif
01212
01213     copy_result = 1;
01214     normerr_ = mtk::GLPKAdapter::SolveSimplexAndCompare(phi.
01215 data(),
01216                                     order_accuracy_ + 1,
01217                                     order_accuracy_,
01218                                     order_accuracy_,
01219                                     hh,
01220                                     weights_cbs_,
01221                                     minrow_,
01222                                     mimetic_threshold_,
01223                                     copy_result);
01224
01225     mtk::Real aux_{normerr_/norm_};
01226     #if MTK_VERBOSE_LEVEL > 2
01227         std::cout << "Relative norm: " << aux_ << std::endl;
01228         std::cout << std::endl;
01229     #endif
01230
01231     delete [] lamed;
01232     lamed = nullptr;
01233 }
01234
01235 delete [] hh;
01236 hh = nullptr;
01237
01238 return true;
01239 }

```

```

01240
01241 bool mtk::Div1D::ComputeStencilBoundaryGrid(void) {
01242
01243     #if MTK_VERBOSE_LEVEL > 3
01244     std::cout << "weights_CBSA + lambda =" << std::endl;
01245     for (auto ii = 0; ii < num_bndy_coeffs_ - 1; ++ii) {
01246         std::cout << std::setw(12) << weights_cbs_[ii] << std::endl;
01247     }
01248     std::cout << std::endl;
01249     #endif
01250
01252
01253     mtk::Real *lambda{}; // Collection of bottom values from weights_.
01254
01255     try {
01256         lambda = new mtk::Real[dim_null_];
01257     } catch (std::bad_alloc &memory_allocation_exception) {
01258         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
01259             std::endl;
01260         std::cerr << memory_allocation_exception.what() << std::endl;
01261     }
01262     memset(lambda, mtk::kZero, sizeof(lambda[0])*dim_null_);
01263
01264     for (auto ii = 0; ii < dim_null_; ++ii) {
01265         lambda[ii] = weights_cbs_[order_accuracy_ + ii];
01266     }
01267
01268     #if MTK_VERBOSE_LEVEL > 3
01269     std::cout << "lambda =" << std::endl;
01270     for (auto ii = 0; ii < dim_null_; ++ii) {
01271         std::cout << std::setw(12) << lambda[ii] << std::endl;
01272     }
01273     std::cout << std::endl;
01274     #endif
01275
01277
01278     mtk::Real *alpha{}; // Collection of alpha values.
01279
01280     try {
01281         alpha = new mtk::Real[dim_null_];
01282     } catch (std::bad_alloc &memory_allocation_exception) {
01283         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
01284             std::endl;
01285         std::cerr << memory_allocation_exception.what() << std::endl;
01286     }
01287     memset(alpha, mtk::kZero, sizeof(alpha[0])*dim_null_);
01288
01289     for (auto ii = 0; ii < dim_null_; ++ii) {
01290         alpha[ii] = lambda[ii]/weights_cbs_[ii] ;
01291     }
01292
01293     #if MTK_VERBOSE_LEVEL > 3
01294     std::cout << "alpha =" << std::endl;
01295     for (auto ii = 0; ii < dim_null_; ++ii) {
01296         std::cout << std::setw(12) << alpha[ii] << std::endl;
01297     }
01298     std::cout << std::endl;
01299     #endif
01300
01302
01303     try {
01304         mim_bndy_ = new mtk::Real[num_bndy_coeffs_*dim_null_];
01305     } catch (std::bad_alloc &memory_allocation_exception) {
01306         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
01307             std::endl;
01308         std::cerr << memory_allocation_exception.what() << std::endl;
01309     }
01310     memset(mim_bndy_,
01311         mtk::kZero,
01312         sizeof(mim_bndy_[0])*num_bndy_coeffs_*dim_null_);
01313
01314     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
01315         for (auto jj = 0; jj < dim_null_; ++jj) {
01316             mim_bndy_[ii*dim_null_ + jj] =
01317                 prem_apps_[ii*dim_null_ + jj] +
01318                 alpha[jj]*rat_basis_null_space_.data()[jj*num_bndy_coeffs_ + ii];
01319         }
01320     }
01321
01322     #if MTK_VERBOSE_LEVEL > 3
01323     std::cout << "Collection of mimetic approximations:" << std::endl;

```

```

01324     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
01325         for (auto jj = 0; jj < dim_null_; ++jj) {
01326             std::cout << std::setw(13) << mim_bndy_[ii*dim_null_ + jj];
01327         }
01328         std::cout << std::endl;
01329     }
01330     std::cout << std::endl;
01331 #endif
01332
01333     delete[] lambda;
01334     lambda = nullptr;
01335
01336     delete[] alpha;
01337     alpha = nullptr;
01338
01339     return true;
01340 }
01341
01342 bool mtk::Div1D::AssembleOperator(void) {
01343
01344     // The output array will have this form:
01345     // 1. The first entry of the array will contain used order order_accuracy_.
01346     // 2. The second entry of the array will contain the collection of
01347     // approximating coefficients for the interior of the grid.
01348     // 3. IF order_accuracy_ > 2, then the third entry will contain a collection
01349     // of weights.
01350     // 4. IF order_accuracy_ > 2, the next dim_null_ entries will contain the
01351     // collections of approximating coefficients for the west boundary of the
01352     // grid.
01353
01354     if (order_accuracy_ > mtk::kDefaultOrderAccuracy) {
01355         divergence_length_ =
01356             1 + order_accuracy_ + order_accuracy_ + dim_null_*num_bndy_coeffs_;
01357     } else {
01358         divergence_length_ = 1 + order_accuracy_;
01359     }
01360
01361     #if MTK_VERBOSE_LEVEL > 2
01362     std::cout << "divergence_length_ = " << divergence_length_ << std::endl;
01363 #endif
01364
01365     try {
01366         divergence_ = new double[divergence_length_];
01367     } catch (std::bad_alloc &memory_allocation_exception) {
01368         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
01369             std::endl;
01370         std::cerr << memory_allocation_exception.what() << std::endl;
01371     }
01372     memset(divergence_, mtk::kZero, sizeof(divergence_[0])*divergence_length_);
01373
01374
01375     divergence_[0] = order_accuracy_;
01376
01377
01378     for (auto ii = 0; ii < order_accuracy_; ++ii) {
01379         divergence_[ii + 1] = coeffs_interior_[ii];
01380     }
01381
01382
01383     if (order_accuracy_ > 2) {
01384         for (auto ii = 0; ii < order_accuracy_; ++ii) {
01385             divergence_[1 + order_accuracy_ + ii] = weights_cbs_[ii];
01386         }
01387     }
01388
01389     if (order_accuracy_ > 2) {
01390         auto offset = (2*order_accuracy_ + 1);
01391         int mm{};
01392         for (auto ii = 0; ii < dim_null_; ++ii) {
01393             for (auto jj = 0; jj < num_bndy_coeffs_; ++jj) {
01394                 divergence_[offset + (mm)] = mim_bndy_[jj*dim_null_ + ii];
01395                 ++mm;
01396             }
01397         }
01398     }
01399
01400     #if MTK_VERBOSE_LEVEL > 1
01401     std::cout << "1D " << order_accuracy_ << "-order div built!" << std::endl;
01402     std::cout << std::endl;
01403 #endif

```



```

00018 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00019 and a copy of the modified files should be reported once modifications are
00020 completed, unless these modifications are made through the project's GitHub
00021 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00022 should be developed and included in any deliverable.
00023
00024 2. Redistributions of source code must be done through direct
00025 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00026
00027 3. Redistributions in binary form must reproduce the above copyright notice,
00028 this list of conditions and the following disclaimer in the documentation and/or
00029 other materials provided with the distribution.
00030
00031 4. Usage of the binary form on proprietary applications shall require explicit
00032 prior written permission from the the copyright holders, and due credit should
00033 be given to the copyright holders.
00034
00035 5. Neither the name of the copyright holder nor the names of its contributors
00036 may be used to endorse or promote products derived from this software without
00037 specific prior written permission.
00038
00039 The copyright holders provide no reassurances that the source code provided does
00040 not infringe any patent, copyright, or any other intellectual property rights of
00041 third parties. The copyright holders disclaim any liability to any recipient for
00042 claims brought against recipient by any third party for infringement of that
00043 parties intellectual property rights.
00044
00045 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00046 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00047 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00048 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00049 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00050 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00051 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00052 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00053 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00054 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00055 */
00056
00057 #include <cstdlib>
00058 #include <cstdio>
00059
00060 #include <iostream>
00061 #include <iomanip>
00062
00063 #include "mtk_roots.h"
00064 #include "mtk_enums.h"
00065 #include "mtk_uni_stg_grid_ld.h"
00066 #include "mtk_div_ld.h"
00067 #include "mtk_div_2d.h"
00068
00069 mtk::Div2D::Div2D():
00070     order_accuracy_(
00071         mimetic_threshold_() {}
00072
00073 mtk::Div2D::Div2D(const Div2D &div):
00074     order_accuracy_(div.order_accuracy_),
00075     mimetic_threshold_(div.mimetic_threshold_) {}
00076
00077 mtk::Div2D::~Div2D() {}
00078
00079 bool mtk::Div2D::ConstructDiv2D(const
00080     mtk::UniStgGrid2D &grid,
00081     int order_accuracy,
00082     mtk::Real mimetic_threshold) {
00083     int num_cells_x = grid.num_cells_x();
00084     int num_cells_y = grid.num_cells_y();
00085
00086     int mx = num_cells_x + 2; // Dx vertical dimension.
00087     int nx = num_cells_x + 1; // Dx horizontal dimension.
00088     int my = num_cells_y + 2; // Dy vertical dimension.
00089     int ny = num_cells_y + 1; // Dy horizontal dimension.
00090
00091     mtk::Div1D div;
00092
00093     bool info = div.ConstructDiv1D(order_accuracy, mimetic_threshold);
00094
00095     #ifdef MTK_PERFORM_PREVENTIONS
00096     if (!info) {
00097         std::cerr << "Mimetic div could not be built." << std::endl;

```

```

00098     return info;
00099 }
00100 #endif
00101
00102 auto west = grid.west_bndy();
00103 auto east = grid.east_bndy();
00104 auto south = grid.south_bndy();
00105 auto north = grid.east_bndy();
00106
00107 mtk::UniStgGrid1D grid_x(west, east, num_cells_x);
00108 mtk::UniStgGrid1D grid_y(south, north, num_cells_y);
00109
00110 mtk::DenseMatrix dx(div.ReturnAsDenseMatrix(grid_x));
00111 mtk::DenseMatrix dy(div.ReturnAsDenseMatrix(grid_y));
00112
00113 bool padded{true};
00114 bool transpose{false};
00115
00116 mtk::DenseMatrix ix(num_cells_x, padded, transpose);
00117 mtk::DenseMatrix iy(num_cells_y, padded, transpose);
00118
00119 mtk::DenseMatrix dxy(mtk::DenseMatrix::Kron(iy, dx));
00120 mtk::DenseMatrix dyx(mtk::DenseMatrix::Kron(dy, ix));
00121
00122 #if MTK_VERBOSE_LEVEL > 2
00123 std::cout << "Dx: " << mx << " by " << nx << std::endl;
00124 std::cout << "Iy : " << num_cells_y << " by " << ny << std::endl;
00125 std::cout << "Dy: " << my << " by " << ny << std::endl;
00126 std::cout << "Ix : " << num_cells_x << " by " << nx << std::endl;
00127 std::cout << "Div 2D: " << mx*num_cells_y + my*num_cells_x << " by " <<
00128     nx*ny << std::endl;
00129 #endif
00130
00131 mtk::DenseMatrix d2d(mx*my, nx*num_cells_y + ny*num_cells_x);
00132
00133 for (auto ii = 0; ii < mx*my; ii++) {
00134     for (auto jj = 0; jj < nx*num_cells_y; jj++) {
00135         d2d.SetValue(ii, jj, dxy.GetValue(ii, jj));
00136     }
00137     for (auto kk = 0; kk < ny*num_cells_x; kk++) {
00138         d2d.SetValue(ii, kk + nx*num_cells_y, dyx.GetValue(ii, kk));
00139     }
00140 }
00141
00142 divergence_ = d2d;
00143
00144 return info;
00145 }
00146
00147 mtk::DenseMatrix mtk::Div2D::ReturnAsDenseMatrix() const {
00148
00149     return divergence_;
00150 }

```

17.81 src/mtk_div_3d.cc File Reference


Implements the class Div3D.

```

#include <cstdlib>
#include <cstdio>
#include <iostream>
#include <iomanip>
#include "mtk_roots.h"
#include "mtk_div_1d.h"
#include "mtk_div_3d.h"

```


Include dependency graph for mtk_div_3d.cc:



17.81.1 Detailed Description

This class implements a 3D divergence operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (CBSA).

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_div_3d.cc](#).

17.82 mtk_div_3d.cc

```

00001
00011 /*
00012 Copyright (C) 2015, Computational Science Research Center, San Diego State
00013 University. All rights reserved.
00014
00015 Redistribution and use in source and binary forms, with or without modification,
00016 are permitted provided that the following conditions are met:
00017
00018 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00019 and a copy of the modified files should be reported once modifications are
00020 completed, unless these modifications are made through the project's GitHub
00021 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00022 should be developed and included in any deliverable.
00023
00024 2. Redistributions of source code must be done through direct
00025 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00026
00027 3. Redistributions in binary form must reproduce the above copyright notice,
00028 this list of conditions and the following disclaimer in the documentation and/or
00029 other materials provided with the distribution.
00030
00031 4. Usage of the binary form on proprietary applications shall require explicit
00032 prior written permission from the the copyright holders, and due credit should
00033 be given to the copyright holders.
00034
00035 5. Neither the name of the copyright holder nor the names of its contributors
00036 may be used to endorse or promote products derived from this software without
00037 specific prior written permission.
00038
00039 The copyright holders provide no reassurances that the source code provided does
00040 not infringe any patent, copyright, or any other intellectual property rights of
00041 third parties. The copyright holders disclaim any liability to any recipient for
00042 claims brought against recipient by any third party for infringement of that

```

```

00043 parties intellectual property rights.
00044
00045 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00046 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00047 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00048 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00049 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00050 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00051 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00052 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00053 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00054 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00055 */
00056
00057 #include <cstdlib>
00058 #include <cstdio>
00059
00060 #include <iostream>
00061 #include <iomanip>
00062
00063 #include "mtk_roots.h"
00064 #include "mtk_div_1d.h"
00065 #include "mtk_div_3d.h"
00066
00067 mtk::Div3D::Div3D():
00068     order_accuracy_(),
00069     mimetic_threshold_() {}
00070
00071 mtk::Div3D::Div3D(const Div3D &grad):
00072     order_accuracy_(grad.order_accuracy_),
00073     mimetic_threshold_(grad.mimetic_threshold_) {}
00074
00075 mtk::Div3D::~Div3D() {}
00076
00077 bool mtk::Div3D::ConstructDiv3D(const
    mtk::UniStgGrid3D &grid,
                                int order_accuracy,
                                mtk::Real mimetic_threshold) {
00078
00079
00080
00081     int num_cells_x = grid.num_cells_x();
00082     int num_cells_y = grid.num_cells_y();
00083     int num_cells_z = grid.num_cells_z();
00084
00085     int mx = num_cells_x + 1; // Dx vertical dimension.
00086     int nx = num_cells_x + 2; // Dx horizontal dimension.
00087     int my = num_cells_y + 1; // Dy vertical dimension.
00088     int ny = num_cells_y + 2; // Dy horizontal dimension.
00089     int mz = num_cells_z + 1; // Dz vertical dimension.
00090     int nz = num_cells_z + 2; // Dz horizontal dimension.
00091
00092     mtk::Div1D div;
00093
00094     bool info = div.ConstructDiv1D(order_accuracy, mimetic_threshold);
00095
00096     #ifdef MTK_PERFORM_PREVENTIONS
00097     if (!info) {
00098         std::cerr << "Mimetic div could not be built." << std::endl;
00099         return info;
00100     }
00101     #endif
00102
00103     auto west = grid.west_bndy();
00104     auto east = grid.east_bndy();
00105     auto south = grid.south_bndy();
00106     auto north = grid.east_bndy();
00107     auto bottom = grid.bottom_bndy();
00108     auto top = grid.top_bndy();
00109
00110     mtk::UniStgGrid1D grid_x(west, east, num_cells_x);
00111     mtk::UniStgGrid1D grid_y(south, north, num_cells_y);
00112     mtk::UniStgGrid1D grid_z(bottom, top, num_cells_z);
00113
00114     mtk::DenseMatrix Dx(div.ReturnAsDenseMatrix(grid_x));
00115     mtk::DenseMatrix Dy(div.ReturnAsDenseMatrix(grid_y));
00116     mtk::DenseMatrix Dz(div.ReturnAsDenseMatrix(grid_z));
00117
00118     bool padded{true};
00119     bool transpose{false};
00120
00121     mtk::DenseMatrix ix(num_cells_x, padded, transpose);
00122     mtk::DenseMatrix iy(num_cells_y, padded, transpose);

```

```

00123     mtk::DenseMatrix iz(num_cells_z, padded, transpose);
00124
00126
00127     mtk::DenseMatrix aux1(mtk::DenseMatrix::Kron(iz, iy));
00128     mtk::DenseMatrix dx(mtk::DenseMatrix::Kron(aux1, Dx));
00129
00131
00132     mtk::DenseMatrix aux2(mtk::DenseMatrix::Kron(iz, Dy));
00133     mtk::DenseMatrix dy(mtk::DenseMatrix::Kron(aux2, ix));
00134
00136
00137     mtk::DenseMatrix aux3(mtk::DenseMatrix::Kron(Dz, iy));
00138     mtk::DenseMatrix dz(mtk::DenseMatrix::Kron(aux3, ix));
00139
00140     #if MTK_VERBOSE_LEVEL > 2
00141     std::cout << "Dx: " << mx << " by " << nx << std::endl;
00142     std::cout << "Ix: " << num_cells_x << " by " << nx << std::endl;
00143     std::cout << "Dy: " << my << " by " << ny << std::endl;
00144     std::cout << "Iy: " << num_cells_y << " by " << ny << std::endl;
00145     std::cout << "Dz: " << mz << " by " << nz << std::endl;
00146     std::cout << "Iz: " << num_cells_z << " by " << nz << std::endl;
00147     #endif
00148
00150
00151     int total_rows{nx*ny*nz};
00152     int total_cols{mx*num_cells_y*num_cells_z +
00153                   num_cells_x*my*num_cells_z +
00154                   num_cells_x*num_cells_y*mz};
00155
00156     #if MTK_VERBOSE_LEVEL > 2
00157     std::cout << "Div 3D: " << total_rows << " by " << total_cols << std::endl;
00158     #endif
00159
00160     mtk::DenseMatrix d3d(total_rows, total_cols);
00161
00162     for (auto ii = 0; ii < total_rows; ++ii) {
00163
00164         for (auto jj = 0; jj < mx*num_cells_y*num_cells_z; ++jj) {
00165             d3d.SetValue(ii, jj, dx.GetValue(ii, jj));
00166         }
00167
00168         int offset = mx*num_cells_y*num_cells_z;
00169
00170         for(auto kk = 0; kk < num_cells_x*my*num_cells_z; ++kk) {
00171             d3d.SetValue(ii, kk + offset, dy.GetValue(ii, kk));
00172         }
00173
00174         offset += num_cells_x*my*num_cells_z;
00175
00176         for(auto ll = 0; ll < num_cells_x*num_cells_y*mz; ++ll) {
00177             d3d.SetValue(ii, ll + offset, dz.GetValue(ii, ll));
00178         }
00179     }
00180
00181     divergence_ = d3d;
00182
00183     return info;
00184 }
00185
00186 mtk::DenseMatrix mtk::Div3D::ReturnAsDenseMatrix() const {
00187
00188     return divergence_;
00189 }

```

17.83 src/mtk_glpk_adapter.cc File Reference


Adapter class for the GLPK API.

```

#include <cmath>
#include <cstring>
#include <iostream>
#include <iomanip>
#include <limits>
#include "mtk_roots.h"
#include "mtk_blas_adapter.h"
#include "mtk_glpk_adapter.h"

```

Include dependency graph for mtk_glpk_adapter.cc:



17.83.1 Detailed Description

This class contains a collection of static classes, that posses direct access to the underlying structure of the matrices, thus allowing programmers to exploit some of the numerical methods implemented in the GLPK.

The **GLPK (GNU Linear Programming Kit)** package is intended for solving large-scale linear programming (LP), mixed integer programming (MIP), and other related problems. It is a set of routines written in ANSI C and organized in the form of a callable library.

See also

<http://www.gnu.org/software/glpk/>

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_glpk_adapter.cc](#).

17.84 mtk_glpk_adapter.cc

```

00001
00019 /*
00020 Copyright (C) 2015, Computational Science Research Center, San Diego State
00021 University. All rights reserved.
00022
00023 Redistribution and use in source and binary forms, with or without modification,
00024 are permitted provided that the following conditions are met:
00025

```

```

00026 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00027 and a copy of the modified files should be reported once modifications are
00028 completed, unless these modifications are made through the project's GitHub
00029 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00030 should be developed and included in any deliverable.
00031
00032 2. Redistributions of source code must be done through direct
00033 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00034
00035 3. Redistributions in binary form must reproduce the above copyright notice,
00036 this list of conditions and the following disclaimer in the documentation and/or
00037 other materials provided with the distribution.
00038
00039 4. Usage of the binary form on proprietary applications shall require explicit
00040 prior written permission from the the copyright holders, and due credit should
00041 be given to the copyright holders.
00042
00043 5. Neither the name of the copyright holder nor the names of its contributors
00044 may be used to endorse or promote products derived from this software without
00045 specific prior written permission.
00046
00047 The copyright holders provide no reassurances that the source code provided does
00048 not infringe any patent, copyright, or any other intellectual property rights of
00049 third parties. The copyright holders disclaim any liability to any recipient for
00050 claims brought against recipient by any third party for infringement of that
00051 parties intellectual property rights.
00052
00053 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00054 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00055 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00056 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00057 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00058 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00059 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00060 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00061 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00062 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00063 */
00064
00065 #include <cmath>
00066 #include <cstring>
00067
00068 #include <iostream>
00069 #include <iomanip>
00070 #include <limits>
00071
00072 #include "mtk_roots.h"
00073 #include "mtk_blas_adapter.h"
00074 #include "mtk_glpk_adapter.h"
00075
00076 mtk::Real mtk::GLPKAdapter::SolveSimplexAndCompare(
    mtk::Real *A,
                                int nrows,
                                int ncols,
                                int kk,
                                mtk::Real *hh,
                                mtk::Real *qq,
                                int robjective,
                                mtk::Real mimetic_threshold,
                                int copy) {
00077
00078
00079
00080
00081
00082
00083
00084
00085
00086 #if MTK_DEBUG_LEVEL > 0
00087 char mps_file_name[18]; // File name for the MPS files.
00088 #endif
00089 char rname[5];          // Row name.
00090 char cname[5];          // Column name.
00091
00092 glp_prob *lp; // Linear programming problem.
00093
00094 int *ia; // Array for the problem.
00095 int *ja; // Array for the problem.
00096
00097 int problem_size; // Size of the problem.
00098 int lp_nrows;     // Number of rows.
00099 int lp_ncols;     // Number of columns.
00100 int matsize;      // Size of the matrix.
00101 int glp_index{1}; // Index of the objective function.
00102 int ii;           // Iterator.
00103 int jj;           // Iterator.
00104
00105 mtk::Real *ar; // Array for the problem.

```

```

00106 mtk::Real *objective; // Array containing the objective function.
00107 mtk::Real *rhs; // Array containing the rhs.
00108 mtk::Real *err; // Array of errors.
00109
00110 mtk::Real x1; // Norm-2 of the error.
00111
00112 #if MTK_DEBUG_LEVEL > 0
00113 mtk::Real obj_value; // Value of the objective function.
00114 #endif
00115
00116 lp_nrows = kk;
00117 lp_ncols = kk;
00118
00119 matsize = lp_nrows*lp_ncols;
00120
00122
00124 problem_size = lp_nrows*lp_ncols + 1;
00125
00126 try {
00127     ia = new int[problem_size];
00128 } catch (std::bad_alloc &memory_allocation_exception) {
00129     std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00130     std::endl;
00131     std::cerr << memory_allocation_exception.what() << std::endl;
00132 }
00133 memset(ia, 0, sizeof(ia[0])*problem_size);
00134
00135 try {
00136     ja = new int[problem_size];
00137 } catch (std::bad_alloc &memory_allocation_exception) {
00138     std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00139     std::endl;
00140     std::cerr << memory_allocation_exception.what() << std::endl;
00141 }
00142 memset(ja, 0, sizeof(ja[0])*problem_size);
00143
00144 try {
00145     ar = new mtk::Real[problem_size];
00146 } catch (std::bad_alloc &memory_allocation_exception) {
00147     std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00148     std::endl;
00149     std::cerr << memory_allocation_exception.what() << std::endl;
00150 }
00151 memset(ar, mtk::kZero, sizeof(ar[0])*problem_size);
00152
00153 try {
00154     objective = new mtk::Real[lp_ncols + 1];
00155 } catch (std::bad_alloc &memory_allocation_exception) {
00156     std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00157     std::endl;
00158     std::cerr << memory_allocation_exception.what() << std::endl;
00159 }
00160 memset(objective, mtk::kZero, sizeof(objective[0])*(lp_ncols + 1));
00161
00162 try {
00163     rhs = new mtk::Real[lp_nrows + 1];
00164 } catch (std::bad_alloc &memory_allocation_exception) {
00165     std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00166     std::endl;
00167     std::cerr << memory_allocation_exception.what() << std::endl;
00168 }
00169 memset(rhs, mtk::kZero, sizeof(rhs[0])*(lp_nrows + 1));
00170
00171 try {
00172     err = new mtk::Real[lp_nrows];
00173 } catch (std::bad_alloc &memory_allocation_exception) {
00174     std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00175     std::endl;
00176     std::cerr << memory_allocation_exception.what() << std::endl;
00177 }
00178 memset(err, mtk::kZero, sizeof(err[0])*(lp_nrows));
00179
00180 #if MTK_DEBUG_LEVEL > 0
00181 std::cout << "Problem size: " << problem_size << std::endl;
00182 std::cout << "lp_nrows = " << lp_nrows << std::endl;
00183 std::cout << "lp_ncols = " << lp_ncols << std::endl;
00184 std::cout << std::endl;
00185 #endif
00186
00187 lp = glp_create_prob();
00188

```

```

00189   glp_set_prob_name (lp, "mtk::GLPKAdapter::Simplex");
00190
00191   glp_set_obj_dir (lp, GLP_MIN);
00192
00193   glp_add_rows(lp, lp_nrows);
00194
00195   for (ii = 1; ii <= lp_nrows; ++ii) {
00196       sprintf(rname, "R%02d",ii);
00197       glp_set_row_name(lp, ii, rname);
00198   }
00199
00200   glp_add_cols(lp, lp_ncols);
00201
00202   for (ii = 1; ii <= lp_ncols; ++ii) {
00203       sprintf(cname, "Q%02d",ii);
00204       glp_set_col_name (lp, ii, cname);
00205   }
00206
00207   #if MTK_DEBUG_LEVEL>0
00208   std::cout << "Using row " << robjective + 1 << " as objective." << std::endl;
00209   #endif
00210   for (jj = 0; jj < kk; ++jj) {
00211       objective[glp_index] = A[jj + robjective * ncols];
00212       glp_index++;
00213   }
00214   #if MTK_DEBUG_LEVEL >0
00215   std::cout << std::endl;
00216   #endif
00217
00218   glp_index = 1;
00219   rhs[0] = mtk::kZero;
00220   for (ii = 0; ii <= lp_nrows; ++ii) {
00221       if (ii != robjective) {
00222           rhs[glp_index] = hh[ii];
00223           glp_set_row_bnds(lp, glp_index, GLP_UP, 0.0, rhs[glp_index]);
00224           glp_index++;
00225       }
00226   }
00227
00228   #if MTK_DEBUG_LEVEL > 0
00229   std::cout << "rhs =" << std::endl;
00230   for (auto ii = 0; ii < lp_nrows; ++ii) {
00231       std::cout << std::setw(15) << rhs[ii] << std::endl;
00232   }
00233   std::cout << std::endl;
00234   #endif
00235
00236   for (ii = 1; ii <= lp_ncols; ++ii) {
00237       glp_set_obj_coef (lp, ii, objective[ii]);
00238   }
00239
00240   for (ii = 1; ii <= lp_ncols; ++ii) {
00241       glp_set_col_bnds (lp, ii, GLP_LO, mimetic_threshold, 0.0);
00242   }
00243
00244   glp_index = 1;
00245   for (ii = 0; ii <= kk; ++ii) {
00246       for (jj = 0; jj < kk; ++jj) {
00247           if (ii != robjective) {
00248               ar[glp_index] = A[jj + ii * ncols];
00249               glp_index++;
00250           }
00251       }
00252   }
00253
00254   glp_index = 0;
00255   for (ii = 1; ii < problem_size; ++ii) {
00256       if (((ii - 1) % lp_ncols) == 0) {
00257           glp_index++;
00258       }
00259       ia[ii] = glp_index;
00260       ja[ii] = (ii - 1) % lp_ncols + 1;
00261   }
00262
00263
00264
00265
00266
00267
00268
00269
00270
00271
00272
00273
00274
00275

```

```

00276 glp_load_matrix (lp, matsize, ia, ja, ar);
00277
00278 #if MTK_DEBUG_LEVEL > 0
00279 sprintf(mps_file_name, "LP_MPS_row_%02d.mps", robjective);
00280 glp_write_mps(lp, GLP_MPS_FILE, nullptr, mps_file_name);
00281 #endif
00282
00283 glp_simplex (lp, nullptr);
00284
00285 // Check status of the solution.
00286
00287 if (glp_get_status(lp) == GLP_OPT) {
00288
00289     for(ii = 1; ii <= lp_ncols; ++ii) {
00290         err[ii - 1] = qq[ii - 1] - glp_get_col_prim(lp, ii);
00291     }
00292
00293     #if MTK_DEBUG_LEVEL > 0
00294     obj_value = glp_get_obj_val (lp);
00295     std::cout << std::setw(12) << "CBS" << std::endl;
00296     for (ii = 0; ii < lp_ncols; ++ii) {
00297         std::cout << "q_" << ii + 1 << " = " << std::setw(12) <<
00298             glp_get_col_prim(lp, ii + 1) << std::setw(12) << qq[ii] << std::endl;
00299     }
00300     std::cout << "Objective function value (row " << robjective + 1 << ") = " <<
00301         obj_value << std::endl;
00302     #endif
00303
00304     if (copy) {
00305         for(ii = 0; ii < lp_ncols; ++ii) {
00306             qq[ii] = glp_get_col_prim(lp, ii + 1);
00307         }
00308         // Preserve the bottom values of qq.
00309     }
00310
00311     x1 = mtk::BLASAdapter::RealNRM2(err, lp_ncols);
00312
00313 } else {
00314     x1 = std::numeric_limits<mtk::Real>::infinity();
00315 }
00316
00317 glp_delete_prob (lp);
00318 glp_free_env ();
00319
00320 delete [] ia;
00321 delete [] ja;
00322 delete [] ar;
00323 delete [] objective;
00324 delete [] rhs;
00325 delete [] err;
00326
00327 return x1;
00328 }

```

17.85 src/mtk_grad_1d.cc File Reference


Implements the class Grad1D.

```

#include <cmath>
#include <cstring>
#include <iostream>
#include <iomanip>
#include <limits>
#include <algorithm>
#include "mtk_tools.h"
#include "mtk_blas_adapter.h"
#include "mtk_lapack_adapter.h"
#include "mtk_glpk_adapter.h"
#include "mtk_grad_1d.h"

```


Include dependency graph for mtk_grad_1d.cc:



Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

Functions

- `std::ostream & mtk::operator<< (std::ostream &stream, mtk::Grad1D &in)`

17.85.1 Detailed Description

This class implements a 1D gradient matrix operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Todo Overload ostream operator as in [mtk::Lap1D](#).

Todo Implement creation of `■` w. [mtk::BLASAdapter](#).

Definition in file [mtk_grad_1d.cc](#).

17.86 mtk_grad_1d.cc

```
00001
00015 /*
00016 Copyright (C) 2015, Computational Science Research Center, San Diego State
00017 University. All rights reserved.
00018
00019 Redistribution and use in source and binary forms, with or without modification,
00020 are permitted provided that the following conditions are met:
00021
00022 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00023 and a copy of the modified files should be reported once modifications are
00024 completed, unless these modifications are made through the project's GitHub
00025 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00026 should be developed and included in any deliverable.
```

```

00027
00028 2. Redistributions of source code must be done through direct
00029 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00030
00031 3. Redistributions in binary form must reproduce the above copyright notice,
00032 this list of conditions and the following disclaimer in the documentation and/or
00033 other materials provided with the distribution.
00034
00035 4. Usage of the binary form on proprietary applications shall require explicit
00036 prior written permission from the the copyright holders, and due credit should
00037 be given to the copyright holders.
00038
00039 5. Neither the name of the copyright holder nor the names of its contributors
00040 may be used to endorse or promote products derived from this software without
00041 specific prior written permission.
00042
00043 The copyright holders provide no reassurances that the source code provided does
00044 not infringe any patent, copyright, or any other intellectual property rights of
00045 third parties. The copyright holders disclaim any liability to any recipient for
00046 claims brought against recipient by any third party for infringement of that
00047 parties intellectual property rights.
00048
00049 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00050 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00051 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00052 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00053 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00054 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00055 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00056 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00057 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00058 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00059 */
00060
00061 #include <cmath>
00062 #include <cstring>
00063
00064 #include <iostream>
00065 #include <iomanip>
00066 #include <limits>
00067 #include <algorithm>
00068
00069 #include "mtk_tools.h"
00070
00071 #include "mtk_blas_adapter.h"
00072 #include "mtk_lapack_adapter.h"
00073 #include "mtk_glpk_adapter.h"
00074
00075 #include "mtk_grad_ld.h"
00076
00077 namespace mtk {
00078
00079 std::ostream& operator <<(std::ostream &stream, mtk::GradLD &in) {
00080
00081
00082     stream << "gradient_[0] = " << std::setw(9) << in.gradient_[0] << std::endl;
00083
00084
00085     stream << "gradient_[1:" << in.order_accuracy_ << "] = ";
00086     for (auto ii = 1; ii <= in.order_accuracy_; ++ii) {
00087         stream << std::setw(9) << in.gradient_[ii] << " ";
00088     }
00089     stream << std::endl;
00090
00091     stream << "gradient_[\" << in.order_accuracy_ + 1 << ":" <<
00092         2*in.order_accuracy_ << "] = ";
00093     for (auto ii = in.order_accuracy_ + 1; ii <= 2*in.
00094         order_accuracy_; ++ii) {
00095         stream << std::setw(9) << in.gradient_[ii] << " ";
00096     }
00097     stream << std::endl;
00098
00099     int offset{2*in.order_accuracy_ + 1};
00100     int mm {};
00101
00102     stream << "gradient_[\" << offset + mm << ":" <<
00103         offset + mm + in.num_bndy_coeffs_ - 1 << "] = ";
00104
00105     if (in.order_accuracy_ > mtk::kDefaultOrderAccuracy) {

```

```

00111     for (auto ii = 0; ii < in.num_bndy_approxs_ ; ++ii) {
00112         for (auto jj = 0; jj < in.num_bndy_coeffs_ ; ++jj) {
00113             auto value = in.gradient_[offset + (mm)];
00114             stream << std::setw(9) << value << " ";
00115             mm++;
00116         }
00117     }
00118 } else {
00119     stream << std::setw(9) << in.gradient_[offset + 0] << ' ';
00120     stream << std::setw(9) << in.gradient_[offset + 1] << ' ';
00121     stream << std::setw(9) << in.gradient_[offset + 2] << ' ';
00122 }
00123 stream << std::endl;
00124
00125 return stream;
00126 }
00127 }
00128
00129 mtk::Grad1D::Grad1D():
00130     order_accuracy_(mtk::kDefaultOrderAccuracy),
00131     dim_null_(),
00132     num_bndy_approxs_(),
00133     num_bndy_coeffs_(),
00134     gradient_length_(),
00135     minrow_(),
00136     row_(),
00137     coeffs_interior_(),
00138     prem_apps_(),
00139     weights_crs_(),
00140     weights_cbs_(),
00141     mim_bndy_(),
00142     gradient_(),
00143     mimetic_threshold_(mtk::kDefaultMimeticThreshold) {}
00144
00145 mtk::Grad1D::Grad1D(const Grad1D &grad):
00146     order_accuracy_(grad.order_accuracy_),
00147     dim_null_(grad.dim_null_),
00148     num_bndy_approxs_(grad.num_bndy_approxs_),
00149     num_bndy_coeffs_(grad.num_bndy_coeffs_),
00150     gradient_length_(grad.gradient_length_),
00151     minrow_(grad.minrow_),
00152     row_(grad.row_),
00153     coeffs_interior_(grad.coeffs_interior_),
00154     prem_apps_(grad.prem_apps_),
00155     weights_crs_(grad.weights_crs_),
00156     weights_cbs_(grad.weights_cbs_),
00157     mim_bndy_(grad.mim_bndy_),
00158     gradient_(grad.gradient_),
00159     mimetic_threshold_(grad.mimetic_threshold_) {}
00160
00161 mtk::Grad1D::~Grad1D() {
00162
00163     delete[] coeffs_interior_;
00164     coeffs_interior_ = nullptr;
00165
00166     delete[] prem_apps_;
00167     prem_apps_ = nullptr;
00168
00169     delete[] weights_crs_;
00170     weights_crs_ = nullptr;
00171
00172     delete[] weights_cbs_;
00173     weights_cbs_ = nullptr;
00174
00175     delete[] mim_bndy_;
00176     mim_bndy_ = nullptr;
00177
00178     delete[] gradient_;
00179     gradient_ = nullptr;
00180 }
00181
00182 bool mtk::Grad1D::ConstructGrad1D(int order_accuracy,
00183     Real mimetic_threshold) {
00184
00185     #ifdef MTK_PERFORM_PREVENTIONS
00186     mtk::Tools::Prevent(order_accuracy < 2, __FILE__, __LINE__, __func__);
00187     mtk::Tools::Prevent((order_accuracy%2) != 0, __FILE__, __LINE__, __func__);
00188     mtk::Tools::Prevent(mimetic_threshold <= mtk::kZero,
00189         __FILE__, __LINE__, __func__);
00189
00190     if (order_accuracy >= mtk::kCriticalOrderAccuracyGrad) {

```

```

00191     std::cout << "WARNING: Numerical accuracy is high." << std::endl;
00192 }
00193
00194 std::cout << "order_accuracy_ = " << order_accuracy << std::endl;
00195 std::cout << "mimetic_threshold_ = " << mimetic_threshold << std::endl;
00196 #endif
00197
00198 order_accuracy_ = order_accuracy;
00199 mimetic_threshold_ = mimetic_threshold;
00200
00201 bool abort_construction = ComputeStencilInteriorGrid();
00202
00203 #ifdef MTK_PERFORM_PREVENTIONS
00204 if (!abort_construction) {
00205     std::cerr << "Could NOT complete stage 1." << std::endl;
00206     std::cerr << "Exiting..." << std::endl;
00207     return false;
00208 }
00209 #endif
00210
00211 // At this point, we already have the values for the interior stencil stored
00212 // in the coeffs_interior_ array.
00213
00214 dim_null_ = order_accuracy/2 - 1;
00215 num_bndy_approxs_ = dim_null_ + 1;
00216
00217 #ifdef MTK_PRECISION_DOUBLE
00218 num_bndy_coeffs_ = (int) (3.0*((mtk::Real) order_accuracy)/2.0);
00219 #else
00220 num_bndy_coeffs_ = (int) (3.0f*((mtk::Real) order_accuracy)/2.0f);
00221 #endif
00222
00223 // For this we will follow recommendations given in:
00224 //
00225 // http://icl.cs.utk.edu/lapack-forum/viewtopic.php?f=5&t=4506
00226 //
00227 // We will compute the QR Factorization of the transpose, as in the
00228 // following (MATLAB) pseudo-code:
00229 //
00230 // [Q,R] = qr(V'); % Full QR as defined in
00231 // % http://www.stanford.edu/class/ee263/notes/qr_matlab.pdf
00232 //
00233 // null-space = Q(:, last (order_accuracy/2 - 1) columns of Q );
00234 //
00235 // However, given the nature of the Vandermonde matrices we've just
00236 // computed, they all possess the same null-space. Therefore, we impose the
00237 // convention of computing the null-space of the first Vandermonde matrix
00238 // (west boundary).
00239 //
00240 // In the case of the gradient, the first Vandermonde system has a unique
00241 // solution for the case of second-order-accuracy. Ergo, the Vandermonde
00242 // matrix used to assemble said system, will have an empty null-space.
00243 //
00244 // Therefore, we only compute a rational basis for the case of order higher
00245 // than second.
00246
00247 if (dim_null_ > 0) {
00248     abort_construction = ComputeRationalBasisNullSpace();
00249
00250     #ifdef MTK_PERFORM_PREVENTIONS
00251     if (!abort_construction) {
00252         std::cerr << "Could NOT complete stage 2.1." << std::endl;
00253         std::cerr << "Exiting..." << std::endl;
00254         return false;
00255     }
00256     #endif
00257 }
00258
00259 abort_construction = ComputePreliminaryApproximations();
00260
00261 #ifdef MTK_PERFORM_PREVENTIONS
00262 if (!abort_construction) {
00263     std::cerr << "Could NOT complete stage 2.2." << std::endl;
00264     std::cerr << "Exiting..." << std::endl;
00265     return false;
00266 }
00267 #endif
00268
00269 #endif
00270
00271
00272
00273
00274

```

```

00276 abort_construction = ComputeWeights();
00277
00278 #ifdef MTK_PERFORM_PREVENTIONS
00279 if (!abort_construction) {
00280     std::cerr << "Could NOT complete stage 2.3." << std::endl;
00281     std::cerr << "Exiting..." << std::endl;
00282     return false;
00283 }
00284 #endif
00285
00286 if (dim_null_ > 0) {
00287
00288     abort_construction = ComputeStencilBoundaryGrid();
00289
00290     #ifdef MTK_PERFORM_PREVENTIONS
00291     if (!abort_construction) {
00292         std::cerr << "Could NOT complete stage 2.4." << std::endl;
00293         std::cerr << "Exiting..." << std::endl;
00294         return false;
00295     }
00296     #endif
00297 }
00298
00299
00300 // Once we have the following three collections of data:
00301 // (a) the coefficients for the interior,
00302 // (b) the coefficients for the boundary (if it applies),
00303 // (c) and the weights (if it applies),
00304 // we will store everything in the output array:
00305
00306 abort_construction = AssembleOperator();
00307
00308 #ifdef MTK_PERFORM_PREVENTIONS
00309 if (!abort_construction) {
00310     std::cerr << "Could NOT complete stage 3." << std::endl;
00311     std::cerr << "Exiting..." << std::endl;
00312     return false;
00313 }
00314 #endif
00315
00316 return true;
00317 }
00318
00319 int mtk::Grad1D::num_bndy_coeffs() const {
00320     return num_bndy_coeffs_;
00321 }
00322
00323 mtk::Real *mtk::Grad1D::coeffs_interior() const {
00324     return coeffs_interior_;
00325 }
00326
00327 mtk::Real *mtk::Grad1D::weights_crs() const {
00328     return weights_crs_;
00329 }
00330
00331 mtk::Real *mtk::Grad1D::weights_cbs() const {
00332     return weights_cbs_;
00333 }
00334
00335 mtk::DenseMatrix mtk::Grad1D::mim_bndy() const {
00336     mtk::DenseMatrix xx(dim_null_ + 1, 3*order_accuracy_/2);
00337
00338     auto counter = 0;
00339     for (auto ii = 0; ii < dim_null_ + 1; ++ii) {
00340         for (auto jj = 0; jj < 3*order_accuracy_/2; ++jj) {
00341             xx.SetValue(ii, jj, gradient_[2*order_accuracy_ + 1 + counter]);
00342             counter++;
00343         }
00344     }
00345
00346     return xx;
00347 }
00348
00349 mtk::DenseMatrix mtk::Grad1D::ReturnAsDenseMatrix(
00350     mtk::Real west,
00351     mtk::Real east,

```

```

00358                                     int num_cells_x) const {
00359
00360     int nn{num_cells_x}; // Number of cells on the grid.
00361
00362     #ifdef MTK_PERFORM_PREVENTIONS
00363         mtk::Tools::Prevent(east < west, __FILE__, __LINE__, __func__);
00364         mtk::Tools::Prevent(nn < 3*order_accuracy_ - 2, __FILE__, __LINE__, __func__);
00365         mtk::Tools::Prevent(nn <= 0, __FILE__, __LINE__, __func__);
00366     #endif
00367
00368     mtk::Real delta_x = (east - west)/((mtk::Real) num_cells_x);
00369
00370     mtk::Real inv_delta_x{mtk::kOne/delta_x};
00371
00372     int gg_num_rows = nn + 1;
00373     int gg_num_cols = nn + 2;
00374     int elements_per_row = num_bndy_coeffs_;
00375     int num_extra_rows = order_accuracy_/2;
00376
00377     // Output matrix featuring sizes for gradient operators.
00378     mtk::DenseMatrix out(gg_num_rows, gg_num_cols);
00379
00380     auto ee_index = 0;
00381     for (auto ii = 0; ii < num_extra_rows; ii++) {
00382         auto cc = 0;
00383         for(auto jj = 0 ; jj < gg_num_cols; jj++) {
00384             if(cc >= elements_per_row) {
00385                 out.SetValue(ii, jj, mtk::kZero);
00386             } else {
00387                 out.SetValue(ii, jj,
00388                             gradient_[2*order_accuracy_ + 1 + ee_index++]*inv_delta_x);
00389                 cc++;
00390             }
00391         }
00392     }
00393 }
00394
00395
00396
00397
00398     for (auto ii = num_extra_rows; ii < gg_num_rows - num_extra_rows; ii++) {
00399         auto jj = ii - num_extra_rows + 1;
00400         for (auto cc = 0; cc < order_accuracy_; cc++, jj++) {
00401             out.SetValue(ii, jj, coeffs_interior_[cc]*inv_delta_x);
00402         }
00403     }
00404
00405
00406
00407     ee_index = 0;
00408     for (auto ii = gg_num_rows - 1; ii >= gg_num_rows - num_extra_rows; ii--) {
00409         auto cc = 0;
00410         for (auto jj = gg_num_cols - 1; jj >= 0; jj--) {
00411             if(cc >= elements_per_row) {
00412                 out.SetValue(ii, jj, mtk::kZero);
00413             } else {
00414                 out.SetValue(ii, jj,
00415                             -gradient_[2*order_accuracy_ + 1 +
00416 ee_index++]*inv_delta_x);
00417                 cc++;
00418             }
00419         }
00420     }
00421
00422     return out;
00423 }
00424
00425 mtk::DenseMatrix mtk::Grad1D::ReturnAsDenseMatrix(
00426     const UniStgGrid1D &grid) const {
00427
00428     int nn{grid.num_cells_x()}; // Number of cells on the grid.
00429
00430     #ifdef MTK_PERFORM_PREVENTIONS
00431         mtk::Tools::Prevent(nn <= 0, __FILE__, __LINE__, __func__);
00432         mtk::Tools::Prevent(nn < 3*order_accuracy_ - 2, __FILE__, __LINE__, __func__);
00433     #endif
00434
00435     mtk::Real inv_delta_x{mtk::kOne/grid.delta_x()};
00436
00437     int gg_num_rows = nn + 1;
00438     int gg_num_cols = nn + 2;
00439     int elements_per_row = num_bndy_coeffs_;
00440     int num_extra_rows = order_accuracy_/2;
00441

```

```

00442 // Output matrix featuring sizes for gradient operators.
00443 mtk::DenseMatrix out(gg_num_rows, gg_num_cols);
00444
00445
00446
00447 auto ee_index = 0;
00448 for (auto ii = 0; ii < num_extra_rows; ii++) {
00449     auto cc = 0;
00450     for(auto jj = 0 ; jj < gg_num_cols; jj++) {
00451         if(cc >= elements_per_row) {
00452             out.SetValue(ii, jj, mtk::kZero);
00453         } else {
00454             out.SetValue(ii, jj,
00455                 gradient_[2*order_accuracy_ + 1 + ee_index++]*inv_delta_x);
00456             cc++;
00457         }
00458     }
00459 }
00460
00461
00462
00463 for (auto ii = num_extra_rows; ii < gg_num_rows - num_extra_rows; ii++) {
00464     auto jj = ii - num_extra_rows + 1;
00465     for (auto cc = 0; cc < order_accuracy_; cc++, jj++) {
00466         out.SetValue(ii, jj, coeffs_interior_[cc]*inv_delta_x);
00467     }
00468 }
00469
00470
00471
00472 ee_index = 0;
00473 for (auto ii = gg_num_rows - 1; ii >= gg_num_rows - num_extra_rows; ii--) {
00474     auto cc = 0;
00475     for (auto jj = gg_num_cols - 1; jj >= 0; jj--) {
00476         if(cc >= elements_per_row) {
00477             out.SetValue(ii, jj, mtk::kZero);
00478         } else {
00479             out.SetValue(ii, jj,
00480                 -gradient_[2*order_accuracy_ + 1 + ee_index++]*inv_delta_x);
00481             cc++;
00482         }
00483     }
00484 }
00485
00486 return out;
00487 }
00488
00489 mtk::DenseMatrix mtk::Grad1D::ReturnAsDimensionlessDenseMatrix
00490 (
00491     int num_cells_x) const {
00492     int nn[num_cells_x]; // Number of cells on the grid.
00493
00494     #ifdef MTK_PERFORM_PREVENTIONS
00495     mtk::Tools::Prevent(nn <= 0, __FILE__, __LINE__, __func__);
00496     mtk::Tools::Prevent(nn < 3*order_accuracy_ - 2, __FILE__, __LINE__, __func__);
00497     #endif
00498
00499     int gg_num_rows = nn + 1;
00500     int gg_num_cols = nn + 2;
00501     int elements_per_row = num_bndy_coeffs_;
00502     int num_extra_rows = order_accuracy_/2;
00503
00504     // Output matrix featuring sizes for gradient operators.
00505     mtk::DenseMatrix out(gg_num_rows, gg_num_cols);
00506
00507
00508
00509     auto ee_index = 0;
00510     for (auto ii = 0; ii < num_extra_rows; ii++) {
00511         auto cc = 0;
00512         for(auto jj = 0 ; jj < gg_num_cols; jj++) {
00513             if(cc >= elements_per_row) {
00514                 out.SetValue(ii, jj, mtk::kZero);
00515             } else {
00516                 out.SetValue(ii, jj,
00517                     gradient_[2*order_accuracy_ + 1 + ee_index++]);
00518                 cc++;
00519             }
00520         }
00521     }
00522
00523
00524
00525     for (auto ii = num_extra_rows; ii < gg_num_rows - num_extra_rows; ii++) {
00526         auto jj = ii - num_extra_rows + 1;

```

```

00527     for (auto cc = 0; cc < order_accuracy_; cc++, jj++) {
00528         out.SetValue(ii, jj, coeffs_interior_[cc]);
00529     }
00530 }
00531
00532
00533
00534 ee_index = 0;
00535 for (auto ii = gg_num_rows - 1; ii >= gg_num_rows - num_extra_rows; ii--) {
00536     auto cc = 0;
00537     for (auto jj = gg_num_cols - 1; jj >= 0; jj--) {
00538         if(cc >= elements_per_row) {
00539             out.SetValue(ii, jj, mtk::kZero);
00540         } else {
00541             out.SetValue(ii, jj,
00542                 -gradient_[2*order_accuracy_ + 1 + ee_index++]);
00543             cc++;
00544         }
00545     }
00546 }
00547
00548 return out;
00549 }
00550
00551 bool mtk::Grad1D::ComputeStencilInteriorGrid() {
00552
00553
00554
00555     mtk::Real* pp{}; // Spatial coordinates to create interior stencil.
00556
00557     try {
00558         pp = new mtk::Real[order_accuracy_];
00559     } catch (std::bad_alloc &memory_allocation_exception) {
00560         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00561             std::endl;
00562         std::cerr << memory_allocation_exception.what() << std::endl;
00563     }
00564     memset(pp, mtk::kZero, sizeof(pp[0])*order_accuracy_);
00565
00566     #ifdef MTK_PRECISION_DOUBLE
00567     pp[0] = 1.0/2.0 - ((mtk::Real) order_accuracy_)/2.0;
00568     #else
00569     pp[0] = 1.0f/2.0f - ((mtk::Real) order_accuracy_)/2.0f;
00570     #endif
00571
00572     for (auto ii = 1; ii < order_accuracy_; ++ii) {
00573         pp[ii] = pp[ii - 1] + mtk::kOne;
00574     }
00575
00576     #if MTK_VERBOSE_LEVEL > 3
00577     std::cout << "pp =" << std::endl;
00578     for (auto ii = 0; ii < order_accuracy_; ++ii) {
00579         std::cout << std::setw(12) << pp[ii];
00580     }
00581     std::cout << std::endl << std::endl;
00582     #endif
00583
00584     bool transpose{false};
00585
00586     mtk::DenseMatrix vander_matrix(pp, order_accuracy_, order_accuracy_, transpose);
00587
00588
00589
00590     #if MTK_VERBOSE_LEVEL > 4
00591     std::cout << "vander_matrix =" << std::endl;
00592     std::cout << vander_matrix << std::endl << std::endl;
00593     #endif
00594
00595
00596
00597     try {
00598         coeffs_interior_ = new mtk::Real[order_accuracy_];
00599     } catch (std::bad_alloc &memory_allocation_exception) {
00600         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00601             std::endl;
00602         std::cerr << memory_allocation_exception.what() << std::endl;
00603     }
00604     memset(coeffs_interior_, mtk::kZero,
00605         sizeof(coeffs_interior_[0])*order_accuracy_);
00606
00607     coeffs_interior_[1] = mtk::kOne;
00608
00609     #if MTK_VERBOSE_LEVEL > 3
00610     std::cout << "oo =" << std::endl;
00611     for (auto ii = 0; ii < order_accuracy_; ++ii) {

```



```

00612     std::cout << std::setw(12) << coeffs_interior_[ii] << std::endl;
00613 }
00614 std::cout << std::endl;
00615 #endif
00616
00618
00619 int info{mtk::LAPACKAdapter::SolveDenseSystem(vander_matrix,
00620                                               coeffs_interior_)};
00621
00622 #ifdef MTK_PERFORM_PREVENTIONS
00623 if (!info) {
00624     std::cout << "System solved! Interior stencil attained!" << std::endl;
00625     std::cout << std::endl;
00626 }
00627 else {
00628     std::cerr << "Something wrong solving system! info = " << info << std::endl;
00629     std::cerr << "Exiting..." << std::endl;
00630     return false;
00631 }
00632 #endif
00633
00634 #if MTK_VERBOSE_LEVEL > 3
00635 std::cout << "coeffs_interior_ =" << std::endl;
00636 for (auto ii = 0; ii < order_accuracy_; ++ii) {
00637     std::cout << std::setw(12) << coeffs_interior_[ii];
00638 }
00639 std::cout << std::endl << std::endl;
00640 #endif
00641
00642 delete [] pp;
00643 pp = nullptr;
00644
00645 return true;
00646 }
00647
00648 bool mtk::Grad1D::ComputeRationalBasisNullSpace(void) {
00649
00651
00652     mtk::Real* gg{}; // Generator vector for the first Vandermonde matrix.
00653
00654     try {
00655         gg = new mtk::Real[num_bndy_coeffs_];
00656     } catch (std::bad_alloc &memory_allocation_exception) {
00657         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00658             std::endl;
00659         std::cerr << memory_allocation_exception.what() << std::endl;
00660     }
00661     memset(gg, mtk::kZero, sizeof(gg[0])*num_bndy_coeffs_);
00662
00663     #ifdef MTK_PRECISION_DOUBLE
00664     gg[1] = 1.0/2.0;
00665     #else
00666     gg[1] = 1.0f/2.0f;
00667     #endif
00668     for (auto ii = 2; ii < num_bndy_coeffs_; ++ii) {
00669         gg[ii] = gg[ii - 1] + mtk::kOne;
00670     }
00671
00672     #if MTK_VERBOSE_LEVEL > 3
00673     std::cout << "gg =" << std::endl;
00674     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
00675         std::cout << std::setw(12) << gg[ii];
00676     }
00677     std::cout << std::endl << std::endl;
00678     #endif
00679
00681
00682     bool tran{true}; // Should I transpose the Vandermonde matrix.
00683
00684     mtk::DenseMatrix aa_west_t(gg, num_bndy_coeffs_, order_accuracy_ + 1, tran);
00685
00686     #if MTK_VERBOSE_LEVEL > 4
00687     std::cout << "aa_west_t =" << std::endl;
00688     std::cout << aa_west_t << std::endl;
00689     #endif
00690
00692
00693     mtk::DenseMatrix qq_t(mtk::LAPACKAdapter::QRFactorDenseMatrix
00694         (aa_west_t));
00694
00695     #if MTK_VERBOSE_LEVEL > 3

```

```

00696     std::cout << "qq_t = " << std::endl;
00697     std::cout << qq_t << std::endl;
00698     #endif
00699
00700     int kk_num_rows{num_bndy_coeffs_};
00701     int kk_num_cols{dim_null_};
00702
00703     mtk::DenseMatrix kk(kk_num_rows, kk_num_cols);
00704
00705     // In the case of the gradient, even though we must solve for a null-space
00706     // of dimension 2, we must only extract ONE basis for the kernel.
00707     // We perform this extraction here:
00708
00709     int aux{kk_num_rows - kk_num_cols};
00710     for (auto ii = kk_num_rows - kk_num_cols; ii < kk_num_rows; ii++) {
00711         aux--;
00712         for (auto jj = 0; jj < kk_num_rows; jj++) {
00713             kk.data()[jj*kk_num_cols + (kk_num_rows - kk_num_cols - aux - 1)] =
00714                 qq_t.data()[ii*num_bndy_coeffs_ + jj];
00715         }
00716     }
00717
00718     #if MTK_VERBOSE_LEVEL > 2
00719     std::cout << "kk =" << std::endl;
00720     std::cout << kk << std::endl;
00721     std::cout << "kk.num_rows() = " << kk.num_rows() << std::endl;
00722     std::cout << "kk.num_cols() = " << kk.num_cols() << std::endl;
00723     std::cout << std::endl;
00724     #endif
00725
00726     // Scale thus requesting that the last entries of the attained basis for the
00727     // null-space, adopt the pattern we require.
00728     // Essentially we will implement the following MATLAB pseudo-code:
00729     // scalers = kk(num_bndy_approx - (dim_null - 1):num_bndy_approx,:)\B
00730     // SK = kk*scalers
00731     // where SK is the scaled null-space.
00732
00733     // In this point, we almost have all the data we need correctly allocated
00734     // in memory. We will create the matrix iden_, and elements we wish to scale
00735     // in the kk array. Using the concept of the leading dimension, we could just
00736     // use kk, with the correct leading dimension and that is it. BUT I DO NOT
00737     // GET how does it work. So I will just create a matrix with the content of
00738     // this array that we need, solve for the scalers and then scale the
00739     // whole kk:
00740
00741     // We will then create memory for that sub-matrix of kk (subk).
00742
00743     mtk::DenseMatrix subk(dim_null_, dim_null_);
00744
00745     auto zz = 0;
00746     for (auto ii = order_accuracy_ + 1; ii < num_bndy_coeffs_; ii++) {
00747         for (auto jj = 0; jj < dim_null_; jj++) {
00748             subk.data()[zz*(dim_null_) + jj] = kk.data()[ii*(dim_null_) + jj];
00749         }
00750         zz++;
00751     }
00752
00753     #if MTK_VERBOSE_LEVEL > 4
00754     std::cout << "subk =" << std::endl;
00755     std::cout << subk << std::endl;
00756     #endif
00757
00758     subk.Transpose();
00759
00760     #if MTK_VERBOSE_LEVEL > 4
00761     std::cout << "subk_t =" << std::endl;
00762     std::cout << subk << std::endl;
00763     #endif
00764
00765     bool padded{false};
00766     tran = false;
00767
00768     mtk::DenseMatrix iden(dim_null_, padded, tran);
00769
00770     #if MTK_VERBOSE_LEVEL > 4
00771     std::cout << "iden =" << std::endl;
00772     std::cout << iden << std::endl;
00773     #endif
00774
00775
00776

```

```

00779 // Solve the system to compute the scalars.
00780 // An example of the system to solve, for k = 8, is:
00781 //
00782 // subk*scalars = iden or
00783 //
00784 // | 0.386018 -0.0339244 -0.129478 | | 1 0 0 |
00785 // | -0.119774 0.0199423 0.0558632 |*scalars = | 0 1 0 |
00786 // | 0.0155708 -0.00349546 -0.00853182 | | 0 0 1 |
00787 //
00788 // Notice this is a nrhs = 3 system.
00789 // Noteworthy: we do NOT ACTUALLY ALLOCATE space for the scalars... they
00790 // will be stored in the created identity matrix.
00791 // Let us first transpose subk (because of LAPACK):
00792
00793 int info{mtk::LAPACKAdapter::SolveDenseSystem(subk, iden)};
00794
00795 #ifdef MTK_PERFORM_PREVENTIONS
00796 if (!info) {
00797     std::cout << "System successfully solved!" <<
00798         std::endl;
00799 } else {
00800     std::cerr << "Something went wrong solving system! info = " << info <<
00801         std::endl;
00802     std::cerr << "Exiting..." << std::endl;
00803     return false;
00804 }
00805 std::cout << std::endl;
00806 #endif
00807
00808 #if MTK_VERBOSE_LEVEL > 4
00809 std::cout << "Computed scalars:" << std::endl;
00810 std::cout << iden << std::endl;
00811 #endif
00812
00813 // Multiply the two matrices to attain a scaled basis for null-space.
00814
00815 rat_basis_null_space_ = mtk::BLASAdapter::RealDenseMM(kk, iden);
00816
00817 #if MTK_VERBOSE_LEVEL > 4
00818 std::cout << "Rational basis for the null-space:" << std::endl;
00819 std::cout << rat_basis_null_space_ << std::endl;
00820 #endif
00821
00822 // At this point, we have a rational basis for the null-space, with the
00823 // pattern we need! :)
00824
00825 delete [] gg;
00826 gg = nullptr;
00827
00828 return true;
00829 }
00830
00831 bool mtk::Grad1D::ComputePreliminaryApproximations() {
00832
00833     mtk::Real *gg{}; // Generator vector for the first approximation.
00834
00835     try {
00836         gg = new mtk::Real[num_bndy_coeffs_];
00837     } catch (std::bad_alloc &memory_allocation_exception) {
00838         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00839             std::endl;
00840         std::cerr << memory_allocation_exception.what() << std::endl;
00841     }
00842     memset(gg, mtk::kZero, sizeof(gg[0])*num_bndy_coeffs_);
00843
00844     #ifdef MTK_PRECISION_DOUBLE
00845     gg[1] = 1.0/2.0;
00846     #else
00847     gg[1] = 1.0f/2.0f;
00848     #endif
00849     for (auto ii = 2; ii < num_bndy_coeffs_; ++ii) {
00850         gg[ii] = gg[ii - 1] + mtk::kOne;
00851     }
00852
00853     #if MTK_VERBOSE_LEVEL > 3
00854     std::cout << "gg0 =" << std::endl;
00855     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
00856         std::cout << std::setw(12) << gg[ii];
00857     }
00858     std::cout << std::endl << std::endl;
00859
00860

```

```

00861 #endif
00862
00863 // Allocate 2D array to store the collection of preliminary approximations.
00864 try {
00865     prem_apps_ = new mtk::Real[num_bndy_coeffs_*num_bndy_approxs_];
00866 } catch (std::bad_alloc &memory_allocation_exception) {
00867     std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00868 std::endl;
00869     std::cerr << memory_allocation_exception.what() << std::endl;
00870 }
00871 memset(prem_apps_,
00872         mtk::kZero,
00873         sizeof(prem_apps_[0])*num_bndy_coeffs_*num_bndy_approxs_);
00874
00875 for (auto ll = 0; ll < num_bndy_approxs_; ++ll) {
00876
00877     // Re-check new generator vector for every iteration except for the first.
00878     #if MTK_VERBOSE_LEVEL > 3
00879     if (ll > 0) {
00880         std::cout << "gg_" << ll << " =" << std::endl;
00881         for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
00882             std::cout << std::setw(12) << gg[ii];
00883         }
00884         std::cout << std::endl << std::endl;
00885     }
00886     #endif
00887
00888     bool transpose{false};
00889
00890     mtk::DenseMatrix aa(gg,
00891                         num_bndy_coeffs_, order_accuracy_ + 1,
00892                         transpose);
00893
00894     #if MTK_VERBOSE_LEVEL > 4
00895     std::cout << "aa_" << ll << " =" << std::endl;
00896     std::cout << aa << std::endl;
00897     #endif
00898
00899     mtk::Real *ob{};
00900
00901     auto ob_ld = num_bndy_coeffs_;
00902
00903     try {
00904         ob = new mtk::Real[ob_ld];
00905     } catch (std::bad_alloc &memory_allocation_exception) {
00906         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00907         std::endl;
00908         std::cerr << memory_allocation_exception.what() << std::endl;
00909     }
00910     memset(ob, mtk::kZero, sizeof(ob[0])*ob_ld);
00911
00912     ob[1] = mtk::kOne;
00913
00914     #if MTK_VERBOSE_LEVEL > 3
00915     std::cout << "ob = " << std::endl << std::endl;
00916     for (auto ii = 0; ii < ob_ld; ++ii) {
00917         std::cout << std::setw(12) << ob[ii] << std::endl;
00918     }
00919     std::cout << std::endl;
00920     #endif
00921
00922     // However, this is an under-determined system of equations. So we can not
00923     // use the same LAPACK routine (dgesv_). We will instead use dgels_, through
00924     // our LAPACKAdapter class.
00925
00926     int info_{
00927         mtk::LAPACKAdapter::SolveRectangularDenseSystem(aa, ob
00928 , ob_ld)};
00929
00930     #ifdef MTK_PERFORM_PREVENTIONS
00931     if (!info_) {
00932         std::cout << "System successfully solved!" << std::endl << std::endl;
00933     } else {
00934         std::cerr << "Error solving system! info = " << info_ << std::endl;
00935         return false;
00936     }
00937     #endif
00938

```

```

00945
00946     #if MTK_VERBOSE_LEVEL > 3
00947     std::cout << "ob =" << std::endl;
00948     for (auto ii = 0; ii < ob_ld; ++ii) {
00949         std::cout << std::setw(12) << ob[ii] << std::endl;
00950     }
00951     std::cout << std::endl;
00952     #endif
00953
00954
00955     // This implies a DAXPY operation. However, we must construct the arguments
00956     // for this operation.
00957
00958     // Save them into the ob_bottom array:
00959
00960     Real *ob_bottom{}; // Bottom part of the attained kernel used to scale it.
00961
00962     try {
00963         ob_bottom = new mtk::Real[dim_null_];
00964     } catch (std::bad_alloc &memory_allocation_exception) {
00965         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00966             std::endl;
00967         std::cerr << memory_allocation_exception.what() << std::endl;
00968     }
00969     memset(ob_bottom, mtk::kZero, sizeof(ob_bottom[0])*dim_null_);
00970
00971     for (auto ii = 0; ii < dim_null_; ++ii) {
00972         ob_bottom[(dim_null_ - 1) - ii] = ob[num_bndy_coeffs_ - ii - 1];
00973     }
00974
00975     #if MTK_VERBOSE_LEVEL > 3
00976     std::cout << "ob_bottom =" << std::endl;
00977     for (auto ii = 0; ii < dim_null_; ++ii) {
00978         std::cout << std::setw(12) << ob_bottom[ii] << std::endl;
00979     }
00980     std::cout << std::endl;
00981     #endif
00982
00983     // We must computed an scaled ob, sob, using the scaled null-space in
00984     // rat_basis_null_space_.
00985     // Such operation is: sob = ob - rat_basis_null_space_*ob_bottom
00986     // or:
00987     // thus:
00988     //          Y =      a*A      *x      +      b*Y (DAXPY).
00989
00990     #if MTK_VERBOSE_LEVEL > 4
00991     std::cout << "Rational basis for the null-space:" << std::endl;
00992     std::cout << rat_basis_null_space_ << std::endl;
00993     #endif
00994
00995     mtk::Real alpha{-mtk::kOne};
00996     mtk::Real beta{mtk::kOne};
00997
00998     mtk::BLASAdapter::RealDenseMV(alpha, rat_basis_null_space_,
00999                                     ob_bottom, beta, ob);
01000
01001     #if MTK_VERBOSE_LEVEL > 3
01002     std::cout << "scaled ob:" << std::endl;
01003     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
01004         std::cout << std::setw(12) << ob[ii] << std::endl;
01005     }
01006     std::cout << std::endl;
01007     #endif
01008
01009     // We save the recently scaled solution, into an array containing these.
01010     // We can NOT start building the pi matrix, simply because I want that part
01011     // to be separated since its construction depends on the algorithm we want
01012     // to implement.
01013
01014     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
01015         prem_apps_[ii*num_bndy_approxs_ + 11] = ob[ii];
01016     }
01017
01018     // After the first iteration, simply shift the entries of the last
01019     // generator vector used:
01020     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
01021         gg[ii]--;
01022     }
01023
01024     // Garbage collection for this loop:
01025     delete[] ob;

```

```

01029     ob = nullptr;
01030
01031     delete[] ob_bottom;
01032     ob_bottom = nullptr;
01033 } // End of: for (ll = 0; ll < dim_null; ll++);
01034
01035 #if MTK_VERBOSE_LEVEL > 4
01036 std::cout << "Matrix post-scaled preliminary apps: " << std::endl;
01037 for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
01038     for (auto jj = 0; jj < num_bndy_approxs_; ++jj) {
01039         std::cout << std::setw(12) << prem_apps_[ii*num_bndy_approxs_ + jj];
01040     }
01041     std::cout << std::endl;
01042 }
01043 std::cout << std::endl;
01044 #endif
01045
01046 delete[] gg;
01047 gg = nullptr;
01048
01049 return true;
01050 }
01051
01052 bool mtk::Grad1D::ComputeWeights() {
01053
01054     // Matrix to compute the weights as in the CRSA.
01055     mtk::DenseMatrix pi(num_bndy_coeffs_, num_bndy_coeffs_ - 1);
01056
01057     // Assemble the pi matrix using:
01058     // 1. The collection of scaled preliminary approximations.
01059     // 2. The collection of coefficients approximating at the interior.
01060     // 3. The scaled basis for the null-space.
01061
01062     // 1.1. Process array of scaled preliminary approximations.
01063
01064     // These are queued in scaled_solutions. Each one of these, will be a column
01065     // of the pi matrix:
01066     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
01067         for (auto jj = 0; jj < num_bndy_approxs_; ++jj) {
01068             pi.data()[ii*(2*(num_bndy_approxs_ - 1) + (order_accuracy_/2 + 1)) + jj] =
01069                 prem_apps_[ii*num_bndy_approxs_ + jj];
01070         }
01071     }
01072
01073     // 1.2. Add columns from known stencil approximating at the interior.
01074
01075     // However, these must be padded by zeros, according to their position in the
01076     // final pi matrix:
01077     auto mm = 1;
01078     for (auto jj = num_bndy_approxs_; jj < order_accuracy_; ++jj) {
01079         for (auto ii = 0; ii < order_accuracy_; ++ii) {
01080             auto de = (ii + mm)*(2*(num_bndy_approxs_ - 1) +
01081                 (order_accuracy_/2 + 1)) + jj;
01082             pi.data()[de] = coeffs_interior_[ii];
01083         }
01084         ++mm;
01085     }
01086
01087     rat_basis_null_space_.OrderColMajor();
01088
01089     #if MTK_VERBOSE_LEVEL > 4
01090     std::cout << "Rational basis for the null-space (col. major):" << std::endl;
01091     std::cout << rat_basis_null_space_ << std::endl;
01092     #endif
01093
01094     // 1.3. Add final set of columns: rational basis for null-space.
01095
01096     for (auto jj = dim_null_ + (order_accuracy_/2 + 1);
01097         jj < num_bndy_coeffs_ - 1; ++jj) {
01098         for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
01099             auto og =
01100                 (jj - (dim_null_ + (order_accuracy_/2 + 1)))*num_bndy_coeffs_ + ii;
01101             auto de = ii*(2*dim_null_ + (order_accuracy_/2 + 1)) + jj;
01102             pi.data()[de] = rat_basis_null_space_.data()[og];
01103         }
01104     }
01105
01106     #if MTK_VERBOSE_LEVEL > 4
01107     std::cout << "coeffs_interior_ =" << std::endl;
01108     for (auto ii = 0; ii < order_accuracy_; ++ii) {

```

```

01111     std::cout << std::setw(12) << coeffs_interior_ii];
01112 }
01113 std::cout << std::endl << std::endl;
01114 #endif
01115
01116 #if MTK_VERBOSE_LEVEL > 4
01117 std::cout << "Constructed pi matrix for CRS Algorithm: " << std::endl;
01118 std::cout << pi << std::endl;
01119 #endif
01120
01121 // This imposes the mimetic condition.
01122
01123 mtk::Real *hh{}; // Right-hand side to compute weights in the C{R,B}SA.
01124
01125 try {
01126     hh = new mtk::Real[num_bndy_coeffs_];
01127 } catch (std::bad_alloc &memory_allocation_exception) {
01128     std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
01129     std::endl;
01130     std::cerr << memory_allocation_exception.what() << std::endl;
01131 }
01132 memset(hh, mtk::kZero, sizeof(hh[0])*num_bndy_coeffs_);
01133
01134 hh[0] = -mtk::kOne;
01135 for (auto ii = (order_accuracy_/2 + 2 - 1); ii < num_bndy_coeffs_; ++ii) {
01136     auto aux_xx = mtk::kZero;
01137     for (auto jj = 0; jj < ((ii - (order_accuracy_/2 - 1)) - 1); ++jj) {
01138         aux_xx += coeffs_interior_[jj];
01139     }
01140     hh[ii] = -mtk::kOne*aux_xx;
01141 }
01142
01143 // That is, we construct a system, to solve for the weights.
01144
01145 // Once again we face the challenge of solving with LAPACK. However, for the
01146 // CRSA, this matrix PI is over-determined, since it has more rows than
01147 // unknowns. However, according to the theory, the solution to this system is
01148 // unique. We will use dgels_.
01149
01150 try {
01151     weights_cbs_ = new mtk::Real[num_bndy_coeffs_];
01152 } catch (std::bad_alloc &memory_allocation_exception) {
01153     std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
01154     std::endl;
01155     std::cerr << memory_allocation_exception.what() << std::endl;
01156 }
01157 memset(weights_cbs_, mtk::kZero, sizeof(weights_cbs_[0])*num_bndy_coeffs_);
01158
01159 int weights_ld{pi.num_cols() + 1};
01160
01161 // Preserve hh.
01162 std::copy(hh, hh + weights_ld, weights_cbs_);
01163
01164 pi.Transpose();
01165
01166 int info{
01167     mtk::LAPACKAdapter::SolveRectangularDenseSystem(pi,
01168     weights_cbs_, weights_ld)
01169 };
01170
01171 #ifdef MTK_PERFORM_PREVENTIONS
01172 if (!info) {
01173     std::cout << "System successfully solved!" << std::endl << std::endl;
01174 } else {
01175     std::cerr << "Error solving system! info = " << info << std::endl;
01176     return false;
01177 }
01178 #endif
01179
01180 #if MTK_VERBOSE_LEVEL > 3
01181 std::cout << "hh =" << std::endl;
01182 for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
01183     std::cout << std::setw(11) << hh[ii] << std::endl;
01184 }
01185 std::cout << std::endl;
01186 #endif
01187
01188 // Preserve the original weights for research.
01189
01190

```

```

01194     try {
01195         weights_crs_ = new mtk::Real[num_bndy_coeffs_];
01196     } catch (std::bad_alloc &memory_allocation_exception) {
01197         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
01198             std::endl;
01199         std::cerr << memory_allocation_exception.what() << std::endl;
01200     }
01201     memset(weights_crs_, mtk::kZero, sizeof(weights_crs_[0])*num_bndy_coeffs_);
01202
01203     std::copy(weights_cbs_, weights_cbs_ + (weights_ld - 1), weights_crs_);
01204
01205     #if MTK_VERBOSE_LEVEL > 3
01206     std::cout << "weights_CRSA + lambda =" << std::endl;
01207     for (auto ii = 0; ii < weights_ld - 1; ++ii) {
01208         std::cout << std::setw(12) << weights_crs_[ii] << std::endl;
01209     }
01210     std::cout << std::endl;
01211     #endif
01212
01213     if (order_accuracy_ >= mtk::kCriticalOrderAccuracyGrad) {
01214
01215         int minrow{std::numeric_limits<int>::infinity()};
01216
01217         mtk::Real norm{mtk::BLASAdapter::RealNRM2(weights_cbs_,
01218             order_accuracy_)};
01219         mtk::Real minnorm{std::numeric_limits<mtk::Real>::infinity()};
01220
01221
01222         mtk::DenseMatrix phi(order_accuracy_ + 1, order_accuracy_);
01223
01224         // 6.1. Insert preliminary approximations to first set of columns.
01225
01226         for (auto ii = 0; ii < order_accuracy_ + 1; ++ii) {
01227             for (auto jj = 0; jj < num_bndy_approx_ + 1; ++jj) {
01228                 phi.data()[ii*(order_accuracy_ + 1) + jj] =
01229                     prem_apps_[ii*num_bndy_approx_ + jj];
01230             }
01231         }
01232
01233         // 6.2. Skip a column and negate preliminary approximations.
01234
01235         for (auto jj = 0; jj < order_accuracy_ + 1; ++jj) {
01236             for (auto ii = 1; ii < num_bndy_approx_ + 1; ++ii) {
01237                 auto de = (ii + order_accuracy_ - num_bndy_approx_ + jj*order_accuracy_);
01238                 auto og = (num_bndy_approx_ - ii + (jj)*num_bndy_approx_);
01239                 phi.data()[de] = -pre_apps_[og];
01240             }
01241         }
01242
01243         // 6.3. Flip negative columns up-down.
01244
01245         for (auto ii = 0; ii < order_accuracy_/2; ++ii) {
01246             for (auto jj = num_bndy_approx_ + 1; jj < order_accuracy_; ++jj) {
01247                 auto aux = phi.data()[ii*order_accuracy_ + jj];
01248                 phi.data()[ii*order_accuracy_ + jj] =
01249                     phi.data()[ (order_accuracy_ - ii)*order_accuracy_ + jj];
01250                 phi.data()[ (order_accuracy_ - ii)*order_accuracy_ + jj] = aux;
01251             }
01252         }
01253
01254         // 6.4. Insert stencil.
01255
01256         auto mm = 0;
01257         for (auto jj = num_bndy_approx_ + 1; jj < num_bndy_approx_ + 1; ++jj) {
01258             for (auto ii = 0; ii < order_accuracy_ + 1; ++ii) {
01259                 if (ii == 0) {
01260                     phi.data()[jj] = 0.0;
01261                 } else {
01262                     phi.data()[ (ii + mm)*order_accuracy_ + jj] = coeffs_interior_[ii - 1];
01263                 }
01264             }
01265             mm++;
01266         }
01267
01268         #if MTK_VERBOSE_LEVEL > 4
01269         std::cout << "phi =" << std::endl;
01270         std::cout << phi << std::endl;
01271         #endif
01272     }
01273
01274     #endif
01275
01276

```



```

01277     mtk::Real *lamed{}; // Used to build big lambda.
01278
01279     try {
01280         lamed = new mtk::Real[num_bndy_approxs_ - 1];
01281     } catch (std::bad_alloc &memory_allocation_exception) {
01282         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
01283             std::endl;
01284         std::cerr << memory_allocation_exception.what() << std::endl;
01285     }
01286     memset(lamed, mtk::kZero, sizeof(lamed[0])*(num_bndy_approxs_ - 1));
01287
01288     for (auto ii = 0; ii < num_bndy_approxs_ - 1; ++ii) {
01289         lamed[ii] = hh[ii + order_accuracy_ + 1] ;
01290     }
01291
01292     #if MTK_VERBOSE_LEVEL > 3
01293     std::cout << "lamed =" << std::endl;
01294     for (auto ii = 0; ii < num_bndy_approxs_ - 1; ++ii) {
01295         std::cout << std::setw(12) << lamed[ii] << std::endl;
01296     }
01297     std::cout << std::endl;
01298     #endif
01299
01300     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
01301         mtk::Real temp = mtk::kZero;
01302         for (auto jj = 0; jj < num_bndy_approxs_ - 1; ++jj) {
01303             temp = temp +
01304                 lamed[jj]*rat_basis_null_space_.data()[jj*num_bndy_coeffs_ + ii];
01305         }
01306         hh[ii] = hh[ii] - temp;
01307     }
01308
01309     #if MTK_VERBOSE_LEVEL > 3
01310     std::cout << "big_lambda =" << std::endl;
01311     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
01312         std::cout << std::setw(12) << hh[ii] << std::endl;
01313     }
01314     std::cout << std::endl;
01315     #endif
01316
01317     int copy_result{}; // Should I replace the solution... not for now.
01318
01319     mtk::Real normerr_; // Norm of the error for the solution on each row.
01320
01321     for (auto row_ = 0; row_ < order_accuracy_ + 1; ++row_) {
01322         normerr_ = mtk::GLPKAdapter::SolveSimplexAndCompare(phi.
01323             data(),
01324                 order_accuracy_ + 1,
01325                 order_accuracy_,
01326                 order_accuracy_,
01327                 hh,
01328                 weights_cbs_,
01329                 row_,
01330                 mimetic_threshold_,
01331                 copy_result);
01332
01333         mtk::Real aux{normerr_/norm};
01334
01335         #if MTK_VERBOSE_LEVEL > 2
01336         std::cout << "Relative norm: " << aux << " " << std::endl;
01337         std::cout << std::endl;
01338         #endif
01339
01340         if (aux < minnorm) {
01341             minnorm = aux;
01342             minrow_ = row_;
01343         }
01344     }
01345
01346     #if MTK_VERBOSE_LEVEL > 3
01347     std::cout << "weights_CBSA + lambda (after brute force search):" <<
01348         std::endl;
01349     for (auto ii = 0; ii < num_bndy_coeffs_ - 1; ++ii) {
01350         std::cout << std::setw(12) << weights_cbs_[ii] << std::endl;
01351     }
01352     std::cout << std::endl;
01353     #endif
01354
01355     // After we know which row yields the smallest relative norm that row is
01356     // chosen to be the objective function and the result of the optimizer is

```

```

01359     // chosen to be the new weights_.
01360
01361     #if MTK_VERBOSE_LEVEL > 2
01362     std::cout << "Minimum Relative Norm " << minnorm << " found at row " <<
01363         minrow_ + 1 << std::endl;
01364     std::cout << std::endl;
01365     #endif
01366
01367     copy_result = 1;
01368     normerr_ = mtk::GLPKAdapter::SolveSimplexAndCompare(phi.
data(),
01369
01370         order_accuracy_ + 1,
01371         order_accuracy_,
01372         order_accuracy_,
01373         hh,
01374         weights_cbs_,
01375         minrow_,
01376         mimetic_threshold_,
01377         copy_result);
01378
01379     mtk::Real aux_{normerr_/norm};
01380     #if MTK_VERBOSE_LEVEL > 2
01381     std::cout << "Relative norm: " << aux_ << std::endl;
01382     std::cout << std::endl;
01383     #endif
01384     delete [] lamed;
01385     lamed = nullptr;
01386 }
01387
01388 delete [] hh;
01389 hh = nullptr;
01390
01391 return true;
01392 }
01393
01394 bool mtk::Grad1D::ComputeStencilBoundaryGrid(void) {
01395
01396     #if MTK_VERBOSE_LEVEL > 3
01397     std::cout << "weights_* + lambda =" << std::endl;
01398     for (auto ii = 0; ii < num_bndy_coeffs_ - 1; ++ii) {
01399         std::cout << std::setw(12) << weights_cbs_[ii] << std::endl;
01400     }
01401     std::cout << std::endl;
01402     #endif
01403
01404     mtk::Real *lambda{}; // Collection of bottom values from weights_.
01405
01406     try {
01407         lambda = new mtk::Real[dim_null_];
01408     } catch (std::bad_alloc &memory_allocation_exception) {
01409         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
01410             std::endl;
01411         std::cerr << memory_allocation_exception.what() << std::endl;
01412     }
01413     memset(lambda, mtk::kZero, sizeof(lambda[0])*dim_null_);
01414
01415     for (auto ii = 0; ii < dim_null_; ++ii) {
01416         lambda[ii] = weights_cbs_[order_accuracy_ + ii];
01417     }
01418
01419     #if MTK_VERBOSE_LEVEL > 3
01420     std::cout << "lambda =" << std::endl;
01421     for (auto ii = 0; ii < dim_null_; ++ii) {
01422         std::cout << std::setw(12) << lambda[ii] << std::endl;
01423     }
01424     std::cout << std::endl;
01425     #endif
01426
01427     mtk::Real *alpha{}; // Collection of alpha values.
01428
01429     try {
01430         alpha = new mtk::Real[dim_null_];
01431     } catch (std::bad_alloc &memory_allocation_exception) {
01432         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
01433             std::endl;
01434         std::cerr << memory_allocation_exception.what() << std::endl;
01435     }
01436     memset(alpha, mtk::kZero, sizeof(alpha[0])*dim_null_);
01437
01438
01439
01440

```

```

01441     for (auto ii = 0; ii < dim_null_; ++ii) {
01442         alpha[ii] = lambda[ii]/weights_cbs_[ii] ;
01443     }
01444
01445     #if MTK_VERBOSE_LEVEL > 3
01446     std::cout << "alpha =" << std::endl;
01447     for (auto ii = 0; ii < dim_null_; ++ii) {
01448         std::cout << std::setw(12) << alpha[ii] << std::endl;
01449     }
01450     std::cout << std::endl;
01451     #endif
01452
01453     try {
01454         mim_bndy_ = new mtk::Real[num_bndy_coeffs_*num_bndy_approxs_];
01455     } catch (std::bad_alloc &memory_allocation_exception) {
01456         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
01457             std::endl;
01458         std::cerr << memory_allocation_exception.what() << std::endl;
01459     }
01460     memset(mim_bndy_,
01461         mtk::kZero,
01462         sizeof(mim_bndy_[0])*num_bndy_coeffs_*num_bndy_approxs_);
01463
01464     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
01465         for (auto jj = 0; jj < (num_bndy_approxs_ - 1); ++jj) {
01466             mim_bndy_[ii*num_bndy_approxs_ + jj] =
01467                 prem_apps_[ii*num_bndy_approxs_ + jj] +
01468                 alpha[jj]*rat_basis_null_space_.data()[jj*num_bndy_coeffs_ + ii];
01469         }
01470     }
01471
01472     for(auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
01473         mim_bndy_[ii*num_bndy_approxs_ + (num_bndy_approxs_ - 1)] =
01474             prem_apps_[ii*num_bndy_approxs_ + (num_bndy_approxs_ - 1)];
01475     }
01476
01477     #if MTK_VERBOSE_LEVEL > 4
01478     std::cout << "Collection of mimetic approximations:" << std::endl;
01479     for (auto ii = 0; ii < num_bndy_coeffs_; ++ii) {
01480         for (auto jj = 0; jj < num_bndy_approxs_; ++jj) {
01481             std::cout << std::setw(13) << mim_bndy_[ii*num_bndy_approxs_ + jj];
01482         }
01483         std::cout << std::endl;
01484     }
01485     std::cout << std::endl;
01486     #endif
01487
01488     delete[] lambda;
01489     lambda = nullptr;
01490
01491     delete[] alpha;
01492     alpha = nullptr;
01493
01494     return true;
01495 }
01496
01497 bool mtk::Grad1D::AssembleOperator(void) {
01498
01499     // The output array will have this form:
01500     // 1. The first entry of the array will contain the used order kk.
01501     // 2. The second entry of the array will contain the collection of
01502     // approximating coefficients for the interior of the grid.
01503     // 3. The third entry will contain a collection of weights.
01504     // 4. The next dim_null - 1 entries will contain the collections of
01505     // approximating coefficients for the west boundary of the grid.
01506
01507     gradient_length_ = 1 + order_accuracy_ + order_accuracy_ +
01508         num_bndy_approxs_*num_bndy_coeffs_;
01509
01510     #if MTK_VERBOSE_LEVEL > 2
01511     std::cout << "gradient_length_ = " << gradient_length_ << std::endl;
01512     #endif
01513
01514     try {
01515         gradient_ = new mtk::Real[gradient_length_];
01516     } catch (std::bad_alloc &memory_allocation_exception) {
01517         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
01518             std::endl;
01519         std::cerr << memory_allocation_exception.what() << std::endl;
01520     }
01521 }

```

```

01523  memset(gradient_, mtk::kZero, sizeof(gradient_[0])*gradient_length_);
01524
01526
01527  gradient_[0] = order_accuracy_;
01528
01531
01532  for (auto ii = 0; ii < order_accuracy_; ++ii) {
01533      gradient_[ii + 1] = coeffs_interior_[ii];
01534  }
01535
01537
01538  for (auto ii = 0; ii < order_accuracy_; ++ii) {
01539      gradient_[(order_accuracy_ + 1) + ii] = weights_cbs_[ii];
01540  }
01541
01544
01545  int offset{2*order_accuracy_ + 1};
01546
01547  int aux {}; // Auxiliary variable.
01548
01549  if (order_accuracy_ > mtk::kDefaultOrderAccuracy) {
01550      for (auto ii = 0; ii < num_bndy_approxs_ ; ii++) {
01551          for (auto jj = 0; jj < num_bndy_coeffs_ ; jj++) {
01552              gradient_[offset + aux] = mim_bndy_[jj]*num_bndy_approxs_ + ii;
01553              aux++;
01554          }
01555      }
01556  } else {
01557      gradient_[offset + 0] = prem_apps_[0];
01558      gradient_[offset + 1] = prem_apps_[1];
01559      gradient_[offset + 2] = prem_apps_[2];
01560  }
01561
01562  #if MTK_VERBOSE_LEVEL > 1
01563  std::cout << "1D " << order_accuracy_ << "-order grad built!" << std::endl;
01564  std::cout << std::endl;
01565  #endif
01566
01567  return true;
01568 }

```

17.87 src/mtk_grad_2d.cc File Reference


Implements the class Grad2D.

```

#include <cstdlib>
#include <cstdio>
#include <iostream>
#include <iomanip>
#include "mtk_roots.h"
#include "mtk_grad_1d.h"
#include "mtk_grad_2d.h"

```

Include dependency graph for mtk_grad_2d.cc:



17.87.1 Detailed Description

This class implements a 2D gradient operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (C↔BSA).

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_grad_2d.cc](#).

17.88 mtk_grad_2d.cc

```

00001
00011 /*
00012 Copyright (C) 2015, Computational Science Research Center, San Diego State
00013 University. All rights reserved.
00014
00015 Redistribution and use in source and binary forms, with or without modification,
00016 are permitted provided that the following conditions are met:
00017
00018 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00019 and a copy of the modified files should be reported once modifications are
00020 completed, unless these modifications are made through the project's GitHub
00021 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00022 should be developed and included in any deliverable.
00023
00024 2. Redistributions of source code must be done through direct
00025 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00026
00027 3. Redistributions in binary form must reproduce the above copyright notice,
00028 this list of conditions and the following disclaimer in the documentation and/or
00029 other materials provided with the distribution.
00030
00031 4. Usage of the binary form on proprietary applications shall require explicit
00032 prior written permission from the the copyright holders, and due credit should
00033 be given to the copyright holders.
00034
00035 5. Neither the name of the copyright holder nor the names of its contributors
00036 may be used to endorse or promote products derived from this software without
00037 specific prior written permission.
00038
00039 The copyright holders provide no reassurances that the source code provided does
00040 not infringe any patent, copyright, or any other intellectual property rights of
00041 third parties. The copyright holders disclaim any liability to any recipient for
00042 claims brought against recipient by any third party for infringement of that

```

```

00043 parties intellectual property rights.
00044
00045 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00046 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00047 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00048 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00049 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00050 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00051 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00052 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00053 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00054 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00055 */
00056
00057 #include <cstdlib>
00058 #include <cstdio>
00059
00060 #include <iostream>
00061 #include <iomanip>
00062
00063 #include "mtk_roots.h"
00064 #include "mtk_grad_1d.h"
00065 #include "mtk_grad_2d.h"
00066
00067 mtk::Grad2D::Grad2D():
00068     order_accuracy_(),
00069     mimetic_threshold_() {}
00070
00071 mtk::Grad2D::Grad2D(const Grad2D &grad):
00072     order_accuracy_(grad.order_accuracy_),
00073     mimetic_threshold_(grad.mimetic_threshold_) {}
00074
00075 mtk::Grad2D::~Grad2D() {}
00076
00077 bool mtk::Grad2D::ConstructGrad2D(const
    mtk::UniStgGrid2D &grid,
                                int order_accuracy,
                                mtk::Real mimetic_threshold) {
00078
00079
00080
00081     int num_cells_x = grid.num_cells_x();
00082     int num_cells_y = grid.num_cells_y();
00083
00084     int mx = num_cells_x + 1; // Gx vertical dimension
00085     int nx = num_cells_x + 2; // Gx horizontal dimension
00086     int my = num_cells_y + 1; // Gy vertical dimension
00087     int ny = num_cells_y + 2; // Gy horizontal dimension
00088
00089     mtk::Grad1D grad;
00090
00091     bool info = grad.ConstructGrad1D(order_accuracy, mimetic_threshold);
00092
00093     #ifdef MTK_PERFORM_PREVENTIONS
00094     if (!info) {
00095         std::cerr << "Mimetic grad could not be built." << std::endl;
00096         return info;
00097     }
00098     #endif
00099
00100     auto west = grid.west_bndy();
00101     auto east = grid.east_bndy();
00102     auto south = grid.south_bndy();
00103     auto north = grid.east_bndy();
00104
00105     mtk::UniStgGrid1D grid_x(west, east, num_cells_x);
00106     mtk::UniStgGrid1D grid_y(south, north, num_cells_y);
00107
00108     mtk::DenseMatrix Gx(grad.ReturnAsDenseMatrix(grid_x));
00109     mtk::DenseMatrix Gy(grad.ReturnAsDenseMatrix(grid_y));
00110
00111     bool padded{true};
00112     bool transpose{true};
00113
00114     mtk::DenseMatrix tix(num_cells_x, padded, transpose);
00115     mtk::DenseMatrix tiy(num_cells_y, padded, transpose);
00116
00117     mtk::DenseMatrix gxy(mtk::DenseMatrix::Kron(tiy, Gx));
00118     mtk::DenseMatrix gyx(mtk::DenseMatrix::Kron(Gy, tix));
00119
00120     #if MTK_VERBOSE_LEVEL > 2
00121     std::cout << "Gx: " << mx << " by " << nx << std::endl;
00122     std::cout << "Transpose Iy: " << num_cells_y << " by " << ny << std::endl;

```

```

00123     std::cout << "Gy: " << my << " by " << ny << std::endl;
00124     std::cout << "Transpose Ix: " << num_cells_x << " by " << nx << std::endl;
00125     std::cout << "Grad 2D: " << mx*num_cells_y + my*num_cells_x << " by " <<
00126         nx*ny <<std::endl;
00127     #endif
00128
00129     mtk::DenseMatrix g2d(mx*num_cells_y + my*num_cells_x, nx*ny);
00130
00131     for(auto ii = 0; ii < nx*ny; ii++) {
00132         for(auto jj = 0; jj < mx*num_cells_y; jj++) {
00133             g2d.SetValue(jj,ii, gxy.GetValue(jj,ii));
00134         }
00135         for(auto kk = 0; kk < my*num_cells_x; kk++) {
00136             g2d.SetValue(kk + mx*num_cells_y, ii, gyx.GetValue(kk,ii));
00137         }
00138     }
00139
00140     gradient_ = g2d;
00141
00142     return info;
00143 }
00144
00145 mtk::DenseMatrix mtk::Grad2D::ReturnAsDenseMatrix() const {
00146
00147     return gradient_;
00148 }

```

17.89 src/mtk_grad_3d.cc File Reference


Implements the class Grad3D.

```

#include <cstdlib>
#include <stdio>
#include <iostream>
#include <iomanip>
#include "mtk_roots.h"
#include "mtk_grad_1d.h"
#include "mtk_grad_3d.h"

```

Include dependency graph for mtk_grad_3d.cc:



17.89.1 Detailed Description

This class implements a 3D gradient operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (C↔BSA).

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_grad_3d.cc](#).

17.90 mtk_grad_3d.cc

```

00001
00011 /*
00012 Copyright (C) 2015, Computational Science Research Center, San Diego State
00013 University. All rights reserved.
00014
00015 Redistribution and use in source and binary forms, with or without modification,
00016 are permitted provided that the following conditions are met:
00017
00018 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00019 and a copy of the modified files should be reported once modifications are
00020 completed, unless these modifications are made through the project's GitHub
00021 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00022 should be developed and included in any deliverable.
00023
00024 2. Redistributions of source code must be done through direct
00025 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00026
00027 3. Redistributions in binary form must reproduce the above copyright notice,
00028 this list of conditions and the following disclaimer in the documentation and/or
00029 other materials provided with the distribution.
00030
00031 4. Usage of the binary form on proprietary applications shall require explicit
00032 prior written permission from the the copyright holders, and due credit should
00033 be given to the copyright holders.
00034
00035 5. Neither the name of the copyright holder nor the names of its contributors
00036 may be used to endorse or promote products derived from this software without
00037 specific prior written permission.
00038
00039 The copyright holders provide no reassurances that the source code provided does
00040 not infringe any patent, copyright, or any other intellectual property rights of
00041 third parties. The copyright holders disclaim any liability to any recipient for
00042 claims brought against recipient by any third party for infringement of that
00043 parties intellectual property rights.
00044
00045 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00046 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00047 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00048 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00049 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00050 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00051 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00052 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00053 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00054 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00055 */
00056
00057 #include <cstdlib>
00058 #include <cstdio>
00059
00060 #include <iostream>
00061 #include <iomanip>
00062
00063 #include "mtk_roots.h"
00064 #include "mtk_grad_ld.h"
00065 #include "mtk_grad_3d.h"
00066
00067 mtk::Grad3D::Grad3D():
00068     order_accuracy_(),
00069     mimetic_threshold_() {}
00070
00071 mtk::Grad3D::Grad3D(const Grad3D &grad):
00072     order_accuracy_(grad.order_accuracy_),
00073     mimetic_threshold_(grad.mimetic_threshold_) {}
00074
00075 mtk::Grad3D::~~Grad3D() {}
00076
00077 bool mtk::Grad3D::ConstructGrad3D(const

```



```

mtk::UniStgGrid3D &grid,
00078                                     int order_accuracy,
00079                                     mtk::Real mimetic_threshold) {
00080
00081     int num_cells_x = grid.num_cells_x();
00082     int num_cells_y = grid.num_cells_y();
00083     int num_cells_z = grid.num_cells_z();
00084
00085     int mx = num_cells_x + 1; // Gx vertical dimension.
00086     int nx = num_cells_x + 2; // Gx horizontal dimension.
00087     int my = num_cells_y + 1; // Gy vertical dimension.
00088     int ny = num_cells_y + 2; // Gy horizontal dimension.
00089     int mz = num_cells_z + 1; // Gz vertical dimension.
00090     int nz = num_cells_z + 2; // Gz horizontal dimension.
00091
00092     mtk::Grad1D grad;
00093
00094     bool info = grad.ConstructGrad1D(order_accuracy, mimetic_threshold);
00095
00096     #ifdef MTK_PERFORM_PREVENTIONS
00097     if (!info) {
00098         std::cerr << "Mimetic grad could not be built." << std::endl;
00099         return info;
00100     }
00101     #endif
00102
00103     auto west = grid.west_bndy();
00104     auto east = grid.east_bndy();
00105     auto south = grid.south_bndy();
00106     auto north = grid.north_bndy();
00107     auto bottom = grid.bottom_bndy();
00108     auto top = grid.top_bndy();
00109
00110     mtk::UniStgGrid1D grid_x(west, east, num_cells_x);
00111     mtk::UniStgGrid1D grid_y(south, north, num_cells_y);
00112     mtk::UniStgGrid1D grid_z(bottom, top, num_cells_z);
00113
00114     mtk::DenseMatrix Gx(grad.ReturnAsDenseMatrix(grid_x));
00115     mtk::DenseMatrix Gy(grad.ReturnAsDenseMatrix(grid_y));
00116     mtk::DenseMatrix Gz(grad.ReturnAsDenseMatrix(grid_z));
00117
00118     bool padded{true};
00119     bool transpose{true};
00120
00121     mtk::DenseMatrix tix(num_cells_x, padded, transpose);
00122     mtk::DenseMatrix tiy(num_cells_y, padded, transpose);
00123     mtk::DenseMatrix tiz(num_cells_z, padded, transpose);
00124
00125
00126     mtk::DenseMatrix aux1(mtk::DenseMatrix::Kron(tiz, tiy));
00127     mtk::DenseMatrix gx(mtk::DenseMatrix::Kron(aux1, Gx));
00128
00129
00130     mtk::DenseMatrix aux2(mtk::DenseMatrix::Kron(tiz, Gy));
00131     mtk::DenseMatrix gy(mtk::DenseMatrix::Kron(aux2, tix));
00132
00133
00134     mtk::DenseMatrix aux3(mtk::DenseMatrix::Kron(Gz, tiy));
00135     mtk::DenseMatrix gz(mtk::DenseMatrix::Kron(aux3, tix));
00136
00137
00138     #if MTK_VERBOSE_LEVEL > 2
00139     std::cout << "Gx: " << mx << " by " << nx << std::endl;
00140     std::cout << "Transpose Ix: " << num_cells_x << " by " << nx << std::endl;
00141     std::cout << "Gy: " << my << " by " << ny << std::endl;
00142     std::cout << "Transpose Iy: " << num_cells_y << " by " << ny << std::endl;
00143     std::cout << "Gz: " << mz << " by " << nz << std::endl;
00144     std::cout << "Transpose Iz: " << num_cells_z << " by " << nz << std::endl;
00145     #endif
00146
00147     int total_rows{mx*num_cells_y*num_cells_z +
00148                   num_cells_x*my*num_cells_z +
00149                   num_cells_x*num_cells_y*mz};
00150     int total_cols{nx*ny*nz};
00151
00152     #if MTK_VERBOSE_LEVEL > 2
00153     std::cout << "Grad 3D: " << total_rows << " by " << total_cols << std::endl;
00154     #endif
00155
00156     mtk::DenseMatrix g3d(total_rows, total_cols);
00157
00158
00159
00160
00161

```

```

00162     for(auto ii = 0; ii < total_cols; ii++) {
00163         for(auto jj = 0; jj < mx*num_cells_y*num_cells_z; jj++) {
00164             g3d.SetValue(jj,ii, gx.GetValue(jj,ii));
00165         }
00166
00167         int offset = mx*num_cells_y*num_cells_z;
00168
00169         for(auto kk = 0; kk < num_cells_x*my*num_cells_z; kk++) {
00170             g3d.SetValue(kk + offset, ii, gy.GetValue(kk,ii));
00171         }
00172
00173         offset += num_cells_x*my*num_cells_z;
00174
00175         for(auto ll = 0; ll < num_cells_x*num_cells_y*mz; ll++) {
00176             g3d.SetValue(ll + offset, ii, gz.GetValue(ll,ii));
00177         }
00178     }
00179
00180     gradient_ = g3d;
00181
00182     return info;
00183 }
00184
00185 mtk::DenseMatrix mtk::Grad3D::ReturnAsDenseMatrix() const {
00186
00187     return gradient_;
00188 }

```

17.91 src/mtk_interp_1d.cc File Reference


Includes the implementation of the class Interp1D.

```

#include <cstring>
#include "mtk_tools.h"
#include "mtk_interp_1d.h"

```

Include dependency graph for mtk_interp_1d.cc:



Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

Functions

- `std::ostream & mtk::operator<< (std::ostream &stream, mtk::Interp1D &in)`

17.91.1 Detailed Description

This class implements a 1D interpolation operator.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu
 : Johnny Corbino - jcorbino at mail dot sdsu dot edu

Definition in file [mtk_interp_1d.cc](#).

17.92 mtk_interp_1d.cc

```

00001
00012 /*
00013 Copyright (C) 2015, Computational Science Research Center, San Diego State
00014 University. All rights reserved.
00015
00016 Redistribution and use in source and binary forms, with or without modification,
00017 are permitted provided that the following conditions are met:
00018
00019 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00020 and a copy of the modified files should be reported once modifications are
00021 completed, unless these modifications are made through the project's GitHub
00022 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00023 should be developed and included in any deliverable.
00024
00025 2. Redistributions of source code must be done through direct
00026 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00027
00028 3. Redistributions in binary form must reproduce the above copyright notice,
00029 this list of conditions and the following disclaimer in the documentation and/or
00030 other materials provided with the distribution.
00031
00032 4. Usage of the binary form on proprietary applications shall require explicit
00033 prior written permission from the the copyright holders, and due credit should
00034 be given to the copyright holders.
00035
00036 5. Neither the name of the copyright holder nor the names of its contributors
00037 may be used to endorse or promote products derived from this software without
00038 specific prior written permission.
00039
00040 The copyright holders provide no reassurances that the source code provided does
00041 not infringe any patent, copyright, or any other intellectual property rights of
00042 third parties. The copyright holders disclaim any liability to any recipient for
00043 claims brought against recipient by any third party for infringement of that
00044 parties intellectual property rights.
00045
00046 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00047 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00048 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00049 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00050 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00051 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00052 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00053 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00054 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00055 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00056 */
00057
00058 #include <cstring>
00059
00060 #include "mtk_tools.h"
00061
00062 #include "mtk_interp_1d.h"

```

```

00063
00064 namespace mtk {
00065
00066 std::ostream& operator <<(std::ostream &stream, mtk::Interp1D &in) {
00067
00069     stream << "coeffs_interior_[1:" << in.order_accuracy_ << "]" = ";
00070     for (auto ii = 0; ii < in.order_accuracy_; ++ii) {
00071         stream << std::setw(9) << in.coeffs_interior_[ii] << " ";
00072     }
00073     stream << std::endl;
00074
00075     return stream;
00076 }
00077 }
00078
00079 mtk::Interp1D::Interp1D():
00080     dir_interp_(mtk::SCALAR_TO_VECTOR),
00081     order_accuracy_(mtk::kDefaultOrderAccuracy),
00082     coeffs_interior_(nullptr) {}
00083
00084 mtk::Interp1D::Interp1D(const Interp1D &interp):
00085     dir_interp_(interp.dir_interp_),
00086     order_accuracy_(interp.order_accuracy_),
00087     coeffs_interior_(interp.coeffs_interior_) {}
00088
00089 mtk::Interp1D::~Interp1D() {
00090     delete[] coeffs_interior_;
00091     coeffs_interior_ = nullptr;
00092 }
00093
00094 bool mtk::Interp1D::ConstructInterp1D(int order_accuracy,
00095     mtk::DirInterp dir) {
00096
00097     #if MTK_PERFORM_PREVENTIONS
00098     mtk::Tools::Prevent(order_accuracy < 2, __FILE__, __LINE__, __func__);
00099     mtk::Tools::Prevent((order_accuracy%2) != 0, __FILE__, __LINE__, __func__);
00100     mtk::Tools::Prevent(dir < mtk::SCALAR_TO_VECTOR &&
00101         dir > mtk::VECTOR_TO_SCALAR,
00102         __FILE__, __LINE__, __func__);
00103     #endif
00104
00105     #if MTK_VERBOSE_LEVEL > 2
00106     std::cout << "order_accuracy_ = " << order_accuracy << std::endl;
00107     #endif
00108
00109     order_accuracy_ = order_accuracy;
00110
00111     try {
00112         coeffs_interior_ = new mtk::Real[order_accuracy_];
00113     } catch (std::bad_alloc &memory_allocation_exception) {
00114         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00115             std::endl;
00116         std::cerr << memory_allocation_exception.what() << std::endl;
00117     }
00118
00119     memset(coeffs_interior_,
00120         mtk::kZero,
00121         sizeof(coeffs_interior_[0])*order_accuracy_);
00122
00123     for (int ii = 0; ii < order_accuracy_; ++ii) {
00124         coeffs_interior_[ii] = mtk::kOne;
00125     }
00126
00127     return true;
00128 }
00129
00130 mtk::Real *mtk::Interp1D::coeffs_interior() const {
00131
00132     return coeffs_interior_;
00133 }
00134
00135 mtk::DenseMatrix mtk::Interp1D::ReturnAsDenseMatrix(
00136     const UniStgGrid1D &grid) const {
00137
00138     int nn{grid.num_cells_x()}; // Number of cells on the grid.
00139
00140     #if MTK_PERFORM_PREVENTIONS
00141     mtk::Tools::Prevent(nn <= 0, __FILE__, __LINE__, __func__);
00142     #endif

```

```

00145
00146 int gg_num_rows{}; // Number of rows.
00147 int gg_num_cols{}; // Number of columns.
00148
00149 if (dir_interp_ == mtk::SCALAR_TO_VECTOR) {
00150     gg_num_rows = nn + 1;
00151     gg_num_cols = nn + 2;
00152 } else {
00153     gg_num_rows = nn + 2;
00154     gg_num_cols = nn + 1;
00155 }
00156
00157 // Output matrix featuring sizes for gradient operators.
00158
00159 mtk::DenseMatrix out(gg_num_rows, gg_num_cols);
00160
00162
00163 out.SetValue(0, 0, mtk::kOne);
00164
00166
00167 for (auto ii = 1; ii < gg_num_rows - 1; ++ii) {
00168     for (auto jj = ii; jj < order_accuracy_ + ii; ++jj) {
00169         out.SetValue(ii, jj, mtk::kOne/order_accuracy_);
00170     }
00171 }
00172
00174
00175 out.SetValue(gg_num_rows - 1, gg_num_cols - 1, mtk::kOne);
00176
00177 return out;
00178 }

```

17.93 src/mtk_lap_1d.cc File Reference


Includes the implementation of the class Lap1D.

```

#include <cstdlib>
#include <cstdio>
#include <cstring>
#include <iostream>
#include <iomanip>
#include "mtk_roots.h"
#include "mtk_tools.h"
#include "mtk_blas_adapter.h"
#include "mtk_grad_1d.h"
#include "mtk_div_1d.h"
#include "mtk_lap_1d.h"

```

Include dependency graph for mtk_lap_1d.cc:



Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

Functions

- `std::ostream & mtk::operator<< (std::ostream &stream, mtk::Lap1D &in)`

17.93.1 Detailed Description

This class implements a 1D Laplacian operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (CBSA).

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_lap_1d.cc](#).

17.94 mtk_lap_1d.cc

```

00001
00011 /*
00012 Copyright (C) 2015, Computational Science Research Center, San Diego State
00013 University. All rights reserved.
00014
00015 Redistribution and use in source and binary forms, with or without modification,
00016 are permitted provided that the following conditions are met:
00017
00018 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00019 and a copy of the modified files should be reported once modifications are
00020 completed, unless these modifications are made through the project's GitHub
00021 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00022 should be developed and included in any deliverable.
00023
00024 2. Redistributions of source code must be done through direct
00025 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00026
00027 3. Redistributions in binary form must reproduce the above copyright notice,
00028 this list of conditions and the following disclaimer in the documentation and/or
00029 other materials provided with the distribution.
00030
00031 4. Usage of the binary form on proprietary applications shall require explicit
00032 prior written permission from the the copyright holders, and due credit should
00033 be given to the copyright holders.
00034
00035 5. Neither the name of the copyright holder nor the names of its contributors
00036 may be used to endorse or promote products derived from this software without
00037 specific prior written permission.
00038
00039 The copyright holders provide no reassurances that the source code provided does
00040 not infringe any patent, copyright, or any other intellectual property rights of
00041 third parties. The copyright holders disclaim any liability to any recipient for
00042 claims brought against recipient by any third party for infringement of that
00043 parties intellectual property rights.
00044
00045 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00046 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00047 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00048 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00049 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00050 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00051 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00052 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT

```

```

00053 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00054 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00055 */
00056
00057 #include <cstdlib>
00058 #include <cstdio>
00059 #include <cstring>
00060
00061 #include <iostream>
00062 #include <iomanip>
00063
00064 #include "mtk_roots.h"
00065 #include "mtk_tools.h"
00066 #include "mtk_blas_adapter.h"
00067 #include "mtk_grad_1d.h"
00068 #include "mtk_div_1d.h"
00069 #include "mtk_lap_1d.h"
00070
00071 namespace mtk {
00072
00073 std::ostream& operator <<(std::ostream &stream, mtk::Lap1D &in) {
00074
00075     stream << "laplacian_[0] = " << in.laplacian_[0] << std::endl << std::endl;
00076
00077     stream << "laplacian_[1:" << 2*in.order_accuracy_ - 1 << "]" = " <<
00078         std::endl << std::endl;
00079     for (auto ii = 1; ii <= (2*in.order_accuracy_ - 1); ++ii) {
00080         stream << std::setw(13) << in.laplacian_[ii] << " ";
00081     }
00082     stream << std::endl << std::endl;
00083
00084     auto offset = 1 + (2*in.order_accuracy_ - 1);
00085
00086     stream << "laplacian_[ " << offset << ":" << offset +
00087         (in.order_accuracy_ - 1)*(2*in.order_accuracy_ - 1 << "] = " <<
00088         std::endl << std::endl;
00089
00090     for (auto ii = 0; ii < in.order_accuracy_ - 1; ++ii) {
00091         for (auto jj = 0; jj < 2*in.order_accuracy_; ++jj) {
00092             stream << std::setw(13) <<
00093                 in.laplacian_[offset + ii*(2*in.order_accuracy_) + jj];
00094         }
00095         stream << std::endl;
00096     }
00097
00098     return stream;
00099 }
00100
00101 mtk::Lap1D::Lap1D():
00102     order_accuracy_(mtk::kDefaultOrderAccuracy),
00103     laplacian_length_(),
00104     delta_(mtk::kZero),
00105     mimetic_threshold_(mtk::kDefaultMimeticThreshold) {}
00106
00107 mtk::Lap1D::~Lap1D() {
00108
00109     delete [] laplacian_;
00110     laplacian_ = nullptr;
00111 }
00112
00113 int mtk::Lap1D::order_accuracy() const {
00114
00115     return order_accuracy_;
00116 }
00117
00118 mtk::Real mtk::Lap1D::mimetic_threshold() const {
00119
00120     return mimetic_threshold_;
00121 }
00122
00123 mtk::Real mtk::Lap1D::delta() const {
00124
00125     return delta_;
00126 }
00127
00128 bool mtk::Lap1D::ConstructLap1D(int order_accuracy,
00129     mtk::Real mimetic_threshold) {

```

```

00137
00138 #ifdef MTK_PERFORM_PREVENTIONS
00139 mtk::Tools::Prevent(order_accuracy < 2, __FILE__, __LINE__, __func__);
00140 mtk::Tools::Prevent((order_accuracy%2) != 0, __FILE__, __LINE__, __func__);
00141 mtk::Tools::Prevent(mimetic_threshold <= mtk::kZero,
00142                     __FILE__, __LINE__, __func__);
00143
00144 if (order_accuracy >= mtk::kCriticalOrderAccuracyDiv) {
00145     std::cout << "WARNING: Numerical accuracy is high." << std::endl;
00146 }
00147
00148 std::cout << "order_accuracy_ = " << order_accuracy << std::endl;
00149 std::cout << "mimetic_threshold_ = " << mimetic_threshold << std::endl;
00150 #endif
00151
00152 order_accuracy_ = order_accuracy;
00153 mimetic_threshold_ = mimetic_threshold;
00154
00155 mtk::Grad1D grad; // Mimetic gradient.
00156
00157 bool info = grad.ConstructGrad1D(order_accuracy_, mimetic_threshold_);
00158
00159 #ifdef MTK_PERFORM_PREVENTIONS
00160 if (!info) {
00161     std::cerr << "Mimetic grad could not be built." << std::endl;
00162     return false;
00163 }
00164 #endif
00165
00166 mtk::Div1D div; // Mimetic divergence.
00167
00168 info = div.ConstructDiv1D(order_accuracy_, mimetic_threshold_);
00169
00170 #ifdef MTK_PERFORM_PREVENTIONS
00171 if (!info) {
00172     std::cerr << "Mimetic div could not be built." << std::endl;
00173     return false;
00174 }
00175 #endif
00176
00177 // Since these are mimetic operator, we must multiply the matrices arising
00178 // from both the divergence and the Laplacian, in order to get the
00179 // approximating coefficients for the Laplacian operator.
00180
00181 // However, we must choose a grid that implied a step size of 1, so to get
00182 // the approximating coefficients, without being affected from the
00183 // normalization with respect to the grid (dimensionless).
00184
00185 // Also, the grid must be of the minimum size to support the requested order
00186 // of accuracy. We must please the divergence for this!
00187
00188 mtk::UniStgGrid1D aux(mtk::kZero,
00189                      (mtk::Real) 3*order_accuracy_ - 1,
00190                      3*order_accuracy_ - 1);
00191
00192 #if MTK_VERBOSE_LEVEL > 2
00193 std::cout << "aux =" << std::endl;
00194 std::cout << aux << std::endl;
00195 std::cout << "aux.delta_x() = " << aux.delta_x() << std::endl;
00196 std::cout << std::endl;
00197 #endif
00198
00199 mtk::DenseMatrix grad_m(grad.ReturnAsDenseMatrix(aux));
00200
00201 #if MTK_VERBOSE_LEVEL > 4
00202 std::cout << "grad_m =" << std::endl;
00203 std::cout << grad_m << std::endl;
00204 #endif
00205
00206 mtk::DenseMatrix div_m(div.ReturnAsDenseMatrix(aux));
00207
00208 #if MTK_VERBOSE_LEVEL > 4
00209 std::cout << "div_m =" << std::endl;
00210 std::cout << div_m << std::endl;
00211 #endif
00212
00213 mtk::DenseMatrix lap; // Laplacian matrix to hold to computed coefficients.
00214
00215

```



```

00224     lap = mtk::BLASAdapter::RealDenseMM(div_m, grad_m);
00225
00226     #if MTK_VERBOSE_LEVEL > 4
00227     std::cout << "lap =" << std::endl;
00228     std::cout << lap << std::endl;
00229     #endif
00230
00231
00232
00233
00234
00235     // The output array will have this form:
00236     // 1. The first entry of the array will contain the used order kk.
00237     // 2. The second entry of the array will contain the collection of
00238     // approximating coefficients for the interior of the grid.
00239     // 3. The next entries will contain the collections of approximating
00240     // coefficients for the west boundary of the grid.
00241
00242     laplacian_length_ = 1 + (2*order_accuracy_ - 1) +
00243         (order_accuracy_ - 1)*(2*order_accuracy_);
00244
00245     #if MTK_VERBOSE_LEVEL > 2
00246     std::cout << "laplacian_length_ = " << laplacian_length_ << std::endl;
00247     std::cout << std::endl;
00248     #endif
00249
00250     try {
00251         laplacian_ = new mtk::Real[laplacian_length_];
00252     } catch (std::bad_alloc &memory_allocation_exception) {
00253         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00254             std::endl;
00255         std::cerr << memory_allocation_exception.what() << std::endl;
00256     }
00257     memset(laplacian_, mtk::kZero, sizeof(laplacian_[0])*laplacian_length_);
00258
00259
00260
00261     laplacian_[0] = order_accuracy_;
00262
00263
00264
00265     for (auto ii = 0; ii < 2*order_accuracy_ - 1; ++ii) {
00266         laplacian_[ii + 1] = lap.GetValue(1 + (order_accuracy_ - 1), ii + 1);
00267     }
00268
00269
00270
00271
00272     auto offset = 1 + (2*order_accuracy_ - 1);
00273
00274     for (auto ii = 0; ii < order_accuracy_ - 1; ++ii) {
00275         for (auto jj = 0; jj < 2*order_accuracy_; ++jj) {
00276             laplacian_[offset + ii*(2*order_accuracy_) + jj] =
00277                 lap.GetValue(1 + ii, jj);
00278         }
00279     }
00280
00281     delta_ = mtk::kZero;
00282
00283     return true;
00284 }
00285
00286 mtk::DenseMatrix mtk::Lap1D::ReturnAsDenseMatrix(
00287     const UniStgGrid1D &grid) const {
00288
00289     int nn{grid.num_cells_x()}; // Number of cells on the grid.
00290
00291     #ifdef MTK_PERFORM_PREVENTIONS
00292     mtk::Tools::Prevent(nn <= 0, __FILE__, __LINE__, __func__);
00293     mtk::Tools::Prevent(nn < 3*order_accuracy_ - 1, __FILE__, __LINE__, __func__);
00294     #endif
00295
00296     mtk::DenseMatrix lap(nn + 2, nn + 2); // Laplacian matrix to be returned.
00297
00298     delta_ = grid.delta_x();
00299
00300     mtk::Real idx{mtk::kOne/(grid.delta_x()*grid.delta_x())}; // Inverse of
    dx^2.
00301
00302
00303
00304     auto offset = (1 + 2*order_accuracy_ - 1);
00305
00306     for (auto ii = 0; ii < order_accuracy_ - 1; ++ii) {
00307         for (auto jj = 0; jj < 2*order_accuracy_; ++jj) {
00308             lap.SetValue(1 + ii,
00309                 jj,
00310                 idx*laplacian_[offset + ii*2*order_accuracy_ + jj]);

```

```

00311     }
00312 }
00313
00315
00316 offset = 1 + (order_accuracy_ - 1);
00317
00318 int kk{1};
00319 for (auto ii = order_accuracy_; ii <= nn - (order_accuracy_ - 1); ++ii) {
00320     int mm{1};
00321     for (auto jj = 0; jj < 2*order_accuracy_ - 1; ++jj) {
00322         lap.SetValue(ii, jj + kk, idx*laplacian_[mm]);
00323         mm = mm + 1;
00324     }
00325     kk = kk + 1;
00326 }
00327
00329
00330 offset = (1 + 2*order_accuracy_ - 1);
00331
00332 auto aux = order_accuracy_ + (nn - 2*(order_accuracy_ - 1));
00333
00334 auto ll = 1;
00335 auto rr = 1;
00336 for (auto ii = nn; ii > aux - 1; --ii) {
00337     auto cc = 0;
00338     for (auto jj = nn + 2 - 1; jj >= (nn + 2) - 2*order_accuracy_; --jj) {
00339         lap.SetValue(ii, jj, lap.GetValue(rr, cc));
00340         ++ll;
00341         ++cc;
00342     }
00343     rr++;
00344 }
00345
00352
00353 return lap;
00354 }
00355
00356 const mtk::Real* mtk::Lap1D::data(const UniStgGrid1D &grid) const {
00357
00358     mtk::DenseMatrix tmp;
00359
00360     tmp = ReturnAsDenseMatrix(grid);
00361
00362     return tmp.data();
00363 }

```

17.95 src/mtk_lap_2d.cc File Reference


Includes the implementation of the class Lap2D.

```

#include <cstdlib>
#include <cstdio>
#include <iostream>
#include <iomanip>
#include "mtk_roots.h"
#include "mtk_blas_adapter.h"
#include "mtk_grad_2d.h"
#include "mtk_div_2d.h"
#include "mtk_lap_2d.h"

```

Include dependency graph for mtk_lap_2d.cc:



17.95.1 Detailed Description

This class implements a 2D Laplacian operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (CBSA).

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_lap_2d.cc](#).

17.96 mtk_lap_2d.cc

```

00001
00011 /*
00012 Copyright (C) 2015, Computational Science Research Center, San Diego State
00013 University. All rights reserved.
00014
00015 Redistribution and use in source and binary forms, with or without modification,
00016 are permitted provided that the following conditions are met:
00017
00018 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00019 and a copy of the modified files should be reported once modifications are
00020 completed, unless these modifications are made through the project's GitHub
00021 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00022 should be developed and included in any deliverable.
00023
00024 2. Redistributions of source code must be done through direct
00025 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00026
00027 3. Redistributions in binary form must reproduce the above copyright notice,
00028 this list of conditions and the following disclaimer in the documentation and/or
00029 other materials provided with the distribution.
00030
00031 4. Usage of the binary form on proprietary applications shall require explicit
00032 prior written permission from the the copyright holders, and due credit should
00033 be given to the copyright holders.
00034
00035 5. Neither the name of the copyright holder nor the names of its contributors
00036 may be used to endorse or promote products derived from this software without
00037 specific prior written permission.
00038
00039 The copyright holders provide no reassurances that the source code provided does
00040 not infringe any patent, copyright, or any other intellectual property rights of
00041 third parties. The copyright holders disclaim any liability to any recipient for
00042 claims brought against recipient by any third party for infringement of that
  
```

```

00043 parties intellectual property rights.
00044
00045 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00046 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00047 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00048 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00049 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00050 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00051 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00052 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00053 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00054 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00055 */
00056
00057 #include <cstdlib>
00058 #include <cstdio>
00059
00060 #include <iostream>
00061 #include <iomanip>
00062
00063 #include "mtk_roots.h"
00064 #include "mtk_blas_adapter.h"
00065 #include "mtk_grad_2d.h"
00066 #include "mtk_div_2d.h"
00067 #include "mtk_lap_2d.h"
00068
00069 mtk::Lap2D::Lap2D(): order_accuracy_(), mimetic_threshold_() {}
00070
00071 mtk::Lap2D::Lap2D(const Lap2D &lap):
00072     order_accuracy_(lap.order_accuracy_),
00073     mimetic_threshold_(lap.mimetic_threshold_) {}
00074
00075 mtk::Lap2D::~~Lap2D() {}
00076
00077 bool mtk::Lap2D::ConstructLap2D(const
    mtk::UniStgGrid2D &grid,
00078                                int order_accuracy,
00079                                mtk::Real mimetic_threshold) {
00080
00081     mtk::Grad2D gg;
00082     mtk::Div2D dd;
00083
00084     bool info{gg.ConstructGrad2D(grid, order_accuracy, mimetic_threshold)};
00085
00086     #ifdef MTK_PERFORM_PREVENTIONS
00087     if (!info) {
00088         std::cerr << "Mimetic lap could not be built." << std::endl;
00089         return info;
00090     }
00091     #endif
00092
00093     info = dd.ConstructDiv2D(grid, order_accuracy, mimetic_threshold);
00094
00095     #ifdef MTK_PERFORM_PREVENTIONS
00096     if (!info) {
00097         std::cerr << "Mimetic div could not be built." << std::endl;
00098         return info;
00099     }
00100     #endif
00101
00102     mtk::DenseMatrix ggm(gg.ReturnAsDenseMatrix());
00103     mtk::DenseMatrix ddm(dd.ReturnAsDenseMatrix());
00104
00105     laplacian_ = mtk::BLASAdapter::RealDenseMM(ddm, ggm);
00106
00107     return info;
00108 }
00109
00110 mtk::DenseMatrix mtk::Lap2D::ReturnAsDenseMatrix() const {
00111
00112     return laplacian_;
00113 }
00114
00115 mtk::Real *mtk::Lap2D::data() const {
00116
00117     return laplacian_.data();
00118 }


```

17.97 src/mtk_lap_3d.cc File Reference

Includes the implementation of the class Lap3D.

```
#include <cstdlib>
#include <cstdio>
#include <iostream>
#include <iomanip>
#include "mtk_roots.h"
#include "mtk_blas_adapter.h"
#include "mtk_grad_3d.h"
#include "mtk_div_3d.h"
#include "mtk_lap_3d.h"
```

Include dependency graph for mtk_lap_3d.cc:



17.97.1 Detailed Description

This class implements a 3D Laplacian operator, constructed using the Castillo-Blomgren-Sanchez (CBS) Algorithm (CBSA).

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_lap_3d.cc](#).

17.98 mtk_lap_3d.cc

```
00001
00011 /*
00012 Copyright (C) 2015, Computational Science Research Center, San Diego State
00013 University. All rights reserved.
00014
00015 Redistribution and use in source and binary forms, with or without modification,
00016 are permitted provided that the following conditions are met:
00017
00018 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00019 and a copy of the modified files should be reported once modifications are
00020 completed, unless these modifications are made through the project's GitHub
00021 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00022 should be developed and included in any deliverable.
00023
```

```

00024 2. Redistributions of source code must be done through direct
00025 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00026
00027 3. Redistributions in binary form must reproduce the above copyright notice,
00028 this list of conditions and the following disclaimer in the documentation and/or
00029 other materials provided with the distribution.
00030
00031 4. Usage of the binary form on proprietary applications shall require explicit
00032 prior written permission from the the copyright holders, and due credit should
00033 be given to the copyright holders.
00034
00035 5. Neither the name of the copyright holder nor the names of its contributors
00036 may be used to endorse or promote products derived from this software without
00037 specific prior written permission.
00038
00039 The copyright holders provide no reassurances that the source code provided does
00040 not infringe any patent, copyright, or any other intellectual property rights of
00041 third parties. The copyright holders disclaim any liability to any recipient for
00042 claims brought against recipient by any third party for infringement of that
00043 parties intellectual property rights.
00044
00045 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00046 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00047 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00048 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00049 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00050 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00051 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00052 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00053 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00054 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00055 */
00056
00057 #include <cstdlib>
00058 #include <cstdio>
00059
00060 #include <iostream>
00061 #include <iomanip>
00062
00063 #include "mtk_roots.h"
00064 #include "mtk_blas_adapter.h"
00065 #include "mtk_grad_3d.h"
00066 #include "mtk_div_3d.h"
00067 #include "mtk_lap_3d.h"
00068
00069 mtk::UniStgGrid3D mtk::Lap3D::operator*(const
mtk::UniStgGrid3D &grid) const {
00070
00071     mtk::UniStgGrid3D out;
00072
00073     return out;
00074 }
00075
00076 mtk::Lap3D::Lap3D(): order_accuracy_(), mimetic_threshold_() {}
00077
00078 mtk::Lap3D::Lap3D(const Lap3D &lap):
00079     order_accuracy_(lap.order_accuracy_),
00080     mimetic_threshold_(lap.mimetic_threshold_) {}
00081
00082 mtk::Lap3D::~Lap3D() {}
00083
00084 bool mtk::Lap3D::ConstructLap3D(const
mtk::UniStgGrid3D &grid,
00085                                 int order_accuracy,
00086                                 mtk::Real mimetic_threshold) {
00087
00088     mtk::Grad3D gg;
00089     mtk::Div3D dd;
00090
00091     bool info{gg.ConstructGrad3D(grid, order_accuracy, mimetic_threshold)};
00092
00093     #ifdef MTK_PERFORM_PREVENTIONS
00094     if (!info) {
00095         std::cerr << "Mimetic lap could not be built." << std::endl;
00096         return info;
00097     }
00098     #endif
00099
00100     info = dd.ConstructDiv3D(grid, order_accuracy, mimetic_threshold);
00101
00102     #ifdef MTK_PERFORM_PREVENTIONS

```

```

00103     if (!info) {
00104         std::cerr << "Mimetic div could not be built." << std::endl;
00105         return info;
00106     }
00107     #endif
00108
00109     mtk::DenseMatrix ggm(gg.ReturnAsDenseMatrix());
00110     mtk::DenseMatrix ddm(dd.ReturnAsDenseMatrix());
00111
00112     laplacian_ = mtk::BLASAdapter::RealDenseMM(ddm, ggm);
00113
00114     return info;
00115 }
00116
00117 mtk::DenseMatrix mtk::Lap3D::ReturnAsDenseMatrix() const {
00118     return laplacian_;
00119 }
00120 }
00121
00122 mtk::Real *mtk::Lap3D::data() const {
00123
00124     return laplacian_.data();
00125 }

```

17.99 src/mtk_lapack_adapter.cc File Reference


Adapter class for the LAPACK API.

```

#include <cstring>
#include <iostream>
#include <iomanip>
#include <algorithm>
#include "mtk_tools.h"
#include "mtk_dense_matrix.h"
#include "mtk_lapack_adapter.h"

```

Include dependency graph for mtk_lapack_adapter.cc:



Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

Functions

- void `mtk::sgesv_` (int *n, int *nrhs, Real *a, int *lda, int *ipiv, Real *b, int *ldb, int *info)
- void `mtk::sgels_` (char *trans, int *m, int *n, int *nrhs, Real *a, int *lda, Real *b, int *ldb, Real *work, int *lwork, int *info)
Single-precision GEneral matrix Least Squares solver.
- void `mtk::sgeqrf_` (int *m, int *n, Real *a, int *lda, Real *tau, Real *work, int *lwork, int *info)
Single-precision GEneral matrix QR Factorization.
- void `mtk::sormqr_` (char *side, char *trans, int *m, int *n, int *k, Real *a, int *lda, Real *tau, Real *c, int *ldc, Real *work, int *lwork, int *info)
Single-precision Orthogonal [Matrix](#) from QR factorization.

17.99.1 Detailed Description

This class contains a collection of static classes, that posses direct access to the underlying structure of the matrices, thus allowing programmers to exploit some of the numerical methods implemented in the LAPACK.

The **LAPACK (Linear Algebra PACKage)** is written in Fortran 90 and provides routines for solving systems of simultaneous linear equations, least-squares solutions of linear systems of equations, eigenvalue problems, and singular value problems.

See also

<http://www.netlib.org/lapack/>

Todo Write documentation using LaTeX.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_lapack_adapter.cc](#).

17.100 mtk_lapack_adapter.cc

```
00001
00021 /*
00022 Copyright (C) 2015, Computational Science Research Center, San Diego State
00023 University. All rights reserved.
00024
00025 Redistribution and use in source and binary forms, with or without modification,
00026 are permitted provided that the following conditions are met:
00027
00028 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00029 and a copy of the modified files should be reported once modifications are
00030 completed, unless these modifications are made through the project's GitHub
00031 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00032 should be developed and included in any deliverable.
00033
00034 2. Redistributions of source code must be done through direct
00035 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00036
00037 3. Redistributions in binary form must reproduce the above copyright notice,
00038 this list of conditions and the following disclaimer in the documentation and/or
00039 other materials provided with the distribution.
00040
00041 4. Usage of the binary form on proprietary applications shall require explicit
00042 prior written permission from the the copyright holders, and due credit should
00043 be given to the copyright holders.
```



```

00044
00045 5. Neither the name of the copyright holder nor the names of its contributors
00046 may be used to endorse or promote products derived from this software without
00047 specific prior written permission.
00048
00049 The copyright holders provide no reassurances that the source code provided does
00050 not infringe any patent, copyright, or any other intellectual property rights of
00051 third parties. The copyright holders disclaim any liability to any recipient for
00052 claims brought against recipient by any third party for infringement of that
00053 parties intellectual property rights.
00054
00055 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00056 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00057 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00058 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00059 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00060 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00061 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00062 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00063 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00064 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00065 */
00066
00067 #include <cstring>
00068
00069 #include <iostream>
00070 #include <iomanip>
00071
00072 #include <algorithm>
00073
00074 #include "mtk_tools.h"
00075 #include "mtk_dense_matrix.h"
00076 #include "mtk_lapack_adapter.h"
00077
00078 namespace mtk {
00079
00080 extern "C" {
00081
00082 #ifdef MTK_PRECISION_DOUBLE
00083
00102 void dgesv_(int* n,
00103             int* nrhs,
00104             Real* a,
00105             int* lda,
00106             int* ipiv,
00107             Real* b,
00108             int* ldb,
00109             int* info);
00110 #else
00111
00130 void sgesv_(int* n,
00131             int* nrhs,
00132             Real* a,
00133             int* lda,
00134             int* ipiv,
00135             Real* b,
00136             int* ldb,
00137             int* info);
00138 #endif
00139
00140 #ifdef MTK_PRECISION_DOUBLE
00141
00184 void dgels_(char* trans,
00185             int* m,
00186             int* n,
00187             int* nrhs,
00188             Real* a,
00189             int* lda,
00190             Real* b,
00191             int* ldb,
00192             Real* work,
00193             int* lwork,
00194             int* info);
00195 #else
00196
00239 void sgels_(char* trans,
00240             int* m,
00241             int* n,
00242             int* nrhs,
00243             Real* a,
00244             int* lda,

```

```

00245         Real* b,
00246         int* ldb,
00247         Real* work,
00248         int* lwork,
00249         int* info);
00250 #endif
00251
00252 #ifdef MTK_PRECISION_DOUBLE
00253
00282 void dgeqrf_(int *m,
00283              int *n,
00284              Real *a,
00285              int *lda,
00286              Real *tau,
00287              Real *work,
00288              int *lwork,
00289              int *info);
00290 #else
00291
00320 void sgeqrf_(int *m,
00321              int *n,
00322              Real *a,
00323              int *lda,
00324              Real *tau,
00325              Real *work,
00326              int *lwork,
00327              int *info);
00328 #endif
00329
00330 #ifdef MTK_PRECISION_DOUBLE
00331
00365 void dormqr_(char *side,
00366              char *trans,
00367              int *m,
00368              int *n,
00369              int *k,
00370              Real *a,
00371              int *lda,
00372              Real *tau,
00373              Real *c,
00374              int *ldc,
00375              Real *work,
00376              int *lwork,
00377              int *info);
00378 #else
00379
00413 void sormqr_(char *side,
00414              char *trans,
00415              int *m,
00416              int *n,
00417              int *k,
00418              Real *a,
00419              int *lda,
00420              Real *tau,
00421              Real *c,
00422              int *ldc,
00423              Real *work,
00424              int *lwork,
00425              int *info);
00426 #endif
00427 }
00428 }
00429
00430 int mtk::LAPACKAdapter::SolveDenseSystem(
    mtk::DenseMatrix &mm,
00431                                         mtk::Real *rhs) {
00432
00433     #ifdef MTK_PERFORM_PREVENTIONS
00434     mtk::Tools::Prevent(rhs == nullptr, __FILE__, __LINE__, __func__);
00435     #endif
00436
00437     int *ipiv{};           // Array for pivoting information.
00438     int nrhs{1};          // Number of right-hand sides.
00439     int info{};           // Status of the solution.
00440     int mm_rank{mm.num_rows()}; // Rank of the matrix.
00441
00442     try {
00443         ipiv = new int[mm_rank];
00444     } catch (std::bad_alloc &memory_allocation_exception) {
00445         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00446             std::endl;

```

```

00447     std::cerr << memory_allocation_exception.what() << std::endl;
00448 }
00449 memset(ipiv, 0, sizeof(ipiv[0])*mm_rank);
00450
00451 int ldbb = mm_rank;
00452 int mm_ld = mm_rank;
00453
00454 #ifdef MTK_PRECISION_DOUBLE
00455 dgesv_(&mm_rank, &nrhs, mm.data(), &mm_ld, ipiv, rhs, &ldbb, &info);
00456 #else
00457 fgesv_(&mm_rank, &nrhs, mm.data(), &mm_ld, ipiv, rhs, &ldbb, &info);
00458 #endif
00459
00460 delete [] ipiv;
00461
00462 return info;
00463 }
00464
00465 int mtk::LAPACKAdapter::SolveDenseSystem(
    mtk::DenseMatrix &mm,
    mtk::DenseMatrix &bb) {
00466
00467     int nrhs{bb.num_rows()}; // Number of right-hand sides.
00468
00469     #ifdef MTK_PERFORM_PREVENTIONS
00470     mtk::Tools::Prevent(nrhs <= 0, __FILE__, __LINE__, __func__);
00471     #endif
00472
00473     int *ipiv{}; // Array for pivoting information.
00474     int info{}; // Status of the solution.
00475     int mm_rank{mm.num_rows()}; // Rank of the matrix.
00476
00477     try {
00478         ipiv = new int[mm_rank];
00479     } catch (std::bad_alloc &memory_allocation_exception) {
00480         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00481             std::endl;
00482         std::cerr << memory_allocation_exception.what() << std::endl;
00483     }
00484     memset(ipiv, 0, sizeof(ipiv[0])*mm_rank);
00485
00486     int ldbb = mm_rank;
00487     int mm_ld = mm_rank;
00488
00489     #ifdef MTK_PRECISION_DOUBLE
00490     dgesv_(&mm_rank, &nrhs, mm.data(), &mm_ld, ipiv, bb.data(), &ldbb, &info);
00491     #else
00492     fgesv_(&mm_rank, &nrhs, mm.data(), &mm_ld, ipiv, bb.data(), &ldbb, &info);
00493     #endif
00494
00495     delete [] ipiv;
00496
00497     // After output, the data in the matrix will be column-major ordered.
00498
00499     bb.SetOrdering(mtk::COL_MAJOR);
00500
00501     #if MTK_VERBOSE_LEVEL > 12
00502     std::cout << "bb_col_maj_ord =" << std::endl;
00503     std::cout << bb << std::endl;
00504     #endif
00505
00506     bb.OrderRowMajor();
00507
00508     #if MTK_VERBOSE_LEVEL > 12
00509     std::cout << "bb_row_maj_ord =" << std::endl;
00510     std::cout << bb << std::endl;
00511     #endif
00512
00513     return info;
00514 }
00515
00516
00517 int mtk::LAPACKAdapter::SolveDenseSystem(
    mtk::DenseMatrix &mm,
    mtk::UniStgGrid1D &rhs) {
00518
00519     int nrhs{1}; // Number of right-hand sides.
00520
00521     int *ipiv{}; // Array for pivoting information.
00522     int info{}; // Status of the solution.
00523     int mm_rank{mm.num_rows()}; // Rank of the matrix.
00524
00525

```

```

00526     try {
00527         ipiv = new int[mm_rank];
00528     } catch (std::bad_alloc &memory_allocation_exception) {
00529         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00530             std::endl;
00531         std::cerr << memory_allocation_exception.what() << std::endl;
00532     }
00533     memset(ipiv, 0, sizeof(ipiv[0])*mm_rank);
00534
00535     int ldbb = mm_rank;
00536     int mm_ld = mm_rank;
00537
00538     mm.OrderColMajor();
00539
00540     #ifdef MTK_PRECISION_DOUBLE
00541     dgesv_(&mm_rank, &nrhs, mm.data(), &mm_ld, ipiv,
00542         rhs.discrete_field(), &ldbb, &info);
00543     #else
00544     fgesv_(&mm_rank, &nrhs, mm.data(), &mm_ld, ipiv,
00545         rhs.discrete_field(), &ldbb, &info);
00546     #endif
00547
00548     mm.OrderRowMajor();
00549
00550     delete [] ipiv;
00551
00552     return info;
00553 }
00554
00555 int mtk::LAPACKAdapter::SolveDenseSystem(
    mtk::DenseMatrix &mm,
00556                                     mtk::UniStgGrid2D &rhs) {
00557
00558     int nrhs{1}; // Number of right-hand sides.
00559
00560     int *ipiv{}; // Array for pivoting information.
00561     int info{}; // Status of the solution.
00562     int mm_rank{mm.num_rows()}; // Rank of the matrix.
00563
00564     try {
00565         ipiv = new int[mm_rank];
00566     } catch (std::bad_alloc &memory_allocation_exception) {
00567         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00568             std::endl;
00569         std::cerr << memory_allocation_exception.what() << std::endl;
00570     }
00571     memset(ipiv, 0, sizeof(ipiv[0])*mm_rank);
00572
00573     int ldbb = mm_rank;
00574     int mm_ld = mm_rank;
00575
00576     mm.OrderColMajor();
00577
00578     #ifdef MTK_PRECISION_DOUBLE
00579     dgesv_(&mm_rank, &nrhs, mm.data(), &mm_ld, ipiv,
00580         rhs.discrete_field(), &ldbb, &info);
00581     #else
00582     fgesv_(&mm_rank, &nrhs, mm.data(), &mm_ld, ipiv,
00583         rhs.discrete_field(), &ldbb, &info);
00584     #endif
00585
00586     mm.OrderRowMajor();
00587
00588     delete [] ipiv;
00589
00590     return info;
00591 }
00592
00593 mtk::DenseMatrix mtk::LAPACKAdapter::QRFactorDenseMatrix
    (mtk::DenseMatrix &aa) {
00594
00595     mtk::Real *work{}; // Working array.
00596     mtk::Real *tau{}; // Array for the Householder scalars.
00597
00598     // Prepare to factorize: allocate and inquire for the value of lwork.
00599     try {
00600         work = new mtk::Real[1];
00601     } catch (std::bad_alloc &memory_allocation_exception) {
00602         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00603             std::endl;
00604         std::cerr << memory_allocation_exception.what() << std::endl;

```

```

00605     }
00606     memset(work, mtk::kZero, sizeof(aa.data()[0])*1);
00607
00608     int lwork{-1};
00609     int info{};
00610
00611     int aa_num_cols = aa.num_cols();
00612     int aaT_num_rows = aa.num_cols();
00613     int aaT_num_cols = aa.num_rows();
00614
00615     #if MTK_VERBOSE_LEVEL > 12
00616     std::cout << "Input matrix BEFORE QR factorization:" << std::endl;
00617     std::cout << aa << std::endl;
00618     #endif
00619
00620     #ifdef MTK_PRECISION_DOUBLE
00621     dgeqrf_(&aaT_num_rows, &aaT_num_cols, aa.data(), &aaT_num_rows,
00622            tau,
00623            work, &lwork, &info);
00624     #else
00625     fgeqrf_(&aaT_num_rows, &aaT_num_cols, aa.data(), &aaT_num_rows,
00626            tau,
00627            work, &lwork, &info);
00628     #endif
00629
00630     if (info == 0) {
00631         lwork = (int) work[0];
00632     } else {
00633         std::cerr << "Could not get value for lwork on line " << __LINE__ - 5 <<
00634             std::endl;
00635         std::cerr << "Exiting..." << std::endl;
00636     }
00637
00638     #if MTK_VERBOSE_LEVEL > 10
00639     std::cout << "lwork = " << std::endl << std::setw(12) << lwork << std::endl
00640         << std::endl;
00641     #endif
00642
00643     delete [] work;
00644     work = nullptr;
00645
00646     // Once we know lwork, we can actually invoke the factorization:
00647     try {
00648         work = new mtk::Real [lwork];
00649     } catch (std::bad_alloc &memory_allocation_exception) {
00650         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00651             std::endl;
00652         std::cerr << memory_allocation_exception.what() << std::endl;
00653     }
00654     memset(work, mtk::kZero, sizeof(work[0])*lwork);
00655
00656     int ltau = std::min(aaT_num_rows, aaT_num_cols);
00657
00658     try {
00659         tau = new mtk::Real [ltau];
00660     } catch (std::bad_alloc &memory_allocation_exception) {
00661         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00662             std::endl;
00663         std::cerr << memory_allocation_exception.what() << std::endl;
00664     }
00665     memset(tau, mtk::kZero, sizeof(0.0)*ltau);
00666
00667     #ifdef MTK_PRECISION_DOUBLE
00668     dgeqrf_(&aaT_num_rows, &aaT_num_cols, aa.data(), &aaT_num_rows,
00669            tau, work, &lwork, &info);
00670     #else
00671     fgeqrf_(&aaT_num_rows, &aaT_num_cols, aa.data(), &aaT_num_rows,
00672            tau, work, &lwork, &info);
00673     #endif
00674
00675     #ifdef MTK_PERFORM_PREVENTIONS
00676     if (!info) {
00677         std::cout << "QR factorization completed!" << std::endl << std::endl;
00678     } else {
00679         std::cerr << "Error solving system! info = " << info << std::endl;
00680         std::cerr << "Exiting..." << std::endl;
00681     }
00682     #endif
00683
00684     #if MTK_VERBOSE_LEVEL > 12
00685     std::cout << "Input matrix AFTER QR factorization:" << std::endl;

```

```

00686     std::cout << aa << std::endl;
00687     #endif
00688
00689     // We now generate the real matrix Q with orthonormal columns. This has to
00690     // be done separately since the actual output of dgegrf_ (AA_) represents
00691     // the orthogonal matrix Q as a product of min(aa_num_rows,aa_num_cols)
00692     // elementary Householder reflectors. Notice that we must re-inquire the new
00693     // value for lwork that is used.
00694
00695     bool padded{false};
00696
00697     bool transpose{false};
00698
00699     mtk::DenseMatrix QQ_(aa.num_cols(),padded,transpose);
00700
00701     #if MTK_VERBOSE_LEVEL > 12
00702     std::cout << "Initialized QQ_T: " << std::endl;
00703     std::cout << QQ_ << std::endl;
00704     #endif
00705
00706     // Assemble the QQ_ matrix:
00707     lwork = -1;
00708
00709     delete[] work;
00710     work = nullptr;
00711
00712     try {
00713         work = new mtk::Real[lwork];
00714     } catch (std::bad_alloc &memory_allocation_exception) {
00715         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00716             std::endl;
00717         std::cerr << memory_allocation_exception.what() <<
00718             std::endl;
00719     }
00720     memset(work, mtk::kZero, sizeof(work[0])*lwork);
00721
00722     char side_{'L'};
00723     char trans_{'N'};
00724
00725     int aux = QQ_.num_rows();
00726
00727     #ifdef MTK_PRECISION_DOUBLE
00728     dormqr_(&side_, &trans_,
00729         &aa_num_cols, &aa_num_cols, &ltau, aa.data(), &aaT_num_rows, tau,
00730         QQ_.data(), &aux, work, &lwork, &info);
00731     #else
00732     formqr_(&side_, &trans_,
00733         &aa_num_cols, &aa_num_cols, &ltau, aa.data(), &aaT_num_rows, tau,
00734         QQ_.data(), &aux, work, &lwork, &info);
00735     #endif
00736
00737     if (info == 0) {
00738         lwork = (int) work[0];
00739     } else {
00740         std::cerr << "Could not get lwork on line " << __LINE__ - 5 << std::endl;
00741         std::cerr << "Exiting..." << std::endl;
00742     }
00743
00744     #if MTK_VERBOSE_LEVEL > 10
00745     std::cout << "lwork = " << std::endl << std::setw(12) << lwork <<
00746         std::endl << std::endl;
00747     #endif
00748
00749     delete[] work;
00750     work = nullptr;
00751
00752     try {
00753         work = new mtk::Real[lwork];
00754     } catch (std::bad_alloc &memory_allocation_exception) {
00755         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00756             std::endl;
00757         std::cerr << memory_allocation_exception.what() << std::endl;
00758     }
00759     memset(work, mtk::kZero, sizeof(work[0])*lwork);
00760
00761     #ifdef MTK_PRECISION_DOUBLE
00762     dormqr_(&side_, &trans_,
00763         &aa_num_cols, &aa_num_cols, &ltau, aa.data(), &aaT_num_rows, tau,
00764         QQ_.data(), &aux, work, &lwork, &info);
00765     #else
00766     formqr_(&side_, &trans_,

```

```

00767         &aa_num_cols, &aa_num_cols, &lttau, aa.data(), &aaT_num_rows, tau,
00768         QQ_.data(), &aux, work, &lwork, &info);
00769     #endif
00770
00771     #ifdef MTK_PERFORM_PREVENTIONS
00772     if (!info) {
00773         std::cout << "Q matrix successfully assembled!" << std::endl << std::endl;
00774     } else {
00775         std::cerr << "Something went wrong solving system! info = " << info <<
00776         std::endl;
00777         std::cerr << "Exiting..." << std::endl;
00778     }
00779     #endif
00780
00781     delete[] work;
00782     work = nullptr;
00783
00784     delete[] tau;
00785     tau = nullptr;
00786
00787     return QQ_;
00788 }
00789
00790 int mtk::LAPACKAdapter::SolveRectangularDenseSystem(const
mtk::DenseMatrix &aa,
00791
00792         mtk::Real *ob_,
00793         int ob_ld_) {
00794
00795     // We first invoke the solver to query for the value of lwork. For this,
00796     // we must at least allocate enough space to allow access to WORK(1), or
00797     // work[0]:
00798
00799     // If LWORK = -1, then a workspace query is assumed; the routine only
00800     // calculates the optimal size of the WORK array, returns this value as
00801     // the first entry of the WORK array, and no error message related to
00802     // LWORK is issued by XERBLA.
00803
00804     mtk::Real *work{}; // Work array.
00805
00806     try {
00807         work = new mtk::Real[1];
00808     } catch (std::bad_alloc &memory_allocation_exception) {
00809         std::cerr << "Memory allocation exception on line " << __LINE__ - 3 <<
00810         std::endl;
00811         std::cerr << memory_allocation_exception.what() << std::endl;
00812     }
00813
00814     memset(work, mtk::kZero, sizeof(work[0])*1);
00815
00816     char trans_{'N'};
00817     int nrhs_{1};
00818     int info{0};
00819     int lwork{-1};
00820
00821     int AA_num_rows_ = aa.num_cols();
00822     int AA_num_cols_ = aa.num_rows();
00823     int AA_ld_ = std::max(1, aa.num_cols());
00824
00825     #ifdef MTK_PRECISION_DOUBLE
00826     dgels_(&trans_, &AA_num_rows_, &AA_num_cols_, &nrhs_, aa.data(), &AA_ld_,
00827         ob_, &ob_ld_,
00828         work, &lwork, &info);
00829     #else
00830     sgels_(&trans_, &AA_num_rows_, &AA_num_cols_, &nrhs_, aa.data(), &AA_ld_,
00831         ob_, &ob_ld_,
00832         work, &lwork, &info);
00833     #endif
00834
00835     if (info == 0) {
00836         lwork = (int) work[0];
00837     } else {
00838         std::cerr << "Could not get value for lwork on line " << __LINE__ - 2 <<
00839         std::endl;
00840         std::cerr << "Exiting..." << std::endl;
00841         return info;
00842     }
00843
00844     #if MTK_VERBOSE_LEVEL > 10
00845     std::cout << "lwork = " << std::endl << std::setw(12)<< lwork <<
00846     std::endl << std::endl;
00847     #endif

```

```

00847 // We then use lwork's new value to create the work array:
00848 delete[] work;
00849 work = nullptr;
00850
00851 try {
00852     work = new mtk::Real[lwork];
00853 } catch (std::bad_alloc &memory_allocation_exception) {
00854     std::cerr << "Memory allocation exception on line " << __LINE__ - 3 << std::endl;
00855     std::cerr << memory_allocation_exception.what() << std::endl;
00856 }
00857 memset(work, 0.0, sizeof(work[0])*lwork);
00858
00859 // We now invoke the solver again:
00860 #ifdef MTK_PRECISION_DOUBLE
00861 dgels_(&trans_, &AA_num_rows_, &AA_num_cols_, &nrhs_, aa.data(), &AA_ld_,
00862        ob_, &ob_ld_,
00863        work, &lwork, &info);
00864 #else
00865 sgels_(&trans_, &AA_num_rows_, &AA_num_cols_, &nrhs_, aa.data(), &AA_ld_,
00866        ob_, &ob_ld_,
00867        work, &lwork, &info);
00868 #endif
00869
00870 delete [] work;
00871 work = nullptr;
00872
00873 return info;
00874 }

```

17.101 src/mtk_matrix.cc File Reference


Implementing the representation of a matrix in the MTK.

```

#include <cstdlib>
#include <cstdio>
#include <cstring>
#include <cmath>
#include <iomanip>
#include <iostream>
#include "mtk_tools.h"
#include "mtk_matrix.h"

```

Include dependency graph for mtk_matrix.cc:



17.101.1 Detailed Description

Implementation of the representation for the matrices implemented in the MTK.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_matrix.cc](#).

17.102 mtk_matrix.cc

```

00001
00010 /*
00011 Copyright (C) 2015, Computational Science Research Center, San Diego State
00012 University. All rights reserved.
00013
00014 Redistribution and use in source and binary forms, with or without modification,
00015 are permitted provided that the following conditions are met:
00016
00017 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00018 and a copy of the modified files should be reported once modifications are
00019 completed, unless these modifications are made through the project's GitHub
00020 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00021 should be developed and included in any deliverable.
00022
00023 2. Redistributions of source code must be done through direct
00024 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00025
00026 3. Redistributions in binary form must reproduce the above copyright notice,
00027 this list of conditions and the following disclaimer in the documentation and/or
00028 other materials provided with the distribution.
00029
00030 4. Usage of the binary form on proprietary applications shall require explicit
00031 prior written permission from the the copyright holders, and due credit should
00032 be given to the copyright holders.
00033
00034 5. Neither the name of the copyright holder nor the names of its contributors
00035 may be used to endorse or promote products derived from this software without
00036 specific prior written permission.
00037
00038 The copyright holders provide no reassurances that the source code provided does
00039 not infringe any patent, copyright, or any other intellectual property rights of
00040 third parties. The copyright holders disclaim any liability to any recipient for
00041 claims brought against recipient by any third party for infringement of that
00042 parties intellectual property rights.
00043
00044 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00045 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00046 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00047 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00048 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00049 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00050 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00051 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00052 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00053 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00054 */
00055
00056 #include <cstdlib>
00057 #include <cstdio>
00058 #include <cstring>
00059 #include <cmath>
00060
00061 #include <iomanip>
00062 #include <iostream>
00063
00064 #include "mtk_tools.h"
00065 #include "mtk_matrix.h"
00066
00067 mtk::Matrix::Matrix():
00068     storage_(mtk::DENSE),
00069     ordering_(mtk::ROW_MAJOR),
00070     num_rows_(),
00071     num_cols_(),
00072     num_values_(),
00073     ld_(),
00074     num_zero_(),
00075     num_non_zero_(),
00076     num_null_(),

```

```

00077     num_non_null_(),
00078     kl_(),
00079     ku_(),
00080     bandwidth_(),
00081     abs_density_(),
00082     rel_density_(),
00083     abs_sparsity_(),
00084     rel_sparsity_() {}
00085
00086 mtk::Matrix::Matrix(const Matrix &in):
00087     storage_(in.storage_),
00088     ordering_(in.ordering_),
00089     num_rows_(in.num_rows_),
00090     num_cols_(in.num_cols_),
00091     num_values_(in.num_values_),
00092     ld_(in.ld_),
00093     num_zero_(in.num_zero_),
00094     num_non_zero_(in.num_non_zero_),
00095     num_null_(in.num_null_),
00096     num_non_null_(in.num_non_null_),
00097     kl_(in.kl_),
00098     ku_(in.ku_),
00099     bandwidth_(in.bandwidth_),
00100     abs_density_(in.abs_density_),
00101     rel_density_(in.rel_density_),
00102     abs_sparsity_(in.abs_sparsity_),
00103     rel_sparsity_(in.rel_sparsity_) {}
00104
00105 mtk::Matrix::~Matrix() noexcept {}
00106
00107 mtk::MatrixStorage mtk::Matrix::storage() const noexcept {
00108
00109     return storage_;
00110 }
00111
00112 mtk::MatrixOrdering mtk::Matrix::ordering() const noexcept {
00113
00114     return ordering_;
00115 }
00116
00117 int mtk::Matrix::num_rows() const noexcept {
00118
00119     return num_rows_;
00120 }
00121
00122 int mtk::Matrix::num_cols() const noexcept {
00123
00124     return num_cols_;
00125 }
00126
00127 int mtk::Matrix::num_values() const noexcept {
00128
00129     return num_values_;
00130 }
00131
00132 int mtk::Matrix::ld() const noexcept {
00133
00134     return ld_;
00135 }
00136
00137 int mtk::Matrix::num_zero() const noexcept {
00138
00139     return num_zero_;
00140 }
00141
00142 int mtk::Matrix::num_non_zero() const noexcept {
00143
00144     return num_non_zero_;
00145 }
00146
00147 int mtk::Matrix::num_null() const noexcept {
00148
00149     return num_null_;
00150 }
00151
00152 int mtk::Matrix::num_non_null() const noexcept {
00153
00154     return num_non_null_;
00155 }
00156
00157 int mtk::Matrix::kl() const noexcept {

```

```

00158
00159     return kl_;
00160 }
00161
00162 int mtk::Matrix::ku() const noexcept {
00163
00164     return ku_;
00165 }
00166
00167 int mtk::Matrix::bandwidth() const noexcept {
00168
00169     return bandwidth_;
00170 }
00171
00172 mtk::Real mtk::Matrix::rel_density() const noexcept {
00173
00174     return rel_density_;
00175 }
00176
00177 mtk::Real mtk::Matrix::abs_sparsity() const noexcept {
00178
00179     return abs_sparsity_;
00180 }
00181
00182 mtk::Real mtk::Matrix::rel_sparsity() const noexcept {
00183
00184     return rel_sparsity_;
00185 }
00186
00187 void mtk::Matrix::set_storage(const mtk::MatrixStorage &ss)
noexcept {
00188
00189     #ifdef MTK_PERFORM_PREVENTIONS
00190     mtk::Tools::Prevent(!(ss == mtk::DENSE ||
00191                          ss == mtk::BANDED ||
00192                          ss == mtk::CRS),
00193                        __FILE__, __LINE__, __func__);
00194     #endif
00195     storage_ = ss;
00196 }
00197
00198
00199 void mtk::Matrix::set_ordering(const
mtk::MatrixOrdering &oo) noexcept {
00200
00201     #ifdef MTK_PERFORM_PREVENTIONS
00202     mtk::Tools::Prevent(!(oo == mtk::ROW_MAJOR || oo ==
mtk::COL_MAJOR),
00203                        __FILE__, __LINE__, __func__);
00204     #endif
00205     ordering_ = oo;
00206
00207     ld_ = (ordering_ == mtk::ROW_MAJOR)?
std::max(1,num_cols_): std::max(1,num_rows_);
00210 }
00211
00212 void mtk::Matrix::set_num_rows(const int &in) noexcept {
00213
00214     #ifdef MTK_PERFORM_PREVENTIONS
00215     mtk::Tools::Prevent(in < 1, __FILE__, __LINE__, __func__);
00216     #endif
00217     num_rows_ = in;
00218     num_values_ = num_rows_*num_cols_;
00219     ld_ = (ordering_ == mtk::ROW_MAJOR)?
std::max(1,num_cols_): std::max(1,num_rows_);
00222 }
00223
00224 void mtk::Matrix::set_num_cols(const int &in) noexcept {
00225
00226     #ifdef MTK_PERFORM_PREVENTIONS
00227     mtk::Tools::Prevent(in < 1, __FILE__, __LINE__, __func__);
00228     #endif
00229     num_cols_ = in;
00230     num_values_ = num_rows_*num_cols_;
00231     ld_ = (ordering_ == mtk::ROW_MAJOR)?
std::max(1,num_cols_): std::max(1,num_rows_);
00233 }
00234
00235

```

```

00236 void mtk::Matrix::set_num_zero(const int &in) noexcept {
00237
00238     #ifdef MTK_PERFORM_PREVENTIONS
00239     mtk::Tools::Prevent(in < 0, __FILE__, __LINE__, __func__);
00240     #endif
00241
00242     num_zero_ = in;
00243     num_non_zero_ = num_values_ - num_zero_;
00244
00246     rel_density_ = (mtk::Real) num_non_zero_/num_values_;
00247     rel_sparsity_ = 1.0 - rel_density_;
00248 }
00249
00250 void mtk::Matrix::set_num_null(const int &in) noexcept {
00251
00252     #ifdef MTK_PERFORM_PREVENTIONS
00253     mtk::Tools::Prevent(in < 0, __FILE__, __LINE__, __func__);
00254     #endif
00255
00256     num_null_ = in;
00257     num_non_null_ = num_values_ - num_null_;
00258
00260     abs_density_ = (mtk::Real) num_non_null_/num_values_;
00261     abs_sparsity_ = 1.0 - abs_density_;
00262 }
00263
00264 void mtk::Matrix::IncreaseNumZero() noexcept {
00265
00267     num_zero_++;
00268     num_non_zero_ = num_values_ - num_zero_;
00270     rel_density_ = (mtk::Real) num_non_zero_/num_values_;
00271     rel_sparsity_ = 1.0 - rel_density_;
00272 }
00273
00274 void mtk::Matrix::IncreaseNumNull() noexcept {
00275
00277     num_null_++;
00278     num_non_null_ = num_values_ - num_null_;
00280     abs_density_ = (mtk::Real) num_non_null_/num_values_;
00281     abs_sparsity_ = 1.0 - abs_density_;
00282 }

```

17.103 src/mtk_robin_bc_descriptor_1d.cc File Reference


Impose Robin boundary conditions on the operators and on the grids.

```

#include "mtk_tools.h"
#include "mtk_grad_1d.h"
#include "mtk_robin_bc_descriptor_1d.h"

```

Include dependency graph for mtk_robin_bc_descriptor_1d.cc:



17.103.1 Detailed Description

This class presents an interface for the user to specify Robin boundary conditions on 1D mimetic operators and the grids they are acting on.

Def. Let $u(\mathbf{x}, t) : \Omega \times [t_0, t_n] \mapsto \mathbb{R}$ be the solution to an ordinary or partial differential equation of interest. We say that u satisfies a **Robin boundary condition** on $\partial\Omega$ if and only if there exists $\beta(\mathbf{x}, t) : \Omega \times [t_0, t_n] \mapsto \mathbb{R}$ so that:

$$\forall t \in [t_0, t_n] \forall \mathbf{x} \in \partial\Omega : \delta(\mathbf{x}, t)u(\mathbf{x}, t) + \eta(\mathbf{x}, t)(\hat{\mathbf{n}} \cdot \nabla u) = \beta(\mathbf{x}, t).$$

Intuitively, a **Robin boundary condition** is a constraint that must be satisfied by any linear combination of any scalar field u and its first normal derivative, in order for u to represent a unique solution to a given ordinary or partial differential equation of interest.

In a 1D context ($\partial\Omega = \{a, b\} \subset \mathbb{R}$), this condition can be written as follows:

$$\delta_a(a, t)u(a, t) - \eta_a(a, t)u'(a, t) = \beta_a(a, t),$$

$$\delta_b(b, t)u(b, t) + \eta_b(b, t)u'(b, t) = \beta_b(b, t).$$

Instances of this class receive information about the coefficient functions and each condition for any subset of the boundary (west and east, in 1D). These instances then handle the complexity of placing the coefficients in the differentiation matrices and the condition in the grids.

See also

<http://mathworld.wolfram.com/NormalVector.html>

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_robin_bc_descriptor_1d.cc](#).

17.104 mtk_robin_bc_descriptor_1d.cc

```

00001
00043 /*
00044 Copyright (C) 2015, Computational Science Research Center, San Diego State
00045 University. All rights reserved.
00046
00047 Redistribution and use in source and binary forms, with or without modification,
00048 are permitted provided that the following conditions are met:
00049
00050 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00051 and a copy of the modified files should be reported once modifications are
00052 completed, unless these modifications are made through the project's GitHub
00053 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00054 should be developed and included in any deliverable.
00055
00056 2. Redistributions of source code must be done through direct
00057 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00058
00059 3. Redistributions in binary form must reproduce the above copyright notice,
00060 this list of conditions and the following disclaimer in the documentation and/or
00061 other materials provided with the distribution.
00062
00063 4. Usage of the binary form on proprietary applications shall require explicit
00064 prior written permission from the the copyright holders, and due credit should
00065 be given to the copyright holders.
00066
00067 5. Neither the name of the copyright holder nor the names of its contributors
00068 may be used to endorse or promote products derived from this software without
00069 specific prior written permission.
00070
00071 The copyright holders provide no reassurances that the source code provided does
00072 not infringe any patent, copyright, or any other intellectual property rights of
00073 third parties. The copyright holders disclaim any liability to any recipient for
00074 claims brought against recipient by any third party for infringement of that
00075 parties intellectual property rights.
00076
00077 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00078 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00079 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00080 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00081 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00082 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00083 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00084 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00085 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00086 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00087 */
00088
00089 #include "mtk_tools.h"
00090 #include "mtk_grad_1d.h"
00091 #include "mtk_robin_bc_descriptor_1d.h"
00092
00093 mtk::RobinBCDescriptor1D::RobinBCDescriptor1D() :
00094     highest_order_diff_west_(-1),
00095     highest_order_diff_east_(-1),
00096     west_condition_(nullptr),
00097     east_condition_(nullptr) {}
00098
00099 mtk::RobinBCDescriptor1D::RobinBCDescriptor1D(
00100     const mtk::RobinBCDescriptor1D &desc) :
00101     highest_order_diff_west_(desc.highest_order_diff_west_),
00102     highest_order_diff_east_(desc.highest_order_diff_east_),
00103     west_condition_(desc.west_condition_),
00104     east_condition_(desc.east_condition_) {}
00105
00106 mtk::RobinBCDescriptor1D::~~RobinBCDescriptor1D() noexcept {}
00107
00108 int mtk::RobinBCDescriptor1D::highest_order_diff_west()
00109     const noexcept {
00110     return highest_order_diff_west_;
00111 }
00112
00113 int mtk::RobinBCDescriptor1D::highest_order_diff_east()
00114     const noexcept {
00115     return highest_order_diff_east_;
00116 }
00117

```

```

00118 void mtk::RobinBCDescriptor1D::PushBackWestCoeff(
00119     mtk::CoefficientFunction0D cw) {
00120
00121     #ifdef MTK_PERFORM_PREVENTIONS
00122     mtk::Tools::Prevent(cw == nullptr, __FILE__, __LINE__, __func__);
00123     mtk::Tools::Prevent(highest_order_diff_west_ > 1,
00124         __FILE__, __LINE__, __func__);
00125     #endif
00126
00127     west_coefficients_.push_back(cw);
00128
00129     highest_order_diff_west_++;
00130 }
00131
00132 void mtk::RobinBCDescriptor1D::PushBackEastCoeff(
00133     mtk::CoefficientFunction0D ce) {
00134
00135     #ifdef MTK_PERFORM_PREVENTIONS
00136     mtk::Tools::Prevent(ce == nullptr, __FILE__, __LINE__, __func__);
00137     mtk::Tools::Prevent(highest_order_diff_east_ > 1,
00138         __FILE__, __LINE__, __func__);
00139     #endif
00140
00141     east_coefficients_.push_back(ce);
00142
00143     highest_order_diff_east_++;
00144 }
00145
00146 void mtk::RobinBCDescriptor1D::set_west_condition(
00147     mtk::Real (*west_condition)(const mtk::Real &tt)) noexcept {
00148
00149     #ifdef MTK_PERFORM_PREVENTIONS
00150     mtk::Tools::Prevent(west_condition == nullptr, __FILE__, __LINE__, __func__);
00151     #endif
00152
00153     west_condition_ = west_condition;
00154 }
00155
00156 void mtk::RobinBCDescriptor1D::set_east_condition(
00157     mtk::Real (*east_condition)(const mtk::Real &tt)) noexcept {
00158
00159     #ifdef MTK_PERFORM_PREVENTIONS
00160     mtk::Tools::Prevent(east_condition == nullptr, __FILE__, __LINE__, __func__);
00161     #endif
00162
00163     east_condition_ = east_condition;
00164 }
00165
00166 bool mtk::RobinBCDescriptor1D::ImposeOnLaplacianMatrix(
00167     const mtk::Lap1D &lap,
00168     mtk::DenseMatrix &matrix,
00169     const mtk::Real &time) const {
00170
00171     #ifdef MTK_PERFORM_PREVENTIONS
00172     mtk::Tools::Prevent(highest_order_diff_west_ == -1,
00173         __FILE__, __LINE__, __func__);
00174     mtk::Tools::Prevent(highest_order_diff_east_ == -1,
00175         __FILE__, __LINE__, __func__);
00176     mtk::Tools::Prevent(matrix.num_rows() == 0, __FILE__, __LINE__, __func__);
00177     mtk::Tools::Prevent(matrix.num_cols() == 0, __FILE__, __LINE__, __func__);
00178     #endif
00179
00182     matrix.SetValue(0, 0, (west_coefficients_[0])(time));
00183
00185     matrix.SetValue(matrix.num_rows() - 1,
00186         matrix.num_cols() - 1,
00187         (east_coefficients_[0])(time));
00188
00190     if (highest_order_diff_west_ > 0) {
00191
00193         mtk::Grad1D grad;
00194         if (!grad.ConstructGrad1D(lap.order_accuracy(),
00195             lap.mimetic_threshold())) {
00196             return false;
00197         }
00198
00200         mtk::DenseMatrix coeffs(grad.mim_bndy());
00201
00205         mtk::Real idx = mtk::kOne/lap.delta();
00206
00207

```

```

00209     for (int ii = 0; ii < coeffs.num_cols(); ++ii) {
00211         mtk::Real aux{idx*coeffs.GetValue(0, ii)};
00214         mtk::Real unit_normal{-mtk::kOne};
00215         aux *= unit_normal*(west_coefficients_[1])(time);
00217         matrix.SetValue(0, ii, matrix.GetValue(0, ii) + aux);
00218     }
00219
00221
00226
00227     for (int ii = 0; ii < coeffs.num_cols(); ++ii) {
00229         mtk::Real aux{idx*coeffs.GetValue(0, ii)};
00233         mtk::Real unit_normal{mtk::kOne};
00234         aux *= -unit_normal*(east_coefficients_[1])(time);
00236         matrix.SetValue(matrix.num_rows() - 1,
00237             matrix.num_rows() - 1 - ii,
00238             matrix.GetValue(matrix.num_rows() - 1,
00239                 matrix.num_rows() - 1 - ii) + aux);
00240     }
00241 }
00242
00243 return true;
00244 }
00245
00246 void mtk::RobinBCDescriptor1D::ImposeOnGrid(
00247     UniStgGrid1D &grid,
00248     const mtk::Real &time) const {
00249
00250     #ifdef MTK_PERFORM_PREVENTIONS
00251     mtk::Tools::Prevent(grid.num_cells_x() == 0, __FILE__, __LINE__, __func__);
00252     mtk::Tools::Prevent(west_condition_ == nullptr, __FILE__, __LINE__, __func__);
00253     mtk::Tools::Prevent(east_condition_ == nullptr, __FILE__, __LINE__, __func__);
00254     #endif
00255
00256     (grid.discrete_field())[0] = west_condition_(time);
00257     (grid.discrete_field())[grid.num_cells_x() + 1] = east_condition_(time);
00258 }

```

17.105 src/mtk_robin_bc_descriptor_2d.cc File Reference


Impose Robin boundary conditions on the operators and on the grids.

```

#include "mtk_tools.h"
#include "mtk_robin_bc_descriptor_2d.h"

```


Include dependency graph for mtk_robin_bc_descriptor_2d.cc:



17.105.1 Detailed Description

This class presents an interface for the user to specify Robin boundary conditions on 2D mimetic operators and the grids they are acting on.

Def. Let $u(\mathbf{x}, t) : \Omega \times [t_0, t_n] \mapsto \mathbb{R}$ be the solution to an ordinary or partial differential equation of interest. We say that u satisfies a **Robin boundary condition** on $\partial\Omega$ if and only if there exists $\beta(\mathbf{x}, t) : \Omega \times [t_0, t_n] \mapsto \mathbb{R}$ so that:

$$\forall t \in [t_0, t_n] \forall \mathbf{x} \in \partial\Omega : \delta(\mathbf{x}, t)u(\mathbf{x}, t) + \eta(\mathbf{x}, t)(\hat{\mathbf{n}} \cdot \nabla u) = \beta(\mathbf{x}, t).$$

Intuitively, a **Robin boundary condition** is a constraint that must be satisfied by any linear combination of any scalar field u and its first normal derivative, in order for u to represent a unique solution to a given ordinary or partial differential equation of interest.

Instances of this class receive information about the coefficient functions and each condition for any subset of the boundary (west, east, south and north in 2D). These instances then handle the complexity of placing the coefficients in the differentiation matrices and the conditions in the grids.

See also

<http://mathworld.wolfram.com/NormalVector.html>

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_robin_bc_descriptor_2d.cc](#).

17.106 mtk_robin_bc_descriptor_2d.cc

```

00001
00034 /*
00035 Copyright (C) 2015, Computational Science Research Center, San Diego State
00036 University. All rights reserved.
00037
00038 Redistribution and use in source and binary forms, with or without modification,
00039 are permitted provided that the following conditions are met:
00040
00041 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00042 and a copy of the modified files should be reported once modifications are
00043 completed, unless these modifications are made through the project's GitHub
00044 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00045 should be developed and included in any deliverable.
00046
00047 2. Redistributions of source code must be done through direct
00048 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00049
00050 3. Redistributions in binary form must reproduce the above copyright notice,
00051 this list of conditions and the following disclaimer in the documentation and/or
00052 other materials provided with the distribution.
00053
00054 4. Usage of the binary form on proprietary applications shall require explicit
00055 prior written permission from the the copyright holders, and due credit should
00056 be given to the copyright holders.
00057
00058 5. Neither the name of the copyright holder nor the names of its contributors
00059 may be used to endorse or promote products derived from this software without
00060 specific prior written permission.
00061
00062 The copyright holders provide no reassurances that the source code provided does
00063 not infringe any patent, copyright, or any other intellectual property rights of
00064 third parties. The copyright holders disclaim any liability to any recipient for
00065 claims brought against recipient by any third party for infringement of that
00066 parties intellectual property rights.
00067
00068 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00069 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00070 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00071 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00072 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00073 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00074 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00075 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00076 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00077 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00078 */
00079
00080 #include "mtk_tools.h"
00081
00082 #include "mtk_robin_bc_descriptor_2d.h"
00083
00084 mtk::RobinBCDescriptor2D::RobinBCDescriptor2D() :
00085     highest_order_diff_west_(-1),
00086     highest_order_diff_east_(-1),
00087     highest_order_diff_south_(-1),
00088     highest_order_diff_north_(-1),
00089     west_condition_(),
00090     east_condition_(),
00091     south_condition_(),
00092     north_condition_() {}
00093
00094 mtk::RobinBCDescriptor2D::RobinBCDescriptor2D(
00095     const mtk::RobinBCDescriptor2D &desc):
00096     highest_order_diff_west_(desc.highest_order_diff_west_),
00097     highest_order_diff_east_(desc.highest_order_diff_east_),
00098     highest_order_diff_south_(desc.highest_order_diff_south_),
00099     highest_order_diff_north_(desc.highest_order_diff_north_),
00100     west_condition_(desc.west_condition_),
00101     east_condition_(desc.east_condition_),
00102     south_condition_(desc.south_condition_),
00103     north_condition_(desc.north_condition_) {}
00104
00105 mtk::RobinBCDescriptor2D::~~RobinBCDescriptor2D() noexcept {}
00106
00107 int mtk::RobinBCDescriptor2D::highest_order_diff_west()
00108     const noexcept {
00109     return highest_order_diff_west_;

```

```

00110 }
00111
00112 int mtk::RobinBCDescriptor2D::highest_order_diff_east()
    const noexcept {
00113
00114     return highest_order_diff_east_;
00115 }
00116
00117 int mtk::RobinBCDescriptor2D::highest_order_diff_south()
    const noexcept {
00118
00119     return highest_order_diff_south_;
00120 }
00121
00122 int mtk::RobinBCDescriptor2D::highest_order_diff_north()
    const noexcept {
00123
00124     return highest_order_diff_north_;
00125 }
00126
00127 void mtk::RobinBCDescriptor2D::PushBackWestCoeff(
    mtk::CoefficientFunction1D cw) {
00128
00129     #ifdef MTK_PERFORM_PREVENTIONS
00130     mtk::Tools::Prevent(cw == nullptr, __FILE__, __LINE__, __func__);
00131     mtk::Tools::Prevent(highest_order_diff_west_ > 1,
00132                         __FILE__, __LINE__, __func__);
00133     #endif
00134
00135     west_coefficients_.push_back(cw);
00136     highest_order_diff_west_++;
00137 }
00138
00141 void mtk::RobinBCDescriptor2D::PushBackEastCoeff(
    mtk::CoefficientFunction1D ce) {
00142
00143     #ifdef MTK_PERFORM_PREVENTIONS
00144     mtk::Tools::Prevent(ce == nullptr, __FILE__, __LINE__, __func__);
00145     mtk::Tools::Prevent(highest_order_diff_east_ > 1,
00146                         __FILE__, __LINE__, __func__);
00147     #endif
00148
00149     east_coefficients_.push_back(ce);
00150     highest_order_diff_east_++;
00151 }
00152
00155 void mtk::RobinBCDescriptor2D::PushBackSouthCoeff(
    mtk::CoefficientFunction1D cs) {
00156
00157     #ifdef MTK_PERFORM_PREVENTIONS
00158     mtk::Tools::Prevent(cs == nullptr, __FILE__, __LINE__, __func__);
00159     mtk::Tools::Prevent(highest_order_diff_south_ > 1,
00160                         __FILE__, __LINE__, __func__);
00161     #endif
00162
00163     south_coefficients_.push_back(cs);
00164     highest_order_diff_south_++;
00165 }
00166
00169 void mtk::RobinBCDescriptor2D::PushBackNorthCoeff(
    mtk::CoefficientFunction1D cn) {
00170
00171     #ifdef MTK_PERFORM_PREVENTIONS
00172     mtk::Tools::Prevent(cn == nullptr, __FILE__, __LINE__, __func__);
00173     mtk::Tools::Prevent(highest_order_diff_north_ > 1,
00174                         __FILE__, __LINE__, __func__);
00175     #endif
00176
00177     north_coefficients_.push_back(cn);
00178     highest_order_diff_north_++;
00179 }
00180
00183 void mtk::RobinBCDescriptor2D::set_west_condition(
    mtk::Real (*west_condition)(const mtk::Real &yy,
                                const mtk::Real &tt)) noexcept {
00184
00185     #ifdef MTK_PERFORM_PREVENTIONS

```

```

00188     mtk::Tools::Prevent(west_condition == nullptr, __FILE__, __LINE__, __func__);
00189 #endif
00190
00191     west_condition_ = west_condition;
00192 }
00193
00194 void mtk::RobinBCDescriptor2D::set_east_condition(
00195     mtk::Real (*east_condition)(const mtk::Real &yy,
00196                                 const mtk::Real &tt)) noexcept {
00197
00198     #ifdef MTK_PERFORM_PREVENTIONS
00199     mtk::Tools::Prevent(east_condition == nullptr, __FILE__, __LINE__, __func__);
00200     #endif
00201
00202     east_condition_ = east_condition;
00203 }
00204
00205 void mtk::RobinBCDescriptor2D::set_south_condition(
00206     mtk::Real (*south_condition)(const mtk::Real &xx,
00207                                 const mtk::Real &tt)) noexcept {
00208
00209     #ifdef MTK_PERFORM_PREVENTIONS
00210     mtk::Tools::Prevent(south_condition == nullptr,
00211                         __FILE__, __LINE__, __func__);
00212     #endif
00213
00214     south_condition_ = south_condition;
00215 }
00216
00217 void mtk::RobinBCDescriptor2D::set_north_condition(
00218     mtk::Real (*north_condition)(const mtk::Real &xx,
00219                                 const mtk::Real &tt)) noexcept {
00220
00221     #ifdef MTK_PERFORM_PREVENTIONS
00222     mtk::Tools::Prevent(north_condition == nullptr,
00223                         __FILE__, __LINE__, __func__);
00224     #endif
00225
00226     north_condition_ = north_condition;
00227 }
00228
00229 bool mtk::RobinBCDescriptor2D::ImposeOnSouthBoundaryNoSpace
00230 (
00231     const mtk::Lap2D &lap,
00232     const mtk::UniStgGrid2D &grid,
00233     mtk::DenseMatrix &matrix,
00234     const mtk::Real &time) const {
00235
00236     // For the south-west corner:
00237     auto cc = (south_coefficients_[0])(grid.west_bndy(), time);
00238
00239     #if MTK_VERBOSE_LEVEL > 2
00240     std::cout << "Matrix has " << matrix.num_rows() << " rows and " <<
00241         matrix.num_cols() << " columns." << std::endl;
00242     std::cout << "Setting at " << 0 << ' ' << 0 << std::endl;
00243     #endif
00244
00245     matrix.SetValue(0, 0, cc);
00246
00247     // Compute first centers per dimension.
00248     auto first_center_x = grid.west_bndy() + grid.delta_x()/
00249         mtk::kTwo;
00250
00251     // For each entry on the diagonal (south boundary):
00252     for (int ii = 0; ii < grid.num_cells_x(); ++ii) {
00253         // Evaluate next set spatial coordinates to evaluate the coefficient.
00254         mtk::Real xx = first_center_x + ii*grid.delta_x();
00255         // Evaluate and assign the Dirichlet coefficient.
00256         cc = (south_coefficients_[0])(xx, time);
00257
00258         #if MTK_VERBOSE_LEVEL > 2
00259         std::cout << "Setting at " << ii + 1 << ' ' << ii + 1 << std::endl;
00260         #endif
00261
00262         matrix.SetValue(ii + 1, ii + 1, cc);
00263     }
00264
00265     // For the south-east corner:
00266     cc = (south_coefficients_[0])(grid.east_bndy(), time);
00267

```

```

00268 #if MTK_VERBOSE_LEVEL > 2
00269 std::cout << "Setting at " << grid.num_cells_x() + 1 << ' ' <<
00270     grid.num_cells_x() + 1 << std::endl;
00271 #endif
00272
00273 matrix.SetValue(grid.num_cells_x() + 1, grid.num_cells_x() + 1, cc);
00274
00275 if (highest_order_diff_south_ > 0) {
00276
00277 }
00280
00281 return true;
00282 }
00283
00284 bool mtk::RobinBCDescriptor2D::ImposeOnSouthBoundaryWithSpace
(
00285     const mtk::Lap2D &lap,
00286     const mtk::UniStgGrid2D &grid,
00287     mtk::DenseMatrix &matrix,
00288     const mtk::Real &time) const {
00289
00290
00291
00292
00293 // For each entry on the diagonal:
00294 for (int ii = 0; ii < grid.num_cells_x() + 2; ++ii) {
00295     // Evaluate next set spatial coordinates to evaluate the coefficient.
00296     mtk::Real xx{(grid.discrete_domain_x())[ii]};
00297     // Evaluate and assign the Dirichlet coefficient.
00298     mtk::Real cc = (south_coefficients_[0])(xx, time);
00299     matrix.SetValue(ii, ii, cc);
00300 }
00301
00302 if (highest_order_diff_south_ > 0) {
00303
00304 }
00305
00306 return true;
00307 }
00308
00309 bool mtk::RobinBCDescriptor2D::ImposeOnNorthBoundaryNoSpace
(
00310     const mtk::Lap2D &lap,
00311     const mtk::UniStgGrid2D &grid,
00312     mtk::DenseMatrix &matrix,
00313     const mtk::Real &time) const {
00314
00315 int north_offset{(grid.num_cells_y() + 1)*(grid.num_cells_x() + 2)};
00316
00317
00318 // For the north-west corner:
00319 mtk::Real cc =
00320     (north_coefficients_[0])(grid.west_bndy(), time);
00321
00322 #if MTK_VERBOSE_LEVEL > 2
00323 std::cout << "Matrix has " << matrix.num_rows() << " rows and " <<
00324     matrix.num_cols() << " columns." << std::endl;
00325 std::cout << "Setting at " << north_offset << ' ' << north_offset <<
00326     std::endl;
00327 #endif
00328
00329 matrix.SetValue(north_offset, north_offset, cc);
00330
00331 // Compute first centers per dimension.
00332 auto first_center_x = grid.west_bndy() + grid.delta_x()/
00333     mtk::kTwo;
00334
00335 // For each entry on the diagonal (north boundary):
00336 for (int ii = 0; ii < grid.num_cells_x(); ++ii) {
00337     // Evaluate next set spatial coordinates to evaluate the coefficient.
00338     mtk::Real xx = first_center_x + ii*grid.delta_x();
00339     // Evaluate and assign the Dirichlet coefficient.
00340     cc = (north_coefficients_[0])(xx, time);
00341
00342     #if MTK_VERBOSE_LEVEL > 2
00343     std::cout << "Setting at " << north_offset + ii + 1 << ' ' <<
00344         north_offset + ii + 1 << std::endl;
00345     #endif
00346
00347     matrix.SetValue(north_offset + ii + 1, north_offset + ii + 1, cc);
00348 }
00349
00350
00351
00352

```

```

00353 // For the north-east corner:
00354 cc = (north_coefficients_[0])(grid.east_bndy(), time);
00355
00356 #if MTK_VERBOSE_LEVEL > 2
00357 std::cout << "Setting at " << north_offset + grid.num_cells_x() + 1 <<
00358     ' ' << north_offset + grid.num_cells_x() + 1 << std::endl;
00359 #endif
00360
00361 matrix.SetValue(north_offset + grid.num_cells_x() + 1,
00362     north_offset + grid.num_cells_x() + 1, cc);
00363
00364 if (highest_order_diff_north_ > 0) {
00365 }
00366
00367 return true;
00370 }
00371
00372 bool mtk::RobinBCDescriptor2D::ImposeOnNorthBoundaryWithSpace
00373 (
00374     const mtk::Lap2D &lap,
00375     const mtk::UniStgGrid2D &grid,
00376     mtk::DenseMatrix &matrix,
00377     const mtk::Real &time) const {
00378
00379     int north_offset{(grid.num_cells_y() + 1)*(grid.num_cells_x() + 2)};
00380
00381     for (int ii = 0; ii < grid.num_cells_x() + 2; ++ii) {
00382         mtk::Real xx{(grid.discrete_domain_x())[ii]};
00383         mtk::Real cc = (north_coefficients_[0])(xx, time);
00384         matrix.SetValue(north_offset + ii, north_offset + ii, cc);
00385     }
00386
00387     if (highest_order_diff_north_ > 0) {
00388     }
00389
00390     return true;
00391 }
00392
00393 bool mtk::RobinBCDescriptor2D::ImposeOnWestBoundaryNoSpace
00394 (
00395     const mtk::Lap2D &lap,
00396     const mtk::UniStgGrid2D &grid,
00397     mtk::DenseMatrix &matrix,
00398     const mtk::Real &time) const {
00399
00400     // For the south-west corner:
00401     auto cc = (west_coefficients_[0])(grid.south_bndy(), time);
00402
00403     #if MTK_VERBOSE_LEVEL > 2
00404     std::cout << "Matrix has " << matrix.num_rows() << " rows and " <<
00405         matrix.num_cols() << " columns." << std::endl;
00406     std::cout << "Setting at " << 0 << ' ' << 0 << std::endl;
00407     #endif
00408
00409     mtk::Real harmonic_mean = mtk::kOne/matrix.GetValue(0, 0) +
00410         mtk::kOne/cc;
00411     harmonic_mean = mtk::kTwo/harmonic_mean;
00412
00413     matrix.SetValue(0, 0, harmonic_mean);
00414
00415     int west_offset{grid.num_cells_x() + 1};
00416
00417     auto first_center_y = grid.south_bndy() + grid.delta_y()/
00418         mtk::kTwo;
00419
00420     // For each west entry on the diagonal (west boundary):
00421     for (int ii = 0; ii < grid.num_cells_y(); ++ii) {
00422         // Evaluate next set spatial coordinates to evaluate the coefficient.
00423         mtk::Real yy = first_center_y + ii*grid.delta_y();
00424         // Evaluate and assign the Dirichlet coefficient.
00425         cc = (west_coefficients_[0])(yy, time);
00426
00427         #if MTK_VERBOSE_LEVEL > 2
00428         std::cout << "Setting at " << west_offset + ii + 1 << ' ' <<
00429             west_offset + ii + 1 << std::endl;
00430         #endif
00431     }

```

```

00440
00441     matrix.SetValue(west_offset + ii + 1, west_offset + ii + 1, cc);
00442
00443     west_offset += grid.num_cells_x() + 1;
00444 }
00445
00446 // For the north-west corner:
00447 cc = (west_coefficients_[0])(grid.north_bndy(), time);
00448
00449 west_offset += grid.num_cells_x() + 1;
00450 int aux(west_offset);
00451 #if MTK_VERBOSE_LEVEL > 2
00452 std::cout << "Setting at " << aux << ' ' << aux << std::endl;
00453 #endif
00454
00455 harmonic_mean = mtk::kOne/matrix.GetValue(aux, aux) +
mtk::kOne/cc;
00456 harmonic_mean = mtk::kTwo/harmonic_mean;
00457
00458 matrix.SetValue(aux, aux, harmonic_mean);
00459
00460 if (highest_order_diff_west_ > 0) {
00461 }
00462
00463 return true;
00464 }
00465 }
00466 }
00467
00468 bool mtk::RobinBCDescriptor2D::ImposeOnWestBoundaryWithSpace
(
00469     const mtk::Lap2D &lap,
00470     const mtk::UniStgGrid2D &grid,
00471     mtk::DenseMatrix &matrix,
00472     const mtk::Real &time) const {
00473
00474
00475
00476     int west_offset(grid.num_cells_x() + 1);
00477     // For each west entry on the diagonal:
00478     for (int ii = 0; ii < grid.num_cells_y() + 2; ++ii) {
00479         // Evaluate next set spatial coordinates to evaluate the coefficient.
00480         mtk::Real yy{(grid.discrete_domain_y())[ii]};
00481         // Evaluate and assign the Dirichlet coefficient.
00482         mtk::Real cc = (west_coefficients_[0])(yy, time);
00483         matrix.SetValue(west_offset + ii, west_offset + ii, cc);
00484         west_offset += grid.num_cells_x() + 1;
00485     }
00486
00487     if (highest_order_diff_west_ > 0) {
00488     }
00489 }
00490 }
00491
00492 return true;
00493 }
00494
00495 bool mtk::RobinBCDescriptor2D::ImposeOnEastBoundaryNoSpace
(
00496     const mtk::Lap2D &lap,
00497     const mtk::UniStgGrid2D &grid,
00498     mtk::DenseMatrix &matrix,
00499     const mtk::Real &time) const {
00500
00501
00502
00503     // For the south-east corner:
00504     auto cc = (east_coefficients_[0])(grid.south_bndy(), time);
00505
00506     int east_offset(grid.num_cells_x() + 1);
00507     #if MTK_VERBOSE_LEVEL > 2
00508     std::cout << "Matrix has " << matrix.num_rows() << " rows and " <<
00509     matrix.num_cols() << " columns." << std::endl;
00510     std::cout << "Setting at " << east_offset << ' ' << east_offset <<
00511     std::endl;
00512     #endif
00513
00514     mtk::Real harmonic_mean =
00515     mtk::kOne/matrix.GetValue(east_offset, east_offset) +
mtk::kOne/cc;
00516     harmonic_mean = mtk::kTwo/harmonic_mean;
00517
00518     matrix.SetValue(east_offset, east_offset, harmonic_mean);
00519
00520     auto first_center_y = grid.south_bndy() + grid.delta_y()/

```

```

mtk::kTwo;
00521
00522 // For each east entry on the diagonal (east boundary):
00523 for (int ii = 0; ii < grid.num_cells_y(); ++ii) {
00524
00525     east_offset += grid.num_cells_x() + 1;
00526
00527     // Evaluate next set spatial coordinates to evaluate the coefficient.
00528     mtk::Real yy = first_center_y + ii*grid.delta_y();
00529     // Evaluate and assign the Dirichlet coefficient.
00530     cc = (east_coefficients_[0])(yy, time);
00531
00532     #if MTK_VERBOSE_LEVEL > 2
00533     std::cout << "Setting at " << east_offset + ii + 1 << ' ' <<
00534         east_offset + ii + 1 << std::endl;
00535     #endif
00536
00537     matrix.SetValue(east_offset + ii + 1, east_offset + ii + 1, cc);
00538 }
00539
00540 // For the north-east corner:
00541 cc = (east_coefficients_[0])(grid.north_bndy(), time);
00542
00543 east_offset += grid.num_cells_x() + 1;
00544 east_offset += grid.num_cells_x() + 1;
00545 int aux{east_offset};
00546 #if MTK_VERBOSE_LEVEL > 2
00547 std::cout << "Setting at " << aux << ' ' << aux << std::endl;
00548 #endif
00549
00550 harmonic_mean =
00551     mtk::kOne/matrix.GetValue(aux, aux) + mtk::kOne/cc;
00552 harmonic_mean = mtk::kTwo/harmonic_mean;
00553
00554 matrix.SetValue(aux, aux, harmonic_mean);
00555
00556 if (highest_order_diff_east_ > 0) {
00557
00558 }
00559
00560 return true;
00561 }
00562 }
00563
00564 bool mtk::RobinBCDescriptor2D::ImposeOnEastBoundaryWithSpace
(
00565     const mtk::Lap2D &lap,
00566     const mtk::UniStgGrid2D &grid,
00567     mtk::DenseMatrix &matrix,
00568     const mtk::Real &time) const {
00569
00570
00571
00572     int east_offset{grid.num_cells_x() + 1};
00573     // For each west entry on the diagonal:
00574     for (int ii = 0; ii < grid.num_cells_y() + 2; ++ii) {
00575         east_offset += grid.num_cells_x() + 1;
00576         // Evaluate next set spatial coordinates to evaluate the coefficient.
00577         mtk::Real yy{(grid.discrete_domain_y())[ii]};
00578         // Evaluate and assign the arithmetic mean of Dirichlet coefficients.
00579         mtk::Real cc = (east_coefficients_[0])(yy, time);
00580         matrix.SetValue(east_offset + ii, east_offset + ii, cc);
00581     }
00582
00583     if (highest_order_diff_east_ > 0) {
00584
00585     }
00586
00587     return true;
00588 }
00589 }
00590
00591 bool mtk::RobinBCDescriptor2D::ImposeOnLaplacianMatrix(
00592     const mtk::Lap2D &lap,
00593     const mtk::UniStgGrid2D &grid,
00594     mtk::DenseMatrix &matrix,
00595     const mtk::Real &time) const {
00596
00597     #ifdef MTK_PERFORM_PREVENTIONS
00598     mtk::Tools::Prevent(highest_order_diff_south_ == -1,
00599         __FILE__, __LINE__, __func__);
00600     mtk::Tools::Prevent(highest_order_diff_north_ == -1,
00601         __FILE__, __LINE__, __func__);
00602     mtk::Tools::Prevent(highest_order_diff_west_ == -1,

```



```

00603         __FILE__, __LINE__, __func__);
00604 mtk::Tools::Prevent(highest_order_diff_east_ == -1,
00605         __FILE__, __LINE__, __func__);
00606 mtk::Tools::Prevent(grid.nature() != mtk::SCALAR,
00607         __FILE__, __LINE__, __func__);
00608 mtk::Tools::Prevent(grid.num_cells_x() == 0, __FILE__, __LINE__, __func__);
00609 mtk::Tools::Prevent(grid.num_cells_y() == 0, __FILE__, __LINE__, __func__);
00610 mtk::Tools::Prevent(matrix.num_rows() == 0, __FILE__, __LINE__, __func__);
00611 mtk::Tools::Prevent(matrix.num_cols() == 0, __FILE__, __LINE__, __func__);
00612 #endif
00613
00616
00617 bool success{true};
00618
00619 if (!grid.Bound()) {
00620     success = ImposeOnSouthBoundaryNoSpace(lap, grid, matrix, time);
00621     #ifdef MTK_PERFORM_PREVENTIONS
00622     if (!success) {
00623         return false;
00624     }
00625     #endif
00626     success = ImposeOnNorthBoundaryNoSpace(lap, grid, matrix, time);
00627     #ifdef MTK_PERFORM_PREVENTIONS
00628     if (!success) {
00629         return false;
00630     }
00631     #endif
00632     success = ImposeOnWestBoundaryNoSpace(lap, grid, matrix, time);
00633     #ifdef MTK_PERFORM_PREVENTIONS
00634     if (!success) {
00635         return false;
00636     }
00637     #endif
00638     success = ImposeOnEastBoundaryNoSpace(lap, grid, matrix, time);
00639     #ifdef MTK_PERFORM_PREVENTIONS
00640     if (!success) {
00641         return false;
00642     }
00643     #endif
00644 } else {
00645     success = ImposeOnSouthBoundaryWithSpace(lap, grid, matrix, time);
00646     #ifdef MTK_PERFORM_PREVENTIONS
00647     if (!success) {
00648         return false;
00649     }
00650     #endif
00651     success = ImposeOnNorthBoundaryWithSpace(lap, grid, matrix, time);
00652     #ifdef MTK_PERFORM_PREVENTIONS
00653     if (!success) {
00654         return false;
00655     }
00656     #endif
00657     success = ImposeOnWestBoundaryWithSpace(lap, grid, matrix, time);
00658     #ifdef MTK_PERFORM_PREVENTIONS
00659     if (!success) {
00660         return false;
00661     }
00662     #endif
00663     success = ImposeOnEastBoundaryWithSpace(lap, grid, matrix, time);
00664     #ifdef MTK_PERFORM_PREVENTIONS
00665     if (!success) {
00666         return false;
00667     }
00668     #endif
00669 }
00670
00671 return success;
00672 }
00673
00674 void mtk::RobinBCDescriptor2D::ImposeOnGrid(
00675     mtk::UniStgGrid2D &grid,
00676     const mtk::Real &time) const {
00677
00678     #ifdef MTK_PERFORM_PREVENTIONS
00679     mtk::Tools::Prevent(grid.num_cells_x() == 0, __FILE__, __LINE__, __func__);
00680     mtk::Tools::Prevent(grid.num_cells_y() == 0, __FILE__, __LINE__, __func__);
00681     mtk::Tools::Prevent(west_condition_ == nullptr, __FILE__, __LINE__, __func__);
00682     mtk::Tools::Prevent(east_condition_ == nullptr, __FILE__, __LINE__, __func__);
00683     mtk::Tools::Prevent(south_condition_ == nullptr,
00684         __FILE__, __LINE__, __func__);
00685     mtk::Tools::Prevent(north_condition_ == nullptr,

```

```

00686         __FILE__, __LINE__, __func__);
00687     #endif
00688
00690     if (grid.nature() == mtk::SCALAR) {
00691
00693
00695         mtk::Real xx = grid.west_bndy();
00696         (grid.discrete_field())[0] = south_condition_(xx, time);
00697
00699         xx = xx + grid.delta_x()/mtk::kTwo;
00700         // For every point on the south boundary:
00701         for (int ii = 0; ii < grid.num_cells_x(); ++ii) {
00702             (grid.discrete_field())[ii + 1] =
00703                 south_condition_(xx + ii*grid.delta_x(), time);
00704         }
00705
00707         xx = grid.east_bndy();
00708         (grid.discrete_field())[grid.num_cells_x() + 1] =
00709             south_condition_(xx, time);
00710
00712
00714         xx = grid.west_bndy();
00715         int north_offset{(grid.num_cells_y() + 1)*(grid.num_cells_x() + 2)};
00716         (grid.discrete_field())[north_offset] = north_condition_(xx, time);
00717
00719         xx = xx + grid.delta_x()/mtk::kTwo;
00720         for (int ii = 0; ii < grid.num_cells_x(); ++ii) {
00721             (grid.discrete_field())[north_offset + ii + 1] =
00722                 north_condition_(xx + ii*grid.delta_x(), time);
00723         }
00724
00726         xx = grid.east_bndy();
00727         (grid.discrete_field())[north_offset + grid.num_cells_x() + 1] =
00728             north_condition_(xx, time);
00729
00731
00733         mtk::Real yy = grid.south_bndy();
00734         (grid.discrete_field())[0] =
00735             ((grid.discrete_field())[0] + west_condition_(yy, time))/
00736             mtk::kTwo;
00737
00738         int west_offset{grid.num_cells_x() + 1 + 1};
00739         yy = yy + grid.delta_y()/mtk::kTwo;
00740         for (int ii = 0; ii < grid.num_cells_y(); ++ii) {
00741             #if MTK_VERBOSE_LEVEL > 2
00742                 std::cout << "Adding on " << west_offset << "-th position." << std::endl;
00743             #endif
00744             (grid.discrete_field())[west_offset] =
00745                 west_condition_(yy + ii*grid.delta_y(), time);
00746             west_offset += grid.num_cells_x() + 1 + 1;
00747         }
00748
00750         yy = grid.north_bndy();
00751         north_offset = (grid.num_cells_y() + 1)*(grid.num_cells_x() + 2);
00752         (grid.discrete_field())[north_offset] =
00753             ((grid.discrete_field())[north_offset] + west_condition_(yy, time))/
00754             mtk::kTwo;
00755
00756         yy = grid.south_bndy();
00757         int east_offset{grid.num_cells_x() + 1};
00758         (grid.discrete_field())[east_offset] =
00759             ((grid.discrete_field())[east_offset] + east_condition_(yy, time))/
00760             mtk::kTwo;
00761
00762         yy = yy + grid.delta_y()/mtk::kTwo;
00763         for (int ii = 0; ii < grid.num_cells_y(); ++ii) {
00764             east_offset += grid.num_cells_x() + 1 + 1;
00765             #if MTK_VERBOSE_LEVEL > 2
00766                 std::cout << "Adding on " << east_offset << "-th position." << std::endl;
00767             #endif
00768             (grid.discrete_field())[east_offset] =
00769                 east_condition_(yy + ii*grid.delta_y(), time);
00770         }
00771
00772         yy = grid.north_bndy();
00773         (grid.discrete_field())[north_offset + grid.num_cells_x() + 1] =
00774             ((grid.discrete_field())[north_offset + grid.num_cells_x() + 1] +
00775              east_condition_(yy, time))/mtk::kTwo;
00776
00777     } else {

```

```

00785
00787
00789  }
00790 }

```

17.107 src/mtk_tools.cc File Reference


Implements a execution tool manager class.

```

#include <iostream>
#include "mtk_roots.h"
#include "mtk_tools.h"

```

Include dependency graph for mtk_tools.cc:



17.107.1 Detailed Description

Basic tools to ensure execution correctness.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_tools.cc](#).

17.108 mtk_tools.cc

```

00001
00010 /*
00011 Copyright (C) 2015, Computational Science Research Center, San Diego State
00012 University. All rights reserved.
00013
00014 Redistribution and use in source and binary forms, with or without modification,
00015 are permitted provided that the following conditions are met:
00016
00017 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu

```

```

00018 and a copy of the modified files should be reported once modifications are
00019 completed, unless these modifications are made through the project's GitHub
00020 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00021 should be developed and included in any deliverable.
00022
00023 2. Redistributions of source code must be done through direct
00024 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00025
00026 3. Redistributions in binary form must reproduce the above copyright notice,
00027 this list of conditions and the following disclaimer in the documentation and/or
00028 other materials provided with the distribution.
00029
00030 4. Usage of the binary form on proprietary applications shall require explicit
00031 prior written permission from the the copyright holders, and due credit should
00032 be given to the copyright holders.
00033
00034 5. Neither the name of the copyright holder nor the names of its contributors
00035 may be used to endorse or promote products derived from this software without
00036 specific prior written permission.
00037
00038 The copyright holders provide no reassurances that the source code provided does
00039 not infringe any patent, copyright, or any other intellectual property rights of
00040 third parties. The copyright holders disclaim any liability to any recipient for
00041 claims brought against recipient by any third party for infringement of that
00042 parties intellectual property rights.
00043
00044 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00045 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00046 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00047 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00048 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00049 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00050 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00051 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00052 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00053 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00054 */
00055
00056 #include <iostream>
00057
00058 #include "mtk_roots.h"
00059 #include "mtk_tools.h"
00060
00061 void mtk::Tools::Prevent(const bool condition,
00062                          const char *const fname,
00063                          int lineno,
00064                          const char *const fxname) noexcept {
00065
00066     if (lineno < 1) {
00067         std::cerr << __FILE__ << ": " << "Incorrect parameter at line " <<
00068         __LINE__ - 2 << " (" << __func__ << ")" << std::endl;
00069         exit(EXIT_FAILURE);
00070     }
00071
00072     if (condition) {
00073         std::cerr << fname << ": " << "Incorrect parameter at line " <<
00074         lineno << " (" << fxname << ")" << std::endl;
00075         exit(EXIT_FAILURE);
00076     }
00077 }
00078
00079
00080 int mtk::Tools::test_number_; // Used to control the correctness of the test.
00081
00082 mtk::Real mtk::Tools::duration_; // Duration of the current test.
00083
00084 clock_t mtk::Tools::begin_time_; // Used to time tests.
00085
00086 void mtk::Tools::BeginUnitTestNo(const int &nn) noexcept {
00087
00088     #if MTK_PERFORM_PREVENTIONS
00089     mtk::Tools::Prevent(nn <= 0, __FILE__, __LINE__, __func__);
00090     #endif
00091
00092     test_number_ = nn;
00093
00094     std::cout << "Beginning test " << nn << "." << std::endl;
00095     begin_time_ = clock();
00096 }
00097
00098 void mtk::Tools::EndUnitTestNo(const int &nn) noexcept {

```

```

00101
00102  #if MTK_PERFORM_PREVENTIONS
00103  mtk::Tools::Prevent(test_number_ != nn, __FILE__, __LINE__, __func__);
00104  #endif
00105
00106  duration_ = mtk::Real(clock() - begin_time_)/CLOCKS_PER_SEC;
00107 }
00108
00109 void mtk::Tools::Assert(const bool &condition) noexcept {
00110
00111  if (condition) {
00112      std::cout << "Test " << test_number_ << ": PASSED in " << duration_ <<
00113      " s." << std::endl;
00114  } else {
00115      std::cout << "Test " << test_number_ << ": FAILED in " << duration_ <<
00116      " s." << std::endl;
00117  }
00118 }

```

17.109 src/mtk_uni_stg_grid_1d.cc File Reference


Implementation of an 1D uniform staggered grid.

```

#include <iostream>
#include <iomanip>
#include <fstream>
#include "mtk_roots.h"
#include "mtk_enums.h"
#include "mtk_tools.h"
#include "mtk_uni_stg_grid_1d.h"

```

Include dependency graph for mtk_uni_stg_grid_1d.cc:



Namespaces

- [mtk](#)
Mimetic Methods Toolkit namespace.

Functions

- `std::ostream & mtk::operator<< (std::ostream &stream, mtk::UniStgGrid1D &in)`

17.109.1 Detailed Description

Implementation of an 1D uniform staggered grid.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_uni_stg_grid_1d.cc](#).

17.110 mtk_uni_stg_grid_1d.cc

```

00001
00010 /*
00011 Copyright (C) 2015, Computational Science Research Center, San Diego State
00012 University. All rights reserved.
00013
00014 Redistribution and use in source and binary forms, with or without modification,
00015 are permitted provided that the following conditions are met:
00016
00017 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00018 and a copy of the modified files should be reported once modifications are
00019 completed, unless these modifications are made through the project's GitHub
00020 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00021 should be developed and included in any deliverable.
00022
00023 2. Redistributions of source code must be done through direct
00024 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00025
00026 3. Redistributions in binary form must reproduce the above copyright notice,
00027 this list of conditions and the following disclaimer in the documentation and/or
00028 other materials provided with the distribution.
00029
00030 4. Usage of the binary form on proprietary applications shall require explicit
00031 prior written permission from the the copyright holders, and due credit should
00032 be given to the copyright holders.
00033
00034 5. Neither the name of the copyright holder nor the names of its contributors
00035 may be used to endorse or promote products derived from this software without
00036 specific prior written permission.
00037
00038 The copyright holders provide no reassurances that the source code provided does
00039 not infringe any patent, copyright, or any other intellectual property rights of
00040 third parties. The copyright holders disclaim any liability to any recipient for
00041 claims brought against recipient by any third party for infringement of that
00042 parties intellectual property rights.
00043
00044 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00045 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00046 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00047 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00048 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00049 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00050 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00051 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00052 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00053 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00054 */
00055
00056 #include <iostream>
00057 #include <iomanip>
00058 #include <fstream>
00059
00060 #include "mtk_roots.h"
00061 #include "mtk_enums.h"
00062 #include "mtk_tools.h"
00063
00064 #include "mtk_uni_stg_grid_1d.h"
00065
00066 namespace mtk {
00067
00068 std::ostream& operator <<(std::ostream &stream, mtk::UniStgGrid1D &in) {
00069
00070     stream << '[' << in.west_bndy_x << ':' << in.num_cells_x << ':' <<
00071     in.east_bndy_x << "]" = " << std::endl << std::endl;
00072
00073
00074
00075     stream << "x:";
00076     for (unsigned int ii = 0; ii < in.discrete_domain_x.size(); ++ii) {
00077         stream << std::setw(10) << in.discrete_domain_x[ii];

```

```

00078     }
00079     stream << std::endl;
00080
00082
00083     if (in.nature_ == mtk::SCALAR) {
00084         stream << "u:";
00085     }
00086     else {
00087         stream << "v:";
00088     }
00089     for (unsigned int ii = 0; ii < in.discrete_field_.size(); ++ii) {
00090         stream << std::setw(10) << in.discrete_field_[ii];
00091     }
00092
00093     stream << std::endl;
00094
00095     return stream;
00096 }
00097 }
00098
00099 mtk::UniStgGrid1D::UniStgGrid1D():
00100     nature_(),
00101     discrete_domain_x_(),
00102     discrete_field_(),
00103     west_bndy_x_(),
00104     east_bndy_x_(),
00105     num_cells_x_(),
00106     delta_x_() {}
00107
00108 mtk::UniStgGrid1D::UniStgGrid1D(const
UniStgGrid1D &grid):
00109     nature_(grid.nature_),
00110     west_bndy_x_(grid.west_bndy_x_),
00111     east_bndy_x_(grid.east_bndy_x_),
00112     num_cells_x_(grid.num_cells_x_),
00113     delta_x_(grid.delta_x_) {
00114
00115         std::copy(grid.discrete_domain_x_.begin(),
00116                 grid.discrete_domain_x_.begin() + grid.
discrete_domain_x_.size(),
00117                 discrete_domain_x_.begin());
00118
00119         std::copy(grid.discrete_field_.begin(),
00120                 grid.discrete_field_.begin() + grid.discrete_field_.size(),
00121                 discrete_field_.begin());
00122 }
00123
00124 mtk::UniStgGrid1D::UniStgGrid1D(const Real &west_bndy_x,
00125                                 const Real &east_bndy_x,
00126                                 const int &num_cells_x,
00127                                 const mtk::FieldNature &nature) {
00128
00129     #ifdef MTK_PERFORM_PREVENTIONS
00130     mtk::Tools::Prevent(west_bndy_x < mtk::kZero, __FILE__, __LINE__, __func__);
00131     mtk::Tools::Prevent(east_bndy_x < mtk::kZero, __FILE__, __LINE__, __func__);
00132     mtk::Tools::Prevent(east_bndy_x <= west_bndy_x, __FILE__, __LINE__, __func__);
00133     mtk::Tools::Prevent(num_cells_x < 0, __FILE__, __LINE__, __func__);
00134     #endif
00135
00136     nature_ = nature;
00137     west_bndy_x_ = west_bndy_x;
00138     east_bndy_x_ = east_bndy_x;
00139     num_cells_x_ = num_cells_x;
00140
00141     delta_x_ = (east_bndy_x - west_bndy_x)/((mtk::Real) num_cells_x);
00142 }
00143
00144 mtk::UniStgGrid1D::~UniStgGrid1D() {}
00145
00146 mtk::Real mtk::UniStgGrid1D::west_bndy_x() const {
00147
00148     return west_bndy_x_;
00149 }
00150
00151 mtk::Real mtk::UniStgGrid1D::east_bndy_x() const {
00152
00153     return east_bndy_x_;
00154 }
00155
00156 mtk::Real mtk::UniStgGrid1D::delta_x() const {
00157

```

```

00158     return delta_x_;
00159 }
00160
00161 const mtk::Real *mtk::UniStgGrid1D::discrete_domain_x() const
00162 {
00163     return discrete_domain_x_.data();
00164 }
00165
00166 mtk::Real *mtk::UniStgGrid1D::discrete_field() {
00167     return discrete_field_.data();
00168 }
00169 }
00170
00171 int mtk::UniStgGrid1D::num_cells_x() const {
00172     return num_cells_x_;
00173 }
00174 }
00175
00176 void mtk::UniStgGrid1D::BindScalarField(
00177     mtk::Real (*ScalarField)(const mtk::Real &xx)) {
00178
00179     #ifdef MTK_PERFORM_PREVENTIONS
00180     mtk::Tools::Prevent(nature_ == mtk::VECTOR, __FILE__, __LINE__, __func__);
00181     #endif
00182
00183     discrete_domain_x_.reserve(num_cells_x_ + 2);
00184
00185     discrete_domain_x_.push_back(west_bndy_x_);
00186     #ifdef MTK_PRECISION_DOUBLE
00187     auto first_center = west_bndy_x_ + delta_x_/2.0;
00188     #else
00189     auto first_center = west_bndy_x_ + delta_x_/2.0f;
00190     #endif
00191     discrete_domain_x_.push_back(first_center);
00192     for (auto ii = 1; ii < num_cells_x_; ++ii) {
00193         discrete_domain_x_.push_back(first_center + ii*delta_x_);
00194     }
00195     discrete_domain_x_.push_back(east_bndy_x_);
00196
00197     discrete_field_.reserve(num_cells_x_ + 2);
00198     discrete_field_.push_back(ScalarField(west_bndy_x_));
00199     discrete_field_.push_back(ScalarField(first_center));
00200     for (auto ii = 1; ii < num_cells_x_; ++ii) {
00201         discrete_field_.push_back(ScalarField(first_center + ii*delta_x_));
00202     }
00203     discrete_field_.push_back(ScalarField(east_bndy_x_));
00204 }
00205
00206 void mtk::UniStgGrid1D::BindVectorField(
00207     mtk::Real (*VectorField)(mtk::Real xx)) {
00208
00209     #ifdef MTK_PERFORM_PREVENTIONS
00210     mtk::Tools::Prevent(nature_ == mtk::SCALAR, __FILE__, __LINE__, __func__);
00211     #endif
00212
00213     discrete_domain_x_.reserve(num_cells_x_ + 1);
00214
00215     discrete_domain_x_.push_back(west_bndy_x_);
00216     for (auto ii = 1; ii < num_cells_x_; ++ii) {
00217         discrete_domain_x_.push_back(west_bndy_x_ + ii*delta_x_);
00218     }
00219     discrete_domain_x_.push_back(east_bndy_x_);
00220
00221     discrete_field_.reserve(num_cells_x_ + 1);
00222     discrete_field_.push_back(VectorField(west_bndy_x_));
00223     for (auto ii = 1; ii < num_cells_x_; ++ii) {
00224         discrete_field_.push_back(VectorField(west_bndy_x_ + ii*delta_x_));
00225     }
00226     discrete_field_.push_back(VectorField(east_bndy_x_));
00227 }
00228
00229 bool mtk::UniStgGrid1D::WriteToFile(std::string filename,
00230     std::string space_name,

```



```

00242                                     std::string field_name) const {
00243
00244     std::ofstream output_dat_file; // Output file.
00245     output_dat_file.open(filename);
00246
00247     if (!output_dat_file.is_open()) {
00248         return false;
00249     }
00250
00251     output_dat_file << "#" << space_name << " " << field_name << std::endl;
00252     for (unsigned int ii = 0; ii < discrete_domain_x_.size(); ++ii) {
00253         output_dat_file << discrete_domain_x_[ii] << " " << discrete_field_[ii] <<
00254             std::endl;
00255     }
00256
00257     output_dat_file.close();
00258
00259     return true;
00260 }
00261

```

17.111 src/mtk_uni_stg_grid_2d.cc File Reference


Implementation of a 2D uniform staggered grid.

```

#include <iostream>
#include <iomanip>
#include <fstream>
#include <algorithm>
#include "mtk_tools.h"
#include "mtk_uni_stg_grid_2d.h"

```

Include dependency graph for mtk_uni_stg_grid_2d.cc:



Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

Functions

- `std::ostream & mtk::operator<< (std::ostream &stream, mtk::UniStgGrid2D &in)`

17.111.1 Detailed Description

Implementation of a 2D uniform staggered grid.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_uni_stg_grid_2d.cc](#).

17.112 mtk_uni_stg_grid_2d.cc

```

00001
00010 /*
00011 Copyright (C) 2015, Computational Science Research Center, San Diego State
00012 University. All rights reserved.
00013
00014 Redistribution and use in source and binary forms, with or without modification,
00015 are permitted provided that the following conditions are met:
00016
00017 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00018 and a copy of the modified files should be reported once modifications are
00019 completed, unless these modifications are made through the project's GitHub
00020 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00021 should be developed and included in any deliverable.
00022
00023 2. Redistributions of source code must be done through direct
00024 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00025
00026 3. Redistributions in binary form must reproduce the above copyright notice,
00027 this list of conditions and the following disclaimer in the documentation and/or
00028 other materials provided with the distribution.
00029
00030 4. Usage of the binary form on proprietary applications shall require explicit
00031 prior written permission from the the copyright holders, and due credit should
00032 be given to the copyright holders.
00033
00034 5. Neither the name of the copyright holder nor the names of its contributors
00035 may be used to endorse or promote products derived from this software without
00036 specific prior written permission.
00037
00038 The copyright holders provide no reassurances that the source code provided does
00039 not infringe any patent, copyright, or any other intellectual property rights of
00040 third parties. The copyright holders disclaim any liability to any recipient for
00041 claims brought against recipient by any third party for infringement of that
00042 parties intellectual property rights.
00043
00044 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00045 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00046 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00047 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00048 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00049 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00050 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00051 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00052 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00053 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00054 */
00055
00056 #include <iostream>
00057 #include <iomanip>
00058 #include <fstream>
00059
00060 #include <algorithm>
00061
00062 #include "mtk_tools.h"
00063 #include "mtk_uni_stg_grid_2d.h"
00064
00065 namespace mtk {
00066
00067 std::ostream& operator <<(std::ostream &stream, mtk::UniStgGrid2D &in) {
00068
00069     stream << '[' << in.west_bndy_ << ':' << in.num_cells_x_ << ':' <<

```

```

00070     in.east_bndy_ << "]" x ";
00071
00072     stream << '[' << in.south_bndy_ << ':' << in.num_cells_y_ << ':' <<
00073     in.north_bndy_ << "]" = " << std::endl << std::endl;
00074
00075
00076
00077     stream << "x:";
00078     for (unsigned int ii = 0; ii < in.discrete_domain_x_.size(); ++ii) {
00079         stream << std::setw(10) << in.discrete_domain_x_[ii];
00080     }
00081     stream << std::endl;
00082
00083     stream << "y:";
00084     for (unsigned int ii = 0; ii < in.discrete_domain_y_.size(); ++ii) {
00085         stream << std::setw(10) << in.discrete_domain_y_[ii];
00086     }
00087     stream << std::endl;
00088
00089
00090
00091     if (in.nature_ == mtk::SCALAR) {
00092         stream << "u:" << std::endl;
00093         if (in.discrete_field_.size() > 0) {
00094             for (int ii = 0; ii < in.num_cells_x_ + 2; ++ii) {
00095                 for (int jj = 0; jj < in.num_cells_y_ + 2; ++jj) {
00096                     stream << std::setw(10) << in.discrete_field_[ii*in.
num_cells_y_ + jj];
00097                 }
00098                 stream << std::endl;
00099             }
00100         }
00101     } else {
00102
00103         int mm{in.num_cells_x_};
00104         int nn{in.num_cells_y_};
00105         int p_offset{nn*(mm + 1) - 1};
00106
00107         stream << "p(x,y):" << std::endl;
00108         for (int ii = 0; ii < nn; ++ii) {
00109             for (int jj = 0; jj < mm + 1; ++jj) {
00110                 stream << std::setw(10) << in.discrete_field_[ii*(mm + 1) + jj];
00111             }
00112             stream << std::endl;
00113         }
00114         stream << std::endl;
00115
00116         stream << "q(x,y):" << std::endl;
00117         for (int ii = 0; ii < nn + 1; ++ii) {
00118             for (int jj = 0; jj < mm; ++jj) {
00119                 stream << std::setw(10) <<
00120                 in.discrete_field_[p_offset + ii*mm + jj];
00121             }
00122             stream << std::endl;
00123         }
00124         stream << std::endl;
00125     }
00126
00127     return stream;
00128 }
00129 }
00130
00131 mtk::UniStgGrid2D::UniStgGrid2D():
00132     discrete_domain_x_(),
00133     discrete_domain_y_(),
00134     discrete_field_(),
00135     nature_(),
00136     west_bndy_(),
00137     east_bndy_(),
00138     num_cells_x_(),
00139     delta_x_(),
00140     south_bndy_(),
00141     north_bndy_(),
00142     num_cells_y_(),
00143     delta_y_() {}
00144
00145 mtk::UniStgGrid2D::UniStgGrid2D(const
UniStgGrid2D &grid):
00146     nature_(grid.nature_),
00147     west_bndy_(grid.west_bndy_),
00148     east_bndy_(grid.east_bndy_),
00149     num_cells_x_(grid.num_cells_x_),
00150     delta_x_(grid.delta_x_),

```

```

00151     south_bndy_(grid.south_bndy_),
00152     north_bndy_(grid.north_bndy_),
00153     num_cells_y_(grid.num_cells_y_),
00154     delta_y_(grid.delta_y_) {
00155
00156     std::copy(grid.discrete_domain_x_.begin(),
00157               grid.discrete_domain_x_.begin() + grid.
00158               discrete_domain_x_.size(),
00159               discrete_domain_x_.begin());
00160     std::copy(grid.discrete_domain_y_.begin(),
00161               grid.discrete_domain_y_.begin() + grid.
00162               discrete_domain_y_.size(),
00163               discrete_domain_y_.begin());
00164     std::copy(grid.discrete_field_.begin(),
00165               grid.discrete_field_.begin() + grid.discrete_field_.size(),
00166               discrete_field_.begin());
00167 }
00168
00169 mtk::UniStgGrid2D::UniStgGrid2D(const Real &west_bndy,
00170                                 const Real &east_bndy,
00171                                 const int &num_cells_x,
00172                                 const Real &south_bndy,
00173                                 const Real &north_bndy,
00174                                 const int &num_cells_y,
00175                                 const mtk::FieldNature &nature) {
00176
00177     #ifdef MTK_PERFORM_PREVENTIONS
00178     mtk::Tools::Prevent(west_bndy < mtk::kZero, __FILE__, __LINE__, __func__);
00179     mtk::Tools::Prevent(east_bndy < mtk::kZero, __FILE__, __LINE__, __func__);
00180     mtk::Tools::Prevent(east_bndy <= west_bndy, __FILE__, __LINE__, __func__);
00181     mtk::Tools::Prevent(num_cells_x < 0, __FILE__, __LINE__, __func__);
00182     mtk::Tools::Prevent(south_bndy < mtk::kZero, __FILE__, __LINE__, __func__);
00183     mtk::Tools::Prevent(north_bndy < mtk::kZero, __FILE__, __LINE__, __func__);
00184     mtk::Tools::Prevent(north_bndy <= south_bndy,
00185                         __FILE__, __LINE__, __func__);
00186     mtk::Tools::Prevent(num_cells_y < 0, __FILE__, __LINE__, __func__);
00187     #endif
00188     nature_ = nature;
00189
00190     west_bndy_ = west_bndy;
00191     east_bndy_ = east_bndy;
00192     num_cells_x_ = num_cells_x;
00193
00194     south_bndy_ = south_bndy;
00195     north_bndy_ = north_bndy;
00196     num_cells_y_ = num_cells_y;
00197
00198     delta_x_ = (east_bndy_ - west_bndy_) / (mtk::Real) num_cells_x;
00199     delta_y_ = (north_bndy_ - south_bndy_) / (mtk::Real) num_cells_y;
00200 }
00201
00202
00203 mtk::UniStgGrid2D::~UniStgGrid2D() {}
00204
00205 mtk::FieldNature mtk::UniStgGrid2D::nature() const {
00206
00207     return nature_;
00208 }
00209
00210 mtk::Real mtk::UniStgGrid2D::west_bndy() const {
00211
00212     return west_bndy_;
00213 }
00214
00215 mtk::Real mtk::UniStgGrid2D::east_bndy() const {
00216
00217     return east_bndy_;
00218 }
00219
00220 int mtk::UniStgGrid2D::num_cells_x() const {
00221
00222     return num_cells_x_;
00223 }
00224
00225 mtk::Real mtk::UniStgGrid2D::delta_x() const {
00226
00227     return delta_x_;
00228 }
00229

```

```

00230 const mtk::Real* mtk::UniStgGrid2D::discrete_domain_x() const
00231 {
00232     return discrete_domain_x_.data();
00233 }
00234
00235 mtk::Real mtk::UniStgGrid2D::south_bndy() const {
00236     return south_bndy_;
00237 }
00238
00239
00240 mtk::Real mtk::UniStgGrid2D::north_bndy() const {
00241     return north_bndy_;
00242 }
00243
00244
00245 int mtk::UniStgGrid2D::num_cells_y() const {
00246     return num_cells_y_;
00247 }
00248
00249
00250 mtk::Real mtk::UniStgGrid2D::delta_y() const {
00251     return delta_y_;
00252 }
00253
00254
00255 bool mtk::UniStgGrid2D::Bound() const {
00256     return discrete_field_.size() != 0;
00257 }
00258
00259
00260 const mtk::Real* mtk::UniStgGrid2D::discrete_domain_y() const
00261 {
00262     return discrete_domain_y_.data();
00263 }
00264
00265 mtk::Real* mtk::UniStgGrid2D::discrete_field() {
00266     return discrete_field_.data();
00267 }
00268
00269
00270 int mtk::UniStgGrid2D::Size() const {
00271     return discrete_field_.size();
00272 }
00273
00274
00275 void mtk::UniStgGrid2D::BindScalarField(
00276     Real (*ScalarField)(const Real &xx, const Real &yy)) {
00277
00278     #ifdef MTK_PERFORM_PREVENTIONS
00279     mtk::Tools::Prevent(nature_ != mtk::SCALAR, __FILE__, __LINE__, __func__);
00280     #endif
00281
00282     discrete_domain_x_.reserve(num_cells_x_ + 2);
00283
00284     discrete_domain_x_.push_back(west_bndy_);
00285     #ifdef MTK_PRECISION_DOUBLE
00286     auto first_center = west_bndy_ + delta_x_/2.0;
00287     #else
00288     auto first_center = west_bndy_ + delta_x_/2.0f;
00289     #endif
00290     discrete_domain_x_.push_back(first_center);
00291     for (auto ii = 1; ii < num_cells_x_; ++ii) {
00292         discrete_domain_x_.push_back(first_center + ii*delta_x_);
00293     }
00294     discrete_domain_x_.push_back(east_bndy_);
00295
00296     discrete_domain_y_.reserve(num_cells_y_ + 2);
00297
00298     discrete_domain_y_.push_back(south_bndy_);
00299     #ifdef MTK_PRECISION_DOUBLE
00300     first_center = south_bndy_ + delta_x_/2.0;
00301     #else
00302     first_center = south_bndy_ + delta_x_/2.0f;
00303     #endif
00304     discrete_domain_y_.push_back(first_center);
00305     for (auto ii = 1; ii < num_cells_y_; ++ii) {
00306         discrete_domain_y_.push_back(first_center + ii*delta_y_);
00307     }
00308 }

```

```

00311     }
00312     discrete_domain_y_.push_back(north_bndy_);
00313
00315     discrete_field_.reserve((num_cells_x_ + 2)*(num_cells_y_ + 2));
00317
00318     for (int ii = 0; ii < num_cells_y_ + 2; ++ii) {
00319         for (int jj = 0; jj < num_cells_x_ + 2; ++jj) {
00320             #if MTK_VERBOSE_LEVEL > 6
00321                 std::cout << "Pushing value for x = " << discrete_domain_x_[jj] <<
00322                     " y = " << discrete_domain_y_[ii] << std::endl;
00323             #endif
00324             discrete_field_.push_back(ScalarField(discrete_domain_x_[jj],
00325                                                     discrete_domain_y_[ii]));
00326         }
00327     }
00328 }
00329
00330 void mtk::UniStgGrid2D::BindVectorFieldPComponent(
00331     mtk::Real (*VectorField)(const mtk::Real &xx, const
00332     mtk::Real &yy)) {
00333     int mm{num_cells_x_};
00334     int nn{num_cells_y_};
00335
00336     int total{nn*(mm + 1) + mm*(nn + 1)};
00337
00338     #ifdef MTK_PRECISION_DOUBLE
00339     double half_delta_x{delta_x_/2.0};
00340     double half_delta_y{delta_y_/2.0};
00341     #else
00342     float half_delta_x{delta_x_/2.0f};
00343     float half_delta_y{delta_y_/2.0f};
00344     #endif
00345
00347     // We need every data point of the discrete domain; i.e. we need all the
00348     // nodes and all the centers. There are mm centers for the x direction, and
00349     // nn centers for the y direction. Since there is one node per center, that
00350     // amounts to 2*mm. If we finally consider the final boundary node, it
00351     // amounts to a total of 2*mm + 1 for the x direction. Analogously, for the
00352     // y direction, this amounts to 2*nn + 1.
00353
00354     discrete_domain_x_.reserve(2*mm + 1);
00355
00356     discrete_domain_x_.push_back(west_bndy_);
00357     for (int ii = 1; ii < (2*mm + 1); ++ii) {
00358         discrete_domain_x_.push_back(west_bndy_ + ii*half_delta_x);
00359     }
00360
00361     discrete_domain_y_.reserve(2*nn + 1);
00362
00363     discrete_domain_y_.push_back(south_bndy_);
00364     for (int ii = 1; ii < (2*nn + 1); ++ii) {
00365         discrete_domain_y_.push_back(south_bndy_ + ii*half_delta_y);
00366     }
00367
00368     discrete_field_.reserve(total);
00369
00370     // For each y-center.
00371     for (int ii = 1; ii < 2*nn + 1; ii += 2) {
00372         // Bind all of the x-nodes for this y-center.
00373         for (int jj = 0; jj < 2*mm + 1; jj += 2) {
00374             discrete_field_.push_back(VectorField(discrete_domain_x_[jj],
00375                                                     discrete_domain_y_[ii]));
00376
00377             #if MTK_VERBOSE_LEVEL > 6
00378                 std::cout << "Binding v at x = " << discrete_domain_x_[jj] << " y = " <<
00379                     discrete_domain_y_[ii] << " = " <<
00380                     VectorField(discrete_domain_x_[jj],discrete_domain_y_[ii]) << std::endl;
00381             #endif
00382         }
00383     }
00384
00385     #if MTK_VERBOSE_LEVEL > 6
00386     std::cout << std::endl;
00387     #endif
00388 }
00389
00390 #if MTK_VERBOSE_LEVEL > 6
00391     std::cout << std::endl;
00392 #endif
00393 }
00394

```

```

00395 void mtk::UniStgGrid2D::BindVectorFieldQComponent(
00396     mtk::Real (*VectorField)(const mtk::Real &xx, const
00397         mtk::Real &yy)) {
00398     int mm{num_cells_x_};
00399     int nn{num_cells_y_};
00400
00401     // For each y-node.
00402     for (int ii = 0; ii < 2*nn + 1; ii += 2) {
00403         // Bind all of the x-center for this y-node.
00404         for (int jj = 1; jj < 2*mm + 1; jj += 2) {
00405             discrete_field_.push_back(VectorField(discrete_domain_x_[jj],
00406                 discrete_domain_y_[ii]));
00407
00408             #if MTK_VERBOSE_LEVEL > 6
00409             std::cout << "Binding v at x = " << discrete_domain_x_[jj] << " y = " <<
00410                 discrete_domain_y_[ii] << " = " <<
00411                 VectorField(discrete_domain_x_[jj],discrete_domain_y_[ii]) << std::endl;
00412             #endif
00413         }
00414     }
00415     #if MTK_VERBOSE_LEVEL > 6
00416     std::cout << std::endl;
00417     #endif
00418 }
00419 void mtk::UniStgGrid2D::BindVectorField(
00420     Real (*VectorFieldPComponent)(const Real &xx, const Real &yy),
00421     Real (*VectorFieldQComponent)(const Real &xx, const Real &yy)) {
00422     #ifdef MTK_PERFORM_PREVENTIONS
00423     mtk::Tools::Prevent(nature_ != mtk::VECTOR, __FILE__, __LINE__, __func__);
00424     #endif
00425     BindVectorFieldPComponent(VectorFieldPComponent);
00426     BindVectorFieldQComponent(VectorFieldQComponent);
00427 }
00428 bool mtk::UniStgGrid2D::WriteToFile(std::string filename,
00429     std::string space_name_x,
00430     std::string space_name_y,
00431     std::string field_name) const {
00432     std::ofstream output_dat_file; // Output file.
00433     output_dat_file.open(filename);
00434     if (!output_dat_file.is_open()) {
00435         return false;
00436     }
00437     if (nature_ == mtk::SCALAR) {
00438         output_dat_file << "# " << space_name_x << ' ' << space_name_y << ' ' <<
00439             field_name << std::endl;
00440         int idx{};
00441         for (unsigned int ii = 0; ii < discrete_domain_y_.size(); ++ii) {
00442             for (unsigned int jj = 0; jj < discrete_domain_x_.size(); ++jj) {
00443                 output_dat_file << discrete_domain_x_[jj] << ' ' <<
00444                     discrete_domain_y_[ii] << ' ' <<
00445                     discrete_field_[idx] <<
00446                     std::endl;
00447                 idx++;
00448             }
00449             output_dat_file << std::endl;
00450         }
00451     } else {
00452         output_dat_file << "# " << space_name_x << ' ' << space_name_y << ' ' <<
00453             field_name << std::endl;
00454         output_dat_file << "# Horizontal component:" << std::endl;
00455         int mm{num_cells_x_};
00456         int nn{num_cells_y_};
00457
00458         // For each y-center.
00459         int idx{};
00460         for (int ii = 1; ii < 2*nn + 1; ii += 2) {

```

```

00477     // Bind all of the x-nodes for this y-center.
00478     for (int jj = 0; jj < 2*mm + 1; jj += 2) {
00479
00480         output_dat_file << discrete_domain_x_[jj] << ' ' <<
00481             discrete_domain_y_[ii] << ' ' << discrete_field_[idx] << ' ' <<
00482             mtk::kZero << std::endl;
00483
00484         ++idx;
00485     }
00486 }
00487
00488 int p_offset{nn*(mm + 1) - 1};
00489 idx = 0;
00490 output_dat_file << "# Vertical component:" << std::endl;
00491 // For each y-node.
00492 for (int ii = 0; ii < 2*nn + 1; ii += 2) {
00493     // Bind all of the x-center for this y-node.
00494     for (int jj = 1; jj < 2*mm + 1; jj += 2) {
00495
00496         output_dat_file << discrete_domain_x_[jj] << ' ' <<
00497             discrete_domain_y_[ii] << ' ' << mtk::kZero << ' ' <<
00498             discrete_field_[p_offset + idx] << std::endl;
00499
00500         ++idx;
00501     }
00502 }
00503 }
00504 }
00505
00506 output_dat_file.close();
00507
00508 return true;
00509 }

```

17.113 src/mtk_uni_stg_grid_3d.cc File Reference


Implementation of a 2D uniform staggered grid.

```

#include <iostream>
#include <iomanip>
#include <fstream>
#include <algorithm>
#include "mtk_tools.h"
#include "mtk_uni_stg_grid_3d.h"

```

Include dependency graph for mtk_uni_stg_grid_3d.cc:



Namespaces

- [mtk](#)

Mimetic Methods Toolkit namespace.

Functions

- `std::ostream & mtk::operator<< (std::ostream &stream, mtk::UniStgGrid3D &in)`

17.113.1 Detailed Description

Implementation of a 2D uniform staggered grid.

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_uni_stg_grid_3d.cc](#).

17.114 mtk_uni_stg_grid_3d.cc

```

00001
00010 /*
00011 Copyright (C) 2015, Computational Science Research Center, San Diego State
00012 University. All rights reserved.
00013
00014 Redistribution and use in source and binary forms, with or without modification,
00015 are permitted provided that the following conditions are met:
00016
00017 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00018 and a copy of the modified files should be reported once modifications are
00019 completed, unless these modifications are made through the project's GitHub
00020 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00021 should be developed and included in any deliverable.
00022
00023 2. Redistributions of source code must be done through direct
00024 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00025
00026 3. Redistributions in binary form must reproduce the above copyright notice,
00027 this list of conditions and the following disclaimer in the documentation and/or
00028 other materials provided with the distribution.
00029
00030 4. Usage of the binary form on proprietary applications shall require explicit
00031 prior written permission from the the copyright holders, and due credit should
00032 be given to the copyright holders.
00033
00034 5. Neither the name of the copyright holder nor the names of its contributors
00035 may be used to endorse or promote products derived from this software without
00036 specific prior written permission.
00037
00038 The copyright holders provide no reassurances that the source code provided does
00039 not infringe any patent, copyright, or any other intellectual property rights of
00040 third parties. The copyright holders disclaim any liability to any recipient for
00041 claims brought against recipient by any third party for infringement of that
00042 parties intellectual property rights.
00043
00044 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00045 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00046 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00047 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00048 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00049 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00050 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00051 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00052 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00053 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00054 */
00055
00056 #include <iostream>
00057 #include <iomanip>
00058 #include <fstream>

```

```

00059
00060 #include <algorithm>
00061
00062 #include "mtk_tools.h"
00063 #include "mtk_uni_stg_grid_3d.h"
00064
00065 namespace mtk {
00066
00067 std::ostream& operator <<(std::ostream &stream, mtk::UniStgGrid3D &in) {
00068
00069     stream << '[' << in.west_bndy_ << ':' << in.num_cells_x_ << ':' <<
00070     in.east_bndy_ << "]" x ";
00071
00072     stream << '[' << in.south_bndy_ << ':' << in.num_cells_y_ << ':' <<
00073     in.north_bndy_ << "]" x ";
00074
00075     stream << '[' << in.bottom_bndy_ << ':' << in.num_cells_z_ << ':' <<
00076     in.top_bndy_ << "]" = " << std::endl << std::endl;
00077
00078     stream << "x: ";
00079     for (auto const &cc: in.discrete_domain_x_) {
00080         stream << std::setw(10) << cc;
00081     }
00082     stream << std::endl;
00083
00084     stream << "y: ";
00085     for (auto const &cc: in.discrete_domain_y_) {
00086         stream << std::setw(10) << cc;
00087     }
00088     stream << std::endl;
00089
00090     stream << "z: ";
00091     for (auto const &cc: in.discrete_domain_z_) {
00092         stream << std::setw(10) << cc;
00093     }
00094     stream << std::endl;
00095
00096     if (in.nature_ == mtk::SCALAR) {
00097         stream << "u(x,y,z):" << std::endl;
00098         if (in.discrete_field_.size() > 0) {
00099
00100         }
00101     } else {
00102         stream << "p(x,y,z):" << std::endl;
00103         stream << "q(x,y,z):" << std::endl;
00104         if (in.discrete_field_.size() > 0) {
00105
00106         }
00107     }
00108     return stream;
00109 }
00110
00111 mtk::UniStgGrid3D mtk::UniStgGrid3D::operator=(const
00112 mtk::UniStgGrid3D &in) {
00113
00114     UniStgGrid3D out(in);
00115
00116     return out;
00117 }
00118
00119 mtk::UniStgGrid3D::UniStgGrid3D():
00120     discrete_domain_x_(),
00121     discrete_domain_y_(),
00122     discrete_domain_z_(),
00123     discrete_field_(),
00124     nature_(),
00125     west_bndy_(),
00126     east_bndy_(),
00127     num_cells_x_(),
00128     delta_x_(),
00129     south_bndy_(),
00130     north_bndy_(),
00131     num_cells_y_(),
00132     delta_y_(),
00133     bottom_bndy_(),
00134     top_bndy_(),
00135     num_cells_z_(),
00136     delta_z_() {}

```

```

00141
00142 mtk::UniStgGrid3D::UniStgGrid3D(const
    UniStgGrid3D &grid):
00143     nature_(grid.nature_),
00144     west_bndy_(grid.west_bndy_),
00145     east_bndy_(grid.east_bndy_),
00146     num_cells_x_(grid.num_cells_x_),
00147     delta_x_(grid.delta_x_),
00148     south_bndy_(grid.south_bndy_),
00149     north_bndy_(grid.north_bndy_),
00150     num_cells_y_(grid.num_cells_y_),
00151     delta_y_(grid.delta_y_),
00152     bottom_bndy_(grid.bottom_bndy_),
00153     top_bndy_(grid.top_bndy_),
00154     num_cells_z_(grid.num_cells_z_),
00155     delta_z_(grid.delta_z_) {
00156
00157     std::copy(grid.discrete_domain_x_.begin(),
00158         grid.discrete_domain_x_.begin() + grid.
discrete_domain_x_.size(),
        discrete_domain_x_.begin());
00159
00160
00161     std::copy(grid.discrete_domain_y_.begin(),
00162         grid.discrete_domain_y_.begin() + grid.
discrete_domain_y_.size(),
        discrete_domain_y_.begin());
00163
00164
00165     std::copy(grid.discrete_domain_z_.begin(),
00166         grid.discrete_domain_z_.begin() + grid.
discrete_domain_z_.size(),
        discrete_domain_z_.begin());
00167
00168
00169     std::copy(grid.discrete_field_.begin(),
00170         grid.discrete_field_.begin() + grid.discrete_field_.size(),
00171         discrete_field_.begin());
00172 }
00173
00174 mtk::UniStgGrid3D::UniStgGrid3D(const Real &west_bndy,
    const Real &east_bndy,
00175     const int &num_cells_x,
    const Real &south_bndy,
00176     const Real &north_bndy,
    const int &num_cells_y,
00177     const Real &bottom_bndy,
    const Real &top_bndy,
00178     const int &num_cells_z,
    const mtk::FieldNature &nature) {
00179
00180
00181
00182
00183
00184
00185 #ifdef MTK_PERFORM_PREVENTIONS
00186 mtk::Tools::Prevent(west_bndy < mtk::kZero, __FILE__, __LINE__, __func__);
00187 mtk::Tools::Prevent(east_bndy < mtk::kZero, __FILE__, __LINE__, __func__);
00188 mtk::Tools::Prevent(east_bndy <= west_bndy, __FILE__, __LINE__, __func__);
00189 mtk::Tools::Prevent(num_cells_x < 0, __FILE__, __LINE__, __func__);
00190 mtk::Tools::Prevent(south_bndy < mtk::kZero, __FILE__, __LINE__, __func__);
00191 mtk::Tools::Prevent(north_bndy < mtk::kZero, __FILE__, __LINE__, __func__);
00192 mtk::Tools::Prevent(north_bndy <= south_bndy,
    __FILE__, __LINE__, __func__);
00193
00194 mtk::Tools::Prevent(num_cells_y < 0, __FILE__, __LINE__, __func__);
00195 mtk::Tools::Prevent(bottom_bndy < mtk::kZero, __FILE__, __LINE__, __func__);
00196 mtk::Tools::Prevent(top_bndy < mtk::kZero, __FILE__, __LINE__, __func__);
00197 mtk::Tools::Prevent(top_bndy <= bottom_bndy,
    __FILE__, __LINE__, __func__);
00198
00199 mtk::Tools::Prevent(num_cells_z < 0, __FILE__, __LINE__, __func__);
00200 #endif
00201
00202 nature_ = nature;
00203
00204 west_bndy_ = west_bndy;
00205 east_bndy_ = east_bndy;
00206 num_cells_x_ = num_cells_x;
00207
00208 south_bndy_ = south_bndy;
00209 north_bndy_ = north_bndy;
00210 num_cells_y_ = num_cells_y;
00211
00212 bottom_bndy_ = bottom_bndy;
00213 top_bndy_ = top_bndy;
00214 num_cells_z_ = num_cells_z;
00215
00216 delta_x_ = (east_bndy_ - west_bndy_) / ((mtk::Real) num_cells_x);
00217 delta_y_ = (north_bndy_ - south_bndy_) / ((mtk::Real) num_cells_y);

```

```

00218     delta_z_ = (top_bndy_ - bottom_bndy_) / ((mtk::Real) num_cells_z);
00219 }
00220
00221 mtk::UniStgGrid3D::~~UniStgGrid3D() {}
00222
00223 mtk::FieldNature mtk::UniStgGrid3D::nature() const {
00224     return nature_;
00225 }
00226
00227
00228 mtk::Real mtk::UniStgGrid3D::west_bndy() const {
00229     return west_bndy_;
00230 }
00231
00232
00233 mtk::Real mtk::UniStgGrid3D::east_bndy() const {
00234     return east_bndy_;
00235 }
00236
00237
00238 int mtk::UniStgGrid3D::num_cells_x() const {
00239     return num_cells_x_;
00240 }
00241
00242
00243 mtk::Real mtk::UniStgGrid3D::delta_x() const {
00244     return delta_x_;
00245 }
00246
00247
00248 const mtk::Real* mtk::UniStgGrid3D::discrete_domain_x() const
00249 {
00250     return discrete_domain_x_.data();
00251 }
00252
00253 mtk::Real mtk::UniStgGrid3D::south_bndy() const {
00254     return south_bndy_;
00255 }
00256
00257
00258 mtk::Real mtk::UniStgGrid3D::north_bndy() const {
00259     return north_bndy_;
00260 }
00261
00262
00263 int mtk::UniStgGrid3D::num_cells_y() const {
00264     return num_cells_y_;
00265 }
00266
00267
00268 mtk::Real mtk::UniStgGrid3D::delta_y() const {
00269     return delta_y_;
00270 }
00271
00272
00273 const mtk::Real* mtk::UniStgGrid3D::discrete_domain_y() const
00274 {
00275     return discrete_domain_y_.data();
00276 }
00277
00278 mtk::Real mtk::UniStgGrid3D::bottom_bndy() const {
00279     return bottom_bndy_;
00280 }
00281
00282
00283 mtk::Real mtk::UniStgGrid3D::top_bndy() const {
00284     return top_bndy_;
00285 }
00286
00287
00288 int mtk::UniStgGrid3D::num_cells_z() const {
00289     return num_cells_z_;
00290 }
00291
00292
00293 mtk::Real mtk::UniStgGrid3D::delta_z() const {
00294     return delta_z_;
00295 }
00296

```

```

00297
00298 const mtk::Real* mtk::UniStgGrid3D::discrete_domain_z() const
00299 {
00300     return discrete_domain_z_.data();
00301 }
00302
00303 mtk::Real* mtk::UniStgGrid3D::discrete_field() {
00304     return discrete_field_.data();
00305 }
00306
00307
00308 bool mtk::UniStgGrid3D::Bound() const {
00309     return discrete_field_.size() != 0;
00310 }
00311
00312
00313 int mtk::UniStgGrid3D::Size() const {
00314     return discrete_field_.size();
00315 }
00316
00317
00318 void mtk::UniStgGrid3D::BindScalarField(
00319     mtk::Real (*ScalarField)(const mtk::Real &xx,
00320                             const mtk::Real &yy,
00321                             const mtk::Real &zz)) {
00322
00323     #ifdef MTK_PERFORM_PREVENTIONS
00324     mtk::Tools::Prevent(nature_ != mtk::SCALAR, __FILE__, __LINE__, __func__);
00325     #endif
00326
00327
00328
00329     discrete_domain_x_.reserve(num_cells_x_ + 2);
00330
00331     discrete_domain_x_.push_back(west_bndy_);
00332     #ifdef MTK_PRECISION_DOUBLE
00333     auto first_center = west_bndy_ + delta_x_/2.0;
00334     #else
00335     auto first_center = west_bndy_ + delta_x_/2.0f;
00336     #endif
00337     discrete_domain_x_.push_back(first_center);
00338     for (auto ii = 1; ii < num_cells_x_; ++ii) {
00339         discrete_domain_x_.push_back(first_center + ii*delta_x_);
00340     }
00341     discrete_domain_x_.push_back(east_bndy_);
00342
00343
00344
00345     discrete_domain_y_.reserve(num_cells_y_ + 2);
00346
00347     discrete_domain_y_.push_back(south_bndy_);
00348     #ifdef MTK_PRECISION_DOUBLE
00349     first_center = south_bndy_ + delta_x_/2.0;
00350     #else
00351     first_center = south_bndy_ + delta_x_/2.0f;
00352     #endif
00353     discrete_domain_y_.push_back(first_center);
00354     for (auto ii = 1; ii < num_cells_y_; ++ii) {
00355         discrete_domain_y_.push_back(first_center + ii*delta_y_);
00356     }
00357     discrete_domain_y_.push_back(north_bndy_);
00358
00359
00360
00361     discrete_domain_z_.reserve(num_cells_z_ + 2);
00362
00363     discrete_domain_z_.push_back(bottom_bndy_);
00364     first_center = bottom_bndy_ + delta_z_/mtk::kTwo;
00365     discrete_domain_z_.push_back(first_center);
00366     for (auto ii = 1; ii < num_cells_z_; ++ii) {
00367         discrete_domain_z_.push_back(first_center + ii*delta_z_);
00368     }
00369     discrete_domain_z_.push_back(top_bndy_);
00370
00371
00372
00373     int aux{(num_cells_x_ + 2)*(num_cells_y_ + 2)*(num_cells_z_ + 2)};
00374
00375     discrete_field_.reserve(aux);
00376
00377     for (int kk = 0; kk < num_cells_z_ + 2; ++kk) {
00378         for (int ii = 0; ii < num_cells_y_ + 2; ++ii) {
00379             for (int jj = 0; jj < num_cells_x_ + 2; ++jj) {
00380                 #if MTK_VERBOSE_LEVEL > 6

```

```

00381         std::cout << "At z = " << discrete_domain_z_[kk] << ": Pushing value"
00382         " for x = " << discrete_domain_x_[jj] << " y = " <<
00383         discrete_domain_y_[ii] << std::endl;
00384     #endif
00385     discrete_field_.push_back(ScalarField(discrete_domain_x_[jj],
00386                                         discrete_domain_y_[ii],
00387                                         discrete_domain_z_[kk]));
00388 }
00389 }
00390 }
00391 }
00392
00393 void mtk::UniStgGrid3D::BindVectorFieldPComponent (
00394     mtk::Real (*VectorField) (const mtk::Real &xx,
00395                               const mtk::Real &yy,
00396                               const mtk::Real &zz)) {
00397
00398 }
00399
00400 void mtk::UniStgGrid3D::BindVectorFieldQComponent (
00401     mtk::Real (*VectorField) (const mtk::Real &xx,
00402                               const mtk::Real &yy,
00403                               const mtk::Real &zz)) {
00404
00405 }
00406
00407 void mtk::UniStgGrid3D::BindVectorFieldRComponent (
00408     mtk::Real (*VectorField) (const mtk::Real &xx,
00409                               const mtk::Real &yy,
00410                               const mtk::Real &zz)) {
00411
00412 }
00413
00414 void mtk::UniStgGrid3D::BindVectorField(
00415     mtk::Real (*VectorFieldPComponent) (const mtk::Real &xx,
00416                                         const mtk::Real &yy,
00417                                         const mtk::Real &zz),
00418     mtk::Real (*VectorFieldQComponent) (const mtk::Real &xx,
00419                                         const mtk::Real &yy,
00420                                         const mtk::Real &zz),
00421     mtk::Real (*VectorFieldRComponent) (const mtk::Real &xx,
00422                                         const mtk::Real &yy,
00423                                         const mtk::Real &zz)) {
00424
00425     #ifdef MTK_PERFORM_PREVENTIONS
00426     mtk::Tools::Prevent(nature_ != mtk::VECTOR, __FILE__, __LINE__, __func__);
00427     #endif
00428
00429     BindVectorFieldPComponent(VectorFieldPComponent);
00430     BindVectorFieldQComponent(VectorFieldQComponent);
00431 }
00432
00433 bool mtk::UniStgGrid3D::WriteToFile(std::string filename,
00434                                     std::string space_name_x,
00435                                     std::string space_name_y,
00436                                     std::string space_name_z,
00437                                     std::string field_name) const {
00438
00439     std::ofstream output_dat_file; // Output file.
00440
00441     output_dat_file.open(filename);
00442
00443     if (!output_dat_file.is_open()) {
00444         return false;
00445     }
00446
00447     if (nature_ == mtk::SCALAR) {
00448         output_dat_file << "# " << space_name_x << ' ' << space_name_y << ' ' <<
00449         space_name_z << ' ' << field_name << std::endl;
00450
00451         int idx{};
00452         for (int kk = 0; kk < num_cells_z_ + 2; ++kk) {
00453             for (int ii = 0; ii < num_cells_y_ + 2; ++ii) {
00454                 for (int jj = 0; jj < num_cells_x_ + 2; ++jj) {
00455                     output_dat_file << discrete_domain_x_[jj] << ' ' <<
00456                     discrete_domain_y_[ii] << ' ' << discrete_domain_z_[kk] << ' ' <<
00457                     discrete_field_[idx] << std::endl;
00458                     idx++;
00459                 }
00460             }
00461         }
00462     }

```


```
00462
00463 } else {
00464     output_dat_file << "# " << space_name_x << ' ' << space_name_y << ' ' <<
00465     space_name_z << ' ' << field_name << std::endl;
00466 }
00467
00468
00469 output_dat_file.close();
00470
00471 return true;
00472 }
```

17.115 tests/mtk_blas_adapter_test.cc File Reference

Test file for the [mtk::BLASAdapter](#) class.

```
#include <iostream>
```

Include dependency graph for mtk_blas_adapter_test.cc:



Functions

- `int main ()`

17.115.1 Detailed Description

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_blas_adapter_test.cc](#).

17.115.2 Function Documentation

17.115.2.1 `int main ()`

Definition at line [109](#) of file [mtk_blas_adapter_test.cc](#).

17.116 mtk_blas_adapter_test.cc

```

00001
00008 /*
00009 Copyright (C) 2015, Computational Science Research Center, San Diego State
00010 University. All rights reserved.
00011
00012 Redistribution and use in source and binary forms, with or without modification,
00013 are permitted provided that the following conditions are met:
00014
00015 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00016 and a copy of the modified files should be reported once modifications are
00017 completed, unless these modifications are made through the project's GitHub
00018 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00019 should be developed and included in any deliverable.
00020
00021 2. Redistributions of source code must be done through direct
00022 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00023
00024 3. Redistributions in binary form must reproduce the above copyright notice,
00025 this list of conditions and the following disclaimer in the documentation and/or
00026 other materials provided with the distribution.
00027
00028 4. Usage of the binary form on proprietary applications shall require explicit
00029 prior written permission from the the copyright holders, and due credit should
00030 be given to the copyright holders.
00031
00032 5. Neither the name of the copyright holder nor the names of its contributors
00033 may be used to endorse or promote products derived from this software without
00034 specific prior written permission.
00035
00036 The copyright holders provide no reassurances that the source code provided does
00037 not infringe any patent, copyright, or any other intellectual property rights of
00038 third parties. The copyright holders disclaim any liability to any recipient for
00039 claims brought against recipient by any third party for infringement of that
00040 parties intellectual property rights.
00041
00042 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00043 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00044 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00045 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00046 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00047 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00048 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00049 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00050 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00051 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00052 */
00053
00054 #if __cplusplus == 201103L
00055
00056 #include <iostream>
00057
00058 #include "mtk.h"
00059
00060 void TestRealDenseMM() {
00061
00062     mtk::Tools::BeginUnitTestNo(1);
00063
00064     int rr = 2;
00065     int cc = 3;
00066
00067     mtk::DenseMatrix aa(rr,cc);
00068
00069     aa.SetValue(0,0,1.0);
00070     aa.SetValue(0,1,2.0);
00071     aa.SetValue(0,2,3.0);
00072     aa.SetValue(1,0,4.0);
00073     aa.SetValue(1,1,5.0);
00074     aa.SetValue(1,2,6.0);
00075
00076     mtk::DenseMatrix bb(cc,rr);
00077
00078     bb.SetValue(0,0,7.0);
00079     bb.SetValue(0,1,8.0);
00080     bb.SetValue(1,0,9.0);
00081     bb.SetValue(1,1,10.0);
00082     bb.SetValue(2,0,11.0);
00083     bb.SetValue(2,1,12.0);
00084

```



```

00085     mtk::DenseMatrix pp = mtk::BLASAdapter::RealDenseMM(aa,bb);
00086
00087     mtk::DenseMatrix ff(rr,rr);
00088
00089     ff.SetValue(0,0,58.0);
00090     ff.SetValue(0,1,64.00);
00091     ff.SetValue(1,0,139.0);
00092     ff.SetValue(1,1,154.0);
00093
00094     mtk::Tools::EndUnitTestNo(1);
00095     mtk::Tools::Assert(pp == ff);
00096 }
00097
00098 int main () {
00099
00100     std::cout << "Testing mtk::BLASAdapter class." << std::endl;
00101
00102     TestRealDenseMM();
00103 }
00104
00105 #else
00106 #include <iostream>
00107 using std::cout;
00108 using std::endl;
00109 int main () {
00110     cout << "This code HAS to be compiled with support for C++11." << endl;
00111     cout << "Exiting..." << endl;
00112 }
00113 #endif


```

17.117 tests/mtk_dense_matrix_test.cc File Reference

Test file for the `mtk::DenseMatrix` class.

```
#include <iostream>
```

Include dependency graph for `mtk_dense_matrix_test.cc`:



Functions

- `int main ()`

17.117.1 Detailed Description

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_dense_matrix_test.cc](#).

17.117.2 Function Documentation**17.117.2.1 int main ()**

Definition at line 330 of file [mtk_dense_matrix_test.cc](#).

17.118 mtk_dense_matrix_test.cc

```

00001
00008 /*
00009 Copyright (C) 2015, Computational Science Research Center, San Diego State
00010 University. All rights reserved.
00011
00012 Redistribution and use in source and binary forms, with or without modification,
00013 are permitted provided that the following conditions are met:
00014
00015 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00016 and a copy of the modified files should be reported once modifications are
00017 completed, unless these modifications are made through the project's GitHub
00018 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00019 should be developed and included in any deliverable.
00020
00021 2. Redistributions of source code must be done through direct
00022 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00023
00024 3. Redistributions in binary form must reproduce the above copyright notice,
00025 this list of conditions and the following disclaimer in the documentation and/or
00026 other materials provided with the distribution.
00027
00028 4. Usage of the binary form on proprietary applications shall require explicit
00029 prior written permission from the the copyright holders, and due credit should
00030 be given to the copyright holders.
00031
00032 5. Neither the name of the copyright holder nor the names of its contributors
00033 may be used to endorse or promote products derived from this software without
00034 specific prior written permission.
00035
00036 The copyright holders provide no reassurances that the source code provided does
00037 not infringe any patent, copyright, or any other intellectual property rights of
00038 third parties. The copyright holders disclaim any liability to any recipient for
00039 claims brought against recipient by any third party for infringement of that
00040 parties intellectual property rights.
00041
00042 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00043 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00044 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00045 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00046 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00047 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00048 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00049 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00050 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00051 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00052 */
00053
00054 #if __cplusplus == 201103L
00055
00056 #include <iostream>
00057 #include <ctime>
00058
00059 #include "mtk.h"
00060
00061 void TestDefaultConstructor() {
00062
00063     mtk::Tools::BeginUnitTestNo(1);

```

```

00064
00065     mtk::DenseMatrix m1;
00066
00067     mtk::Tools::EndUnitTestNo(1);
00068     mtk::Tools::Assert(m1.data() == nullptr);
00069 }
00070
00071 void TestConstructorWithNumRowsNumCols() {
00072
00073     mtk::Tools::BeginUnitTestNo(2);
00074
00075     int rr = 4;
00076     int cc = 7;
00077
00078     mtk::DenseMatrix m2(rr,cc);
00079
00080     mtk::Tools::EndUnitTestNo(2);
00081
00082     bool assertion =
00083         m2.data() != nullptr && m2.num_rows() == rr && m2.num_cols() == cc;
00084
00085     mtk::Tools::Assert(assertion);
00086 }
00087
00088 void TestConstructAsIdentity() {
00089
00090     mtk::Tools::BeginUnitTestNo(3);
00091
00092     int rank = 5;
00093     bool padded = true;
00094     bool transpose = false;
00095
00096     mtk::DenseMatrix m3(rank,padded,transpose);
00097
00098     mtk::DenseMatrix rr(rank + 2,rank);
00099
00100     for (int ii = 0; ii < rank; ++ii) {
00101         rr.SetValue(ii + 1, ii, mtk::kOne);
00102     }
00103
00104     mtk::Tools::EndUnitTestNo(3);
00105     mtk::Tools::Assert(m3 == rr);
00106 }
00107
00108 void TestConstructAsVandermonde() {
00109
00110     mtk::Tools::BeginUnitTestNo(4);
00111
00112     int rank = 5;
00113     bool padded = false;
00114     bool transpose = false;
00115
00116     mtk::DenseMatrix m4(rank,padded,transpose);
00117
00118     mtk::DenseMatrix rr(rank,rank);
00119
00120     for (int ii = 0; ii < rank; ++ii) {
00121         rr.SetValue(ii, ii, mtk::kOne);
00122     }
00123
00124     mtk::Tools::EndUnitTestNo(4);
00125     mtk::Tools::Assert(m4 == rr);
00126 }
00127
00128 void TestSetValueGetValue() {
00129
00130     mtk::Tools::BeginUnitTestNo(5);
00131
00132     int rr = 4;
00133     int cc = 7;
00134
00135     mtk::DenseMatrix m5(rr,cc);
00136
00137     for (auto ii = 0; ii < rr; ++ii) {
00138         for (auto jj = 0; jj < cc; ++jj) {
00139             m5.SetValue(ii,jj,(mtk::Real) ii + jj);
00140         }
00141     }
00142
00143     mtk::Real *vals = m5.data();
00144

```

```

00145     bool assertion{true};
00146
00147     for (auto ii = 0; ii < rr && assertion; ++ii) {
00148         for (auto jj = 0; jj < cc && assertion; ++jj) {
00149             assertion = assertion && m5.GetValue(ii,jj) == vals[ii*cc + jj];
00150         }
00151     }
00152
00153     mtk::Tools::EndUnitTestNo(5);
00154     mtk::Tools::Assert(assertion);
00155 }
00156
00157 void TestConstructAsVandermondeTranspose() {
00158
00159     mtk::Tools::BeginUnitTestNo(6);
00160
00161     bool transpose = false;
00162     int generator_length = 3;
00163     int progression_length = 4;
00164
00165     mtk::Real generator[] = {-0.5, 0.5, 1.5};
00166
00167     mtk::DenseMatrix m6(generator,generator_length,progression_length,transpose);
00168
00169     transpose = true;
00170
00171     mtk::DenseMatrix m7(generator,generator_length,progression_length,transpose);
00172     mtk::DenseMatrix rr(progression_length, generator_length);
00173
00174     rr.SetValue(0, 0, 1.0);
00175     rr.SetValue(0, 1, 1.0);
00176     rr.SetValue(0, 2, 1.0);
00177
00178     rr.SetValue(1, 0, -0.5);
00179     rr.SetValue(1, 1, 0.5);
00180     rr.SetValue(1, 2, 1.5);
00181
00182     rr.SetValue(2, 0, 0.25);
00183     rr.SetValue(2, 1, 0.25);
00184     rr.SetValue(2, 2, 2.25);
00185
00186     rr.SetValue(3, 0, -0.125);
00187     rr.SetValue(3, 1, 0.125);
00188     rr.SetValue(3, 2, 3.375);
00189
00190     mtk::Tools::EndUnitTestNo(6);
00191     mtk::Tools::Assert(m7 == rr);
00192 }
00193
00194 void TestKron() {
00195
00196     mtk::Tools::BeginUnitTestNo(7);
00197
00198     bool padded = false;
00199     bool transpose = false;
00200     int lots_of_rows = 2;
00201     int lots_of_cols = 5;
00202     mtk::DenseMatrix m8(lots_of_rows,padded,transpose);
00203
00204     mtk::DenseMatrix m9(lots_of_rows,lots_of_cols);
00205
00206     for (auto ii = 0; ii < lots_of_rows; ++ii) {
00207         for (auto jj = 0; jj < lots_of_cols; ++jj) {
00208             m9.SetValue(ii,jj,(mtk::Real) ii*lots_of_cols + jj + 1);
00209         }
00210     }
00211
00212     mtk::DenseMatrix m10 = mtk::DenseMatrix::Kron(m8,m9);
00213
00214     mtk::DenseMatrix rr(lots_of_rows*lots_of_rows, lots_of_rows*lots_of_cols);
00215
00216     rr.SetValue(0,0,1.0);
00217     rr.SetValue(0,1,2.0);
00218     rr.SetValue(0,2,3.0);
00219     rr.SetValue(0,3,4.0);
00220     rr.SetValue(0,4,5.0);
00221     rr.SetValue(0,5,0.0);
00222     rr.SetValue(0,6,0.0);
00223     rr.SetValue(0,7,0.0);
00224     rr.SetValue(0,8,0.0);
00225     rr.SetValue(0,9,0.0);

```

```

00226
00227     rr.SetValue(1,0,6.0);
00228     rr.SetValue(1,1,7.0);
00229     rr.SetValue(1,2,8.0);
00230     rr.SetValue(1,3,9.0);
00231     rr.SetValue(1,4,10.0);
00232     rr.SetValue(1,5,0.0);
00233     rr.SetValue(1,6,0.0);
00234     rr.SetValue(1,7,0.0);
00235     rr.SetValue(1,8,0.0);
00236     rr.SetValue(1,9,0.0);
00237
00238     rr.SetValue(2,0,0.0);
00239     rr.SetValue(2,1,0.0);
00240     rr.SetValue(2,2,0.0);
00241     rr.SetValue(2,3,0.0);
00242     rr.SetValue(2,4,0.0);
00243     rr.SetValue(2,5,1.0);
00244     rr.SetValue(2,6,2.0);
00245     rr.SetValue(2,7,3.0);
00246     rr.SetValue(2,8,4.0);
00247     rr.SetValue(2,9,5.0);
00248
00249     rr.SetValue(3,0,0.0);
00250     rr.SetValue(3,1,0.0);
00251     rr.SetValue(3,2,0.0);
00252     rr.SetValue(3,3,0.0);
00253     rr.SetValue(3,4,0.0);
00254     rr.SetValue(3,5,6.0);
00255     rr.SetValue(3,6,7.0);
00256     rr.SetValue(3,7,8.0);
00257     rr.SetValue(3,8,9.0);
00258     rr.SetValue(3,9,10.0);
00259
00260     mtk::Tools::EndUnitTestNo(7);
00261     mtk::Tools::Assert(m10 == rr);
00262 }
00263
00264 void TestConstructWithNumRowsNumColsAssignmentOperator() {
00265
00266     mtk::Tools::BeginUnitTestNo(8);
00267
00268     int lots_of_rows = 4;
00269     int lots_of_cols = 3;
00270     mtk::DenseMatrix m11(lots_of_rows,lots_of_cols);
00271
00272     for (auto ii = 0; ii < lots_of_rows; ++ii) {
00273         for (auto jj = 0; jj < lots_of_cols; ++jj) {
00274             m11.SetValue(ii,jj,(mtk::Real) ii*lots_of_cols + jj + 1);
00275         }
00276     }
00277
00278     m11.Transpose();
00279
00280     mtk::DenseMatrix m12;
00281
00282     m12 = m11;
00283
00284     mtk::Tools::EndUnitTestNo(8);
00285     mtk::Tools::Assert(m11 == m12);
00286 }
00287
00288 void TestConstructAsVandermondeTransposeAssignmentOperator() {
00289
00290     mtk::Tools::BeginUnitTestNo(9);
00291
00292     bool transpose = false;
00293     int gg_l = 3;
00294     int progression_length = 4;
00295     mtk::Real gg[] = {-0.5, 0.5, 1.5};
00296
00297     mtk::DenseMatrix m13(gg, gg_l ,progression_length, transpose);
00298
00299     mtk::DenseMatrix m14;
00300
00301     m14 = m13;
00302
00303     m13.Transpose();
00304
00305     m14 = m13;
00306

```

```

00307     mtk::Tools::EndUnitTestNo(9);
00308     mtk::Tools::Assert(m13 == m14);
00309 }
00310
00311 int main () {
00312
00313     std::cout << "Testing mtk::DenseMatrix class." << std::endl;
00314
00315     TestDefaultConstructor();
00316     TestConstructorWithNumRowsNumCols();
00317     TestConstructAsIdentity();
00318     TestConstructAsVandermonde();
00319     TestSetValueGetValue();
00320     TestConstructAsVandermondeTranspose();
00321     TestKron();
00322     TestConstructWithNumRowsNumColsAssignmentOperator();
00323     TestConstructAsVandermondeTransposeAssignmentOperator();
00324 }
00325
00326 #else
00327 #include <iostream>
00328 using std::cout;
00329 using std::endl;
00330 int main () {
00331     cout << "This code HAS to be compiled with support for C++11." << endl;
00332     cout << "Exiting..." << endl;
00333 }
00334 #endif


```

17.119 tests/mtk_div_1d_test.cc File Reference

Testing the mimetic 1D divergence, constructed with the CBS algorithm.

```
#include <iostream>
```

Include dependency graph for mtk_div_1d_test.cc:



Functions

- int `main` ()

17.119.1 Detailed Description

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_div_1d_test.cc](#).

17.119.2 Function Documentation**17.119.2.1 int main ()**

Definition at line 288 of file [mtk_div_1d_test.cc](#).

17.120 mtk_div_1d_test.cc

```
00001
00008 /*
00009 Copyright (C) 2015, Computational Science Research Center, San Diego State
00010 University. All rights reserved.
00011
00012 Redistribution and use in source and binary forms, with or without modification,
00013 are permitted provided that the following conditions are met:
00014
00015 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00016 and a copy of the modified files should be reported once modifications are
00017 completed, unless these modifications are made through the project's GitHub
00018 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00019 should be developed and included in any deliverable.
00020
00021 2. Redistributions of source code must be done through direct
00022 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00023
00024 3. Redistributions in binary form must reproduce the above copyright notice,
00025 this list of conditions and the following disclaimer in the documentation and/or
00026 other materials provided with the distribution.
00027
00028 4. Usage of the binary form on proprietary applications shall require explicit
00029 prior written permission from the the copyright holders, and due credit should
00030 be given to the copyright holders.
00031
00032 5. Neither the name of the copyright holder nor the names of its contributors
00033 may be used to endorse or promote products derived from this software without
00034 specific prior written permission.
00035
00036 The copyright holders provide no reassurances that the source code provided does
00037 not infringe any patent, copyright, or any other intellectual property rights of
00038 third parties. The copyright holders disclaim any liability to any recipient for
00039 claims brought against recipient by any third party for infringement of that
00040 parties intellectual property rights.
00041
00042 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00043 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00044 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00045 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00046 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00047 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00048 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00049 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00050 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00051 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00052 */
00053
00054 #if __cplusplus == 201103L
00055
00056 #include <iostream>
00057
00058 #include "mtk.h"
00059
00060 void TestDefaultConstructorFactoryMethodDefault() {
00061
00062     mtk::Tools::BeginUnitTestNo(1);
00063 }
```

```
00064     mtk::Div1D div2;
00065
00066     bool assertion = div2.ConstructDiv1D();
00067
00068     if (!assertion) {
00069         std::cerr << "Mimetic div (2nd order) could not be built." << std::endl;
00070     }
00071
00072     mtk::Tools::EndUnitTestNo(1);
00073     mtk::Tools::Assert(assertion);
00074 }
00075
00076 void TestDefaultConstructorFactoryMethodFourthOrder() {
00077
00078     mtk::Tools::BeginUnitTestNo(2);
00079
00080     mtk::Div1D div4;
00081
00082     bool assertion = div4.ConstructDiv1D(4);
00083
00084     if (!assertion) {
00085         std::cerr << "Mimetic div (4th order) could not be built." << std::endl;
00086     }
00087
00088     mtk::Tools::EndUnitTestNo(2);
00089     mtk::Tools::Assert(assertion);
00090 }
00091
00092 void TestDefaultConstructorFactoryMethodSixthOrder() {
00093
00094     mtk::Tools::BeginUnitTestNo(3);
00095
00096     mtk::Div1D div6;
00097
00098     bool assertion = div6.ConstructDiv1D(6);
00099
00100     if (!assertion) {
00101         std::cerr << "Mimetic div (6th order) could not be built." << std::endl;
00102     }
00103
00104     mtk::Tools::EndUnitTestNo(3);
00105     mtk::Tools::Assert(assertion);
00106 }
00107
00108 void TestDefaultConstructorFactoryMethodEightOrderDefThreshold() {
00109
00110     mtk::Tools::BeginUnitTestNo(4);
00111
00112     mtk::Div1D div8;
00113
00114     bool assertion = div8.ConstructDiv1D(8);
00115
00116     if (!assertion) {
00117         std::cerr << "Mimetic div (8th order) could not be built." << std::endl;
00118     }
00119
00120     mtk::Tools::EndUnitTestNo(4);
00121     mtk::Tools::Assert(assertion);
00122 }
00123
00124 void TestDefaultConstructorFactoryMethodTenthOrderDefThreshold() {
00125
00126     mtk::Tools::BeginUnitTestNo(5);
00127
00128     mtk::Div1D div10;
00129
00130     bool assertion = div10.ConstructDiv1D(10);
00131
00132     if (!assertion) {
00133         std::cerr << "Mimetic div (10th order) could not be built." << std::endl;
00134     }
00135
00136     mtk::Tools::EndUnitTestNo(5);
00137     mtk::Tools::Assert(assertion);
00138 }
00139
00140 void TestDefaultConstructorFactoryMethodTwelfthOrderDefThreshold() {
00141
00142     mtk::Tools::BeginUnitTestNo(6);
00143
00144     mtk::Div1D div12;
```



```

00145
00146     bool assertion = div12.ConstructDiv1D(12);
00147
00148     if (!assertion) {
00149         std::cerr << "Mimetic div (12th order) could not be built." << std::endl;
00150     }
00151
00152     mtk::Tools::EndUnitTestNo(6);
00153     mtk::Tools::Assert(assertion);
00154 }
00155
00156 void TestDefaultConstructorFactoryMethodFourteenthOrderDefThreshold() {
00157
00158     mtk::Tools::BeginUnitTestNo(7);
00159
00160     mtk::Div1D div14;
00161
00162     bool assertion = div14.ConstructDiv1D(14);
00163
00164     if (!assertion) {
00165         std::cerr << "Mimetic div (14th order) could not be built." << std::endl;
00166     }
00167
00168     mtk::Tools::EndUnitTestNo(7);
00169     mtk::Tools::Assert(assertion);
00170 }
00171
00172 void TestSecondOrderReturnAsDenseMatrixWithGrid() {
00173
00174     mtk::Tools::BeginUnitTestNo(8);
00175
00176     mtk::Div1D div2;
00177
00178     bool assertion = div2.ConstructDiv1D();
00179
00180     if (!assertion) {
00181         std::cerr << "Mimetic div (2nd order) could not be built." << std::endl;
00182     }
00183
00184     mtk::UniStgGrid1D grid(0.0, 1.0, 5);
00185
00186     mtk::DenseMatrix div2m(div2.ReturnAsDenseMatrix(grid));
00187
00188     int rr{7};
00189     int cc{6};
00190
00191     mtk::DenseMatrix ref(rr, cc);
00192
00193     // Row 2.
00194     ref.SetValue(1,0,-5.0);
00195     ref.SetValue(1,1,5.0);
00196     ref.SetValue(1,2,0.0);
00197     ref.SetValue(1,3,0.0);
00198     ref.SetValue(1,4,0.0);
00199     ref.SetValue(1,5,0.0);
00200     ref.SetValue(1,6,0.0);
00201
00202     // Row 3.
00203     ref.SetValue(2,0,0.0);
00204     ref.SetValue(2,1,-5.0);
00205     ref.SetValue(2,2,5.0);
00206     ref.SetValue(2,3,0.0);
00207     ref.SetValue(2,4,0.0);
00208     ref.SetValue(2,5,0.0);
00209     ref.SetValue(2,6,0.0);
00210
00211     // Row 4.
00212     ref.SetValue(3,0,0.0);
00213     ref.SetValue(3,1,0.0);
00214     ref.SetValue(3,2,-5.0);
00215     ref.SetValue(3,3,5.0);
00216     ref.SetValue(3,4,0.0);
00217     ref.SetValue(3,5,0.0);
00218     ref.SetValue(3,6,0.0);
00219
00220     // Row 5.
00221     ref.SetValue(4,0,0.0);
00222     ref.SetValue(4,1,0.0);
00223     ref.SetValue(4,2,0.0);
00224     ref.SetValue(4,3,-5.0);
00225     ref.SetValue(4,4,5.0);

```

```

00226     ref.SetValue(4,5,0.0);
00227     ref.SetValue(4,6,0.0);
00228
00229     // Row 6.
00230     ref.SetValue(5,0,0.0);
00231     ref.SetValue(5,1,0.0);
00232     ref.SetValue(5,2,0.0);
00233     ref.SetValue(5,3,0.0);
00234     ref.SetValue(5,4,-5.0);
00235     ref.SetValue(5,5,5.0);
00236     ref.SetValue(5,6,0.0);
00237
00238     assertion = assertion && (div2m == ref);
00239
00240     mtk::Tools::EndUnitTestNo(8);
00241     mtk::Tools::Assert(assertion);
00242 }
00243
00244 void TestFourthOrderReturnAsDenseMatrixWithGrid() {
00245
00246     mtk::Tools::BeginUnitTestNo(9);
00247
00248     mtk::Div1D div4;
00249
00250     bool assertion = div4.ConstructDiv1D(4);
00251
00252     if (!assertion) {
00253         std::cerr << "Mimetic div (4th order) could not be built." << std::endl;
00254     }
00255
00256     std::cout << div4 << std::endl;
00257
00258     mtk::UniStgGrid1D grid(0.0, 1.0, 11);
00259
00260     std::cout << grid << std::endl;
00261
00262     mtk::DenseMatrix div4m(div4.ReturnAsDenseMatrix(grid));
00263
00264     std::cout << div4m << std::endl;
00265
00266     mtk::Tools::EndUnitTestNo(9);
00267 }
00268
00269 int main () {
00270
00271     std::cout << "Testing mtk::Div1D class." << std::endl;
00272
00273     TestDefaultConstructorFactoryMethodDefault();
00274     TestDefaultConstructorFactoryMethodFourthOrder();
00275     TestDefaultConstructorFactoryMethodSixthOrder();
00276     TestDefaultConstructorFactoryMethodEightOrderDefThreshold();
00277     TestDefaultConstructorFactoryMethodTenthOrderDefThreshold();
00278     TestDefaultConstructorFactoryMethodTwelfthOrderDefThreshold();
00279     TestDefaultConstructorFactoryMethodFourteenthOrderDefThreshold();
00280     TestSecondOrderReturnAsDenseMatrixWithGrid();
00281     TestFourthOrderReturnAsDenseMatrixWithGrid();
00282 }
00283
00284 #else
00285 #include <iostream>
00286 using std::cout;
00287 using std::endl;
00288 int main () {
00289     cout << "This code HAS to be compiled with support for C++11." << endl;
00290     cout << "Exiting..." << endl;
00291 }
00292 #endif


```

17.121 tests/mtk_div_2d_test.cc File Reference

Test file for the `mtk::Div2D` class.

```
#include <iostream>
```

Include dependency graph for mtk_div_2d_test.cc:



Functions

- int [main](#) ()

17.121.1 Detailed Description

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_div_2d_test.cc](#).

17.121.2 Function Documentation

17.121.2.1 int main ()

Definition at line [139](#) of file [mtk_div_2d_test.cc](#).

17.122 mtk_div_2d_test.cc

```

00001
00008 /*
00009 Copyright (C) 2015, Computational Science Research Center, San Diego State
00010 University. All rights reserved.
00011
00012 Redistribution and use in source and binary forms, with or without modification,
00013 are permitted provided that the following conditions are met:
00014
00015 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00016 and a copy of the modified files should be reported once modifications are
00017 completed, unless these modifications are made through the project's GitHub
00018 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00019 should be developed and included in any deliverable.
00020
00021 2. Redistributions of source code must be done through direct
00022 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00023
00024 3. Redistributions in binary form must reproduce the above copyright notice,

```

```

00025 this list of conditions and the following disclaimer in the documentation and/or
00026 other materials provided with the distribution.
00027
00028 4. Usage of the binary form on proprietary applications shall require explicit
00029 prior written permission from the the copyright holders, and due credit should
00030 be given to the copyright holders.
00031
00032 5. Neither the name of the copyright holder nor the names of its contributors
00033 may be used to endorse or promote products derived from this software without
00034 specific prior written permission.
00035
00036 The copyright holders provide no reassurances that the source code provided does
00037 not infringe any patent, copyright, or any other intellectual property rights of
00038 third parties. The copyright holders disclaim any liability to any recipient for
00039 claims brought against recipient by any third party for infringement of that
00040 parties intellectual property rights.
00041
00042 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00043 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00044 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00045 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00046 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00047 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00048 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00049 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00050 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00051 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00052 */
00053
00054 #if __cplusplus == 201103L
00055 #include <cmath>
00056 #include <ctime>
00057 #include <iostream>
00058
00059 #include "mtk.h"
00060
00061 void TestDefaultConstructorFactory() {
00062
00063     mtk::Tools::BeginUnitTestNo(1);
00064
00065     mtk::Div2D dd;
00066
00067     mtk::Real aa = 0.0;
00068     mtk::Real bb = 1.0;
00069     mtk::Real cc = 0.0;
00070     mtk::Real ee = 1.0;
00071
00072     int nn = 5;
00073     int mm = 5;
00074
00075     mtk::UniStgGrid2D ddg(aa, bb, nn, cc, ee, mm);
00076
00077     bool assertion = dd.ConstructDiv2D(ddg);
00078
00079     if (!assertion) {
00080         std::cerr << "Mimetic div (2nd order) could not be built." << std::endl;
00081     }
00082
00083     mtk::Tools::EndUnitTestNo(1);
00084     mtk::Tools::Assert(assertion);
00085 }
00086
00087 void TestReturnAsDenseMatrixWriteToFile() {
00088
00089     mtk::Tools::BeginUnitTestNo(2);
00090
00091     mtk::Div2D dd;
00092
00093     mtk::Real aa = 0.0;
00094     mtk::Real bb = 1.0;
00095     mtk::Real cc = 0.0;
00096     mtk::Real ee = 1.0;
00097
00098     int nn = 5;
00099     int mm = 5;
00100
00101     mtk::UniStgGrid2D ddg(aa, bb, nn, cc, ee, mm);
00102
00103     bool assertion = dd.ConstructDiv2D(ddg);
00104
00105

```

```

00106
00107     if (!assertion) {
00108         std::cerr << "Mimetic div (2nd order) could not be built." << std::endl;
00109     }
00110
00111     mtk::DenseMatrix ddm(dd.ReturnAsDenseMatrix());
00112
00113     assertion = assertion && (ddm.num_rows() != mtk::kZero);
00114
00115     std::cout << ddm << std::endl;
00116
00117     assertion = assertion && ddm.WriteToFile("mtk_div_2d_test_02.dat");
00118
00119     if (!assertion) {
00120         std::cerr << "Error writing to file." << std::endl;
00121     }
00122
00123     mtk::Tools::EndUnitTestNo(2);
00124     mtk::Tools::Assert(assertion);
00125 }
00126
00127 int main () {
00128
00129     std::cout << "Testing mtk::Div2D class." << std::endl;
00130
00131     TestDefaultConstructorFactory();
00132     TestReturnAsDenseMatrixWriteToFile();
00133 }
00134
00135 #else
00136 #include <iostream>
00137 using std::cout;
00138 using std::endl;
00139 int main () {
00140     cout << "This code HAS to be compiled with support for C++11." << endl;
00141     cout << "Exiting..." << endl;
00142 }
00143 #endif


```

17.123 tests/mtk_div_3d_test.cc File Reference

Test file for the `mtk::Div3D` class.

```
#include <iostream>
```

Include dependency graph for `mtk_div_3d_test.cc`:



Functions

- `int main ()`

17.123.1 Detailed Description

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_div_3d_test.cc](#).

17.123.2 Function Documentation

17.123.2.1 int main ()

Definition at line 145 of file [mtk_div_3d_test.cc](#).

17.124 mtk_div_3d_test.cc

```
00001
00008 /*
00009 Copyright (C) 2015, Computational Science Research Center, San Diego State
00010 University. All rights reserved.
00011
00012 Redistribution and use in source and binary forms, with or without modification,
00013 are permitted provided that the following conditions are met:
00014
00015 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00016 and a copy of the modified files should be reported once modifications are
00017 completed, unless these modifications are made through the project's GitHub
00018 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00019 should be developed and included in any deliverable.
00020
00021 2. Redistributions of source code must be done through direct
00022 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00023
00024 3. Redistributions in binary form must reproduce the above copyright notice,
00025 this list of conditions and the following disclaimer in the documentation and/or
00026 other materials provided with the distribution.
00027
00028 4. Usage of the binary form on proprietary applications shall require explicit
00029 prior written permission from the the copyright holders, and due credit should
00030 be given to the copyright holders.
00031
00032 5. Neither the name of the copyright holder nor the names of its contributors
00033 may be used to endorse or promote products derived from this software without
00034 specific prior written permission.
00035
00036 The copyright holders provide no reassurances that the source code provided does
00037 not infringe any patent, copyright, or any other intellectual property rights of
00038 third parties. The copyright holders disclaim any liability to any recipient for
00039 claims brought against recipient by any third party for infringement of that
00040 parties intellectual property rights.
00041
00042 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00043 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00044 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00045 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00046 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00047 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00048 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00049 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00050 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00051 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00052 */
00053
00054 #if __cplusplus == 201103L
00055
00056 #include <cmath>
00057 #include <ctime>
00058
00059 #include <iostream>
00060
```

```

00061 #include "mtk.h"
00062
00063 void TestDefaultConstructorFactory() {
00064
00065     mtk::Tools::BeginUnitTestNo(1);
00066
00067     mtk::Div3D div;
00068
00069     mtk::Real aa = 0.0;
00070     mtk::Real bb = 1.0;
00071     mtk::Real cc = 0.0;
00072     mtk::Real dd = 1.0;
00073     mtk::Real ee = 0.0;
00074     mtk::Real ff = 1.0;
00075
00076     int nn = 5;
00077     int mm = 5;
00078     int oo = 5;
00079
00080     mtk::UniStgGrid3D divg(aa, bb, nn, cc, dd, mm, ee, ff, oo);
00081
00082     bool assertion = div.ConstructDiv3D(divg);
00083
00084     if (!assertion) {
00085         std::cerr << "Mimetic div (2nd order) could not be built." << std::endl;
00086     }
00087
00088     mtk::Tools::EndUnitTestNo(1);
00089     mtk::Tools::Assert(assertion);
00090 }
00091
00092 void TestReturnAsDenseMatrixWriteToFile() {
00093
00094     mtk::Tools::BeginUnitTestNo(2);
00095
00096     mtk::Div3D div;
00097
00098     mtk::Real aa = 0.0;
00099     mtk::Real bb = 1.0;
00100     mtk::Real cc = 0.0;
00101     mtk::Real dd = 1.0;
00102     mtk::Real ee = 0.0;
00103     mtk::Real ff = 1.0;
00104
00105     int nn = 5;
00106     int mm = 5;
00107     int oo = 5;
00108
00109     mtk::UniStgGrid3D divg(aa, bb, nn, cc, dd, mm, ee, ff, oo);
00110
00111     bool assertion = div.ConstructDiv3D(divg);
00112
00113     if (!assertion) {
00114         std::cerr << "Mimetic div (2nd order) could not be built." << std::endl;
00115     }
00116
00117     mtk::DenseMatrix divm(div.ReturnAsDenseMatrix());
00118
00119     assertion = assertion && (divm.num_rows() != mtk::kZero);
00120
00121     std::cout << divm << std::endl;
00122
00123     assertion = assertion && divm.WriteToFile("mtk_div_3d_test_02.dat");
00124
00125     if (!assertion) {
00126         std::cerr << "Error writing to file." << std::endl;
00127     }
00128
00129     mtk::Tools::EndUnitTestNo(2);
00130     mtk::Tools::Assert(assertion);
00131 }
00132
00133 int main () {
00134
00135     std::cout << "Testing mtk::Div3D class." << std::endl;
00136
00137     TestDefaultConstructorFactory();
00138     TestReturnAsDenseMatrixWriteToFile();
00139 }
00140
00141 #else

```


```
00142 #include <iostream>
00143 using std::cout;
00144 using std::endl;
00145 int main () {
00146     cout << "This code HAS to be compiled with support for C++11." << endl;
00147     cout << "Exiting..." << endl;
00148 }
00149 #endif
```

17.125 tests/mtk_glpk_adapter_test.cc File Reference

Test file for the [mtk::GLPKAdapter](#) class.

```
#include <iostream>
```

Include dependency graph for mtk_glpk_adapter_test.cc:



Functions

- int [main](#) ()

17.125.1 Detailed Description

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Todo Test the [mtk::GLPKAdapter](#) class.

Definition in file [mtk_glpk_adapter_test.cc](#).

17.125.2 Function Documentation

17.125.2.1 int main ()

Definition at line [81](#) of file [mtk_glpk_adapter_test.cc](#).

17.126 mtk_glpk_adapter_test.cc


```
00001
00010 /*
00011 Copyright (C) 2015, Computational Science Research Center, San Diego State
00012 University. All rights reserved.
00013
00014 Redistribution and use in source and binary forms, with or without modification,
00015 are permitted provided that the following conditions are met:
00016
00017 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00018 and a copy of the modified files should be reported once modifications are
00019 completed, unless these modifications are made through the project's GitHub
00020 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00021 should be developed and included in any deliverable.
00022
00023 2. Redistributions of source code must be done through direct
00024 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00025
00026 3. Redistributions in binary form must reproduce the above copyright notice,
00027 this list of conditions and the following disclaimer in the documentation and/or
00028 other materials provided with the distribution.
00029
00030 4. Usage of the binary form on proprietary applications shall require explicit
00031 prior written permission from the the copyright holders, and due credit should
00032 be given to the copyright holders.
00033
00034 5. Neither the name of the copyright holder nor the names of its contributors
00035 may be used to endorse or promote products derived from this software without
00036 specific prior written permission.
00037
00038 The copyright holders provide no reassurances that the source code provided does
00039 not infringe any patent, copyright, or any other intellectual property rights of
00040 third parties. The copyright holders disclaim any liability to any recipient for
00041 claims brought against recipient by any third party for infringement of that
00042 parties intellectual property rights.
00043
00044 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00045 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00046 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00047 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00048 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00049 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00050 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00051 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00052 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00053 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00054 */
00055
00056 #if __cplusplus == 201103L
00057
00058 #include <iostream>
00059 #include <ctime>
00060
00061 #include "mtk.h"
00062
00063 void Test1() {
00064
00065     mtk::Tools::BeginUnitTestNo(1);
00066
00067     mtk::Tools::EndUnitTestNo(1);
00068 }
00069
00070 int main () {
00071
00072     std::cout << "Testing mtk::GLPKAdapter class." << std::endl;
00073
00074     Test1();
00075 }
00076
00077 #else
00078 #include <iostream>
00079 using std::cout;
00080 using std::endl;
00081 int main () {
00082     cout << "This code HAS to be compiled with support for C++11." << endl;
00083     cout << "Exiting..." << endl;
00084 }
00085 #endif
```

17.127 tests/mtk_grad_1d_test.cc File Reference

Testing the mimetic 1D gradient, constructed with the CBS algorithm.

```
#include <iostream>
```

Include dependency graph for mtk_grad_1d_test.cc:



Functions

- int [main](#) ()

17.127.1 Detailed Description

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_grad_1d_test.cc](#).

17.127.2 Function Documentation

17.127.2.1 int main ()

Definition at line [319](#) of file [mtk_grad_1d_test.cc](#).

17.128 mtk_grad_1d_test.cc

```

00001
00008 /*
00009 Copyright (C) 2015, Computational Science Research Center, San Diego State
00010 University. All rights reserved.
00011
00012 Redistribution and use in source and binary forms, with or without modification,
00013 are permitted provided that the following conditions are met:
00014
00015 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00016 and a copy of the modified files should be reported once modifications are
00017 completed, unless these modifications are made through the project's GitHub
00018 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications

```

```

00019 should be developed and included in any deliverable.
00020
00021 2. Redistributions of source code must be done through direct
00022 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00023
00024 3. Redistributions in binary form must reproduce the above copyright notice,
00025 this list of conditions and the following disclaimer in the documentation and/or
00026 other materials provided with the distribution.
00027
00028 4. Usage of the binary form on proprietary applications shall require explicit
00029 prior written permission from the the copyright holders, and due credit should
00030 be given to the copyright holders.
00031
00032 5. Neither the name of the copyright holder nor the names of its contributors
00033 may be used to endorse or promote products derived from this software without
00034 specific prior written permission.
00035
00036 The copyright holders provide no reassurances that the source code provided does
00037 not infringe any patent, copyright, or any other intellectual property rights of
00038 third parties. The copyright holders disclaim any liability to any recipient for
00039 claims brought against recipient by any third party for infringement of that
00040 parties intellectual property rights.
00041
00042 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00043 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00044 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00045 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00046 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00047 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00048 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00049 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00050 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00051 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00052 */
00053
00054 #if __cplusplus == 201103L
00055
00056 #include <iostream>
00057
00058 #include "mtk.h"
00059
00060 void TestDefaultConstructorFactoryMethodDefault() {
00061
00062     mtk::Tools::BeginUnitTestNo(1);
00063
00064     mtk::Grad1D grad2;
00065
00066     bool assertion = grad2.ConstructGrad1D();
00067
00068     if (!assertion) {
00069         std::cerr << "Mimetic grad (2nd order) could not be built." << std::endl;
00070     }
00071
00072     std::cout << grad2 << std::endl;
00073
00074     mtk::Tools::EndUnitTestNo(1);
00075     mtk::Tools::Assert(assertion);
00076 }
00077
00078 void TestDefaultConstructorFactoryMethodFourthOrder() {
00079
00080     mtk::Tools::BeginUnitTestNo(2);
00081
00082     mtk::Grad1D grad4;
00083
00084     bool assertion = grad4.ConstructGrad1D(4);
00085
00086     if (!assertion) {
00087         std::cerr << "Mimetic grad (4th order) could not be built." << std::endl;
00088     }
00089
00090     std::cout << grad4 << std::endl;
00091
00092     mtk::Tools::EndUnitTestNo(2);
00093     mtk::Tools::Assert(assertion);
00094 }
00095
00096 void TestDefaultConstructorFactoryMethodSixthOrder() {
00097
00098     mtk::Tools::BeginUnitTestNo(3);
00099

```

```

00100
00101     mtk::Grad1D grad6;
00102
00103     bool assertion = grad6.ConstructGrad1D(6);
00104
00105     if (!assertion) {
00106         std::cerr << "Mimetic grad (6th order) could not be built." << std::endl;
00107     }
00108
00109     std::cout << grad6 << std::endl;
00110
00111     mtk::Tools::EndUnitTestNo(3);
00112     mtk::Tools::Assert(assertion);
00113 }
00114
00115 void TestDefaultConstructorFactoryMethodEightOrderDefThreshold() {
00116
00117     mtk::Tools::BeginUnitTestNo(4);
00118
00119     mtk::Grad1D grad8;
00120
00121     bool assertion = grad8.ConstructGrad1D(8);
00122
00123     if (!assertion) {
00124         std::cerr << "Mimetic grad (8th order) could not be built." << std::endl;
00125     }
00126
00127     std::cout << grad8 << std::endl;
00128
00129     mtk::Tools::EndUnitTestNo(4);
00130     mtk::Tools::Assert(assertion);
00131 }
00132
00133 void TestDefaultConstructorFactoryMethodTenthOrderDefThreshold() {
00134
00135     mtk::Tools::BeginUnitTestNo(5);
00136
00137     mtk::Grad1D grad10;
00138
00139     bool assertion = grad10.ConstructGrad1D(10);
00140
00141     if (!assertion) {
00142         std::cerr << "Mimetic grad (10th order) could not be built." << std::endl;
00143     }
00144
00145     std::cout << grad10 << std::endl;
00146
00147     mtk::Tools::EndUnitTestNo(5);
00148     mtk::Tools::Assert(assertion);
00149 }
00150
00151 void TestReturnAsDenseMatrixWithGrid() {
00152
00153     mtk::Tools::BeginUnitTestNo(6);
00154
00155     mtk::Grad1D grad2;
00156
00157     bool assertion = grad2.ConstructGrad1D();
00158
00159     if (!assertion) {
00160         std::cerr << "Mimetic grad (2nd order) could not be built." << std::endl;
00161     }
00162
00163     mtk::UniStgGrid1D grid(0.0, 1.0, 5);
00164
00165     mtk::DenseMatrix grad2m(grad2.ReturnAsDenseMatrix(grid));
00166
00167     int rr{6};
00168     int cc{7};
00169
00170     mtk::DenseMatrix ref(rr, cc);
00171
00172     // Row 1.
00173     ref.SetValue(0,0,-13.3333);
00174     ref.SetValue(0,1,15);
00175     ref.SetValue(0,2,-1.66667);
00176     ref.SetValue(0,3,0.0);
00177     ref.SetValue(0,4,0.0);
00178     ref.SetValue(0,5,0.0);
00179     ref.SetValue(0,6,0.0);
00180

```

```

00181 // Row 2.
00182 ref.SetValue(1,0,0.0);
00183 ref.SetValue(1,1,-5.0);
00184 ref.SetValue(1,2,5.0);
00185 ref.SetValue(1,3,0.0);
00186 ref.SetValue(1,4,0.0);
00187 ref.SetValue(1,5,0.0);
00188 ref.SetValue(1,6,0.0);
00189
00190 // Row 3.
00191 ref.SetValue(2,0,0.0);
00192 ref.SetValue(2,1,0.0);
00193 ref.SetValue(2,2,-5.0);
00194 ref.SetValue(2,3,5.0);
00195 ref.SetValue(2,4,0.0);
00196 ref.SetValue(2,5,0.0);
00197 ref.SetValue(2,6,0.0);
00198
00199 // Row 4.
00200 ref.SetValue(3,0,0.0);
00201 ref.SetValue(3,1,0.0);
00202 ref.SetValue(3,2,0.0);
00203 ref.SetValue(3,3,-5.0);
00204 ref.SetValue(3,4,5.0);
00205 ref.SetValue(3,5,0.0);
00206 ref.SetValue(3,6,0.0);
00207
00208 // Row 5.
00209 ref.SetValue(4,0,0.0);
00210 ref.SetValue(4,1,0.0);
00211 ref.SetValue(4,2,0.0);
00212 ref.SetValue(4,3,0.0);
00213 ref.SetValue(4,4,-5.0);
00214 ref.SetValue(4,5,5.0);
00215 ref.SetValue(4,6,0.0);
00216
00217 // Row 6.
00218 ref.SetValue(5,0,0.0);
00219 ref.SetValue(5,1,0.0);
00220 ref.SetValue(5,2,0.0);
00221 ref.SetValue(5,3,0.0);
00222 ref.SetValue(5,4,1.66667);
00223 ref.SetValue(5,5,-15.0);
00224 ref.SetValue(5,6,13.3333);
00225
00226 mtk::Tools::EndUnitTestNo(6);
00227 mtk::Tools::Assert(grad2m == ref);
00228 }
00229
00230 void TestReturnAsDimensionlessDenseMatrix() {
00231
00232     mtk::Tools::BeginUnitTestNo(7);
00233
00234     mtk::Grad1D grad4;
00235
00236     bool assertion = grad4.ConstructGrad1D(4);
00237
00238     if (!assertion) {
00239         std::cerr << "Mimetic grad (4th order) could not be built." << std::endl;
00240     }
00241
00242     mtk::DenseMatrix grad4m(grad4.ReturnAsDimensionlessDenseMatrix
00243 (10));
00244
00245     std::cout << grad4m << std::endl;
00246
00247     mtk::Tools::EndUnitTestNo(7);
00248     mtk::Tools::Assert(assertion);
00249 }
00250
00251 void TestWriteToFile() {
00252
00253     mtk::Tools::BeginUnitTestNo(8);
00254
00255     mtk::Grad1D grad2;
00256
00257     bool assertion = grad2.ConstructGrad1D();
00258
00259     if (!assertion) {
00260         std::cerr << "Mimetic grad (2nd order) could not be built." << std::endl;
00261     }

```

```

00261
00262     mtk::UniStgGrid1D grid(0.0, 1.0, 50);
00263
00264     mtk::DenseMatrix grad2m(grad2.ReturnAsDenseMatrix(grid));
00265
00266     std::cout << grad2m << std::endl;
00267
00268     assertion = assertion && grad2m.WriteToFile("mtk_grad_1d_test_08.dat");
00269
00270     if(!assertion) {
00271         std::cerr << "Error writing to file." << std::endl;
00272     }
00273
00274     mtk::Tools::EndUnitTestNo(8);
00275     mtk::Tools::Assert(assertion);
00276 }
00277
00278 void TestMimBndy() {
00279
00280     mtk::Tools::BeginUnitTestNo(9);
00281
00282     mtk::Grad1D grad2;
00283
00284     bool assertion = grad2.ConstructGrad1D();
00285
00286     if (!assertion) {
00287         std::cerr << "Mimetic grad (2nd order) could not be built." << std::endl;
00288     }
00289
00290     std::cout << grad2 << std::endl;
00291
00292     mtk::DenseMatrix grad2m(grad2.mim_bndy());
00293
00294     std::cout << grad2m << std::endl;
00295
00296     mtk::Tools::EndUnitTestNo(9);
00297     mtk::Tools::Assert(assertion);
00298 }
00299
00300 int main () {
00301
00302     std::cout << "Testing mtk::Grad1D class." << std::endl;
00303
00304     TestDefaultConstructorFactoryMethodDefault();
00305     TestDefaultConstructorFactoryMethodFourthOrder();
00306     TestDefaultConstructorFactoryMethodSixthOrder();
00307     TestDefaultConstructorFactoryMethodEightOrderDefThreshold();
00308     TestDefaultConstructorFactoryMethodTenthOrderDefThreshold();
00309     TestReturnAsDenseMatrixWithGrid();
00310     TestReturnAsDimensionlessDenseMatrix();
00311     TestWriteToFile();
00312     TestMimBndy();
00313 }
00314
00315 #else
00316 #include <iostream>
00317 using std::cout;
00318 using std::endl;
00319 int main () {
00320     cout << "This code HAS to be compiled with support for C++11." << endl;
00321     cout << "Exiting..." << endl;
00322 }
00323 #endif


```

17.129 tests/mtk_grad_2d_test.cc File Reference

Test file for the [mtk::Grad2D](#) class.

```
#include <iostream>
```

Include dependency graph for mtk_grad_2d_test.cc:



Functions

- int [main](#) ()

17.129.1 Detailed Description

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_grad_2d_test.cc](#).

17.129.2 Function Documentation

17.129.2.1 int main ()

Definition at line [139](#) of file [mtk_grad_2d_test.cc](#).

17.130 mtk_grad_2d_test.cc

```

00001
00008 /*
00009 Copyright (C) 2015, Computational Science Research Center, San Diego State
00010 University. All rights reserved.
00011
00012 Redistribution and use in source and binary forms, with or without modification,
00013 are permitted provided that the following conditions are met:
00014
00015 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00016 and a copy of the modified files should be reported once modifications are
00017 completed, unless these modifications are made through the project's GitHub
00018 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00019 should be developed and included in any deliverable.
00020
00021 2. Redistributions of source code must be done through direct
00022 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00023
00024 3. Redistributions in binary form must reproduce the above copyright notice,

```

```

00025 this list of conditions and the following disclaimer in the documentation and/or
00026 other materials provided with the distribution.
00027
00028 4. Usage of the binary form on proprietary applications shall require explicit
00029 prior written permission from the the copyright holders, and due credit should
00030 be given to the copyright holders.
00031
00032 5. Neither the name of the copyright holder nor the names of its contributors
00033 may be used to endorse or promote products derived from this software without
00034 specific prior written permission.
00035
00036 The copyright holders provide no reassurances that the source code provided does
00037 not infringe any patent, copyright, or any other intellectual property rights of
00038 third parties. The copyright holders disclaim any liability to any recipient for
00039 claims brought against recipient by any third party for infringement of that
00040 parties intellectual property rights.
00041
00042 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00043 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00044 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00045 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00046 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00047 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00048 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00049 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00050 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00051 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00052 */
00053
00054 #if __cplusplus == 201103L
00055
00056 #include <cmath>
00057 #include <ctime>
00058
00059 #include <iostream>
00060
00061 #include "mtk.h"
00062
00063 void TestDefaultConstructorFactory() {
00064
00065     mtk::Tools::BeginUnitTestNo(1);
00066
00067     mtk::Grad2D gg;
00068
00069     mtk::Real aa = 0.0;
00070     mtk::Real bb = 1.0;
00071     mtk::Real cc = 0.0;
00072     mtk::Real dd = 1.0;
00073
00074     int nn = 5;
00075     int mm = 5;
00076
00077     mtk::UniStgGrid2D ggg(aa, bb, nn, cc, dd, mm, mtk::VECTOR);
00078
00079     bool assertion = gg.ConstructGrad2D(ggg);
00080
00081     if (!assertion) {
00082         std::cerr << "Mimetic grad (2nd order) could not be built." << std::endl;
00083     }
00084
00085     mtk::Tools::EndUnitTestNo(1);
00086     mtk::Tools::Assert(assertion);
00087 }
00088
00089 void TestReturnAsDenseMatrixWriteToFile() {
00090
00091     mtk::Tools::BeginUnitTestNo(2);
00092
00093     mtk::Grad2D gg;
00094
00095     mtk::Real aa = 0.0;
00096     mtk::Real bb = 1.0;
00097     mtk::Real cc = 0.0;
00098     mtk::Real dd = 1.0;
00099
00100     int nn = 5;
00101     int mm = 5;
00102
00103     mtk::UniStgGrid2D ggg(aa, bb, nn, cc, dd, mm, mtk::VECTOR);
00104
00105     bool assertion = gg.ConstructGrad2D(ggg);

```



```

00106
00107     if (!assertion) {
00108         std::cerr << "Mimetic grad (2nd order) could not be built." << std::endl;
00109     }
00110
00111     mtk::DenseMatrix ggm(gg.ReturnAsDenseMatrix());
00112
00113     assertion = assertion && (ggm.num_rows() != mtk::kZero);
00114
00115     std::cout << ggm << std::endl;
00116
00117     assertion = assertion && ggm.WriteToFile("mtk_grad_2d_test_02.dat");
00118
00119     if (!assertion) {
00120         std::cerr << "Error writing to file." << std::endl;
00121     }
00122
00123     mtk::Tools::EndUnitTestNo(2);
00124     mtk::Tools::Assert(assertion);
00125 }
00126
00127 int main () {
00128
00129     std::cout << "Testing mtk::Grad2D class." << std::endl;
00130
00131     TestDefaultConstructorFactory();
00132     TestReturnAsDenseMatrixWriteToFile();
00133 }
00134
00135 #else
00136 #include <iostream>
00137 using std::cout;
00138 using std::endl;
00139 int main () {
00140     cout << "This code HAS to be compiled with support for C++11." << endl;
00141     cout << "Exiting..." << endl;
00142 }
00143 #endif


```

17.131 tests/mtk_grad_3d_test.cc File Reference

Test file for the `mtk::Grad3D` class.

```
#include <iostream>
```

Include dependency graph for `mtk_grad_3d_test.cc`:



Functions

- int `main` ()

17.131.1 Detailed Description

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_grad_3d_test.cc](#).

17.131.2 Function Documentation

17.131.2.1 int main ()

Definition at line 145 of file [mtk_grad_3d_test.cc](#).

17.132 mtk_grad_3d_test.cc

```
00001
00008 /*
00009 Copyright (C) 2015, Computational Science Research Center, San Diego State
00010 University. All rights reserved.
00011
00012 Redistribution and use in source and binary forms, with or without modification,
00013 are permitted provided that the following conditions are met:
00014
00015 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00016 and a copy of the modified files should be reported once modifications are
00017 completed, unless these modifications are made through the project's GitHub
00018 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00019 should be developed and included in any deliverable.
00020
00021 2. Redistributions of source code must be done through direct
00022 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00023
00024 3. Redistributions in binary form must reproduce the above copyright notice,
00025 this list of conditions and the following disclaimer in the documentation and/or
00026 other materials provided with the distribution.
00027
00028 4. Usage of the binary form on proprietary applications shall require explicit
00029 prior written permission from the the copyright holders, and due credit should
00030 be given to the copyright holders.
00031
00032 5. Neither the name of the copyright holder nor the names of its contributors
00033 may be used to endorse or promote products derived from this software without
00034 specific prior written permission.
00035
00036 The copyright holders provide no reassurances that the source code provided does
00037 not infringe any patent, copyright, or any other intellectual property rights of
00038 third parties. The copyright holders disclaim any liability to any recipient for
00039 claims brought against recipient by any third party for infringement of that
00040 parties intellectual property rights.
00041
00042 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00043 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00044 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00045 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00046 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00047 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00048 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00049 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00050 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00051 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00052 */
00053
00054 #if __cplusplus == 201103L
00055
00056 #include <cmath>
00057 #include <ctime>
00058
00059 #include <iostream>
00060
```

```

00061 #include "mtk.h"
00062
00063 void TestDefaultConstructorFactory() {
00064
00065     mtk::Tools::BeginUnitTestNo(1);
00066
00067     mtk::Grad3D gg;
00068
00069     mtk::Real aa = 0.0;
00070     mtk::Real bb = 1.0;
00071     mtk::Real cc = 0.0;
00072     mtk::Real dd = 1.0;
00073     mtk::Real ee = 0.0;
00074     mtk::Real ff = 1.0;
00075
00076     int nn = 5;
00077     int mm = 5;
00078     int oo = 5;
00079
00080     mtk::UniStgGrid3D ggg(aa, bb, nn, cc, dd, mm, ee, ff, oo,
mtk::VECTOR);
00081
00082     bool assertion = gg.ConstructGrad3D(ggg);
00083
00084     if (!assertion) {
00085         std::cerr << "Mimetic grad (2nd order) could not be built." << std::endl;
00086     }
00087
00088     mtk::Tools::EndUnitTestNo(1);
00089     mtk::Tools::Assert(assertion);
00090 }
00091
00092 void TestReturnAsDenseMatrixWriteToFile() {
00093
00094     mtk::Tools::BeginUnitTestNo(2);
00095
00096     mtk::Grad3D gg;
00097
00098     mtk::Real aa = 0.0;
00099     mtk::Real bb = 1.0;
00100     mtk::Real cc = 0.0;
00101     mtk::Real dd = 1.0;
00102     mtk::Real ee = 0.0;
00103     mtk::Real ff = 1.0;
00104
00105     int nn = 5;
00106     int mm = 5;
00107     int oo = 5;
00108
00109     mtk::UniStgGrid3D ggg(aa, bb, nn, cc, dd, mm, ee, ff, oo,
mtk::VECTOR);
00110
00111     bool assertion = gg.ConstructGrad3D(ggg);
00112
00113     if (!assertion) {
00114         std::cerr << "Mimetic grad (2nd order) could not be built." << std::endl;
00115     }
00116
00117     mtk::DenseMatrix ggm(gg.ReturnAsDenseMatrix());
00118
00119     assertion = assertion && (ggm.num_rows() != mtk::kZero);
00120
00121     std::cout << ggm << std::endl;
00122
00123     assertion = assertion && ggm.WriteToFile("mtk_grad_3d_test_02.dat");
00124
00125     if (!assertion) {
00126         std::cerr << "Error writing to file." << std::endl;
00127     }
00128
00129     mtk::Tools::EndUnitTestNo(2);
00130     mtk::Tools::Assert(assertion);
00131 }
00132
00133 int main () {
00134
00135     std::cout << "Testing mtk::Grad2D class." << std::endl;
00136
00137     TestDefaultConstructorFactory();
00138     TestReturnAsDenseMatrixWriteToFile();
00139 }

```


```
00140
00141 #else
00142 #include <iostream>
00143 using std::cout;
00144 using std::endl;
00145 int main () {
00146     cout << "This code HAS to be compiled with support for C++11." << endl;
00147     cout << "Exiting..." << endl;
00148 }
00149 #endif
```

17.133 tests/mtk_interp_1d_test.cc File Reference

Testing the 1D interpolation.

```
#include <iostream>
```

Include dependency graph for mtk_interp_1d_test.cc:



Functions

- `int main ()`

17.133.1 Detailed Description

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu
: Johnny Corbino - jcorbino at mail dot sdsu dot edu

Definition in file [mtk_interp_1d_test.cc](#).

17.133.2 Function Documentation

17.133.2.1 `int main ()`

Definition at line [113](#) of file [mtk_interp_1d_test.cc](#).

17.134 mtk_interp_1d_test.cc

```

00001
00010 /*
00011 Copyright (C) 2015, Computational Science Research Center, San Diego State
00012 University. All rights reserved.
00013
00014 Redistribution and use in source and binary forms, with or without modification,
00015 are permitted provided that the following conditions are met:
00016
00017 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00018 and a copy of the modified files should be reported once modifications are
00019 completed, unless these modifications are made through the project's GitHub
00020 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00021 should be developed and included in any deliverable.
00022
00023 2. Redistributions of source code must be done through direct
00024 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00025
00026 3. Redistributions in binary form must reproduce the above copyright notice,
00027 this list of conditions and the following disclaimer in the documentation and/or
00028 other materials provided with the distribution.
00029
00030 4. Usage of the binary form on proprietary applications shall require explicit
00031 prior written permission from the the copyright holders, and due credit should
00032 be given to the copyright holders.
00033
00034 5. Neither the name of the copyright holder nor the names of its contributors
00035 may be used to endorse or promote products derived from this software without
00036 specific prior written permission.
00037
00038 The copyright holders provide no reassurances that the source code provided does
00039 not infringe any patent, copyright, or any other intellectual property rights of
00040 third parties. The copyright holders disclaim any liability to any recipient for
00041 claims brought against recipient by any third party for infringement of that
00042 parties intellectual property rights.
00043
00044 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00045 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00046 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00047 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00048 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00049 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00050 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00051 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00052 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00053 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00054 */
00055
00056 #if __cplusplus == 201103L
00057
00058 #include <iostream>
00059
00060 #include "mtk.h"
00061
00062 void TestDefaultConstructorFactoryMethodDefault() {
00063
00064     mtk::Tools::BeginUnitTestNo(1);
00065
00066     mtk::Interp1D inter;
00067
00068     bool assertion = inter.ConstructInterp1D();
00069
00070     if (!assertion) {
00071         std::cerr << "Mimetic interp could not be built." << std::endl;
00072     }
00073
00074     mtk::Tools::EndUnitTestNo(1);
00075     mtk::Tools::Assert(assertion);
00076 }
00077
00078 void TestReturnAsDenseMatrixWithGrid() {
00079
00080     mtk::Tools::BeginUnitTestNo(2);
00081
00082     mtk::Interp1D inter;
00083
00084     bool assertion = inter.ConstructInterp1D();
00085
00086     if (!assertion) {

```

```

00087     std::cerr << "Mimetic grad (2nd order) could not be built." << std::endl;
00088 }
00089
00090 mtk::UniStgGrid1D grid(0.0, 1.0, 5);
00091
00092 mtk::DenseMatrix interpm(inter.ReturnAsDenseMatrix(grid));
00093
00094 assertion =
00095     assertion && interpm.GetValue(0,0) == 1.0 && interpm.GetValue(5,6) == 1.0;
00096
00097 mtk::Tools::EndUnitTestNo(2);
00098 mtk::Tools::Assert(assertion);
00099 }
00100
00101 int main () {
00102
00103     std::cout << "Testing mtk::Interp1D class." << std::endl;
00104
00105     TestDefaultConstructorFactoryMethodDefault();
00106     TestReturnAsDenseMatrixWithGrid();
00107 }
00108
00109 #else
00110 #include <iostream>
00111 using std::cout;
00112 using std::endl;
00113 int main () {
00114     cout << "This code HAS to be compiled with support for C++11." << endl;
00115     cout << "Exiting..." << endl;
00116 }
00117 #endif


```

17.135 tests/mtk_lap_1d_test.cc File Reference

Testing the 1D Laplacian operator.

```
#include <iostream>
```

Include dependency graph for mtk_lap_1d_test.cc:



Functions

- int `main` ()

17.135.1 Detailed Description

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu
 : Johnny Corbino - jcorbino at mail dot sdsu dot edu

Definition in file [mtk_lap_1d_test.cc](#).

17.135.2 Function Documentation**17.135.2.1 int main ()**

Definition at line 193 of file [mtk_lap_1d_test.cc](#).

17.136 mtk_lap_1d_test.cc

```

00001
00010 /*
00011 Copyright (C) 2015, Computational Science Research Center, San Diego State
00012 University. All rights reserved.
00013
00014 Redistribution and use in source and binary forms, with or without modification,
00015 are permitted provided that the following conditions are met:
00016
00017 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00018 and a copy of the modified files should be reported once modifications are
00019 completed, unless these modifications are made through the project's GitHub
00020 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00021 should be developed and included in any deliverable.
00022
00023 2. Redistributions of source code must be done through direct
00024 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00025
00026 3. Redistributions in binary form must reproduce the above copyright notice,
00027 this list of conditions and the following disclaimer in the documentation and/or
00028 other materials provided with the distribution.
00029
00030 4. Usage of the binary form on proprietary applications shall require explicit
00031 prior written permission from the the copyright holders, and due credit should
00032 be given to the copyright holders.
00033
00034 5. Neither the name of the copyright holder nor the names of its contributors
00035 may be used to endorse or promote products derived from this software without
00036 specific prior written permission.
00037
00038 The copyright holders provide no reassurances that the source code provided does
00039 not infringe any patent, copyright, or any other intellectual property rights of
00040 third parties. The copyright holders disclaim any liability to any recipient for
00041 claims brought against recipient by any third party for infringement of that
00042 parties intellectual property rights.
00043
00044 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00045 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00046 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00047 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00048 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00049 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00050 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00051 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00052 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00053 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00054 */
00055
00056 #if __cplusplus == 201103L
00057
00058 #include <iostream>
00059
00060 #include "mtk.h"
00061
00062 void TestDefaultConstructorFactoryMethodDefault() {
00063
00064     mtk::Tools::BeginUnitTestNo(1);

```

```

00065
00066     mtk::Lap1D lap2;
00067
00068     bool assertion = lap2.ConstructLap1D();
00069
00070     if (!assertion) {
00071         std::cerr << "Mimetic lap (2nd order) could not be built." << std::endl;
00072     }
00073
00074     mtk::Tools::EndUnitTestNo(1);
00075     mtk::Tools::Assert(assertion);
00076 }
00077
00078 void TestDefaultConstructorFactoryMethodFourthOrder() {
00079
00080     mtk::Tools::BeginUnitTestNo(2);
00081
00082     mtk::Lap1D lap4;
00083
00084     bool assertion = lap4.ConstructLap1D(4);
00085
00086     if (!assertion) {
00087         std::cerr << "Mimetic lap (4th order) could not be built." << std::endl;
00088     }
00089
00090     mtk::Tools::EndUnitTestNo(2);
00091     mtk::Tools::Assert(assertion);
00092 }
00093
00094 void TestDefaultConstructorFactoryMethodSixthOrder() {
00095
00096     mtk::Tools::BeginUnitTestNo(3);
00097
00098     mtk::Lap1D lap6;
00099
00100     bool assertion = lap6.ConstructLap1D(6);
00101
00102     if (!assertion) {
00103         std::cerr << "Mimetic lap (6th order) could not be built." << std::endl;
00104     }
00105
00106     mtk::Tools::EndUnitTestNo(3);
00107     mtk::Tools::Assert(assertion);
00108 }
00109
00110 void TestDefaultConstructorFactoryMethodEightOrderDefThreshold() {
00111
00112     mtk::Tools::BeginUnitTestNo(4);
00113
00114     mtk::Lap1D lap8;
00115
00116     bool assertion = lap8.ConstructLap1D(8);
00117
00118     if (!assertion) {
00119         std::cerr << "Mimetic lap (8th order) could not be built." << std::endl;
00120     }
00121
00122     mtk::Tools::EndUnitTestNo(4);
00123 }
00124
00125 void TestDefaultConstructorFactoryMethodTenthOrderDefThreshold() {
00126
00127     mtk::Tools::BeginUnitTestNo(5);
00128
00129     mtk::Lap1D lap10;
00130
00131     bool assertion = lap10.ConstructLap1D(10);
00132
00133     if (!assertion) {
00134         std::cerr << "Mimetic lap (10th order) could not be built." << std::endl;
00135     }
00136
00137     mtk::Tools::EndUnitTestNo(5);
00138 }
00139
00140 void TestDefaultConstructorFactoryMethodTwelfthOrderDefThreshold() {
00141
00142     mtk::Tools::BeginUnitTestNo(6);
00143
00144     mtk::Lap1D lap12;
00145

```



```

00146     bool assertion = lap12.ConstructLap1D(12);
00147
00148     if (!assertion) {
00149         std::cerr << "Mimetic lap (12th order) could not be built." << std::endl;
00150     }
00151
00152     mtk::Tools::EndUnitTestNo(6);
00153 }
00154
00155 void TestReturnAsDenseMatrix() {
00156
00157     mtk::Tools::BeginUnitTestNo(8);
00158
00159     mtk::Lap1D lap4;
00160
00161     bool assertion = lap4.ConstructLap1D(4);
00162
00163     if (!assertion) {
00164         std::cerr << "Mimetic lap (4th order) could not be built." << std::endl;
00165     }
00166
00167     mtk::UniStgGrid1D aux(0.0, 1.0, 11);
00168
00169     mtk::DenseMatrix lap4_m(lap4.ReturnAsDenseMatrix(aux));
00170
00171     assertion = assertion &&
00172         abs(lap4_m.GetValue(1, 0) - 385.133) < mtk::kDefaultTolerance &&
00173         abs(lap4_m.GetValue(11, 12) - 385.133) < mtk::kDefaultTolerance;
00174     mtk::Tools::EndUnitTestNo(8);
00175     mtk::Tools::Assert(assertion);
00176 }
00177
00178 int main () {
00179
00180     std::cout << "Testing MTK 1D Laplacian" << std::endl;
00181
00182     TestDefaultConstructorFactoryMethodDefault();
00183     TestDefaultConstructorFactoryMethodFourthOrder();
00184     TestDefaultConstructorFactoryMethodSixthOrder();
00185     TestDefaultConstructorFactoryMethodEightOrderDefThreshold();
00186     TestDefaultConstructorFactoryMethodTenthOrderDefThreshold();
00187     TestDefaultConstructorFactoryMethodTwelfthOrderDefThreshold();
00188     TestReturnAsDenseMatrix();
00189 }
00190
00191 #else
00192 #include <iostream>
00193 int main () {
00194     std::cout << "This code HAS to be compiled to support C++11." << std::endl;
00195     std::cout << "Exiting..." << std::endl;
00196 }
00197 #endif


```

17.137 tests/mtk_lap_2d_test.cc File Reference

Test file for the [mtk::Lap2D](#) class.

```
#include <iostream>
```

Include dependency graph for `mtk_lap_2d_test.cc`:



Functions

- `int main ()`

17.137.1 Detailed Description

Author

: Eduardo J. Sanchez (ejspeiro) - [esanchez at mail dot sdsu dot edu](mailto:esanchez@mail.sdsu.edu)

Definition in file [mtk_lap_2d_test.cc](#).

17.137.2 Function Documentation

17.137.2.1 `int main ()`

Definition at line [139](#) of file [mtk_lap_2d_test.cc](#).

17.138 `mtk_lap_2d_test.cc`

```
00001
00008 /*
00009 Copyright (C) 2015, Computational Science Research Center, San Diego State
00010 University. All rights reserved.
00011
00012 Redistribution and use in source and binary forms, with or without modification,
00013 are permitted provided that the following conditions are met:
00014
00015 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00016 and a copy of the modified files should be reported once modifications are
00017 completed, unless these modifications are made through the project's GitHub
00018 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00019 should be developed and included in any deliverable.
00020
00021 2. Redistributions of source code must be done through direct
00022 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00023
00024 3. Redistributions in binary form must reproduce the above copyright notice,
```

```

00025 this list of conditions and the following disclaimer in the documentation and/or
00026 other materials provided with the distribution.
00027
00028 4. Usage of the binary form on proprietary applications shall require explicit
00029 prior written permission from the the copyright holders, and due credit should
00030 be given to the copyright holders.
00031
00032 5. Neither the name of the copyright holder nor the names of its contributors
00033 may be used to endorse or promote products derived from this software without
00034 specific prior written permission.
00035
00036 The copyright holders provide no reassurances that the source code provided does
00037 not infringe any patent, copyright, or any other intellectual property rights of
00038 third parties. The copyright holders disclaim any liability to any recipient for
00039 claims brought against recipient by any third party for infringement of that
00040 parties intellectual property rights.
00041
00042 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00043 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00044 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00045 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00046 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00047 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00048 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00049 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00050 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00051 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00052 */
00053
00054 #if __cplusplus == 201103L
00055 #include <cmath>
00056 #include <ctime>
00057 #include <iostream>
00058 #include "mtk.h"
00059
00060 void TestDefaultConstructorFactory() {
00061     mtk::Tools::BeginUnitTestNo(1);
00062
00063     mtk::Lap2D ll;
00064
00065     mtk::Real aa = 0.0;
00066     mtk::Real bb = 1.0;
00067     mtk::Real cc = 0.0;
00068     mtk::Real dd = 1.0;
00069
00070     int nn = 5;
00071     int mm = 5;
00072
00073     mtk::UniStgGrid2D llg(aa, bb, nn, cc, dd, mm);
00074
00075     bool assertion = ll.ConstructLap2D(llg);
00076
00077     if (!assertion) {
00078         std::cerr << "Mimetic lap (2nd order) could not be built." << std::endl;
00079     }
00080
00081     mtk::Tools::EndUnitTestNo(1);
00082     mtk::Tools::Assert(assertion);
00083 }
00084
00085 void TestReturnAsDenseMatrixWriteToFile() {
00086     mtk::Tools::BeginUnitTestNo(2);
00087
00088     mtk::Lap2D ll;
00089
00090     mtk::Real aa = 0.0;
00091     mtk::Real bb = 1.0;
00092     mtk::Real cc = 0.0;
00093     mtk::Real dd = 1.0;
00094
00095     int nn = 5;
00096     int mm = 5;
00097
00098     mtk::UniStgGrid2D llg(aa, bb, nn, cc, dd, mm);
00099
00100     bool assertion = ll.ConstructLap2D(llg);

```

```

00106
00107     if (!assertion) {
00108         std::cerr << "Mimetic lap (2nd order) could not be built." << std::endl;
00109     }
00110
00111     mtk::DenseMatrix llm(ll.ReturnAsDenseMatrix());
00112
00113     assertion = assertion && (llm.num_rows() != 0);
00114
00115     std::cout << llm << std::endl;
00116
00117     assertion = assertion && llm.WriteToFile("mtk_lap_2d_test_02.dat");
00118
00119     if (!assertion) {
00120         std::cerr << "Error writing to file." << std::endl;
00121     }
00122
00123     mtk::Tools::EndUnitTestNo(2);
00124     mtk::Tools::Assert(assertion);
00125 }
00126
00127 int main () {
00128
00129     std::cout << "Testing mtk::Lap2D class." << std::endl;
00130
00131     TestDefaultConstructorFactory();
00132     TestReturnAsDenseMatrixWriteToFile();
00133 }
00134
00135 #else
00136 #include <iostream>
00137 using std::cout;
00138 using std::endl;
00139 int main () {
00140     cout << "This code HAS to be compiled with support for C++11." << endl;
00141     cout << "Exiting..." << endl;
00142 }
00143 #endif


```

17.139 tests/mtk_lap_3d_test.cc File Reference

Test file for the `mtk::Lap3D` class.

```
#include <iostream>
```

Include dependency graph for `mtk_lap_3d_test.cc`:



Functions

- int `main` ()

17.139.1 Detailed Description

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_lap_3d_test.cc](#).

17.139.2 Function Documentation

17.139.2.1 int main ()

Definition at line 145 of file [mtk_lap_3d_test.cc](#).

17.140 mtk_lap_3d_test.cc

```

00001
00008 /*
00009 Copyright (C) 2015, Computational Science Research Center, San Diego State
00010 University. All rights reserved.
00011
00012 Redistribution and use in source and binary forms, with or without modification,
00013 are permitted provided that the following conditions are met:
00014
00015 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00016 and a copy of the modified files should be reported once modifications are
00017 completed, unless these modifications are made through the project's GitHub
00018 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00019 should be developed and included in any deliverable.
00020
00021 2. Redistributions of source code must be done through direct
00022 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00023
00024 3. Redistributions in binary form must reproduce the above copyright notice,
00025 this list of conditions and the following disclaimer in the documentation and/or
00026 other materials provided with the distribution.
00027
00028 4. Usage of the binary form on proprietary applications shall require explicit
00029 prior written permission from the the copyright holders, and due credit should
00030 be given to the copyright holders.
00031
00032 5. Neither the name of the copyright holder nor the names of its contributors
00033 may be used to endorse or promote products derived from this software without
00034 specific prior written permission.
00035
00036 The copyright holders provide no reassurances that the source code provided does
00037 not infringe any patent, copyright, or any other intellectual property rights of
00038 third parties. The copyright holders disclaim any liability to any recipient for
00039 claims brought against recipient by any third party for infringement of that
00040 parties intellectual property rights.
00041
00042 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00043 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00044 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00045 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00046 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00047 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00048 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00049 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00050 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00051 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00052 */
00053
00054 #if __cplusplus == 201103L
00055
00056 #include <cmath>
00057 #include <ctime>
00058
00059 #include <iostream>
00060

```

```

00061 #include "mtk.h"
00062
00063 void TestDefaultConstructorFactory() {
00064
00065     mtk::Tools::BeginUnitTestNo(1);
00066
00067     mtk::Lap3D ll;
00068
00069     mtk::Real aa = 0.0;
00070     mtk::Real bb = 1.0;
00071     mtk::Real cc = 0.0;
00072     mtk::Real dd = 1.0;
00073     mtk::Real ee = 0.0;
00074     mtk::Real ff = 1.0;
00075
00076     int nn = 5;
00077     int mm = 5;
00078     int oo = 5;
00079
00080     mtk::UniStgGrid3D llg(aa, bb, nn, cc, dd, mm, ee, ff, oo);
00081
00082     bool assertion = ll.ConstructLap3D(llg);
00083
00084     if (!assertion) {
00085         std::cerr << "Mimetic lap (2nd order) could not be built." << std::endl;
00086     }
00087
00088     mtk::Tools::EndUnitTestNo(1);
00089     mtk::Tools::Assert(assertion);
00090 }
00091
00092 void TestReturnAsDenseMatrixWriteToFile() {
00093
00094     mtk::Tools::BeginUnitTestNo(2);
00095
00096     mtk::Lap3D ll;
00097
00098     mtk::Real aa = 0.0;
00099     mtk::Real bb = 1.0;
00100     mtk::Real cc = 0.0;
00101     mtk::Real dd = 1.0;
00102     mtk::Real ee = 0.0;
00103     mtk::Real ff = 1.0;
00104
00105     int nn = 5;
00106     int mm = 5;
00107     int oo = 5;
00108
00109     mtk::UniStgGrid3D llg(aa, bb, nn, cc, dd, mm, ee, ff, oo);
00110
00111     bool assertion = ll.ConstructLap3D(llg);
00112
00113     if (!assertion) {
00114         std::cerr << "Mimetic lap (2nd order) could not be built." << std::endl;
00115     }
00116
00117     mtk::DenseMatrix llm(ll.ReturnAsDenseMatrix());
00118
00119     assertion = assertion && (llm.num_rows() != 0);
00120
00121     std::cout << llm << std::endl;
00122
00123     assertion = assertion && llm.WriteToFile("mtk_lap_3d_test_02.dat");
00124
00125     if (!assertion) {
00126         std::cerr << "Error writing to file." << std::endl;
00127     }
00128
00129     mtk::Tools::EndUnitTestNo(2);
00130     mtk::Tools::Assert(assertion);
00131 }
00132
00133 int main () {
00134
00135     std::cout << "Testing mtk::Lap3D class." << std::endl;
00136
00137     TestDefaultConstructorFactory();
00138     TestReturnAsDenseMatrixWriteToFile();
00139 }
00140
00141 #else

```


```
00142 #include <iostream>
00143 using std::cout;
00144 using std::endl;
00145 int main () {
00146     cout << "This code HAS to be compiled with support for C++11." << endl;
00147     cout << "Exiting..." << endl;
00148 }
00149 #endif
```

17.141 tests/mtk_lapack_adapter_test.cc File Reference

Test file for the [mtk::LAPACKAdapter](#) class.

```
#include <iostream>
```

Include dependency graph for mtk_lapack_adapter_test.cc:



Functions

- `int main ()`

17.141.1 Detailed Description

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Todo Test the [mtk::LAPACKAdapter](#) class.

Definition in file [mtk_lapack_adapter_test.cc](#).

17.141.2 Function Documentation

17.141.2.1 `int main ()`

Definition at line [81](#) of file [mtk_lapack_adapter_test.cc](#).

17.142 mtk_lapack_adapter_test.cc

```

00001
00010 /*
00011 Copyright (C) 2015, Computational Science Research Center, San Diego State
00012 University. All rights reserved.
00013
00014 Redistribution and use in source and binary forms, with or without modification,
00015 are permitted provided that the following conditions are met:
00016
00017 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00018 and a copy of the modified files should be reported once modifications are
00019 completed, unless these modifications are made through the project's GitHub
00020 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00021 should be developed and included in any deliverable.
00022
00023 2. Redistributions of source code must be done through direct
00024 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00025
00026 3. Redistributions in binary form must reproduce the above copyright notice,
00027 this list of conditions and the following disclaimer in the documentation and/or
00028 other materials provided with the distribution.
00029
00030 4. Usage of the binary form on proprietary applications shall require explicit
00031 prior written permission from the the copyright holders, and due credit should
00032 be given to the copyright holders.
00033
00034 5. Neither the name of the copyright holder nor the names of its contributors
00035 may be used to endorse or promote products derived from this software without
00036 specific prior written permission.
00037
00038 The copyright holders provide no reassurances that the source code provided does
00039 not infringe any patent, copyright, or any other intellectual property rights of
00040 third parties. The copyright holders disclaim any liability to any recipient for
00041 claims brought against recipient by any third party for infringement of that
00042 parties intellectual property rights.
00043
00044 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00045 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00046 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00047 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00048 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00049 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00050 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00051 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00052 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00053 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00054 */
00055
00056 #if __cplusplus == 201103L
00057
00058 #include <iostream>
00059 #include <ctime>
00060
00061 #include "mtk.h"
00062
00063 void Test1() {
00064
00065     mtk::Tools::BeginUnitTestNo(1);
00066
00067     mtk::Tools::EndUnitTestNo(1);
00068 }
00069
00070 int main () {
00071
00072     std::cout << "Testing mtk::LAPACKAdapter class." << std::endl;
00073
00074     Test1();
00075 }
00076
00077 #else
00078 #include <iostream>
00079 using std::cout;
00080 using std::endl;
00081 int main () {
00082     cout << "This code HAS to be compiled with support for C++11." << endl;
00083     cout << "Exiting..." << endl;
00084 }
00085 #endif


```


17.143 tests/mtk_robin_bc_descriptor_2d_test.cc File Reference

Test file for the [mtk::RobinBCDescriptor2D](#) class.

```
#include <iostream>
```

Include dependency graph for `mtk_robin_bc_descriptor_2d_test.cc`:



Functions

- `int main ()`

17.143.1 Detailed Description

Author

: Eduardo J. Sanchez (ejspeiro) - [esanchez at mail dot sdsu dot edu](#)

Definition in file [mtk_robin_bc_descriptor_2d_test.cc](#).

17.143.2 Function Documentation

17.143.2.1 `int main ()`

Definition at line [198](#) of file [mtk_robin_bc_descriptor_2d_test.cc](#).

17.144 mtk_robin_bc_descriptor_2d_test.cc

```
00001
00008 /*
00009 Copyright (C) 2015, Computational Science Research Center, San Diego State
00010 University. All rights reserved.
00011
00012 Redistribution and use in source and binary forms, with or without modification,
00013 are permitted provided that the following conditions are met:
00014
00015 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00016 and a copy of the modified files should be reported once modifications are
00017 completed, unless these modifications are made through the project's GitHub
```

```

00018 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00019 should be developed and included in any deliverable.
00020
00021 2. Redistributions of source code must be done through direct
00022 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00023
00024 3. Redistributions in binary form must reproduce the above copyright notice,
00025 this list of conditions and the following disclaimer in the documentation and/or
00026 other materials provided with the distribution.
00027
00028 4. Usage of the binary form on proprietary applications shall require explicit
00029 prior written permission from the the copyright holders, and due credit should
00030 be given to the copyright holders.
00031
00032 5. Neither the name of the copyright holder nor the names of its contributors
00033 may be used to endorse or promote products derived from this software without
00034 specific prior written permission.
00035
00036 The copyright holders provide no reassurances that the source code provided does
00037 not infringe any patent, copyright, or any other intellectual property rights of
00038 third parties. The copyright holders disclaim any liability to any recipient for
00039 claims brought against recipient by any third party for infringement of that
00040 parties intellectual property rights.
00041
00042 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00043 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00044 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00045 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00046 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00047 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00048 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00049 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00050 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00051 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00052 */
00053
00054 #if __cplusplus == 201103L
00055
00056 #include <cmath>
00057 #include <ctime>
00058
00059 #include <iostream>
00060
00061 #include "mtk.h"
00062
00063 void TestDefaultConstructorGetters() {
00064
00065     mtk::Tools::BeginUnitTestNo(1);
00066
00067     mtk::RobinBCDescriptor2D bcd;
00068
00069     bool assertion{true};
00070
00071     assertion = assertion && bcd.highest_order_diff_west() == -1;
00072     assertion = assertion && bcd.highest_order_diff_east() == -1;
00073     assertion = assertion && bcd.highest_order_diff_south() == -1;
00074     assertion = assertion && bcd.highest_order_diff_north() == -1;
00075
00076     mtk::Tools::EndUnitTestNo(1);
00077     mtk::Tools::Assert(assertion);
00078 }
00079
00080 mtk::Real cc(const mtk::Real &xx, const mtk::Real &yy) {
00081
00082     return mtk::kOne;
00083 }
00084
00085 void TestPushBackImposeOnLaplacianMatrix() {
00086
00087     mtk::Tools::BeginUnitTestNo(2);
00088
00089     mtk::RobinBCDescriptor2D bcd;
00090
00091     bool assertion{true};
00092
00093     bcd.PushBackWestCoeff(cc);
00094     bcd.PushBackEastCoeff(cc);
00095     bcd.PushBackSouthCoeff(cc);
00096     bcd.PushBackNorthCoeff(cc);
00097
00098     assertion = assertion && bcd.highest_order_diff_west() == 0;

```

```

00099  assertion = assertion && bcd.highest_order_diff_east() == 0;
00100  assertion = assertion && bcd.highest_order_diff_south() == 0;
00101  assertion = assertion && bcd.highest_order_diff_north() == 0;
00102
00103  mtk::Real aa = 0.0;
00104  mtk::Real bb = 1.0;
00105  mtk::Real cc = 0.0;
00106  mtk::Real dd = 1.0;
00107
00108  int nn = 5;
00109  int mm = 5;
00110
00111  mtk::UniStgGrid2D llg(aa, bb, nn, cc, dd, mm);
00112
00113  mtk::Lap2D ll;
00114
00115  assertion = ll.ConstructLap2D(llg);
00116
00117  if (!assertion) {
00118      std::cerr << "Mimetic lap (2nd order) could not be built." << std::endl;
00119  }
00120
00121  mtk::DenseMatrix llm(ll.ReturnAsDenseMatrix());
00122
00123  assertion = assertion && (llm.num_rows() != 0);
00124
00125  bcd.ImposeOnLaplacianMatrix(ll, llg, llm);
00126
00127  assertion = assertion &&
00128      llm.WriteToFile("mtk_robin_bc_descriptor_2d_test_02.dat");
00129
00130  mtk::Tools::EndUnitTestNo(2);
00131  mtk::Tools::Assert(assertion);
00132 }
00133
00134 mtk::Real ScalarField(const mtk::Real &xx, const mtk::Real &yy) {
00135
00136     mtk::Real aux{-(1.0/2.0)*xx*xx - (1.0/2.0)*yy*yy};
00137
00138     return xx*yy*exp(aux);
00139 }
00140
00141 mtk::Real HomogeneousDiricheletBC(const mtk::Real &xx,
00142                                   const mtk::Real &tt) {
00143
00144     return mtk::kZero;
00145 }
00146
00147 void TestImposeOnGrid() {
00148
00149     mtk::Tools::BeginUnitTestNo(3);
00150
00151     mtk::Real aa = 0.0;
00152     mtk::Real bb = 1.0;
00153     mtk::Real cc = 0.0;
00154     mtk::Real dd = 1.0;
00155
00156     int nn = 5;
00157     int mm = 5;
00158
00159     mtk::UniStgGrid2D gg(aa, bb, nn, cc, dd, mm);
00160
00161     gg.BindScalarField(ScalarField);
00162
00163     mtk::RobinBCDescriptor2D desc;
00164
00165     desc.set_west_condition(HomogeneousDiricheletBC);
00166     desc.set_east_condition(HomogeneousDiricheletBC);
00167     desc.set_south_condition(HomogeneousDiricheletBC);
00168     desc.set_north_condition(HomogeneousDiricheletBC);
00169
00170     desc.ImposeOnGrid(gg);
00171
00172     bool assertion{gg.WriteToFile("mtk_robin_bc_descriptor_2d_test_03.dat",
00173                                   "x",
00174                                   "y",
00175                                   "u(x,y) ")};
00176
00177     if (!assertion) {
00178         std::cerr << "Error writing to file." << std::endl;
00179     }

```

```

00180
00181     mtk::Tools::EndUnitTestNo(3);
00182     mtk::Tools::Assert(assertion);
00183 }
00184
00185 int main () {
00186     std::cout << "Testing mtk::RobinBCDescriptor2D class." << std::endl;
00187
00188     TestDefaultConstructorGetters();
00189     TestPushBackImposeOnLaplacianMatrix();
00190     TestImposeOnGrid();
00191 }
00192
00193 #else
00194 #include <iostream>
00195 using std::cout;
00196 using std::endl;
00197
00198 int main () {
00199     cout << "This code HAS to be compiled with support for C++11." << endl;
00200     cout << "Exiting..." << endl;
00201 }
00202 #endif


```

17.145 tests/mtk_uni_stg_grid_1d_test.cc File Reference

Test file for the [mtk::UniStgGrid1D](#) class.

```
#include <iostream>
```

Include dependency graph for `mtk_uni_stg_grid_1d_test.cc`:



Functions

- `int main ()`

17.145.1 Detailed Description

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_uni_stg_grid_1d_test.cc](#).

17.145.2 Function Documentation

17.145.2.1 int main ()

Definition at line 172 of file [mtk_uni_stg_grid_1d_test.cc](#).

17.146 mtk_uni_stg_grid_1d_test.cc

```

00001
00008 /*
00009 Copyright (C) 2015, Computational Science Research Center, San Diego State
00010 University. All rights reserved.
00011
00012 Redistribution and use in source and binary forms, with or without modification,
00013 are permitted provided that the following conditions are met:
00014
00015 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00016 and a copy of the modified files should be reported once modifications are
00017 completed, unless these modifications are made through the project's GitHub
00018 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00019 should be developed and included in any deliverable.
00020
00021 2. Redistributions of source code must be done through direct
00022 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00023
00024 3. Redistributions in binary form must reproduce the above copyright notice,
00025 this list of conditions and the following disclaimer in the documentation and/or
00026 other materials provided with the distribution.
00027
00028 4. Usage of the binary form on proprietary applications shall require explicit
00029 prior written permission from the the copyright holders, and due credit should
00030 be given to the copyright holders.
00031
00032 5. Neither the name of the copyright holder nor the names of its contributors
00033 may be used to endorse or promote products derived from this software without
00034 specific prior written permission.
00035
00036 The copyright holders provide no reassurances that the source code provided does
00037 not infringe any patent, copyright, or any other intellectual property rights of
00038 third parties. The copyright holders disclaim any liability to any recipient for
00039 claims brought against recipient by any third party for infringement of that
00040 parties intellectual property rights.
00041
00042 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00043 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00044 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00045 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00046 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00047 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00048 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00049 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00050 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00051 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00052 */
00053
00054 #if __cplusplus == 201103L
00055
00056 #include <iostream>
00057 #include <ctime>
00058
00059 #include "mtk.h"
00060
00061 void TestDefaultConstructor() {
00062
00063     mtk::Tools::BeginUnitTestNo(1);
00064
00065     mtk::UniStgGrid1D gg;
00066
00067     mtk::Tools::EndUnitTestNo(1);
00068     mtk::Tools::Assert(gg.delta_x() == mtk::kZero);
00069 }
00070
00071 mtk::Real ScalarField(const mtk::Real &xx) {
00072
00073     return 2.0*xx;

```

```

00074 }
00075
00076 void TestConstructWithWestBndyEastBndyNumCellsOStreamOperatorBindScalarField() {
00077     mtk::Tools::BeginUnitTestNo(2);
00078     mtk::Real aa = 0.0;
00081     mtk::Real bb = 1.0;
00082
00083     int nn = 5;
00084
00085     mtk::UniStgGrid1D gg(aa, bb, nn);
00086
00087     gg.BindScalarField(ScalarField);
00088
00089     std::cout << gg << std::endl;
00090
00091     mtk::Tools::EndUnitTestNo(2);
00092     mtk::Tools::Assert(gg.delta_x() == 0.2 && gg.
num_cells_x() == 5);
00093 }
00094
00095 void TestBindScalarFieldWriteToFile() {
00096     mtk::Tools::BeginUnitTestNo(3);
00097     mtk::Real aa = 0.0;
00100     mtk::Real bb = 1.0;
00101
00102     int nn = 5;
00103
00104     mtk::UniStgGrid1D gg(aa, bb, nn);
00105
00106     bool assertion{true};
00107
00108     gg.BindScalarField(ScalarField);
00109
00110     assertion =
00111         assertion &&
00112         gg.discrete_field()[0] == 0.0 &&
00113         gg.discrete_field()[gg.num_cells_x() + 2 - 1] == 2.0;
00114
00115     if(!gg.WriteToFile("mtk_uni_stg_grid_1d_test_03.dat", "x", "u(x)")) {
00116         std::cerr << "Error writing to file." << std::endl;
00117         assertion = false;
00118     }
00119
00120     mtk::Tools::EndUnitTestNo(3);
00121     mtk::Tools::Assert(assertion);
00122 }
00123
00124 mtk::Real VectorFieldPComponent(mtk::Real xx) {
00125     return xx*xx;
00126 }
00127
00128 void TestBindVectorField() {
00129     mtk::Tools::BeginUnitTestNo(4);
00130
00131     mtk::Real aa = 0.0;
00134     mtk::Real bb = 1.0;
00135
00136     int nn = 20;
00137
00138     mtk::UniStgGrid1D gg(aa, bb, nn, mtk::VECTOR);
00139
00140     bool assertion{true};
00141
00142     gg.BindVectorField(VectorFieldPComponent);
00143
00144     assertion =
00145         assertion &&
00146         gg.discrete_field()[0] == 0.0 &&
00147         gg.discrete_field()[gg.num_cells_x() + 1 - 1] == 1.0;
00148
00149     if(!gg.WriteToFile("mtk_uni_stg_grid_1d_test_04.dat", "x", "v(x)")) {
00150         std::cerr << "Error writing to file." << std::endl;
00151         assertion = false;
00152     }
00153 }

```

```

00154     mtk::Tools::EndUnitTestNo(4);
00155     mtk::Tools::Assert(assertion);
00156 }
00157
00158 int main () {
00159
00160     std::cout << "Testing mtk::UniStgGrid1D class." << std::endl;
00161
00162     TestDefaultConstructor();
00163     TestConstructWithWestBndyEastBndyNumCellsOStreamOperatorBindScalarField();
00164     TestBindScalarFieldWriteToFile();
00165     TestBindVectorField();
00166 }
00167
00168 #else
00169 #include <iostream>
00170 using std::cout;
00171 using std::endl;
00172 int main () {
00173     cout << "This code HAS to be compiled with support for C++11." << endl;
00174     cout << "Exiting..." << endl;
00175 }
00176 #endif


```

17.147 tests/mtk_uni_stg_grid_2d_test.cc File Reference

Test file for the [mtk::UniStgGrid2D](#) class.

```
#include <iostream>
```

Include dependency graph for mtk_uni_stg_grid_2d_test.cc:



Functions

- int [main](#) ()

17.147.1 Detailed Description

Author

: Eduardo J. Sanchez (ejspeiro) - esanchez at mail dot sdsu dot edu

Definition in file [mtk_uni_stg_grid_2d_test.cc](#).

17.147.2 Function Documentation

17.147.2.1 `int main ()`

Definition at line 202 of file `mtk_uni_stg_grid_2d_test.cc`.

17.148 `mtk_uni_stg_grid_2d_test.cc`

```

00001
00008 /*
00009 Copyright (C) 2015, Computational Science Research Center, San Diego State
00010 University. All rights reserved.
00011
00012 Redistribution and use in source and binary forms, with or without modification,
00013 are permitted provided that the following conditions are met:
00014
00015 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00016 and a copy of the modified files should be reported once modifications are
00017 completed, unless these modifications are made through the project's GitHub
00018 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00019 should be developed and included in any deliverable.
00020
00021 2. Redistributions of source code must be done through direct
00022 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00023
00024 3. Redistributions in binary form must reproduce the above copyright notice,
00025 this list of conditions and the following disclaimer in the documentation and/or
00026 other materials provided with the distribution.
00027
00028 4. Usage of the binary form on proprietary applications shall require explicit
00029 prior written permission from the the copyright holders, and due credit should
00030 be given to the copyright holders.
00031
00032 5. Neither the name of the copyright holder nor the names of its contributors
00033 may be used to endorse or promote products derived from this software without
00034 specific prior written permission.
00035
00036 The copyright holders provide no reassurances that the source code provided does
00037 not infringe any patent, copyright, or any other intellectual property rights of
00038 third parties. The copyright holders disclaim any liability to any recipient for
00039 claims brought against recipient by any third party for infringement of that
00040 parties intellectual property rights.
00041
00042 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00043 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00044 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00045 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00046 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00047 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00048 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00049 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00050 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00051 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00052 */
00053
00054 #if __cplusplus == 201103L
00055
00056 #include <cmath>
00057 #include <ctime>
00058
00059 #include <iostream>
00060
00061 #include "mtk.h"
00062
00063 void TestDefaultConstructor() {
00064
00065     mtk::Tools::BeginUnitTestNo(1);
00066
00067     mtk::UniStgGrid2D gg;
00068
00069     mtk::Tools::EndUnitTestNo(1);
00070     mtk::Tools::Assert(gg.delta_x() == mtk::kZero && gg.
00071     delta_y() == mtk::kZero);
00072 }
00073

```



```

00073 void
00074 TestConstructWithWestEastNumCellsXSouthNorthBndysNumCellsYOSTreamOperator() {
00075
00076     mtk::Tools::BeginUnitTestNo(2);
00077
00078     mtk::Real aa = 0.0;
00079     mtk::Real bb = 1.0;
00080     mtk::Real cc = 0.0;
00081     mtk::Real dd = 1.0;
00082
00083     int nn = 5;
00084     int mm = 7;
00085
00086     mtk::UniStgGrid2D gg(aa, bb, nn, cc, dd, mm);
00087
00088     std::cout << gg << std::endl;
00089
00090     mtk::Tools::EndUnitTestNo(2);
00091     mtk::Tools::Assert(gg.delta_x() == 0.2 &&
00092         abs(gg.delta_y() - 0.142857) <
00093         mtk::kDefaultTolerance);
00094 }
00095 void TestGetters() {
00096
00097     mtk::Tools::BeginUnitTestNo(3);
00098
00099     mtk::Real aa = 0.0;
00100     mtk::Real bb = 1.0;
00101     mtk::Real cc = 0.0;
00102     mtk::Real dd = 1.0;
00103
00104     int nn = 5;
00105     int mm = 7;
00106
00107     mtk::UniStgGrid2D gg(aa, bb, nn, cc, dd, mm);
00108
00109     bool assertion{true};
00110
00111     assertion = assertion && (gg.west_bndy() == aa);
00112     assertion = assertion && (gg.east_bndy() == bb);
00113     assertion = assertion && (gg.num_cells_x() == nn);
00114     assertion = assertion && (gg.south_bndy() == cc);
00115     assertion = assertion && (gg.north_bndy() == dd);
00116     assertion = assertion && (gg.num_cells_y() == mm);
00117
00118     mtk::Tools::EndUnitTestNo(3);
00119     mtk::Tools::Assert(assertion);
00120 }
00121
00122 mtk::Real ScalarField(const mtk::Real &xx, const mtk::Real &yy) {
00123
00124     mtk::Real aux{-(1.0/2.0)*xx*xx - (1.0/2.0)*yy*yy};
00125
00126     return xx*yy*exp(aux);
00127 }
00128
00129 void TestBindScalarFieldWriteToFile() {
00130
00131     mtk::Tools::BeginUnitTestNo(4);
00132
00133     mtk::Real aa = 0.0;
00134     mtk::Real bb = 1.0;
00135     mtk::Real cc = 0.0;
00136     mtk::Real dd = 1.0;
00137
00138     int nn = 5;
00139     int mm = 5;
00140
00141     mtk::UniStgGrid2D gg(aa, bb, nn, cc, dd, mm);
00142
00143     gg.BindScalarField(ScalarField);
00144
00145     if(!gg.WriteToFile("mtk_uni_stg_grid_2d_test_04.dat", "x", "y", "u(x,y)")) {
00146         std::cerr << "Error writing to file." << std::endl;
00147     }
00148
00149     mtk::Tools::EndUnitTestNo(4);
00150 }
00151
00152 mtk::Real VectorFieldPComponent(const mtk::Real &xx, const

```

```

    mtk::Real &yy) {
00153
00154     return xx + 0.01;
00155 }
00156
00157 mtk::Real VectorFieldQComponent(const mtk::Real &xx, const
    mtk::Real &yy) {
00158
00159     return yy + 0.01;
00160 }
00161
00162 void TestBindVectorField() {
00163
00164     mtk::Tools::BeginUnitTestNo(5);
00165
00166     mtk::Real aa = 0.0;
00167     mtk::Real bb = 1.0;
00168     mtk::Real cc = 0.0;
00169     mtk::Real dd = 1.0;
00170
00171     int nn = 5;
00172     int mm = 5;
00173
00174     mtk::UniStgGrid2D gg(aa, bb, nn, cc, dd, mm, mtk::VECTOR);
00175
00176     gg.BindVectorField(VectorFieldPComponent, VectorFieldQComponent);
00177
00178     std::cout << gg << std::endl;
00179
00180     if(!gg.WriteToFile("mtk_uni_stg_grid_2d_test_05.dat", "x", "y", "v(x,y)")) {
00181         std::cerr << "Error writing to file." << std::endl;
00182     }
00183
00184     mtk::Tools::EndUnitTestNo(5);
00185 }
00186
00187 int main () {
00188
00189     std::cout << "Testing mtk::UniStgGrid2D class." << std::endl;
00190
00191     TestDefaultConstructor();
00192     TestConstructWithWestEastNumCellsXSouthNorthBndysNumCellsYStreamOperator();
00193     TestGetters();
00194     TestBindScalarFieldWriteToFile();
00195     TestBindVectorField();
00196 }
00197
00198 #else
00199 #include <iostream>
00200 using std::cout;
00201 using std::endl;
00202 int main () {
00203     cout << "This code HAS to be compiled with support for C++11." << endl;
00204     cout << "Exiting..." << endl;
00205 }
00206 #endif


```

17.149 tests/mtk_uni_stg_grid_3d_test.cc File Reference

Test file for the [mtk::UniStgGrid3D](#) class.

```
#include <iostream>
```

Include dependency graph for mtk_uni_stg_grid_3d_test.cc:



Functions

- int [main](#) ()

17.149.1 Detailed Description

Author

: Eduardo J. Sanchez (ejspeiro) - [esanchez at mail dot sdsu dot edu](mailto:esanchez@mail.sdsu.edu)

Definition in file [mtk_uni_stg_grid_3d_test.cc](#).

17.149.2 Function Documentation

17.149.2.1 int main ()

Definition at line [184](#) of file [mtk_uni_stg_grid_3d_test.cc](#).

17.150 mtk_uni_stg_grid_3d_test.cc

```

00001
00008 /*
00009 Copyright (C) 2015, Computational Science Research Center, San Diego State
00010 University. All rights reserved.
00011
00012 Redistribution and use in source and binary forms, with or without modification,
00013 are permitted provided that the following conditions are met:
00014
00015 1. Modifications to source code should be reported to: esanchez@mail.sdsu.edu
00016 and a copy of the modified files should be reported once modifications are
00017 completed, unless these modifications are made through the project's GitHub
00018 page: http://www.csrc.sdsu.edu/mtk. Documentation related to said modifications
00019 should be developed and included in any deliverable.
00020
00021 2. Redistributions of source code must be done through direct
00022 downloads from the project's GitHub page: http://www.csrc.sdsu.edu/mtk
00023

```

```

00024 3. Redistributions in binary form must reproduce the above copyright notice,
00025 this list of conditions and the following disclaimer in the documentation and/or
00026 other materials provided with the distribution.
00027
00028 4. Usage of the binary form on proprietary applications shall require explicit
00029 prior written permission from the the copyright holders, and due credit should
00030 be given to the copyright holders.
00031
00032 5. Neither the name of the copyright holder nor the names of its contributors
00033 may be used to endorse or promote products derived from this software without
00034 specific prior written permission.
00035
00036 The copyright holders provide no reassurances that the source code provided does
00037 not infringe any patent, copyright, or any other intellectual property rights of
00038 third parties. The copyright holders disclaim any liability to any recipient for
00039 claims brought against recipient by any third party for infringement of that
00040 parties intellectual property rights.
00041
00042 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
00043 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
00044 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
00045 DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
00046 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
00047 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
00048 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
00049 ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
00050 (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
00051 SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
00052 */
00053
00054 #if __cplusplus == 201103L
00055
00056 #include <cmath>
00057 #include <ctime>
00058
00059 #include <iostream>
00060
00061 #include "mtk.h"
00062
00063 void TestDefaultConstructor() {
00064
00065     mtk::Tools::BeginUnitTestNo(1);
00066
00067     mtk::UniStgGrid3D gg;
00068
00069     mtk::Tools::EndUnitTestNo(1);
00070     mtk::Tools::Assert(gg.delta_x() == mtk::kZero &&
00071                       gg.delta_y() == mtk::kZero &&
00072                       gg.delta_z() == mtk::kZero);
00073 }
00074
00075 void
00076 TestConstructWithWestEastNumCellsXSouthNorthBndysNumCellsYostreamOperator() {
00077
00078     mtk::Tools::BeginUnitTestNo(2);
00079
00080     mtk::Real aa = 0.0;
00081     mtk::Real bb = 1.0;
00082     mtk::Real cc = 0.0;
00083     mtk::Real dd = 1.0;
00084     mtk::Real ee = 0.0;
00085     mtk::Real ff = 1.0;
00086
00087     int nn = 5;
00088     int mm = 7;
00089     int oo = 7;
00090
00091     mtk::UniStgGrid3D gg(aa, bb, nn, cc, dd, mm, ee, ff, oo);
00092
00093     std::cout << gg << std::endl;
00094
00095     mtk::Tools::EndUnitTestNo(2);
00096     mtk::Tools::Assert(gg.delta_x() == 0.2 &&
00097                       abs(gg.delta_y() - 0.142857) <
00098                       mtk::kDefaultTolerance);
00099 }
00100 void TestGetters() {
00101
00102     mtk::Tools::BeginUnitTestNo(3);
00103

```

```

00104     mtk::Real aa = 0.0;
00105     mtk::Real bb = 1.0;
00106     mtk::Real cc = 0.0;
00107     mtk::Real dd = 1.0;
00108     mtk::Real ee = 0.0;
00109     mtk::Real ff = 1.0;
00110
00111     int nn = 5;
00112     int mm = 7;
00113     int oo = 6;
00114
00115     mtk::UniStgGrid3D gg(aa, bb, nn, cc, dd, mm, ee, ff, oo);
00116
00117     bool assertion{true};
00118
00119     assertion = assertion && (gg.west_bndy() == aa);
00120     assertion = assertion && (gg.east_bndy() == bb);
00121     assertion = assertion && (gg.num_cells_x() == nn);
00122     assertion = assertion && (gg.south_bndy() == cc);
00123     assertion = assertion && (gg.north_bndy() == dd);
00124     assertion = assertion && (gg.num_cells_y() == mm);
00125     assertion = assertion && (gg.bottom_bndy() == ee);
00126     assertion = assertion && (gg.top_bndy() == ff);
00127     assertion = assertion && (gg.num_cells_z() == oo);
00128
00129     mtk::Tools::EndUnitTestNo(3);
00130     mtk::Tools::Assert(assertion);
00131 }
00132
00133 mtk::Real ScalarField(const mtk::Real &xx,
00134                      const mtk::Real &yy,
00135                      const mtk::Real &zz) {
00136
00137     return xx + yy + zz;
00138 }
00139
00140 void TestBindScalarFieldWriteToFile() {
00141
00142     mtk::Tools::BeginUnitTestNo(4);
00143
00144     mtk::Real aa = 0.0;
00145     mtk::Real bb = 1.0;
00146     mtk::Real cc = 0.0;
00147     mtk::Real dd = 1.0;
00148     mtk::Real ee = 0.0;
00149     mtk::Real ff = 1.0;
00150
00151     int nn = 50;
00152     int mm = 50;
00153     int oo = 50;
00154
00155     mtk::UniStgGrid3D gg(aa, bb, nn, cc, dd, mm, ee, ff, oo);
00156
00157     gg.BindScalarField(ScalarField);
00158
00159     if(!gg.WriteToFile("mtk_uni_stg_grid_3d_test_04.dat",
00160                      "x",
00161                      "y",
00162                      "z",
00163                      "u(x,y,z)")) {
00164         std::cerr << "Error writing to file." << std::endl;
00165     }
00166
00167     mtk::Tools::EndUnitTestNo(4);
00168 }
00169
00170 int main () {
00171
00172     std::cout << "Testing mtk::UniStgGrid3D class." << std::endl;
00173
00174     TestDefaultConstructor();
00175     TestConstructWithWestEastNumCellsXSouthNorthBndysNumCellsYostreamOperator();
00176     TestGetters();
00177     TestBindScalarFieldWriteToFile();
00178 }
00179
00180 #else
00181 #include <iostream>
00182 using std::cout;
00183 using std::endl;
00184 int main () {

```

```
00185     cout << "This code HAS to be compiled with support for C++11." << endl;
00186     cout << "Exiting..." << endl;
00187 }
00188 #endif
```

Index

BANDED
Enumerations., [35](#)

COL_MAJOR
Enumerations., [35](#)

CRS
Enumerations., [35](#)

DENSE
Enumerations., [35](#)

Data structures., [37](#)

Enumerations., [34](#)
BANDED, [35](#)
COL_MAJOR, [35](#)
CRS, [35](#)
DENSE, [35](#)
ROW_MAJOR, [35](#)
SCALAR, [34](#)
SCALAR_TO_VECTOR, [34](#)
VECTOR, [34](#)
VECTOR_TO_SCALAR, [34](#)

Execution tools., [36](#)

Grids., [39](#)

Mimetic operators., [40](#)

mtk, [43](#)
operator<<, [46](#), [47](#)

Numerical methods., [38](#)

operator<<
mtk, [46](#), [47](#)

ROW_MAJOR
Enumerations., [35](#)

Real
Roots., [32](#)

Roots., [31](#)
Real, [32](#)

SCALAR
Enumerations., [34](#)

SCALAR_TO_VECTOR
Enumerations., [34](#)

VECTOR
Enumerations., [34](#)
VECTOR_TO_SCALAR
Enumerations., [34](#)